Nat. Hazards Earth Syst. Sci. Discuss., 1, 1319–1353, 2013 www.nat-hazards-earth-syst-sci-discuss.net/1/1319/2013/ doi:10.5194/nhessd-1-1319-2013 © Author(s) 2013. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Natural Hazards and Earth System Sciences (NHESS). Please refer to the corresponding final paper in NHESS if available.

New developments in ambient noise analysis to characterise the seismic response of landslide prone slopes

V. Del Gaudio¹, J. Wasowski², and S. Muscillo³

 ¹Dipartimento di Scienze della Terra e Geoambientali, Università degli Studi di Bari "Aldo Moro", via E. Orabona, 4 – 70125 Bari, Italy
 ²Consiglio Nazionale delle Ricerche – Istituto di Ricerca per la Protezione Idrogeologica,

via Amendola, 122 I, 70126 Bari, Italy

³Dipartimento di Scienze della Terra e Geoambientali, Università degli Studi di Bari "Aldo Moro", via E. Orabona, 4 – 70125 Bari, Italy

Received: 15 January 2013 - Accepted: 26 March 2013 - Published: 17 April 2013

Correspondence to: S. Muscillo (sandro.muscillo@uniba.it)

Published by Copernicus Publications on behalf of the European Geosciences Union.

Discussion Pa	NHESSD 1, 1319–1353, 2013		
per Discussior	New deve in ambie analy V. Del Gau	New developments in ambient noise analysis V. Del Gaudio et al.	
n Pap	Title Page		
	Abstract	Introduction	
	Conclusions	References	
iscuss	Tables	Figures	
on P	14	►I	
aper	•	Þ	
	Back	Close	
Discu	Full Screen / Esc		
ssior	Printer-friendly Version		
Pap	Interactive Discussion		
)er			

Abstract

We report on new developments in the application of ambient noise analysis applied to investigate the dynamic response of landslide prone slopes to seismic shaking with special attention to the directional resonance phenomena recognised in previous stud-

- ies. Investigations relying on the calculation of horizontal-to-vertical noise spectral ratio (HVNR) were carried out in the area of Caramanico Terme (central Italy) where an ongoing accelerometer monitoring on slopes with different characteristics offers the possibility of validation of HVNR analysis. The noise measurements, carried out in different times to test the result repeatability, revealed that sites affected by response directivity
- ¹⁰ persistently show major peaks with a common orientation consistent with the resonance direction inferred from accelerometer data. At sites where directivity is absent, the HVNR peaks do not generally show a preferential orientation, with rare exceptions that could be linked to the presence of temporarily active sources of polarised noise. The observed spectral ratio amplitude variations can be related to temporal changes in
- site conditions, which can hinder the recognition of main resonance frequencies. Therefore, it is recommended to conduct simultaneous measurements at nearby sites within the same study area and to repeat measurements at different times in order to distinguish significant systematic polarisation caused by site specific response directivity from polarisation controlled by properties of noise sources. Furthermore, an analysis of persistence in noise recordings of signals with systematic directivity showed that only
- a portion of recordings contains wave trains having a clear polarisation representative of site directional resonance. Thus a careful selection of signals for HVNR analysis is needed for a correct characterisation of site directional properties.

1 Introduction

²⁵ Several studies have reported evidence that landslide triggering during earthquakes can be considerably influenced by ground motion amplification related to topography



(e.g. Harp et al., 1981, Harp and Jibson 2002; Sepúlveda et al., 2005; Meunier et al., 2008) and/or subsoil physical characteristics (e.g. Bourdeau and Havenith, 2008; Bozzano et al., 2008). However, the dynamic response of marginally stable slopes under seismic shaking is still difficult to understand and predict: indeed, it is charac-

- ⁵ terised by a complex interaction of different factors (topography, slope material properties, 3-D shape of geological features), concurring to produce effects of directional resonance. Such effects were revealed by instrumental recordings of seismic ground motion on landslide prone areas (Del Gaudio and Wasowski, 2007, 2011; Gallipoli and Mucciarelli, 2007; Garambois et al., 2010; Moore et al., 2011).
- ¹⁰ The presence of a strong anisotropy in site response can have important implications for the susceptibility of slopes to seismic failures, enhancing it where directions of potential sliding and of maximum amplification are similar. However, a clear comprehension of factors controlling the occurrence of site response directivity is still lacking, thus, the characterisation of dynamic response of slopes needs to be supported by
- ¹⁵ ground motion data acquisition. The direct assessment of site response properties requires the comparison between several seismic events recordings at study sites and at nearby reference sites not affected by resonance phenomena (Borcherdt, 1970), according to the so called SSR technique (Standard Spectral Ratio). However a diffuse and long term accelerometer monitoring of landslide prone slopes appears impracti-
- cal, thus the development of site response characterisation based on the analysis of short term recordings of ambient seismic noise with portable instruments represents a promising alternative approach. This approach is based on the Nakamura's method (Nogoshi and Igarashi, 1971; Nakamura, 1989), also known by the acronym HVNR (Horizontal to Vertical Noise Ratio), consisting in analysing the spectral ratios between
- ²⁵ horizontal and vertical components of ambient noise recording, searching significant peaks of H/V spectral ratios, which are interpreted as indicative of site resonance properties. The underlying postulate is that ambient noise consists mainly of surface waves (Rayleigh and Love) and/or body shear waves reflected and refracted inside shallow layers characterised by a strong impedance contrast. The presence of H/V



peaks at site resonance frequencies is explained assuming that horizontal and vertical components of noise wave field have a comparable amplitude at the substratum (within an approximation factor of 2) and that only horizontal components are significantly amplified by the effect of shallow layers. Some preliminary tests on landslide areas showed that an analysis of azimuthal variation of H/V spectral ratios can reveal the occurrence and orientation of directional resonance possibly related to sliding directions (Del Gaudio et al., 2008).

5

Despite its uncertain theoretical bases (cf. Bonnefoy-Claudet et al., 2006), the HVNR method proved to be an effective technique in investigating resonance frequencies under simple site conditions characterised by soft surface layers overlying a more rigid

- ¹⁰ under simple site conditions characterised by soft surface layers overlying a more rigid substratum (Lermo and Chávez-García, 1994). Indeed, regardless of the nature of the noise wave field, the *H/V* peaks are observed at the resonance frequency of the Swaves even when the noise is dominated by Rayleigh waves (Asten, 2004). However there are difficulties in inferring amplification factors from HVNR, because the amplitude of the *H/V* spectral ratios, even though correlated to amplification factor, may not be
- representative of its actual value and can change according to the nature of the noise wave field (Asten, 2004; Castellaro and Mulargia, 2009).

The assessment of amplification is even more difficult in geologically and geomorphologically complex site conditions like those of landslide areas, where directivity

- ²⁰ represents an important aspect of site response. The standard HVNR measurements make use of a geometric mean of the two horizontal spectra to calculate H/V ratios, then averaging the ratios obtained from a large number of recording time windows. This is justified, in case of 1-D layering conditions, by the assumption of a isotropic site response. In this way the effects of differently polarised surface wave trains and
- ²⁵ of body S-waves propagating with different incidence angles are averaged, correcting the bias that would result from the analysis of waves coming from a single source of polarised noise. The averaging over multiple time windows allows also estimating standard deviation of spectral ratios, which helps to distinguish whether the H/V values are representative of persistent spectral properties of site response, or are affected





by a strong variability related to properties of transient noise sources (Castellaro and Mulargia, 2009).

When site response cannot be considered isotropic, as in the case of landslide prone slopes, the geometric averaging between horizontal components is not justified and one can focus on analysing directional variations of site responses. In this case, however, the calculation of azimuthal variation of HVNR values can be biased by the presence of persistent source of polarised noise. This problem can be exacerbated when site response analysis is extended to relatively low frequencies (i.e. longer wavelengths), which are of interest in the context of seismic triggering of large landslides. In noise spectrum frequencies below 1 Hz are dominated by an ubiquitous "microseis-

- In noise spectrum frequencies below 1 Hz are dominated by an ubiquitous "microseismic" signal down to at least 0.05 Hz (Peterson, 1993), distinct from the anthropogenic "microtremors" observed at higher frequencies. The microseismic signal, was recognised as an effect of sea wave energy coupling with solid earth vibrations. It shows two main peaks: a relative maximum at a frequency between 0.04 and 0.1 Hz (defined pri-
- ¹⁵ mary or "single-frequency" microseism), generated by ocean wave pressure on sloping seafloor, and a major "double frequency" (DF) peak at frequencies twice the previous (Haubrich et al., 1963), consisting of Rayleigh waves excited by sea water pressure perturbations on inshore ocean bottom, for the collision between oppositely propagating waves (Tanimoto, 2007). An analysis of the location of microseism sources showed that the undergoing descent perturbations of the previous of the second perturbations of the previous of the second perturbation of microseism sources and the second perturbation of microseism sources are perturbations.
- ²⁰ that they undergo seasonal variations related to meteorology-depending changes of ocean swells (Schimmel et al., 2011).

Microseismic signal can propagate through very long distances, thus one can expect that ambient noise analysis at microseismic frequencies will show signals with seasonally varying Rayleigh-type polarisation, originated by sources located thousands

of kilometres away from the recording sites. Bromirski et al. (2005) pointed out a distinction between microseisms having double-frequency peaks around 0.15 Hz (LPDF, Long Period Double-Frequency), which can travel with low attenuation over very long distances, from those having peaks at frequencies between 0.2 and 0.3 Hz, which are much more attenuated and observed only in coastal areas relatively near the source. At



frequency larger than 0.3 Hz microseismic energy does not seem to propagate through ocean floor beyond a few hundreds of km and signals observed at these frequencies are generally excited by wind-generated local waves.

- Therefore, while analysing ambient noise of frequencies below 1 Hz to characterise local dynamic response of slopes to seismic shaking, problems can be encountered in distinguishing site-specific directivity properties of site response and polarisation due to the presence of persistent sources of polarised noise. Furthermore, the analysis cannot be reliably extended below 0.3 Hz, whereas frequencies between 0.3 and 1 Hz can be exploited taking into account the possibility of a bias related to microseismic signals coming from the pearest coastal areas. This problem can be faced acquiring simultane-
- ¹⁰ coming from the nearest coastal areas. This problem can be faced acquiring simultaneous recordings at different sites in the same study area, which helps to distinguish low frequency polarisation specific of certain sites from that having a "regional" diffusion related to an external origin. Furthermore, the repetition of measurements at different times (possibly in different seasons) can reveal if a polarisation shows a site-specific permanent character or a seasonal variability.

In this paper we present new results of applications of the HVNR technique on slopes affected by or prone to failures, focusing on the uncertainties in data interpretation related to space-time variation of noise wave field properties. After describing the study area characteristics and the data processing solutions adopted, we present and discuss the results from sites for which comparative seismic response data were provided by accelerometer recordings of recent earthquakes, as well as results from several other slope sites.

2 Measurements

20

Ambient noise measurements were carried out using two kinds of instruments, a tromograph (i.e. an instrument specifically devised to record small amplitude ground vibrations) and a portable broad band seismograph. We employed tromographs Tromino[®] (model ENGY PLUS, http://www.tromino.eu) which are three-component, compact,



"all-in-one" instruments including both sensors and acquisition system, working at frequencies down to 0.3 Hz.

When investigating low frequency ambient noise, we also tested the use of a portable broad band seismometer Trillium Compact combined with an acquisition unit Taurus (both produced by Nanometrics) providing an homogeneous instrumental response in the interval 0.02–50 Hz).

5

10

Given the need to analyse noise up to periods of about 3 s, data were acquired with sessions lasting at least a few tens of minutes, thus satisfying the SESAME project guideline recommendations of obtaining data sufficient to extract not less than 200 cycles of the longest period to be analysed (Bard and The SESAME Team, 2004). However, following the results of first tests, the duration of data acquisition sessions was considerably extended, taking into account that: (i) in comparison to the standard appli-

cations, directional analysis necessitates a larger number of time windows to increase the probability of recording signal noise coming from different directions; (ii) a certain number of time windows has to be discarded from the analysis if the recordings are

- ¹⁵ number of time windows has to be discarded from the analysis if the recordings are characterised by transient signal coming from temporary and very close sources of ground vibration, whose polarisation is more likely to reflect source directivity properties rather than site-specific effects. Furthermore, building upon the previous experiences, the most recent measurements were conducted via simultaneous recordings at
- different nearby sites with two instruments, often keeping on recording at a "reference" station for several hours and moving a "rover" recorder to different sites in the same study area.

Our first HVNR measurements on landslide prone slopes were carried out in the area of Caramanico Terme, in Abruzzi region (Central Italy). The study area is located

in a valley whose flanks are characterised by Pliocene clay-rich formations mantled by thick Quaternary colluvial deposits (Fig. 1). The town of Caramanico Terme is overlooked by the Colle Alto hill, which constitutes a caprock made of Quaternary carbonate megabreccias. The caprock is bounded by very steep scarps which are frequently affected by rockfalls.



Topographic and geological conditions make the Caramanico area susceptible to seismic triggering of different types of landslides, as repeatedly occurred during historic and recent earthquakes (Wasowski and Del Gaudio, 2000). A local accelerometer network was installed there in 2002 to study slope dynamic response to seismic shak-

- ⁵ ing under different lithological and topographic conditions (Del Gaudio and Wasowski, 2007, 2011). Data acquired by this network offer the possibility of validating site response information that can be derived from ambient noise analysis. Thus, first tests of HVNR measurements were carried out at sites of accelerometer stations (Fig. 1). One of these stations, CAR2, is positioned on the head of a landslide that in 1989 had
- ¹⁰ mobilised about 40 m thick colluvial deposits overlying mudstones. Two other stations are located on the same slope, but outside the limits of the 1989 landslide: one (CAR1) is located on an outcrop of the Pliocene mudstone constituting the substratum of the 1989 landslide, whereas another station (CAR5) is located on the same kind of material affected by the 1989 failure, but about 200 m away, upslope of the landslide crown, on a stable, gently inclined area (< 7°).

Two stations are sited on rock: one (CAR3) is located at the rim of a 50 m deep ESE– WNW oriented gorge, on 10 m of carbonate breccias overlying Miocene limestones, whereas the other (CAR4) is located on an outcrop of the same limestones as at CAR3, but on a relatively flat surface (inclination < 7°) located at about 2.5 km distance from

²⁰ Caramanico Terme. CAR4 is used as reference to compare site response of the other stations.

Additional ambient noise recordings were carried out on three other landslide-prone slopes in Caramanico (Fig. 1). One of these sites (T7) is on the lschio landslide, a 250 m long, complex mass movement located on the lower slopes of the river valley. During

its last major re-activations in 1973 and 1996–1997, retrogressive, multiple rotational movements in the uppermost part of the slide affected a few tens of meter thick carbonate breccia caprock overlying the Pliocene-age mudstone substratum (Wasowski, 1997). The actual depth of the basal slip surface in the mudstones is unknown. The



presence of shallow translational movements was observed in the middle-lower part of the slide, where the thickness of carbonate debris is within 5 m.

Measurements were also conducted at three different points (T6, T6N, T6S) of the slope affected by a deep landslide, which involved few tens of meters thick carbonate debris overlying Pliocene mudstones. The failure was triggered in 1627 by a magnitude 6.7–7 earthquake which occurred about 120 km from Caramanico. The long distance from the earthquake source suggested that site amplification was a factor in landslide triggering (Wasowski et al., 2013).

Finally, ambient noise measurements were also carried out at two sites on top of the megabreccia caprock, one (T4) on the rim of a steep scarp, and the other (T4E) few tens of meters away from the scarp edge.

3 Data processing

Data acquired during recording sessions were subdivided into time windows of 30 s (i.e. 10 times the longest period of interest), applying a linear detrending to each window

- to remove long term drift. Spectra were calculated for each component and smoothed using a triangular average on frequency intervals of ±10% of the central frequency. Horizontal to vertical spectral ratios were then calculated for horizontal components along directions at 10° azimuth intervals. Following the recommendation of Castellaro and Mulargia (2009), spectrograms reporting spectral ratios as function of time for E–
- ²⁰ W and N–S components were examined to discard time windows having anomalously high spectral ratio values resulting from strong transient signals. Finally, the average spectral ratios H/V of all the accepted time window intervals were calculated for each direction.

The difficulty in establishing whether observed peaks are significant persistent features attributable to site response, or reflect transient effects due to noise source characteristics, is commonly encountered when interpreting the HVNR values. Bard and The SESAME Team (2004) proposed that a minimum threshold of 2 for peak amplitude



and a small standard deviation around the mean HVNR values obtained from all the analysed time windows can be used to assess the significance of H/V peak. However, these criteria, defined for 1-D layering conditions, appear too restrictive for a directional analysis under complex site conditions that are typical of landslide areas. Indeed, when

- ⁵ analysing azimuthal variation of H/V ratios, one should keep in mind that a source of variability could result also from the recording of differently polarised wave trains arriving at different times from different noise sources around the measurement site. In such a case the effect of source controlled polarisation would add to site specific directivity, increasing standard deviation around the mean HVNR values along each direction.
- ¹⁰ Therefore, carefully defined criteria are needed to infer site specific directivity from HVNR data, through an identification of a systematic preferential orientation of H/Vrelative maxima. Del Gaudio et al. (2008) considered the distribution of HVNR values as function of azimuth and frequency and proposed an approach based on the detection of multiple major peaks having coherent orientation (within 30°) and satisfying the ¹⁵ following significance criteria:
 - (a) amplitude of H/V relative maximum larger than 2;

20

25

 (b) ratio between *H/V* maximum and minimum found at the same frequency (typically along an approximately orthogonal direction) larger than 1.5 (which implies a shaking energy along maximum direction larger by more than a factor of 2 in comparison to minimum).

In order to facilitate identification of directivity, we propose here an additional step consisting in the evaluation of the temporal recurrence of signals having coherent polarisation. The procedure consists in finding, preliminarily, all the relative maxima appearing in the distribution of HVNR values and satisfying the criteria (a) and (b) mentioned above. This is done both for mean HVNR values and for HVNR relative to each time window taken separately. Comparing each peak of mean HVNR values with the peak that in each time window shows a minimum difference in frequency and azimuth from



the mean H/V peak, standard deviations can be estimated for peak frequency, azimuth and amplitude.

Then we examine the occurrence rate of significant directional H/V peaks among the time windows of a recording session. Since the frequency of peaks is typically affected by an uncertainty (expressed through standard deviation) of about 0.25 Hz, peaks that along each orientation (spaced by 10°) have frequencies falling within a 0.5 Hz interval are grouped together in separate bins. Then, for each frequency-azimuth bin the percentage of time windows showing significant H/V peaks belonging to that bin is calculated. The results can be represented through a 3-D histogram, where the column height represents the occurrence rate and a colour scale is used to represent the mean H/V values of the peaks belonging to each bin.

We define the resulting percentage as "Directional H/V Peak Occurrence Rate" (DHVPOR). A concentration of high percentage values around a given frequency and azimuth implies that a large amount of the recording time windows shows persistently directional peaks with those frequency/azimuth characteristics.

15

The outcomes of a single recording session may not always be considered conclusive to demonstrate a site response directivity, because a concentration of H/V peaks along an azimuth could also result from the presence of sources of polarised noise. Nevertheless, the persistence of similar maxima of DHVPOR values in data acquired

at different times (possibly obtained from recordings carried out in different seasons), if combined with the observation that such preferential direction is not present at nearby sites during contemporary recording, provides a robust evidence of directional resonance properties specific of the investigated site.



4 Results

4.1 Measurements at accelerometer sites on landslide-prone slopes

Early recordings of small-moderate magnitude earthquakes by the Caramanico accelerometer network had demonstrated that sites CAR2 and CAR3 (Fig. 1) are char-

- ⁵ acterised by a pronounced site response directivity with maximum of ground motion along azimuths of 80°-110° and 120°-130°, respectively (Del Gaudio and Wasowski, 2007). The presence of directional phenomena has been further confirmed following the recordings of a large number of events belonging to the seismic sequence that in 2009 hit L'Aquila (about 60 km NW of Caramanico), with a mainshock of moment ¹⁰ magnitude $M_w = 6.3$ (Del Gaudio and Wasowski, 2011). Figure 2 shows the SSR val-
- ues obtained for CAR2 and CAR3, by comparing their recordings with those of the reference station CAR4.

For CAR2 (Fig. 2a), the SSR values were derived from 23 seismic events mostly distant between 40 and 60 km: the highest peak (amplification factor AF = 10 ± 3) was observed along an azimuth of $100^{\circ} \pm 33^{\circ}$ at a frequency of 2.3 ± 0.1 Hz. This appears to be a major resonance frequency, possibly related to the effects of the 40 m thick colluvium. Seismic investigations conducted on this site using the ReMi technique provided for shear wave velocity $V_{\rm s}$ an average estimate of about 400 m s⁻¹ (Coccia et al., 2010). Following the simplified relation connecting surface layer $V_{\rm s}$ velocity and thickness *H* to resonance frequency $F_{\rm o}$ (i.e. $F_{\rm o} = V_{\rm s}/4H$), this velocity value provides an estimate of $F_{\rm o} = 2.5$ Hz.

Other similarly oriented significant peaks were observed at frequencies of 3.3 and 6.5–7 Hz (AF \approx 8), 1.5 and 4.7 Hz (AF \approx 7.5), 8.5–9 Hz (AF \approx 6.5), 9–10 Hz (AF \approx 6) and 12.5 Hz (AF \approx 4.5). All the amplification factors observed at different frequencies along directions of maxima exceed those at the same frequency along orthogonal directions

²⁵ directions of maxima exceed those at the same frequency along orthogonal directions by a factor ranging from 1.5 to 3. Additional secondary peaks were found along an azimuth of 130° (e.g. at 5.0–5.5 Hz), but with a less pronounced directional character.



Comparatively, the structure of the SSR diagram appears simpler for CAR3 (Fig. 2b) located on fractured rock, which seems to cause strong amplification at relatively higher frequencies. In this case the average of 15 events revealed a band of strong directional maxima extending between 10 and 16 Hz, oriented along an azimuth of $120^{\circ}-130^{\circ}$, with two major peaks at frequencies of 12.6 and 13.6 Hz, both characterised by an AF = 14 ± 4 . The amplification along an approximately orthogonal direction was about 50 % lower.

These new SSR results appear consistent with those obtained from the first ambient noise recording campaign carried out in July 2007 using a prototype of Tromino (Del Gaudio et al., 2008). The azimuthal variation of HVNR values in Fig. 3 shows major directional peaks corresponding to the main SSR peaks found at CAR2 and CAR3 (Fig. 3). At CAR2 the maximum H/V was found at a frequency of 2.4±0.1 Hz along an azimuth of 80° ± 22°, whereas at CAR3 the peak frequency was 12.7±0.3 Hz along an azimuth of 130° ± 20°.

- Interestingly, at CAR3 site the peak value of H/V ratios (12.6 ± 3.8) is in excellent agreement with the mean AF value derived from seismic events analysis, whereas at CAR2 the H/V maximum of 4.2±1.6 is much smaller than the corresponding mean AF. A possible explanation of this difference lies in the SSR values relative to the vertical components (Fig. 2): recordings of earthquakes showed that at frequencies of horizon-
- tal ground motion maximum amplification, CAR2 site is also affected by a concomitant amplification of the vertical component by a factor of about 4 and this can results in a reduction of noise H/V spectral ratios. At CAR3 vertical amplification factor is absent or negligible (less than 2).

A further support to the above interpretation comes from the analysis of a secondary maximum at a frequency of 13.2 ± 0.7 Hz (with H/V of 3.0 ± 0.6) in the CAR2 HVNR diagram (Fig. 3a). Considering the uncertainties involved in this frequency identification, this maximum could be related to the SSR 12.5 Hz peak, which has a comparable AF (4.6 ± 2.1): at 12.5 Hz frequency the vertical component shows a weaker mean



amplification (by a factor less than 2) and this can explain the presence of a prominent peak in H/V spectral ratios.

With the exception of sites very close to earthquake source, vertical ground motion is dominated by P waves, whose velocity (V_p) in shallow porous layers are influenced ⁵ by water content. Furthermore the V_p/V_s ratio influence the ellipticity of Rayleigh waves (cf. Asten, 2004). This suggests a possible explanation of the variable results obtained repeating noise measurements in June 2010 at CAR2 and CAR3, using a broad band sensor Trillium, and in May 2011 at CAR2, using simultaneously Trillium and Tromino. Whereas the results at CAR3 were substantially confirmed with regard to frequency (13.1 ± 0.4 Hz) and orientation (130° ± 18°) of the major peak, though with a limited decrease of the H/V peak value (9.1 ± 1.6), the HVNR values at CAR2 showed a considerable weakening of the peak around 2.5 Hz (with H/V dropped to 2.2–2.5).

Considering that vertical ground motion amplification reveals the presence of significant contrast of V_p velocity between the mudstone bedrock and the overlying more soft

- ¹⁵ and porous colluvium, one can speculate that H/V amplitude changes at CAR2 can reflect seasonal variation of Rayleigh wave ellipticity influenced by V_p variations related to colluvium water content. This raises the problem of the stability of noise recordings results in terms of resonance properties identification in cases when analysis relies on azimuth/frequency distribution of mean H/V ratio values alone. Therefore, the use
- of DHVPOR approach is advocated here to support the analysis of directional resonance: the persistent recurrence of H/V relative maxima for a given azimuth/frequency combination, during recordings carried out at different times can lead to identify main resonance frequencies even in presence of a strong variability of H/V ratios.

Figure 4 shows the histograms of the DHVPOR values obtained for the four noise measurements carried out at CAR2 located on the 1989 landslide. The noise recordings reveal the presence of significant directional peaks concentrated within a azimuth interval between 80° and 110°; such peaks are almost absent along other directions at least for frequencies higher than 3 Hz. Below this frequency directional H/V peaks appear oriented also along different azimuths, even though, at least above 1 Hz, the





relative maxima of their occurrence rate are constantly within the $80^{\circ}-110^{\circ}$ azimuth range. The more dispersed orientation of H/V peaks at lower frequencies can reflect the fact that, due to the weaker attenuation of such frequencies, contributions to local noise wavefield arrive from more distant sources characterised by different polarisations.

5

10

Comparatively, no systematic preferential direction was observed in H/V peaks recorded at sites CAR1 and CAR5 (Fig. 5), located on the same slope but outside the 1989 landslide. This is consistent with the results of earthquake recording analyses, which demonstrated that these sites are not affected by response directivity (Del Gaudio and Wasowski, 2011).

A general consideration based on the examination of the DHVPOR histograms (Figs. 4 and 5) is that the maximum occurrence rates of directional peaks are not particularly high (less than 50 % of time windows showed significant directional peaks in all the examined cases). This implies that, for most part of a noise recording session,

- signals do not show a pronounced polarisation. Nonetheless, when polarised signals appear at sites characterised by response directivity, they tend to have common orientation consistent with that of the site directional resonance. This suggests that the majority of the recorded signal consists of weak background noise that does not reflect the site resonance properties. Therefore, to investigate the possibility of deriving more
- ²⁰ details on resonance frequencies from noise analysis, it is of interest to examine the results obtained restricting the average of H/V ratios only to those corresponding to relative maxima.

In general, the H/V peak values belonging to each azimuth/frequency bin showed a moderate dispersion around their average (standard deviation typically about 1/3 of

²⁵ the average), except for frequencies below 1 Hz, often characterised by standard deviation close to or even larger than the average. Thus at microseismic frequencies the signal seems affected by a strong variability related to noise source properties, which hampers the recognition of site specific features of spectral ratios. Figure 6 shows, as function of frequency, the average values of H/V relative maxima found for frequency



intervals of 0.5 Hz along directions of maximum concentration of peak occurrence. For CAR3 this diagram reveals consistent results for the two measurements of 2007 and 2010, with a major peak corresponding to frequency and orientation of the directional resonance revealed by the earthquake recordings. For CAR2, the general pattern of ⁵ mean *H/V* peak ratios observed at different times along an azimuth (90° N) characterised by high recurrence of significant *H/V* peaks appears consistent, with a first major peak around 2 Hz frequency and a series of other peaks between 4 and 13 Hz, with the largest one around 12.5 Hz. This pattern is comparable to that of the SSR values calculated along the same azimuth, even though up to about 10 Hz the *H/V* spectral ratios are largely below the SSR. Thus, through this kind of analysis it is possible to obtain (at least) a rough indication of main resonance frequencies, even in case

of complex site spectral response.

4.2 Measurements at other landslide-prone sites

Measurements carried out at site T7 (Fig. 1) on the Ischio landslide did not show evidence of a significant site response. HVNR values (Fig. 7a) have only one peak satisfying the significance requirements described in Sect. 3., i.e. a weak maximum of 2.3 ± 0.7 at a frequency of 1.4 ± 0.1 Hz due 40° N $\pm23^{\circ}$. The DHVPOR histogram (Fig. 7b) shows that directional H/V maxima in recording time windows are mostly found at low frequencies with a wide variability of directions and relatively low values of spectral ratios.

²⁰ The absence of clear site effects could be related to the limited thickness (< 5 m) of the "slow" carbonate debris material and the lack of impedance contrast.

Measurements in the 1627 landslide area were carried out with Tromino at three sites, distant about one hundred meters from each other: one (T6) is located in the central part of the accumulation zone of the landslide and the others (T6S and T6N)

are close to its boundary. A first recording session was conducted in May 2011 at the site T6. In January and May 2012 measurements were repeated at T6 and additional sites were investigated. In January 2012 two instruments were used simultaneously,



one kept fixed at T6S and the other exploited as "rover" for measurements at T6 and T6N.

DHVPOR histograms show that T6 seems affected by a response directivity approximately N–S oriented, with azimuth range of 170° – 180° (Fig. 8). This directivity cannot

- ⁵ be attributed to noise source properties (e.g. dominant winds shaking trees), because the measurements carried out simultaneously at T6S revealed a weak directivity oriented E–W. Measurement carried out at different times show that the average of H/Vpeak values along the azimuth of 170° appear consistent and indicate two maxima at frequencies of about 5 and 7.5 Hz (Fig. 8c).
- Conversely, no significant site effect was detected at T6S (Fig. 9): indeed, despite the presence of a common preferential orientation of rare polarised signals, the *H/V* ratios fall very close to the threshold of 2 (Fig. 9d). The low *H/V* ratios could perhaps be related to the location of this site at the margin of the main landslide body, where thickness of the disturbed material is greatly reduced. Some weak evidence of directivity was found at site T6N (Fig. 10) with azimuth 120°–130°. The analysis of the mean *H/V* peak values along this direction (Fig. 10c) provided consistent results in two different
- data acquisitions, showing a maximum of spectral response at frequencies between 8 and 13 Hz, even though with modest (around 3) H/V ratios.

At present it is unclear what factors can determine the directivity at T6 and, to a mi-²⁰ nor extent, at T6N. The exact location of the 1627 landslide detachment zone and the main sliding direction are somewhat uncertain (Wasowski et al., 2013). Nevertheless, considering the WSW facing slope geometry it seems likely that slide movement direction is close to be orthogonal to the response directivity at T6 as indicated by noise analysis. Thus, this case is different from the landslide at CAR2, where directivity is present along the maximum slope direction.

Finally, noise measurements were conducted also in an area representing a major source of rockfalls at Caramanico, i.e. at the caprock of the Colle Alto hill. Measurements were carried out in December 2011 and May 2012 on two sites, one (T4) on



the rim of the caprock with west facing steep scarp, and the other (T4E) a few tens of meters to the east of T4 (Fig. 1).

Measurements of December 2011 suggested a possible E–W directivity at T4 and, less pronounced, also at T4E (Fig. 11a, b), but in the data acquired in May 2012 evidence of such directivity appeared much weaker at T4 and practically absent at T4E (Fig. 11c, d). However, mean values of *H/V* peaks oriented along E–W direction seem to indicate that a significant resonance may be present at T4 (Fig. 12a), possibly without a pronounced directional character, with maxima of spectral response around 8 and 12 Hz. Moving away from the caprock rim (and the steep scarp), at T4E this resonance appears weaker (Fig. 12b), which suggests a possible relation with local topography.

5 Discussion and conclusions

The new results of ambient noise analysis concerning slopes affected by or prone to landslides indicate that they can be characterised by a complex seismic response showing pronounced directional variations. This complexity makes necessary a more sophisticated analysis in order to draw reliable information on site resonance properties. Furthermore, to improve our comprehension of relations between seismic noise signal properties and response under seismic shaking, more ambient noise data ought to be collected, especially at sites where results from seismic ground motion monitoring are available. This is related to a general need to acquire more data from accelerometer stations sited on hillslopes (including potentially unstable slopes). Indeed, the available

- stations sited on hillslopes (including potentially unstable slopes). Indeed, the available recordings of actual strong motions affecting slopes are very few and generally limited to the aftershock phases (Wasowski et al., 2011). The tests conducted at the sites of the Caramanico accelerometer network suggest that standard techniques of ambient noise analysis can produce unreliable results under conditions characterised by
- ²⁵ possible variations of Rayleigh wave ellipticity related to changing site conditions (e.g. seasonal hydrogeological variations). These variations can modify the horizontal-to-vertical spectral ratios of noise, thereby "hiding" important resonance frequencies.



Given the variability shown by signal properties, adequate criteria need to be defined to select the portions of the recorded signals that best reflect the site resonance properties. In particular, in a scarcely noisy environment (e.g. far from urbanised zones), a "global" *H/V* average could be biased by spectral ratios belonging to very weak signals having a low signal/noise ratio: such ratio in this context is to be intended as the ratio between coherent and incoherent part of the noise, where the coherence mainly derives from Rayleigh waves which can provide relevant information on site response characteristics.

Importantly, when polarised noise signals are recorded at sites characterised by seis-¹⁰mic response directivity, they show a coherent direction of polarisation that is also consistent with maximum resonance direction. Thus, while investigating directional resonance, it is better to analyze an average restricted to the part of noise signal which shows a clear polarisation with a coherent preferential orientation rather than focusing on a global average of total recorded *H/V* ratios. A simple way to do it consists in ¹⁵averaging *H/V* relative maxima observed in different time windows along directions of persistent recurrence of significant peaks.

The extension of noise analysis below 1 Hz appears still difficult for the strong variability of signal polarisation observed at such frequencies. It is unclear whether this is due to a lack of directivity for the investigated sites at these frequencies or to the superimposition of too many signals arriving from more distant sources of differently polarised noise, as an effect of the weaker attenuation of low frequencies. Perhaps in this appear it will be preserved a dept or more unfined method of collection of users.

20

this case it will be necessary to adopt a more refined method of selection of useful signal portion, analysing comparatively recordings acquired simultaneously at more sites to filter strongly polarised signals coming from distant sources.

Another open question concerns the identification of factors controlling site response directivity. Our experience shows that, even though this phenomenon is recurrent in landslide areas, no systematic relation was observed in terms of site characteristics or between resonance and slope directions. Among the landslide cases examined here, one (CAR2) shows a directivity parallel to the sliding direction, whereas for the other



(T6) no apparent relation exists with the directions of prominent topographic features. Similar tests were also recently conducted in Taiwan on slopes affected by large landslides triggered by the 1999 M = 7.6 Chi-Chi earthquake (Del Gaudio et al., 2013). In one case (Jufengershan landslide) HVNR values showed evidence of directivity parallel

to the slide direction, which also coincides with dip direction of a monoclinal bedding. In the second case (Tsaoling landslide) the sliding direction does not coincide with HVNR maximum direction, even though HVNR values were very high (about 15) along the maximum slope direction as well.

On the whole, the analysis of ambient noise seems very useful, because it can lead to the detection of directional resonance phenomena and to the recognition of their orientations. Although a simple examination of azimuthal variation of mean H/V spectral ratios in a single station may not be sufficient to identify directional resonance properties of a site, a comparison between simultaneous recordings at nearby sites under different geological conditions can resolve the question whether directivity revealed by

HVNR measurements is site specific or is due to noise source. Furthermore, for a correct identification of main resonance frequencies, more advanced signal analysis is needed including a proper selection of portions of noise recordings that are most representative of site response properties. In this context it is useful to compare recordings obtained at different times and under different seasonal conditions to recognise persistent site specific properties of ground vibration.

Finally, considering efforts aimed at an approximate quantification of spectral am-

plification factors, it seems that their success can in some cases depend on specific site conditions. In particular, where ground motion vertical component is not amplified, the H/V peak values appear to approximate well mean amplification factors. The

presence of a strong variability of Rayleigh wave ellipticity among measurements carried out at different times could result from changing site conditions. In such a case numerical modelling of slopes could perhaps help to provide constrains on amplification estimates, but this implies the acquisition of detailed (and typically costly) data on geometrical-physical characteristic of slope materials.



Acknowledgements. The authors thank Alessandro Pasuto (CNR – IRPI, Padova) for lending us one tromograph Tromino for the noise recordings of May 2011.

References

5

20

Asten, M. W.: Comment on "Microtremor observations of deep sediment resonance in metropolitan Memphis, Tennesse", by Bodin et al., Eng. Geol., 72, 343–349, 2004.

- Bard, P. Y. (coordinator) and The SESAME Team: Guidelines for the implementation of the *H/V* spectral ratio technique on ambient vibrations: measurements, processing and interpretation. SESAME European research project, WP12 Deliverable D23.12, available at: ftp://ftp.geo.uib.no/pub/seismo/SOFTWARE/SESAME/USER-GUIDELINES/ SESAME-HV-User-Guidelines.pdf, 2004.
 - Bonnefoy-Claudet, S., Cotton, F., and Bard, P.-Y.: The nature of seismic noise wavefield and its implications for site effects studies a literature review, Earth Sci. Rev., 79, 205–227, 2006.
 Borcherdt, R. D.: Effects of local geology on ground motion near San Francisco Bay, B. Seismol. Soc. Am., 60, 29–61, 1970.
- ¹⁵ Bourdeau, C. and Havenith, H.-B.: Site effects modeling applied to the slope affected by the Suusamyr earthquake (Kyrgyzstan, 1992), Eng. Geol., 97, 126–145, 2008.
 - Bozzano, F., Lenti, L., Martino, M., Paciello, A., and Scarascia Mugnozza, G.: Selfexcitation process due to local seismic amplification responsible for the reactivation of the Salcito landslide (Italy) on 31 October 2002, J. Geophys. Res., 113, B10312, doi:10.1029/2007JB005309, 2008.
 - Bromirski, P. D., Duennebier, F. K., and Stephen, R. A.: Mid-ocean microseisms, Geochem. Geophys. Geosy., 6, Q04009, doi:10.1029/2004GC000768, 2005.
 - Castellaro, S. and Mulargia, F.: VS₃₀ estimates using constrained *H/V* measurements, B. Seismol. Soc. Am., 99, 761–773, 2009.
- ²⁵ Coccia, S., Del Gaudio, V., Venisti, N., and Wasowski, J.: Application of Refraction Microtremor (ReMi) technique for determination of 1-D shear wave velocity in a landslide area, J. Appl. Geophys., 71, 71–89, doi:10.1016/j.jappgeo.2010.05.001, 2010.
 - Del Gaudio, V. and Wasowski, J.: Directivity of slope dynamic response to seismic shaking, Geophys. Res. Lett., 34, L12301, doi:10.1029/2007GL029842, 2007.



1340

- quake induced landslides, Earth Planet Sc Lett., 275, 221–232, 2008.
 Moore, J. R., Gischig, V., Burjanek, J., Loew, S., and Fäh, D.: Site Effects in unstable rock slopes: dynamic behavior of the randa instability (Switzerland), B. Seismol. Soc. Am., 101, 3110–3116, 2011.
 - Nakamura, Y.: A method for dynamic characteristics estimation of subsurface using microtremors on the ground surface, Quarterly Report Railway Tech. Res. Inst., 30, 25–30, 1989.

- Del Gaudio, V. and Wasowski, J.: Advances and problems in understanding the seismic response of potentially unstable slopes, Eng. Geol., 122, 73–83, 2011.
 Del Gaudio, V., Coccia, S., Wasowski, J., Gallipoli, M. R., and Mucciarelli, M.: Detection of directivity in seismic site response from microtremor spectral analysis, Nat. Hazards Earth Syst. Sci., 8, 751–762, doi:10.5194/nhess-8-751-2008, 2008.
 Del Gaudio, V., Lee, C. T., and Wasowski, J.: Inferring seismic response of landslide-prone slopes from microtremor study, in: Proceedings of the Second World Landslide Forum, Rome, 3–7 October 2011, 7 pp., in press, 2013.
- Gallipoli, M. R. and Mucciarelli, M.: Effetti direzionali in registrazioni sismometriche in
- aree in frana e bordi di bacino, XXVI GNGTS Conference, Rome, 13–15 November 2007, available at: http://www2.ogs.trieste.it/gngts/gngts/convegniprecedenti/2007/riassunti/ tema-2/2-sess-2/22-gall.pdf, 2007.

5

25

Garambois, S., Quintero, A., Massey, C., and Voisin, C.: Azimuthal and thickness variabilities of seismic site effect response of the Utiku landslide (North Island, New-Zealand), EGU General

- Assembly 2010, 2–7 May 2010, Vienna, Geophysical Research Abstracts, 12, EGU2010-2430, 2010.
 - Harp, E. L. and Jibson, R. W.: Anomalous concentrations of seismically triggered rock falls in Paicoma Canyon: are they caused by highly susceptible slopes or local amplification of seismic shaking?, B. Seismol. Soc. Am., 92, 3180–3189, 2002.
- ²⁰ Harp, E. L., Wilson, R. C., and Wieczorek, G. F.: Landslides from the 4 February 1976, Guatemala earthquake, USGS Professional Paper 1204-A, 40 pp., 1981.

Haubrich, R. A., Munk, W. H., and Snodgrass, F. E.: Comparative spectra of microseism and swell, B. Seismol. Soc. Am., 53, 27–37, 1963.

Lermo, J. and Chávez-García, F. J.: Are microtremors useful in site response evaluation?, B. Seismol. Soc. Am., 84, 1350–1364, 1994.

Meunier, P., Hovius, N., and Haines, J. A.: Topographic site effects and the location of earthguake induced landslides, Earth Planet Sc Lett., 275, 221–232, 2008.

13



- Nogoshi, M. and Igarashi, T.: On the amplitude characteristics of microtremor (part 2), J. Seism. Soc. Japan, 24, 26–40, 1971 (in Japanese with English abstract).
- Peterson, J.: Observation and modeling of background seismic noise, US Geol. Surv. Open-File Rept., Albuquerque, 93–322, 1993.
- ⁵ Schimmel, M., Stutzmann, E., Ardhuin, F., and Gallart, J.: Polarized Earth's ambient microseismic noise, Geochem. Geophys. Geosy., 12, Q07014, doi:10.1029/2011GC003661, 2011.
 - Sepúlveda, S. A., Murphy, W., Jibson, R. W., and Petley D. N.: Seismically induced rock slope failures resulting from topographic amplification of strong ground motions: the case of Pacoima Canyon California, Eng. Geol., 80, 336–348, 2005.
- ¹⁰ Tanimoto, T.: Excitation of microseisms, Geophys. Res. Let., 34, L05308, doi:10.1029/2006GL029046, 2007.

Wasowski, J.: Reactivation of a deep slope movement due to the interruption of spring water withdrawal: case history of the Case Mancini landslide, Italy, in: Proceedings of the 2nd Panamerican Symposium on Landslides, Novembre 1997, Rio de Janeiro, Brasile, 1, 145–154, 1997.

15 **1**

20

- Wasowski, J. and Del Gaudio, V.: Evaluating seismically-induced mass movement hazard in Caramanico Terme (Italy), Eng. Geol., 58, 291–311, 2000.
- Wasowski, J., Lee, C., and Keefer, D.: Toward the next generation of research on earthquake induced landslides: current issues and future challenges, Eng. Geol., 122, 1–8, doi:10.1016/j.enggeo.2011.06.001, 2011.
- Wasowski, J., Del Gaudio, V., Casarano, D., Lollino, P., and Muscillo, S.: Local scale seismic landslide susceptibility assessment based on historic earthquake records combined with accelerometer monitoring and ambient noise data, in: "Earthquake-Induced Landslides", Proceedings of the International Symposium on Earthquake-Induced Landslides, Kiryu (Japan),
- ²⁵ 7–9 November 2012, edited by: Ugai, K., Yagi, H., and Wakai, A., 11–20 pp., ISBN:978-3-642-32237-2, Springer, Berlin Heidelberg, doi:10.1007/978-3-642-32238-9_2, 2013.

NHE	SSD	
1, 1319–1	353, 2013	
New developments in ambient noise analysis		
V. Del Gaudio et al.		
Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
I	►I	
•	×.	
Back	Close	
Full Screen / Esc		
Printer-friendly Version		
Interactive Discussion		
(C)	•	

Jiscussion Pape

Discussion Paper

Discussion Paper

Discussion Paper



Fig. 1. Geographic location of the Caramanico test area (inset) and DEM showing lithology and measurement sites (modified after Del Gaudio and Wasowski, 2011). White continuous and dashed lines mark, respectively, lithological contacts and boundaries of investigated landslides; two possible source areas for the 1627 landslide are indicated. CAR1-5 mark the location of the accelerometer stations (reference station CAR4, located 2.5 km SE of Caramanico, is not shown); T4, T4E, T6, T6N, T6S and T7 indicate the additional sites of HVNR measurements discussed in the paper.





Fig. 2. Azimuthal variation of SSR values obtained for the sites of the accelerometer stations CAR2 (a) and CAR3 (b), averaging spectral ratios calculated for 23 and 15 seismic events, respectively, in comparison to the reference site CAR4. Vertical bars show the SSR values relative to vertical component.





Fig. 3. Azimuthal variation of HVNR values at the sites CAR2 (a) and CAR3 (b) from noise measurements carried out on July 2007 using a tromograph Tromino.





Discussion Paper NHESSD 1, 1319-1353, 2013 **New developments** in ambient noise analysis **Discussion** Paper V. Del Gaudio et al. **Title Page** Abstract Introduction Conclusions References Discussion Paper Tables Figures Back Close Full Screen / Esc **Discussion** Paper **Printer-friendly Version** Interactive Discussion

Fig. 4. Histograms of DHVPOR (Directional H/V Peak Occurrence Rate) values obtained for noise measurements carried out at site CAR2 in 2007 with Tromino (a), in 2010 with Trillium (b) and in 2011 using simultaneously Tromino (c) and Trillium (d). The colours represent, according to the reported scale, the average of H/V peak values in recording time windows along different azimuths and within 0.5 Hz frequency intervals.



Tromino in 2007 (a, b) and in 2010 (c, d) at sites CAR1 and CAR5, respectively.

Interactive Discussion



Fig. 6. Diagram of spectral ratios along a direction characterised by a high recurrence of significant directional maximum at site CAR2 (a) and CAR3 (b). Thin solid line represents the SSR values obtained along the azimuths specified in legend; other lines represent mean values of noise H/V peaks having the same directions and frequencies binned by 0.5 Hz intervals, resulting from different HVNR measurements (see legend); thick solid line represents the average of noise H/V peak values derived from the HVNR measurements.





Fig. 7. Results of noise measurements at sites T7 (Ischio landslide): (a) mean HVNR diagram; (b) DHVPOR histogram.





Fig. 8. Results of noise measurement at site T6 (1627 landslide): DHVPOR histograms relative to measurements of May 2011 (a) and January 2012 (b) and mean values of H/V peaks oriented due 170° N; thick solid line represents the average of noise H/V peak values derived from different measurements.





Fig. 9. Results of noise measurement at site T6S (1627 landslide): DHVPOR histograms relative to measurements of January (**a**, **b**) and May 2012 (**c**) and mean values of H/V peaks oriented due 90° N; thick solid line represents the average of noise H/V peak values derived from different measurements. Note that the first of the two January measurements was simultaneous with that at site T6 (Fig. 8b), whereas the second one was simultaneous with that at sites T6N (Fig. 10a).







Fig. 10. Results of noise measurement at site T6N (1627 landslide): DHVPOR histograms relative to measurements of January (a) and May (b) 2012 and mean values of H/V peaks oriented due 130° N; thick solid line represents the average of noise H/V peak values derived from different measurements.



Fig. 11. Histograms of DHVPOR values relative to noise measurements carried out at sites T4 and T4E (Colle Alto Hill) on December 2011 and May 2012.

Interactive Discussion



Fig. 12. Mean values of H/V peaks oriented due 90° N resulting from noise measurements at sites T4 (a) and T4E (b), on the rim of the megabreccia scarp; thick solid line represents the average of noise H/V peak values derived from different measurements.

