Nat. Hazards Earth Syst. Sci. Discuss., 1, 3991–4036, 2013 www.nat-hazards-earth-syst-sci-discuss.net/1/3991/2013/ doi:10.5194/nhessd-1-3991-2013 © Author(s) 2013. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Natural Hazards and Earth System Sciences (NHESS). Please refer to the corresponding final paper in NHESS if available.

# Evaluation of vegetation fire smoke plume dynamics and aerosol load using UV scanning lidar and fire-atmosphere modelling during the Mediterranean Letia 2010 experiment

V. Leroy-Cancellieri<sup>1</sup>, P. Augustin<sup>2,4</sup>, J. B. Filippi<sup>1</sup>, C. Mari<sup>3</sup>, M. Fourmentin<sup>2,4</sup>, F. Bosseur<sup>1</sup>, F. Morandini<sup>1</sup>, and H. Delbarre<sup>2,4</sup>

<sup>1</sup>Laboratoire Sciences Pour l'Environnement, CNRS-Université de Corse, Corte, France
 <sup>2</sup>ULCO, LPCA, 59140 Dunkerque, France
 <sup>3</sup>Laboratoire d'Aérologie, CNRS-Université Paul Sabatier, Toulouse, France
 <sup>4</sup>Université Lille Nord de France, 59000 Lille, France

Received: 25 June 2013 – Accepted: 3 July 2013 – Published: 8 August 2013

Correspondence to: V. Leroy-Cancellieri (vcancellieri@univ-corse.fr)

Published by Copernicus Publications on behalf of the European Geosciences Union.



#### Abstract

Vegetation fires emit large amount of gases and aerosols which are detrimental to human health. Smoke exposure near and downwind of fires depends on the fire propagation, the atmospheric circulations and the burnt vegetation. A better knowledge of

- the interaction between wildfire and atmosphere is a primary requirement to investigate fire smoke and particle transport. The purpose of this paper is to highlight the usefulness of an UV scanning lidar to characterize the fire smoke plume and consequently validate fire-atmosphere model simulations.
- An instrumented burn was conducted in a Mediterranean area typical of ones frequently concern by wildfire with low dense shrubs. Using Lidar measurements positioned near the experimental site, fire smoke plume was thoroughly characterized by its optical properties, edge and dynamics. These parameters were obtained by combining methods based on lidar inversion technique, wavelet edge detection and a backscatter barycenter technique. The smoke plume displacement was determined using a digital video camera coupled with the Lidar.
- The simulation was performed using a meso-scale atmospheric model in a large eddy simulation configuration (Meso-NH) coupled to a fire propagation physical model (ForeFire) taking into account the effect of wind, slope and fuel properties. A passive numerical scalar tracer was injected in the model at fire location to mimic the smoke plume. The simulated fire smoke plume width remained within the edge smoke plume and the edge smoke plume.
- obtained from lidar measurements. The maximum smoke injection derived from lidar backscatter coefficients and the simulated passive tracer was around 200 m. The vertical position of the simulated plume barycenter was systematically below the barycenter derived from the lidar backscatter coefficients due to the oversimplified properties of the
- passive tracer compared to real aerosols particles. Simulated speed and horizontal location of the plume compared well with the observations derived from the videography and lidar method suggesting that fire convection and advection were correctly taken into account.



## 1 Introduction

5

Southern Europe and the Mediterranean basin are regularly affected by forest fires which can burn thousands of hectares in a few days. A recent publication from the European Forest Fire Information System accounts for 65 000 fires which occur in Europe every year, burning half a million hectares of vegetation and forest; 85% of the burnt area being in the European Mediterranean region (San-Miguel-Ayanz et al., 2012).

These vegetation fires emit large amount of gases and aerosols (Langmann et al., 2009), which are detrimental to human health (Wegesser et al., 2009; Franzi et al., 2011) and degrade visibility. Smoke exposure of fire fighters during fire operations is of particular concern (Reinhardt and Ottmar, 2004; Leonard et al., 2007). Fire experimental fields in France (Barboni et al., 2010) and Portugal (Miranda et al., 2005) revealed concentrations of toxic air pollutants well above exposure limit values settle by the European regulatory rules. Using airborne observations, Phuleria et al. (2005)

and Singh et al. (2012) documented the contribution of fire emissions to the urban pollution during the Californian fires in 2003 and 2008, respectively. Elevated PM<sub>2.5</sub> concentrations were observed by air quality ground stations tens of kilometers downwind of an arson fire in southern France (Strada et al., 2012). During the Gestosa 2002 experimental field fires in Portugal, Miranda et al. (2005) reported extreme hourly

- averaged particulate matter concentration respectively of 2350 μgm<sup>-3</sup> for PM<sub>2.5</sub> and
   1430 μgm<sup>-3</sup> for PM<sub>10</sub>. During the last decade, considerable efforts were made to characterize the organic and inorganic compounds in the gaz and particulate phases from prescribed fires (Lee et al., 2005; Yan et al., 2008; Alves et al., 2011; Burling et al., 2011) or uncontrolled fires (Alves et al., 2010; Vincente et al., 2012) in contrasted fuel
- and meteorological conditions. Despite of these recent studies, the characterization of the chemical compounds in smoke remains incomplete, in particular for Mediterranean fires, mainly due to the extreme difficulties in obtaining smoke samples from real and even experimental fires.



To comply with regulatory rules, modeling tools are needed to accurately predict the contribution of fire emissions to visibility attenuation and gas and particle concentrations. Unfortunately, the ability of existing models to simulate smoke production and dispersion is currently limited by inaccurate fire emissions, uncertainties in fire behav-

- <sup>5</sup> ior and plume-rise estimates (Miranda, 2004; Hodzic et al., 2007; Strada et al., 2012). In particular, it is well known that weather has a dominant role on the fire propagation, especially wind force and direction. Conversely, the fire influences the dynamics and the chemistry of the atmosphere through the injection of heat fluxes and chemical compounds. Two models were developed recently which integrate the two-way interactions
- between the fire and the surrounding atmosphere: the WRF/SFIRE model (Mandel et al., 2011) based on the former work of Clark et al. (1996) and the Meso-NH/ForeFire model (Filippi et al., 2009, 2011). An accurate validation of the smoke plume rise forecast by these fire-atmosphere mesoscale models for a wide range of meteorological, fire behavior, fuel, and topography is critical. Prescribed fires, such as the one con ducted in Letia (France) in 2010 and further described in Sect. 2, can help to validate
- these models even through the fuel conditions and meteorology significantly differ from wildfires.

In particular, this paper describes a rigorous evaluation of a fire plume rise and dispersion achieved through the comparison of the model forecast with lidar (light detection and ranging) observations of fire aerosols. Lidars measure the backscattered

20

- radiation intensity from detected aerosols in the atmosphere. Lidar observations indirectly provide a measure of smoke density distribution. The usefulness of groundbased scanning lidars to assess plume rise dynamics and height was illustrated recently by Kovalev et al. (2009) and Wold et al. (2010). Utkin et al. (2003), Lavrov
- et al., (2006) and Fernandes et al. (2006) demonstrated the feasibility of forest-fire smoke detection using lidar even if the source is out of sight or under unfavourable visibility conditions. Matis et al. (2003) used lidar observed backscatter and extinction coefficients, particles optical depths, extinction-to-backscatter ratios and depolarization ratio to identify unequivocally aged smoke lidar observations from Siberian fires



Discussion

Paper

**Discussion** Paper

**Discussion** Paper

Discussion

Pa



above Germany in spring 2003. Following a similar approach, Amiridis et al. (2012) identified highly absorbing fresh smoke particles lofted between 2 and 4 km with lidar measurements during the wildfires in Greece in 2003. Pahlow et al. (2005) and Kovalev et al. (2009) used lidar measurements of smoke particles as tracers for the study of the atmospheric boundary layer structure and fire injection height during a fire event. Lidar observation is therefore of prime interest not only for fire surveillance but also to derive the injection height of fire emitted compounds.

The present paper focuses on the validation of simulated smoke injection heights and dynamics derived from a high-resolution fire-atmosphere model using lidar vertical

- scans during a prescribed fire held in Corsica. The second section describes the experimental strategy and instrumentation deployed during the experimental fire. Section 3 is devoted to the lidar and camera instrumentation set up. This section also describes the technique to derive particles backscatter coefficient from lidar raw signals and the barycenter method applied for the comparison between lidar observations and the fire-
- atmosphere model. In Sect. 4, the core physical equations of the fire spread model and the coupling technique between the atmospheric and fire models are defined. In the last section, results from the Meso-NH-ForeFire coupled model are compared with the lidar observations and discussed in terms of plume injection height and dynamics.

#### 2 The Letia 2010 experiment

5

25

#### 20 2.1 Site description and instrumental deployment

The experimental burn took place on 5 November 2010 in Corsica (8° 51' 36" E, 42° 13' 25" N, in the South of France. The site is located at an altitude of 1400 m. It was chosen by our public partners: the French Forest Service and the Regional Natural reserve of Corsica since this burning joins in the problem of country planning in rural areas. The climate is typically Mediterranean with hot dry summers.



The experimental site (see Fig. 1) was  $720 \text{ m}^2$ . It was a rectangle with 24 m wide perpendicular to the slope and 30 m long parallel to the slope. The experiment is located in an area with a steep slope between  $12.5^\circ$  and  $13^\circ$ . In order to preserve the integrity of the personnel but also to prevent any fire breakout, a fuel break delimits the left side

and the top corresponding to the crest of the mountain. A line ignition was performed along the bottom of the slope on the entire length of the plot using a petrol-torch. The fire started at 10:22 and ended at 10:37 UTC.

In order to characterize the initial conditions and the behavior of the fire, different measuring apparatus were deployed on the site. The devices are depicted hereafter and displayed in Fig. 2 which presents the overall experimental setup.

## 2.2 Vegetation cover

10

Because not all biomass burns the same ways, a description of fuel properties is required for predicting whether a fire will be ignited, its rate of spread and its intensity. The qualitative and quantitative determinations of fuels are thus essential to serve as input data for a fire spread model. The collection of fuel properties is generally discriminated

<sup>15</sup> data for a fire spread model. The collection of fuel properties is generally discriminated by size class and dead/live condition.

For the present experiment, fuel consisted of endemic broom (*Genista Salzmannii*). This specie is characterized by a very strong homogeneity and a 90 % cover. The height varies from 30 to 60 cm with a mean value of 45 cm. In this case of homogenous fuel

- <sup>20</sup> bed, experimental measurements of the residence time of fires (which is defined as the length of time a flaming front passes a particular point) have showed that only small fuel particles ( $\varphi < 6 \text{ mm}$  and surface-to-volume > 600 m<sup>-1</sup>) can contribute actively to the dynamics of a wildfire (Burrows, 2001). At landscape scale, it was also assumed that thin dead fuels are mainly responsible of fire spread considering that live fuels
- <sup>25</sup> and coarse dead fuels are partly desiccated within the flame and not only ahead of the fire front (Santoni et al., 2011). According to these observations fuel characteristics



were done for thin dead particles, these informations will serve as data entrance for the combustion model and are listed in Table 1.

Fuel moisture is an important parameter because it affects the proportion of flaming to smoldering and their relative combustion efficiency. Fuel moisture content on dry

- <sup>5</sup> basis (the ratio of the difference between the wet and oven-dried weights to the oven-dried weight) was measured for the sample collected the day of the burn by oven-dried 24 h at 333 K. In order to take into account the structural properties of the fuel, the surface to volume ratio and density were measured following the method proposed by Moro (2006). The day of the burn, total fuel loading (mass of fuel per unit area) was
   10 estimated through destructive sampling of a 2m × 2m plot. The heat of combustion
- estimated through destructive sampling of a  $2m \times 2m$  plot. The heat of combustion and specific heat content were measured in an oxygen bomb calorimeter following the standard (ASTM, 1996). The rate of heat release for the burnt fuel was  $33.5 \text{ MJm}^{-2}$  of dead fuels.

Table 1 gathers the characteristics of the Genista Salzamannii specie in the burning5 conditions, parameters of live particles was also provided for information.

## 2.3 Meteorological conditions

The wind velocity and direction were recorded using a two-dimensional ultrasonic anemometer at 2.5 m above the ground surface to reflect the average wind acting on the fire front. The anemometer was located on the downwind edge of the vegetation plot to minimise the influence of the fire on the wind measurements. Furthermore, such a location protected the ultrasonic transducers from smoke and large-diameter firebrands generated by the fire which can affect sonic measurements. The wind data were recorded using another (synchronised) data logger at a sampling rate of 1 Hz (Fig. 3). The average velocity of the wind measured during the experiment was 2.6 m s<sup>-1</sup> and its direction was close to SSE.

The ambient temperature, relative humidity and pressure were measured at the start of experiment.



#### 3 Lidar and camera methods

# 3.1 Scanning lidar experimental set up

During this experiment, a UV scanning lidar has been used to monitor the fire smoke plume dispersion. Indeed, eye-safe UV lidars are suitable for tropospheric aerosol stud-

- <sup>5</sup> ies (Royer et al., 2011) and particularly to detect smoke forest fire (Lavrov et al., 2003). The total atmospheric backscatter is much stronger in UV (Rayleigh scattering) than in the near-infrared which implies high signal-to-noise ratio in this spectral range. This lidar operates with a third harmonic of a Nd-YAG laser (355 nm) with an energy pulse of about 16 mJ at a repetition rate of 20 Hz. This instrument was located at about 170 m
- East from the experimental burning site (Fig. 2). High temporal/spatial resolutions continuous monitoring is performed by successive vertical scans along different azimuth angles from the burning site (265°) to west north west (315°). Each vertical scan duration was about 2 min corresponding to an average of 50–100 shots per profile (Table 3).
- The theoretical lidar blind distance *r*<sub>0</sub> for optimal near-field overlap is about 250 m and the spatial resolution is 15 m along each beam. In order to reduce the blind distance from the lidar, a Geometrical Form Factor (GFF) has been deduced by using horizontal profile measurements in the direction of a south (from the burning site) homogeneous clear atmosphere area before the start of the burning (Sasano et al., 1979). The GFF, deduced experimentally, has been applied in each profile obtained during the burning period, to reduce the blind distance from 250 m to 105 m.

# 3.2 Lidar inversion methodology

Under several assumptions, lidar signal can be inverted to determine aerosol optical properties. In the present work, the raw lidar electrical signal is converted to backscatter coefficients following a precise technique described below.



The raw lidar return voltage V(r) at a range *r* from the lidar is:

$$V(r \ge r_0) = \frac{K}{r^2} \beta(r) T_{\rm M}^2(r_0, r) T_{\rm A}^2(r_0, r) + V_0$$
<sup>(1)</sup>

where  $T_{\rm M}$  and  $T_{\rm A}$  are the molecular and the aerosol transmittance respectively, *K* is the lidar system constant (over  $r_0$ ),  $V_0$  is the offset voltage and  $\beta$  is the total backscatter coefficient sum of the molecular and the aerosol backscatter coefficient  $\beta_{\rm M}$ ,  $\beta_{\rm A}$ , respectively.

The extraction of the fire smoke optical properties (optical depth, extinction and backscatter coefficient) from lidar measurements, requires the knowledge of the aerosol extinction to backscatter ratio called lidar ratio ( $L_R$ ). This parameter depends of the shape, the size distribution and the refractive index of the aerosol. In the case of multiple scattering effects on lidar signal returns, the accurate of the Effective Lidar ratio (EL) which is the product of the single scattering lider ratio (L)

ratio (EL<sub>R</sub>) which is the product of the single scattering lidar ratio  $L_{\rm R}$  and a multiple scattering factor  $\eta$  (Platt, 1981), is important to deduce correctly the backscatter coefficient of the aerosol smoke plume.

<sup>15</sup> In this study, we applied a technique developed by Young (1995) to retrieve, directly from lidar measurements, the optical properties of the fire smoke plume located in a homogeneous atmosphere. This algorithm was proven to be robust to inverse the lidar equation in previous studies with applications on cloud characteristics (Das et al., 2009; Di Donfrancesco et al., 2006; Winker et al., 2009), desert dust layer (Mona et al.,

20 2012), volcano ash plume (Marenco et al., 2011) or smoke plume (Omar et al., 2009; Vadrevu et al., 2012).

The Effective Optical Depth (EOD)  $\tau^*$  and the aerosol transmittance  $T_A$  of the smoke plume can be deduced by linear regression between the measured lidar signal and the modeled signal (Bucholtz, 1995; Bodhaine et al., 1999) over a range (from lidar) below ( $r_b$ ) and above ( $r_i$ ) the fire plume smoke.

 $T_{\mathsf{A}}(r_{\mathsf{b}}, r_{\mathsf{t}}) = \exp\left[-\tau^*(r_{\mathsf{b}}, r_{\mathsf{t}})\right]$ 

5

25

ISCUSSION Pape

Iscussion Pape

Iscussion Pape

Discussion Pape

(2)

with

$$\tau^*(r_{\rm b},r_{\rm t})={\rm EL}_{\rm R}\int_{r_{\rm b}}^{r_{\rm t}}\beta_{\rm A}(r'){\rm d}r'.$$

Then the EL<sub>R</sub> can be determined by integrating the range corrected lidar signal  $Pr^2$ from  $r_b$  to  $r_t$ . Finally, the inversion of the lidar equation in order to deduce the backscatter coefficient can be done by using the following modified Fernald equations including the effects of multiple scattering (Fernald, 1984; Young, 1995):

$$\beta(r) = \frac{P(r)r^2 \exp\left[-2(\mathsf{EL}_{\mathsf{R}} - 8\pi/3)\int_{r_{\mathsf{c}}}^{r}\beta_{\mathsf{M}}(z)\mathsf{d}z\right]}{C(r_{\mathsf{c}}) + 2\mathsf{EL}_{\mathsf{R}}\int_{r_{\mathsf{c}}}^{r}P(r)r^2 \exp\left[-2(\mathsf{EL}_{\mathsf{R}} - 8\pi/3)\int_{r_{\mathsf{c}}}^{z}\beta_{\mathsf{M}}(s)\mathsf{d}s\right]\mathsf{d}z}$$

where

 $P(r) = V(r) - V_0(r)$ 

<sup>10</sup> and  $C(r_c)$  is a calibration term deduced at a sufficient clear air range  $r_c$ .

#### 3.3 Edge plume detection from lidar

Many different lidar techniques have been developed to detect atmospheric transition zone relying on the backscattered lidar signal (Boers and Eloranta, 1986), its first or second derivative (Flamant et al., 1997; Menut et al., 1999), its variance (Hooper and Eloranta, 1986) or fitting lidar signal technics (Steyn et al., 1999; Kovalev et al., 2009). Methods based on the Haar wavelet transform provide robust, objective, semi-automated, efficient and flexible methods and they are less affected by signal noise than others (Davis et al., 2000; Cohn and Angevine, 2000, Gan et al., 2011; Pal et al., 2010; Mao et al., 2013). In order to determine the smoke plume edge (*r*<sub>b</sub> and *r*<sub>t</sub>), which



(3)

(4)

(5)

is characterized by heterogeneous backscattering lidar signals, we have used the Haar wavelet covariance transform method (Gamage et al., 1993; Brooks et al., 2003; Baars et al., 2008). This method is well suited to identify the locations of coherent transition zone between clear atmosphere and the smoke plume edge (Fig. 4).

5 The Haar wavelet is defined as:

$$H\frac{(r-b)}{a} = \begin{cases} -1 \quad \Rightarrow b - \frac{a}{2} \le r \le b\\ 1 \quad \Rightarrow b < r \le b + \frac{a}{2}\\ 0 \quad \Rightarrow \text{ otherwise} \end{cases}$$

where *a* and *b* are the dilation and translation coefficients of the Haar wavelet, respectively. The covariance transform  $W_f$  is defined as the convolution between the logarithm range-corrected lidar signal S(r) and the Haar wavelet *H*:

<sup>10</sup> 
$$W_f(a,b) = \frac{1}{a} \int_{r_0}^r \left\{ S(r')H\left(\frac{r'-b}{a}\right) \right\} \mathrm{d}r'$$

where

15

$$S(r) = \ln\left\{P(r)r^2\right\}$$

Locations of the local maxima and minima of the covariance transform are identified as a transition zone of various atmospheric structures. For a well-selected dilatation coefficient, the  $W_f$  maximum and minimum values correspond to the smoke plume edge crossed by the laser beam.

During the experimental period, the maximum of the wavelet variance, defined as  $D^2$  by Gamage et al. (1993), can be used to deduce the well dilatation coefficient to determine dominant atmospheric structure in the lidar signal (Davis et al., 2000) which

(6)

(7)

(8)

corresponds, in our case, to the scale of the plume structure.

$$D^{2}(a) = \int_{r_{0}}^{r} [W_{f}(a,b)]^{2} db.$$

This method has been applied on each profile of all vertical scans obtained during the LETIA experiment to obtain the bottom and top of the fire smoke plume.

#### **5 3.4 Fire smoke plume location from barycenter method**

Ideally, information about the location of the smoke plume or its inclination angle from the emission site can be estimated with the aerosol concentration. This approach was not possible in the present work for two reasons. The current version of the fireatmosphere model only simulates the emission and transport of a passive tracer with no hypothesis on initial mass or size to mimic aerosols. Second, in order to derive aerosol mass concentrations from the lidar signal, additional variables have to be observed simultaneously. Raut and Chazette (2009) retrieved, from lidar and in situ optical aerosol measurements, an empirical linear method, which relates the aerosol mass concentration and the extinction coefficient. To achieve this kind of conversion, in situ

- additional information (scattering coefficients, aerosol size distribution or mass concentration) are thus needed. Another approach was proposed by Lavrov et al. (2006) who used the measured profiles of extinction and backscatter coefficients in a fire plume to derive the aerosol mass concentration, assuming that the aerosol mass was proportional to these optical properties. Unfortunately, a high quality estimation of aerosol concentration are backscatter profiles are backgatter profiles.
- <sup>20</sup> concentration from extinction or backscatter profiles can not be obtained only with a single wavelength lidar. Previous studies have shown relationships between aerosol mass concentrations and optical thickness but in distinct environments and sources (Shinozuka et al., 2007; Chu et al., 2003; Wang and Christopher, 2003; van Donkelaar et al., 2006) which can not be applied directly to fire emissions.



(9)

Thus, we have used a method based on the calculation of a barycenter *G* of a fire smoke plume of *n* points weighted by backscatter coefficient  $\beta_i$  (deduced directly from lidar measurements) with coordinates  $r_i$ , to study the dynamics of the smoke plume. The average of the weighted position coordinates of the backscatter distribution in space corresponds to the coordinates of the barycenter. In our case, the smoke plume backscatter barycenter location can be calculated by the following equation:

$$\overrightarrow{OG} = \frac{\sum_{i=1}^{n} \overrightarrow{r}_{i} \beta_{i}}{\sum_{i=1}^{n} \beta_{i}}.$$

5

Moreover, the smoke plume inclination angle can be deduced, from this method, as the angle between the horizontal plan of the experimental site and the source to the barycenter coordinates straight line. Therefore, the smoke plume backscatter barycenter of each scan lidar can be compared with the smoke plume passive tracer concentration barycenter from model outputs.

The major limitation of this comparison method is that unlike the backscatter barycenter derived from lidar observations, the concentration barycenter deduced from the simulation does not take account the aging of gases and aerosols from the emission source through nucleation or condensation processes.

#### 3.5 Smoke plume displacement from videography method

A digital video camera, located next to the lidar and oriented toward the fire field site (25 images per second), has been used to estimate the smoke plume displacement by combining with the lidar measurement (Weibring et al., 1998). Firstly, each sample selected from the video camera original image, corresponding to the plume structure, has been handled in order to extract the sky background by using a reference image without smoke plume. Secondly, a high Fourier frequency filter process has been applied to enhance the edges plume structure in the spatial domain and to remove residual back-

<sup>25</sup> ground noise. Thirdly, highest cross-correlation values of the images taken at time *t* and



(10)

t + dt, corresponding to the combination of horizontal and vertical pixel displacements has been selected during the burning period. At last, the horizontal pixel displacements are converted into true displacement and are corrected from the scaling effects of the distance between the plume and the camera (Weibring et al., 1998).

## 5 4 Fire-atmosphere coupled model

## 4.1 Model description

10

This section describes the numerical coupling between an atmospheric mesoscale model (Meso-NH) and a fire propagation model (ForeFire) used to reproduce the complex fire-atmosphere interactions (Filippi et al., 2009, 2011). Most fire models takes into account the effects of the atmosphere (wind, humidity) on fire behavior. We have used the theoretical 3-D physical model of Balbi et al. (2009) for the propagation velocity in the ForeFire simulation code. Feedback from the fire to the atmosphere is taken into account by injecting water vapor and heat fluxes in the Meso-NH model.

## 4.1.1 Meso-NH atmospheric model

- <sup>15</sup> Meso-NH is an anelastic non hydrostatic mesoscale model (Lafore et al., 1998), intended to be applicable to all scales ranging from regional to micro scales and can be coupled with an on-line atmospheric chemistry module. Primary meteorological variables (pressure, velocity and temperature) are advected with a centered 4th order scheme, while scalars and other meteorological variables (such as water vapor frac-
- tion) are advected with a so-called monotonic Piecewise Parabolic Method (Colella and Woodward, 1984). Temporal derivatives are computed following the so-called leapfrog algorithm. In this study Meso-NH is run in Large Eddy Simulation configuration as the typical size of structures that we need to solve is less than a hundred meter (Filippi et al., 2009).



## 4.1.2 Fire propagation model and simulator

The propagation model for the fire front is based on the assumption that the front propagates in the normal direction to the front. To obtain an analytical formulation for the rate of spread the fire is considered as the sum of a "conductive" part (vegetation un-<sup>5</sup> der pyrolysis) and a flame heating the vegetation in front of it (Balbi, 2009). The model accounts for slope, atmospheric properties (wind velocity  $\mathbf{v}$ , air density  $\rho_a$  and temperature  $T_a$ ), spatial characterization of the fuels (mass loading  $\sigma$ , height *e*, emissivity  $\varepsilon_v$  and moisture content *m* (fraction of water over total weight) and the fuel combustion properties (ignition temperature  $T_i$ , calorific capacity  $c_{p,v}$ , combustion enthalpy  $\Delta h$ , stoichiometry *s* and mass exchange rate due to pyrolysis  $\dot{\sigma}$ ). It is assumed that only a given portion  $\chi_0$  of the total combustion energy is released as radiation, and that the flame can be modeled as a tilted radiant panel with 2 parameters: flame tilt angle towards the unburnt fuel  $\gamma$  and front depth  $\lambda$ . The equation governing the propagation velocity of the front reads (Balbi, 2009):

<sup>15</sup> 
$$R = R_0(\varepsilon_v, T_i, e, \sigma, m, T_a) + \chi_0 \Delta h \dot{\sigma} f(\lambda, \gamma)$$

where  $R_0$  is the contribution of the vegetation undergoing pyrolysis (*B* is the Boltzmann constant and  $\Delta h_w$  the water evaporation enthalpy):

$$R_0 = \varepsilon_v B T_i^4 e / 2\sigma \left[ c_{p,v} (T_i - T_a) + m \Delta h_w \right].$$
<sup>(12)</sup>

The second term accounts for the propagation by radiation and reads:

$$_{20} \quad f(\lambda,\gamma) = \frac{\lambda}{2 + \mu\lambda\cos\gamma} (1 + \sin\gamma - \cos\gamma)\mathcal{H}_{\mathbb{R}^+}(\gamma) \tag{1}$$

where  $\mathcal{H}_{\mathbb{R}^+}$  is the Heaviside function for positive reals and  $\mu$  is a coefficient stemming from the model of evolution of the ratio of radiated energy versus combustion energy released with the volume-to-surface ratio (Balbi, 2009). The flame tilt angle depends on



(11)

3)

the slope angle  $\alpha$  and wind  $\mathbf{v}$  as follows:  $\tan \gamma = \tan \alpha + \rho_a (\mathbf{v} \cdot \mathbf{n})/2(1 + s)\dot{\sigma}$ , with  $\mathbf{n}$  the normal to the front. The front tracking is carried through a discretization in a Lagrangian manner. The front is discretized as an ordered list of markers, i.e. each marker has the knowledge of its neighbors, defined by convention in clockwise direction. The outward normal  $\mathbf{n}_i$  of marker *i* defines the direction of propagation, and  $r_i$  the local rate of spread. One has to choose the maximum distance  $p_r$  allowed between two consecutive markers called the perimeter resolution. If two markers are farther than this distance, a re-mapping of the front is carried in order to keep the resolution constant. A filtering distance  $d_f = p_r/2$  is also needed to avoid over-crossing of two markers and potential inversion of the normal.

The advection scheme is an Euler first order integration in space:

$$\mathbf{x}_{i}^{(n+1)} = \mathbf{x}_{i}^{(n)} + \delta I \cdot \mathbf{x}_{i}^{(n)}$$
(14a)  
$$t_{i}^{(n+1)} = t_{i}^{(n)} + \frac{\delta I}{r_{i}^{(n)}}$$
(14b)

<sup>15</sup> where the superscripts  $\varphi^{(n)}$  and  $\varphi^{(n+1)}$  denote the value of the variable at the next state (for our algorithm at the next space-step) and the subscript  $\varphi_i$  the number of the marker. The spatial increment  $\delta I$  determines the resolution in the propagation of the fire front and should be smaller than the smallest space scale influencing the fire propagation, which are usually fires breaks such as roads, i.e. in typical simulations  $\delta I \approx 0.1 \text{ m}.$ 

## 4.1.3 Coupling atmospheric and wildfire models

Forcing of the atmosphere on the fire behavior reduces to compute the wind at flame mid-height. We use a bi-linear interpolation in space and time with the ground wind issued by the atmospheric model.

<sup>25</sup> Forcing the atmospheric model with ground conditions stemming from the fire is somewhat more difficult but elegant as Meso-NH is able to treat fluxes at ground level.

Discussion Paper

Discussion Pape

Discussion Paper

As a meso-scale atmospheric model, there is a clear limitation to the level of the combustion process that can be resolved. The atmospheric model is not designed for cells smaller than a few meters and the combustion model is therefore handled as a subgrid process, unlike other codes such as WFDS or FIRETEC. Despite these limitations, us-

ing a meso-scale atmospheric model is mandatory to simulate large wildfires (that can extend several tens of kilometers) as more refined models cannot handle such large domains. The forcing mechanisms imposed by the fire on the atmosphere are then treated as ground fluxes to the atmospheric simulation.

Discussions on the relevant forcing mechanisms are beyond the scope of this article.
 The authors chose to limit themselves to the ones usually considered in the literature (Kochanski et al., 2011) i.e. heat and water vapor fluxes. The modeling of these fluxes can be tricky, as they should represent several physical phenomena such as vegetation drying by radiation, pyrolysis and soot production by combustion. All these effects are modeled within ForeFire to provide the best boundary conditions to the atmospheric model.

Computation of the desired fluxes is carried out using a high resolution arrival time matrix that is updated locally each time a marker is moved. Burning area is determined at each atmospheric time step and for each ground atmospheric cell as the difference between current time *t* and arrival time of the fire at the location  $t^{a}(x)$ . Integration of local fluxes is performed by applying a flux model  $\Phi$  on all the burning map cells  $I_{c}$  contained in an atmospheric cell:

$$\Phi^{\text{atmo}}(t) = \int_{l_c} \Phi(x, t)$$

20

and thus the resolution of the burning map  $\Delta x^{at}$  has to be much higher than atmospheric, one to insure that averages over each atmospheric ground cell define wellposed boundary conditions forced by the fire on the atmosphere. Flux models for heat



(15)

 $\Phi_h$  and water  $\Phi_w$  were defined as a constant release during a flaming duration  $\tau$ :

$$\Phi_{h}(x,t) = \frac{\Phi_{h}^{t}}{\tau} \Pi_{[0,1]} \left( \frac{t - t^{a}(x)}{\tau} \right)$$
$$\Phi_{w}(x,t) = \frac{\Phi_{w}^{t}}{\tau} \Pi_{[0,1]} \left( \frac{t - t^{a}(x)}{\tau} \right)$$

<sup>5</sup> with  $\Pi_{[0,1]}$  the gate function on time interval [0,1],  $\Phi_h^t$  the total heat to be released and  $\Phi_w^t$  the total water mass to be vaporized.

#### 4.2 Simulation setup

The fuel is assumed to be homogeneous over the burning area and the parameterisation used in the velocity model (from Anderson, 1969) resulted in a flaming dura-

- <sup>10</sup> tion  $\tau = 24$  s. Ignition temperature is taken as  $T_i = 600$  K, water evaporation enthalpy is taken as  $\Delta h_w = 2.3 \times 10^6$  J kg<sup>-1</sup> and combustion enthalpy as  $\Delta h = 20 \times 10^6$  J kg<sup>-1</sup>. Heat and vapor fluxes (resp.  $\Phi_h$  and  $\Phi_v$ ) used throughout the domain are considered to constantly release heat and water vapor during the burning process over the flaming area. The total amount released during this process is induced from several assumptions.
- <sup>15</sup> The fraction of radiant energy and combustion efficiency (portion of flaming energy usefull for convection) are assumed to take values  $\chi_0 = 0.30 (30\%)$  and  $E_c = 0.5 (50\%)$ . Moisture content was approximately 18% on the dead fuel at the time of the burn, so the total water mass to be vaporized is  $0.14 \text{ kgm}^{-2}$ . Dry fuel load was measured at  $0.79 \text{ kgm}^{-2}$  giving a potential energy of  $15.8 \times 10^6 \text{ Jm}^{-2}$  on which  $0.32 \times 10^6 \text{ Jm}^{-2}$  is lost to water evaporation, 30% is lost in radiation resulting in  $10.7 \times 10^6 \text{ Jm}^{-2}$  of available energy. With an efficiency at 0.5 this gives a total heat release forced at ground level of  $\Phi_{-}^{t} = 5350 \text{ kJm}^{-2}$  (with  $\tau = 24$  s this gives a nominal heat fluxes of 222 kW m<sup>-2</sup>). At
  - energy. With an efficiency at 0.5 this gives a total heat release forced at ground level of  $\Phi_w^t = 5350 \text{ kJm}^{-2}$  (with  $\tau = 24 \text{ s}$  this gives a nominal heat fluxes of 222 kW m<sup>-2</sup>). At 10 m resolution, typical burning area of the fire front are about 70 % of an atmospheric



(16a)

(16b)

cell resulting in actual typical heat fluxes of  $155 \, \text{kW} \, \text{m}^{-2}$  forced in the ground level of the atmospheric model.

The simulation domain was designed to incorporate the dimensions of Letia experiment using a 1280 m large, 1280 m long, 3681 m high box at  $\Delta x = \Delta y = 10$  m resolution nested in a 10240 m large, 10240 m long, 3681 m high box at  $\Delta x = \Delta y = 40$  m resolution initialized with analysis gathered from the Aladin Aladin Limited Area Model at 12:00 UTC. Atmospheric vertical resolution, and more precisely the elevation of the first cell  $\Delta z^{g}$ , impacts the dynamics of the simulation heavily as the fire is mostly a sub-cell phenomena modeled at ground level (from the atmospheric point of view) and thus injected fluxes in a better resolved simulation produce larger responses from the atmospheric model.

The fire propagation resolution is  $\delta I = 0.02$  m, filtering distance  $p_r = 0.5$  m and  $\Delta x^{at} = 0.05$  m.

Because of the scale of the experiment, observations of the precise characterization of the fuel quantity and speed of ignition of the initial fire line were limited. Fire was ignited by crew members with torches. In the simulation, the ignition procedure has been forced by imposing a 1 m wide hexagon ignited from the ignition location.

Total computational time was  $96\,000\,\text{s}$  for the high-resolution run. The fraction of CPU time that is used by the forest fire simulation is  $4400\,\text{s}$  (5%).

## 20 5 Results and discussion

## 5.1 Fire smoke plume optical properties

During this experiment, five vertical scans were performed consecutively along different azimuth angles from the burning site to West North West. The fire smoke plume EOD of each slant profile has been extracted and plotted separately by each scan in Fig. 5.

The temporal evolution of the smoke plume EOD spreads widely from  $0.03 \pm 10^{-3}$  up to  $1.17 \pm 0.17$ , and more particularly during the scan 3, which exhibits some disparate,



peaks around 1. High values of EOD (0.5–0.8) are observed in the second half period of the scan 1 and scan 2, corresponding to the lower part of the vertical scans located near ground. In contrast, during the scan 3 and 4, they are, mainly, detected in the first half period of the scan duration. Furthermore they decreased both from about 1 down to 0.03 whereas during the middle of the scan 5 duration, the EOD varies slightly (0.15–0.23). One can, easily, distinguish the increase and the decrease of the EOD,

which are associated to the inner and outer edge portion of the smoke plume.

5

The  $EL_R$  average smoke plume value of all scan is 79 sr with a standard deviation of 19 sr and a median of 75 sr. The  $EL_R$  range mean values obtained during each scan

- <sup>10</sup> varies between 68 sr (scan 5) and 101 sr (scan 1). The high EL<sub>R</sub> values are mainly, more particularly, observed near the source site and may reveal the absorption nature of the fresh smoke aerosols. This EL<sub>R</sub> range, obtained at 355 nm wavelength, is in agreement with the lidar ratio ( $L_R$ ) measured from a Raman lidar during DABEX (Heese and Wiegner, 2008), 2009 Attica wild fires (Amiridis et al., 2012) and during smoke plumes advection of period from biomass burning regions over Thessaloniki in
- Greece (Amiridis et al., 2009). Moreover, the EL<sub>R</sub> values, retrieved during the LETIA experiment is in the range of the  $L_R$  of biomass burning aerosols deduced during the winter campaign SAMUM 2 at Cape Verde (Tesche et al., 2011; Gross et al., 2011). Therefore the EL<sub>R</sub> LETIA experiment values, corresponding to a pure biomass burning smoke, may indicate low effects of the multiple scattering inside the smoke plume.

The knowledge of EL<sub>R</sub> for each slant profile allows us to inverse correctly the lidar equation in the aim to extract the backscatter coefficient. Vertical aerosol backscatter coefficient cross-sections (Fig. 6) clearly show heterogeneous spatial distribution of backscatter coefficient inside the fire smoke plume. Although some scans do not detect the fully smoke plume, it is possible to distinguish the core and the plume rise on most scans. In the beginning of the burning, the plume rises up to about 60–80 m height (Fig. 6a and b). Maximum backscatter coefficients of scan 1 (> 0.1 km<sup>-1</sup> sr<sup>-1</sup>) are mainly located in the lower part of the plume rise near the ground at about 200 m range from the lidar (Fig. 6a) and during the scan 2, one can see the core of the plume,



associated with high backscatter coefficients (>  $0.15 \text{ km}^{-1} \text{ sr}^{-1}$ ) located between 20 and 40 m height. Then, 10–12 min later (Fig. 6c and d), the scans 3 and 4 reveal an increase of the backscatter coefficients in the upper part of the plume, reaching  $0.19 \text{ km}^{-1} \text{ sr}^{-1}$  at the height of 100 m in the scan 3 and 180 m in the scan 4 (Fig. 6c, d).

- <sup>5</sup> During the scan 4, a transition phase between the rising smoke plume domination period and the smoke plume residual advection layer period seems to be perceptible. The smoke plume is decoupled (vertically) from the ground and the smoke injection height appears at about 200 m and remains the same in the next scan (Fig. 6e). Finally, 15 min after the scan 1, the plume is detected at about 300 m range from the lidar and between
- 10 100 m and 200 m above the altitude of the lidar. The maximum backscatter values observed decreases of about 0.1 km<sup>-1</sup> sr<sup>-1</sup>. Although, this scan was accomplished after the burning period, this strong relative backscatter coefficient decrease shows a high effect of smoke plume dilution (especially horizontally) in a thin layer of less than 100 m.

## 5.2 Simulation results and correlation with Lidar observations

In order to assess the ability of the model to reproduce the fire smoke plume characteristics (density and dynamics), a passive numerical scalar tracer was injected at the first atmospheric model level with a surface concentration of 1 s<sup>-1</sup> m<sup>-2</sup> wherever the fire is active (flaming). Figure 7 represents the simulated smoke plume in the two model domains at 10 m (inner domain) and 40 m (outer domain) resolutions. The lower model
 resolution in the outer domain does not allow to resolve turbulent structures with critical length smaller than 40 m and shorter than a few seconds duration.

It is worth noting that the passive tracer is appropriate to figure the dynamics of the fire emissions but it does not directly relate to the optical properties of the fire plume (opacity). Due to this limitation, the characteristics of the observed and simu-

<sup>25</sup> lated smoke plumes are discussed in terms of smoke plume edge (Sect. 3.3), vertical and horizontal smoke plume location (Sects. 3.2 and 3.4) and plume inclination angle (Sect. 3.4).



Figure 8 represents simulated vertical cross section (diagnosed from the same location and time as lidar scans shots in Fig. 6) of passive tracer concentration. Experimental smoke plume edge (red star) has been superimposed on the simulated vertical cross section. In most cases, the model was able to capture the local fire smoke plume which is well located within the edge of the observed smoke plume, deduced from the

- lidar, more particularly during the first two scans. A slight shift of about 50 m toward E/ESE of the smoke bottom part is found in the scans 3 and 4 whereas in the smoke plume upper layer, the simulated passive tracer concentration spreads continuously outside the experimental edge plume toward W/WNW direction but with low values
- (< 1.5 a.u.). During the scan 3, the upper part plume dispersions directions along the 10 axis E–W seem to be opposite probably due to the effect of turbulence. In the scans 3 and 4, the simulated injection height of the passive tracer underestimates the observed smoke plume altitude shown in Fig. 6. During the three last scans, the observed smoke plume is decoupled from the ground, which is not reproduced by the model. The smoke
- tracer is injected continuously at the ground level and the model does not account for 15 chemical or physical loss terms (deposition, nucleation or condensation of particles, etc.). The passive tracer is therefore maximum at the surface, decreasing with altitude. The observed smoke plume is sensitive to high opacity particles which tend to form at lower temperatures i.e. at higher altitude in the plume. Nevertheless, the simulated smoke injection height and smoke plume edge of the last scans appears to agree well 20
- with the observations (at about 200 m).

5

The main location of the smoke plume density estimated by the backscatter coefficient barycenter for the observation (red circle) and the passive tracer concentration barycenter for the model (black circle) have been plotted on the simulated scans in

Fig. 8 and synthesized in Fig. 9. At the beginning of the burning (scan 1 and 2), experi-25 mental and modeled barycenters are well located with only a slight difference height of 15 m. This difference increases in the two next scans (50 m and 70 m) corresponding to a plume inclination angle difference (observation/model) of 24° and 22° instead of 14° and 10° in the scan 1 and 2. The model systematically underestimates the height



Discussion

of the barycenter in the scan 3 and 4, this difference decreases in the last scan 5. This underestimation of the simulated injection height could be partially explained, not only by higher passive tracer concentration injection near the ground but also by a slight overestimation of the simulated horizontal wind speed compared to the observed wind

- <sup>5</sup> speed derived from the videography method. Nevertheless, except during the scan 3, experimental and simulated horizontal wind speeds during the burning period, are in agreement (Fig. 10). The simulation has been initialized with 12:00 UTC meteorological analysis from the operational Aladin LAM at 2.4 km resolution. These analyses prove to be in very good accordance with the observed conditions of the day, with
- a slightly more westerly direction but correct wind speed according to the anemometer. Given the mountainous region it is expected that the LAM cannot represent precisely the ground flows in such steep orography. However, the model simulates correctly the smoke plume advection with a maximum deviation, between both barycenter locations (observation/model), of about 100 m, which corresponds to a relative deviation of about 20 % from the burning site (Fig. 11).
- <sup>15</sup> 20% from the burning site (Fig. 11).

#### 6 Conclusions

20

25

An instrumented field experimental burn was performed in the mountainous Mediterranean region of Letia, Corsica, a typical great wildfire danger area. The burnt vegetation was characterized by homogeneously distributed low shrubs with a heat release estimated at 33.5 MJ m<sup>-2</sup> of dead fuels.

An UV scanning lidar was deployed at a range of 170 m from the burning site to assess the temporal and spatial evolution and injection height of the smoke plume. Aerosols optical properties and the fire smoke plume edge and main locations were derived from a combination of methods based on lidar inversion technique, wavelet edge detection method and a backscatter barycenter technique. A digital video camera was coupled with the lidar measurements to estimate the smoke plume displace-



from 0.03 ± 10<sup>-3</sup> up to 1.17 ± 0.17 and the Effective Lidar ratio (EL<sub>R</sub>) average smoke plume estimate is 79 sr with a standard deviation of 19 sr and a median of 75 sr. Inside the fire smoke plume, backscatter coefficient spatial distribution is heterogeneous with a maximum of 0.19 km<sup>-1</sup> sr<sup>-1</sup> observed 10 min later after the burning start. The maximum smoke injection height derived from the lidar observation reaches about 200 m. Lidar observations revealed that the smoke plume when identified by the backscatter coefficients, representative of smoke opacity, is rapidly disconnected from the ground. A fire-atmosphere model Meso-NH/ForeFire was used to simulate the experimental burn and the smoke plume at high resolution. The fire propagation was simulated with

- <sup>10</sup> a simplified 3-D fully physical fire model based on a high-resolution front advection approach. The fire front velocity model was parameterized with the actual properties of the fuel on the burn day. The fire propagation model was coupled with a mesoscale anelastic meteorological model Meso-NH. The numerical set-up consisted of 2 nested domains, at 10 m high resolution near the fire and 40 m resolution over a 10 km by
- 10 km area. A passive tracer was injected at the fire location to mimic the smoke plume in the model. Simulated plume width showed good agreement with the lidar observations. Simulated smoke plume top location remained within 60 m from the altitude derived from the lidar observations. The simulated smoke plume remained in contact with the surface due to continuous emission and missing loss processes such as depo-
- sition or particles aging. Simulated wind speed over the fire plume compared well with the wind speed derived from the videography method, suggesting that fire convection was correctly taken into account.

This paper demonstrated the benefit of lidar observations of smoke plume for the validation of fire-atmosphere models. Further work is needed to simulated properly

<sup>25</sup> pyrogenic aerosols in the coupled model in order to take full advantage of the lidar measurements and increase our capacity to derive smoke exposure and associated health effects.



Supplementary material related to this article is available online at http://www.nat-hazards-earth-syst-sci.net/1/3991/2013/ nhessd-1-3991-2013-supplement.zip.

Acknowledgements. This research is supported by the Agence Nationale de la Recherche,
 IDEA ANR-09-COSI-006, http://anridea.univ-corse.fr. The LETIA experiment and consequent research work were supported by the french program INSU-LEFE-CHAT and the french ADEME (Agence de l'Environnement et de la maitrise de l'Energie) agency. The computing ressources were provided by GENCI-CINES. We thank the MESO-NH support team, project members and anonymous reviewers for the precious help and discussions.

#### **10** References

20

- Alves, C. A., Gonçalves, C., Evtyugina, M., Pio, C. A., Mirante, F., and Puxbaum, H.: Particulate organic compounds emitted from experimental wildland fires in a Mediterranean ecosystem, Atmos. Environ., 44, 2750–2759, 2010.
- Alves, C. A., Vincente, A., Monteiro, C., Goncalves, C., Evtyugina, M., and Pio, C.: Emission of trace gases and organic components in smoke particules from a wildfire in mixed-evergreen
- trace gases and organic components in smoke particules from a wildfire in mit forest in Portugal, Sci. Total Environ., 409, 1466–1475, 2011.
  - Amiridis, V., Balis, D. S., Giannakaki, E., Stohl, A., Kazadzis, S., Koukouli, M. E., and Zanis, P.: Optical characteristics of biomass burning aerosols over Southeastern Europe determined from UV-Raman lidar measurements, Atmos. Chem. Phys., 9, 2431–2440, doi:10.5194/acp-9-2431-2009, 2009.
  - Amiridis, V., Zerefos, C., Kazadzis, S., Gerasopoulos, E., Eleftheratos, K., Vrekoussis, M., Stohl A., Mamouri, R. E., Kokkalis, P., Papayannis, A., Eleftheriadis, K., Diapouli, E., Keramitsoglou, I., Kontoes, C., Kotronid, V., Lagouvardos, K., Marinou, E., Giannakaki, E., Kostopoulou, E., Giannakopoulos, C., Richter, A., Burrows, J. P., and Mihalopoulos, N.: Im-
- pact of the 2009 Attica wild fires on the air quality in urban Athens, Atmos. Environ., 46, 536–544, 2012.



Anderson, H. E.: Heat transfer and fire spread, USDA Forest Service research paper INT. Intermountain Forest and Range Experiment Station, Forest Service, US Dept. of Agriculture, Ogden, Utah, 1969.

ASTM: D2015-96 Standard Test Method for Gross Calorific Value of Solid Fuel by the Adiabatic Bomb Calorimeter, ASTM International, West Conshohocken, PA, 1996.

Bomb Calorimeter, ASTM International, West Conshohocken, PA, 1996.
 Baars, H., Ansmann, A., Engelmann, R., and Althausen, D.: Continuous monitoring of the boundary-layer top with lidar, Atmos. Chem. Phys., 8, 7281–7296, doi:10.5194/acp-8-7281-2008, 2008.

Balbi, J. H., Morandini, F., Silvani, X., Filippi, J. B., and Rinieri, F.: A physical model for wildland fires, Combust. Flame, 156, 2217–2230, 2009.

10

15

Barboni, T., Cannac, M., Pasqualini, V., Simeoni, A., Leoni, E., and Chiaramonti, N.: Volatile and semi-volatile organic compounds in smoke exposure of firefighters during prescribed burning in the Mediterranean region, Int. J. Wildland Fire, 19, 606–612, 2010.

Bodhaine, B., Wood, N. B., Dutton, E. G., and Slusser, J. R.: On Rayleigh optical depth calculations, J. Atmos. Ocean. Tech., 16, 1854–1861, 1999.

Boers, R. and Eloranta, E. W.: Lidar measurement of the atmospheric entrainment zone and the potential temperature jump across the top of the mixed layer, Bound.-Lay. Meteorol., 34, 357–375, 1986.

Brooks, I. M.: Finding boundary layer top: application of a wavelet covariance transform to lidar

- back- scatter profiles, J. Atmos. Ocean. Tech., 20, 1092–1105, 2003.
   Bucholtz, A.: Rayleigh-scattering calculations for the terrestrial atmosphere, Appl. Optics, 34, 2765–2773, 1995.
  - Burling, I. R., Yokelson, R. J., Akagi, S. K., Urbanski, S. P., Wold, C. E., Griffith, D. W. T., Johnson, T. J., Reardon, J., and Weise, D. R.: Airborne and ground-based measurements of
- the trace gases and particles emitted by prescribed fires in the United States, Atmos. Chem. Phys., 11, 12197–12216, doi:10.5194/acp-11-12197-2011, 2011.
  - Burrows, N. D.: Flame residence times and rates of weight loss of eucalypt forest fuel particles, Int. J. Wildland Fire, 10, 137–143, doi:10.1071/WF01005, 2001.
  - Chu, D. A., Kaufman, Y. J., Zibordi, G., Chern, J. D., Mao, J., Li, C., and Holben, B. N.: Global monitoring of air pollution over land from the Earth observing System-Terra Mod-
- Global monitoring of air pollution over land from the Earth observing System-Terra Moderate Resolution Imaging Spectroradiometer (MODIS), J. Geophys. Res., 108, 4661, doi:10.1029/2002JD003179, 2003.



- Clark, T. L., Jenkins, M. A., Coen, J. L., and Packham, D. R.: A coupled atmosphere–fire model: convective feedback on fire line dynamics, J. Appl. Meteorol., 35, 875–901, 1996.
- Cohn, S. A. and Angevine, W. M.: Boundary layer height and entrainment zone thickness measured by lidars and wind-profiling radars, J. Appl. Meteorol., 39, 1233–1247, 2000.
- <sup>5</sup> Colella, P. and Woodward, P. R.: The Piecewise Parabolic Method (PPM) for gasdynamical simulations, J. Comput. Phys., 54, 174–201, 1984.

Das, S. K., Chiang, C.-W., and Nee, J.-B.: Characteristics of cirrus clouds and its radiative properties based on lidar observation over Chung-Li, Taiwan, Atmos. Res., 93, 723–735, 2009.

- Davis, K., Gamage, N., Hagelberg, C. Kiemle, C. Lenschow, D. H., and Sullivan, P. P.: An objective method for determining atmospheric structure from airborne lidar observations, J. Atmos. Ocean. Tech., 17, 1455–1468, 2000.
  - Di Donfrancesco, G., Cairo, F., Buontempo, C., Adriani, A., Viterbini, M., Snels, M., Morbidini, R., Piccolo, F., Cardillo, F., Pommereau, J. P., and Garnier, A.: Balloonborne lidar for cloud physics studies. Appl. Optics, 45, 5701–5708, 2006.
  - Fernald, F. G.: Analysis of atmospheric lidar observations: some comments, Appl. Optics, 23, 652–653, 1984.

15

20

- Fernandes, A. M., Utkin, A. B., Lavrov, A. V., and Vilar, R.: Optimisation of location and number of lidar apparatuses for early forest fire detection in hilly terrain, Fire Safety J., 41, 144–154, 2006.
- Filippi, J. B., Bosseur, F., Mari, C., Lac, C., Le Moigne, P., Cuenot, B., Veynante, D., Cariolle, D., and Balbi, J. H.: Coupled atmosphere-wildland fire modelling, Journal of Advances in Modeling Earth Systems, 1, 11, doi:10.3894/JAMES.2009.1.11, 2009.

Filippi, J. B., Bosseur, F., Pialat, X., Santoni, P. A., Strada, S., and Mari, C.: Simulation of cou-

- pled fire/atmosphere interaction with the MesoNH-ForeFire models, Journal of Combustion, 2011, 540390, doi:10.1155/2011/540390, 2011.
  - Flamant, C., Pelon, J., Flamant, P. H., and Durand, P.: Lidar determination of the entrainment zone thickness at the top of the unstable marine atmospheric boundary layer, Bound.-Lay. Meteorol., 83, 247–284, 1997.
- Franzi, L., Bratt, J. M., Williams, K. M., and Last, J. A.: Why is particulate matter produced by wildfires toxic to lung macrophages?, Toxicol. Appl. Pharm., 257, 182–188, doi:10.1016/j.taap.2011.09.003, 2011.



Discussion

Paper

Discussion

Paper

Discussion Pape



- Gamage, N. K. K. and Hagelberg, C.: Detection and analysis of microfronts and associated coherent events using localized transforms, J. Atmos. Sci., 50, 750-756, 1993.
- Gan, C.-M., Wu, Y., Madhavan, B. L., Gross, B., and Moshary, F.: Application of active optical sensors to probe the vertical structure of the urban boundary layer and assess anomalies in air quality model PM<sub>2.5</sub> forecasts, Atmos. Environ., 45, 6613–6621, 2011.
- 5 Gross, S., Tesche, M., Freudenthaler, V., Toledano, C., Wiegner, M., Ansmann, A., Althausen, D., and Seefeldner, M.: Characterization of Saharan dust, marine aerosols and a mixture of biomass-burning aerosols and dust by means of multi-wavelength depolarizationand Raman measurements during SAMUM-2, Tellus B, 63, 706-724, doi:10.1111/j.1600-0889.2011.00556.x. 2011.

10

Heese, B. and Wiegner, M.: Vertical aerosol profiles from Raman polarization lidar observations during the dry season AMMA field campaign, J. Geophys. Res., 113, D00C11, doi:10.1029/2007JD009487.2008.

Hodzic, A., Madronich, S., Bohn, B., Massie, S., Menut, L., and Wiedinmyer, C.: Wildfire par-

- ticulate matter in Europe during summer 2003; meso-scale modeling of smoke emissions. 15 transport and radiative effects, Atmos. Chem. Phys., 7, 4043–4064, doi:10.5194/acp-7-4043-2007, 2007.
  - Hooper, W. P. and Eloranta, E. W.: Lidar measurements of wind in the planetary boundary layer: the method, accuracy and results from joint measurements with radiosonde and kytoon, J.

Clim. Appl. Meteorol., 25, 990–1001, 1986. 20

- Kochanski, A., Jenkins, M. A., Krueger, S. K., Mandel, J., Beezley, J. D., and Clements, C. B.: Coupled atmosphere-fire simulations of the FireFlux experiment: impacts of model resolution on its performance, Ninth Symposium on Fire and Forest Meteorology, 18-20 October 2011, Palm Springs, CA, 10.2, 1–8, 2011.
- <sup>25</sup> Kovalev, V. A., Petkov, A., Wold, C., Urbanski, S., and Hao, W. M.: Determination of smoke plume and layer heights using scanning lidar data, Appl. Optics, 48, 5287–5294, 2009.
  - Lafore, J. P., Stein, J., Asencio, N., Bougeault, P., Ducrocq, V., Duron, J., Fischer, C., Héreil, P., Mascart, P., Masson, V., Pinty, J. P., Redelsperger, J. L., Richard, E., and Vilà-Guerau de Arellano, J.: The Meso-NH Atmospheric Simulation System. Part I: adiabatic formulation and control simulations, Ann. Geophys., 16, 90–109, doi:10.1007/s00585-997-0090-6, 1998.
- 30 Langmann, B., Duncan, B., Textor, C., Trentmann, J., and Van der Werf, G. R.: Vegetation fire emissions and their impact on air pollution and climate, Atmos. Environ., 43, 107-116, 2009.





- Lavrov, A., Utkin, A. B., Vilar, R., and Fernandes, A.: Application of lidar in ultraviolet, visible and infrared ranges for early forest fire detection, Int. J. Wildland Fire, 12, 159–166, 2003.
- Lavrov, A., Utkin, A. B., Vilar, R., and Fernandes, A.: Evaluation of smoke dispersion from forest fire plumes using lidar experiments and modelling, Int. J. Thermal Sci., 45, 848–859, 2006.
- Lee, S., Baumann, K., Schauer, J. J., Sheesley, R. J., Naeher, L. P., Meinardi, S., Blake, D. R., Edgerton, E. S., Russell, A. G., and Clements, M.: Gaseous and particulate emissions from prescribed burning in Georgia, Environ. Sci. Technol., 39, 9049–9056, doi:10.1021/es051583I, 2005.

Leonard, S., Castranova, V., Chen, B. T., Schwegler-Berry, D., Hoover, M., Piacitelli, C., and

- Gaughan, D. M.: Particle size-dependent radical generation from wildland fire smoke, Toxicology, 236, 103–113, doi:10.1016/j.tox.2007.04.008, 2007.
  - Menut, L., Flamant, C., Pelon, J., and Flamant, P. H.: Urban boundary-layer height determination from lidar measurements over the Paris area, Appl. Optics, 38, 945–954, 1999.

Mandel, J., Beezley, J. D., and Kochanski, A. K.: Coupled atmosphere-wildland fire modeling

- with WRF 3.3 and SFIRE 2011, Geosci. Model Dev., 4, 591–610, doi:10.5194/gmd-4-591-2011, 2011.
  - Mao, F., Gong, W., Song, S., and Zhu, Z.: Determination of the boundary layer top from lidar backscatter profiles using a Haar wavelet method over Wuhan, China, Opt. Laser Technol., 49, 343–349, 2013.
- Marenco, F., Johnson, B., Turnbull, K., Newman, S., Haywood, J., Webster, H., and Ricketts, H.: Airborne lidar observations of the 2010 Eyjafjallajokull volcanic ash plume, J. Geophys. Res.-Atmos., 116, D00U05, doi:10.1029/2011JD016396, 2011.
  - Matis, I., Ansmann, A., Wandinger, U., and Muller, D.: Unexpectedly high aerosol load in the free troposphere over central Europe in spring/summer 2003, Geophys. Res. Lett., 30, 2178, doi:10.1029/2003GL018442, 2003.

25

30

- Miranda, A. I.: An integrated numerical system to estimate air quality effects of forest fires, Int. J. Wildland Fire, 13, 217–226, doi:10.1071/WF02047, 2004.
- Miranda, A. I., Ferreira, J., Valente, J., Santos, P., Amorin, J. H., and Borrego, C.: Smoke measurements during Gestosa-2002 experimental field fires, Int. J. Wildland Fire, 14, 107–116, 2005.
- Mona, L., Liu, Z., Mueller, D., Omar, A., Papayannis, A., Pappalardo, G., Sugimoto, N., and Vaughan, M.: Lidar measurements for desert dust characterization: an overview, Advances in Meteorology, 2012, 356265, doi:10.1155/2012/356265, 2012.



Discussion

Paper

**Discussion** Paper

**Discussion** Pape

Moro, C.: Détermination des caractéristiques physiques de particules de quelques espèces forestières méditerranéennes, INRA-URFM, Document PIF2006-06, Avignon, France, 2006 (in French).

Omar, A., Winker, D., Kittaka, C., Vaughan, M., Liu, Z., Hu, Y., Trepte, C. R., Ferrare, R. A., Lee,

5 K.-P., and Hostetler, C. A.: The CALIPSO automated aerosol classification and lidar ratio selection algorithm, J. Atmos. Ocean. Tech., 26, 1994–2014, 2009.

Pahlow, M., Kleissl, J., Parlange, M. B., Ondov, J. O., and Harrison, D.: Atmospheric boundarylayer structure observed during a haze event due to forest-fire smoke, Bound.-Lay. Meteorol., 114, 53–70, 2005.

Phuleria, H. C., Fine, P. M., Zhu, Y., and Sioutas, C.: Air quality impacts of the October 2003 Southern California wildfires, J. Geophys. Res., 110, D07S20, doi:10.1029/2004JD004626, 2005.

Platt, C. M. R.: Remote sounding of high clouds, 3: Monte Carlo calculations of multiplescattered lidar returns, J. Atmos. Sci., 38, 156–167, 1981.

- <sup>15</sup> Raut, J.-C. and Chazette, P.: Assessment of vertically-resolved PM<sub>10</sub> from mobile lidar observations, Atmos. Chem. Phys., 9, 8617–8638, doi:10.5194/acp-9-8617-2009, 2009.
  - Reinhardt, T. E. and Ottmar, R. D.: Baseline measurements of smoke exposure among wildland firefighters, J. Occup. Environ. Hyg., 1, 593–606, 2004.

Royer, P., Chazette, P., Sartelet, K., Zhang, Q. J., Beekmann, M., and Raut, J.-C.: Compar-

- ison of lidar-derived PM<sub>10</sub> with regional modeling and ground-based observations in the frame of MEGAPOLI experiment, Atmos. Chem. Phys., 11, 10705–10726, doi:10.5194/acp-11-10705-2011, 2011.
- San-Miguel-Ayanz, J., Schulte, E., Schmuck, G., Camia, A., Strobl, P., Liberta, G., Giovando, C., Boca, R., Sedano, F., Kempeneers, P., McInerney, D., Withmore, C., Santos de Oliveira, S., Rodrigues, M., Durrant, T., Corti, P., Oehler, F., Vilar, L., and Amatulli, G.: Comprehensive monitoring of wildfires in Europe: the European Forest Fire Information System (EFFIS), in: Approaches to Managing Disaster Assessing Hazards, Emergencies and Disaster Impacts, edited by: Tiefenbacher, J., InTech, available at: http://cdn.intechopen.com/pdfs/31818/InTech-comprehensive\_monitoring\_of\_wildfires\_in\_europe\_the\_european\_forest\_fire\_information\_system\_effis\_.pdf, last access: 11 July 2013, 2012

| <b>NHESSD</b><br>1, 3991–4036, 2013                      |                             |  |  |
|--|-----------------------------|--|--|
| Evaluation of<br>vegetation fire smoke<br>plume dynamics |                             |  |  |
| V. Leroy-Car   | V. Leroy-Cancellieri et al. |  |  |
| Title  | Page                        |  |  |
| Abstract   | Introduction                |  |  |
| Conclusions  | References                  |  |  |
| Tables   | Figures                     |  |  |
| 14   | ۶I                          |  |  |
| •  | •                           |  |  |
| Back   | Close                       |  |  |
| Full Screen / Esc  |                             |  |  |
| Printer-friendly Version                                 |                             |  |  |
| Interactive Discussion                                   |                             |  |  |
|  |                             |  |  |

Discussion Paper

**Discussion** Paper

**Discussion** Paper

Santoni, P. A., Filippi, J. B., Balbi, J. H., and Bosseur, F.: Wildland fire behaviour case studies and fuel models for landscape-scale fire modeling, J. Combustion, 2011, 613424, doi:10.1155/2011/613424, 2011.

Sasano, Y., Shimizu, H., Takeuchi, N., and Okuda, M.: Geometrical form factor in the laser radar equation: an experimental determination, Appl. Optics, 18, 3908–3910, 1979.

- <sup>5</sup> equation: an experimental determination, Appl. Optics, 18, 3908–3910, 1979. Shinozuka, Y., Clarke, A. D., Howell, S. G., Kapustin, V. N., McNaughton, C. S., Zhou, J., and Anderson, B. E.: Aircraft profiles of aerosol microphysics and optical properties over North America: Aerosol optical depth and its association with PM<sub>2.5</sub> and water uptake, J. Geophys. Res., 112, D12S20, doi:10.1029/2006JD007918, 2007.
- <sup>10</sup> Singh, H. B., Cai, C., Kaduwela, A., Weinheimer, A., and Wisthaler, A.: Interactions of fire emissions and urban pollution over California: ozone formation and air quality simulations, Atmos. Environ., 56, 45–51, doi:10.1016/j.atmosenv.2012.03.046, 2012.

Steyn, D. G., Baldi, M., and Hoff, R. M.: The detection of mixed layer depth and entrainment zone thickness from lidar backscatter profiles, J. Atmos. Ocean. Tech., 16, 953–959, 1999.

- Strada, S., Mari, C., Filippi, J. B., and Bosseur, F.: Wildfire and the atmosphere: modelling the chemical and dynamic interactions at the regional scale, Atmos. Environ., 51, 234–249, 2012.
  - Tesche, M., Müller, D., Gross, S., Ansmann, A., Althausen, D., Freudenthaler, V., Weinzierl, B., Veira, A., and Petzold, A.: Optical and microphysical properties of smoke over Cape Verde
- inferred from multiwavelength lidar measurements, Tellus B, 63, 677–694, 2011. Utkin, A. B., Fernandes, A., Simoes, F., Lavrov, A., and Vilar, R.: Feasibility of forest-fire smoke detection using lidar, Int. J. Wildland Fire, 12, 159–166, 2003.
  - Vadrevu, K. P., Ellicott, E., Giglio, L., Badarinath, K. V. S., Vermote, E., Justice, C., and Lau, W. K. M.: Vegetation fires in the himalayan region aerosol load, black carbon emissions and smoke plume beights. Atmos Emirer 47, 041, 051, 0010
- sions and smoke plume heights, Atmos. Environ., 47, 241–251, 2012.
   van Donkelaar, A., Martin, R. V., and Park, R. J.: Estimating ground-level PM<sub>2.5</sub> using aerosol
  - optical depth determined from satellite remote sensing, J. Geophys. Res., 111, D21201, doi:10.1029/2005JD006996, 2006.

Vincente, A., Alves, C., Monteiro, C., Nunes, T., Mirante, F., Cerqueira, M., Calvo, A., and Pio, C.: Organic speciation of aerosols from wildfires in control Portugal during cummer 2000. Attack

<sup>30</sup> Organic speciation of aerosols from wildfires in central Portugal during summer 2009, Atmos. Environ., 57, 186–196, 2012.

| NHE                             | NHESSD   |  |  |
|---------------------------------|--|--|--|
| 1, 3991–4                       | 1036, 2013   |  |  |
| Evalua<br>vegetation<br>plume d | Evaluation of<br>vegetation fire smoke<br>plume dynamics |  |  |
| V. Leroy-Ca                     | V. Leroy-Cancellieri et al.                              |  |  |
| Title                           | Title Page   |  |  |
| Abstract                        | Introduction   |  |  |
| Conclusions                     | References   |  |  |
| Tables                          | Figures  |  |  |
| 14                              | ►I   |  |  |
| •                               | •  |  |  |
| Back                            | Close  |  |  |
| Full Scre                       | Full Screen / Esc  |  |  |
| Printer-frier                   | Printer-friendly Version                                 |  |  |
| Interactive                     | Interactive Discussion                                   |  |  |
|                                 |  |  |  |

Discussion Paper

**Discussion** Paper

**Discussion** Paper

Wang, J. and Christopher, S. A.: Intercomparison between satellite derived aerosol optical thickness and PM<sub>2.5</sub> mass: implications for air quality studies, Geophys. Res. Lett., 30, 2095, doi:10.1029/2003GL018174, 2003.

Wegesser, T. C., Pinkerton, K. E., and Last, J. A.: California wildfires of 2008: coarse and fine particulate matter toxicity, Environ. Health Persp., 117, 893–897, 2009.

5

15

20

Weibring, P., Andersson, M., Edner, H., and Svanberg, S., Remote monitoring of industrial emissions by combination of lidar and plume velocity measurements, Appl. Phys. B, 66, 383–388, 1998.

Winker, D. M., Vaughan, M. A., Omar, A., Hu, Y., Powell, K. A., Liu, Z., Hunt, W. H., and

- 10 Young, S. A.: Overview of the CALIPSO mission and CALIOP data processing algorithms, J. Atmos. Ocean. Tech., 26, 2310–2323, 2009.
  - Wold, C. E., Urbanski, S., Kovalev, V., Petkov, A., and Hao, W. M.: Validation of smoke plume rise models using ground based lidar, in: Proceedings of 3rd Fire Behavior and Fuels Conference, Spokane, WA, Birmingham, AL, edited by: Wade, D. D. and Robinson, M. L., International Association of Wildland Fire, 11, 2010.
  - Yan, B., Zheng, M., Hu, Y. T., Lee, S., Kim, H. K., and Russell, A. G.: Organic composition of carbonaceous aerosols in an aged prescribed fire plume, Atmos. Chem. Phys., 8, 6381– 6394, doi:10.5194/acp-8-6381-2008, 2008.

Young, S. A.: Analysis of lidar backscatter profiles in optically thin clouds, Appl. Optics, 34, 7019–7031, 1995.



**Table 1.** Fuel characteristics derived from laboratory measurements for *Genista Salzamannii* collected on the experimental site in Letia.

| Parameters                                 | Variable   | Genista Salzamannii $(\varphi < 6 \text{ mm})$ |       |
|--|------------|--|-------|
|  |            | Live   | Dead  |
| Moisture content on dry basis (%)          | т          | 66.7   | 17.9  |
| Fuel load (kgm <sup>-2</sup> )             | Ŵ          | 0.997  | 0.790 |
| Heat of combustion (kJ kg <sup>-1</sup> )  | $\Delta H$ | 20 645   | 20239 |
| Specific heat content $(J kg^{-1} K^{-1})$ | $C_{p}$    | 1648   | 1922  |
| Surface to volume $(m^{-1})$               | σ          | 3100   | 2505  |



| lienteeinn | <b>NHE</b><br>1, 3991–4         | <b>SSD</b><br>036, 2013          |  |  |  |
|------------|---------------------------------|----------------------------------|--|--|--|
|            | Evalua<br>vegetation<br>plume d | tion of<br>fire smoke<br>ynamics |  |  |  |
|            | V. Leroy-Cancellieri et al.     |                                  |  |  |  |
| DDD        | Abstract                        | Introduction                     |  |  |  |
| -          | Conclusions                     | References                       |  |  |  |
|            | Tables                          | Figures                          |  |  |  |
|            | I                               | ►I                               |  |  |  |
|            | •                               | •                                |  |  |  |
| _          | Back                            | Close                            |  |  |  |
|            | Full Screen / Esc               |                                  |  |  |  |
|            | Printer-friendly Version        |                                  |  |  |  |
| Dapo       | Interactive                     | Discussion                       |  |  |  |
|            | $\odot$                         | ()<br>BY                         |  |  |  |

 Table 2. Meteorological conditions.

| Wind velocity        | Wind direction | Pressure | Temperature | Air Humidity |
|----------------------|----------------|----------|-------------|--------------|
| (m s <sup>-1</sup> ) | (°)            | (hPa)    | (°C)        | (%)          |
| 2.6                  | SSE            | 867      | 21.0        | 33.1         |

|            | Time (UTC)  | Zenith (°) | Azimut (°) | Step (zenith) | No. of shoot |
|------------|-------------|------------|------------|---------------|--------------|
| Scan no. 1 | 10:27–10:29 | 70–89°     | 265°       | 1°            | 100          |
| Scan no. 2 | 10:30–10:32 | 70–89°     | 270°       | 1°            | 100          |
| Scan no. 3 | 10:33–10:35 | 50–89°     | 280°       | 1°            | 50           |
| Scan no. 4 | 10:36–10:39 | 30–89°     | 285°       | 1°            | 50           |
| Scan no. 5 | 10:41–10:43 | 40–89°     | 315°       | 1°            | 50           |
|            |             |            |            |               |              |

 Table 3. Lidar strategy measurements.





Fig. 1. Experimental site.

| <b>NHE</b><br>1, 3991–4         | <b>NHESSD</b><br>1, 3991–4036, 2013                      |  |  |
|---------------------------------|--|--|--|
| Evalua<br>vegetation<br>plume d | Evaluation of<br>vegetation fire smoke<br>plume dynamics |  |  |
| V. Leroy-Car                    | V. Leroy-Cancellieri et al.                              |  |  |
| Title                           | Title Page   |  |  |
| Abstract                        | Introduction   |  |  |
| Conclusions                     | References   |  |  |
| Tables                          | Figures  |  |  |
| I                               | ►I.  |  |  |
| •                               | Þ  |  |  |
| Back                            | Close  |  |  |
| Full Scre                       | Full Screen / Esc  |  |  |
| Printer-friendly Version        |  |  |  |
| Interactive Discussion          |  |  |  |
|                                 |  |  |  |

**Discussion Paper** 

**Discussion** Paper

**Discussion** Paper



Fig. 2. Array of devices.





Fig. 3. Wind velocity and direction measured during the fire spread experiment.





**Fig. 4.** Backscatter coefficient profile deduced from lidar measurements during LETIA experiment. Vertical bars correspond to the smoke plume edge ( $r_{\rm b}$  and  $r_{\rm t}$ ) from the lidar.





Fig. 5. Time evolution of the fire smoke plume Effective Optical Depth (EOD) deduced from (a) scan 1, (b) scan 2, (c) scan 3, (d) scan 4, (e) scan 5.





**Fig. 6.** Vertical cross-section of backscatter coefficient along azimuth **(a)** 265° at 10:27–10:29 UTC (scan 1), **(b)** 270° at 10:30–10:32 UTC (scan 2), **(c)** 280° at 10:33–10:35 UTC (scan 3), **(d)** 285° at 10:36–10:39 UTC (scan 4), **(e)** 315° at 10:41–10:43 UTC (scan 5).





**Fig. 7.** Simulated smoke tracer in the large and nested domain at *t*: 1000 s. Lidar location is shown in red.

| Discussion Pa | <b>NHESSD</b><br>1, 3991–4036, 2013 |                                  |  |  |
|---------------|-------------------------------------|----------------------------------|--|--|
| aper   Di     | Evalua<br>vegetation<br>plume d     | tion of<br>fire smoke<br>ynamics |  |  |
| scussion      | V. Leroy-Car                        | ncellieri et al.                 |  |  |
| Pap           | Title                               | Title Page                       |  |  |
| <u> </u>      | Abstract                            | Introduction                     |  |  |
| _             | Conclusions                         | References                       |  |  |
| )iscus        | Tables                              | Figures                          |  |  |
| sion F        | I                                   | ►1                               |  |  |
| Daper         | •                                   | Þ                                |  |  |
| _             | Back                                | Close                            |  |  |
|               | Full Screen / Esc                   |                                  |  |  |
| cussion       | Printer-friendly Version            |                                  |  |  |
| n Pa          | Interactive                         | Interactive Discussion           |  |  |
| per           | C                                   | <b>D</b><br>BY                   |  |  |



**Fig. 8.** As Fig. 6 but for the simulated passive tracer concentration. Observed smoke plume edge (red star), experimental (red circle) and simulated (black circle) barycenters are superimposed on the simulated passive tracer concentration vertical cross-sections.





**Fig. 9.** Vertical locations of experimental (red circle) and simulated (black circle) barycenters, red cross and green circle symbolized lidar burning site positions respectively.





Fig. 10. Experimental (red circle) and simulated (black circle) horizontal plume speeds.





Fig. 11. As Fig. 9 but for horizontal locations.

