Nat. Hazards Earth Syst. Sci. Discuss., 1, 855–894, 2013 www.nat-hazards-earth-syst-sci-discuss.net/1/855/2013/ doi:10.5194/nhessd-1-855-2013 © Author(s) 2013. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Natural Hazards and Earth System Sciences (NHESS). Please refer to the corresponding final paper in NHESS if available.

Wind shear over the Nice Côte d'Azur airport: case studies

A. Boilley^{1,2,*} and J.-F. Mahfouf¹

¹GAME/CNRM, (Météo-France/CNRS), UMR3589, 42, Av. G. Coriolis, 31057 Toulouse Cedex 1, France
 ²Degréane-Horizon, 730 rue de l'initiative, 83390 Cuers, France
 ^{*} now at: MINES ParisTech, O.I.E. – Observation Impacts Energy, CS 10207 06904 Sophia-Antipolis Cedex, France

Received: 22 January 2013 - Accepted: 11 March 2013 - Published: 2 April 2013

Correspondence to: J.-F. Mahfouf (jean-francois.mahfouf@meteo.fr)

Published by Copernicus Publications on behalf of the European Geosciences Union.





Abstract

The Nice Côte d'Azur international airport is subject to horizontal low-level wind shears. Detecting and predicting these hazards is a major concern for aircraft security. A measurement campaign took place over the Nice airport in 2009 including 4 anemometers,

⁵ 1 wind lidar and 1 wind profiler. Two wind shear events were observed during this measurement campaign. Numerical simulations were carried out with Meso-NH in a configuration compatible with near-real time applications to determine the ability of the numerical model to predict these events and to study the meteorological situations generating a horizontal wind shear. A comparison between numerical simulation and the observation dataset is conducted in this paper.

1 Introduction

15

Air transport growth over the long-term demonstrates a stable trend despite economic stagnation and is expected to increase after an upturn of the economy (Eurocontrol, 2010). In that context, any delay concerning a plane during take off or landing impacts all the airport traffic. Weather conditions account for 15% among all the causes of delay in Europe. Low-level wind shears (LLW) are hazardous events particularly in the vicinity of airports where airplanes fly close to the ground at low speed.

A LLW is defined in aeronautics as a wind direction and/or intensity change in space, updraft and downdraft included, that may cause a variation on the plane lift. In case of wind shear encounter during landing, aircrafts initiate a go-around procedure, fly back up to the circuit and prepare for landing once again. This manoeuvre disturbs the whole following approach organization in case of high traffic. Moreover, in case of horizontal wind shears crossing the runways, landing and take off directions are switched. Therefore LLW have important security and economic consequences.

²⁵ Several measurement campaigns (Wilson et al., 1984) and numerical simulations (Proctor, 1988) were carried out in the United States since the 80's and provided a





better comprehension of wind shears due to storms which are called microbursts (Fu-jita, 1986). The low-level wind shear advisory system (LLWAS, Soffer, 1990) is a consequence of the measurement campaigns. The initial system consisted in the analysis of the difference between the wind observed by a central anemometer and the wind
 ⁵ observed by one of five anemometers distributed around the airport. A 15 knots or greater difference triggered an alarm.

Since then, the LLWAS has been updated and can now count several ground and buoy anemometers, a wind lidar, several wind profilers. Since the development in the 90s of a wind shear dedicated radar, LLWAS can be combined with a Terminal Doppler Weather Radar (TDWR, Michelson et al., 1990), to detect wind shear events both on the runways and in altitude. Shun and Chan (2008) present such an updated system applied at the Chek Lap Kok Airport in Hong Kong, China.

10

15

Another system, initially based on the Hong Kong airport concept was developed for the Juneau, Alaska airport: the Juneau Airport Wind System. It relies upon a number of sensors (anemometers and wind profilers) installed on high peaks around the airport and on two aircraft wind measurement campaigns. Based on aircraft measurements, an estimation of turbulence has been computed. Then regression coefficients were

- defined to correlate the computed turbulence intensity with the profiler and anemometer measurements (Politovich et al., 2011).
- ²⁰ Over smaller airports where wind shear occurence is high but where the aforementionned systems cannot be installed because of the location of the airport or because of the cost, there is a need of an alternative. The Nice Côte d'Azur airport, located southeast of France, is the seat of horizontal wind shears mostly in winter. Between 10 and 20 events are observed each year according to aircraft pilots' reports. The relatively
- dense urban area surrounding the airport and the final approaches over the sea, limit the implementation of a complex wind shear detection system. Since the approach routes are located above sea as described in the next section, conventional observations do not provide information in this area. A wind lidar campaign (LIDAR2009) was established at the beginning of 2009 to obtain high frequency measurements





approximately 10 km around the lidar position. This measurement system has proven its ability to detect wind shears in clear-sky conditions as stated in Shun and Chan (2008).

Though a wind lidar can detect wind shears, the most interesting part for air traffic ⁵ management would be to predict them. For that reason, a method based on available observations and numerical simulations is considered for the Nice airport. Chan (2012) studies a wind shear event using both observational and numerical data and demonstrates that a numerical model could be able to predict the wind shear event.

The goal of this paper is to study two different horizontal wind shear events over the complex terrain of the Nice region and to determine the numerical model capability to predict these events compared to the observations. Moreover, the complementarity of numerical modelling and observations can provide information about the mechanisms generating a wind shear over the Nice airport. We conducted numerical simulations for two different wind shear situations that took place during LIDAR2009. The comparison presented in the following study determine the capability of the model to predict wind

shears. When the model was able to reasonably simulate the event, it has been used to highlight the key elements leading to the wind shear situation.

We first describe the Nice Côte d'Azur airport location and the instruments installed on the airport during the LIDAR2009 measurement campaign. Two wind shear events

have been selected. The meteorological situation for both events is given in Sect. 3. The numerical model Meso-NH (Lafore et al., 1998) as well as its setup and the diagnostics used in this study are described in the beginning of Sect. 4. The comparison and analysis of the numerical results towards observations are then studied in the following of the section.





2 Location and description of the LIDAR2009 measurement campaign

2.1 The Nice airport

10

The Nice Côte d'Azur International airport is the third busiest French airport by total passenger traffic. Each year 10 million passengers cross the gates of the airport whereas the theoretical maximum passenger traffic is 13 million. The airport is close to its limit. Due to the dense urban area surrounding the airport, no extensions are possible. A better LLW anticipation is one way to limit their impact on air traffic.

The airport is located south-east of France, seven kilometers west from downtown Nice. It has been built at the land/sea interface in a bay between two capes: the Ferrat cape (FC) to the east and the Antibes cape (AC) to the west. The airport runways are

- approximately 3.5 km long in the direction 44°/244°. The Var valley runs north-south and opens on to the west of the runways leading to frequent and well predicted vertical wind shear events. The Côte d'Azur is in the lee of the southern Alps where many peaks culminate well above 2500 m, generating discontinuous flow over the Nice airport.
- A special feature of the Nice airport is the approach routes imposed to aircrafts in clear-sky conditions. In case of easterly wind, good visibility and clouds bottom above 900 m a.g.l., airplanes have to go round the Antibes cape by south, then fly to the north and turn 90° to the east to get aligned with runways (dashed line in Fig. 1a). In westerly flow conditions, airplanes cannot take the direct approach because of the relief. They must come from the south-east and turn 90° to the west to get aligned (dotted line in Fig. 1a). Due to these specific conditions only 25% flights use the instrument landing

system (continuous line in Fig. 1a).

During "good weather" conditions, airplanes do a 90° bend at 200 m a.s.l. where LLW can have disastrous effects on airplane trajectory. Due to its location, the airport expe-²⁵ riences horizontal and vertical LLW. Most of vertical wind shears are due to mountain breezes in the Var valley. The north breezes spreading a relatively dense air at the mouth of the valley are perpendicular and divert the synoptic flow over the sea. Due to dense air it appears first in the lowest part of the atmosphere and is rapidly detected by





local forecasters. On the contrary, horizontal LLW causes are complex and depends on both synoptic and local condition. The following study describes two types of horizontal LLW generation.

2.2 LIDAR2009 campaign

- Several sensors are permanently installed on the airport platform (Fig. 1b). Three anemometers are installed at the east (D in Fig. 1b), center (C) and west (B) of the runways and measure the 10 m wind over the airport. The western anemometer is part of the worldwide surface synoptic network: SYNOP. A wind profiler is located at the mouth of the Var valley, 500 m north-east of the runways (A) and provides vertical wind profile
- time-series up to 5000 m. It is a PCL-1300 Degreane-Horizon wind profiler emitting a signal at 1274 MHz. Two different emission times are available leading to two different configurations: a high resolution mode providing data from 75 m to 2000 m a.g.l. every 75 m and a low resolution mode which provides data from 300 m to 5000 m a.g.l. every 150 m. The wind profiler can provide a profile every 2 min.
- ¹⁵ In the hazardous areas (west and east of the runways over sea) where aircrafts turn, no continuous measurement is made actually. In these conditions, local forecasters estimate that a 3 km wind measurement range is a minimum to detect hazards in the direct vicinity of the airport and in the runway axis. A wind lidar campaign (LIDAR2009) was set up for a three months period, from January to March 2009, on the Nice airport.
- A Lockheed Martin Doppler wind lidar (WindTracer[®]) was installed by Meteo-France near the eastern anemometer, letter B in Fig. 1b. It emits a near-infrared (2 μm wavelength) laser beam and computes wind speed from the Doppler shift of aerosol echoes. A laser beam has no secondary lobes improving the spatial resolution through high directivity. In case of low-level clouds or rain, however, the laser beam is strongly at-
- tenuated, which drastically reduces the maximal range. The WindTracer[®] geographical maximal scan area is represented by a gray circle in Fig. 1a. Horizontal scans and elevations can be hemispherical. Indeed, over the Nice airport the wind lidar measurement cycle is made of two hemispherical scans at 2 and 4° elevation followed by two





vertical scans from 2° to 10° elevation in the runway directions (44 and 224°) and a vertical scan from 1 to 10° elevation at 335° azimuth which corresponds to the Var valley direction.

A sonic anemometer was installed near the wind profiler during LIDAR2009. It is located in the Var valley direction (335°) in order to validate data from the lidar. A Météo-France internal report demonstrates the good agreement between lidar and anemometer measurements with a correlation above 0.9 for both sonic and standard anemometers with a difference on the altitude of 10 m. These results and those obtained by Shun and Chan (2008) demonstrate the reliability of the lidar to detect hazardous events close to airports on the aircraft route compared to meteorological ground stations. On 24 and on 27 March two wind shear events were observed by the lidar. The significant amount of data obtained during the LIDAR2009 campaign is supplemented by numerical simulations leading to a regional description of the meteorological phenomena.

3 Synoptic and observational situations

¹⁵ For each observed wind shear event the description of the meteorological situation is constructed from synoptic observation range to locally observed flow.

3.1 24 March 2009

20

25

On 24 March 2009 at 12:45 UTC, a rather unusual type of wind shear was observed over the Nice airport. It is particular since it occurs in cloudy conditions. Therefore, the Monaco heliport was closed during 1.5 h and severe turbulences were reported over the Nice bay by pilots.

The 500 hPa geopotential is represented as isolignes in Fig. 2 at 12:00 and 18:00 UTC, from the European Center for Medium-range Weather Forecasts (ECMWF) analysis. A talweg is present over north Italy. The north-westerly synoptic flow over France is influenced by the talweg and turns westerly over the Côte d'Azur. The talweg





position moves to the south-west during the next six hours and a northerly flow settles over the Côte d'Azur and north Italy.

As previously mentioned the event took place during cloudy conditions. The visible images observed by the SEVIRI sensor onboard Meteosat satellite show clouds all over the Genoa gulf to the French–Italian border at 12:30 UTC (Fig. 3a). A cloud front moves towards west and reaches the Nice region between 12:45 and 13:00 h (Fig. 3a). Its progression to the west is stopped at 14:30 UTC and then the clouds are advected to the south-east (not shown).

Vertical wind profile time-series (one profile every two minutes) obtained from the ¹⁰ wind profiler are presented in Fig. 4. It demonstrates the rapid wind change over the Nice airport in the first 5000 m from an easterly to a westerly wind. In Fig. 4b, the westerly wind is observed between 12:45 and 16:30. Afterwards another change in wind direction occurs and a south-easterly flow is observed in the lowest 400 m.

The rapid change coincides with an increasing signal to noise ratio (SNR) between 3000 m and 5000 m. A rapid increase in the SNR value is due to either a temperature drop or a humidity increase. Since clouds were observed from satellite, the SNR increase is likely related to the cloud front arrival over the Nice airport, generating a rise in humidity and a fall in temperature. A SNR increase is also observed in the lower part of the atmosphere (under 1000 m) revealing a change in air mass during the LLW.

The air mass change during the LLW in the lowest part of the atmosphere is confirmed by the ground station measurements. For example, the 2-m temperature and the 2-m relative humidity on the Nice airport are respectively 17.8 °C and 20 % at 12:00. Two hours later, once the cloud front has reached the Nice airport, the 2-m temperature has dropped down to 11.9 °C and the 2-m relative humidity has reached 50 % (not shown).

The wind lidar installed on the runways during the LIDAR2009 field campaign provided 360° horizontal scans of radial wind every 3 min approximately. The evolution of the local wind structure is well captured. Two scans are presented in Fig. 5 at 12:45 and at 13:00. At 12:45 the LLW is located at approximately 6 km of the wind lidar





location. 15 min later, a westerly wind blows over the entire airport and the easterly wind is pushed away to the west. The situation remains identical for the two next hours. Afterwards a continuous wind rotation from west to east by the south is observed.

- The wind direction change observed by the different sensors can be related to the talweg position. As long as the talweg is located over the Alps, all the northerly synoptic flow rounds the Alps and then is drained off to the west over the Mediterranean sea. When the talweg moves from the Alps to the Italian coast, a part of the synoptic flow can cross the Alps and reach the Pô valley. The meeting of both parts of the flow at the French–Italian border generates a cloud front observed by satellite. The continuous move of the talweg to the south forces the flow crossing the Alps to get an easterly
- ¹⁰ ous move of the falweg to the south forces the flow crossing the Alps to get an easterly direction along the coast when the talweg is located just above the Genoa gulf. This easterly flow is opposed to the westerly flow coming from the Rhône valley and generates a wind shear over the Mediterranean sea as presented in the conceptual scheme in Fig. 6a. This case will be called a "Crossing the Alps" case.

15 3.2 27 March 2009

On 27 March 2009, a horizontal wind shear was observed between 7:30 and 08:00 UTC by the lidar and induced a switch of the approach procedure directions by the air traffic control.

- A westerly wind blows all day long over western central Europe generated by a low geopotential region over northern Ireland and a high geopotential region over the Canary islands (Fig. 7). In the lower layer, the Massif Central (center of France) and the Alpine range split the westerly flow in two parts. The one rounding mountains by the south, reinforced by the wind blowing out of the Rhône valley, is at the origin of the wind shear. It reaches the Mediterranean sea and blows along the French coast to the Italian border. The shape of the extreme south of the Alps and of the Genoa gulf conduct
- to a lee vortex in the Genoa gulf similar to the lee vortices simulated in Ólafsson and Bougeault (1996) past an elliptic mountain ridge. The vortex is initially contained in the Genoa gulf. The synoptic westerly wind reinforcement after sunrise induces a growth





of the vortex. Its extent reaches the Nice airport where a horizontal LLW is observed at 07:45 UTC. This case will be called "vortex case" in the following and a conceptual scheme of this event is presented in Fig. 6b.

Vertically, the wind flow over the Nice airport can be separated in two parts clearly visible on the vertical wind profiles given by the AMDAR message at 08:37 presented in Fig. 8. Above 500 m, the strong westerly wind flow is relatively constant all day long. Under this altitude the flow is varying. For example, at the time of the AMDAR message, the LLW had already happened on the Nice airport and only the first 500 m of the atmosphere were concerned.

The SYNOP network provides a regional point of vue of the 10-m wind. A westerly wind has been observed all day long by the stations located at the extreme south of the Alpine range (Toulon region cf. Figure 6b) whereas the stations in the lee of the Alps demonstrate a perturbed wind. Indeed, a northerly wind, typical of valley breezes, is observed by most French coastal and valley stations in the early morning. In one hour, between 07:00 and 08:00, the wind direction changes from a northerly to an

easterly wind for all the coastal stations whereas northern inland stations still observe an easterly 10 m wind. The wind direction is only observed in the boundary layer in the coastal area.

The 2-m temperature is also rapidly and simultaneously changing during this event. It ranges between 6 and 10 °C before 07:00 all along the coast. After sunrise, the temperature goes up and reaches 11.8 °C at the Nice airport at 10:00. At the same time, the observed 2-m temperature at the extreme south of the Alps is 22 °C. This temperature difference remains constant until the end of the day, showing two contrasted air masses. A cold air mass associated with an easterly wind settles along the Côte d'Azur

²⁵ coast and a warm air mass associated with a westerly wind is present away from the coast. It can be noticed that the wind direction in the warm air mass is similar to the synoptic flow in altitude.

According to the previous statements and in absence of observations over the sea, we speculate that in the early morning the valley breezes drain a cold air to the sea





which is advected by the westerly wind to the Genoa gulf. The accumulated cold air combined with the shape of the Alps and the Appenines range generate a stable low level air mass as high as the mean Appenines (approx. 500 m). In these conditions, the synoptic westerly wind needs to circle around this stable area leading to the rotation

⁵ of the cold air mass in the Genoa gulf. The enhancement of the westerly wind in the morning induces a blocking of the cold air against the Alps. It increases its horizontal extent to the Nice airport and the associated easterly wind along the coast. This configuration explains the observed difference in 2-m temperature.

Over the Nice airport, the four anemometers associated with the high frequency vertical and horizontal wind lidar scans confirm the previously described morning flow above the Nice airport and show a more complex local flow than a single rapid wind change.

In the morning, the three western anemometers record a northerly wind due to the valley breeze (Fig. 9). The eastern anemometer time-series exhibit a weak north-¹⁵ westerly wind as the breeze is influenced by the westerly low level wind blowing over the sea. The valley breeze wind direction is already modified 2 km away from the Var valley mouth (distance separating the central and eastern anemometers). At 08:00 UTC, the wind speed decreases to less than 0.5 ms^{-1} over the entire airport platform. A first wind direction change from north to south-east occurs in 15 min. The wind speed and direction remain stable until 09:30 when a second wind shear happens. From that time, the wind blows from the east and the intensity increases rapidly: approx. 4 ms^{-1} in 1 h. The sonic anemometer constantly overestimates the wind speed (Fig. 9). The same overestimation is made with the time-series for 24 March LLW event. Between 08:30 and 09:30 a transitional period is noticed and the high temporal fre-

quency lidar scans provide supplementary information. On the 2° elevation scan presented in Fig. 10a the south-easterly flow is established on the airport whereas 5 km to the south (corresponding to an altitude of 170 m a.m.s.l.) a westerly flow is observed. These distance and altitude are similar to the distance between the airport and the extreme south of the Antibes cape and the highest altitude of the Ferrat cape. The





wind observed on the airport in the lower layer of the atmosphere is a local wind circulation in the lee of the Antibes cape. This local "whirlwind" responsible for the first wind direction change is observed when the valley breeze ends. It remains unchanged until the eastern wind blows away this local effect at 09:30. At this time (Fig. 10b), the

- south-easterly wind is still observed on the airport platform but an easterly wind (blue part north of the blind zone) appears. This easterly wind corresponds to the Genoa gulf vortex. It blocks the westerly flow observed over the sea at 08:30 as observed on the lidar scan and propagates towards the west generating the second wind direction change between 09:30 and 10:00.
- The LLW vortex case observed on the 27th starts with the advection of a cold air mass over the sea due to local valley breezes. The cold air is then advected to the Genoa gulf where it accumulates in the boundary layer. This stable air mass deviates the westerly synoptic flow and starts spinning generating a local vortex which extends in the next hours. In the mean time, a smaller vortex is generated in the Nice bay sparking off a local wind flow.

4 Numerical modeling

20

In this section comparisons between available observations and numerical simulations are carried out. The ability of the model to simulate LLW is evaluated for both previously described hazardous events against the measurement dataset. The gridded information from a meteorological model is useful to complement the observational network in order to provide a consistent picture of the event. A better understanding of the meteorological conditions leading to wind shear events in the complex orography of the Nice Côte d'Azur airport region is a first step towards improved numerical forecasts.





4.1 Numerical model setup

The numerical simulations are performed with the non-hydrostatic Meso-NH model (Lafore et al., 1998) which is based on the anelastic approximation with purely explicit second order accurate spatial and temporal discretizations. The prognostic variables
⁵ are the three wind components, dry potential temperature, the mixing ratio of six different classes of water, and turbulent kinetic energy. The model contains a comprehensive set of physical parametrization schemes to describe sub-grid scale processes. The terrain-following vertical coordinate is based on the Gal-Chen and Sommerville (1975) parameterization. The SURFEX model is an externalized surface model run in parallel with Meso-NH. It contains several schemes to model fluxes over different surface types such as water surface (Belamari, 2005), urban areas (Masson, 2000) or vegetation (Noilhan and Planton, 1989).

Turbulence equations for both simulations are closed using a 1.5 order scheme resolving only vertical exchanges with the Bougeault and Lacarrère (1989) mixing length

formulation. The ECMWF radiation code is implemented in Meso-NH. It uses the RRTM scheme (Mlawer et al., 1997) for long-wave and the scheme described by Fouquart and Bonnel (1980) for short-wave radiation. Since clouds were observed during one LLW event a complete 6-classes, one-moment Bulk microphysics scheme is used (ICE3; Pinty and Jabouille, 1998). These radiation schemes are the same than those in the operational AROME model (Seity et al., 2011) to be in a configuration that could be set-up for near real-time applications.

The simulation grid domain is presented in Fig. 11. The horizontal resolution is 2.5 km, the domain contains 540 × 480 points horizontally and 60 vertical levels from 10 m to 36 km high including 23 levels below 2000 m. The orography is obtained from the GTOPO30 database which has a 30" of arc angle resolution, i.e. approximately 1 km. Simulations start from the LLW closest analysis time. Initial conditions are obtained from operational analyses of the AROME model at 2.5 km resolution. Each simulation experiment lasts 6 h. The simulations are coupled with hourly forecasts from





the coarser scale (9.5 km) limited area model ALADIN (Bubnova et al., 1995) run over a wider domain. ALADIN includes a 3-D-Var data assimilation system (Fischer et al., 2005). Outputs from Meso-NH are written every 0.5 h. These are the best physical and dynamical configurations of a numerical model that could be made available in real time

to forecasters for issuing warnings over the Nice airport. A 500 m nested domain centered on the airport (360 × 200 points) was also run but did not lead to improvements on LLW simulation compared to the 2.5 km resolution grid. Results from this domain are not presented in the following.

Meso-NH includes a set of diagnostics providing for example, lagrangian tracers,
 chemical and aerosol variables, aircraft or balloon trajectories, radar and lidar simulator. In the following the lidar simulator is used to compare numerical simulations to wind lidar observations. The simulator is based on the radar simulator (Caumont et al., 2006) in which the secondary lobes effect is not taken into account and the range is reduced due to laser wavelength. Output resolution may be increased to obtain a similar
 resolution to the observations. Simulated lidar scans in the following study have a 1 km horizontal resolution and are obtained from 2.5 km resolution simulations outputs.

4.2 24 March 2009

The numerical simulation for 24 March starts at 12:00 UTC using an AROME analysis. In the meteorological situation description the importance of a talweg location
 was demonstrated. The position of this talweg is not well reproduced in the numerical model. Indeed, it has moved too far east and too rapidly in the simulation. On the contrary it does not move enough to the south. At the end of the simulation, the local minimum located north of Corsica in the ECMWF analysis (cf. Fig. 2) is located over north Italy in the numerical simulation (not shown). Consequently, the streamline cur vature simulated by Meso-NH is less pronounced at 18:00 UTC in the Genoa gulf than

in the re-analysis as presented in Fig. 12. Therefore, the flow that crosses the Alps is not enough constrained to the west and may not reach Nice close to the ground. Only when the local minimum is located over Genoa in the simulation, the flow distorsion





gets strong enough to generate a LLW over the Nice airport. But the rapid displacement to the east leads to a rapid disappearence of the curvature.

The cloud cover was found to be a useful tracer of the wind shear position in the meteorological description part. Both infrared (10.8 μ m) Meteosat images and their

simulated equivalent are presented in Fig. 13. The simulated cloud cover is underestimated overall in the simulation domain and particularly over the Alps. Indeed, after 1 h of simulation, no clouds are simulated in the Nice area whereas the cloud front already reaches Nice in the Meteosat images. After 2.5 h of simulation, the cloud front reaches the airport. Afterward, observation and simulation move similarly the clouds towards the sea.

The lack of clouds in the numerical simulation induces a less pronounced air mass contrast in the lower layer over the coast. The 2-m temperature and relative humidity change observed is not as pronounced in the simulation result. The cold and humid air mass is shifted to the south over the sea and does not stay close to the coast. This position is related to the talweg east displacement which does not constraint the flux to

position is related to the talweg east displacement which does not constraint the flux to go to the west along the coast. The Italian side of the Alpin range acts as an obstacle for the cold and humid front which does not reach the Nice airport without the additional constraint of the talweg.

As a consequence of those misrepresentations the LLW occurs 2 h late over the Nice airport as presented on the simulated 10 m wind time-series (Fig. 14). The LLW is simulated at 14:45 whereas all four anemometers record a rapid wind change at 12:45. However, the simulated time-series of the wind direction before and after the LLW is similar to the observed wind direction. The general meteorological circulation is well simulated but the bad location of the talweg generates a shift in space and time of the

LLW. The simulated wind speed is overestimated all day long. It is similar to the synoptic wind observed in the Toulon region. Once again, this can be related to the weaker constraint imposed by the talweg: the westerly synoptic flow is established further east than in the observation. The time variation is however similar to the observed wind





speed. The low wind speed at 14:30 is not simulated long enough due to the rapid displacement of the talweg to the east in the simulation as described previously.

The general circulation is similar and the cause of the forecasted LLW is the same as that of the observed LLW. Therefore, the simulated wind structure near the airport area,

- ⁵ but shifted 2 h before, can be compared to the lidar scans. Figure 15 exhibits a wind lidar scan at 13:00 at 4° elevation and its 2 h later simulated equivalent (15:00) at 1 km resolution. The wind structure is clearly similar with an easterly wind pushing away the previously installed westerly wind. There is a slight difference in the wind direction for the easterly wind: it comes from the east in the simulation whereas it comes from the north-east on the lidar scan. This difference is coherent with the misplacement of the
 - cold and humid cloud front position in the simulation.

The 24 March 2009 LLW case described as a "crossing the Alps" case is related to a talweg location. The mesoscale simulation introduces a bias in the talweg position during the simulation. It leads to 2 h late LLW prediction, overestimation of the wind speed and an underestimation of the cloud cover. However, the wind structure is similar

to the structure observed by the wind lidar over the Nice airport.

In that case, the use of a high resolution numerical model can warn the air traffic management about the possible occurrence of a LLW over the airport. However the time and duration of the hazard can not be provided. It could be profitable in that case

to assimilate local high resolution data (wind lidar for example) and/or high temporal frequency data (wind profiler) to study the impact on the LLW position.

4.3 27 March 2009

25

The numerical simulation of the 27 March 2009 LLW event is initialized at 06:00 UTC with an AROME analysis. It is coupled hourly with ALADIN forecasts and runs until 12:00. In that case, the LLW should occur 1.5 h after starting the simulation.

The streamlines at the nearest model level from 500 hPa in Meso-NH are similar to the geopotential presented in the meteorological description (Fig. 7) and are maintained all along the simulation. The geopotential gradient is strong over the





Mediterranean sea, south of France, inducing a strong wind over this area. In the boundary layer this strong wind is channeled and even more reinforced between the Massif Central and the Pyrenean range (not shown). The general circulation is very similar to the ECMWF analysis.

⁵ On the vertical direction, the comparison between the simulation and the wind profiler (not shown) and the AMDAR reports (Fig. 8) shows an underestimation of the vertical extension of the LLW layer as well as an overestimation of the wind speed at all altitudes even in the lower layer.

The same conclusion arises when examining the 10-m wind time-series over the Nice airport presented in Fig. 9. The wind intensity is slightly overestimated, particularly, during the hour following the LLW. This hour corresponds to the transition period when a vortex takes place locally in the lee of the Antibes cape. However, during this hour and until the end of the simulation period, the wind direction fits the observations even during the second wind direction change at 10:00 UTC. The wind direction is very well simulated but the wind speed is constantly overestimated even at 10 m.

At the beginning of the simulation period, the simulated 10-m wind direction is more perturbed than the observed wind direction. It is fluctuating in the range of the observed direction and 45 min previous to the LLW the numerical model anticipated the wind direction changes, varying from west to north. Both the overestimation of the wind speed and the difference in wind direction can be explained by the fact that the chosen grid point (the nearest) in the numerical simulation is ten meters south of the airport,

20

- above the sea. The nearest point above land was located in the Var valley and was even more perturbed by the complex orography. The wind over the sea is slighty stronger than over land due to lower surface roughness values. The Var valley breeze extension
- reaches the point at the beginning of the simulation, then a wind similar to the wind observed to the east is simulated at 07:30. The LLW seems to be anticipated during the low intensity period when the valley breeze regains in extension and a northerly wind is simulated at this point.





The LLW is simulated a quarter of an hour later than observed but a change of 120° occurs in 5 min in the simulation whereas it takes 15 min to the observed wind direction to change similarly. For that reason, observed and simulated winds fit very rapidly after the LLW.

In the same way, the 2-m temperature is well represented (not shown). Both the magnitude and the position of the 2-m temperature gradient in the Nice area are well captured by the numerical simulation during the entire simulation compared to the ground measurement station network. Since the temperature gradient is related to the position of the LLW as presented in the case description, it confirms that the regional structure of the LLW is well simulated.

At 09:30 a second wind direction change occurs over the Nice airport as shown on the time-series (Fig. 14). Figure 16 presents the wind lidar scans at 2° of elevation at 09:30 and 10:00 UTC as well as the equivalent simulated scans. The simulation reproduces the wind structure in a satisfactory way. There is a time lag at the beginning of

the second LLW. Indeed, as seen previously, the wind speed is stronger in the simulation than measured by the anemometer measurements and the 09:30 simulated scan is similar to the observed one at 10:00. The local wind direction and speed are well simulated but the wind structure is anticipated in the simulation.

The advantage of a numerical simulation is the large amount of regional information available. Vertical cross-sections of vertical velocity and potential temperature are presented in Fig. 17. The vertical wind component at 08:00 and 10:00 is presented in the left column and the temperature superimposed on the wind intensity in the right column. Waves are present in the lee of the mountains, above the Nice airport from the beginning of the simulation. These waves intensify once at 08:00 and strengthen a

second time at 10:00. At that time the wind oscillations appear upwind of the mountains compared to the waves at 08:00. The vertical component oscillation is coupled with a similar oscillation of potential temperature in the lower layer above the mountains. The strong vertical wind component in the lee of the mountain seems to be maintained in altitude even more after the reinforcement at 10:00. The oscillations are probably





absorbed by the cold air mass as stated in Jiang et al. (2006) and as a counterpart they press the cold air to the ground. The cold air mass in the boundary layer acts as a shield preventing the synoptic wind to reach the Nice airport and it maintains the easterly wind. The same kind of cold pool and waves in the lee of the mountains were observed on another similar LLW event over Nice in 2005.

5 Conclusions

5

10

25

This paper is a preliminary study of two different horizontal LLW events taking place over the Nice airport. This airport is mostly concerned with horizontal wind shears and no dedicated systems are installed on the runways. In 2009 a wind lidar campaign took place on the Nice airport providing a very useful and complete dataset. We carried numerical simulations for two particular LLW events in the best configuration that could be obtained in near real time to test the ability of the numerical model to predict these hazardous events. The simulations were carried at high resolution (2.5 km) on a domain covering the overall France to reproduce the synoptic situation. A higher resolution

(500 m) nested domain was also run over the airport area but did not provide real improvements on the LLW timing and position compared to the 2.5 km domain presented in this paper. Indeed, the LLW events were related to local and synoptic meteorological conditions and the 500 m domain was mainly driven by boundary conditions from the 2.5 km resolution domain. However orographic effects (i.e. valley breezes, hill effects)
 were greatly improved and could lead to a better prediction of vertical wind shears or local turbulences.

In the first case, called "crossing the Alps", the LLW was due to large scale conditions. The LLW was not predicted at the right place and time due to the misrepresentation of these conditions. In that case one way to improve the LLW position would be to constrain the simulation more regularly towards large scale conditions through analysis nudging at each time step for example.





For the second LLW event ("vortex case"), the LLW generation is more related to regional effect (orography, breezes, ...). The model successfully anticipates 1.5 h before the wind direction and intensity change. For that reason it has been used to complement measurements. Waves were observed in the lee of the southern part of the Alps.

⁵ During another LLW event over the Nice airport, more intense wave structures were simulated and the LLW was more rapid.

A stable lower layer in the Genoa gulf and a strong synoptic wind are mandatory to generate a LLW over the Nice area in both cases. The Froude number upwind of the Alps in both LLW events was found close to 1. These three caracteristics have to be present for a LLW to occur over the Nice airport.

10

15

To further improve the timing, position and structure prediction of the LLW event, local measurements at high frequency and resolution could be assimilated in the model. To take into account the rapidly changing wind field observed by a wind lidar as many scans as possible should be assimilated. For this purpose an enhanced nudging technique (Back and Forth Nudging, Auroux and Blum, 2005) was developed into Meso-NH (Boilley and Mahfouf, 2012).

To predict wind shears over the Nice airport, a combination of numerical predictions and observations is necessary. Numerical models are able to predict and generate a warning about LLW appearence in the next 6 h. However, the time and position of the wind abange are net well centured and must be complemented by level measuremente

wind change are not well captured and must be complemented by local measurements to keep watch on the position of the LLW. More upwind sensors could also be installed to further anticipate the arrival of a wind shear on the Nice airport area.

Acknowledgements. We would like to acknowledge all the Meso-NH team for their help on numerical setup and particularly Olivier Caumont for developing the wind lidar simulator. We acknowledge Eric Schwartz for sharing his experience, data and sense of humour about these

acknowledge Eric Schwartz for sharing his experience, data and sense of humour about these local "wind reversal" events. Thanks to Lucien Wald who spent time reading this paper with a critical eye.







The publication of this article is financed by CNRS-INSU.

References

5

10

Auroux, D. and Blum, J.: Back and forth nudging algorithm for data assimilation problems, C. R. Acad. Sci. Ser. I, 340, 873–878, 2005. 874

- Belamari, S.: Report on uncertainty estimates of an optimal bulk formulation for surface turbulent fluxes, Technical report, MERSEA-IP deliverable D4.1.2, 29, 2005. 867
- Boilley, A. and Mahfouf, J.-F.: Assimilation of low-level wind in a high-resolution mesoscale model using the back and forth nudging algorithm, Tellus A, 64, doi:10.3402/tellusa.v64i0.18697, 2012. 874
- Bougeault, P. and Lacarrère, P.: Parametrization of orographic induced turbulence in a mesobeta scale model, Mon. Weather Rev., 117, 1872–1890, 1989. 867
- Bubnova, R., Hello, G., Bernard, P., and Geleyn, J.-F.: Integration of the fully elastic equations cast in the hydrostatic-pressure terrain-following coordinate in the framework of the
- ARPEGE/ALADIN NWP system, Mon. Weather Rev., 123, 515–535, 1995. 868 Caumont, O., Ducrocq, V., Delrieu, G., Gosset, M., Pinty, J.-P., du Chatelet, J. P., Andrieu, H., Lemaitre, Y., and Scialom, G.: A radar simulator for high-resolution nonhydrostatic models, J. Atmos. Ocean. Technol., 23, 1049–1067, 2006. 868

Chan, P. W.: An event of tail strike of an aircraft due to terrain-induced wind shear at the Hong

Kong International Airport, Meteor. Appl., 19, 325–333, doi:10.1002/met.264, 2012. 858 Eurocontrol: Long term forecast: IFR Flight Movement 2010–2030, Eurocontrol report CND/STATFOR Doc415, 2010. 856

Fischer, C., Montmerle, T., Berre, L., Auger, L., and Stefanescu, S. E.: An overview of the variational assimilation in the ALADIN/France numerical weather-prediction system, Q. J.

²⁵ Roy. Meteorol. Soc., 131, 3477–3492, 2005. 868





Abstract Introduction Conclusions References **Tables Figures** ◄ Back Close Full Screen / Esc **Printer-friendly Version** Interactive Discussion

- Fouquart, Y. and Bonnel, B.: Computations of solar heating of the earth's atmosphere: a new parameterization, Beitr. Phys. Atmosph., 53, 35–62, 1980. 867
- Fujita, T.: The Downburst: Microburst and Macroburst, University of Chicago Press, 1986. 857 Gal-Chen, T. and Sommerville, C. J.: On the use of a coordinate transformation for the solution of the Navier–Stokes equation, J. Comput. Phys., 17, 209–228, 1975. 867
- of the Navier–Stokes equation, J. Comput. Phys., 17, 209–228, 1975. 867
 Jiang, Q., Doyle, J. D., and Smith, R. B.: Interaction between trapped waves and boundary layers, J. Atmos. Sci., 63, 617–633, 2006. 873
 - Lafore, J. P., Stein, J., Asencio, N., Bougeault, P., Ducrocq, V., Duron, J., Fischer, C., Héreil, P., Mascart, P., Masson, V., Pinty, J. P., Redelsperger, J. L., Richard, E., and Vilà-Guerau de Arel-
- Iano, J.: The Meso-NH Atmospheric Simulation System. Part I: adiabatic formulation and control simulations, Ann. Geophys., 16, 90–109, doi:10.1007/s00585-997-0090-6, 1998. 858, 867

Masson, V.: A physically-based scheme for the urban energy budget in atmospheric models, Bound.-Lay. Meteorol., 94, 357–397, 2000. 867

- ¹⁵ Michelson, M., Shrader, W., and Wieler, J.: Terminal doppler weather radar, Microwave J., 33, 139–148, 1990. 857
 - Mlawer, E. J., Taubman, S. J., Brown, P., Iacono, M., and Clough, S.: Radiative transfer for inhomogeneous atmospheres: RRTM, a validated correlated-k model for the longwave, J. Geophys. Res., 102, 16663–16682, 1997. 867
- Noilhan, J. and Planton, S.: A simple parameterization of land surface process for meteorological models, Mon. Weather Rev., 117, 536–549, 1989. 867
 - Olafsson, H. and Bougeault, P.: Nonlinear flow past an elliptic mountain ridge, J. Atmos. Sci., 53, 2465–2489, 1996. 863

Pinty, J.-P. and Jabouille, P.: A mixed-phase cloud parameterization for use in mesoscale non-

- hydrostatic model: simulations of a squall line and of orographic precipitations, in: 14th Conference on Planned and Inadvertent Weather Modification, Everett, WA, 1998. 867
 - Politovich, M., Goodrich, R. K., Morse, C. S., Yates, A., Barron, R., and Cohn, S.: The Juneau terrain-induced turbulence alert system, B. Am. Meteorol. Soc., 92, 299–313, 2011. 857
 Proctor, F.: Numerical simulations of an isolated microburst, Part 1: Dynamics and structure, J.
- ³⁰ Atmos. Sci., 45, 3137–3160, 1988. 856
 - Seity, Y., Brousseau, P., Malardel, S., Hello, G., Bénard, P., Bouttier, F., Lac, C., and Masson, V.: The AROME-France convective scale operational model, Mon. Weather Rev., 139, 976–991, 2011. 867

876



NHESSD

1,855-894,2013

Wind shear over the

Nice Côte d'Azur

airport

A. Boilley and

J.-F. Mahfouf

Title Page

Pape

Discussion Pape

Discussion Paper

Discussion Pape

- Shun, C. M. and Chan, P. W.: Applications of an infrared doppler lidar in detection of wind shear, J. Atmos. Ocean. Technol., 25, 637–655, 2008. 857, 858, 861
- Soffer, E. P.: Establishment criteria for integrated wind shear detection systems: low-level wind shear alert system (LLWAS), terminal doppler weather radar (TDWR), and modified airport
- surveillance radar, US Department of Transportation, Federal Aviation Administration, Office of Aviation Policy and Plans FAA-APO-90-13, 1990. 857
 - Wilson, J. W., Roberts, R. D., Kessinger, C., and McCarthy, J.: Microburst wind structure and evaluation of Doppler radar for airport wind shear detection, J. Clim. Appl. Meteorol., 23, 898–915, 1984. 856







Fig. 1. Location of the Nice airport on the Shuttle Radar Topography Mission (SRTM) map of the Nice region and airplane routes represented as arrows **(a)**. Approach routes of the airplanes are: direct (continuous line), in easterly wind and good visibility condition (dashed line) and in westerly wind conditions (dotted line). The black and shaded circle represents the scan area of the wind lidar. **(b)** Zoom on the Nice airport SRTM topography and sensor location during the LIDAR2009 measurement campaign. The letters correspond to the different sensors: ultrasonic anemometer and wind profiler (A), west anemometer and wind lidar (B), central anemometer (C), east anemometer (D).







Discussion Pa	NHESSD 1, 855–894, 2013			
tper Di	Wind she Nice Cô air	Wind shear over the Nice Côte d'Azur airport A. Boilley and JF. Mahfouf		
scussion P	A. Boil JF. N			
aper	Title Page			
—	Abstract	Introduction		
Discu	Conclusions	References		
Ission	Tables	Figures		
Pape	14	►I		
Pr.	•	•		
	Back	Close		
iscuss	Full Screen / Esc			
ion P	Printer-frie	Printer-friendly Version		
aper	Interactive Discussion			





Fig. 3. Visible images from SEVIRI onboard Meteosat satellite for 24 March 2009 at 12:30 UTC **(a)** and 13:00 h UTC **(b)**.

Diecueeion Da	NHE 1, 855–4	NHESSD 1, 855–894, 2013 Wind shear over the Nice Côte d'Azur airport A. Boilley and JF. Mahfouf		
nor I Di	Wind she Nice Cô air			
	A. Boi JF. N			
Dunor	Title	Title Page		
_	Abstract	Introduction		
	Conclusions	References		
	Tables	Figures		
Dung	14	►I.		
n n	•	•		
5	Back	Close		
00100	Full Scr	Full Screen / Esc		
200	Printer-frie	Printer-friendly Version		
DDDr	Interactive Discussion			













Fig. 5. 4° elevation wind lidar scans at 12:45 **(a)** and 13:00 UTC **(b)** on 24 March. Warm colors mean a radial wind going away from the lidar contrary to cold colors which represent a wind coming to the lidar. Arrows indicate a wind direction interpretation.







Fig. 6. Conceptual scheme of the "Alps crossing" case (a) and "vortex case" (b). Plain arrows represents the winds above the boundary layer, dashed and pointed arrows are winds in the boundary layer.

Discussion Pa	NHE 1, 855–8	SSD 394, 2013	
per Discussion	Wind shear over the Nice Côte d'Azur airport A. Boilley and JF. Mahfouf		
Paper	Title Page		
—	Abstract	Introduction	
Disc	Conclusions	References	
ussion	Tables	Figures	
Pap	14	►I	
θr	•	×.	
Discussi	Back	Close	
	Full Screen / Esc		
on P	Printer-friendly Version		
aper	Interactive Discussion		





Fig. 7. 500 hPa geopotential over Europe obtained from ECMWF analysis at 06:00 UTC on 27 March 2009.





Fig. 8. Graphical representation of the AMDAR message recorded at 08:37 on 27 March at the Nice airport. The "+" are the geographical position of the plane and the altitude and time of observation are given by red and blue values respectively. The simulated and observed wind barbs on the left correspond to the wind at each "+" point.





Discussion Paper



Fig. 9. Wind intensity **(a)** and wind direction **(b)** observed (colored +) by the four anemometers installed on the runways during the LIDAR2009 experiment and simulated (black dots) over the Nice airport for 27 March 2009.













Fig. 11. Simulation grid domain and name of locations of interest.







(cc

Printer-friendly Version

Interactive Discussion



Fig. 13. 10.8 μ m infrared brightness temperature observed by SEVIRI onboard Meteosat satellite and simulated by Meso-NH at 2.5 km resolution computed using the radiative transfer model RTTOV at 13:00 (a) and 14:30 UTC (b).







Fig. 14. Time series each minute of 10 m wind intensity (a) and direction (b) between 12 h and 18 h on 24 March 2009 observed by the four airport anemometers and simulated by Meso-NH.







Fig. 15. Radial wind intensity: lidar scan at 13:00 UTC (a), equivalent Meso-NH simulated scan at 15:00 UTC (b).







Fig. 16. Lidar scans at 2° at 09:20 (a) and 10:00 (b) on 27 March 2009 and Meso-NH simulated equivalent at 09:30 (c) and 10:00 (d)











