Nat. Hazards Earth Syst. Sci. Discuss., 2, 2639–2680, 2014
www.nat-hazards-earth-syst-sci-discuss.net/2/2639/2014/
doi:10.5194/nhessd-2-2639-2014

Natural Hazards and Earth System Sciences
Open Access
Discussions

Modelling soil erosion at European scale: towards harmonization and reproducibility

C. Bosco[1,2], D. de Rigo[2,3], O. Dewitte[4], J. Poesen[5], and P. Panagos[2]

[1]Loughborough University, Department of Civil and Building Engineering, Loughborough LE11 3TU, UK
[2]Joint Research Centre of the European Commission, Institute for Environment and Sustainability, Via Fermi, 2749, 21027 Ispra, Italy
[3]Politecnico di Milano, Dipartimento di Elettronica, Informazione e Bioingegneria, Via Ponzio 34/5, 20133 Milano, Italy
[4]Royal Museum for Central Africa, Department of Earth Sciences, Leuvensesteenweg 13, 3080 Tervuren, Belgium
[5]KU Leuven, Department of Earth and Environmental Sciences, Celestijnenlaan 200 E, 3001 Leuven, Belgium

Received: 22 November 2013 – Accepted: 23 February 2014 – Published: 11 April 2014

Correspondence to: C. Bosco (c.bosco@lboro.ac.uk)

Published by Copernicus Publications on behalf of the European Geosciences Union.

Abstract

Soil erosion by water is one of the most widespread forms of soil degradation. The loss of soil as a result of erosion can lead to decline in organic matter and nutrient contents, breakdown of soil structure and reduction of the water holding capacity. Measuring soil loss across the whole landscape is impractical and thus research is needed to improve methods of estimating soil erosion with computational modelling, upon which integrated assessment and mitigation strategies may be based. Despite the efforts, the prediction value of existing models is still limited, especially at regional and continental scale. A new approach for modelling soil erosion at large spatial scale is here proposed. It is based on the joint use of low data demanding models and innovative techniques for better estimating model inputs. The proposed modelling architecture has at its basis the semantic array programming paradigm and a strong effort towards computational reproducibility. An extended version of the Revised Universal Soil Loss Equation (RUSLE) has been implemented merging different empirical rainfall-erosivity equations within a climatic ensemble model and adding a new factor for a better consideration of soil stoniness within the model. Pan-European soil erosion rates by water have been estimated through the use of publicly available datasets and locally reliable empirical relationships. The accuracy of the results is corroborated by a visual plausibility check (63 % of a random sample of grid cells are accurate, 83 % at least moderately accurate, bootstrap $p \leq 0.05$). A comparison with country level statistics of pre-existing European maps of soil erosion by water is also provided.

1 Introduction

Soil erosion by rainfall and runoff is one of the main soil threats in Europe (Boardman and Poesen, 2006). Soil erosion costs a surprisingly large amount (Pimentel et al., 1995; Crosson, 1995; Telles et al., 2011; García-Ruiz, 2010). In many regions soil

NHESSD

2, 2639–2680, 2014

erosion affects soil quality reducing soil nutrients content with a consequent increase in food production costs (Pimentel, 2006; Lal, 1998).

The loss in productivity may be significant; the upper part of the soil, which is the most fertile layer, is also the most prone to erosion. Recent research also showed that nutrient and carbon cycling are significantly altered by mobilization and deposition of soil (Quinton et al., 2010). An eroded soil may lose 75–80 % of its carbon content, with consequent release of carbon to the atmosphere (Morgan, 2005). Soil erosion is linked to several natural hazards (Markantonis et al., 2012). It can also cause water pollution and siltation, loss of organic matter and reduction in water holding capacity (Boardman and Poesen, 2006). The protection of soil resources has therefore been recognized as an important objective of environmental policy (CEC, 2006): this requires a correct assessment of erosion rates and their geographical distribution.

It is impractical to measure soil loss across whole landscapes. Therefore, research is needed to improve methods for estimating soil erosion rates using modelling approaches, upon which mitigation strategies can be assessed and implemented.

Several models exist to predict soil erosion rates by water. These models differ greatly in terms of complexity, inputs, spatial and temporal scale. Heterogeneity of the models also affects the processes they represent, the manner in which these processes are represented and the types of output information they provide (de Vente et al., 2013). Many efforts have been made to describe soil erosion processes within models so as to achieve a better predictability and a more effective identification of the involved parameters.

Although models for assessing erosion on large areas have been developed (e.g. Gobin et al., 2004; Kirkby et al., 2008), required input data with sufficient accuracy may not always be available for large spatial extents (Jones et al., 2003) and applications outside the spatial domain in which erosion models have been tested could be problematic (Favis-Mortlock, 1998). It is recognized that the data needed to drive these models are scarce or do not exist even for the less demanding empirical models, if applied at regional scale. There is thus a need to integrate already available research

NHESSD
2, 2639–2680, 2014

methods with new generalization and integration techniques for better predicting the rate and extent of soil erosion at wider scales.

This paper presents an improved approach for modelling soil erosion at regional scale. The semantic array programming paradigm (de Rigo, 2012a, b) has recently been applied in integrated environmental modelling to support scalable generalisation techniques (Bosco et al., 2013; Estreguil et al., 2014). This paradigm and a strong effort toward computational reproducibility (Bosco et al., 2014, 2011b) are at the basis of the proposed modelling architecture. An extended version of the Revised Universal Soil Loss Equation (RUSLE), (Renard et al., 1997) will be implemented. The model is applied to predict soil erosion rates by water in Europe by exclusively relying on publicly available wide-scale datasets along with a series of locally reliable empirical relationships.

1.1 Physically based and empirical models

Distinct modelling approaches can lead to significantly different soil erosion rates even when the same model is applied within the same region (Shen et al., 2009).

The way the model is implemented (i.e. with the selection of different algorithms when available), the use of datasets with different resolution or accuracy (Merritt et al., 2003) and the provenance of a given dataset (Buneman et al., 2000; Simmhan et al., 2005) can play a key role on the output. When incomplete or missing, these pieces of information may affect the assessment of the actual accuracy of data to be used as input, therefore weakening – or in some circumstances even compromising – the application of theoretically accurate models (Saltelli et al., 2010).

While physically based models can in principle offer scientifically sound methods for deriving soil erosion rates from a plethora of detailed input data, their practical suitability for regional or continental scale assessment is controversial (Bras et al., 2003). The enormous gap between the type and accuracy of the needed input parameters and the actual availability of harmonized, verifiable large-scale datasets limits the applicability of such models (Stroosnijder, 2005). In theory, when working with physi-

NHESSD
2, 2639–2680, 2014

cally based models, possibly all the requested parameters are measurable and then could be considered as "known". In practice, often the parameters have to be calibrated against observed data (Beck et al., 1995; Wheater et al., 1993). This calibration adds non-negligible uncertainty in the parameters' values. The heterogeneity, variability and uncertainty associated with input parameter values and their interpolation in spatial or temporal domains outside the observed ones should be considered as key factors (Saltelli et al., 2010; Jetten et al., 2003) which may partially explain why lumped regression-based model can perform better than more complex physically based models (Bosco et al., 2013; de Vente et al., 2013).

If at watershed-scale a trend is observed (Daniel et al., 2011) to complement or replace physically based models with machine-learning techniques (which are advanced empirical modelling techniques), at regional-scale the adaptation of widely adopted empirical models and their improvement with the same techniques could play a meaningful role. Large-scale approximations with robust empirical modelling could provide useful – even if necessarily less accurate – support for risk assessors involved in decision-making processes at regional scale. The main limit of such approach is that empirical models do not necessarily model the right process and should only be used for the range of conditions they were developed for (Hessel, 2002; de Vente et al., 2013).

Computational science is emerging as one of the central topics within environmental modelling (Casagrandi and Guariso, 2009). To overcome these problems, reproducible computational methods based on free software and data are increasingly needed (Stallman, 2005, 2009; Peng, 2011). This may also help to reuse in a controlled way empirical equations for compensating the lack of detailed data.

NHESSD
2, 2639–2680, 2014

2 Materials and methods

2.1 The dataset

Electronic archives are an important data source for the scientific community. The added value and criteria for the selection of electronic archives are the accessibility of large volumes of data, their spatial coverage, their ability to preserve and harmonise historical data (Panagos et al., 2011) and often their free availability.

The base of data needed for running the model is compiled using literature and public available datasets:

- European Soil Geographical Database (SGDBE) (Heineke et al., 1998)
- Harmonized World Soil Database (HWSD) (FAO et al., 2009)
- Shuttle Radar Topography Mission (SRTM) (Farr et al., 2007)
- CORINE Land Cover (CLC) (European Environment Agency, 2011)
- ENSEMBLES Observations gridded dataset (E-OBS) (Haylock et al., 2008)

E-OBS is a European daily gridded observational dataset for precipitation and air temperature that covers the period 1950–2012. E-OBS is based on the largest available pan-European precipitation data set, and its interpolation methods were chosen after careful evaluation of a number of alternatives. The gridded data are delivered on four spatial resolutions and for the presented activities the 0.25° regular lat-lon grid resolution has been used. Another added value of the E-OBS data set is the daily estimates of interpolation uncertainty, provided as standard error.

Information on soil surface texture and rock fragment cover were derived from SGDBE and HWSD. The 1 : 1 000 000 SGDBE dataset contains a list of Soil Typological Units (STU) representing nature and properties of European soils. The STUs are grouped in Soil Mapping Units (SMU) to form soil associations because of the difficulty in delineating the STUs at the database scale. HWSD is a 30 arc-second raster

NHESSD
2, 2639–2680, 2014

database containing over 16 000 soil mapping units. It combines soil information worldwide.

The CLC database provides consistent localized geographical information on land cover in Europe. The 1 : 100 000 database, having a minimum mapping unit (MMU) of 25 ha and minimum width of linear elements of 100 m (EEA, 2007) has been used in the 100 m gridded version (CLC 2006 version 15). The database version for the year 2006 (CLC2006) has been produced by integrating the data on land cover changes for the period 2000–2006 with the map of land cover for the year 2000 (CLC2000).

The SRTM is still probably the most complete and reliable freely-available high-resolution digital topographic database of the Earth. Interferometric radar data were acquired and processed to digital topographic data at 1 arc-second resolution. The SRTM is available as 90 m × 90 m gridded dataset. In this study, the version 4 of the database is used.

2.2 The modelling architecture

A modelling architecture based on an extended version of the RUSLE (e-RUSLE) is here proposed and applied to evaluate soil erosion by water at regional scale. The RUSLE model (derived from USLE, Wischmeier and Smith, 1978) has been selected because of its flexibility and low data demand, compared with other models. Furthermore, the family of models based on the USLE provides long-term average soil loss estimates and has been applied all over the world in different environments and various climatic conditions (e.g. Kinnell, 2010; Lu et al., 2004; Angima et al., 2003; Bosco et al., 2009). The proposed architecture inherits from the RUSLE the ability to be easily linked to other related natural resources. For example, some effects of forest resources and generally of the vegetation component within land-cover are straightforward to assess (de Rigo and Bosco, 2011). Furthermore, approximated rapid assessments of the impact of disturbances (e.g. wildfires, de Rigo et al., 2013a; Di Leo et al., 2013) may be performed by exploiting the RUSLE modular architecture which easily allows potential and actual erosion rates to be estimated for different environmental condi-

NHESSD
2, 2639–2680, 2014

tions by simply considering different arrays of layers. The further seamless integration of multiple estimates in the erosivity component (see Sect. 2.3.1) supports a more robust adaptability to the heterogeneous conditions which are typical at continental scale. This flexibility exemplifies the potential of e-RUSLE within integrated natural resources modelling and management (INRMM, de Rigo, 2012c).

The RUSLE retains from the USLE (based on empirical correlation) some limitations. Within the model there are no factors directly representing physical processes (i.e, runoff, infiltration). The RUSLE only predicts soil losses caused by sheet and rill erosion, not by (ephemeral) gully erosion. Another fundamental lack is linked to the absence of sediment deposition estimation that could lead to overestimation in soil erosion rates. However, the USLE multiplicative structure (Ferro, 2010) is well suited for transforming the modelled quantities into other correlated ones by simply adding custom factors. As an example, for overcoming the absence of sediment deposition calculation, Mitasova et al. (1996) replaced the LS factor with a new index considering the spatial distribution of areas with topographic potential for soil erosion and sediment deposition.

The e-RUSLE preserves the structure of the RUSLE adding to its array of multiplicative factors one more factor for better considering the effect of stoniness on soil erodibility. An array of local estimations of rain erosivity (here based on empirical equations) has also been introduced for mitigating the extrapolation uncertainty associated to each single equation. The array-based estimation of erosivity is proposed to be an ensemble of multiple estimations from partly independent modules (empirical equations) aggregated by a similarity analysis so as to also increase the design diversity (de Rigo, 2013).

The model has been applied at a 1 km resolution for the whole of Europe. The resolution depends on data availability. Due to the use of the 1 : 1 000 000 ESGDB database for the calculation of the soil erodibility factor, it was not possible to produce a map having a better resolution.

NHESSD
2, 2639–2680, 2014

The methodology relies on the paradigm of *Semantic Array Programming* (de Rigo, 2012a, b) which allows the multi-dimensional structure of the mathematical and computational model to be explicitly and concisely exploited. This is achieved by semantically enhancing the chain of involved data-transformation modelling (D-TM) modules so as to better focus on a compact, modular integration of the arrays of data and geospatial layers.

2.2.1 Applying the semantic array programming paradigm

The computational modelling methodology (de Rigo and Bosco, 2011; Bosco and de Rigo, 2014) followed the paradigm of Semantic Array Programming (SemAP, de Rigo, 2012a, b) by combining concise implementation of the model with its conceptual subdivision in semantically enhanced abstract modules. SemAP is an extension of array programming (Iverson, 1980), which originated to ease and improve the translation of mathematical notation as algorithmic implementation. As Iverson (1980) suggested, "the advantages of executability and universality found in programming languages can be effectively combined, in a single coherent language, with the advantages offered by mathematical notation". This may be achieved by describing a model with a precise vector-based mathematical notation, which may ease the implementation of complex algorithms by also moving the "mathematical reasoning directly into the source code, where the mathematical description is actually expressed in a completely formalised and reproducible way" (de Rigo, 2012a).

The effort towards increasing the reproducibility in soil erosion modelling (de Rigo and Bosco, 2011; Bosco et al., 2011a, b) focused our attention mainly on the use of public available databases, free scientific software tools and libraries and we introduced some reproducible techniques in applying the model and its submodels. An innovative ensemble model based on climatic similarity (de Rigo et al., 2013b; Bosco et al., 2013) is applied to estimate rain erosivity from multiple available empirical relationships.

NHESSD
2, 2639–2680, 2014

SemAP array-based semantic constraints (de Rigo, 2012d) have been exploited in the model implementation. Some of them are exemplified hereinafter as active links ::*constraint*::[1].

2.3 The Extended RUSLE model (e-RUSLE)

The RUSLE model is designed to predict only soil loss by sheet and rill erosion. Sediment deposition processes or concentrated overland flow erosion (ephemeral gully erosion) are not considered in the equation. The model uses different factors representing the effect of topography, land cover, climatic erosivity, management practice and soil erodibility for modelling soil erosion. The RUSLE uses a system of mathematical equations for computing soil erosion. The e-RUSLE retains all the equations of his predecessor implementing an extra factor for the computation of soil stoniness interaction.

The basic equation of the extended RUSLE is as follows:

$$\mathrm{Er}_{c,Y} = R_{c,Y} K_{c,Y} L_{c,Y} S_{c,Y} C_{c,Y} St_{c,Y} P_{c,Y} \quad (1)$$

where all factors are ::*nonnegative*::[2] values referring to a given spatial grid cell c and are the average for a certain set of years $Y = y_1, \cdots, y_i, \cdots, y_{n_Y}$ of the corresponding yearly values:

$\mathrm{Er}_{c,Y}$ = average annual soil loss ($\mathrm{t\,ha^{-1}\,yr^{-1}}$).

$R_{c,Y}$ = rainfall erosivity factor ($\mathrm{MJ\,mm\,ha^{-1}\,h^{-1}\,yr^{-1}}$).

$K_{c,Y}$ = soil erodibility factor ($\mathrm{t\,ha\,h\,ha^{-1}\,MJ^{-1}\,mm^{-1}}$).

[1]The mathematical notation ::*constraint*:: refers to the online taxonomy of array-based semantic constraints which defines the Semantic Array Programming paradigm (http://mastrave.org/doc/mtv_m/check_is, de Rigo, 2012d).

[2]http://mastrave.org/doc/mtv_m/check_is#SAP_nonnegative

NHESSD
2, 2639–2680, 2014

$L_{c,Y}$ = slope length factor (dimensionless).

$S_{c,Y}$ = slope steepness factor (dimensionless).

$C_{c,Y}$ = cover management factor (dimensionless).

$St_{c,Y}$ = stoniness correction factor (dimensionless).

$P_{c,Y}$ = support practice aimed at erosion control (dimensionless).

Given the multiplicative structure, all layers are expected to be defined in a given grid cell c without missing values (::*nanless*::[3]) in order for the soil loss to be computable in c.

2.3.1 Rainfall Erosivity Factor

The intensity of rainfall is one of the main factors driving soil water erosion processes. The Rainfall Erosivity Factor (R) is a measure of precipitation's erosivity. Wischmeier (1959) identified a composite parameter, EI30, as the best indicator of rain erosivity.

The rainfall erosivity factor has been implemented in numerous soil erosion models. AGNPS (Young et al., 1989), WATEM/SEDEM (Van Rompaey et al., 2001), USPED (Mitasova et al., 1996), SEMMED (de Jong et al., 1999) and MMF (Morgan et al., 1984) all implement the R factor as the relationship between rainfall energy and intensity developed by Wischmeier and Smith (1978). The rainfall erosivity factor has been widely applied all over the world and it is considered as an important factor for soil erosion assessments under climate change scenarios (e.g. changes in rainfall distribution and intensity, Diodato, 2004a). Despite its frequent use, it retains some limitations. The main weakness of the R factor is in not explicitly considering runoff and this highly influences the capacity of the model to account for event erosion (Kinnell, 2010) and seasonal effects.

The scarcity of accurate datasets for assessing soil water erosion rates at regional scale motivated the introduction of a climatic-based ensemble model to estimate rain-

[3] http://mastrave.org/doc/mtv_m/check_is#SAP_nanless

NHESSD
2, 2639–2680, 2014

fall erosivity. The climatic layers have been computed using GNU R (R Development Core Team, 2011) and GNU Octave (Eaton et al., 2008) with the Mastrave modelling library (de Rigo, 2012a, b). The ensemble is an unsupervised data-transformation model applied to climatic data to reconstruct rain erosivity.

The R factor has been computed using the E-OBS database as data source. Seven empirical equations have been selected from the literature in order for the erosivity to be correlated with climatic information. Spatially distributed climatic information (such as average annual precipitation, Fournier modified index, monthly rainfall for days with ≥ 10.0 mm, (see Table 1b) has been computed from the daily reconstructed (E-OBS) patterns of precipitation in Europe (years 1980–2009).

The selected equations (Table 1c) refer to climate–erosivity regressions which have been validated in 4 geographical areas. Many other elementary relationships exist between climate and erosivity. The selected ones fulfil a series of expert-based criteria such as their reproducibility using the available datasets, the quality of literature and case studies, the climatic coverage of large European regions and the good regression performance validated in their spatial extent.

As an example, although linear in the parameters' regression, the empirical approach (eq. R_{d1}, region A_4 in Table 1c) proposed by de Santos Loureiro and de Azevedo Coutinho (2001) received wide acceptance (Onyando et al., 2005; Taveira-Pinto et al., 2009; Ranzi et al., 2012). The relationship has been tested in Italy (Diodato, 2004b) where it provided estimates more stable than the ones provided by other widely used empirical equations (in the limited validation set, the estimates of R_{d1} did not show rank reversals when compared to the measured erosivity). The relationship with the original parameters has been used also in Spain (López-Vicente et al., 2008).

The rationale for not limiting the estimation of the R factor to the use of one preferred regression-based equation lies on the strengths and limitations that the empirical nature of those simplified equations have in different geographic and climatic conditions. The input variables selected for each empirical equation proved valuable in describing the local distribution of rain erosivity within that equation's spatial domain. While extrap-

NHESSD
2, 2639–2680, 2014

olating the validity of the selected equations may be reasonable in order to cover other climatically similar areas, European regions with different climate could behave quite differently. For these regions, not only the equation's parameters but even the equation's input variables might poorly correlate with the observed soil erosion patterns. This justifies the use of multiple empirical equation families with parameterisations covering the climatic diversity of the European regions (Table 1c).The selected equations allow a pan-European reconstruction of the estimated rain erosivity to be carried on with the E-OBS data of daily precipitation.

The required integration exploited the array structure of the aforementioned quantities (semantic array programming). In particular, the array of regressors (R_i, 7 dimensions, Table 1c) and corresponding validated areas (A_i, 4 dimensions, Table 1c), as well as the array of covariates (C^j, 26 dimensions, Table 1b) have been used. A possible modelling strategy could have been to cluster the pan-European spatial extent A^{EU} in climatic polygons (subsets) associated to corresponding empirical equations. The clustering could have been performed by extrapolating a given equation R_i up to cover the polygon whose climate is closer to the climate observed in the validated area A_i. However, this approach would have generated unnecessary artefacts along the polygon boundaries. Moreover, within each polygon only one estimate would have been exploited (one-to-one approach).

The proposed strategy considers each estimate R_i as covering the whole Europe with a spatially varying degree of reliability (many-to-one approach). This qualitative reliability may be described as a fuzzy set-membership and is based on the Relative Distance Similarity (RDS) algorithm as implemented by the Mastrave modelling library and is applied for each equation R_i to compare the climatic spatial information of each cell in A^{EU} with the corresponding values in A_i . The RDS index has been successfully used in environmental fuzzy ensemble applications (de Rigo et al., 2013b; Bosco et al., 2013). It defines the relative distance between two values C_1^j and C_2^j of a given non-

NHESSD
2, 2639–2680, 2014

negative covariate. The relative distance is a dimensionless ::*possibility*::[4] between 0 (maximum dissimilarity) and 1 (maximum similarity) and is simply the ratio between the minimum and the maximum value: $\min(C_1^j, C_2^j)/\max(C_1^j, C_2^j)$. The behaviour of each empirical equation outside its definition domain was also assessed to prevent meaningless out-of-range values to degrade the ensemble estimation. Therefore, for both the inputs (covariates) and the output (erosivity estimates) of the regressors R_i the RDS index has been computed and then aggregated cautiously considering the minimum index. This may be defined here as:

$$\begin{aligned}
\mathrm{RDS}_c^{i,\mathrm{input}} &= \max_{\alpha \in A^i} \left(\overset{26}{\underset{j=1}{\Omega}} \left(\frac{\max\left(\min\left(C_c^j, C_\alpha^j\right), \delta C^j\right)}{\max\left(\max\left(C_c^j, C_\alpha^j\right), \delta C^j\right)} \right) \right) \\
\mathrm{RDS}_c^{i,\mathrm{output}} &= \max_{\alpha \in A^i} \left(\frac{\max\left(\min\left(R_c^i, R_\alpha^i\right), \delta R^i\right)}{\max\left(\max\left(R_c^i, R_\alpha^i\right), \delta R^i\right)} \right) \\
\mathrm{RDS}_c^i &= \min\left(\mathrm{RDS}_c^{i,\mathrm{input}}, \mathrm{RDS}_c^{i,\mathrm{output}}\right)
\end{aligned} \tag{2}$$

where δC^j is half of the measurement accuracy of the covariates and δR_i is the half of the tolerance of the erosivity estimates. Ω is a statistical operator with which the relative distances along each dimension of the covariates are aggregated in the RDS index. Among the many possibilities, a simple median has been selected here. Median is also a typical robust statistical operator frequently used for ensemble models. The weighted median (de Rigo, 2012c) of the 7 empirical models has here been used (using RDS_c^i as weights) for generating the final R factor layer.

[4] http://mastrave.org/doc/mtv_m/check_is#SAP_possibility

NHESSD
2, 2639–2680, 2014

2.3.2 Soil erodibility factor

The soil erodibility factor (K) "represents the effects of soil properties and soil profile characteristics on soil loss" (Renard et al., 1997). K factor has been largely used within soil erosion models (e.g. PERFECT, Littleboy et al., 1992, AGNPS and USPED) and it is usually determined experimentally using runoff plots. For predicting the K factor information on soil properties is needed. Since the availability of such data is limited at European scale, we applied a simplified equation calibrated on a world-wide dataset of measured K values (Römkens et al., 1986; Renard et al., 1997) using the percentage (::*proportion*::[5]) of sand, silt and clay present within the HWSD and ESGDB datasets. For the volcanic soils the value proposed by van der Knijff et al. (2000) was assigned.

Rock fragments have a major effect on soil erosion rates as they alter soil properties such as water-holding capacity, soil erodibility, rooting volume or bulk density, influencing the hydrological response of a soil as well as its degradation and productivity (Poesen and Lavee, 1994).

In estimating the K factor only the effects of rock fragment within the soil profile are considered. The presence of rock fragments at the soil surface and within the soil profile require special considerations that led to the introduction of the stoniness correction factor within our model (Sect. 2.3.5).

2.3.3 Topographic factor

The effect of topography within the model is simply based on the ::*angle*::[6] of slope. It is accounted for by the L and S factors. Either slope length or slope steepness substantially affect sheet and rill erosion estimated by the model. L and S factors have been determined using the same approach and equations applied by Bosco et al. (2008).

[5] http://mastrave.org/doc/mtv_m/check_is#SAP_proportion

[6] http://mastrave.org/doc/mtv_m/check_is#SAP_angle

NHESSD
2, 2639–2680, 2014

The S factor has been evaluated using Nearing's formula (Nearing, 1997) that provides more reliable results for steep slopes (up to 50 %). In a precautionary way, due to the lack of information regarding the capacity of the applied equation to predict the S factor on slopes over 50 %, the cells having larger slope gradient values were removed from the map.

The LS factor of the RUSLE model is, similarly to the R factor, present within the architecture of many different soil erosion models (AGNPS, PERFECT, MUSLE, Williams, 1975). Our approach is based on the formulation of Moore and Burch (1986) which considers, within the calculation process, the concept of specific catchment area accounting for flow convergence and divergence through this term of the equation (Moore et al., 1991). Specific catchment area (upslope contributing area per unit lenght of contour) is one of the most commonly used terrain attributes in hydrological modelling (Erskine et al., 2006) and it gives to the LS factor stronger physical basis making it suitable for soil erosion modelling.

2.3.4 Cover and management factor

Vegetative canopy, changing the impact and intensity of rainfall, the resistance to water flow and the amount of water available for transporting the sediments, influences soil and water losses (Rousseva, 2003). The cover-management (C) factor represents, as a dimensionless $::proportion:: \in [0,100\,\%]$, the influence of terrain cover, cropping and management practices to mitigate soil erosion. Numerous soil erosion models implement the C factor in their architecture (e.g. AGNPS, ANSWERS, Beasley et al., 1980, or WATEM/SEDEM). The C factor represents the relation between the soil loss in certain agricultural or cover conditions and the erosion that would occur in an area under clean-tilled continuous fallow conditions (Renard et al., 1997).

The cover-management factor is probably, among the different erosion factors, the most important (Morgan and Nearing, 2010). However aggressive the climate, whatever the slope or slope length, whatever the soil type, erosion will be slight or absent with a good soil cover.

NHESSD
2, 2639–2680, 2014

The calculation of the *C* factor is difficult due to its dependence from many different parameter such as the land cover, the protection offered by the vegetative canopy cover, the impact of soil moisture on reduction of runoff from low intensity rainfall or the reduction of soil erosion due to surface roughness. Due to the difficulties in processing all the necessary parameters on a large scale, values from literature have been used for calculating the cover-management factor in Europe (Angeli et al., 2004; DeCaro, 2007; Diodato et al., 2011; Morgan, 2005; Šúri et al., 2002; Cebecauer and Hofierka, 2008; Wischmeier and Smith, 1978; Bazzoffi, 2007; Marker et al., 2008). The implementation details are available in Bosco and de Rigo (2014). The calculation of the cover management factor has been processed using the third level of the CLC database.

2.3.5 Stoniness correction factor

Soil stoniness is known to have a strong influence on erosion rates (Poesen et al., 1994). Rock fragments in the soil top layers affect soil water erosion processes in various ways, both directly and indirectly.

Over the last years, there was a growing interest in soils containing considerable amounts of rock fragments (Cerdan et al., 2010). These soils are widespread and in particular are present in the Mediterranean area where they can occupy more than 60 % of the land (Poesen and Lavee, 1994).

The RUSLE model considers stoniness indirectly within the *K* and the *C* factor. Regarding the *K* factor, as already mentioned, only the effects of rock fragments within the soil profile are considered. For the *C* factor stoniness is taken into account in calculating the Surface Cover Sub-factor. Due to the impossibility to calculate the *C* factor for the whole European continent applying the original equations of the RUSLE model, the contribution of stoniness in reducing soil erosion by water was not really considered. For avoiding overestimation in many different areas of the European continent, a new factor has been added for calculating the contribution of stoniness in mitigating soil erosion by water (stoniness correction factor).

NHESSD
2, 2639–2680, 2014

Poesen and Ingelmo-Sanchez (1992) describing the negative relation between rock fragment cover (Rc) and relative interrill sediment yield (IR), found a relation between these two parameters:

$$IR = e^{-b(Rc)} \quad (3)$$

where b is a coefficient indicating the effectiveness of the rock cover (Rc, $::proportion:: \in [0,1]$) in reducing interrill soil loss.

The authors found an experimental value for the coefficient b of 0.02 if the rock fragments are partly embedded in the sealed topsoil and a value of 0.04 if the fragments are placed on the soil surface. These values are close to values reported by Box (1981) and Collinet and Valentin (1984) ranging from 0.0256 to 0.058.

Equation (3) was applied within the model for calculating the stoniness correction factor, in order to consider the negative effect of rock fragments on soil erosion by water. The coefficient b in Eq. (3) was set equal to 0.04 as proposed by Weltz et al. (1987) and Poesen et al. (1994). Unfortunately detailed information on soil stoniness at European scale is scarce. The only reliable information at European scale that can be used to derive the Stoniness Correction factor is the volumetric rock fragment content of the soils contained in the ESGDB database. The values of volumetric rock fragment content of the soils were used for calculating the Rc parameter in Eq. (3); we assumed the rock fragment cover equals the volumetric rock fragment content (Govers et al., 2006).

2.3.6 Human practices factor

By definition, the P factor is the ratio of soil loss with a specific support practice to the corresponding loss with upslope and downslope tillage (Renard, 1997). It represents how surface and management practices like terracing, stripcropping or contouring affect erosion rates. For areas where there are no support practices or without any information on this aspect, the P factor is set equal to 1. Due to the spatial scale the model

NHESSD
2, 2639–2680, 2014

was applied and because of the consequent lack of information on land management practices, the *P* factor was considered everywhere equal to 1.

3 Validation

The validation of soil erosion estimates at continental scale is problematic. The common validation procedures are not technically and financially applicable for large spatial extents. Nonetheless, some validation option is still applicable.

For validating the 1 km^2 European map of soil erosion by water, we applied a qualitative method based on visual interpretation. The methodology is based on a visual and categorical comparison between modelled and observed erosion rates. Also, country level aggregated statistics have been compared among the proposed results and pre-existing European erosion maps, providing a further plausibility check.

A procedure employing high-resolution Google Earth images and pictures as validation data was applied. High-resolution data from Google Earth (Google Earth, Mountain View, CA: Google Inc., 2009) is a relatively slightly tapped new source of validation data for many research fields. The resolution of the images allows for a visual qualitative estimation of soil erosion phenomena. The coverage of high-resolution Google Earth images has rapidly increased during the last years.

By overlaying the soil erosion by water map of Europe and the selected points in Google Earth, a visual plausibility check, based on the erosion/deposition categories for field validation of Warren et al. (2005), was carried out. A buffer of 3 km × 3 km around 85 selected points was analysed by the authors, with over 700 cells at 1 km × 1 km. For each cell, a visual assessments relied on high-resolution images. Overall, more than 10 000 visual plausibility checks have been made. A statistical overview of the results is shown in Fig. 1a. The full results of the validation, also containing the comments of the evaluators, are available in Bosco et al. (2014). The cumulated percentage of points with a quality equal to a given class (among 5 classes from *very accurate* to *inaccurate*) is shown. A bootstrap analysis (with 10 000 runs) was performed on the

NHESSD
2, 2639–2680, 2014

data in order to assess uncertainty. In Fig. 1a, boxplots are associated with each quality class, highlighting the quartiles and the whiskers with 5 % and 95 % of occurrence.

The land cover appears as rarely very accurate. However, inaccuracy is mostly moderate. The inaccuracy may be explained by classification errors in the CLC 2006 and its temporal gap with the remote sensing and photographic information in Google Earth. The e-RUSLE estimates appear as very accurate for more than one in four cells. The quality decrease seems to be at least partially correlated with land cover uncertainty. Nevertheless, the percentage of land cover cells with at least moderately accurate information is higher than the corresponding percentage in erosion estimates. This highlights other non-negligible sources of uncertainty in the e-RUSLE model. The plausibility check underlines that erosion in 63 % of the cells is accurate or very accurate (this is a conservative assessment including 95 % of bootstrap variability BV; median is higher than 72 %) and for 83 % (95 % BV) is at least moderately accurate (the median value is 90 %). Completely inaccurate estimates appear as rare.

The model results were also compared with other regional soil erosion assessments carried out by local experts using similar or alternative methodologies (Fig. 1b). The soil erosion maps (Fig. 3) provided by different countries through the EIONET-SOIL network and an extensive dataset compiled by Cerdan et al. (2010) were used.

EIONET is a partnership of the European Environment Agency (EEA) involving more than 350 national institutes and approximately 1000 experts. The aim of the network is to collect, organize and disseminate data related to the European environment. Most of the EIONET's maps were calculated applying soil erosion models (mainly the USLE or one of its derivatives) using readily available highly accurate national datasets. The estimates are not seamless between different countries due to the autonomous assessment at country level. The data related to Germany and Poland refer only to agricultural lands.

Cerdan et al. (2010) compiled an extensive database of soil erosion rates based on erosion plots in Europe under natural rainfall. The data were gathered by the authors from literature and personal communication. The data, covering 19 countries, were

NHESSD
2, 2639–2680, 2014

collected on 85 experimental sites. Geostatistical techniques were implemented for interpolating the plot results to the whole European territory.

The average estimates and the standard deviation of the soil erosion rates at country level are heterogeneus. The maximum values also corroborate the expectation of an asymmetric distribution (with positive skewness) which may be linked to the distribution of precipitation intensity over large regions (due to varying orography, distance inland, latitude,...) and of factors such as the one describing the cover-management (whose range of values spans over three orders of magnitude, see Bosco and de Rigo, 2014). Right-tailed distributions are associated with high variance of the quantiles close to the maximum one. Therefore, the greater discrepancy between the values of EIONET-max and e-RUSLE-max when compared to the discrepancy between the corresponding standard deviations is not surprising. This however increases the sensitivity of the average to the modelling stochastic fluctuations of higher quantiles (median estimates would have been more stable: unfortunately, they are not available for EIONET and Cerdan et al. (2010), along with any more detailed quantile distribution).

As underlined by Lovejoy and Schertzer (2007), a growing body of evidence suggests that "geofields are scaling (have power law dependencies on spatial scale, resolution), over wide ranges". This may also suggest the scaling of the topography and other surface fields (e.g. soil erosion) to be "significant because the geophysical processes responsible for them (including orographic, erosional and hydrological processes) are strongly nonlinearly coupled so that the scaling in one is strong evidence for scaling in another" (Lovejoy and Schertzer, 2007).

Applying this hypothesis to the soil erosion distribution over European countries would allow a more articulated comparison to be done between e-RUSLE and the available information (EIONET and Cerdan et al., 2010). This conjecture originated a long debate between lognormality vs. power low (Pareto distribution) – among others – for assessing the most appropriate spatial distribution of scaling geofields (Lovejoy and Schertzer, 2007). Here, we assess both the lognormal and generalized Pareto distribution (with the horizontal shift parameter set to 0, since soil erosion lies in $\mathbb{R}^+$) fitted

NHESSD
2, 2639–2680, 2014

by using the mean and standard deviation values. As shown in Fig. 2, the true quantiles of the e-RUSLE estimations appear as reasonably reconstructed by both distibutions for the higher values. Regarding the lower quantiles, the Pareto distribution generally outperforms the lognormal one. For some of the analysed countries (Germany, the Netherlands and Poland), the lower quantiles are poorly reconstructed. However, provided the distance between lower and higher erosion values exceeds one order of magnitude, risk assessors and policy makers are likely to focus more on high erosion rates whereas the inaccuracy of low quantiles might locally be relevant. Both distributions highlight the discrepancy of e-RUSLE estimates in Austria and the Netherlands. In Italy, e-RUSLE appears in line with EIONET results while higher than the reconstructed distribution of Cerdan et al. (2010). The low soil erosion values reported by EIONET in the Austrian alpine area are highly correlated with the presence of forest areas and other vegetation types (e.g. see the maps in Kempeneers et al., 2012; Martin et al., 2010). The corresponding values of the USLE cover management factor appear to have been set close to zero. The protective role of vegetation is essential even in the values of *C* factor we propose. However, in mountainous areas with high precipitation intensity vegetation may not completely prevent erosion. This different assumption may also be corroborated in Austria by considering the composition of its forests. In particular, deciduous tree species (whose erosion protection in winter is different from that of evergreen taxa) show a considerable cover in Austrian forests (e.g. *Larix decidua* L. and *Fagus sylvatica*).

The different validation methods applied in this paper indicate that the modified RUSLE satisfactorily estimates soil erosion rates. Some uncertainties still remain, but considering that most of the uncertainty can be attributed to a low input data quality, it can be expected that the model's results will improve with improving data quality.

NHESSD
2, 2639–2680, 2014

4 Results and discussion

The resulting soil erosion map is shown in Fig. 3. The well-known role of natural vegetation in mitigating soil erosion (Cerdan et al., 2010; de Rigo and Bosco, 2011; Maetens et al., 2012) may be observed by comparing the presented map with pan-European forest maps (e.g. Kempeneers et al., 2012) and vegetation maps (e.g. Martin et al., 2010, derived from CLC 2006). Brittany, northern Portugal and western Norway show high soil erosion rates that seem to be related to the pattern of the interpolated rainfalls. Especially in northern Portugal and Norway, the positive relationship between erosion rates and slope lenght (Cerdan et al., 2010), that increases the runoff rates, appears to be enhanced by the intense precipitation pattern.

Since some essential factors in the e-RUSLE (C, K factors and stoniness) are derived from categorical information, the uncertainty associated with the corresponding classification (with possibly high misclassification discontinuities) may be propagated in the final erosion map (Fig. 3).

For actually improving the estimation of the C factor, that is still a weakness within the model, it may be necessary to develop new techniques or equations improving the collaboration between soil erosion scientists and remote sensing experts. Although good relationships were obtained since the 80s between C factor and band ratios of NIR to red reflection (Cihlar, 1987; Stephens and Cihlar, 1982) and the studies of the C factor estimation using remote sensing techniques have reached good achievements they still need improvements (Zhang et al., 2011). Further analysis with detailed forest types and tree species distribution maps seem to be necessary for increasing the accuracy of the C factor (de Rigo and Bosco, 2011; Geißler et al., 2012).

The RUSLE model generally tends to overestimate soil loss (De Jong et al., 1986). Jointly with the weakness of data for some of the model's parameters and the use of coarse spatial data (e.g. E-OBS) along with data having sub-optimal resolution (e.g. SRTM), the application of the model can lead to noticeably uncertain soil erosion rates in certain areas. For example, the lack of appropriate datasets for soil stoniness can

NHESSD
2, 2639–2680, 2014

locally lead to an over estimation of the erosion rate (e.g. northern Portugal). However, the precise delimitation of such issues is very difficult as field investigations for validation are required, which is beyond the scope of this paper.

Readers should also be aware that because of the scale of the input data, results (soil erosion index) provide an overview of the soil erosion susceptibility in the landscape rather than an accurate estimation for a specific location.

The classification scheme used for measuring the soil erosion rates (Fig. 3) is based on the one applied in the PESERA Project (Kirkby et al., 2008). From 8 different categories for measuring soil erosion rates by water we derived 7 classes by aggregating the 0.5–1 $t\,ha^{-1}\,yr^{-1}$ and 1–2 $t\,ha^{-1}\,yr^{-1}$ in one single class 0.5–2 $t\,ha^{-1}\,yr^{-1}$ for an easier qualitative classification of the soil erosion map.

The thresholds above which soil erosion should be regarded as a serious problem is controversial, the soil formation processes and rates differing substantially throughout Europe. In Switzerland, the tolerable soil erosion rate is generally 1 $t\,ha^{-1}\,yr^{-1}$, which can increase to 2 $t\,ha^{-1}\,yr^{-1}$ for some soil types (Schaub and Prasuhn, 1998). Verheijen et al. (2009) reports an upper limit of 1.4 $t\,ha^{-1}\,yr^{-1}$. 2 $t\,ha^{-1}\,yr^{-1}$ is the threshold, in Norway, for considering the soil loss as tolerable (Srebotnjak et al., 2010). Our visualisation using the 2 $t\,ha^{-1}\,yr^{-1}$ thresholds for low erosion rates is intended for helping to better highlight the areas with higher rates of erosion by water.

The map shows that approximately 14 % of the European territory is characterized by a significant soil erosion rate (moderate – high level), which is in line with previous estimations that 15–16 % of Europe's land area is affected by soil erosion (Cerdan et al., 2010; EEA, 2003).

It is clear from the map that soil erosion by water is a major problem in many parts of Europe. The average rate of soil erosion by water across the EU-28 is 2.76 $t\,ha^{-1}\,yr^{-1}$, excluding Cyprus (CY), Greece (GR) and Malta (MT). Just over 7 % of cultivated land (arable and permanent cropland) in the EU-25 (excluding GR, CY and MT) is estimated to suffer from moderate to severe erosion (i.e. OECD definition of $> 11\,t\,ha^{-1}\,yr^{-1}$). This corresponds approximately to the entire area of Bulgaria. In comparison, only 2 % of

NHESSD
2, 2639–2680, 2014

permanent grasslands and pasture in the EU-25 is estimated to suffer from moderate to severe erosion. This demonstrates the importance of maintaining permanent vegetation cover as a mechanism to combat soil erosion.

Several countries appear as not affected by notable soil erosion. Others, mainly in the southern part of Europe, result particularly susceptible to erosion, showing a soil erosion rate much higher than the European average. However, such values can be misleading: erosion rates in many areas can be considerably higher, even in those countries having a low average. The opposite is also true for countries with higher values.

Considering the European ecozones (based on the FAO ecological zoning FAO, 2001, 2012), the mountain system shows a mean soil erosion rate 2–3 times higher than the average. (From 4.06 t ha^{-1} yr^{-1} of the subtropical mountain system to 7.8 t ha^{-1} yr^{-1} of the boreal mountain system.)

As already mentioned, there is a high probability for some of the model results to be over-estimated. The *R* factor uncertainty, the coarse resolution of the layers used for calculating the *K* factor, the CLC 2006 misclassification and the presence of areas having a stoniness value much higher than the value indicated by the underlying soil database (e.g. northern Scotland) can be at the basis of many of the uncertain estimations. Further investigations are suggested on the key role of land cover changes and misclassifications (CORINE Land Cover 2006 is found currently accurate in no more than 69 % of the sampled cells, bootstrap $p \leq 0.05$) and of forests and vegetation, especially in mountainous areas with intense precipitation.

Another limit of the proposed approach is that the model does not consider erosion processes such as channel or gully erosion, that locally may cause very high soil losses (Poesen et al., 2003; Mathys et al., 2003; Collinet and Zante, 2005) in Cerdan et al. (2010), tillage erosion that in Europe may have a similar rate as soil erosion by water (van Oost et al., 2009) or soil loss due to root and tuber crop harvesting (Poesen et al., 2001; Ruysschaert et al., 2005).

NHESSD
2, 2639–2680, 2014

Nevertheless, the proposed architecture is designed to be least data demanding while being able to scale up to the continental scale. The fuzzy ensemble application here exemplified for the rain erosivity layer highlights the e-RUSLE approach, which recommends a modular, semantically aware selection of a multeplicity of available estimates for improving the reliability of critical components. This approach would easily allow statistical resampling analysis on the ensemble uncertainty to be performed. Furthermore, a subset of layers are suitable to be used for assessing the potential soil erosion by water under climate change scenarios.

The pan-European assessment of soil erosion rates by water presented in this paper, despite the above mentioned limits, seems to be robust enough for helping to identify areas where to concentrate the effort for preventing soil degradation.

5 Conclusions

An estimation of pan-European soil erosion by water using a modified version of the RUSLE model has been carried out by merging existing empirical rainfall-erosivity equations within a climatic ensemble model based on the relative-distance similarity and by adding a new factor for better considering soil stoniness.

Highly heterogeneous availability of data and knowledge is typical at the continental scale (de Rigo, 2014). The lack of high-resolution pan-European datasets, the non-uniform availability of validated and least data demanding relationships for erosivity in the different European climates and the limitations inherited from the RUSLE architecture lead to a considerable level of uncertainty.

Some of the individual factors can also be interdependent, which results in an even greater impact on the model results (van der Knijff et al., 1999).

As a consequence, quantitative assessment using the model should not be undertaken without the right awareness. The provided estimates cautiously model the erosion rates in the absence of mitigating management practices – which should be regarded as a main factor for limiting the impact of erosion, as long as land use policies.

NHESSD
2, 2639–2680, 2014

It is necessary to have in mind that the main objective of the present paper is not the production of a new soil erosion map of Europe but to contribute to soil erosion research introducing new techniques and algorithms for improving soil erosion estimation at regional scale.

Anyway, our spatially distributed assessment of soil erosion, carried out using the e-RUSLE, even considering all the limits of our approach, helps to identify areas in Europe where to concentrate efforts for preventing soil degradation. The new model can support the European policy making due to the adaptability of its architecture. As an example DG-ESTAT of the European Commission, developing a set of Agri-Environmental indicators in order to track the integration of environmental concerns into the Common Agricultural Policy (CAP), exploited our map for estimating the soil erosion at NUTS3 level (Eurostat, 2013).

Improvement in these erosion estimates lies in better climate, soil and land cover data potentially available from national archives. Especially land cover requires frequent updating, because changes in land use have a major impact on erosion rates. There is the potential to do this through the analysis of remotely sensed images.

Acknowledgements. We acknowledge the E-OBS dataset from the EU-FP6 project ENSEMBLES (http://ensembles-eu.metoffice.com) and the data providers in the ECA&D project (http://eca.knmi.nl).

References

Angeli, L., Bottai, L., Costantini, R., Ferrari, R., Innocenti, L., and Siciliano, G.: Valutazione del rischio erosione: Applicazioni del modello RUSLE, Internal Report RI07-04, LAMMA-CRES, 2004. 2655

Angima, S. D., Stott, D. E., O'Neill, M. K., Ong, C. K., and Weesies, G. A.: Soil erosion prediction using RUSLE for central Kenyan highland conditions, Agr. Ecosyst. Environ., 97, 295–308, 2003. 2645

Bazzoffi, P.: Erosione del Suolo e Sviluppo Rurale: Fondamenti e manualistica per la valutazione agro ambientale, Edagricole, Bologna, 264 pp., 2007. 2655

NHESSD

2, 2639–2680, 2014

Beasley, D. B., Huggins, L. F., and Monke, E. J.: ANSWERS a model for watershed planning, T. ASABE, 23, 938–944, 1980. 2654

Beck, M. B., Jakeman, A. J., and McAleer, M. J.: Construction and evaluation of models of environmental systems, in: Modelling Change in Environmental Systems, edited by: Beck, M. B. and McAleer, M. J., John Wiley and Sons, 3–35, 1995. 2643

Boardman, J. and Poesen, J.: Soil erosion in Europe: major processes, causes and consequences, in: Soil Erosion in Europe, edited by: Boardman, J. and Poesen, J., Wiley, Chichester, 479–487, 2006. 2640, 2641

Bollinne, A., Laurant, A., and Boon, W.: L'érosivité des précipitations a Florennes. Révision de la carte des isohyétes et de la carte d'erosivite de la Belgique, Bulletin de la Société géographique de Liége, 15, 77–99, 1979.

Bosco, C. and de Rigo, D.: Land Cover and Soil Erodibility within the e-RUSLE Model, Sci. Top. Focus, MRI-11b13, Maieutike Research Initiative, doi:10.6084/m9.figshare.856670, 2014. 2647, 2655, 2659

Bosco, C., Rusco, E., Montanarella, L., and Oliveri, S.: Soil erosion risk assessment in the alpine area according to the IPCC scenarios, in: Threats to Soil Quality in Europe, edited by: Toth, G., Montanarella, L., and Rusco, E., EUR 23438 EN, 47–58, 2008. 2653

Bosco, C., Rusco, E., Montanarella, L., and Panagos, P.: Soil erosion in the Alpine area: risk assessment and climate change, Studi Trent. Sci. Nat., 85, 117–123, 2009. 2645

Bosco, C., de Rigo, D., Dewitte, O., and Montanarella, L.: Towards a reproducible pan-european soil erosion risk assessment – RUSLE, Geophys. Res. Abstr., 13, EGU2011–3351–1, 2011a. 2647

Bosco, C., de Rigo, D., Dewitte, O., and Montanarella, L.: Towards the reproducibility in soil erosion modeling: a new pan-European soil erosion map, in: Keesstra, S.D., Mol, G. (Eds.), Wageningen conference on applied soil science : 'Soil Science in a Changing World'. Wageningen University, 9 pp. doi:10.6084/m9.figshare.936872, 2011b. 2642, 2647

Bosco, C., de Rigo, D., Dijkstra, T., Sander, G., and Wasowski, J.: Multi-Scale robust modelling of landslide susceptibility – regional rapid assessment and catchment robust fuzzy ensemble, IFIP Adv. Inf. Commun. Technol., 413, 321–335, doi:10.1007/978-3-642-41151-9_31, 2013. 2642, 2643, 2647, 2651

Bosco, C., de Rigo, D., and Dewitte, O.: Visual Validation of the e-RUSLE Model Applied at the Pan-European Scale, Sci. Top. Focus, MRI-11a13, Maieutike Research Initiative, doi:10.6084/m9.figshare.844627, 2014. 2642, 2657, 2678

NHESSD

2, 2639–2680, 2014

Box, J. E.: The effects of surface slaty fragments on soil erosion by water, Soil Sci. Soc. Am. J., 45, 111–116, 1981. 2656
Bras, R. L., Tucker, G. E., and Teles, V.: Six myths about mathematical modeling in geomorphology, in: Prediction in Geomorphology, edited by: Wilcock, P. R. and Iverson, R. M., American Geophysical Union, Washington DC, 63–79, 2003. 2642
Buneman, P., Khanna, S., and Tan, W. C.: Data provenance: some basic issues, Lect. Notes Comput. Sc., 1974, 87–93, doi:10.1007/3-540-44450-5_6, 2000. 2642
Casagrandi, R. and Guariso, G.: Impact of ICT in Environmental Sciences: a citation analysis 1990–2007, Environ. Modell. Softw., 24, 865–871, 2009. 2643
Cebecauer, T. and Hofierka, J.: The consequences of land-cover changes on soil erosion distribution in Slovakia, Geomorphology, 98, 187–198, 2008. 2655
Commission of the European Communities: Proposal for a Directive of the European Parliament and of the Council establishing a framework for the protection of soil and amending Directive 2004/35/EC, Brussels, COM(2006) 232 final, available at: http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CELEX:52006PC0232:en:PDF (last access: November 2013), 2006. 2641
Cerdan, O., Govers, G., Le Bissonnais, Y., Van Oost, K., Poesen, J., Saby, N., Gobin, A., Vacca, A., Quinton, J., Auerswald, K., Klik, A., Kwaad, F. J. P. M., Raclot, D., Ionita, I., Rejman, J., Rousseva, S., Muxart, T., Roxo, M. J., and Dostal, T.: Rates and spatial variations of soil erosion in Europe: a study based on erosion plot data, Geomorphology, 122, 167–177, doi:10.1016/j.geomorph.2010.06.011, 2010. 2655, 2658, 2659, 2660, 2661, 2662, 2663, 2678, 2679
Cihlar, J.: A methodology for mapping and monitoring cropland soil erosion, Can. J. Soil Sci., 67, 433–444, 1987. 2661
Collinet, J. and Valentin, C.: Evaluation of factors influencing water erosion in West Africa using rainfall simulation, IAHS-AISH P., 144, 451–461, 1984. 2656
Collinet, J. and Zante, P.: Analyse du ravinement de bassin versant à retenue collinaire sur sols à fortes dynamiques structurales (Tunisie), Geomorphologie, 1, 61–74, 2005. 2663
Crosson, P.: Soil erosion estimates and costs, Science, 269, 461–464, doi:10.1126/science.269.5223.461, 1995. 2640
Daniel, E. B., Camp, J. V., LeBoeuf, E. J., Penrod, J. R., Dobbins, J. P., and Abkowit, M. D.: Watershed modeling and its applications: a state-of-the-art review, The Open Hydrology Journal, 5, 26–50, 2011. 2643

NHESSD
2, 2639–2680, 2014

DeCaro, O.: Modelling soil erosion using the universal soil loss equation and a geographic information system: the Kinnarasani river watershed, Andhra Pradesh, India, available at: http://www.webcitation.org/6IzpR15HG, (last access: November 2013), 2007. 2655

De Jong, E., Wang, C., and Rees, H. W.: Soil redistribution on three cultivated New Brunswick hillslopes calculated from 137Cs measurements, solum data and the USLE, Can. J. Soil Sci., 66, 721–730, doi:10.4141/cjss86-071, 1986. 2661

De Jong, S. M., Paracchini, M. L., Bertolo, F., Folving, S., Megier, J., and de Roo, A. P. J.: Regional assessment of soil erosion using the distributed model SEMMED and remotely sensed data, Catena, 37, 291–308, 1999. 2649

de Rigo, D.: Semantic Array Programming with Mastrave – Introduction to Semantic Computational Modeling, The Mastrave project, available at: http://mastrave.org/doc/MTV-1.012-1 (last access: November 2013), 2012a. 2642, 2647, 2650

de Rigo, D.: Semantic array programming for environmental modelling: application of the Mastrave library, in: International Congress on Environment Modelling Software: managing Resources of a Limited Planet, Leipzig, Germany, 1–5 July 2012, 1167–1176, 2012b. 2642, 2647, 2650

de Rigo, D.: Integrated Natural Resources Modelling and Management: minimal redefinition of a known challenge for environmental modelling, Excerpt from the Call for a shared research agenda toward scientific knowledge freedom, Maieutike Research Initiative. available at: http://www.citeulike.org/groupfunc/15400/home (last access: November 2013), 2012c. 2646, 2652

de Rigo, D.: Applying semantic constraints to array programming: the module “check_is” of the Mastrave modelling library, Mastrave project technical report, 2012, available at: http://mastrave.org/doc/mtv_m/check_is (last access: November 2013), 2012d. 2648

de Rigo, D.: Software uncertainty in integrated environmental modelling: the role of semantics and open science, Geophys. Res. Abstr., 15, 13292, doi:10.6084/m9.figshare.155701, 2013. 2646

de Rigo, D.: Behind the horizon of reproducible integrated environmental modelling at European scale: ethics and practice of scientific knowledge freedom, F1000 Research, to appear as discussion paper, 2014. 2664

de Rigo, D. and Bosco, C.: Architecture of a pan-European framework for integrated soil water erosion assessment, IFIP Adv. Inf. Commun. Technol., 359, 310–318, doi:10.1007/978-3-642-22285-6_34, 2011. 2645, 2647, 2661

NHESSD

2, 2639–2680, 2014

de Rigo, D., Rodriguez-Aseretto, D., Bosco, C., Di Leo, M., and San-Miguel-Ayanz, J.: An architecture for adaptive robust modelling of wildfire behaviour under deep uncertainty, IFIP Adv. Inf. Commun. Technol., 413, 367–380, doi:10.1007/978-3-642-41151-9_35, 2013a. 2645

de Rigo, D., Barredo, J. I., Busetto, L., Caudullo, G., and San-Miguel-Ayanz, J.: Continental-Scale living forest biomass and carbon stock: a robust fuzzy ensemble of IPCC tier 1 maps for Europe, IFIP Adv. Inf. Commun. Technol., 413, 271–284, doi:10.1007/978-3-642-41151-9_26, 2013b. 2647, 2651

de Santos Loureiro, N. S., and de Azevedo Coutinho, M.: A new procedure to estimate the RUSLE EI30 index, based on monthly rainfall data and applied to the Algarve region, Portugal, J. Hydrol., 250, 12–18, 2001. 2650

de Vente, J., Poesen, J. Verstraeten, G., Govers, G., Vanmaercke, M., Van Rompaey, A., Arabkhedri, M., and Boix-Fayos, C.: Predicting soil erosion and sediment yield at regional scales: where do we stand?, Earth-Sci. Rev., 127, 16–29, 2013. 2641, 2643

Di Leo, M., de Rigo, D., Rodriguez-Aseretto, D., Bosco, C., Petroliagkis, T., Camia, A., and San-Miguel-Ayanz, J.: Dynamic data driven ensemble for wildfire behaviour assessment: a case study, IFIP Adv. Inf. Commun. Technol., 413, 11–22, doi:10.1007/978-3-642-41151-9_2, 2013. 2645

Diodato, N.: Local models for rainstorm-induced hazard analysis on Mediterranean river-torrential geomorphological systems, Nat. Hazards Earth Syst. Sci., 4, 389–397, doi:10.5194/nhess-4-389-2004, 2004a. 2649

Diodato, N.: Estimating RUSLE's rainfall factor in the part of Italy with a Mediterranean rainfall regime, Hydrol. Earth Syst. Sci., 8, 103–107, doi:10.5194/hess-8-103-2004, 2004b. 2650

Diodato, N., Fagnano, M., and Alberico, I.: Geospatial and visual modeling for exploring sediment source areas across the Sele river landscape, Italy, Italian Journal of Agronomy, 6, 85–90, doi:10.4081/ija.2011.e14, 2011. 2655

Eaton, J. W., Bateman, D., and Hauberg, S.: GNU Octave Manual Version 3. A High-Level Interactive Language for Numerical Computations, Network Theory Limited, ISBN: 0-9546120-6-X, 2008. 2650

Erskine, R. H., Green, T. R., Ramirez, J. A., and MacDonald, L. H.: Comparison of grid-based algorithms for computing upslope contributing area, Water Resour. Res., 42, W09416, doi:10.1029/2005WR004648, 2006. 2654

NHESSD
2, 2639–2680, 2014

Estreguil, C., de Rigo, D., and Caudullo, G.: A proposal for an integrated modelling framework to characterise habitat pattern, Environ. Modell. Softw., 52, 176–191, doi:10.1016/j.envsoft.2013.10.011, 2014. 2642
European Environment Agency: Assessment and Reporting on Soil Erosion, EEA Technical Report, 94, 103 pp., 2003. 2662
European Environment Agency: CLC 2006 Technical Guidelines, EEA Technical Report, 17, 68 pp., 2007. 2645
European Environment Agency: Corine Land Cover 2006 raster data – version 15 (08/2011), available at: http://www.eea.europa.eu/data-and-maps/data/corine-land-cover-2006-raster-1 (last access: November 2013), 2011. 2644
Eurostat: Agri-environmental indicator – soil erosion, in: Agri-environmental indicators, European Commission – Eurostat. Ch. 2.3.7, http://epp.eurostat.ec.europa.eu/statistics_explained/index.php/Agri-environmental_indicator_-_soil_erosion, 2013. 2665
FAO, IIASA, ISRIC, ISSCAS, JRC: Harmonized World Soil Database (version 1.1), FAO, Rome, Italy and IIASA, Laxenburg, Austria, 2009. 2644
Food and Agriculture Organization of the United Nations: Global Ecological Zoning for the Global Forest Resources Assessment 2000 – Final Report, Food and Agriculture Organization of the United Nations, Forestry Department, Rome, Italy, available at: http://www.fao.org/docrep/006/ad652e/ad652e00.htm, 2001. 2663
Food and Agriculture Organization of the United Nations: Global ecological Zones for FAO forest reporting: 2010 update, For. Resour. Assess. Work. Paper 179, available at: http://www.fao.org/docrep/017/ap861e/ap861e00.pdf, 2012. 2663
Farr, T. G., Rosen, P. A., Caro, E., Crippen, R., Duren, R., Hensley, S., Kobrick, M., Paller, M., Rodriguez, E., Roth, L., Seal, D., Shaffer, S., Shimada, J., Umland, J., Werner, M., Oskin, M., Burbank, D. and Alsdorf, D.: The shuttle radar topography mission, Rev. Geophys., 45, RG2004, doi:10.1029/2005RG000183, 2007. 2644
Favis-Mortlock, D.: Validation of field scale soil erosion models using common datasets, in: Modelling Soil Erosion by Water, NATO ASI Series I, 55, edited by: Boardman, J. and Favis-Mortlock, D., Springer, Berlin, 89–127, 1998. 2641
Ferro, V.: Deducing the USLE mathematical structure by dimensional analysis and self-similarity theory, Biosyst. Eng., 106, 216–220, 2010. 2646
Ferro, V., Porto, P., and Yu, B.: A comparative study of rainfall erosivity estimation for southern Italy and southeastern Australia, Hydrolog. Sci. J., 44, 3–24, 1999.

NHESSD
2, 2639–2680, 2014

García-Ruiz, J. M.: The effects of land uses on soil erosion in Spain: a review, Catena, 81, 1–11, doi:10.1016/j.catena.2010.01.001, 2010. 2640

Geißler, C., Lang, A. C., von Oheimb, G., Härdtle, W., Baruffol, M., and Scholten, T.: Impact of tree saplings on the kinetic energy of rainfall – the importance of stand density, species identity and tree architecture in subtropical forests in China, Agr. Forest Meteorol., 156, 31–40, 2012. 2661

Gobin, A., Jones, R., Kirkby, M., Campling, P., Govers, G., Kosmas, C., and Gentile, A. R.: Indicators for pan-European assessment and monitoring of soil erosion by water, Environment Science and Policy, 7, 25–38, 2004. 2641

Govers, G., Van Oost, K., and Poesen, J.: Responses of a semi-arid landscape to human disturbance: a simulation study of the interaction between rock fragment cover, soil erosion and land use change, Geoderma, 133, 19–31, 2006. 2656

Haylock, M. R., Hofstra, N., Klein Tank, A. M. G., Klok, E. J., Jones, P. D., and New, M.: A European daily high-resolution gridded dataset of surface temperature and precipitation, J. Geophys. Res.-Atmos., 113, D20119, doi:10.1029/2008JD010201, 2008. 2644

Heineke, H. J., Eckelmann, W., Thomasson, A. J., Jones, R. J. A., Montanarella, L., and Buckley, B.: Land Information Systems: developments for planning the sustainable use of land resources, Office for Official Publications of the European Communities, Luxembourg, EUR 17729 EN, 1998. 2644

Hessel, R.: Modelling soil erosion in a small catchment on the Chinese Loess Plateau, Ph.D. thesis, Utrecht University, Netherlands, 307 pp., 2002. 2643

Iverson, K. E.: Notation as a tool of thought, Commun. ACM, 23, 444–465, 1980. 2647

Jetten, V., Govers, G., and Hessel, R.: Erosion models: quality of spatial predictions, Hydrol. Process., 17, 887–900, doi:10.1002/hyp.1168, 2003. 2643

Jones, R. J. A., Grim, M., and Montanarella, L.: Use of Meteorological data sets at European level for input to the PESERA Grid Model, PESERA (Contract QLKS-CT-1999-01323) final report, European Commission, Joint Research Centre, European Soil Bureau Soil & Waste Unit, 13 pp., 2003. 2641

Kempeneers, P., Sedano, F., Pekkarinen, A., Seebach, L., Strobl, P., and San-Miguel-Ayanz, J.: Pan-European forest maps derived from optical satellite imagery, IEEE Earthzine, 5, 390004+, available at: http://www.earthzine.org/?p=390004 (last access: November 2013), 2012. 2660, 2661

NHESSD

2, 2639–2680, 2014

Kinnell, P. I. A.: Event soil loss, runoff and the universal soil loss equation family of models: a review, J. Hydrol., 385, 384–397, doi:10.1016/j.jhydrol.2010.01.024, 2010. 2645, 2649
Kirkby, M. J., Irvine, B. J., Jones, R. J. A., Govers, G., and the PESERA Team: The PESERA coarse scale erosion model for Europe, I. – Model rationale and implementation, Eur. J. Soil Sci., 59, 1293–1306, 2008. 2641, 2662
Lal, R.: Soil erosion impact on agronomic productivity and environment quality, Crit. Rev. Plant Sci., 17, 319–464, 1998. 2641
Littleboy, M., Silburn, M. D., Freebairn, D. M., Woodruff, D. R., Hammer, G. L., and Leslie, J. K.: Impact of soil erosion on production in cropping systems, I. Development and validation of a simulation model, Aust. J. Soil Res., 30, 757–774, 1992. 2653
López-Vicente, M., Navas, A., and Machín, J.: Identifying erosive periods by using RUSLE factors in mountain fields of the Central Spanish Pyrenees, Hydrol. Earth Syst. Sci., 12, 523–535, doi:10.5194/hess-12-523-2008, 2008. 2650
Lovejoy, S. and Schertzer, D.: Scaling and multifractal fields in the solid earth and topography, Nonlin. Processes Geophys., 14, 465–502, doi:10.5194/npg-14-465-2007, 2007. 2659
Lu, D., Li, G., Valladares, G. S., and Batistella, M.: Mapping soil erosion risk in Rondonia, Brazilian Amazonia: using RUSLE, remote sensing and GIS, Land Degrad. Dev., 15, 499–512, 2004. 2645
Maetens, W., Vanmaercke, M., Poesen, J., Jankauskas, B., Jankauskien, G., and Ionita, I.: Effects of land use on annual runoff and soil loss in Europe and the Mediterranean: a meta-analysis of plot data, Prog. Phys. Geog., 36, 599–653, 2012. 2661
Markantonis, V., Meyer, V., and Schwarze, R.: Review Article "Valuating the intangible effects of natural hazards – review and analysis of the costing methods", Nat. Hazards Earth Syst. Sci., 12, 1633–1640, doi:10.5194/nhess-12-1633-2012, 2012. 2641
Märker, M., Angeli, L., Bottai, L., Costantini, R., Ferrari, R., Innocenti, L., and Siciliano, G.: Assessment of land degradation susceptibility by scenario analysis: a case study in Southern Tuscany, Italy, Geomorphology, 93, 120–126, 2008. 2655
Martin, J., Henrichs, T., Pirc-Velkavrh, A., Volkery, A., Jarosinska, D., Csagoly, P., and Hoogeveen, Y.: Links between environmental challenges, in: The European Environment State and Outlook 2010: Synthesis, edited by: EEA, 17–23, 2010. 2660, 2661
Mathys, N., Brochot, S., Meunier, M., and Richard, D.: Erosion quantification in the small marly experimental catchments of Draix (Alpes de Haute Provence, France). Calibration of the ETC rainfall–runoff-erosion model, Catena, 50, 527–548, 2003. 2663

NHESSD
2, 2639–2680, 2014

Merritt, W. S., Letcher, R. A., and Jakeman, A. J.: A review of erosion and sediment transport models, Environ. Modell. Softw., 18, 761–799, doi:10.1016/S1364-8152(03)00078-1, 2003. 2642

Mitasova, H., Hofierka, J., Zlocha, M., and Iverson, R. L.: Modeling topographic potential for erosion and deposition using GIS, Int. J. Geogr. Inf. Sci., 10, 629–641, 1996. 2646, 2649

Moore, I. and Burch, G.: Physical basis of the length-slope factor in the universal soil loss equation, Soil Sci. Soc. Am. J., 50, 1294–1298, 1986. 2654

Moore, I. D., Grayson, R. B., and Ladson, A. R.: Digital terrain modelling: a review of hydrological, geomorphological, and biological applications, Hydrol. Process., 5, 3–30, doi:10.1002/hyp.3360050103, 1991. 2654

Morgan, R. P. C., Morgan, D. D. V., and Finney, H. J.: A predictive model for the assessment of erosion risk, J. Agr. Eng. Res., 30, 245–253, 1984. 2649

Morgan, R. P. C.: Soil Erosion and Conservation, 3rd edn, Blackwell Publ., Oxford, 2005. 2641, 2655

Morgan, R. P. C. and Nearing, M.: Handbook of Erosion Modelling, Wiley-Blackwell, 2010. 2654

Nearing, M. A.: A single, continuous function for slope steepness influence on soil loss, Soil Sci. Soc. Am. J., 61, 917–919, 1997. 2654

Onyando, J. O., Kisoyan, P., and Chemelil, M. C.: Estimation of potential soil erosion for river Perkerra catchment in Kenya, Water Resour. Manag., 19, 133–143, 2005. 2650

Panagos, P., Jones, A., Bosco, C., and Senthil Kumar, P. S.: European digital archive on soil maps (EuDASM): preserving important soil data for public free access, International Journal of Digital Earth, 4, 434–443, doi:10.1080/17538947.2011.596580, 2011. 2644

Panagos, P., Meusburger, K., van Liedekerke, M., Alewell, C., Hiederer, R., and Montanarella, L.: Assessing soil erosion in Europe based on data collected through a European network, Soil Sci. Plant Nutr., in press, doi:10.1080/00380768.2013.835701, 2014. 2680

Peng, R. D.: Reproducible research in computational science, Science, 334, 1226–1227, 2011. 2643

Pimentel, D., Harvey, C., Resosudarmo, P., Sinclair, K., Kurz, D., McNair, M., Crist, S., Shpritz, L., Fitton, L., Saffouri, R., and Blair, R.: Environmental and economic costs of soil erosion and conservation benefits, Science, 267, 1117–1123, doi:10.1126/science.267.5201.1117, 1995. 2640

Pimentel, D.: Soil erosion: a food and environmental threat, Environment Development and Sustainability, 8, 119–137, doi:10.1007/s10668-005-1262-8, 2006. 2641

NHESSD

2, 2639–2680, 2014

Poesen, J. and Ingelmo-Sanchez, F.: Runoff and sediment yield from topsoils with different porosity as affected by rock fragment cover and position, Catena, 19, 451–474, 1992. 2656
Poesen, J. and Lavee, H.: Rock fragments in top soils: significance and processes, Catena, 23, 1–28, 1994. 2653, 2655
Poesen, J., Torri, D., and Bunte, K.: Effects of rock fragments on soil erosion by water at different spatial scales: a review, Catena, 23, 141–166, 1994. 2655, 2656
Poesen, J. W. A., Verstraeten, G., Soenens, R., and Seynaeve, L.: Soil losses due to harvesting of chicory roots and sugar beet: an underrated geomorphic process?, Catena, 43, 35–47, 2001. 2663
Poesen, J., Nachtergaele, J., Verstraeten, G., and Valentin, C.: Gully erosion and environmental change: importance and research needs, Catena, 50 (2–4), 91–133, 2003. 2663
Quinton, J. N., Govers, G., Van Oost, K., and Bardgett, R. D.: The impact of agricultural soil erosion on biogeochemical cycling, Nat. Geosci., 3, 311–314, 2010. 2641
Ranzi, R., Le, T. H., and Rulli, M. C.: A RUSLE approach to model suspended sediment load in the lo river (vietnam): effects of reservoirs and land use changes, J. Hydrol., 422, 17–29, doi:10.1016/j.jhydrol.2011.12.009, 2012. 2650
R Development Core Team: The R reference manual, Network Theory Ltd, 2011. 2650
Renard, K. G., Foster, G. R., Weesies, G. A., McCool, D. K., and Yoder, D. C.: Predicting Soil Erosion by Water: a Guide to Conservation Planning with the Revised Universal Soil Loss Equation (RUSLE), US Dept Agric., Agr. Handbook, 703 pp., 1997. 2642, 2653, 2654
Rogler, H. and Schwertmann, U.: Erosivität der Niederschläge und Isoerodentkarte von Bayern (Rainfall erosivity and isoerodent map of Bavaria), Z. Kulturtech. Flurber., 22, 99–112, 1981.
Römkens, M. J. M., Prased, S. N., and Poesen, J. W. A.: Soil erodibility and properties, Trans. 13th congress of the Int. Soc. Of Soil Sci., Hamburg, Germany, 5, 492–504, 1986. 2653
Rousseva, S.: Ideas for Physical Interpretation of the USLE, Lecture given at the College on Soil Physics, Trieste, 2003. 2654
Ruysschaert, G., Poesen, J., Verstraeten, G., and Govers, G.: Interannual variation of soil losses due to sugar beet harvesting in West Europe, Agr. Ecosyst. Environ., 107, 317–329, 2005. 2663
Saltelli, A. and Annoni, P.: How to avoid a perfunctory sensitivity analysis, Environ. Modell. Softw., 25, 1508–1517, 2010. 2642, 2643
Schaub, D. and Prasuhn, V.: A map on soil erosion on arable land as a planning tool for sustainable land use in Switzerland, Adv. Geoecol., 31, 161–168, 1998. 2662

NHESSD
2, 2639–2680, 2014

Shen, Z. Y., Gong, Y. W., Li, Y. H., Hong, Q., Xu, L., and Liu, R. M.: A comparison of WEPP and SWAT for modeling soil erosion of the zhangjiachong watershed in the three gorges reservoir area, Agr. Water Manage., 96, 1435–1442, doi:10.1016/j.agwat.2009.04.017, 2009. 2642

Simmhan, Y. L., Plale, B., and Gannon, D.: A Survey of Data Provenance Techniques, Technical Report IUB-CS-TR618, Computer Science Department, Indiana University, 25 pp., 2005. 2642

Srebotnjak, T., Polzin, C., Giljum, S., Herbert, S., and Lutter, S.: Establishing Environmental Sustainability Thresholds and Indicators, Final report of the project: Establishing thresholds and indicators for environmental sustainability, 138 pp., 2010. 2662

Stallman, R. M.: Free community science and the free development of science, PLoS Med., 2, e47, doi:10.1371/journal.pmed.0020047, 2005. 2643

Stallman, R. M.: Viewpoint: why “open source” misses the point of free software, Commun. ACM, 52, 31–33, 2009. 2643

Stephens, P. R. and Cihlar, J.: Mapping erosion in New Zealand and Canada, in: Remote Sensing for Resource Management, edited by: Johannsen Jr., C. J. and Sanders, J. L., Soil Conservation Society of America, Ankeny, IA, 232–242, 1982. 2661

Stroosnijder, L.: Measurement of erosion: is it possible?, Catena, 64, 162–173, doi:10.1016/j.catena.2005.08.004, 2005. 2642

Šúri, M., Cebecauer, T., Hofierka, J., Fulajtár, E.: Erosion assessment of Slovakia at regional scale using GIS, Ecology, 21, 404–422, 2002. 2655

Taveira-Pinto, F., Petan, S., Mikos, M., and Pais-Barbosa, J.: Application of GIS tools for Leç, WIT Trans. Ecol. Envir., 124, 267–278, doi:10.2495/rm090251, 2009. 2650

Telles, T. S., Guimarães, M., and Dechen, S. C.: The costs of soil erosion, Rev. Bras. Cienc. Solo, 35, 287–298, doi:10.1590/S0100-06832011000200001, 2011. 2640

Van der Knijff, J. M., Jones, R. J. A., and Montanarella, L.: Soil erosion risk assessment in Italy, EUR – Sci. Tech. Res. Rep., EUR 19022 EN, 52 pp., 1999. 2664

Van der Knijff, J. M., Jones, R. J. A., and Montanarella, L.: Soil Erosion Risk Assessment in Europe, EUR – Sci. Tech. Res. Rep., EUR 19044 EN, 34 pp., 2000. 2653

Van Oost, K., Govers, G., and Desmet, P. J. J.: Evaluating the effects of changes in landscape structure on soil erosion by water and tillage, Landscape Ecol., 15, 579–591, 2000.

Van Oost, K., Cerdan, O., and Quine, T. A.: Accelerated fluxes by water and tillage erosion on European agricultural land, Earth Surf. Proc. Land., 34, 1625–1634, 2009. 2663

NHESSD

2, 2639–2680, 2014

Van Rompaey, A., Verstraeten, G., Van Oost, K., Govers, G., and Poesen, J.: Modelling mean annual sediment yield using a distributed approach, Earth Surf. Proc. Land., 26, 1221–1236, 2001. 2649

Verheijen, F. G. A., Jones, R. J. A., Rickson, R. J., and Smith, C. J.: Tolerable versus actual soil erosion rates in Europe, Earth-Sci. Rev., 94, 23–38, 2009. 2662

Warren, S. D., Mitasova, H., Landsberger, S., Iskander, F. Y., Ruzycki, T. S., and Senseman, G. M.: Validation of a 3-D enhancement of the universal soil loss equation for prediction of soil erosion and sediment deposition, Catena, 64, 281–296, 2005. 2657

Weltz, M. A., Renard, K. G., and Simanton, J. R.: Revised universal soil loss equation for western rangelands, General technical report RM – Rocky Mountain Forest and Range Experiment Station, US Dept Agric., Forest Service, 150, 104–111, 1987. 2656

Wheater, H. S., Jakeman, A. J., and Beven, K. J.: Progress and directions in rainfall–runoff modelling, in: Modelling Change in Environmental Systems, edited by: Jakeman, A. J., Beck, M. B., and McAleer, M. J., John Wiley and Sons, Chichester, 101–132, 1993. 2643

Williams, J. R.: Sediment-yield prediction with universal equation using runoff energy factor, Agricultural Research Service ARS-S-40, USDA, 1975. 2654

Wischmeier, W. H.: A rainfall erosion index for a universal Soil-Loss Equation, Soil Sci. Soc. Amer. Proc., 23, 246–249, 1959. 2649

Wischmeier, W. H. and Smith, D. D.: Predicting rainfall erosion losses – a guide for conservation planning, US Dept Agric., Agr. Handbook, 537, 1978. 2645, 2649, 2655

Young, R. A., Onstad, C. A., Bosch, D. D., and Anderson, W. P.: AGNPS: a nonpoint source pollution model for evaluating agricultural watersheds, J. Soil Water Conserv., 44, 168–173, 1989. 2649

Zhang, W., Zhang, Z., Liu, F., Qiao, Z., and Hu, S.: Estimation of the USLE cover and management factor C using satellite remote sensing: a review, Geoinformatics, 19th International Conference on IEEE, 1–5, 2011. 2661

NHESSD

2, 2639–2680, 2014

Table 1. Climatic information: auxiliary variables (A) and covariates (B) based on precipitation patterns $P_{\cdot,c}$ in a given spatial grid cell c. $P_{\mathrm{day},c}$ and $P_{m,c}$ respectively refer to the precipitation in c for the day day and the month m. The values are computed considering years y in a set of n_Y years. In C, a list of empirical equations is provided for estimating the rainfall erosivity (EI_{30}).

A	Climatic information auxiliary variables	Definition	Number of variables
	Average monthly number of days with daily rain ≥ 10 mm [dimensionless]	$D^{10}_{m,c} = \frac{1}{n_Y} \sum_{\mathrm{month(day)} \equiv m} \left[P_{\mathrm{day},c} \geq 10\,\mathrm{mm}\right]$	12
	Annual Modified Fournier index [mm]	$F_{y,c} = \sum_{m=1}^{12} \frac{\left(\sum_{\substack{\mathrm{month(day)} \equiv m \\ \mathrm{year(day)} \equiv y}} P_{\mathrm{day},c}\right)^2}{\sum_{\mathrm{month(day)} \equiv m} P_{\mathrm{day},c}}$	n_Y

B	Climatic information: covariates	Definition	Number of variables
	Average monthly precipitation [mm]	$P^0_{m,c} = \frac{1}{n_Y} \sum_{\mathrm{month(day)} \equiv m} P_{\mathrm{day},c}$	12
	Average monthly precipitation of days with daily rain ≥ 10 mm [mm]	$P^{10}_{m,c} = \frac{1}{n_Y} \sum_{\mathrm{month(day)} \equiv m} P_{\mathrm{day},c} \left[P_{\mathrm{day},c} \geq 10\,\mathrm{mm}\right]$	12
	Modified Fournier index [mm]	$F_c = \frac{1}{n_Y} \sum_{m=1}^{12} \frac{\left(P^0_{m,c}\right)^2}{\sum_{m=1}^{12} P^0_{m,c}}$	1
	Fournier-Ferro index [mm]	$F_{F,c} = \frac{1}{n_Y} \sum_{y=y_1}^{y_{n_Y}} F_{y,c}$	1

C	Validated in: Country/region	ISO3166	Definition	Reference
	A_1 Belgium	BE	$\begin{cases} R_{b1,c} = \alpha_{b1} \exp\left(\beta_{b1} \sum_{m=1}^{12} P^0_{m,c}\right) \\ R_{b2,c} = \alpha_{b2} \exp\left(\beta_{b2} F_c\right) \end{cases}$	Bollinne et al. (1979)
	A_2 Bavaria, Germany	DE-BY	$\begin{cases} R_{r1,c} = \alpha_{r1} + \beta_{r1} \sum_{m=1}^{12} P^0_{m,c} \\ R_{r2,c} = \alpha_{r2} + \beta_{r2} \sum_{m=5}^{10} P^0_{m,c} \end{cases}$	Rogler and Schwertmann (1981)
	A_3 Algarve, Portugal	PT-08	$R_{d1,c} = \alpha_{d1} \sum_{m=1}^{12} P^{10}_{m,c} + \beta_{d1} \sum_{m=1}^{12} D^{10}_{m,c}$	de Santos Loureiro and Azevedo Coutinho (2001)
	A_4 Sicily, Italy	IT-82	$R_{fi,c} = \alpha_{fi} F_{F,c}^{\beta_{fi}}, i = \{1,2\}$	Ferro et al. (1999)

NHESSD
2, 2639–2680, 2014



(b)

	EIONET (%)	EIONET mean	EIONET max	EIONET Std.Dev	e-RUSLE (%)	e-RUSLE mean	e-RUSLE max	e-RUSLE Std.Dev	Cerdan et al mean	Cerdan et al Std.Dev
Austria	97.6	0.66	53.2	1.9	88.4	4.8	339	12.4	1.6	6
Belgium	87.3	3.65	50	4.1	86.3	2.3	30	2.4	1.4	4
Bulgaria	91.2	1.88	71.5	2.7	95	2.2	81	2.6	1.9	6
Germany	46.6	1.39	68.1	2.1	58.2 [E] 93.2 [C]	2.7 [E] 2.2 [C]	89 [E] 240 [C]	3.3 [E] 3.4 [C]	1.9	7
Italy	49.2	6.6	293	13.6	48.2 [E] 91.8 [C]	7.4 [E] 7.8 [C]	276 [E] 327 [C]	12.9 [E] 12.4 [C]	2.3	9
the Netherlands	94.7	0.25	25.7	1	80.3	0.6	27	1.0	0.4	1
Poland	70.1	1.47	106.4	2.8	62.1 [E] 96.5 [C]	1.6 [E] 1.2 [C]	40	2.2 [E] 2.0 [C]	1.5	4
Slovakia	99.5	1.04	60.6	1.5	96.6	2.3	48	2.9	3.2	9

Fig. 1. (a) Expert based plausibility check over 85 random clusters of 3 km × 3 km grid cells (more than 700 cells and 10 000 visual checks were assessed, see Bosco et al., 2014). The bootstrap analysis, based on 10 000 runs, shows the bootstrap cumulated distribution of cells with a given level of accuracy, or more accurate. Box-plots: box with quartiles 25 %, 50 % (red line), 75 %; wiskers with 5 % and 95 % quantiles. **(b)** e-RUSLE erosion rates ($t\,ha^{-1}\,yr^{-1}$) per country compared with EIONET [E] and Cerdan et al. (2010) [C] datasets. In each country, the percentage (%) of e-RUSLE estimates in areas overlapping with the corresponding country surface covered by EIONET and Cerdan at al. (2010) is reported.

NHESSD
2, 2639–2680, 2014



Fig. 2. Quantiles (per country) of e-RUSLE estimated soil erosion by water. Box-plots: box with quartiles 25 %, 50 % (red line), 75 %; wiskers with 5 % and 95 % quantiles. True quantiles are compared with the reconstructed distribution under the hypotesis of lognormal and extended Pareto distribution. The hypothesized distributions are also compared with the ones corresponding to the available statistics from EIONET and Cerdan et al. (2010).

NHESSD
2, 2639–2680, 2014



Fig. 3. Top: average soil erosion rate by water (2006) as estimated with the e-RUSLE model. Bottom: corresponding EIONET estimates (Panagos et al., 2014).

NHESSD
2, 2639–2680, 2014

Modelling soil erosion at European scale

C. Bosco et al.