Nat. Hazards Earth Syst. Sci. Discuss., 3, C140–C141, 2015 www.nat-hazards-earth-syst-sci-discuss.net/3/C140/2015/

© Author(s) 2015. This work is distributed under the Creative Commons Attribute 3.0 License.



NHESSD

3, C140-C141, 2015

Interactive Comment

Interactive comment on "Building and design defects observed in the residential sector and the types of damage observed in recent earthquakes in Turkey" by M. Tolga Çöğürcü

Anonymous Referee #3

Received and published: 6 March 2015

1. The English vocabulary of the paper needs some minor improvements from technical language points. For example, beam-column joint region is generally used instead of column-beam integration zones. 2. Disintegrate is more suitable instead of flake and confinement is suitable instead of winding. 3. Deformed bars are preferred instead of ribbed. Planiform can be changed as undeformed. 4. Lap length is suitable instead ore length. 5. Development length is used instead corbelled additional length. 6. The number of figures or photos and total length of the paper can be decreased. 7. The references must be rechecked.

RESULT; The paper involves several valuable information's for scientific development

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



and can be accepted as a scientific paper and can be published.

Interactive comment on Nat. Hazards Earth Syst. Sci. Discuss., 3, 697, 2015.

NHESSD

3, C140-C141, 2015

Interactive Comment

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper

