



Interactive  
Comment

# ***Interactive comment on “Building and design defects observed in the residential sector and the types of damage observed in recent earthquakes in Turkey” by M. Tolga Çöğürçü***

**T. COGURCU**

mtolgac@selcuk.edu.tr

Received and published: 11 March 2015

âĀĀ The English vocabulary of the paper needs some minor improvements from technical language points. For example, beam-column joint region is generally used instead of column-beam integration zones.

CORRECTED

âĀĀ Disintegrate is more suitable instead of flake and confinement is suitable instead of winding.

CORRECTED

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



â€” Deformed bars is preferred instead of ribbed. Planiform can be changed as undeformed.

CORRECTED

â€” Lap length is suitable instead ore length.

CORRECTED

â€” Development length is used instead corbelled additional length.

CORRECTED

â€” The number of figures or photos and total length of the paper can be can be decreased.

CORRECTED

â€” The references must be rechecked.

RECHECKED

Please also note the supplement to this comment:

<http://www.nat-hazards-earth-syst-sci-discuss.net/3/C185/2015/nhessd-3-C185-2015-supplement.pdf>

---

Interactive comment on Nat. Hazards Earth Syst. Sci. Discuss., 3, 697, 2015.

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper

