

Interactive comment on “Hazard Assessment Comparison of Tazhiping Landslide Before and After Treatment” by Dong Huang et al.

Dong Huang et al.

dhuang@imde.ac.cn

Received and published: 28 April 2017

Manuscript title: (the original title: Hazard Assessment Comparison of Tazhiping Landslide Before and After Treatment) Manuscript number: 2019-391 Thanks very much for reviewer’s comments, which helped us to improve the quality of manuscript. We have made a major revision to address all the comments raised by the reviewer. In the revised manuscript, all changes have been marked in RED which is suggested by the reviewers, and is modified by the authors. We would be happy to make further modifications if required. We hope the changes listed have made the manuscript suitable for publication and we look forward to your response.

Q1: The main contribution of this paper seems to be the computational model proposed. It is desired to add related descriptions to the title of this paper. A1: This paper

[Printer-friendly version](#)

[Discussion paper](#)



title has been revised to "Hazard Assessment Comparison of Tazhiping Landslide Before and After Treatment Using Finite Volume Method". Please see p.1, line 2.

Q2: Previous study on landslide/debris flow issues using the fluid mechanics based method had faced the problem that it predicts higher mobility of the moving body while using the same fluid parameters throughout the whole flowing process. For example, less obvious fluid property is expected when the flow body is approaching stop point. It is stated in this manuscript that a changed frictional resistance is used (L78). However, the details are not clear in the text. Relevant descriptions on this issue should be strengthened. A2: This paper adopted the RAMMS to simulate the mass movement process. In RAMMS, we can automatically generate the friction coefficient for our calculation domain based on topographic data analysis, forest information and global parameters and so on. Therefore, we can use a changed frictional resistance. This problem has been considered in the discussion section. Please see p.22-23, line 378~406.

Q3: It is not clear in the text that how the free surface of the landslide/debris flow is treated or reconstructed. An additional figure is needed to describe the details. A3: We have reconstructed and added Figure 4. Please see p.10, line 218.

Q4: Fig.4 showed the geological profile of Tazhiping Landslide and a slide surface is clearly indicated. Is this slide surface comparable with the simulation result? It would be interesting to show their comparison. A4: We have reconstructed and added Figure 8. Before engineering treatment, Figure 4 and Figure 5 have shown that the sliding mass had an estimated starting volume of about 600,000m³ and a mean thickness of 8m. After fully accounting for the slide-resistant piles and mounds, we introduced the Morgenstern-Price method to calculate the stability coefficient of Tazhiping landslide after treatment. The method was determined with an iterative approach by changing the position of the sliding surface until failure of the dumpsite (Figure 8). Please see p.15, line 300~302 and 306~308.

Q5: In Tab.3, Various hazard zone levels were cataloged. What is the criterion to assign

[Printer-friendly version](#)[Discussion paper](#)

a specific damage situation to a certain zone level? Is there any standard code to follow? A5: We have cited standard code and literature(Fell R et al., 2008; DZ/T 0286-2015). Please see p.18, line 354~355.

Other specific comments are given below.

Q6: The quotations in the manuscript are not in the same format, for example, Line 44, Costa, 1984; VS Line 50, Zhang. Y, 2013. Usually only family name is preferred, please refer to the journal's instructions and make necessary changes throughout the text. p.11, line 266: figure is subtitled with A6:It has been revised. We have revised all references and quotations in the manuscript according to the NHSSD journal style. The reference list has been updated as well. Please see references and quotations section.

Q7: Fig.1 needs proper citation. A7: It has been revised (Christen et al., 2010a).

Q8: In Fig.6, Fig.7, what moment of flow does these figures represent? Different moment should have different deposit thickness, flow velocity and pressure. Please confirm. A8: The Figure.6 and Figure.7 is shown that the last moment of the flow. Different moment have different deposit flow height, velocity and pressure. However, the coloredbar shows the maximum values or an instantaneous for a given time step. It has been revised. Please see p.17, line 324-325.

Q9: L276 "The middle and lower deposits had a thickness of about 5-10m", confusing here, what does "the middle and lower deposits" mean? Similar as "the middle and lower movement speed", please check throughout the text. A9: This sentences has been reformulated, because of wrong word order. Please see p.14, line 288 and p.17, line 328.

Q10: L289. What technique is used for searching the sliding plane. A10: Coupled with field borehole surveying and numerical calculation method to search the sliding plane.

Q11: L305, Fig.4 should be Fig.7. A11: It has been revised. Please see p.17, line 324.

[Printer-friendly version](#)[Discussion paper](#)

Please see p18, line 358 and 359.

Q12: Tab.3. How is the “Building damage probability” evaluated?. A12: By the thickness of the landslide mass to evaluate the ability of a building to withstand a landslide disaster. I have cited some literatures (Hung et al., 1984; Petrazzuoli et al., 2004; GB, 50010–2010; Hu et al., 2012; Zeng et al., 2015). Please see p18, line 358 and 359.

The text of the manuscript has been revised.

Interactive comment on Nat. Hazards Earth Syst. Sci. Discuss., doi:10.5194/nhess-2016-391, 2017.

[Printer-friendly version](#)

[Discussion paper](#)

