# BASIC FEATURES OFTHE PREDICTIVE TOOLS OF EARLY WARNING SYSTEMS FOR WATER-RELATED NATURAL HAZARDS: EXAMPLES FOR SHALLOW LANDSLIDES

Roberto Greco<sup>1</sup>, Luca Pagano<sup>2</sup>

<sup>1</sup>University of Campania Luigi Vanvitelli, Naples, 80125, Italy <sup>2</sup>University of Naples Federico II, Naples, 80125, Italy Correspondence to: <u>luca.pagano@unina.it</u>

### 1

ABSTRACT To manage natural risks, an increasing effort is being put in the development 2 of early warning systems (EWS), namely, approaches facing catastrophic phenomena 3 4 by timely forecasting and alarm spreading throughout exposed population. Research efforts aimed at the development and implementation of effective EWS should 5 especially concern the definition and calibration of the interpretative model. This paper 6 analyses the main features characterizing predictive models working in early warning 7 systems, by discussing their aims and, consistently, their features in terms of model 8 9 accuracy, evolution stage of the phenomenon at which the prediction is carried out, and model architecture. Original classification criteria based on these features are 10 developed throughout the paper and shown in their practical implementation through 11 examples referred to flow-like landslides and earth flows, both characterized by rapid 12 evolution and quite representative of many applications of EWS. 13

14

#### 1 1. Introduction

2 Different natural hazards turning into catastrophes have occurred widespread in Italy 3 in the recent past as well as in the last centuries. Seismic and volcanic phenomena have 4 affected sporadically large areas, while rainfall-induced landslides, floods and snow 5 avalanches have frequently hit sites spread all over the territory. Structural mitigation 6 approaches are inapplicable throughout the entire territory at risk and might be 7 planned only for areas relevant from a socio-economic point of view.

Hence, to manage natural risks, an increasing effort is being put in the development of 8 9 non-structural approaches, based on timely forecasting the catastrophic phenomena from precursors or indicators, so to early spread the alarm throughout the exposed 10 areas (early warning) and temporarily eliminate or, at least, reduce the exposure of 11 12 people, preventing or limiting victims (Basher, 2006). The increasing importance of Early Warning Systems (EWS) is testified by the fact that they are among the priorities 13 adopted by the United Nations, International Strategy for Disaster Reduction (ISDR) 14 (UN-ISDR, 2005; 2006). 15

EWS indeed present undeniable advantages, among which are their fast, simple and low-cost implementation, and environmental friendliness. Focusing on water-related hazards, significant examples of operational early warning systems are currently found in the field of floods, landslides, snow avalanches, earth fill failures. A recent review of EWS operating in Europe for water-related hazards can be found in Alfieri et al. (2012).

As it will be described in detail hereinafter, the architecture of an EWS is strictly related 21 to the time needed for the deployment of the mitigation measures, compared to the 22 time of evolution of the hazardous event. In this respect, EWS for floods present quite 23 different features if they are established along large or small rivers. In the first case, 24 rainfall measurements or predictions are supplemented with river stage measurements 25 in upstream sections (e.g. Rabuffetti and Barbero, 2005), and flood routing models can 26 be run in cascade of hydrological models (e.g. Cranston and Tavendale, 2012). The lead 27 time of prediction, which depends on the length of the river and on the extension of its 28 catchment, can extend up to several days or weeks. In the case of small streams, the 29 30 time lapse between rainfall and peak discharge may be so short that weather nowcasting is needed for the warning to be launched in due time (e.g. Alfieri and 31 Thielen, 2015; de Saint-Aubin et al., 2016). 32

So far, most of the EWS dealing with rainfall-induced landslides are based on rainfall
 measurements, sometimes supported by weather forecasts (e.g. Keefer et al., 1987;
 Ponziani et al., 2012), rarely integrated with monitoring of some soil variables (e.g.
 Ortigao and Justi, 2004; Chleborad et al., 2008; Baum and Godt, 2010). Rainfalls are

interpreted often merely statistically, with an empirical quantification of rainfall 1 thresholds for landslide initiation (e.g. Sirangelo and Versace, 1996; Sirangelo and 2 Braca, 2004; Guzzetti et al., 2007, 2008; Capparelli and Tiranti, 2010; Tiranti and 3 Rabuffetti, 2010; Martelloni et al., 2012; Segoni et al., 2014; Tiranti et al., 2014; Piciullo 4 et al., 2016). In rare cases, physically based approaches are adopted for the 5 interpretation of the effects of rainfall history. The few examples of inclusion of slope 6 infiltration and stability modelling in the assessment of the safety conditions are mostly 7 still at a prototypal stage (e.g. Schmidt et al., 2008; Capparelli and Versace, 2011; 8 9 Ponziani et al., 2012; Eichenberger et al., 2013; Pumo et al., 2016).

EWS operating for snow avalanches monitor snow accumulation and the melting processes, with the former basing essentially on interpreting precipitation and air temperature records, and the latter on air (or snow) temperature(e.g. Liu et al., 2009).

Even in the field of man-made systems, early warning is assuming a prominent role in 13 the assessment of the risk associated with failure. For instance, in the field of earth 14 dams, with regard to all possible collapse mechanisms, i.e. slope instability and internal 15 erosion phenomena, or even earthquake-induced effects, risk mitigation is de-facto 16 17 based on early warning systems (e.g., Pagano and Sica, 2013; Ma and Chi, 2016). The wide monitoring system commonly installed to characterize time-by-time the behavior 18 19 of these structures, carried out essentially in terms of displacements, pore water pressure, seepage flows, and accelerations, is pointed towards a continuous checking 20 of dam safety conditions, aimed at evacuating downstream settlements in case of 21 22 predicted collapse.

Literature indicates that common elements, which typically characterize an early
 warning system (e.g. Intrieri et al., 2012; Intrieri et al., 2013; Calvello and Piciullo, 2016),
 are:

a field monitoring system, recording physical quantities related to the phenomenon
 in hand, and transmitting them to a collection-elaboration center; measured
 variables may conveniently be distinguished into two categories: *cause variables*,
 leading to the initiation of the phenomenon; *effect variables* that, affected by the
 formers, characterize the phenomenon itself during its evolution and at its
 triggering, allowing also to recognize its intensity;

*a predictive model,* formalizing mathematically the relationships linking cause and
 effect variables, allowing to catch the evolution stage of the phenomenon and
 assess system safety conditions;

- 1 3. *thresholds* for the variables related to safety conditions of the system; these 2 thresholds correspond to different alert levels, with the highest one activating the
- 3 spread of the alarm message, aimed at eliminating people exposure;
- 4 4. different *actions* related to each alert level defined at 3.

5 Research efforts aimed at the development and implementation of effective EWS 6 should concern, above all, the definition, calibration and validation of the predictive 7 model (Michoud et al., 2013). It should be as accurate as possible and, at the same time, 8 capable of rapidly carrying out the turning of the monitored quantities into the 9 assessment of system safety conditions. In many applications, dealing with rapidly 10 evolving natural hazards, a real-time working system is in fact required, in order to 11 maximize the lead time available to reduce/eliminate people exposure to the hazard.

Aim of the paper is to address the main features of predictive models for water-related 12 natural hazards. The proposed frame is quite general and applicable to other types of 13 natural hazards, thus references will be briefly made throughout the paper also to 14 applications different from water-related hazards. In particular, based on the precise 15 definition of the aims of the EWS, this work addresses the importance of identifying the 16 17 evolution stage of the catastrophic event at which the prediction should be implemented, so to maximize its effectiveness. For the first time the evolution stage at 18 19 which the predictive model is implemented is considered as one of its features, along with the other traditional approach distinguishing between physically- or empirically-20 based models. 21

In principle, any predictive model might be referred to any spatial scale, which is thus not considered as a valid classification element for EWS models. Rather, the classification criteria proposed throughout the paper may be referred to all scales. The choice to show specific examples all referred to rainfall-induced landslides at a slope scale is not performed in the light to reduce generality to the proposed criteria but, rather, in the attempt to select an application field which representativeness poses challenges extendible to other natural phenomena.

29

# Prediction uncertainty and the minimization of the costs of missing and false alarms of an EWS

Whatever the predictive model adopted, it will never be capable of providing certainty
 about the occurrence of a catastrophic event. A model yields variables systematically
 affected by a given uncertainty degree due to the following possible causes:

- incompleteness of information about the physical system supposed to cause
   catastrophes;
- various error types associated with the measurements provided by the monitoring
   system;
- unavoidable simplifications of reality always introduced in building the predictive
  model;
- randomness of some of the processes involved in the genesis of the catastrophic
  event.

It is obvious that the uncertainties of the predicted variables related to the physical 9 system affect the assumption of different alert stages. With reference to the last stage, 10 it may occur that the early warning system issues an alarm, but no dangerous 11 phenomenon occurs (false alarm) or, conversely, that a dangerous phenomenon takes 12 13 place without any issued alarm (missing alarm). Both false and missing alarms are costly to the community served by the EWS. A lower uncertainty degree in the prediction is 14 required to minimize their number and, consequently, costs during the system 15 operation. Efficiency of the EWS is therefore considered with respect to its economic 16 value for the community, rather than merely to the provided safety performance. In 17 18 this sense, alarm activation has to account for the uncertainties associated with each alert threshold and its overcoming, so to minimize false and missing alarms and related 19 costs. 20

Decisional rules regarding actions associated with each alert threshold should be based not only on the mere quantification of thresholds themselves, but also on criteria defining the *sensitivity* of the EWS, intended as setting the activation of the system at some probability of a given threshold to be exceeded.

The most suitable strategy to quantify such probability of threshold exceedance cannot
 be generalized. It is in fact strongly affected by the following peculiarities characterizing
 the EWS in hand:

- the uncertainty of the prediction, which may be reduced by increasing the initial
   investment (by preliminary acquiring more information about physical system
   features, implementing a more reliable monitoring system with higher spatial and
   temporal resolution, elaborating a more sophisticated and accurate predictive
   model);
- the costs suffered by the community in case of false alarm, in turn depending also on
   the kind of actions planned in case of threshold exceedance;

 the costs resulting from a missing alarm, depending on both the event (type and intensity) and resilience of the exposed goods (related to their nature as well as to socio-economic aspects).

In setting up the EWS sensitivity, it should be taken into account that too many false alarms would discredit the system, implying that, over time, the served community would contribute less in carrying out all the required actions after alerts. In short, the sensitivity has to be calibrated on the basis of a cost-benefit analysis, which can be properly carried out only if the uncertainty of model predictions can be estimated after an adequate period of monitoring of the physical system.

10

### 11 3. Evolution stages of a natural hazard: when should the model do the prediction?

In order to generalize a typical architecture for the predictive model, it comes useful to
 account for a conventional sequence of stages describing the evolution of a natural
 phenomenon resulting into a catastrophe (Figure 1):

- (a) the predisposing stage: the cause variables are subject to such changes to induce
   significant modifications of effect variables;
- (b) the triggering and propagation stage: the failure occurs locally (triggering time)and
   propagates from point to point throughout the physical system up to involve it
   entirely;
- (c) the paroxysmal stage: the physical system collapses and the kinematics of the
   system goes on, eventually hitting the exposed goods.
- 22

The duration of each stage may greatly vary, depending on both the kind of phenomenon and on the features of the physical system involved.

In an earthquake hitting structures located at a given site "S", the predisposing stage 25 (a) is determined by the occurrence of the seismic event at the epicenter and is 26 indicated by the first arrival of the seismic waves at the seismometers nearest to the 27 epicenter. The triggering and propagation stage (b) is determined by acceleration 28 values exceeding the threshold for first local damages to structural elements and is 29 monitored by seismic stations located at "S"; the paroxysmal stage (c) consists of the 30 31 collapse of parts of the structures. For this specific example, the duration of stages (a) and (b) is few tens of seconds, while the duration of stage (c) depends on the system 32 33 considered, spanning from seconds for systems like buildings, rock slopes, gas conduits etc., until hours or even days for natural earth slopes, dams, and, in general, systems 34

which collapse is determined by a slow redistribution or propagation of earthquake induced effects.

3 In a rainfall-induced landslide, the predisposing stage (a) is determined by the sequence of rainfall events and by the hydrological processes leading to increase of pore water 4 pressure and worsening slope stability conditions (e.g. Bogaard and Greco, 2015). The 5 triggering and propagation stage (b) spans from the first local slope failure until the 6 7 formation of a slip surface. The paroxysmal stage(c) is the sliding of the mobilized soil 8 mass downhill along the slip surface. In this second example, the duration of each stage is strongly related to the geomorphology of the specific slope and to the kind of 9 landslide (Varnes, 1978), and may vary from minutes (e.g., flow slides in slopes covered 10 with shallow coarse grained soils) to even years (e.g., some earth flows in slopes of fine 11 grained soils). 12

In a snow-avalanche, the *predisposing stage* (a) is determined by snow accumulation and temperature increments; the *triggering and propagation stage* (b) starts when local failures take place within the snow aggregate and ends with a slip surface formation. The *paroxysmal stage* (c) starts when the mass slides downhill. In this example, the duration of stage (a) may be of hours or days, depending on the evolution of atmospheric variables, the duration of stage (b) results undetectable, and the paroxysmal stage lasts only few seconds.

For the case of an overflow in a river, the predisposing stage (a) is a sequence of 20 precipitation events within the watershed, causing a progressive increase of the water 21 level along the river course; in this case, the triggering and propagation stage (b) and 22 23 the paroxysmal stage (c) are hardly distinguishable from each other. In fact, both stages start when the first local overflow takes place, and both develop with the flood 24 propagating around the river. The stage duration depends on the extension and 25 geomorphology of the watershed. The entire phenomenon may last tens of minutes 26 (e.g., flash floods in small streams with relatively small catchment) to several days (e.g., 27 28 large rivers with large watershed).

It is also important to highlight that for most phenomena the triggering event has to be considered as random and, as such, time and location of its occurrence can be predicted only with a probabilistic approach. On the other hand, the predisposing stage can be usually described with physical laws, so that its spatial and temporal evolution can be predicted deterministically by mathematical models.

For instance, the strategies followed for early warning with respect to snow avalanches
 (e.g., Bakkeoi, 1987) neglect the detection of any possible triggering factor. These may
 be internal to the physical system (related to some peculiar morphologies favoring the

susceptibility to local failures) or external (e.g., a skier path cutting transversally the 1 snow layer slope or a rock-mass falling onto the layer). The randomness of such kind of 2 triggering factors makes them undetectable and useless for early warning purposes. 3 However, it should be noted that these factors may become effective only if a 4 predisposing state takes place in terms of snow layer thickness and temperature. This 5 leads to define the different alert levels on the basis of these two variables, for which 6 experimental quantification is easy and reliable. Consequently, the warning does not 7 deal with exactly identifying when, where and what specific triggering factor might 8 9 generate an avalanche.

In general, early warning prediction can be carried out during any of the above-defined 10 evolution stages. The choice of the particular stage should obviously consider that 11 elapsed times needed to predict the event, spread the alarm and reduce people and 12 13 goods exposure must not exceed the time after which the destructive event occurs. On the other side, the limited time available in-between prediction and event should 14 indicate which kind of actions could be reasonably carried out. So, only in some cases 15 it will be possible to consider the opportunity to evacuate all buildings of an entire 16 neighborhood or forbid all exposed streets to traffic and people access. In some cases, 17 18 the small available time only allows some short actions, such as the interruption of dangerous supplied services (gas and electricity) or closure of important infrastructures 19 highly exposed, such as railways or highways. 20

The first step that has to be followed in the development of the predictive tool is hence 21 22 the detailed study of the mechanisms that control the evolution of the phenomenon in hand, and identify which phenomenon stage is the most suitable for the assessment of 23 24 safety conditions. For some problems, the choice necessarily falls into a specific stage, while for others the choice may be multiple. For instance, the slow kinematics of 25 landslides in fine grained soils allows to place the predictive tool in any of the above 26 defined three stages, while the rapid kinematics of rainfall-induced landslides in coarse 27 grained soils prevents considering the paroxysmal stage. 28

29

#### 30 4. The architecture of the predictive model

The second step of the development of the predictive tool is choosing the predictive model. Promptness and reliability are mandatory requirements of the prediction. The promptness is usually obtained by introducing model simplifications, which should however not imply excessive accuracy losses, because they would increase uncertainties and, consequently, false and missing alarms. An increase of model complexity usually corresponds to a reduction in the observational scale of the phenomenon. Complex models can only be applied to slope scale problems, while,
increasing the observational scale from local to regional, progressive simplifications
have to be introduced in the model and, consistently, less ambitious goals have to be
set in terms of reliability.

5 The wide variety of applications for EWS makes it difficult to generalize criteria to guide 6 the choice of the predictive model. It is only possible to refer to some classification 7 criteria, aiming at clarifying the philosophy of the chosen approach, and what 8 ingredients it requires for its best implementation.

9 A first classification criterion distinguish between empirical and physically-based
10 models. Empirical models extract relationships among cause and effect variables from
11 available monitoring data taken over a prolonged time interval. Once set up the
12 empirical relationships, they typically do not take into any account the physics
13 governing the phenomenon. Their reliability essentially depends on the amount,
14 accuracy and representativeness of the available data-set.

On the other hand, physically-based models relate cause and effect variables through mathematical relationships derived straightforwardly from the physical principles governing the considered phenomenon. The mathematical description of the model typically involves the assumption of simplifications that could strongly affect the accuracy of the prediction.

These two categories may also be used contextually in setting up predictive tools consisting of physically-based as well as of empirical steps.

The second criterion of classification refers essentially to physically-based models, and 22 is strictly related to the need for a rapid prediction. It distinguishes between on-line and 23 out-of-line predictions. The formers consist in real-time solving of the model equations, 24 25 updated continuously over time with changes in boundary conditions indicated by field monitoring. The latter, instead, define simple mathematical equations or abaci relating 26 cause and effect variables, by solving the governing equations preliminarily for a 27 28 number of possible scenarios in terms of initial and boundary conditions (e.g, Pagano and Sica, 2013). These simple mathematical equations or abaci represent the predictive 29 tools adopted to rapidly interpret the data from field monitoring. 30

Strictly related with the selection of the model is, finally, the design of the monitoring
system. It has to be consistent with all the choices made about the previously illustrated
points. The considered specific stage of phenomenon evolution, as well as the choice
of the predictive model, unequivocally identify the physical variables to be monitored,
their location and, finally, the number of measurement points.

In the following sections, the different features above highlighted will guide along the
 illustration of some application cases developed in the field of rainfall-induced flow-like
 landslides.

4

#### 5 5. Examples of set up and calibration of the predictive model for early warning

In Italy the destructive potential of rainfall-induced rapid flowslides and debris flows is 6 7 sadly known. The significance of the problem in terms of number of events and victims 8 becomes clear by merely referring to the disasters occurred over the last years in Campania (Cascini and Ferlisi, 2003, Calcaterra et al., 2004; Pagano et al., 2010; Santo 9 et al., 2012), Piedmont (Villar Pellice, occurred in 2008), Liguria (Cinque Terre, occurred 10 in 2011) and Sicily (Maugeri et al., 2011). The rapid kinematics characterizing the post-11 failure behavior of these phenomena implies that the setup of an early warning system 12 may not rely on the analysis of the short-lasting paroxysmal stage (Figure 2). 13

Exception is made for early warning systems implemented along some roads or 14 railways, where the probability that the sliding mass detaching from a slope directly 15 impacts vehicles is small, while the probability that vehicles crash against previously 16 17 fallen mass obstructing the road is much higher. In such cases, the alarm might be launched in case of the feared road invaded by fallen masses. Hence, the alarm itself 18 could be based on promptly gathering the occurrence of slope instabilities by carrying 19 out monitoring of displacements, and inhibiting road access in case of recorded 20 movements exceeding some threshold (Mannara et al., 2009). 21

If the exposed goods are instead likely to be directly impacted by the sliding mass, the triggering of the instability must be predicted in due advance. The time span required to reduce exposure, typically some hours, implies that the prediction should be based on monitoring and interpretation of triggering precursors, carried out already during the predisposing stage.

The phenomena in hand typically involve the mobilization of shallow covers rarely exceeding 2 meters in thickness, induced by rainfall infiltration and related suction drop. Further physical variables governing the phenomenon are effect variables describing soil cover wetting (e.g. degree of saturation, water content, water storage).

The predictive model may be built on empirical bases whereas, for the reference geographical context, historical rainfall related to their effects are available. Alternatively, it is possible to adopt physically-based approaches through which turning, at any time, rainfall into effect variables related to slope stability conditions. Different levels of these effect variables (or, alternatively, of slope stability indices 1 derived from them), may be chosen as the alert thresholds of the early warning system.

2 If the mathematical model of the slope has been properly simplified, it may be possible

3 to operate "on line" by performing model simulations in few minutes.

Recent advances in field monitoring of effect variables, in particular soil suction and/or 4 water content, nowadays offer an alternative approach to the interpretation of rainfall 5 effects. Sensors like tensiometers, heat dissipation probes and TDR probes, in principle 6 7 could directly deliver all the effect variables needed for the assessment of slope stability 8 conditions. However, the spatial variability of soil properties likely makes an EWS relying only on field monitoring of effect variables unreliable. Field data are in fact 9 always affected by local issues, and so they are poorly representative of the whole 10 monitored area, unless an extremely rich network of sensors is installed, which in most 11 cases is unfeasible. Hence, field monitoring should be deployed supplementing, rather 12 13 than replacing, the estimation of effect variables by means of a more or less simplified estimation of rainfall effects. 14

The following application examples refer to single slopes, with extension of few hectares, located in the Lattari Mountains (Campania, southern Italy) and in the basin of Stura di Lanzo (Piedmont, northern Italy).

18 As already pointed out in the Introduction section, the choice of presenting examples all referred to slope scale does not imply that the proposed classifications and 19 procedures are limited to this case. The scale of the system does not intrinsically relate 20 to model features but, rather, to the spatial resolution of the available input data, which 21 affects the entire structure of the EWS. In the following examples, the choice of the 22 23 slope scale is indeed made to show how, when high resolution data are available, the adopted models and procedures for their calibration could be different and, in 24 principle, applicable to any scale. 25

26

#### 27 5.1 Empirical approach based on rainfall records

The example herein reported refers to the chain of Lattari Mountains and, in particular, to an area spreading in-between the towns of Pagani and Nocera Inferiore (Campania, southern Italy). An intensely fractured calcareous bedrock covered by silty volcanic soils characterizes the geology of the site. Volcanic covers have formed due to pyroclastic air-fall deposits generated by eruptions, mainly those of the volcanic complex of Somma-Vesuvius, occurred over the last 40000 years. Several rainfall-induced flow-like landslides have interested these covers over centuries. Numerous phenomena also occurred in the recent past (Table 1), usually triggered along slopes with inclination
 angle between 30° and 40°.

3 A pluviometer installed in 1950, around 3 Km far from the downslope area, provides a daily rainfall series spanning over 50 years (Pagano et al., 2010). During this period, 4 three significant flow-like landslides occurred in 1960, 1972 and 1997 (Table 1). Daily 5 rainfall heights triggering the three phenomena were 87, 77 and 110 mm, respectively. 6 7 Figure 3 shows all the observed daily rainfall heights larger than the minimum value 8 followed by a landslide ( $h_{dL}$  =77mm;  $h_{dL}$ =minimum daily rainfall associated with a landslide), plotted in ascending order. It may be noticed that the condition  $h_{ds}>h_{dL}$ 9 (hds=significant daily rainfall, with "significant" intended as exceeding hdL) was met 39 10 times, but only twice a landslide was actually triggered. This low correspondence 11 between daily rainfalls and landslides depends on the existence of additional 12 13 influencing factors, related to the conditions of the soil cover at the onset of triggering rainfall, which are neglected if only daily rainfall height is considered. Antecedent 14 precipitation, in particular, is supposed to play a crucial role, as it determines the 15 amount of water stored in the cover and lowering soil suction significantly, before the 16 crucial suction drop induced by the triggering rainfall. 17

The effects of antecedent precipitations may be taken into account by assuming that, 18 19 besides the rainfall directly triggering the event (usually identified with rainfall fallen during the last day), they also play an important role in establishing the predisposing 20 conditions for the triggering of a landslide. The duration "x" of the antecedent period 21 22 may be chosen as the one minimizing the number of events ( $h_{ds}$ ,  $h_x$ ) characterized by  $h_x$ similar to the antecedent precipitation, h<sub>xL</sub>, accumulated before the three observed 23 24 landslides. The minimization yielded x=2 months. This corresponds to h<sub>2mL</sub> values for all three landslides of about 500 mm. Over the reference period only 5rainfall histories 25  $(h_{ds}, h_{2m})$  resulted similar to the three  $(h_{dL}, h_{2mL})$  which were followed by a landslide. If 26 this double threshold criterion had been virtually implemented as early warning 27 criterion in the considered area, it would have produced 5 false alarms over 50 years. 28

- 29
- 30
- 31

## 32 5.2 Stochastic approach

Few examples of real-time predictions of the probability of triggering of rainfall-induced landslides in a small area (i.e. a slope or a small catchment) can be found in the literature (e.g. Sirangelo and Versace, 1996; Sirangelo and Braca, 2004; Schmidt et al.,

2008; Greco et al., 2013; Capparelli et al., 2013; Terranova et al., 2015; Manconi and 1 Giordan, 2016; Ozturk et al., 2016). This is due to the intrinsic difficulty of having 2 available historical data sets of rain storms and corresponding landslides occurred in a 3 small area, with enough data to allow reliable estimation of the probability of landslide 4 triggering during extreme (and thus rare) rainfall events. Usually, only few landslides 5 occur at a site during an observation period of typically some decades, so that 6 probabilistic landslide initiation thresholds are mostly defined at regional scale, so to 7 have a rich data set of observed landslides (e.g. Terlien, 1998; Guzzetti et al., 2007; 8 9 2008; Jakob et al., 2012; Ponziani et al., 2012; Segoni et al., 2015; Iadanza et al., 2016). The use of physically based models of infiltration and slope stability can help in the 10 prediction of slope response under conditions different from those actually 11 encountered during the observation period, thus allowing the definition of site-specific 12 landslide initiation thresholds (e.g. Arnone et al., 2011; Ruiz-Villanueva et al., 2011; 13 Tarolli et al., 2011; Papa et al., 2013; Peres and Cancelliere, 2014; Posner and 14 Georgakakos, 2015; Greco and Bogaard, 2016), which can be useful for carrying out 15 stochastic predictions. However, the application of such physically based approaches in 16 operational early warning systems still suffers the involved computational burden, 17 18 which makes difficult carrying out in real time the calculations required for landslide probability assessment. Consequently, empirical models of the relationship between 19 rainfall and slope stability are still preferred for early warning purposes (Sirangelo and 20 Braca, 2004; Greco et al., 2013; Manconi and Giordan, 2016; Ozturk et al., 2016). 21

An example of setting up an early warning predictive model taking into account the uncertainty of the prediction has been developed by coupling a stochastic predictive model of precipitations (Giorgio and Greco, 2009) with the empirical model FLaIR (Sirangelo and Versace, 1996), which yields predictions of the triggering time for rainfall-induced landslides. The same coupling approach may be used with other recently proposed empirical models, such as GA-SAKe (Terranova et al., 2015).

The FlaIR model associates landslide triggering conditions with values of a mobility function Y(t), obtained by a convolution integral of the rainfall history R(t) with a suitable transfer function  $\psi(t)$ , which allows to model a wide variety of geomorphological contexts, taking into account predisposing conditions generated by antecedent rainfalls (liritano et al., 1998; Sirangelo et al., 2003).

The choice of the transfer function and calibration of its parameters are carried out based on the historical rainfalls data records in a way that the Y(t) function may result as a suitable proxy of slope stability conditions. In particular, parameters are calibrated so that peaks of Y(t) correspond to historical landslides, so to identify a threshold Y<sub>cr</sub> that, if exceeded, indicates landslide occurrence. The FLaIR model is currently implemented as predictive model in early warning systems provided for different thresholds of attention, alert and alarm, corresponding to a progressive approach of Y(t) to the Y<sub>cr</sub> threshold. As an example, for the case of Sarno (pyroclastic slopes in southern Italy) the three mentioned thresholds where suggested at values of 0.4Y<sub>cr</sub>, 0.6Y<sub>cr</sub> and 0.8Y<sub>cr</sub>, respectively (Sirangelo and Braca, 2004).

6 The coupling with a stochastic predictive model of rainfall allows adopting the FLaIR 7 model as a predictor of the probability of occurrence of future landslides (Capparelli et 8 al., 2013). In fact, the convolution integral may be separated into two parts, one 9 deterministic, the other random. The first integral computes the convolution of the 10 rainfall history R<sub>obs</sub>(t) until the time at which the prediction is carried out. The second 11 integral computes the convolution of the rainfall history R<sub>pre</sub>(t) predicted for the future 12 time interval t<sub>pre</sub>, the upper bound of which represents the lead time of the prediction:

13 
$$Y(t) = Y_{det} + Y_{pre} = \int_{-\infty}^{t-t_{pre}} \Psi(t-\tau) R_{obs}(\tau) d\tau + \int_{t-t_{pre}}^{t} \Psi(t-\tau) R_{pre}(\tau) d\tau$$
 (1)

The prediction of Y<sub>pre</sub> is carried out by evaluating the probability conditioned to the 14 15 trend of the rainfall observed before prediction. To this aim, the model DRIP (Disaggregated Rectangular Intensity Pulse) is adopted (Heneker et al., 2001). It defines, 16 through an alternating renewal process, the observed alternation of rainfall and dry 17 periods. This process guarantees, in fact, the stochastic independence of a rainfall event 18 from the duration of the immediately preceding dry period as well as from the duration 19 20 and the total rainfall height of the previous rainstorm. This allows carrying out the conditioned prediction Y<sub>pre</sub> by only taking into account the rainfall history observed 21 during the current event, when the prediction is being carried out. 22

The prediction Y<sub>pre</sub> is carried out by a non-parametric approach, by selecting within the historical data set only the N<sub>i</sub> rainfall events meeting the following two conditions: their duration was equal or longer than the observed part of the current rainstorm; along a time interval as long as the lead time, t<sub>pre</sub>, before the prediction, the mobility function increased in the same proportion as it occurred during the last observed t<sub>pre</sub> interval of the current rainfall event.

The rainfall events selected by following this procedure allow computing the expected value of  $Y_{pre}$  and the probability that, at the end of the interval  $t_{pre}$ , the condition Y>Y\* occurs, whatever Y\*. Hence, once alert and alarm thresholds of the mobility function are defined, the sensitivity of the early warning system can be adjusted by setting up the probability of threshold exceedance at which the relevant messages are launched (activation probability), so to obtain the best trade-off between false and missing alarms (Greco et al., 2013).Low values of the activation probabilities result in high number of alerts and alarms, and may lead to wrong activations of the system (false
 alert/alarms). Conversely, a less sensitive system unavoidably increases the number of
 erroneous non-activations of the system (missing alerts-alarms).

The choice of the more suitable values at which setting the activation probabilities 4 represents an important and crucial feature in the setting of an effective early warning 5 system. As already specified, the system sensitivity has to take into account all 6 7 consequences relating with false and missing alarms. For the alert level, it is usually 8 better to set a high sensitivity, since actions determined by alert activations usually do not imply high costs, nor a significant involvement of the served community. The same, 9 however, cannot be stated for the alarm level, as the procedures resulting from alarm 10 spreading usually imply high costs and discomfort for the community. As an example, 11 evacuation of people involve stopping all activities and interruption of all 12 13 infrastructures and services of public utility.

The described approach has been applied to the slope of Pessinetto, 40km North-East of Turin. The slope, oriented towards South-West, with inclination angle between 30° and 35°, is part of the watershed of the river Stura di Lanzo. It is constituted by a metamorphic bed-rock intensively fractured, covered by a clayey-silt. Six debris flows of different magnitude occurred there, within an area of about 1 km<sup>2</sup>, from November 1962 to October 2000. The thickness of mobilized soils ranged between 1.5 and 2.0 m, with soil volumes between few hundreds to 10000 m<sup>3</sup>.

For the calibration of the stochastic model and of the alert system, the pluviometer data recorded in Lanzo, located 6.5 km east of the slope, were available. In particular, the calibration has been carried out by interpreting the hourly rainfall heights recorded between 1 January 1956 and 10 September 1991, during which four of the six recorded landslides occurred. The subsequent data, from 11 September 1991 to 15 June 2004, have been adopted to validate the predictive model and the performance of an EWS based on its predictions.

The critical value for the mobility function, estimated over the calibration period, was  $Y_{cr}$ =168.4 mm.

The minimum duration of a dry period in-between two rainfall events has been set equal to 10 hours. By assuming only rainfall events exceeding 5 mm to be significant for early warning purposes, a series of 1102 rainfall events meeting the requirements in terms of stochastic independency was selected within the calibration period. These selected events were characterized by durations between 1 hour and 182 hours and rainfall heights between 5 mm and 615 mm (Greco et al., 2013).The validation period of the EWS included 456 rain events selected as for the calibration period.

The EWS has been implemented through the definition of two different operational 1 levels: an alert level and an alarm level. The alert triggers as soon as the mobility 2 function is predicted to approach the value of  $Y_a=0.75Y_{cr}$  with a probability higher than 3 a predefined threshold P<sub>1</sub>. The alarm is issued when the probability that Y exceeds the 4 critical value Y<sub>cr</sub> is higher than a second threshold P<sub>2</sub>. The two thresholds are two 5 examples of possible choices of warning thresholds. As it will be shown hereinafter, for 6 a given choice of warning thresholds, the sensitivity of the EWS depends both on the 7 chosen probability thresholds. Predictions are updated with a hourly frequency and 8 9 refer to a lead time interval from 1 to 6 hour later than the prediction time.

Two examples of the potentiality of the predictions of the probability of exceeding the two defined thresholds are given for two rainfall events occurred during the validation period, both followed by landslides. In particular, the reported predictions were carried out with lead times of up to 5 hours.

The first event occurred between 22 and 25 September 1993, and Y<sub>a</sub> and Y<sub>cr</sub> were overtaken54 and 58 hours after the beginning of the rain, respectively. A landslide was triggered after 60 hours. In the second example, a rainfall event occurred between the 12 and 15 October 2000, Y<sub>a</sub> was passed 39 hours after the beginning of the rain storm, K<sub>cr</sub> after 45 hours, and the landslide occurred after 46 hours.

The effectiveness of the stochastic approach for early warning is shown in figures 4 and 19 5. The graphs give the probability of exceeding the alert and alarm thresholds in the 20 following five hours, predicted in real time. During the two considered rainfall events, 21 the system predicted high values of the probability of exceeding both thresholds several 22 23 hours in advance. In particular, assuming the activation probabilities  $P_1=P_2=0.3$ , in both cases (25 September 1993, figure 4; 14 October 2000, figure 5) the alert would have 24 been issued about 9 hours before the landslide, while the alarm would have been 25 launched already 6 hours earlier than the triggering time. 26

Hence, for the chosen values of  $Y_a$  and  $Y_{cr}$ , by properly setting  $P_1$  and  $P_2$ , the EWS would 27 have been capable to issue, in both cases, the alert and alarm messages several hours 28 before the actual landslide triggering. Tables 2 and 2 show the influence of different 29 30 choices for  $P_1$  and  $P_2$  on the performance of the EWS, evaluated in terms of total numbers of missing and false alerts and alarms during the entire validation period. It 31 looks clear that, once the alert and alarm thresholds Y<sub>a</sub> and Y<sub>cr</sub> are defined, the 32 sensitivity of the EWS depends on the chosen activation probability: higher probabilities 33 correspond to larger numbers of missing alarms, and smaller numbers of false alarms. 34

The optimal choice of  $P_1$  and  $P_2$ should be identified by comparing the costs deriving from false and missing alerts and alarms, with the benefits of the true alarms. As already pointed out in the previous sections, such a cost-benefit analysis is of course peculiar
 of the particular considered case.

The capability of issuing the alert some hours earlier than the triggering time is a nontrivial feature of the system, when it is implemented to mitigate risks from phenomena characterized by a very rapid evolution, such as debris flows and other types of fast landslides, as well as flash floods. In these cases, effective measures to prevent damages and victims may be successfully implemented only if the alarm is issued sufficiently earlier than the triggering time of the phenomenon.

9

#### 10 **5.3 Physically based approach**

In the town of Nocera Inferiore a rain gauge, installed in 1997, recorded hourly rainfalls 11 500 m far from the slope where on 4 March 2005 a large landslide was triggered (Figure 12 13 6). The slope had an inclination angle of 40° and was covered with a 2 meters thick layer of silty volcanic soils. Rainfall records are adopted in this example to validate a 14 physically based approach (Pagano et al., 2010), suitable to take into account a number 15 of known influencing factors (e.g. triggering event, antecedent precipitation, 16 17 instantaneous rainfall intensity, evolution of potential infiltration) (Pagano et al., 2008; Rianna et al., 2014a). 18

In modelling the problem, only factors considered of minor importance were neglected,
 according to Pagano et al. (2010). In particular, a one-dimensional infiltration problem
 through an unsaturated rigid medium was set through Richards equations, solved by
 the FEM code SEEP/W (GEOSLOPE 2004).

Hourly rainfall records were adopted to quantify boundary fluxes at the uppermost 23 boundary, while at the lowermost boundary two different limit boundary conditions 24 25 were assumed (Reder et al., 2017) to account for the possible effects exerted by the fractured bedrock on the silty volcanic cover: a seepage surface condition, which 26 simulates the capillary barrier effect under the hypothesis that fractures are empty; a 27 flux regulated by the unit gradient, which instead approaches the case of fractures filled 28 with the same material as that constituting the cover. The hydraulic properties of the 29 soil, i.e. water retention curve and hydraulic conductivity function, were obtained by 30 means of laboratory tests (Nicotera and Papa, 2007), as well as by coupled 31 measurements of soil matric suction (Jet-fill tensiometers) and volumetric water 32 content (TDR) carried out in a lysimeter (Rianna et al., 2014b). 33

Results yielded by the analyses (Reder et al., 2017) in terms of suction evolution refer to the hydrological year 2004-2005 (Figure 7), which includes the landslide event. They

clearly show how the predictions indicate a singularity at the triggering time, consisting 1 in a drop of suction throughout the cover below3kPafor both boundary condition-types 2 assumed at the bottom. Analyses conducted for the whole historical series of recorded 3 rainfalls, covering a time interval of 10 years including the landslide (Pagano et al., 4 2010), indicate that the same singularity is yielded by the prediction only once more. 5 Hence, if this singularity (suction below 3 kPa throughout the cover) had been adopted 6 as an alarm criterion, the number of false alarms would have resulted significantly low. 7 Furthermore, the short time required to update the prediction (few minutes) is 8 9 consistent with the requirement of promptness of an EWS and allows carrying out "in line" predictions. 10

11

#### 12 6. CONCLUSIONS

After preliminarily analyzing the reasons which may lead a community to adopt an EWS, 13 14 in place of structural approaches, to mitigate risks associated with natural hazards, the paper identifies the key elements of an EWS, which make it effective in accomplishing 15 the task of continuously checking the safety of a system. In particular, the work 16 highlights the importance of the accuracy of the prediction of the future evolution of 17 18 the system, which is the feature allowing the minimization of false and missing alarms. Then, the definition of three evolution stages of natural hazards is proposed, so to set 19 rational criteria to identify the time at which the prediction should be carried out within 20 an EWS. In fact, depending on the characteristics of the hazardous phenomenon and 21 on the time required for the prediction, the chosen stage should allow deploying in due 22 23 time the actions aiming at reducing people and goods exposure.

Two further classification criteria are also adopted throughout the paper: the wellknown distinction between empirical and physically-based models; and the distinction between on-line and off-line predictions, never adopted in the field of water-related natural hazards.

The practical application of the proposed evolution framing requires detailed physical knowledge of how the phenomenon develops over time and of the variables which can be used as a proxy of its evolution. This novel framework for EWS setting up attempts to bring some order in their design procedures, and is introduced with reference to various kinds of natural hazards, as in principle it is suitable of general application. Nonetheless, the paper is mainly focused on water-related natural hazards, and particularly to landslides, for which some application examples are given.

With reference to two different landslide phenomena, namely flow-like landslides and 1 debris flows, both characterized by rapid evolution, the paper describes examples of 2 application of the proposed framework. First, the considered natural hazards are 3 analyzed in terms of their possible evolution stages. Then, the most suitable stage for 4 implementing the prediction is identified, along with cause and effect variables suitable 5 to characterize its evolution and to assess system safety conditions. The presented 6 examples show how either empirical or physically-based models may be adopted, and 7 how prediction uncertainty can be considered in setting up the sensitivity of an EWS. 8

9 The proposed frame and examples of application show how, to design and set-up an 10 effective EWS (i.e. choosing the predictive model, the prediction time, the alert and 11 alarm thresholds and their sensitivity, the mitigation actions allowed by the obtained 12 lead time of prediction), an in-depth analysis of the physical characteristics of the 13 hazardous phenomenon is mandatory.

14

#### 15 **References**

Alfieri L., Salamon P., Pappenberger F., Wetterhall F., Thielen J.: Operational early
 warning systems for water-related hazards in Europe. Environmental Science& Policy,
 21, 35–49, <u>http://dx.doi.org/10.1016/j.envsci.2012.01.008</u>, 2012

Alfieri L., Thielen J.: A European precipitation index for extreme rain-storm and flash
 flood early warning. Meteorological Applications, 22, 3–13,
 http://dx.doi.org/10.1002/met.1328, 2015

Arnone E., Noto L.V., Lepore C., Bras R.L.: Physically-based and distributed approach to
 analyze rainfall-triggered landslides at watershed scale, Geomorphology, 133, 121-131,
 http://dx.doi.org/10.1016/j.geomorph.2011.03.019, 2011

Bakkehoi S.: Snow avalanche prediction using a probabilistic method. Avalanche
 Formation, Movement and Effects, Proceedings of the Davos Symposium, September
 1986, IAHS Publ. 162,1986

Basher R.: Global early warning systems for natural hazards: systematic and people
centred. Philosophical Transactions of the Royal Society A, 364, 2167-2182,
http://dx.doi.org/10.1098/rsta.2006.1819, 2006

Baum R.L., Godt J.W.: Early warning of rainfall-induced shallow landslides and debris flows in the USA, Landslides, 7(3), 259–272, <u>http://dx.doi.org/10.1007/s10346-009-</u> 0177-0, 2010 Bogaard T.A., Greco R.: Landslide hydrology: from hydrology to pore pressure, WIREs
 Water,3(3), 439-459, http://dx.doi.org/10.1002/wat2.1126, 2015

Calcaterra D., de Riso R., Evangelista A., et al.: Slope instabilities in the pyroclastic
deposits of the Phlegraean district and the carbonate Apennine (Campania, Italy),
Proceedings of an International Workshop on Occurrence and Mechanisms of Flows in
Natural Slopes and Earthfills held in Sorrento, Italy, 14-16 May 2003, 61-75, 2004

Calvello M., Piciullo L.: Assessing the performance of regional landslide early warning
models: the EDuMaP method, Natural Hazards Earth System Sciences, 16, 103-122,
https://doi.org/10.5194/nhess-16-103-2016, 2016

Capparelli G., Giorgio M., Greco R.:Shallow Landslides Risk Mitigation by Early Warning:
 The Sarno Case, in Margottini et al (Eds), Landslide Science and Practice, Springer Verlag, Berlin, 6, 767-772, http://dx.doi.org/10.1007/978-3-642-31319-698, 2013

Capparelli G., Tiranti D.: Application of the MoniFLaIR early warning system for rainfall induced landslides in Piedmont region (Italy), Landslides, 7(4), 401-410,
 <u>http://dx.doi.org/10.1007/s10346-009-0189-9</u>, 2010

Capparelli G., Versace P.: FLaIR and SUSHI: two mathematical models for early warning
 of landslides induced by rainfall, Landslides, 8(1), 67-79,
 <u>http://dx.doi.org/10.1007/s10346-010-0228-6</u>, 2011

Cascini L., Ferlisi S.: Occurrence and consequences of flowslides: a case study,
 Proceedings of an International Conference on Fast Slope Movements – Prediction and
 Prevention for Risk Mitigation held in Napoli, 11-13 May 2003,1, 85-92, 2003

Chleborad A.F., Baum R.L., Godt J.W.: A prototype system for forecasting landslides in
the Seattle, Washington, area, in Baum R.L., Godt J.W., Highland L.M. (Eds.),
Engineering geology and landslides of the Seattle, Washington, area, Geological Society
of America Reviews in Engineering Geology, Geological Society of America, Boulder, XX,
103–120, <u>http://dx.doi.org/10.1130/2008.4020(06)</u>, 2008

Cranston M.D., Tavendale A.C.W.: Advances in operational flood forecasting in
 Scotland, Proceedings of the Institution of Civil Engineers - Water Management, 165(2),
 69-87, http://doi.org/10.1680/wama.2012.165.2.79, 2012

30

de Riso R, Budetta P, Calcaterra D, Santo A: Riflessioni sul comportamento delle colate
rapide non incanalate della Campania, alla luce delle conoscenze pregresse - Proc
National Conf on La Mitigazione del Rischio da Colate di Fango, Napoli, May, 2-3, 2005:
81-92, 2007, in Italian

de Saint-Aubin C., Garandeau L., Janet B., Javelle P.: A new French flash flood warning
service, in Samuels P., Klijn F., Lang M. (Eds.), E3S Web of Conferences, 3rd European
Conference on Flood Risk Management, FLOODrisk 2016, Lyon, France, 17-21 October
2016, EDP Sciences, Les Ulis, 7, 18-24, <u>http://doi.org/10.1051/e3sconf/20160718024</u>,

6 2016

1

7 Eichenberger J., Ferrari A., Laloui L.: Early warning thresholds for partially saturated
8 slopes in volcanic ashes, Computers and Geotechnics, 49, 79–89,
9 <u>http://dx.doi.org/10.1016/j.compgeo.2012.11.002</u>, 2013

GEO-SLOPE: SEEP/W for finite element seepage analysis, GEO-SLOPE International,
 Calgary, 2004

Giorgio M., Greco R.: Rainfall height stochastic modelling as a support tool for floods
 and flowslides early warning, Water Engineering for a Sustainable Environment,
 Proceedings of XXXIII IAHR Congress. Vancouver, International Association of Hydraulic
 Engineering & Research, August 2009, 6812-6819, 2009

Greco R., Bogaard T.A.: The influence of non-linear hydraulic behavior of slope soil
covers on rainfall intensity-duration thresholds, in S. Aversa et al (Eds), Landslides and
Engineered Slopes. Experience, Theory and Practice, 2, 1021-1025, Taylor and Francis,
2016

Greco R., Giorgio M., Capparelli G., Versace P.: Early warning of rainfall-induced
 landslides based on empirical mobility function predictor, Engineering Geology, 153,
 68-79, http://dx.doi.org/10.1016/j.enggeo.2012.11.009, 2013

Guzzetti F., Peruccacci S., Rossi M., Stark C.P.: Rainfall thresholds for the initiation of
 landslides in central and southern Europe. Meteorology and Atmospheric Physics, 98,
 239–267, http://dx.doi.org/10.1007/s00703-007-0262-7, 2007

Guzzetti F., Peruccacci S., Rossi M., Stark C.P.: The rainfall intensity-duration control of
 shallow landslides and debris flows: an update, Landslides, 5, 3–17,
 <u>http://dx.doi.org/10.1007/s10346-007-0112-1</u>, 2008

Heneker T.M., Lambert M.F., Kuczera G.: A point rainfall model for risk-based design.
 Journal of Hydrology, 247 (1–2), 54–71, <u>http://dx.doi.org/10.1016/S0022-</u>
 <u>1694(01)00361-4</u>, 2001

Iadanza C., Trigila A., Napolitano F.:Identification and characterization of rainfall events
 responsible for triggering of debris flows and shallow landslides, Journal of Hydrology,

<sup>34</sup> 541, 230-245, <u>http://dx.doi.org/10.1016/j.jhydrol.2016.01.018</u>, 2016

liritano G., Versace P., Sirangelo B.: Real-time estimation of hazard for landslides
 triggered by rainfall, Environmental Geology, 35(2-3), 175-183,
 <u>http://dx.doi.org/10.1007/s002540050303</u>, 1998

Intrieri E., Gigli G., Mugnai F., Fanti R., Casagli N.: Design and implementation of a
landslide early warning system. Engineering Geology, 147–148,
http://doi.org/10.1016/j.enggeo.2012.07.017,2012

Intrieri E., Gigli G., Casagli N., Nadim F.: Brief Communication: "Landslide Early Warning
System: toolbox and general concepts", Natural Hazards Earth System Sciences, 13, 85–
90, http://dx.doi.org/10.5194/nhess-13-85-2013, 2013

Jakob M., Owen T., Simpson T.: A regional real-time debris-flow warning system for the
 District of North Vancouver, Canada, Landslides, 9, 165–178,
 <u>http://dx.doi.org/10.1007/s10346-011-0282-8</u>, 2012

Keefer D.K., Wilson R.C., Mark R.K., Brabb E.E., Brown W.M., Ellen S.D., Harp E.L.,
 Wieczorek G.F., Alger C.S., Zatkin R.S.: Real-time landslide warning during heavy rainfall,
 Science, 238, 921–925, <u>http://dx.doi.org/10.1126/science.238.4829.921</u>, 1987

Liu X., Liu Y., Li L., Ren Y.: Disaster monitoring and early-warning system for snow
 avalanche along Tianshan highway, IEEE International Geoscience and Remote Sensing
 Symposium, IGARSS 2009, Cape Town. South Africa; 12-17 July 2009, IEEE Geoscience
 and Remote Sensing Society, 2, 11634-11637,
 <u>http://dx.doi.org/10.1109/IGARSS.2009.5418166</u>, 2009

Ma H., Chi F.: Major Technologies for Safe Construction of High Earth-Rockfill Dams,
 Engineering, 2, 498–509, <u>http://dx.doi.org/10.1016/J.ENG.2016.04.001</u>, 2016

Manconi A., Giordan D.: Landslide failure forecast in near-real-time. Geomatics, Natural
Hazards and Risk, 7(2), 639-648, <u>http://dx.doi.org/10.1080/19475705.2014.942388</u>,
2016

Mannara G., Sarnataro A., Sposito P., Piccolo G., Ciancia N., Infante S.: Rete di sensori
 accelerometrici MEMS per il monitoraggio in continuo di rilievi franosi in ambito
 ferroviario, SEF09 Sicurezza ed Esercizio Ferroviario I Convegno Nazionale, Roma 20
 marzo 2009, 2009 (in Italian)

Martelloni G., Segoni S., Fanti R., Catani F.: Rainfall thresholds for the forecasting of landslide occurrence at regional scale, Landslides, 9(4), 485-495, http://dx.doi.org/10.1007/s10346-011-0308-2, 2012

Maugeri M., Motta E.: Slope Failure. Effects of Heavy Rainfalls on Slope Behavior: The October 1, 2009 Disaster of Messina (Italy), in Iai S. (Ed), Geotechnics and Earthquake

- Geotechnics Towards Global Sustainability, Geotechnical, Geological, and Earthquake
   Engineering, Springer, Dordrecht, 15, 2011
- 3 Michoud C., Bazin S., Blikra L.H., Derron M.H., Jaboyedoff M.: Experiences from site-
- 4 specific landslide early warning systems, Natural Hazards and Earth System Sciences,
- 5 13, 2659-2673, <u>http://dx.doi.org/10.5194/nhess-13-2659-2013</u>, 2013
- Ortigao B., Justi M.G. 2004: Rio-Watch: the Rio de Janeiro landslide alarm system,
  Geotechnical News, 22(3), 28–31, 2013
- Nicotera M., Papa R.: Comportamento idraulico e meccanico della serie piroclastica di
   Monteforte Irpino, Progetto PETIT-OSA Monitoraggio Frane: Contributo alle
   Conoscenze sulla Franosità in Campania, 272-280. ARACNE, 2007 (in Italian)
- Ozturk U., Tarakegn Y.A., Longoni L., Brambilla D., Papini M., Jensen J.: A simplified
   early-warning system for imminent landslide prediction based on failure index fragility
   curves developed through numerical analysis, Geomatics, Natural Hazards and Risk,
   7(4), 1406-1425, http://dx.doi.org/10.1080/19475705.2015.1058863, 2016
- Pagano L., Picarelli L., Rianna G., Urciuoli G.: A simple numerical procedure for timely
   prediction of precipitation-induced landslides in unsaturated pyroclastic soils,
   Landslides, 7, 273-289, http://dx.doi.org/10.1007/s10346-010-0216-x, 2010
- Pagano L., Zingariello M.C., Vinale F.: A large physical model to simulate flowslides in
   pyroclastic soils, Proc First European Conf on Unsaturated Soils: Advances in Geo Engineering, Durham, 205-213, 2008
- Pagano L., Sica S.: Earthquake Early Warning for Earth Dams: Concepts and Objectives,
   Natural Hazards, 66, 303–318, <u>http://dx.doi.org/10.1007/s11069-012-0486-9, 2013</u>
- Papa M.N., Medina V., Ciervo F., Bateman A.: Derivation of critical rainfall thresholds
  for shallow landslides as a tool for debris flow early warning systems, Hydrology and
  Earth System Sciences, 17, 4095–4107, http://dx.doi.org/10.5194/hess-17-4095-2013,
  2013
- Peres D.J., Cancelliere A.: Derivation and evaluation of landslide-triggering thresholds
   by a Monte Carlo approach, Hydrology and Earth System Sciences, 18, 4913–4931,
   <u>http://dx.doi.org/10.5194/hess-18-4913-2014</u>, 2014
- Piciullo L., Gariano S.L., Melillo M., Brunetti M.T., Peruccacci S., Guzzetti F., Calvello M.:
   Definition and performance of a threshold-based regional early warning model for
   rainfall-induced landslides, Landslides, 14(3), 995-1008,
   <u>http://dx.doi.org/10.1007/s10346-016-0750-2</u>, 2017

Ponziani F., Pandolfo C., Stelluti M., Berni N., Brocca L., Moramarco T.: Assessment of
 rainfall thresholds and soil moisture modeling for operational hydrogeological risk
 prevention in the Umbria region (central Italy), Landslides, 9, 229–237,
 <u>http://dx.doi.org/10.1007/s10346-011-0287-3</u>, 2012

Posner A.J., Georgakakos K.P.: Soil moisture and precipitation thresholds for real-time
 landslide prediction in El Salvador, Landslides, 12, 1179–1196,
 http://dx.doi.org/10.1007/s10346-015-0618-x, 2015

Pumo D., Francipane A., Lo Conti F., Arnone E., Bitonto P., Viola F., La Loggia G., Noto
 L.V.: The SESAMO early warning system for rainfall-triggered landslides, Journal of

10 Hydroinformatics, 18(2), 256-276, http://dx.doi.org/10.2166/hydro.2015.060, 2016

Rabuffetti D., Barbero S.: Operational hydro-meteorological warning and real-time
 flood forecasting: the Piemonte Region case study, Hydrology and Earth System
 Sciences, 9, 457-466, https://doi.org/10.5194/hess-9-457-2005, 2005

Reder A., Pagano, L., Picarelli, L., Rianna G.: The role of the lowermost boundary
conditions in the hydrological response of shallow sloping covers, Landslides 14, 3, 861873, <u>https://doi.org/10.1007/s10346-016-0753-z</u>, 2017

Rianna G., Pagano L., Urciuoli G.: Rainfall patterns triggering shallow flowslides in
 pyroclastic soils, Engineering Geology, 174, 22-35,
 http://dx.doi.org/10.1016/j.enggeo.2014.03.004, 2014a

Rianna G., Pagano L., Urciuoli G.: Investigation of soil-atmosphere interaction in
 pyroclastic soils, Journal of Hydrology, 510, 480-492,
 http://dx.doi.org/10.1016/j.jhydrol.2013.12.042, 2014b

Ruiz-Villanueva V., BodoqueJ.M., Díez-Herrero A., Calvo C.: Triggering threshold
 precipitation and soil hydrological characteristics of shallow landslides in granitic
 landscapes, Geomorphology, 133, 178-189,
 <u>http://dx.doi.org/10.1016/j.geomorph.2011.05.018</u>, 2011

Santo A., Di Crescenzo G., Del Prete S., Di Iorio L.: The Ischia island flash flood of
November 2009 (Italy): Phenomenon analysis and flood hazard. Physics and Chemistry
of the Earth, Parts A/B/C, 49, 3-17, https://doi.org/10.1016/j.pce.2011.12.004, 2012

Schmidt J., Turek G., Clark M.P., Uddstrom M., Dymond J.R.: Probabilistic forecasting of
 shallow, rainfall-triggered landslides using real-time numerical weather predictions,
 Natural Hazards and Earth System Sciences, 8, 349–357,
 http://dx.doi.org/10.5194/nhess-8-349-2008, 2008

1 Segoni S., Battistini A., Rossi G., Rosi A., Lagomarsino D., Catani F., Moretti S., Casagli

2 N.: Technical Note: An operational landslide early warning system at regional scale

3 based on space-time-variable rainfall thresholds, Natural Hazards and Earth System

4 Sciences, 15, 853–861, <u>http://dx.doi.org/10.5194/nhess-15-853-2015</u>, 2015

Segoni S., Rossi G., Rosi A., Catani, F.: Landslides triggered by rainfall: a semiautomated
procedure to define consistent intensity-duration thresholds, Computers &
Geosciences, 63, 123–131, http://dx.doi.org/10.1016/j.cageo.2013.10.009,2014

7 Geosciences, 05, 125–151, http://dx.doi.org/10.1010/j.cage0.2015.10.009,2014

8 Sirangelo B., Braca G.: Identification of hazard conditions for mudflow occurrence by
9 hydrological model. Application of FLaIR model to Sarno warning system, Engineering

<sup>10</sup> Geology, 73, 267–276, <u>http://dx.doi.org/10.1016/j.enggeo.2004.01.008</u>, 2004

Sirangelo B., Versace P.: A real time forecasting model for landslides triggered by
 rainfall, Meccanica, 31(1), 73–85, <u>http://dx.doi.org/10.1007/BF00444156</u>, 1996

Sirangelo B., Versace P., Capparelli G.: Forwarning model for landslides triggered by
 rainfall based on the analysis of historical data file, in Servat E., Najem W., Leduc C.,
 Shakeel A. (Eds.), Hydrology of the Mediterranean and Semiarid Regions, IAHS Publ.,
 278, 298-304, 2003

Tarolli P., Borga M., Chang K.T., Chiang S.H.: Modeling shallow landsliding susceptibility
 by incorporating heavy rainfall statistical properties. Geomorphology, 133, 199-211,
 http://dx.doi.org/10.1016/j.geomorph.2011.02.033, 2011

Terlien M.T.J.: The determination of statistical and deterministic hydrological landslide triggering thresholds, Environmental Geology, 35(2–3), 124-130,
 http://dx.doi.org/10.1007/s002540050299, 1998

Terranova O.G., Gariano S.L., laquinta P., lovine G.G.R.: GASAKe: forecasting landslide
 activations by a genetic-algorithms-based hydrological model, Geoscientific Model
 Development, 8, 1955-1978, http://dx.doi.org/10.5194/gmd-8-1955-2015, 2015

Tiranti D., Cremonini R., Marco F., Gaeta A.R., Barbero S.: The DEFENSE (Debris Flows
triggered by storms-Nowcasting SystEm): an early warning system for torrential
processes by radar storm tracking using a Geographic Information System (GIS),
Computers & Geosciences, 70,96-109, http://dx.doi.org/10.1016/j.cageo.2014.05.004,
2014

Tiranti D., Rabuffetti D.: Estimation of rainfall thresholds triggering shallow landslides
 for an operational warning system implementation, Landslides, 7, 471-481,
 <u>http://dx.doi.org/10.1007/s10346-010-0198-8</u>, 2010

Codice campo modificato

UN-ISDR (United Nations Inter-Agency Secretariat of theInternational Strategy for
 Disaster Reduction): Hyogo framework for action 2005–2015: building the resilience of
 nations and communities to disasters, World Conference on Disaster Reduction, Kobe,
 Japan, January 2005 (<u>http://www.unisdr.org/eng/hfa/docs/Hyogo-framework-</u>
 <u>foraction-english.pdf</u>), 2005

UN-ISDR (United Nations Inter-Agency Secretariat of the International Strategy for 6 7 Disaster Reduction) (2006). Global Survey of Early Warning Systems: An assessment of capacities, gaps and opportunities towards building a comprehensive global early 8 warning system for all natural hazards 9 (http://www.unisdr.org/2006/ppew/inforesources/ewc3/Global-Survey-of-Early-10 Warning-Systems.pdf), 2006 11

Varnes, D. J.: Slope movement types and processes, in Schuster, R. L. and Krizek, R. J.
(Eds), Special Report 176: Landslides: Analysis and Control. Transportation and Road
Research Board, National Academy of Science, Washington D. C., 11-33, 1978.

- 15

   16

   17

   18

   19

   20

   21

   22

   23
- 24
- 25

Location	Town	Date	н	L (m)	V	
		(y.m.d)	(m)		(m³)	
S. Pantaleone	Pagani	1960.12.08				
Scrajo	Vico Equense	1966. 11.23	220	300	10,000	
Monte	Gragnano	1971.01.02	205	375	7,500	
Pendolo						
S. Pantaleone	Pagani	1972.03.06	90	180	5,000	

Codice campo modificato

S. Pantaleone	Pagani	1997.01.10	135	240	4,500	
Pozzano	Castellammare	1997.01.10 440		750	40,000	
	di Stabia					
Monte	Gragnano	1997.01.10	125	210	4,500	
Pendolo						
Monte	Pimonte	1997.01.10	125	135	4,300	
Pendolo						
Corsara	Corbara	1997.01.10	160	135	750	
Ospedaletto	Ospedaletto	1997.01.10	250	450	10,000	
S. Egidio M.	S. Egidio	1997.01.10	215	500	10,000	
Albino						
Molina di	Vietri sul Mare	1998.05.05	570	1700	9,000	
Vietri						
S.Egidio M.	Nocera Inferiore	2005.03.04	295	530	33,000	
Albino						
Table 1						

1 Ta

2

d <sub>pre</sub> [h]	P <sub>1</sub> =0.2		P <sub>1</sub> =0.25			P <sub>1</sub> =0.3			
	$N_{1L}$	$N_{1F}$	N <sub>1M</sub>	$N_{1L}$	$N_{1F}$	$N_{1M}$	N <sub>1L</sub>	$N_{1F}$	$N_{1M}$
2	23	7	2	19	3	2	18	2	2
4	27	11	3	22	7	4	21	6	4
6	31	12	3	25	7	4	22	5	5

Table 2

d <sub>pre</sub> [h]	P <sub>2</sub> =0.2			P <sub>2</sub> =0.25			P <sub>2</sub> =0.3		
	$N_{2L}$	$N_{2F}$	$N_{2M}$	$N_{2L}$	$N_{2F}$	$N_{2M}$	$N_{2L}$	$N_{2F}$	$N_{2M}$
2	16	4	0	14	2	0	11	1	2
4	22	10	0	17	5	0	15	4	1
6	29	16	1	20	7	1	13	4	5

Table 3

# 3 CAPTIONS

4 Figure 1. Evolution stages of a collapse mechanism

Figure 2. Evolution stages of collapse mechanism in rainfall-induced landslides featured
 by rapid kinematic

Figure 3 - Daily and antecedent-bi-monthly rainfalls recorded at the Nocera Inferiore
 site and corresponding to significant events (red circles are associated with landslide
 triggering, green circle with rainfall histories similar to those resulting in landslides)

6

Figure 4. Stochastic approach to early warning: probability of exceeding alert and alarm
thresholds of the mobility function at the slope of Pessinetto, predicted in real time (the
upper panel reports the observed hyetograph) during the storm of 22.09.1993, when
an earth flow occurred 60 hours after the beginning of the rain.

11

Figure 5. Stochastic approach to early warning: probability of exceeding alert and alarm thresholds of the mobility function at the slope of Pessinetto, predicted in real time (the upper panel reports the observed hyetograph) during the storm of 12.10.2000, when an earth flow occurred 46 hours after the beginning of the rain.

16

17 Figure6. The Nocera Inferiore 2005 landslide area (Pagano et al., 2010, modified)

Figure7. Prediction of suction evolution over the hydrological year of the Nocera
Inferiore 2005 landslide at four different depths and for two different hydraulic
conditions at the lowermost boundary (Reder et al., 2017, modified)

21

Table 1. Major flow-like landslides triggered since 1950 in the Mts. Lattari (H =
difference in elevation between the main crown and the tip of the accumulation zone;
L = projection on the horizontal plane of the distance between the crown and the tip; V
= volume of the landslide body) (modified from de Riso et al., 2007)

26

Table 2.Stochastic approach to early warning: numbers of launched ( $N_{1L}$ ), false ( $N_{1F}$ ) and missing ( $N_{1M}$ ) alerts at the slope of Pessinetto for three different lead times  $t_{pre}$  and three different choices of the probability of alert activation P<sub>1</sub>.For each lead time, the system carried out 964 predictions between 11 September 1991 and 15 June 2004 (validation period).

32

- 1 Table 3. Stochastic approach to early warning: numbers of launched  $(N_{2L})$ , false  $(N_{2F})$
- $_{2}$   $\,$  and missing (N\_{2M}) alarms at the slope of Pessinetto for three different lead times  $t_{pre}$
- 3 and three different choices of the probability of alarm activation P<sub>2</sub>. For each lead time,
- 4 the system carried out 964 predictions between 11 September 1991 and 15 June 2004
- 5 (validation period).





time needed to eliminate people exposure

Figure 1





Figure 3



Figure 4



Figure 5



Figure 6



