



1	Characterizing severe weather potential in synoptically weakly forced
2	thunderstorm environments
3	Ву
4	
5	Paul W. Miller [*]
6	
7	and
8	
9	Thomas L. Mote
10	
11	Department of Geography
12	University of Georgia, Athens, Georgia
13	
14	*Corresponding author address: Department of Geography, 210 Field Street, Room 204
15	Athens, GA 30602. Email: paul.miller@uga.edu
-	
16	
10	
17	
18	
19	





21 Abstract

22 Weakly forced thunderstorms (WFTs), short-lived convection forming in synoptically 23 quiescent regimes, are a contemporary forecasting challenge. The convective environments that 24 support severe WFTs are often similar to those that yield only nonsevere WFTs, and additionally, 25 only a small proportion individual WFTs will ultimately produce severe weather. The purpose of this study is to better characterize the relative severe weather potential in these settings as a 26 27 function of the convective environment. Thirty near-storm convective parameters for >200,000 28 WFTs in the Southeast United States are calculated from a high-resolution numerical forecasting 29 model, the Rapid Refresh (RAP). For each parameter, the relative likelihood of WFT days with at 30 least one severe weather event is assessed along a moving threshold. Parameters (and the values 31 of them) that reliably separate severe-weather-supporting from nonsevere WFT days are 32 highlighted.

33 Only two convective parameters, vertical totals (VT) and total totals (TT), appreciably 34 differentiate severe-wind-supporting and severe-hail-supporting days from nonsevere WFT days. 35 When VTs exceeded values between 24.6–25.1°C or TTs between 46.5–47.3°C, severe-wind days 36 were roughly 5x more likely. Meanwhile, severe-hail days became roughly 10x more likely when 37 VTs exceeded 24.4–26.0°C or TTs exceeded 46.3–49.2°C. The stronger performance of VT and 38 TT is partly attributed to the more accurate representation of these parameters in the numerical 39 model. Under-reporting of severe weather and model error are posited to exacerbate the forecasting 40 challenge by obscuring the subtle convective environmental differences enhancing storm severity. 41

42 Keywords: weakly forced thunderstorms, pulse thunderstorms, storm environments, severe

43 weather





44 **1. Introduction**

45 Weakly forced thunderstorms (WFTs), convection forming in synoptically benign, weakly sheared environments, are a dual forecasting challenge. Not only is the exact location and time of 46 47 convective initiation difficult to predict, but once present, the successful differentiation of severe 48 WFTs from their benign counterparts is equally demanding. Consequently, severe weather 49 warnings issued on WFTs in the U.S. are less accurate than more organized storm modes, such as 50 squall lines and supercells (Guillot et al., 2008). American operational meteorologists have coined 51 these severe WFTs "pulse thunderstorms" because the surge of the updraft that produces the severe 52 weather occurs in a brief "pulse" (Miller and Mote, 2017). The United States National Weather Service defines "severe weather" as any of the following: winds ≥ 26 m s⁻¹, hail ≥ 0.56 cm in 53 54 diameter, or a tornado.

55 Environments thought to support pulse thunderstorms are typically characterized by weak vertical wind shear and strong convective available potential energy (CAPE). However, not all 56 57 weak-shear, high-CAPE environments facilitate pulse thunderstorms, nor are all pulse 58 thunderstorms confined to environments with the weakest shear and/or strongest instability. The 59 result is a low signal-to-noise ratio (SNR) which obstructs the reliable discernment of pulse-60 supporting environments. In this context, the "signal" refers to the true difference between the large-scale convective environments that support severe weather and those that do not. Meanwhile, 61 62 the "noise" is represented the many processes than might cause storms to produce (not produce) 63 severe weather in an environment where it was not expected (expected). Cell interactions, stabilization from prior convection, surface convergence, locally enhanced shear, etc, can act as 64 noise in the operational setting. 65





66 Prior research directed at pulse thunderstorms is limited, and work has not typically 67 included a representative proportion of nonsevere WFTs in their samples (Atkins and Wakimoto, 68 1991; Cerniglia and Snyder, 2002). If the sample contains too many pulse thunderstorms, the SNR 69 may be artificially bolstered, results overstated, and the potential reliability in an operational 70 setting diminished. For instance, in a meta-analysis of studies pertaining to new lightning-based storm warning techniques, Murphy (2017) found that the studies' reported FARs were directly 71 72 proportional to the fraction of nonsevere storms contained in the sample. Samples that included a 73 realistic ratio of severe-to-nonsevere storms demonstrated the weakest skill scores.

74 Most research considering pulse thunderstorms in the Southeast U.S. has typically focused 75 on one of its primary severe weather mechanisms: the wet microburst. Severe wet microbursts 76 generally occur in atmospheres characterized by a deep moist layer extending from the surface to 77 4–5 km above ground level (Johns and Doswell, 1992). Above the moist layer lies a mid-level dry 78 layer with lower equivalent potential temperature values (θ_e). In wet microburst environments, the 79 difference between the maximum θ_e observed just above the surface and the minimum θ_e aloft 80 exceeded 20 K, whereas non-microburst-producing thunderstorm days had differences less than 81 13 K (Atkins and Wakimoto, 1991; Roberts and Wilson, 1989; Stewart, 1991; Wheeler and Spratt, 82 1995). However, Atkins and Wakimoto (1991) examined only 14 microburst days versus three non-microburst days. Adding to the uncertainty, James and Markowski (2010) challenged the role 83 84 of mid-level dry air in severe weather production. The results of their cloud-scale modeling 85 experiment indicated that, for all but the highest instabilities tested, drier mid-level air did not 86 correspond to increased downdraft and cold pool intensity.

87 Building on these findings, several severe weather forecasting parameters have been 88 developed to distill the atmosphere's vertical thermodynamic profile into a single value





89 representing the damaging wind potential. McCann (1994) developed a microburst-predicting 90 "wind index" (WINDEX) to be used in the forecasting of wet downburst potential. However, 91 although WINDEX performed well when tested in known microburst environments, no null cases 92 were presented (McCann, 1994). Additional severe wind potential indices include the wind 93 damage parameter and the microburst index described by the United States Storm Prediction 94 Center (SPC; http://www.spc.noaa.gov/exper/soundings/help/index.html). Tools such as total 95 totals, k-index, the severe weather and threat (SWEAT) index, etc, are also commonly used to 96 forecast convective potential as well as the severity of thunderstorms.

97 However, the comparative utility of these environmental parameters within weakly forced 98 regimes is unclear, particularly when they are tested with a realistic proportion of severe storms. 99 Many of the results above were obtained by analyzing relatively small datasets, and they have not 100 been tested against each other in a weakly forced environment. Therefore, this study seeks to 101 compare the relative skill of convective parameters using a large WFT dataset to determine which 102 are most appropriate for detecting environments supportive of pulse-thunderstorm-related severe 103 weather.

104

105 **2. Data and Methods**

106 2.1 WFT selection and environmental characterization

107 This study uses the 15-yr WFT dataset developed by Miller and Mote (2017) for the 108 Southeast U.S. (Fig. 1). Their catalogue identifies thunderstorms as regions of spatiotemporally 109 contiguous composite reflectivities meeting or exceeding 40 dBZ with WFTs representing the 110 subset of generally small, short-lived thunderstorms that formed in weak-shear, strong-instability 111 environments. The WFTs are spatially referenced according to their first-detection location, the





centroid of the composite reflectivities constituting the first appearance on radar. The storms were then paired with severe weather reports from *Storm Data*, a storm event database maintained by the United States National Centers of Environmental Information, to differentiate benign WFTs from pulse thunderstorms. The entire 15-yr dataset contains 885,496 WFTs including 5316 pulse thunderstorms.

117 Meanwhile, the thermodynamic and kinematic environment of each WFT was 118 characterized using the 0-hr Rapid Refresh (RAP; Benjamin et al., 2016) analysis. The RAP, 119 implemented on 9 May 2012, is a 13-km non-hydrostatic weather model initialized hourly for the 120 purpose of near-term mesoscale forecasting which is operated by the United States National Center 121 for Environmental Prediction. The model has output available at 37 vertical levels spaced at 25-122 hPa intervals between 1000 and 100 hPa and 10-hPa intervals above 100 hPa. Several previous 123 studies have relied upon the RAP's predecessor, the Rapid Update Cycle (RUC; Benjamin et al., 124 2004), to effectively characterize near-storm environments differentiating supercellular versus 125 non-supercellular and tornadic versus non-tornadic thunderstorms (Thompson et al., 2007; 126 Thompson et al., 2014).

For the grid cell containing each WFT's first-detection location, a RAP proxy sounding was created using the SHARPpy software package (Blumberg et al., 2017). Thus, each proxy sounding represents the model-derived storm environment for a point no more than 13-km and 30 min distant from the WFT first-detection location. The proxy soundings were used to calculate 30 near-storm environmental variables and indices, a complete list of which is provided in Table 1 with more thorough descriptions in Appendix A. The 30 variables were largely selected by virtue of their accessibility in SHARPpy. Four warm seasons of the Miller and Mote (2017) dataset,





134 containing 228,363 WFTs and 1481 pulse thunderstorms, overlapped with the RAP's operational

135 archive period allowing >6 million near-storm parameters to contribute to the analysis.

- 136
- 137 2.2 RAP error assessment

138 Thompson et al. (2003) demonstrated the suitability of the RUC, version 2 (RUC-2), to 139 represent storm environments as evaluated using co-located radiosonde observations, and the 140 Benjamin et al. (2016) RAP validation statistics show that the RAP is more accurate than its 141 predecessor. Figure 2a shows the results of an error evaluation specific to the purposes of this 142 study. Vertical error profiles were calculated for 3562 co-located RAP predictions and observed 143 radiosonde profiles in the Southeast U.S. The comparisons contain 0000 and 1200 UTC soundings 144 during the warm season (May-September) between 2012 and 2015 at three launch sites along a 145 north-south trajectory through the Miller and Mote (2017) domain: Nashville, Tenn., Peachtree 146 City, Ga., and Tampa, Fla., corresponding to U.S. radar identification codes KOHX, KFFC, and 147 KTBW in Fig. 1. The synoptic station codes for these three sites are the same as their U.S. radar 148 identifications with the exception of Nashville, Tenn., whose synoptic code is KBNA.

149 Similar to the Thompson RUC-2 analysis, the greatest, albeit small, temperature and 150 moisture biases (mean errors) from the RAP reside near the surface and the upper atmosphere (Fig. 151 2a). Aided by the large sample of comparison soundings, the 95% confidence intervals indicate 152 that the true bias of the selected RAP output variables at these sites can be estimated with 153 reasonable confidence. The 95% mixing ratio confidence interval captures zero at all altitudes except 500 hPa, where the RAP predicted drier-than-observed values by 0.08 g kg⁻¹. Temperatures 154 155 are warmer than observed throughout most of the troposphere with a maximum bias of 0.26° C at 156 850 hPa. In contrast, the RAP underestimated wind speeds on average throughout the depth of the





157 troposphere. The largest bias, 0.46 m s⁻¹, was found at 925 hPa with similar errors above 500 hPa.
158 The 95% confidence interval for wind speed error is largest near the tropopause, and demonstrates
159 larger uncertainty than for temperature and mixing ratio. These results generally agree with the
160 error statistics provided by Benjamin et al. (2016), and the reader should reference that paper for
161 additional information, including validation statistics, about the RAP.

162 Although the RAP appears to resolve temperature, mixing ratios, and wind speeds more 163 accurately than the RUC-2, the transmission of these errors onto the derived convective parameters 164 can be large. Table 2 expresses error measures for surface-based (SBCAPE) and mean-layer CAPE 165 (MLCAPE), 0-3-km and 0-6-km wind shear, total totals, and the theta-e index. Because the focus 166 of this study is surface-based convection, only days when the observed surface-based CAPE was 167 greater than zero were used to calculate the derived quantity error metrics. Similar to previous 168 work (e.g., Lee, 2002), parameters calculated via the vertical integration of a parcel trajectory, 169 such as CAPE, are sensitive to errors in low-level temperature and moisture. The RAP's low-level 170 temperature and moisture biases influence the lifted condensation level (LCL) calculation 171 (negative MLLCL bias; Table 2) yielding a premature transition to the pseudo-adiabatic lapse rate 172 and an overestimate of parcel instability (positive SBCAPE and MLCAPE biases; Table 2)¹. 173 Thompson et al. (2003) identified smaller CAPE errors generated by the RUC-2; however, the 174 nature of the thermodynamic environments being examined is significantly different in this study. 175 Similar to the RUC-2, the RAP is more adept at representing MLCAPE than SBCAPE with Fig. 176 2b, and consequently, the mean-layer parcel trajectory will be used for all parcel-related 177 calculations.

¹ The near-surface temperature and moisture errors in Fig. 2a are more pronounced following the upgrade to RAPv2 in February 2014. However, because the RAP is an operational tool and this work has operational relevance, no attempt was made to correct for this change.





178 Figures 2b-d demonstrate that although large outliers certainly occur, the majority of RAP-179 derived thermodynamic and kinematic parameters are concentrated within a narrower range of 180 error. Figure 3 provides an example skewT-logP diagram for a large MLCAPE error shown in 181 Figure 2d. Though the difference in this case exceeded 1000 J kg⁻¹, the discrepancy can largely be 182 attributed to the RAP's minor mischaracterization of low-level moisture. Otherwise, the depiction 183 of the vertical profile is reasonably accurate. The advantage of the RAP to represent the near-storm 184 environment is underscored when compared to results from coarser-scale models. For instance, 185 the coefficients of determination (R^2) for RAP-derived SBCAPE and MLCAPE are appreciably larger than those calculated from the 32-km horizontal and 3-hr temporal resolution North 186 187 American Regional Reanalysis (NARR; Mesinger et al., 2006) in Gensini et al. (2014).

188

189 2.3 Assessing convective parameter skill

190 The quality of severe weather reports is a significant impediment to severe storm research 191 (e.g., Miller et al., 2016; Weiss et al., 2002), particularly regarding the certainty with which 192 nonsevere storms can be declared nonsevere. These storms may only appear benign because their 193 associated severe weather was not reported. Consequently, the results of the proxy soundings are 194 subdivided by nearest radar site (Fig. 1) and aggregated daily (1200-1200 UTC) with days 195 containing at least one severe weather report considered supportive of severe weather whereas 196 days with no severe weather reports will serve as the control. This approach is similar to the 197 methods the Hurlbut and Cohen (2013) study of severe thunderstorm environments in the 198 Northeast U.S. Severe-wind-supporting (SWS) days and severe-hail-supporting (SHS) days are 199 treated separately because their thermodynamic environments have been shown to contain unique 200 elements related to downdraft and hailstone production (Johns and Doswell, 1992). Table 3





provides the specific subdivision details of the frequency of WFT days, SWS days, SHS days, and their respective control days. Figure 4 shows the annual average of WFT days for each radar site within the study area during the 2012–2015 warm seasons. As expected, WFT days are most frequent along coastlines and the Appalachian Mountains (Miller and Mote, 2017).

205 Given the low SNR in WFT environments, t-tests are deceiving. Statistically significant 206 differences in the mean values of parameters on severe versus nonsevere days are routinely 207 reported, but the considerable overlap between the distributions (e.g., Craven and Brooks, 2004; 208 Taszarek et al., 2017) can remove much practical value. This study explores the relationship 209 between convective parameters and pulse thunderstorm environments by means of an odds ratio 210 (OR; e.g., Fleiss et al., 2003). The OR is a common measure of conditional likelihood in human 211 health and risk literature (e.g., Bland and Altman, 2000) with precedent in the atmospheric sciences 212 (e.g., Black and Mote, 2015; Black et al., 2017). The OR looks past the descriptive statistics of the 213 severe versus nonsevere distributions and more directly compares differences in where the data is 214 concentrated.

Equation 1 shows the standard definition of the OR, essentially the ratio of two ratios,

$$OR = \frac{A/C}{B/D} \tag{1}$$

where the numerator represents the ratio of events (A) to non-events (C) when a condition is met whereas the denominator is the ratio of events (B) to non-events (D) when the same condition is not satisfied. In this context, "events" are SWS or SHS days whereas "non-events" would be the respective control days. Higher ORs indicate that events are more frequent (relative to non-events) when the condition is met, or conversely, that events are less frequent when the condition is not met. For this study, a condition might be a convective parameter exceeding a specified threshold.





For instance, if the SWS OR equals 4 for the condition MLCAPE > 1000 J kg⁻¹, then an SWS day
is 4x more likely when MLCAPE is greater than 1000 J kg⁻¹ than when it is less than 1000 J kg⁻¹.
We employ a modified form of the OR in which both the numerator and denominator are
standardized by the climatological ratio of events to non-events (Eq. 2), allowing the components
of the OR to be separated and interpreted independently by comparison to climatology.

$$OR = \frac{\frac{A/C}{(A+B)/(C+D)}}{\frac{B/D}{(A+B)/(C+D)}}$$
(2)

The modification does not change the value of the quotient OR, but it does improve the interpretability of the numerator and denominator. When the numerator or denominator is near zero (one), then the likelihood of SWS or SHS days is much lower than (nearly equal to) climatology. The climatological odds ratio was 0.069 for SWS days and 0.025 for SHS days. A 95% confidence interval for the OR was calculated using the four-step method presented in Black et al. (2017).

233

234 **3. Results**

235 3.1 Convective environments of pulse thunderstorm wind events

During the four-year study period, pulse thunderstorm wind events were documented somewhere in the study area on 49% of WFT days, although the average frequency within any single subdivision was 6.7% (Table 3). Table 4 shows the 30 convective parameters analyzed from the proxy soundings as well as the number of subdivisions for which each parameter is a statistically significant differentiator of SWS days. A significance threshold of p < 0.10 guided the selection of potentially useful parameters which would be examined in more detail. Nine of the 30





242 variables are statistically significant across at least two-thirds of the study area: VT, TT, MLCAPE,

243 MLLCL, MICROB, DCAPE, TEI, RH_LOW, and ThE_LOW.

244 Figure 5a-h depicts the distributions for several parameters from Table 4 for control versus 245 SWS days. These eight parameters are either significant across much of the domain (VT and TT), 246 demonstrate larger relative changes on SWS days (MLCAPE and MLLCL), and/or are traditional 247 operational severe wind forecasting tools (DCAPE, TEI, WNDG, MICROB). However, as the 248 distributions clearly illustrate, any difference in the mean values between the control days and 249 SWS days is small compared to the spread about their means. This results in the characteristically 250 low SNR described in the Sect. 1. Any attempt to establish a forecasting value indicative of pulse-251 wind potential will yield many missed events occurring beneath the threshold and/or false alarms 252 associated with control days above it.

253 Thus, Fig. 6 employs the OR to characterize the relative skill that some knowledge of the 254 convective environment can contribute to a severe versus nonsevere designation. For each variable in Fig. 5, a progressively larger value is selected, and the OR is calculated at each step. Figure 6 255 256 displays the OR as well as both the numerator and denominator terms for each iteration. Often 257 high ORs result when a near-zero number of severe events exist below the threshold inflating the 258 OR calculation. In these situations, the OR is indicating that severe weather is very unlikely, rather 259 than that the severe weather risk is enhanced. These results are not particularly useful because 260 forecasters would not have needed a decision-support tool in these environments in the first place. 261 Ideally, large ORs will result when the numerator indicates an appreciable increase against the 262 climatology while the denominator simultaneously indicates an appreciable decrease below 263 climatology. Further, these ORs would ideally occur in a range where the severe weather risk may 264 be uncertain. In Fig. 6, the OR is shown in a gray line, but the line is drawn in black whenever the





OR results from a numerator ≥2 and a denominator ≤0.5. ORs resulting from this combination
indicate that the threshold yields a simultaneous two-fold increase (decrease) in the likelihood of
SWS days above (below) the specified value. These ORs will be hereon referenced as "two-fold"
ORs, and represent a goal scenario.

269 Figures 6a-h show ORs for the same eight parameters in Fig. 5. Of all eight parameters, 270 only VT and TT achieve two-fold ORs for any range of thresholds, as indicated by the black 271 segments in Fig. 6a-b. The maximum two-fold OR for VT is 5.16 at 24.6°C, meaning that SWS 272 days are 5.16x more likely when this threshold is met. TT offers slightly more skill with a 273 maximum two-fold OR of 5.70 at 46.5°C. MLCAPE and MLLCL demonstrate consistently lower 274 ORs between 2 and 4. Surprisingly, the four wind-specific variables in Fig. 6e-h are relatively poor 275 differentiators of SWS days in the WFT regime. The maximum OR achieved by any of these 276 parameters is approximately 10 driven by very low values of DCAPE with corresponding wide 277 confidence intervals.

278 Though ORs are greater at lower VT and TT thresholds, these values are also somewhat common. Placing the aforementioned values (24.6°C and 46.5°C, respectively) in the context of 279 the 12,759 WFT environments included in this study, they represent the 58.8th and 58.9th 280 281 percentiles of their distributions. Alternatively, the maximum VT threshold that yields a two-fold OR is 25.1°C, which corresponds to the 70.9th percentile of all VTs in the dataset; however, the 282 283 OR for this value is smaller, 4.77. This result illustrates the trade-off involved by seeking 284 climatologically exceptional values to serve as guidance. As greater values are selected as the 285 threshold, meteorologists can focus on a fewer number of days. However, the OR decreases as 286 more severe weather events occur in environments not satisfying the threshold. As for TT, the maximum two-fold OR value is 47.3°C, corresponding to the 70.6th percentile, but demonstrates 287





an OR of 5.16. This means that when TT meets or exceeds 47.3°C, pulse thunderstorm severe wind

events are 5.16x more likely than when it does not.

290

291 3.2 Convective environments of pulse thunderstorm hail events

Table 5 replicates Table 4 except for SHS days. Many of the same parameters that are statistically significant differentiators of SWS days also rank high for SHS days. However, fewer parameters in Table 5 are statistically significant over two-thirds of the domain. Whereas 10 parameters in Table 4 showed spatially expansive statistical skill on SWS days, only three quantities do so on SHS days. We attribute this result to the pattern in Table 3 and Fig. 4b-c whereby there are fewer SHS days than SWS days, which increases uncertainty related to the statistical tests and makes it harder to confidently detect differences.

299 Nonetheless, VT and TT are once again skillful differentiators, and are now joined by their 300 related parameter CT. Additionally, several new convective variables demonstrate statistical 301 significance across roughly half of the domain on SHS days that demonstrated little skill on SWS days: PW, PEFF, HGT0, and ApWBZ. For comparison, Fig. 7a-d duplicates Fig. 5a-d now 302 303 comparing distributions between the control and SHS days while Fig. 7e-h displays boxplots for 304 the SHS-specific convective parameters listed above. The distributions for MLCAPE and MLLCL 305 are similar; however, there is a larger separation between control and SHS days for VT and TT 306 than was apparent on SWS days. This observation is corroborated by the relative changes in VT 307 and TT on SHS days that are several percentage points larger than for SWS days (Table 5). PW, 308 PEFF, HGT0, and ApWBZ demonstrate smaller differences.

Figure 8 replicates Fig. 6 except by representing SHS days and substituting the four wind specific parameters (DCAPE, TEI, WNDG, MICROB) with the four hail parameters listed above





311 (PW, PEFF, HGT0, ApWBZ). The ORs for VT and TT are large, greater than 10, throughout the 312 entire range of thresholds tested, and contain larger swathes of two-fold ORs. The maximum two-313 fold OR for VT is 13.1 at 24.4°C, and the maximum two-fold-OR-achieving VT threshold is 26.0°C with an OR of 9.61. These values relate to the 53.4th and 86.0th percentiles of the VT 314 315 distribution. As for TT, the maximum two-fold OR is 14.98 at 46.3°C, and the maximum two-316 fold-OR threshold is 49.2°C with an OR of 11.79. These two TT cut-offs translate to the 55.7th and 317 88.4th percentiles. Similar to SWS days, MLCAPE and MLLCL show little skill with ORs generally between 1-2. PW, PEFF, HGT0, and ApWBZ perform more capably than MLCAPE 318 319 and MLLCL; however, they do not produce any two-fold ORs. Values for these metrics are 320 generally around 4 with several instances of higher ORs driven by a small denominator with wide 321 95% confidence intervals.

322

323 3.3 Separating marginal pulse thunderstorm days

324 Because the severe weather generated by pulse thunderstorms is often near the lower limit 325 used to define severe weather in the United States, some pulse thunderstorm environments may 326 closely resemble nonsevere regimes. Consequently, the influence of these "marginal" pulse 327 thunderstorm days on the OR analysis is further scrutinized. For this purpose, "marginal" SWS 328 and SHS days are defined as those on which only one severe wind or hail report was received. 329 Marginal days constitute 48.7% of the SWS days and 57.7% of the SHS days in Table 3. Figure 9 330 replicates the OR analysis for VT and TT, the two most promising environmental parameters from 331 Sects. 3.1 and 3.2, but with only marginal SWS and SHS days being considered. Comparing Figs. 332 6a-b and 8a-b to Fig. 9, marginal SWS and SHS days resemble the OR patterns of the broader set of SWS (Fig. 6a-b) and SHS (Fig. 8a-b) days. Though the ORs for the marginal subset are slightly 333





334 smaller than for the broader group, they bear similar OR patterns as the thresholds are increased. 335 Overall, marginal SWS and SHS days are generally characterized by similar VT and TT values as 336 when all SWS and SHS days were aggregated. Corroborating this finding, an OR analysis 337 comparing marginal SWS and SHS days to those with >1 severe event (not shown) revealed that 338 ORs generally remained near 1 regardless of the VT or TT threshold selected. Thus, although marginal pulse thunderstorm days are by no means easily distinguishable from non-severe WFT 339 340 days, they do not appear to be particularly more challenging to differentiate than active pulse 341 thunderstorm days.

342

343 4. Discussion

344 The relative changes in the convective variables in Table 4 on SWS days versus control days correspond well to previous microburst research. Compared to the nonsevere control days, 345 346 SWS days are characterized by a drier near surface layer (i.e., lower RH, higher LCLs). 347 Simultaneously, steep mid-level lapse rates (i.e., larger VT and TT) aid an increase in CAPE which 348 supports stronger updrafts. As the strong updraft transitions to a downdraft-dominant storm, the 349 drier surface layer supports evaporative cooling, downdraft acceleration, and severe outflow 350 winds. This same conceptual model has been promoted by previous severe convective wind 351 research (e.g., Atkins and Wakimoto, 1991; Kingsmill and Wakimoto, 1991; Wolfson, 1988).

The results of SHS days also support previous findings (Johns and Doswell, 1992; Moore and Pino, 1990; Púčik et al., 2015). The distributions in Fig. 7 (and relative changes in Table 5) indicate that SHS days are characterized by relative decreases in PW, a lower freezing level, a lower wet-bulb freezing level, and dry near-surface air. Smaller PWs result in less waterloading and greater parcel buoyancy (larger VT, TT, and MLCAPE) which maximizes updraft strength.





Meanwhile, lower freezing levels and a dry layer between 1000–850 hPa support evaporative cooling which can together yield a lower wet-bulb zero height, and more efficient growth of hailstones. Interestingly, these two concepts are both represented in the PEFF calculation (Appendix A) which was not developed as a hail indicator. PEFF as defined by Noel and Dobur (2002), equals the product of PW and the mean 1000–700-hPa RH. As both values decrease, PEFF becomes smaller and hail is more likely for the reasons stated above.

363 The poor performance of MLLCLs and MLCAPEs in differentiating SWS and SHS days 364 from their controls is surprising given their prominence in severe storm forecasting. In contrast, 365 VT and TT were among the strongest indicators of both SWS and SHS days. Recalling from Sect. 366 2.2, VT and TT are also very well represented by the RAP. TTs were replicated by the model with 367 a $<1^{\circ}$ C bias and a MAE representing only 3% of the average value (Table 2). Additionally, mid-368 level temperatures, from which VT is computed, also compared very well to the observed 369 soundings (Fig. 2a). Thus, the strong performance of VT and TT compared to other more heavily 370 moisture-weighted metrics may be due to their more accurate representation in the proxy 371 soundings.

372 Regardless, because the severe weather SNR is already low in WFT environments, any 373 systematic error introduced by the data source (in this case the RAP) may significantly dampen, 374 or even remove, whatever environmental differences exist. As Sect. 2.2 indicated and previous 375 work has also concluded, low-level moisture biases can impede the accurate calculation of 376 convective parameters relying on those terms (e.g., Gensini et al., 2014; Thompson et al., 2003). 377 In this study, MLCAPE, MLLCL, PW, PEFF, and others were vulnerable to such errors. The 378 poorer performance of these variables' ORs (relative to the lapse-rate-based parameters) and the 379 sensitivity of PW, PEFF, and ApWBZ to simulated RAP errors suggests that model inaccuracies





may be obscuring their potential skill to detect severe weather environments. The perception ofthe WFT environment as a difficult-to-forecast regime may partly be driven by model

inconsistency exacerbating an already small SNR.

383 Another confounding factor is the quality of the Storm Data severe weather reports. Section 384 3.3 discussed that marginal SWS and SHS days are more similar to days with >1 report than days with no reports. Thus, the basis for the similarity may be that severe weather was simply under-385 386 reported on "marginal" days. Extending this logic, the pulse regime's low SNR may also be 387 partially attributed to under-reporting of severe weather on "nonsevere" days. Given that the severe 388 weather generated by pulse convection is often short-lived, isolated, and narrowly exceeds severe 389 criteria, the notion that some pulse-related severe weather events go undetected is likely. If some 390 "nonsevere" days existing above the tested parameter thresholds in Figs. 6 and 8 did in fact host 391 severe weather, then the ORs would have been larger than those found in Sects. 3.1 and 3.2.

392

393 **5.** Conclusions

394 Hazardous weather within WFT environments is characterized by a lower SNR than other 395 severe thunderstorm regimes. Though past research has developed promising tools for forecasting 396 pulse thunderstorm environments, their relatively small samples sizes may have understated the 397 SNR, and by corollary overstated the reliability of their tools. With recent research suggesting that 398 the performance of new severe weather forecasting tools is closely tied to the proportion of 399 nonsevere thunderstorms in the sample (Murphy, 2017), this study sought to test the relative skill 400 of 30 convective forecasting parameters using realistic proportions of severe and nonsevere WFT 401 environments (severe: 7.9%; nonsevere: 92.1%). Future research may consider broadening the





402 methods of Murphy (2017) to standardize the skill values across previous studies of severe 403 convective environments.

404 Only 13 (5) of the 30 convective parameters tested were statistically significant (p < 0.10) 405 differentiators of SWS (SHS) days across at least half of the domain. Though the distinctive 406 variables for SWS and SHS days were consistent with previous theories of severe microburst and 407 hail formation, considerable overlap between the distribution of values on severe and nonsevere 408 days is problematic. Similarities between the SWS, SHS, and their corresponding control 409 distributions inhibit consistent identification of pulse thunderstorm potential based on the value of 410 any individual parameter. Nonetheless, VT and TT did perform more skillfully than the others. 411 When VTs exceed values between 24.6-25.1°C or TTs between 46.5-47.3°C, the relative 412 likelihood of a wind event increases roughly 5x. Meanwhile, hail events become roughly 10x more 413 likely when VTs exceed values between 24.4–26.0°C or TTs between 46.3–49.2°C.

414 The noteworthy performance of VT and TT, two quantities calculated from the more reliable RAP output fields, is unlikely a coincidence. Our findings suggest that the already weak 415 416 severe weather SNR in WFT environments is exacerbated by model limitations in the low-level 417 moisture and temperature fields. Meteorologists may perhaps alleviate the challenges of the WFT 418 environment by examining convective parameters that are well-represented by models, such as 419 VT, TT, and other measures of lapse rate. Future research might seek to track the transmission of 420 the model errors through calculation of forecast skill statistics, and more concretely ascertain the 421 contribution of model error to the SNR.

422

423 6. Acknowledgments

424 The authors thank Alan Black for providing comments on an earlier draft of this manuscript.





425 **7. References**

- 426 Atkins, N. T. and Wakimoto, R. M.: Wet microburst activity over the southeastern United States:
- 427 Implications for forecasting, Wea. Forecasting, 6, 470–482, doi:10.1175/1520428 0434(1991)006<0470:WMAOTS>2.0.CO;2, 1991.
- 429 Benjamin, S. G., Dévényi, D., Weygandt, S. S., Brundage, K. J., Brown, J. M., Grell, G. A., Kim,
- D., Schwartz, B. E., Smirnova, T. G., Smith, T. L., and Manikin, G. S.: An hourly
 assimilation–forecast cycle: The RUC, Mon. Wea. Rev., 132, 495–518, doi:10.1175/1520-

432 0493(2004)132<0495:AHACTR>2.0.CO;2, 2004.

- 433 Benjamin, S. G., Weygandt, S. S., Brown, J. M., Hu, M., Alexander, C. R., Smirnova, T. G., Olson,
- 434 J. B., James, E. P., Dowell, D. C., Grell, G. A., Lin, H., Peckham, S. E., Smith, T. L.,
- 435 Moninger, W. R., Kenyon, J. S., and Manikin, G. S.: A North American hourly assimilation
- 436 and model forecast cycle: The Rapid Refresh, Mon. Wea. Rev., 144, 1669–1694,
 437 doi:10.1175/MWR-D-15-0242.1, 2016.
- 438 Black, A. W. and Mote, T. L.: Characteristics of Winter-Precipitation-Related Transportation
- 439 Fatalities in the United States, Wea. Climate Soc., 7, 133–145, doi:10.1175/WCAS-D-14440 00011.1, 2015.
- Black, A. W., Villarini, G., and Mote, T. L.: Effects of Rainfall on Vehicle Crashes in Six U.S.
 States, Wea. Climate Soc., 9, 53–70, doi:10.1175/WCAS-D-16-0035.1, 2017.
- 443 Bland, J. M. and Altman, D. G.: The odds ratio, BMJ, 320, 1468, 2000.
- 444 Blumberg, W. G., Halbert, K. T., Supinie, T. A., Marsh, P. T., Thompson, R. L., and Hart, J. A.:
- 445 SHARPpy: An open source sounding analysis toolkit for the atmospheric sciences, Bull.
- 446 Amer. Meteor. Soc., In press, doi:10.1175/BAMS-D-15-00309.1, 2017.





- 447 Cerniglia, C. S. and Snyder, W. R.: Development of warning criteria for severe pulse
- thunderstorms in the Northeastern United States using the WSR-88D. National Weather
 Service, 2002.
- 450 Craven, J. P. and Brooks, H. E.: Baseline climatology of sounding derived parameters associated
 451 with deep, moist convection, Natl. Wea. Dig, 28, 13-24, 2004.
- Fleiss, J. L., Levin, B., and Paik, M. C.: Statistical Methods for Rates and Proportions, Wiley,
 2003.
- Gensini, V. A., Mote, T. L., and Brooks, H. E.: Severe-thunderstorm reanalysis environments and
 collocated radiosonde observations, J. Appl. Meteor. Climatol., 53, 742–751,
 doi:10.1175/JAMC-D-13-0263.1, 2014.
- 457 Guillot, E. M., Smith, T. M., Lakshmanan, V., Elmore, K. L., Burgess, D. W., and Stumpf, G. J.:
- 458 Tornado and severe thunderstorm warning forecast skill and its relationship to storm type,
 459 New Orleans, LA2008.
- Hurlbut, M. M. and Cohen, A. E.: Environments of Northeast U.S. severe thunderstorm events
 from 1999 to 2009, Wea. Forecasting, 29, 3-22, doi:10.1175/WAF-D-12-00042.1, 2013.
- 462 James, R. P. and Markowski, P. M.: A numerical investigation of the effects of dry air aloft on
- 463 deep convection, Mon. Wea. Rev., 138, 140–161, doi:10.1175/2009MWR3018.1, 2010.
- Johns, R. H. and Doswell, C. A. I.: Severe local storms forecasting, Wea. Forecasting, 7, 588–612,
 doi:10.1175/1520-0434(1992)007<0588:SLSF>2.0.CO;2, 1992.
- 466 Kingsmill, D. E. and Wakimoto, R. M.: Kinematic, dynamic, and thermodynamic analysis of a
- 467 weakly sheared severe thunderstorm over northern Alabama, Mon. Wea. Rev., 119, 262–
- 468 297, doi:10.1175/1520-0493(1991)119<0262:KDATAO>2.0.CO;2, 1991.





- 469 Lee, J. W.: Tornado proximity soundings from the NCEP/NCAR reanalysis data, M.S., Dept. of
- 470 Meteorology, University of Oklahoma, 61 pp., 2002.
- 471 McCann, D. W.: WINDEX a new index for forecasting microburst potential, Wea. Forecasting,
- 472 9, 532–541, doi:10.1175/1520-0434(1994)009<0532:WNIFFM>2.0.CO;2, 1994.
- 473 Mesinger, F., DiMego, G., Kalnay, E., Mitchell, K., Shafran, P. C., Ebisuzaki, W., Jović, D.,
- 474 Woollen, J., Rogers, E., Berbery, E. H., Ek, M. B., Fan, Y., Grumbine, R., Higgins, W., Li,
- H., Lin, Y., Manikin, G., Parrish, D., and Shi, W.: North American regional reanalysis,
 Bull. Amer. Meteor. Soc., 87, 343–360, doi:10.1175/bams-87-3-343, 2006.
- 477 Miller, P. and Mote, T.: A climatology of weakly forced and pulse thunderstorms in the Southeast

478 United States, J. Appl. Meteor. Climatol., 2017. In review, 2017.

- 479 Miller, P. W., Black, A. W., Williams, C. A., and Knox, J. A.: Quantitative Assessment of Human
- 480 Wind Speed Overestimation, J. Appl. Meteor. Climatol., 55, 1009–1020,
 481 doi:10.1175/JAMC-D-15-0259.1, 2016.
- 482 Moore, J. T. and Pino, J. P.: An interactive method for estimating maximum hailstone size from 483 forecast soundings, Wea. Forecasting, 5, 508–525, doi:10.1175/1520-

484 0434(1990)005<0508:AIMFEM>2.0.CO;2, 1990.

- Murphy, M.: Preliminary results from the inclusion of lightning type and polarity in the
 identification of severe storms, 8th Conf. on the Meteor. Appl. of Lightning Data, Seattle,
 WA, 1–12, 2017.
- Noel, J. and Dobur, J. C.: A pilot study examining model-derived precipitation efficiency for use
 in precipitation forecasting in the eastern United States, Natl. Wea. Dig., 26, 3–8, 2002.





- 490 Púčik, T., Groenemeijer, P., Rýva, D., and Kolář, M.: Proximity soundings of severe and nonsevere
- thunderstorms in Central Europe, Mon. Wea. Rev., 143, 4805–4821, doi:10.1175/MWR-
- 492 D-15-0104.1, 2015.
- 493 Roberts, R. D. and Wilson, J. W.: A proposed microburst nowcasting procedure using single-
- 494 Doppler radar, J. Appl. Meteor., 28, 285–303, doi:10.1175/1520495 0450(1989)028<0285:APMNPU>2.0.CO;2, 1989.
- 496 Stewart, S. R.: The prediction of pulse-type thunderstorm gusts using vertically integrated liquid
 497 water content (VIL) and the cloud top penetrative downdraft mechanism. NOAA, 1991.
- 498 Taszarek, M., Brooks, H. E., and Czernecki, B.: Sounding-derived parameters associated with
- 499 convective hazards in Europe, Mon. Wea. Rev., 145, 1511-1528, doi:10.1175/MWR-D500 16-0384.1, 2017.
- Thompson, R. L., Edwards, R., Hart, J. A., Elmore, K. L., and Markowski, P.: Close proximity
 soundings within supercell environments obtained from the Rapid Update Cycle, Wea.
 Forecasting, 18, 1243–1261, doi:10.1175/1520-
- 504 0434(2003)018<1243:CPSWSE>2.0.CO;2, 2003.
- Thompson, R. L., Mead, C. M., and Edwards, R.: Effective storm-relative helicity and bulk shear
 in supercell thunderstorm environments, Wea. Forecasting, 22, 102–115,
 doi:10.1175/WAF969.1, 2007.
- 508 Thompson, R. L., Smith, B. T., Dean, A. R., and Marsh, P. T.: Spatial Distributions of Tornadic
- Near-Storm Environments by Convective Mode, Electronic J. Severe Storms Meteor., 8,
 1–22, 2014.





- 511 Weiss, S. J., Hart, J., and Janish, P.: An examination of severe thunderstorm wind report
- 512 climatology: 1970–1999, 21st Conf. Severe Local Storms, San Antonio, TX, 446–449,
- 513 2002.
- 514 Wheeler, M. and Spratt, S. M.: Forecasting the potential for central Florida microbursts. NOAA,
- 515 1995.
- 516 Wolfson, M.: Characteristics of microbursts in the continental United States, Lincoln Lab Journal,
- 517 1, 49–74, 1988.





519 Appendix A.

Table A1. Additional detail describing the convective parameters in Table 1.

Parameter	Comments	Parameter	Comments
MLCAPE		DCAPE	Downdraft CAPE with respect to
MLCIN			parcel with the minimum 100 hPa
MLLCL			layer-averaged theta-e found in
MLLFC			the lowest 400 hPa of the
MLEL			sounding.
K_IND	$T_{850} - T_{500} + T_{d850} - (T_{700} - T_{d700})$	WNDG	(MLCAPE)/2000*(0-3-km lapse
TT	CT + VT		rate)/9*(1–3.5-km mean
CT	$T_{d850} - T_{500}$		wind)/ $15*[(MLCIN + 50)/40)].$
VT	$T_{850} - T_{500}$		Values larger than 1 indicate an
PW	Depth of liquid water if all water		increased risk for strong outflow
	vapor were condensed from the		gusts.
	sounding	TEI	Difference between the surface
HGT0	Pressure level of the 0°C isotherm		theta-e and the minimum theta-e
ApWBZ	Height above ground level of the		value in the lowest 400 hPa AGL
	RAP pressure level with the wet	MICROB	Weighted sum of the following
	bulb temperature nearest to 0°C		individual parameters: surface
W_LOW	Mean mixing ratio between 1000–		theta-e, SBCAPE, surface-based
	850 hPa		lifted index, 0–3-km lapse rate,
w_MID	Mean mixing ratio between 850–		VI, DCAPE, TEI, and PW.
	500 nPa		Values exceeding 9 indicate that
RH_LOW	Mean RH between 1000–850 nPa		microbursts are likely. $12(T = 1) + 20(TT = 40) + 2(U = 1)$
KH_MID	Mean KH between 850–500 hPa	SWEAT	$12(1_{d850}) + 20(11 - 49) + 2(0_{850})$
The_LOW	Mean theta a from 250, 500 hPa		$+(0.500) + 1.25[SIII(0_{dir500} - 0_{dir850})$
IIIE_MID	Bully Dishard Number of the	0.2	+ 0.2] Magnituda of vector sheer
ML_DKN	mean layer parcel	br SHD	between surface and 3 km AGI
Те	Temperature of parcel lowered	MI_{SIIK}	Magnitude of vector shear
IC	dry adjustically from the	bm SHR	between surface and 6 km AGI
	convective condensation level	0-8-	Magnitude of vector shear
PEFE	As defined by Noel and Dobur	km SHR	between surface and 8 km AGI
1 21 1	(2002) PEFE equals the product	EBWD	Magnitude of vector shear
	of PW and the mean 1000–700-		between effective inflow base and
	hPa RH.		one half of the MU equilibrium
			level height





525 Tables

- 526 **Table 1.** List of the 30 convective parameters computed from the proxy soundings where CAPE,
- 527 CIN, LCL, LFC, and EL and correspond to convective available potential energy, convective
- 528 inhibition, lifted condensation level, level of free convection, and equilibrium level, respectively.

Abbrev.	Full Name	Units
MLCAPE	Mean-layer CAPE	J kg ⁻¹
MLCIN	Mean-layer CIN	J kg ⁻¹
MLLCL	Mean-layer LCL	m
MLLFC	Mean-layer LFC	m
MLEL	Mean-layer EL	m
K_IND	K index	°C
TT	Total totals	°C
СТ	Cross totals	°C
VT	Vertical Totals	°C
PW	Precipitable Water	mm
HGT0	Height of 0°C temperature isotherm	hPa
ApWBZ	Approximate height of 0°C wet bulb temperature	m
W_LOW	Mean low-level mixing ratio	g kg ⁻¹
W_MID	Mean mid-level mixing ratio	g kg ⁻¹
RH_LOW	Mean low-level relative humidity	
RH_MID	Mean mid-level relative humidity	
ThE_LOW	Mean low-level theta-e	Κ
ThE_MID	Mean mid-level theta-e	Κ
ML_BRN	Mean layer bulk Richardson number	
Tc	Convective temperature	°C
PEFF	Precipitation efficiency	
DCAPE	Downdraft CAPE	J kg ⁻¹
WNDG	Wind damage parameter	
TEI	Theta-e index	°C
MICROB	Microburst composite index	
SWEAT	Severe weather and threat index	
0-3-km_SHR	0-3-km vertical wind shear	m s ⁻¹
0-6-km_SHR	0-6-km vertical wind shear	m s ⁻¹
0-8-km_SHR	0-8-km vertical wind shear	m s ⁻¹
EBWD	Effective layer vertical wind shear	m s ⁻¹





- 530 Table 2. RAP error statistics for surface-based CAPE (SBCAPE) and several of the variables listed
- 531 in Table 1. The statistics are presented similarly to Thompson et al. (2003) by providing the mean
- 532 RAP-derived value, the mean arithmetic error (bias), and the mean absolute error (MAE).

Parameter	Mean	Bias	MAE	R ²
SBCAPE	1354.3	141.3	530.4	0.59
MLCAPE	943.4	112.6	338.0	0.64
MLLCL	1077.4	-32.9	151.8	0.82
Total Totals	44.8	0.51	1.54	0.74
TEI	21.1	-2.30	3.80	0.69
0–3-km Shear	6.33	-0.48	1.38	0.82
0–6-km Shear	8.39	-0.28	1.40	0.88





Site	WFT	Wind	SWS	% SWS	Hail	SHS	% SHS
	Days	Control	Days		Control	Days	
KAKQ	376	351	25	6.6	363	13	3.5
KAMX	581	569	12	2.1	575	6	1.0
KBMX	376	364	12	3.2	372	4	1.1
KCAE	401	339	62	15.5	377	24	6.0
KCLX	450	407	43	9.6	440	10	2.2
KDGX	426	403	23	5.4	416	10	2.3
KEOX	384	366	18	4.7	382	2	0.5
KEVX	467	449	18	3.9	463	4	0.9
KFCX	408	318	90	22.1	370	38	9.3
KFFC	400	358	42	10.5	387	13	3.3
KGSP	417	334	83	19.9	383	34	8.2
KGWX	362	349	13	3.6	354	8	2.2
KHPX	299	282	17	5.7	294	5	1.7
KHTX	373	343	30	8.0	369	4	1.1
KJAX	555	520	35	6.3	546	9	1.6
KJGX	384	356	28	7.3	377	7	1.8
KLIX	504	492	12	2.4	501	3	0.6
KLTX	452	439	13	2.9	444	8	1.8
KMHX	497	496	1	0.2	495	2	0.4
KMLB	540	532	8	1.5	532	8	1.5
KMOB	451	444	7	1.6	446	5	1.1
KMRX	415	349	66	15.9	384	31	7.5
KMXX	357	346	8	2.2	350	4	1.1
KNQA	356	336	20	5.6	345	11	3.1
KOHX	349	336	13	3.7	345	4	1.1
KPAH	330	305	25	7.6	318	12	3.6
KRAX	367	337	30	8.2	355	12	3.3
KTBW	546	525	21	3.8	535	11	2.0
KTLH	482	461	21	4.4	479	3	0.6
KVAX	457	430	27	5.9	452	5	1.1
Mean	425	398	27	6.7	415	10	2.5

Table 3. WFT, SWS, and SHS day frequency by radar site.





- 536 Table 4. Summary of convective parameters on SWS days. The "Sites" column indicates the
- 537 number of spatial subdivisions within which the difference between the SWS mean and the control
- 538 mean was accompanied by p < 0.10; the "percent change" column shows the relative increase or
- 539 decrease of the mean on SWS days.

Parameter	Sites	Percent change
VT	28	5.1
TT	27	4.2
MLCAPE	25	31.2
MICROB	23	44.0
DCAPE	22	17.3
TEI	22	13.1
MLLCL	21	12.9
ThE_LOW	21	0.9
RH_LOW	20	-5.5
WNDG	19	41.2
CT	19	3.2
Tc	19	5.8
MLEL	18	8.0
SWEAT	14	7.8
W_LOW	10	3.0
K_IND	8	3.8
RH_MID	7	-3.2
ThE_MID	6	0.1
PEFF	6	-3.8
0-6-km_SHR	6	-4.5
0-8-km_SHR	6	-6.5
ApWBZ	5	-0.5
HGT0	4	0.1
W_MID	3	0.0
MLBRN	3	-0.7
PW	2	0.9
0-3-km_SHR	2	-1.2
MLCIN	0	6.6
MLLFC	0	0.9
EBWD	0	-1.9





Table 5. Same as Table 4, except for SHS days.

Parameter	Sites	Percent change
VT	27	8.0
TT	27	7.5
СТ	21	7.1
PEFF	16	-11.0
MLLCL	15	13.2
HGT0	14	2.4
ApWBZ	14	-6.0
RH_LOW	14	-5.3
DCAPE	13	23.3
MLCAPE	12	28.8
PW	12	-6.7
W_MID	11	-9.2
ThE_MID	10	-0.7
WNDG	10	27.4
RH_MID	9	-7.8
TEI	7	10.4
MICROB	7	21.6
SWEAT	7	10.1
W_LOW	6	-2.1
Tc	6	3.2
0-6-km_SHR	6	9.7
0-8-km_SHR	5	6.9
MLEL	4	3.8
K_IND	3	2.7
ThE_LOW	3	-0.1
0-3-km_SHR	3	5.3
MLCIN	1	17.7
MLLFC	1	4.1
MLBRN	1	-15.8
EBWD	1	9.5





543 Figures



545 Figure 1. WSR-88D sites contributing to the Miller and Mote (2017) WFT climatology.







Figure 2. Vertical profiles of RAP output errors measured by co-located radiosonde observations (a). Errors were calculated at 1000, 925, 850, 700, 500, 300, and 200 hPa. The 95% confidence interval for the mean error (solid lines) is shaded. Boxplots of the resulting error for six derived quantities is shown in (b)-(d). The interquartile range (IQR), representing the middle 50% of values, is depicted by the gray box. Values lying more than 1.5*IQR from the median (red line) are marked with dots.







Figure 3. Comparison of observed (a) versus RAP-derived (b) soundings for a case when the MLCAPE discrepancy exceeded 1000 J kg⁻¹ (observed: 1028 J kg⁻¹; RAP: 2051 J kg⁻¹). Minor mischaracterizations of low-level moisture contributed to a large response in MLCAPE during the vertical integration of the parcel trajectory.







559 Figure 4. Average number of WFT days during the four-year study period (a) compared to the











562 Figure 5. Boxplots of selected convective parameters that demonstrated skill in differentiating

⁵⁶³ between the control days and SWS days.







Figure 6. ORs for the same eight convective parameters shown in Fig. 5. Whenever the OR, defined by Eq. (2), results from a numerator (red) ≥ 2 and a denominator (blue) ≤ 0.5 , then the OR is drawn in black. The left y-axis expresses values corresponding to the OR's numerator and denominator (red and blue lines), and the right y-axis corresponds to the OR value (gray line). At very low and very high threshold values, the variance of the OR may be undefined, and the 95% OR confidence interval cannot be computed.







571

572 Figure 7. Same as Fig. 5 except for SHS days. Panes (a)-(d) replicate the same variables shown in

573 Fig. 5 whereas (e)-(h) are replaced with four SHS-specific parameters from Table 5.







574

575 Figure 8. Same as Fig. 6 except for SHS days. Panes (a)-(d) replicate the same variables shown in 576 Fig. 6 whereas (e)-(h) are replaced with four SHS-specific parameters from Table 5. At very low 577 and very high threshold values, the variance of the OR may be undefined, and the 95% OR 578 confidence interval cannot be computed.







Marginal versus control days

580

581 Figure 9. Same as Fig. 6a-b (a-b) and Fig. 8a-b (c-d) except that only marginal SWS and SHS

582 days are used to calculate the OR. At very low and very high threshold values, the variance of the

583 OR may be undefined, and the 95% OR confidence interval cannot be computed.