

Effectiveness of low impact development for urban inundation risk mitigation under different scenarios: a case study in Shenzhen, China

Jiansheng Wu^{1,2}, Rui Yang¹, Jing Song^{3,4}

5 ¹Key Laboratory for Urban Habitat Environmental Science and Technology, Shenzhen Graduate School, Peking University, Shenzhen 518055, PR China

²Key Laboratory for Earth Surface Processes, Ministry of Education, College of Urban and Environmental Sciences, Peking University, Beijing 100871, PR China

³Department of Urban Planning and Design, The University of Hong Kong, Hong Kong

10 ⁴Shenzhen Institute of Research and Innovation, The University of Hong Kong, Shenzhen, China

Correspondence to: Jing Song (songjing@connect.hku.hk)

Abstract. The increase in impervious surfaces associated with rapid urbanization is one of the main causes of urban inundation. Low impact development (LID) practices have been studied for mitigation of urban inundation. This study used a hydrodynamic inundation model, coupling SWMM (Storm Water Management Model) and IFMS Urban (Integrated Urban Flood Modelling System), to assess the effectiveness of LID under different scenarios and hazard levels. The results showed that LID practices can effectively reduce urban inundation. The maximum inundation depth was reduced by 3–29 %, average inundation areas were reduced by 7–55 %, and average inundation time was reduced by 0–43 % under the eight scenarios. The effectiveness of LID practices differed for the three hazard levels, with better mitigation of urban inundation at a low hazard level than at a high hazard level. Permeable pavement (PP) mitigated urban inundation better than green roof (GR) under the different scenarios and hazard levels. We found that more implementation area with LID was not necessarily more efficient and the scenario of 10 % PP + 10 % GR was more efficient for the study area than other scenarios. The results of this study can be used by local governments to provide suggestions for urban inundation control, disaster reduction and urban renewal.

1 Introduction

In recent years, urban stormwater inundation hazards have occurred frequently in major cities all over the world, leading to significant property damage in local areas (Bhattarai et al., 2016). In China, according to a report by the Ministry of Housing and Urban-Rural Development (MOHURD) in 2010, 62 % of 351 cities have suffered from inundation hazards, and 137 of these have had negative effects from urban floods on more than three occasions from 2008 to 2010. In 2012, 2013, 2014, and 2015, the number of cities that suffered urban inundation was 184, 234, 125, and 154, respectively, including Beijing, Shanghai, Guangzhou and Shenzhen. Urban inundation increasingly threatens the sustainable development of urban areas.

Rapid urbanization has become an important cause of frequent urban stormwater inundation, in addition to extreme precipitation and low standards for urban drainage infrastructure (Arnold, 1996; Beckers et al., 2013; Claessens et al., 2006; Zahmatkesh et al., 2015b). Rapid expansion of cities generally leads to an increase in impervious surfaces, which makes the hydrological characteristics of the urban surface change significantly (Arnold, 1996; Jacobson, 2011; Rose and Peters, 2001).

5 Impervious surfaces replace rivers, lakes, green spaces, and urban forests; weaken the flood control capability of the urban system; and change infiltration, evaporation, filtration, and storage (Hao et al., 2015; Jacobson, 2011; Meyer, 2001). The expansion of impervious areas accelerates rainwater convergence on urban surfaces, resulting in increased runoff and peak flows (Hatt et al., 2004; Leopold et al., 1995; Liu et al., 2015). The increase in runoff and peak flows taxes urban drainage facilities and exacerbate the risk of urban inundation.

10 To solve the problem of urban inundation, scholars in China have suggested the “Sponge City” initiative, which allows cities to act as sponges to filtrate, purify, evaporate, and store rainwater (Mao et al., 2017; Sang and Yang, 2016). Low impact development (LID), an important development concept for sponge cities, has been applied in Sponge City construction (Luan et al., 2017); it is widely applied to reduce the impacts of urban inundation associated with rapid urbanization (Dietz and Clausen, 2008; Dietz, 2007; Xia et al., 2017; Zahmatkesh et al., 2015a). LID is a stormwater management strategy that uses

15 microscale and localized practices to control the runoff and pollution caused by a storm (Damodaram et al., 2010; EPA, 2000; HUD, 2003). Since the 1990s, LID practices have been widely used in countries in Europe, the United States of America, and other developed countries. LID practices include PP, GR, bioretention, swales, infiltration wells/trenches, infiltrating wetlands, and rain barrels (Hunt et al., 2010).

The hydrological effectiveness of LID practices has been researched through field and laboratory studies (Abbot and Comino-

20 Mateos, 2003; Berndtsson, 2010; Davis, 2008; Davis et al., 2012; Fassman and Blackbourn, 2010). For example, Hood et al. (2007) monitored low impact residential development and traditional residential development in Waterford, Connecticut, USA, and found that LID practices helped lower runoff, peak flows, and discharge volumes. Dreelin et al. (2006) designed a test to compare the performance of asphalt and PP parking lots in Athens, Georgia, USA, and their results showed that the porous parking lot contributed 93 % less runoff than the asphalt lot during natural storm events. Bliss et al. (2009) constructed and

25 monitored a GR in Pittsburgh, Pennsylvania, USA and reported that the GR reduced runoff by up to 70 % and reduced peak flows by 5–70 %; the hydrograph was delayed by several hours more than a normal roof for the same building.

Many scholars have focused on simulations at a large scale, such as watersheds (Ahiablame et al., 2012; Dietz and Clausen, 2008; Roy et al., 2008; Salvatore et al., 2015), to explore the effectiveness of LID practices. For example, Palla and Gnecco (2015) reported that the LID combination of GR and PP decreased runoff and peak flows by 23 % and 45 %, respectively, and

30 delayed the hydrograph by up to 19 % at the urban catchment scale. Trinh and Chui (2013) conducted a simulation and found that GR could reduce the peak flows by 50 % and delay the hydrograph by 2 hours, bio-retention (BR) systems could reduce the peak flows by 50 %, and the combined GR and BR systems could reduce the peak flows to a pre-urbanized level. Morsy et al. (2016) reported that rain gardens can mitigate runoff by approximately 15, 27, and 38 % for 2-, 5-, and 10-year storm events, respectively, which reduced the watersheds flood risk. Ahiablame et al. (2013) assessed the effectiveness of rain

barrels/cisterns and PP in two urbanized watersheds near Indianapolis, Indiana, USA; by using simulations, they found that LID practices reduced runoff and pollutant loads; they listed some LID combinations that are good retrofitting options for local areas.

5 Peak flows reduction, runoff reduction, and hydrograph delays are widely used indexes for evaluating the performance of LID practices (Ahiablame and Shakya, 2016; Qin et al., 2013; Zhang et al., 2016). However, these indexes are not intuitive, and the performance of LID practices for urban inundation is more useful for local residents, such as providing a guide for their travel behaviour. Some 1D-2D models have been applied for flood management, such as ESTRY-TUFLOW (Fewtrell et al., 2011), InfoWorks ICM (Russo et al., 2015) and MIKE FLOOD (Loewe et al., 2017). However, most of these models have a cost, which limits their application. In recent years, as an open source and free model, SWMM has been coupled with other
10 models, such as BreZo (Burns et al., 2015) and LISFLOOD-FP (Wu et al., 2017), to simulate urban inundation, which means that the coupled models based on SWMM is needed in future research.

The goal of this study was to evaluate the effectiveness of LID practices to mitigate urban inundation in urban watershed using a case study. The specific objectives were to establish a 1D-2D hydrodynamic model that coupled SWMM and IFMS Urban, evaluate the effectiveness of LID practices under different scenarios and hazard levels, and explore the efficiency of the LID
15 scenarios. We intended this study to enrich LID inundation mitigation research at the urban watershed scale and to provide a reference for urban stormwater management and inundation mitigation for local governments.

2 Materials and methodology

2.1 Study site

Shenzhen is in the coastal area of Guangdong Province in southern China (Figure 1). It has a subtropical maritime monsoon
20 climate; Shenzhen is hot and rainy in summer and mild in winter, and the average annual rainfall is 1837 mm. April to September is the rainy season in Shenzhen, and during this period, precipitation is concentrated and stormwater overflows are frequent. There were 38 rainstorm days (95 % of the year) in 2017 and the average rainfall was 170–350 mm every month during this period. Accordingly, urban inundation was particularly serious in this period; it caused loss of life and economic losses for local residents.

25 The study site was located in Guangming New District of Shenzhen, China, and it is in the Maozhou River Basin (Figure 1). The total area of our study site was 37.68 km², of which 69.8 % was impervious surfaces. Guangming New District was selected as the first pilot area for LID practices in Shenzhen in October 2011 because of the intensity of its inundation disasters. There is a need to research the effectiveness of LID on urban inundation mitigation in this area.

2.2 Data

30 The model input data included inundation, land use, a digital elevation model (DEM), weather, and pipe network data. The land use data (2013) and pipe network data were provided by the Shenzhen government. We generalized the original data and

divided the study area into water, low density construction land, high density construction land, bare land, woodland, grassland, and agricultural land using remote sensing images (Figure 1). The DEM of the study area (Figure 2) was downloaded from the Geospatial Data Cloud (30 m resolution). The weather data were sourced from the Shenzhen Meteorological Data System (<https://data.szmb.gov.cn/>). According to the integrity and availability of data, we chose two representative heavy rainstorm event datasets, 11 May 2014 and 10 May 2016 (Figure 3) for model simulation, which included the complete volume of rainfall every hour. The corresponding inundation data were obtained from the Shenzhen SanFang (flood, drought, and wind defence) headquarters and the Guangming New District Urban Construction Bureau. We simplified the drainage data for building the model because the urban pipe network is intricate and substantial: add nodes when the pipeline is too long; keep or add the nodes that change the diameter and slope of pipeline; keep the parallel pipelines and nodes on both sides of the roads; and delete the nodes and pipelines that are independent of this model. Finally, the 4502 pipelines and 1175 nodes in this study were generalized to 597 pipelines and 653 nodes, including 56 outlets and 597 inspection nodes (Figure 2).

2.3 SWMM and IFMS Urban models

Developed by the United States Environmental Protection Agency (US EPA), SWMM is an open-source model that can simulate dynamic runoff quantity and quality from urban areas, and it has been widely used to simulate the hydrologic performance of LID practices (Rossman, 2010; Wu et al., 2013). However, SWMM cannot simulate the spatial and temporal distributions of surface inundation. Recently, some scholars have conducted simulations using secondary developments of this software (Seyoum et al., 2012; Son et al., 2016; Zhu et al., 2016). We expected that this application would be difficult to use in our study area due to differences in computer programming. Coupling a model with SWMM for 2D simulation is another way to simulate the spatial distribution of urban inundation (Huong and Pathirana, 2013; Wu et al., 2017).

The Integrated Urban Flood Modeling System (IFMS Urban) was developed by the China Institute of Water Resources and Hydropower Research (IWHR) in cooperation with other institutions. Based on the simulated results from SWMM, IFMS Urban can simulate the temporal and spatial distribution of urban inundation, and it is compatible with ArcGIS and SWMM. Data conversion and model coupling are accomplished in IFMS Urban, and it does not need additional software programming, which is convenient for researchers and non-expert users.

Therefore, we coupled SWMM and IFMS Urban in this study to simulate urban inundation. SWMM was applied to construct a 1D sewer model. The study area was simplified to 577 sub-catchments, 597 pipelines, and 653 nodes. Details of model building and of SWMM's parameters can be found in many published studies (e.g., Rossman, 2010; Qin et al., 2013; Wu et al., 2017). Model coupling occurred in IFMS Urban. First, an unstructured 2D grid model was meshed with an average cell size of 15 m; second, ground elevations were assigned to each grid; finally, each node was linked with a corresponding grid for water exchange, and the distribution of surface inundation was calculated with 2D shallow water equations. The coupled model had the advantages of SWMM and IFMS Urban, and could be applied to simulate urban inundation and evaluate the performance of LID practices.

2.4 Scenarios of LID combinations for simulation

Considering the feasibility and representativeness of LID practices for urban inundation mitigation, we chose two types of LID practices, GR and PP, to simulate and explore their effectiveness for mitigation of urban inundation. The parameters for PP and GR are listed in Table 1, which were designed based on SWMM requirements and LID research (Ahiablame and Shakya, 2016; Chui et al., 2016; Kong et al., 2017; Qin et al., 2013). Through remote sensing images and field investigations, we found that urban villages have diverse roof structures and shapes, which makes it difficult to implement green roofs. Therefore, we established principles for the implementation of LID practices: GR can only be built on low density construction land, and PP can be built on low and high construction land and on some streets. According to these principles, the available area for PP and GR was 5.95 km² and 8.92 km², respectively. We set a series of proportions from 5 % to 100 % for the density of different types of LID combinations, and a benchmark and eight scenarios are designed below:

Benchmark: No LID practices

Scenario 1 (S 1): 5 % GR + 5 % PP

Scenario 2 (S 2): 10 % GR + 10 % PP

Scenario 3 (S 3): 25 % GR + 25 % PP

Scenario 4 (S 4): 50 % GR + 50 % PP

Scenario 5 (S 5): 75 % GR + 75 % PP

Scenario 6 (S 6): 100 % GR + 100 % PP

Scenario 7 (S 7): 100 % PP

Scenario 8 (S 8): 100 % GR

20 3 Results

3.1 Model calibration and validation

The coupled model was calibrated using rainfall and inundation data from 11 May 2014. Based on the relevant literature and the SWMM manual, we determined the final SWMM parameters (Table 2) through several calibration iterations. From the final calibration results (Table 3), we found that, except for inundation site Gm 20, the absolute value of the maximum inundation depth between the observed and simulated value was approximately 0–0.14 m and the relative error was ranged from 0–30 %.

To further confirm the applicability of the model, the rainfall and inundation data on 10 May 2016 was chosen to validate the coupled model. Three valid datasets were simulated with the coupled model using observed urban inundation data on 10 May 2016 from the Guangming New District Urban Construction Bureau. The results showed that the absolute values of the differences between the observed and simulated maximum inundation depths were 0.04 m (Gm 11), 0.05 m (Gm 12) and 0.02 m (Gm 20), and the relative errors were 20, 7, and 5 %, respectively. In this study, the relative error of calibration were a little

higher, while the relative errors of validation were 5–20 %, which met the requirements of the Standard for Hydrologic Information and Hydrologic Forecasting in China (GBT_22482-2008).

3.2 Inundation depth under different scenarios

Figure 4 and Table 4 show the simulation results of inundation depths under different scenarios. Compared to the benchmark, the reduction rates of maximum inundation depth were 3, 7, 16, 22, 26, and 29 % under S 1 to S 6, respectively. The results for the 100 % PP and 100 % GR scenarios showed that PP and GR had approximately the same performance at the maximum inundation depth and both scenarios reduced maximum inundation by 14 %.

To further explore the impacts of LID practices on inundation mitigation, we set three hazard levels for the depth of urban inundation: low (< 0.2 m), medium (0.2–0.4 m), and high (≥ 0.4 m), based on the literature (Su et al., 2016) and observed data for the study area. Compared to the benchmark, the ranges of average depth reduction rates were 15–80, 5–54, and 4–40 % at low, medium and high hazard levels, respectively, for S 1 to S 6 (Figure 5a). Under different hazard levels, the average depth reduction rates increased from S 1 to S 6. The average depth reduction rates at the low level were 11, 26, 38, 44, 43, and 40 % higher than the high level under S 1 to S 6, respectively. These results suggest that most inundated areas could not be eliminated at the high level.

Figure 5a shows that the average depth reduction rates of 100 % PP and 100 % GR scenarios were between the 25 % GR + 25 % PP and 50 % GR + 50 % PP scenarios under different hazard levels. These results suggest that LID combinations may be more effective in reducing urban inundation than a single type of LID practice. Based on the comparison of the two LID practices, we found that the average depth reduction rates of the 100 % PP scenario were 67, 38 and 23 % at the low, medium and high levels, respectively. These were 6, 7, and 2 % higher than the average depth reduction rates of the 100 % GR scenario. These results suggest that PP may perform better than GR for reducing the depth of inundation.

3.3 Inundation areas under different scenarios

Figure 5b shows changes in the inundation area under different scenarios and hazard levels. Compared to the benchmark, the ranges of average area reduction rates were 6–53, 17–75, and 24–90 % at low, medium, and high levels, respectively, for S 1 to S 6. The inundation areas reduced at different hazard levels after the implementation of LID practices. The average area reduction rates at the high level were up to 24–90 %, which were greater than those at the low level. This likely occurred because, after the implementation of LID practices, the depth of inundation decreased and most inundated areas were downgraded from a high level to a medium level or a low level.

For the 100 % PP and 100 % GR scenarios, the reduction in the inundation areas was similar to the 25 % PP + 25 % GR scenario, which also suggested that LID combinations are more effective than single LID practice. The average area reduction rates for the 100 % PP scenario were 37, 65 and 67 % at the low, medium and high levels, respectively, which were 5, 9, and 0 % higher than those for the 100 % GR scenario.

3.4 Inundation time under different scenarios

Inundation time is another way to represent inundation risk. Table 5 shows that the inundation time for medium and high levels was longer than the inundation time for the low level under the same scenario, which reflects increased risk of inundation at medium and high levels. As the implementation area of LID increased, the average inundation time decreased under the three
5 hazard levels. The 100 % PP and 100 % GR scenarios had lower inundation time than the 25 % PP + 25 % GR scenario, and the inundation time for the 100 % PP scenario was 1.3 h less than the inundation time for the 100 % GR scenario. Compared to the benchmark, the average inundation time under S 1 to S 3 changed slightly, while it decreased from S 4 to S
6. This result did not indicate that LID practices cannot decrease inundation time or that the model had errors. The inundation time decreased for all hazard levels, but for the low and medium levels, some areas inundated for a short-time were no longer
10 flooded, which resulted in a different urban inundation area after the implementation of LID practices. Therefore, the average inundation time was longer than before LID practices were implemented at the low and medium levels. As LID practices were implemented, the average inundation time decreased continuously from 4.1 to 2.3 h under S 3 to S 6.

4 Discussion

4.1 Performance of PP and GR

15 Researching the effectiveness of LID practices for urban inundation mitigation is important for stormwater management. Our analysis showed that, although the implementation area of PP was less than GR, PP provided better urban inundation mitigation than GR. This result may have been due to differences in the LID parameters, but it may also have been caused by the PP's more diffuse spatial pattern. To better identify the effects of parameters, we did a sensitivity analysis carried out by assuming
20 a 50% increase in some parameters under S 7 and S 8, and the results showed that the inundation depth has great sensitivities to some parameters (Table 6). Under the permeable pavement scenario, the inundation decreases 15 %, 16 % and 18 % with thickness of pavement layer, thickness and void ratio of storage layer, respectively. Under the rain roof scenario, the inundation decreases 17 % and 19 % with thickness and porosity of soil layer, respectively. The results indicate that LID parameters might influence the effectiveness on inundation mitigation.

Indeed, except the LID parameters, there are some other factors, such as implementation area, spatial pattern, rainfall intensity
25 and rainfall frequency that will influence the effectiveness, and these are the reasons why PP cannot always perform better and showed varying effectiveness in different studies (Ahiablame and Shakya, 2016; Hu et al., 2017; Qin et al., 2013; Zhang et al., 2016). However, under certain scenarios of this study, PP may be a good choice for local governments because of its effectiveness for stormwater management and its potential use for reconstruction in built-up areas. PP could be gradually applied to roads and parking lots, while GR is harder to implement in densely urbanized areas, especially in the urban villages.

4.2 Effectiveness at different hazard levels

At the high level, the average depth reduction rates decreased from 4 % to 40 %, and the average area reduction rates decreased from 24 % to 90 % under S 1 to S 6. These results showed that the inundation hazard eased at a high level with the implementation of LID practices. However, at the high level, the average depth reduction rates were still 11–40 % lower and the average inundation time was 2.5–7 h longer when compared to the low level; this indicates that LID practices are more effective for urban inundation mitigation at a low hazard level. The hazard level analysis showed that although LID practices can downgrade the inundation hazard level to medium or low, most inundated areas cannot be eliminated at a high hazard level. This means that the inundation problem could not be resolved only with LID practices; and we should recognize the insufficiencies of LID practices.

10 4.3 Cost-effectiveness of LID practices

Under S 1 to S 6, the effectiveness of LID practices for urban inundation mitigation increased with more area implementing LID practices. However, Table 4 and Figure 5 showed that the reduction rates grew slowly with the increase of LID practices from 10 % to 100 %, which suggests that the efficiency of LID practices decreased from S 2 to S 6. A cost-effectiveness indicator (CEI) was used to better describe this phenomenon (Wu et al., 2017):

$$15 \quad \text{CEI} = \frac{R}{P} \quad , \quad (1)$$

where R is the reduction rate of inundation depth and inundation area, and P is the proportion of LID practices which means the cost. Table 7 showed that the CEI increased from S 1 to S 2 and decreased from S 2 to S 6, which means that the efficiency of the 10 % PP + 10 % GR scenario was higher than other scenarios. And we can clearly find that the reduction rates of maximum inundation depth are 7, 16, 22, 26 and 29 % from S 2 to S 6 and the CEI has reduced continuously, especially from S 4 to S 6. This indicates that wider implementation of LID practices may not lead to higher efficiency.

One of the causes behind the phenomenon is that LID practices can not control all the runoff of the watershed. Indeed, the runoff might not only come from sub-catchments around the inundation areas, but also come from other sub-catchments through the roads and pipe networks. And in this study, there are still some areas that can not implement LID practices. Therefore, the runoff from these areas can not be controlled by LID practices and directly influenced the effectiveness of inundation mitigation.

The phenomenon is common. In urban watershed, we could not transform all the roofs and roads to LID practices, and there are still some impervious covers that could influence the inundation that LID practices can not control. Therefore, we should recognize the insufficiencies of LID practices, and consider combine other measures such as restoring river systems, establishing urban wetlands, and improving urban drainage infrastructure to further promote the effectiveness on inundation mitigation. Besides, properly implementing construction intensity of LID practices to achieve optimal efficiency in urban watershed will be very important for the construction of Sponge City.

4.4 Limitations and future studies

Lacking accurate data is a common limitation for most studies. In this study, highly accurate elevation data for the study area is confidential and difficult to obtain; therefore, the ground elevation of streets were interpolated from the dense nodes of the pipe network. This method may have affected the simulation results. Moreover, the accuracy of the coupled model could be further increased with more accurate observed data and information of infrastructure, such as drainage pump station and river channel. Another limitation was that the definition of the thresholds for hazard levels was not considered sufficiently in this study. The results for the three hazard levels would be different if the thresholds changed. Therefore, research on criteria and sensitivity analysis of thresholds is needed in the future. The influences of rainfall intensity and frequency were not considered in this study, which is related to the effectiveness of LID.

10 In China, urban inundation appears to be increasing, and LID practices could be efficient strategies for urban inundation mitigation. At present, most research has focussed on the area with LID practices and the effects on urban inundation mitigation. However, the spatial distribution and landscape patterns of LID practices also contribute to urban flooding mitigation (Giacomini and Joseph, 2017; Kim and Park, 2016), but few studies have considered these variables. In addition, more studies should consider effective integration of LID practices into urban development (Chui et al., 2016), especially for

15 places vulnerable to urban flooding.

5 Conclusion

This study constructed a 2D inundation model that coupled SWMM and IFMS Urban at the urban watershed scale; the model was used to evaluate the effectiveness of LID practices for mitigating urban inundation under different scenarios and hazard levels. We found that the coupled model could be applied to evaluate the effectiveness of LID for urban inundation risk

20 mitigation. The model showed that PP were more effective for urban inundation mitigation than GR. This conclusion may be different in other regions, but it can be used by policy makers on a local basis. LID practices can only affect the inundation depth and downgrade the inundation hazard level, but cannot resolve inundation problems at a high hazard level. Therefore, other methods of stormwater management should also be applied to manage severe waterlogging. In the construction of Sponge City, people paid more attention to the effectiveness, while ignored the cost of LID. Through the analysis of cost-effectiveness,

25 we found that wider implementation of LID practices may not lead to higher efficiency in urban watershed, and the cost and effectiveness of LID practices should be considered in the construction of Sponge City.

Acknowledgements. This research was supported by the National Natural Science Foundation of China (Grant No.41330747 and No.41471370).

References

- Abbot, C. L., and Comino-Mateos, L.: In-situ hydraulic performance of a permeable pavement sustainable urban drainage system, *Journal of the Chartered Institution of Water and Environmental Management*, 17, 187-190, 2003.
- Ahiablame, L., and Shakya, R.: Modeling flood reduction effects of low impact development at a watershed scale, *J Environ Manage*, 171, 81-91, 10.1016/j.jenvman.2016.01.036, 2016.
- Ahiablame, L. M., Engel, B. A., and Chaubey, I.: Effectiveness of Low Impact Development Practices: Literature Review and Suggestions for Future Research, *Water, Air, & Soil Pollution*, 223, 4253-4273, 10.1007/s11270-012-1189-2, 2012.
- Ahiablame, L. M., Engel, B. A., and Chaubey, I.: Effectiveness of low impact development practices in two urbanized watersheds: retrofitting with rain barrel/cistern and porous pavement, *J Environ Manage*, 119, 151-161, 10.1016/j.jenvman.2013.01.019, 2013.
- Arnold, C. G., CJ: Impervious surface coverage - The emergence of a key environmental indicator, *JOURNAL OF THE AMERICAN PLANNING ASSOCIATION*, 62, 243-258, 10.1080/01944369608975688, 1996.
- Berndtsson, J. C.: Green roof performance towards management of runoff water quantity and quality: A review, *Ecological Engineering*, 36, 351-360, 10.1016/j.ecoleng.2009.12.014, 2010.
- Beckers, A., Dewals, B., Erpicum, S., Dujardin, S., Detrembleur, S., Teller, J., Piroton, M., and Archambeau, P.: Contribution of land use changes to future flood damage along the river Meuse in the Walloon region, *Natural Hazards and Earth System Sciences*, 13, 2301-2318, 10.5194/nhess-13-2301-2013, 2013.
- Bhattarai, R., Yoshimura, K., Seto, S., Nakamura, S., and Oki, T.: Statistical model for economic damage from pluvial floods in Japan using rainfall data and socioeconomic parameters, *Natural Hazards and Earth System Sciences*, 16, 1063-1077, 10.5194/nhess-16-1063-2016, 2016.
- Bliss, D. J., Neufeld, R. D., and Ries, R. J.: Storm Water Runoff Mitigation Using a Green Roof, *Environmental Engineering Science*, 26, 407-417, 10.1089/ees.2007.0186, 2009.
- Burns, M. J., Schubert, J. E., Fletcher, T. D., and Sanders, B. F.: Testing the impact of at-source stormwater management on urban flooding through a coupling of network and overland flow models, *Wiley Interdiscip. Rev.-Water*, 2, 291-300, 10.1002/wat2.1078, 2015.
- Chui, T. F. M., Liu, X., and Zhan, W.: Assessing cost-effectiveness of specific LID practice designs in response to large storm events, *Journal of Hydrology*, 533, 353-364, 10.1016/j.jhydrol.2015.12.011, 2016.
- Cipolla, S. S., Maglionico, M., and Stojkov, I.: A long-term hydrological modelling of an extensive green roof by means of SWMM, *Ecological Engineering*, 95, 876-887, 10.1016/j.ecoleng.2016.07.009, 2016.
- Claessens, L., Hopkinson, C., Rastetter, E., and Vallino, J.: Effect of historical changes in land use and climate on the water budget of an urbanizing watershed, *Water Resources Research*, 42, 10.1029/2005wr004131, 2006.

- Damodaram, C., Giacomoni, M. H., Prakash Khedun, C., Holmes, H., Ryan, A., Saour, W., and Zechman, E. M.: Simulation of Combined Best Management Practices and Low Impact Development for Sustainable Stormwater Management¹, *JAWRA Journal of the American Water Resources Association*, 46, 907-918, 10.1111/j.1752-1688.2010.00462.x, 2010.
- Davis, A. P.: Field performance of bioretention: Hydrology impacts, *Journal of Hydrologic Engineering*, 13, 90-95, 10.1061/(asce)1084-0699(2008)13:2(90), 2008.
- Davis, A. P., Traver, R. G., Hunt, W. F., Lee, R., Brown, R. A., and Olszewski, J. M.: Hydrologic Performance of Bioretention Storm-Water Control Measures, *Journal of Hydrologic Engineering*, 17, 604-614, 10.1061/(asce)he.1943-5584.0000467, 2012.
- Dietz, M. E.: Low Impact Development Practices: A Review of Current Research and Recommendations for Future Directions, *Water, Air, and Soil Pollution*, 186, 351-363, 10.1007/s11270-007-9484-z, 2007.
- Dietz, M. E., and Clausen, J. C.: Stormwater runoff and export changes with development in a traditional and low impact subdivision, *J Environ Manage*, 87, 560-566, 10.1016/j.jenvman.2007.03.026, 2008.
- Dreelin, E. A., Fowler, L., and Ronald Carroll, C.: A test of porous pavement effectiveness on clay soils during natural storm events, *Water Res*, 40, 799-805, 10.1016/j.watres.2005.12.002, 2006.
- EPA.: Low impact development (LID). A literature review, EPA-841-B-00e005, Office of Water, Washington, DC.
- Fassman, E. A., and Blackbourn, S.: Urban Runoff Mitigation by a Permeable Pavement System over Impermeable Soils, *Journal of Hydrologic Engineering*, 15, 475-485, 10.1061/(asce)he.1943-5584.0000238, 2010.
- Fewtrell, T. J., Neal, J. C., Bates, P. D., and Harrison, P. J.: Geometric and structural river channel complexity and the prediction of urban inundation, *Hydrological Processes*, 25, 3173-3186, 10.1002/hyp.8035, 2011.
- Giacomoni, M. H., and Joseph, J.: Multi-Objective Evolutionary Optimization and Monte Carlo Simulation for Placement of Low Impact Development in the Catchment Scale, *J. Water Resour. Plan. Manage.-ASCE*, 143, 15, 10.1061/(asce)wr.1943-5452.0000812, 2017.
- Hao, L., Sun, G., Liu, Y., Wan, J., Qin, M., Qian, H., Liu, C., Zheng, J., John, R., Fan, P., and Chen, J.: Urbanization dramatically altered the water balances of a paddy field-dominated basin in southern China, *Hydrology and Earth System Sciences*, 19, 3319-3331, 10.5194/hess-19-3319-2015, 2015.
- Hatt, B. E., Fletcher, T. D., Walsh, C. J., and Taylor, S. L.: The influence of urban density and drainage infrastructure on the concentrations and loads of pollutants in small streams, *Environ Manage*, 34, 112-124, 10.1007/s00267-004-0221-8, 2004.
- Hood, M. J., Clausen, J. C., and Warner, G. S.: Comparison of stormwater lag times for low impact and traditional residential development, *Journal of the American Water Resources Association*, 43, 1036-1046, 10.1111/j.1752-1688.2007.00085.x, 2007.
- Hu, M., Sayama, T., Zhang, X., Tanaka, K., Takara, K., and Yang, H.: Evaluation of low impact development approach for mitigating flood inundation at a watershed scale in China, *J Environ Manage*, 193, 430-438, 10.1016/j.jenvman.2017.02.020, 2017.

- Hunt, W. F., Traver, R. G., Davis, A. P., Emerson, C. H., Collins, K. A., and Stagge, J. H.: *Low Impact Development Practices: Designing to Infiltrate in Urban Environments, Effects of Urbanization on Groundwater*, edited by: Ni-Bin, C., 308-343 pp., 2010.
- Huong, H. T. L., and Pathirana, A.: Urbanization and climate change impacts on future urban flooding in Can Tho city, Vietnam, *Hydrology and Earth System Sciences*, 17, 379-394, 10.5194/hess-17-379-2013, 2013.
- Jacobson, C. R.: Identification and quantification of the hydrological impacts of imperviousness in urban catchments: a review, *J Environ Manage*, 92, 1438-1448, 10.1016/j.jenvman.2011.01.018, 2011.
- Kim, H. W., and Park, Y.: Urban green infrastructure and local flooding: The impact of landscape patterns on peak runoff in four Texas MSAs, *Applied Geography*, 77, 72-81, 10.1016/j.apgeog.2016.10.008, 2016.
- Kong, F. H., Ban, Y. L., Yin, H. W., James, P., and Dronova, I.: Modeling stormwater management at the city district level in response to changes in land use and low impact development, *Environ. Modell. Softw.*, 95, 132-142, 10.1016/j.envsoft.2017.06.021, 2017.
- Leopold, L. B., Wolman, M. G., and Miller, J. P.: *Fluvial Processes in Geomorphology*, *Geographical Journal*, 131, 1995.
- Liu, Y., Ahiablame, L. M., Bralts, V. F., and Engel, B. A.: Enhancing a rainfall-runoff model to assess the impacts of BMPs and LID practices on storm runoff, *J Environ Manage*, 147, 12-23, 10.1016/j.jenvman.2014.09.005, 2015.
- Lowe, R., Urlich, C., Domingo, N. S., Mark, O., Deletic, A., and Arnbjerg-Nielsen, K.: Assessment of urban pluvial flood risk and efficiency of adaptation options through simulations - A new generation of urban planning tools, *Journal of Hydrology*, 550, 355-367, 10.1016/j.jhydrol.2017.05.009, 2017.
- Luan, Q., Fu, X., Song, C., Wang, H., Liu, J., and Wang, Y.: Runoff Effect Evaluation of LID through SWMM in Typical Mountainous, Low-Lying Urban Areas: A Case Study in China, *Water*, 9, 439, 10.3390/w9060439, 2017.
- Mao, X., Jia, H., and Yu, S. L.: Assessing the ecological benefits of aggregate LID-BMPs through modelling, *Ecological Modelling*, 353, 139-149, 10.1016/j.ecolmodel.2016.10.018, 2017.
- Meyer, M. J. P. a. J. L.: Streams in the urban landscape, *Annual Review of Ecology and Systematics*, 32, 333-365, 10.1146/annurev.ecolsys.32.081501.114040, 2001.
- Morsy, M. M., Goodall, J. L., Shatnawi, F. M., and Meadows, M. E.: Distributed Stormwater Controls for Flood Mitigation within Urbanized Watersheds: Case Study of Rocky Branch Watershed in Columbia, South Carolina, *Journal of Hydrologic Engineering*, 21, 10.1061/(asce)he.1943-5584.0001430, 2016.
- Palla, A., and Gnecco, I.: Hydrologic modeling of Low Impact Development systems at the urban catchment scale, *Journal of Hydrology*, 528, 361-368, 10.1016/j.jhydrol.2015.06.050, 2015.
- Qin, H. P., Li, Z. X., and Fu, G.: The effects of low impact development on urban flooding under different rainfall characteristics, *J Environ Manage*, 129, 577-585, 10.1016/j.jenvman.2013.08.026, 2013.
- Rose, S., and Peters, N. E.: Effects of urbanization on streamflow in the Atlanta area (Georgia, USA): a comparative hydrological approach, *Hydrological Processes*, 15, 1441-1457, 10.1002/hyp.218, 2001.


- Rossmann, L. A.: Storm water management model user's manual version 5.0, U.S. Environmental Protection Agency, Washington, DC, EPA/600/R-05040, 2010.
- Roy, A. H., Wenger, S. J., Fletcher, T. D., Walsh, C. J., Ladson, A. R., Shuster, W. D., Thurston, H. W., and Brown, R. R.: Impediments and solutions to sustainable, watershed-scale urban stormwater management: lessons from Australia and the United States, *Environ Manage*, 42, 344-359, 10.1007/s00267-008-9119-1, 2008.
- Russo, B., Sunyer, D., Velasco, M., and Djordjevic, S.: Analysis of extreme flooding events through a calibrated 1D/2D coupled model: the case of Barcelona (Spain), *J. Hydroinform.*, 17, 473-491, 10.2166/hydro.2014.063, 2015.
- Salvadore, E., Bronders, J., and Batelaan, O.: Hydrological modelling of urbanized catchments: A review and future directions, *Journal of Hydrology*, 529, 62-81, 10.1016/j.jhydrol.2015.06.028, 2015.
- 5 Sang, Y.-F., and Yang, M.: Urban waterlogs control in China: more effective strategies and actions are needed, *Natural Hazards*, 85, 1291-1294, 10.1007/s11069-016-2614-4, 2016.
- Seyoum, S. D., Vojinovic, Z., Price, R. K., and Weesakul, S.: Coupled 1D and Noninertia 2D Flood Inundation Model for Simulation of Urban Flooding, *Journal of Hydraulic Engineering-Asce*, 138, 23-34, 10.1061/(asce)hy.1943-7900.0000485, 2012.
- 15 Son, A.-L., Kim, B., and Han, K.-Y.: A Simple and Robust Method for Simultaneous Consideration of Overland and Underground Space in Urban Flood Modeling, *Water*, 8, 494, 10.3390/w8110494, 2016.
- Su, B., Huang, H., and Li, Y.: Integrated simulation method for waterlogging and traffic congestion under urban rainstorms, *Natural Hazards*, 81, 23-40, 10.1007/s11069-015-2064-4, 2016.
- Trinh, D. H., and Chui, T. F. M.: Assessing the hydrologic restoration of an urbanized area via an integrated distributed hydrological model, *Hydrology and Earth System Sciences*, 17, 4789-4801, 10.5194/hess-17-4789-2013, 2013.
- 20 U.S. Department of Housing, and Urban Development: The practice of low impact development, Contract No. H- 21314CA, Office of Policy Development and Research, NAHB Research Center, Washington, DC, 2003.
- Wu, J. Y., Thompson, J. R., Kolka, R. K., Franz, K. J., and Stewart, T. W.: Using the Storm Water Management Model to predict urban headwater stream hydrological response to climate and land cover change, *Hydrology and Earth System Sciences*, 17, 4743-4758, 10.5194/hess-17-4743-2013, 2013.
- 25 Wu, X., Wang, Z., Guo, S., Liao, W., Zeng, Z., and Chen, X.: Scenario-based projections of future urban inundation within a coupled hydrodynamic model framework: A case study in Dongguan City, China, *Journal of Hydrology*, 547, 428-442, 10.1016/j.jhydrol.2017.02.020, 2017.
- Xia, J., Zhang, Y., Xiong, L., He, S., Wang, L., and Yu, Z.: Opportunities and challenges of the Sponge City construction related to urban water issues in China, *Science China Earth Sciences*, 60, 652-658, 10.1007/s11430-016-0111-8, 2017.
- 30 Zahmatkesh, Z., Burian, S. J., Karamouz, M., Tavakol-Davani, H., and Goharian, E.: Low-Impact Development Practices to Mitigate Climate Change Effects on Urban Stormwater Runoff: Case Study of New York City, *Journal of Irrigation and Drainage Engineering*, 141, 04014043, 10.1061/(asce)ir.1943-4774.0000770, 2015a.

Zahmatkesh, Z., Karamouz, M., Goharian, E., and Burian, S. J.: Analysis of the Effects of Climate Change on Urban Storm Water Runoff Using Statistically Downscaled Precipitation Data and a Change Factor Approach, *Journal of Hydrologic Engineering*, 20, 05014022, 10.1061/(asce)he.1943-5584.0001064, 2015b.

Zhang, S. G., Y.: SWMM simulation of the stormwater volume control performance of permeable pavement systems, *Journal of Hydrologic Engineering*, 20, 2015.

Zhang, X., Guo, X., and Hu, M.: Hydrological effect of typical low impact development approaches in a residential district, *Natural Hazards*, 80, 389-400, 10.1007/s11069-015-1974-5, 2016.

Zhu, Z., Chen, Z., Chen, X., and He, P.: Approach for evaluating inundation risks in urban drainage systems, *Sci Total Environ*, 553, 1-12, 10.1016/j.scitotenv.2016.02.025, 2016.



10

Figure 1: Location and land use map of the study area in the Guangming New District of Shenzhen, China.




Figure 2: Altitude (a) and SWMM model (b) of the study area.




Figure 3: Rainfall intensity for events on 11 May 2014 and 10 May 2016 in the study area.




Figure 4: Inundation depth maps of the study area under different scenarios.




Figure 5: Reduction rates of average inundation depth (a) and inundation areas (b) under different scenarios and hazard levels.

Table 1: LID parameters in SWMM.

LID types	structure	parameter	value
PP	Surface	Berm height (mm)	2
		Vegetation volume fraction	0
		Surface roughness (Manning's n)	0.014
		Surface slope (%)	1
	Pavement	Thickness (mm)	100
		Void ratio (voids/solids)	0.25
		Impervious surface fraction	0
		Permeability (mm/h)	250
	Storage	Clogging factor	0
		Thickness (mm)	150
		Void ratio (voids/solids)	0.4
		Seepage fate (mm/h)	1.2
GR	Surface	Clogging factor	0
		Berm height (mm)	3
		Vegetation volume fraction	0.1
		Surface roughness (Manning's n)	0.017
	Soil	Thickness (mm)	100

Drainage mat	Porosity (volume fraction)	0.5
	Field capacity (volume fraction)	0.2
	Wilting point (volume fraction)	0.024
	Conductivity (mm/h)	30
	Conductivity slope	5
	Suction head (mm)	60
	Thickness (mm)	3
	Void fraction	0.5
	Roughness (Manning's n)	0.1

Table 2: Primary calibrated parameters in SWMM.

SWMM parameters	calibrated value
N-Imperv	0.015
N-Perv	0.15
Dstore-Imperv/mm	2
Dstore-Perv/mm	5
Zero-Imperv/%	25
Roughness	0.013
Max.Infil.Rate(mm/h)	76
Min.Infil.Rate(mm/h)	12
Decay Constant	2
Drying Time	5

Table 3: Inundation depth in the observed and simulated results.

Inundation site	Storm on 11 May 2014			Storm on 10 May 2016		
	Observed	Simulated	RE (%)	Observed	Simulated	RE (%)
Gm 11	0.25	0.32	28	0.2	0.24	20
Gm 12	0.55	0.69	25	0.7	0.75	7
Gm 20	0.5	0.24	-52	0.4	0.42	5
Gm 21	0.45	0.46	2	—	—	—
Gm 24	0.2	0.26	30	—	—	—
Gm 22	0.2	0.2	0	—	—	—
Gm 16	0.2	0.23	15	—	—	—

5

“—” means data miss, “RE” means “relative error”, unit: m.

Table 4: Maximum inundation depth under different scenarios.

	Benchmark	Scenario 1	Scenario 2	Scenario 3	Scenario 4	Scenario 5	Scenario 6	Scenario 7	Scenario 8
maximum inundation depth (m)	0.69	0.67	0.64	0.58	0.54	0.51	0.49	0.59	0.59
Reduction rate (%)	—	3	7	16	22	26	29	14	14

Table 5: Inundation time under different scenarios and hazard levels.

	Benchmark	Scenario 1	Scenario 2	Scenario 3	Scenario 4	Scenario 5	Scenario 6	Scenario 7	Scenario 8
Low (h)	3.4	3.4	3.5	3.7	3.3	2.5	2.2	3.3	3.3
Medium (h)	7.7	7.8	8	8.2	7.1	6	4.7	7.5	7.7
High (h)	10.6	10.3	10.5	9.6	7.6	6	4.7	9.3	8.4
Total (h)	4	3.9	4	4.1	3.6	2.8	2.3	3.6	3.6

5 Table 6 Sensitivity of inundation to LID parameters.

Parameter		Inundation reduction (%)	
		Permeable pavement	Green roof
Surface	Berm height	-3%	-1%
	Thickness	-15%	—
Pavement	Permeability	-2%	—
	Thickness	—	-17%
Soil	Porosity	—	-19%
	Conductivity	—	0%
	Thickness	-16%	—
storage	Void ratio	-18%	—

Table 7: CEI under different scenarios.

	Scenario 1	Scenario 2	Scenario 3	Scenario 4	Scenario 5	Scenario 6
maximum inundation depth	0.58	0.72	0.64	0.44	0.35	0.29
average inundation depth	2.76	3.31	2.24	1.40	1.01	0.77
average inundation areas	1.40	1.46	1.35	0.93	0.71	0.55