

## ***Interactive comment on “Stability assessment of roadbed affected by ground subsidence adjacent to urban railways” by Ki-Young Eum et al.***

**Ki-Young Eum et al.**

ssj@inje.ac.kr

Received and published: 8 March 2018

The comment was uploaded in the form of a supplement:  
<https://www.nat-hazards-earth-syst-sci-discuss.net/nhess-2017-412/nhess-2017-412-AC1-supplement.pdf>

Interactive comment on Nat. Hazards Earth Syst. Sci. Discuss., <https://doi.org/10.5194/nhess-2017-412>, 2017.

[Printer-friendly version](#)

[Discussion paper](#)



**Referee #1**

- 1. Abstract: Too many background descriptions are presented and too few results are found in the abstract. Four sentences from lines 13 to 17 in page 1 may be merged in a sentence. However some valuable results and conclusions, e.g., the roadbed settlement and the effects of groundwater level, may be added.**

**P.1. Line 13-26:** Background descriptions are briefly presented and four sentences from lines 13 to 17 in page 1 are merged in a sentence. The roadbed settlement and the effects of groundwater level are added in Abstract.

*In recent years, leakages in aged pipelines for water and sewage in urban areas have frequently induced ground loss resulting in cavities and ground subsidence causes the roadbed settlement greater than the allowable value. In this study, FLAC<sup>3D</sup>, which is a three-dimensional finite-difference numerical modeling software, is used to do stability and risk level assessment for the roadbed in adjacent to urban railways with respect to various groundwater levels and the geometric characteristics of cavities. Numerical results show that roadbed settlement increases as the diameter (D) of the cavity increases and the distance (d) between the roadbed and the cavity decreases. The regression analyses results show that, as D/d is greater than 0.2 and less than 0.3, the roadbed is in the status of caution or warning. It requires a database of measurement sensors for real-time monitoring of the roadbed, structures and groundwater to prevent disasters in advance. As D/d exceeds 0.35, the roadbed settlement, which substantially increases and the roadbed is in the status of danger. Since it may result in highly probable traffic accident, train operation should be stopped and the roadbed should be reinforced or repaired. The effects of groundwater level on the roadbed settlement are examined and the analyses results indicate that a roadbed settlement is highly influenced by groundwater levels to an extent greater than even the influence of the size of the cavity.*

- 2. Discussion in the segment is not clear, and I think the segment is needed to be rewritten**

**P.11. Line 358-376:** Discussion is rewritten in detail.

*The number of occurrences of ground subsidence induced by a leakage of aged pipelines for water and sewage in urban areas resulting in various sizes of cavity near the urban railway in Seoul City has been found to increase and it may cause the roadbed settlement to exceed the allowable value. A large-scale cavity is rarely found, but if it is close to the roadbed, the roadbed is highly influenced by the cavity and may cause train derailment.*

*In this study, numerical analyses are carried out to estimate roadbed stability and its risk level associated with various groundwater levels, sizes of cavities. The analyses results show that roadbed settlement increases as the diameter (D) of the cavity increases and the distance (d) between the roadbed and the cavity decreases. The regression analyses results show that, as D/d is greater than 0.2 and less than 0.3, a database of measurement sensors should be established for real-time monitoring of the roadbed, structures and groundwater to prevent disasters in advance. As D/d exceeds 0.35, the roadbed settlement, which substantially increases and is in the status of danger, may result in highly probable traffic accident. Therefore, train operation should be stopped and the roadbed should be reinforced or repaired. The effects of groundwater level on the roadbed settlement are examined at the distance of 20 m for both 4 and 6 m diameter cavities and at 25 m for both 8 and 10 m diameter cavities. Ground settlement for 4 and 6 m diameter cavities located at a distance of 20 m from the roadbed satisfies the allowable value for GWL = (+) 4 and (-) 12m, respectively. The ground settlement for 8 and 10 m diameter cavities located at a distance of 25 m from the center of the roadbed has substantially decreased as GWL is 8 and 15 m below the ground surface, respectively, and satisfies the allowable value as its level is 18 and 22 m below the ground surface, respectively. It indicates that a roadbed settlement is highly influenced by groundwater levels to*

Fig. 1.

C2

Printer-friendly version

Discussion paper

