

1 **New approaches to modelling of local seismic amplification susceptibility using direct**
2 **characteristics of influencing criteria: case study of Bam City, Iran**

3
4 Reza Hassanzadeh¹, Mehdi Honarmand², Mahdiah Hossienjani Zadeh³, Farzin Naseri⁴

5
6 Department of Ecology, Institute of Science and High Technology and Environmental
7 Sciences, Graduate University of Advanced Technology, Kerman, 7631133131, Iran.

8 1. Hassanzdeh22@yahoo.com, 2. Mehonarmand167@yahoo.com, 3. mh.hosseinjani@gmail.com,
9 4. fnnaseri@yahoo.com

10
11 Correspondence to: Reza Hassanzadeh (Hassanzdeh22@yahoo.com and r.hassanzdeh@kgut.ac.ir).

12
13 **Abstract**

14 This paper proposes a new model in evaluating local seismic amplification susceptibility by considering
15 direct characteristics of influencing criteria and it deals with uncertainty of modelling through production
16 of fuzzy membership functions for each criterion. For this purpose, relevant criteria were identified by
17 reviewing previous literature. These criteria include alluvial thickness, stiffness and strength of alluvial
18 deposits, type of soil and particle size distribution of alluvial deposits, depth of groundwater, type of rock,
19 topographic irregularities, slope and type of bedrock. Two methods, Analytic Hierarchy Process (AHP)
20 and Fuzzy Logic (FL), were applied in order to define priority rank of each criterion and sub-criteria of
21 each criterion through interview data of 10 experts. The criteria and sub-criteria were combined using
22 Weighted Linear Combination method in GIS to develop a model for assessing local seismic amplification
23 susceptibility in the study area of Bam city, Iran. The model's output demonstrated high to very high
24 seismic amplification levels in central, eastern, north-eastern and northern parts of the study area. The
25 validation results based on overall accuracy and Kappa statistics showed 73.6% accuracy, 0.74 Kappa
26 indicating a good fit to the model's output. This model assists planners and decision makers to produce
27 local seismic amplification susceptibility to be incorporated in designing new development plans of urban
28 and rural areas, and to facilitate making informed decision regarding safety measures of existing buildings
29 and infrastructures.

30 **Keywords:** *Seismic Amplification Susceptibility, Site Effects, Spatial Modelling, Analytic Hierarchy*
31 *Process, Fuzzy Logic and GIS.*

۳۴

۳۵ **1. Introduction**

۳۶ This paper explores direct characteristics of influencing criteria in evaluating susceptibility of local
۳۷ seismic amplification and deals with uncertainty of modelling through production of fuzzy membership
۳۸ functions of each criterion. MERM microzonation manual (2003) sets different criteria effecting
۳۹ the amplitude and duration of ground shaking at a specific site. These include “the magnitude of
۴۰ the earthquake, focal point and depth of the earthquake, directivity of the energy released,
۴۱ distance of rupture from the site, **geological condition from the site to the location of the**
۴۲ **earthquake, local geological settings, geotechnical properties, and topographical condition of the**
۴۳ **site” (SM Working Group, 2015;Boore, 2003;Hassanzadeh et al., 2013;Castelli et al.,**
۴۴ **2016a;Castelli et al., 2016b).** It has long been known that local conditions of foundation soils
۴۵ have a significant impact on the effects of an earthquake on building destruction level, as it was
۴۶ demonstrated in previous earthquakes such as Mexico City, 1985 (Beck and Hall, 1986), Kobe,
۴۷ 1995 (Wald, 1996), Izmit, 1999 (Tang, 2000), Umbria-Marche earthquake, 1997 (Moro et al.,
۴۸ 2007) and Bam earthquake, 2003 (Ramazi and Jigheh, 2006) **and L'Aquila earthquake, 2009**
۴۹ **(Monaco et al., 2012;Capilleri et al., 2014)** and buildings that were located on unconsolidated
۵۰ sediments had greater destruction levels (Ramazi and Jigheh, 2006).

۵۱ The aim of seismic microzonation studies is to produce ground-shaking map that can
۵۲ communicate efficient data to planners and policy makers in a geographic area to make informed
۵۳ decision regarding development policies in urban areas. Therefore, this community requires
۵۴ accurate information for developing mitigation plans and strategies. In the spite of this, there are
۵۵ uncertainties in determining local seismic amplification at a site, as this can be influenced by
۵۶ complex factors such as the earthquake source (epicenter of the earthquake), wave propagation
۵۷ and site condition. Uncertainty in these criteria results in uncertain ground-motion estimate from
۵۸ earthquakes (Wang et al., 2017;Wang et al., 2016;Petersen et al., 2016). There are different
۵۹ methods that have been used for assessing ground-motion hazards such as Probabilistic Seismic
۶۰ Hazard Analysis (PSHA), Deterministic Seismic Hazard Analysis (DSHA) and Scenario-based
۶۱ Seismic Hazard Analysis (SSHA). Probabilistic Seismic Hazard Analysis (PSHA) method
۶۲ (Cornell, 1968;Atkinson et al., 2015;Petersen et al., 2016) depends on “the length of the causative
۶۳ faults and depth of the earthquake”, which are generally unknown thus causing uncertainty in
۶۴ assessing ground-motion of earthquakes (Wang et al., 2017). In DSHA method (Campbell,

2003;Atkinson and Boore, 2006) lack of relevant ground-motion attenuation relationship for specific geographic areas can cause uncertainty in assessing ground motions of an earthquake (Wang et al., 2017). SSHA (Panza et al., 2012) applies ground-motion simulations of a scenario earthquake using specified source, path and site parameters, however the parameters needs to be defined in more details. By conducting many simulations, earthquake variability of different sources, ground-motion propagation characteristics, and local site effects can be considered. Therefore, uncertainties using SSHA are quantified explicitly (Wang et al., 2017), although this method is still under development. Furthermore, **Aucelli et al. (2018) proposed a method for producing susceptibility index to local seismic amplification in Isernia Province, Italy based on geological and geomorphological properties of studied areas. This research mostly followed an evidence based approach to estimate susceptibility level of local seismic amplification in the area, although they have not considered the use of multi-criteria decision-making methods (MCDM)in their study.** Several MCDM methods have been developed to deal with ranking and weighting of criteria, such as Regime (Hinlopen et al., 1983), ELECTRE family (Figueira et al., 2005), Analytical Hierarchy Process (AHP) (Saaty, 1980), and Multiple Attribute Utility approach (MAUT) (Keeney and Raiffa, 1993). In this research, Analytical Hierarchal Process (AHP) (Saaty, 1980) has been utilize as it is one of the most useful method in calculating criteria's weights, and AHP in combination with GIS were applied to produce seismic microzonation map of Bangalore (Sitharam and Anbazhagan, 2008) (2008), Dehli (Mohanty et al., 2007), Haldia, Bengal Basin (India) (Mohanty and Walling, 2008), Erbaa (Turkey) (Akin et al., 2013) and Al-Madinah (Moustafa et al., 2016) **and generating ground-shaking map for Catania (Italy) using GIS (Castelli et al., 2016a).** According to these methods experts evaluate and choose among qualitative and quantitative criteria. Since experts' judgments can be subjective and imprecise, uncertainty also exists in this analysis. Such uncertainties can be dealt with based on fuzzy logic principles (Zadeh, 1965) and inference systems (Klir, 2004;Zadeh, 1975). Fuzzy Logic method was used for evaluation of earthquake damage to buildings (Sen, 2010), and evaluation of seismic microzonation (Teramo et al., 2005;Nath and Thingbaijam, 2009;Boostan et al., 2015). Although, there were a number of publications on evaluating the local seismic amplification in the literature, but few researchers have considered the use of Fuzzy Logic approach and direct characteristics of each criteria in evalaution of local seismic amplification susceptibility. These are motivations **behind** conducting this research.

96 The purpose of this paper is to develop a model for evaluation of local seismic amplification
97 based on direct characteristics of relevant criteria. Firstly, selected criteria were weighted using
98 AHP method by interviewing 10 experts, next criteria were converted into fuzzy sets, then fuzzy
99 membership functions (MFs) were produced, finally WLC method and fuzzy inference rules
100 were applied to produce a level - 1 susceptibility map of local seismic amplification for a study
101 area.

102 **2. Material and methods**

103 This study investigates the importance of influencing factors on susceptibility of local seismic
104 amplification. Firstly, these criteria have been derived by a critical analysis of previous literature.
105 Secondly, Analytic Hierarchy Process (AHP) and Fuzzy Logic (FL) Methods have been applied
106 to deal with weighting and fuzziness of criteria due to associated uncertainties in decision-making
107 process on preparing susceptibility map of local seismic amplification through interviewing experts.
108 Next, criteria and sub criteria have been combined based on WLC method to develop a model.
109 Finally, the model has been validated using Overall Accuracy (OA) and Kappa statistics methods
110 by comparing to the measured. This study has been conducted on the case study of Bam City,
111 southeast of Iran (Figure 1), and it followed four steps of investigations shown in figure 2.
112

113
114
115 **Figure 1. Case study of Bam City, Iran**

116
117 **Figure 2. The methodological approach of the study**

118 119 120 **2.1. Identification, Weighting and Fuzzification of Criteria**

121 The susceptibility level of local seismic amplification can be influenced by several criteria. These
122 criteria were identified by reviewing literature and interviewing experts through data gathering
123 process. Then, identified and selected criteria were weighted and fuzzified using AHP and FL
124 methods, as explained in the following sub-sections.
125
126

127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154

2.2.1. Analytical methods

2.2.1. Analytic Hierarchy Process (AHP) method

AHP is one of the most commonly used multi-criteria decision making (MCDM) tools, and allows the consideration of both objective and subjective factors in ranking alternatives in a hierarchical decision model (Saaty, 1980; Saaty, 1990). This method is applied to convert the experts' view on the importance of each criterion and sub-criterion to a numerical value by comparing each other, one pair at a time (pair-wise comparison) (Saaty, 1980).

AHP matrix (A) is developed from the pair-wise comparison of the relative importance of criterion A_i to criterion A_j (α_{ij}, represents a quantified judgment on a pair of criteria) (Figure 3). The values assigned to α_{ij} according to the Saaty's scale (1980) range from 1 to 9 or their reciprocals. In order to calculate the priority ranking of each criterion (weight), Saaty (1990) suggested the mathematical computation of eigenvector based on Eq. 1 & 2.

Figure 3.AHP matrix (A)

$$\lambda_{max} = \sum_{j=1}^n a_{ij} \frac{W_j}{W_i} \tag{Eq. 1}$$

Where: λ_{max}= the largest eigenvalue; α_{ij}= judgment; W_i & W_j = numerical weights for judgment α_{ij}.

$$(A - \lambda_{max} I)X = 0 \tag{Eq. 2}$$

Where: A= AHP matrix; λ_{max}= the largest eigenvalue; I= Unique matrix; X= eigenvector.

In addition, the assignment of weights to each criterion relates to the process of the experts' logical and analytical thinking, which is tested for each matrix with Consistency Ratio (CR) statistics. If this statistics is less than 0.1 (CR < 0.1), the experts' answers are logical. Following the testing for consistency, the weights are aggregated to determine ranking of decision

100 alternatives (the weights) for each criteria. Therefore, in this research, AHP method is applied to
106 calculate the degree of importance of each criterion influencing on the susceptibility level of local
107 seismic amplification in a region,

108
109
110

111 **2.2.2. Fuzzy Logic (FL) method**

112 Fuzzy logic is a method of “approximating modes of reasoning” (Novák et al., 2012), and it is a
113 mathematical tool that deals with uncertainty in a different way that can relate independent
114 variables to dependent variables. Zadeh (1965) introduced Fuzzy set theory indicating that the
115 boundary is not precise and the gradual change is expressed by a membership function, and it
116 changes from non-membership to membership in a fuzzy set (Eq. 3). The characteristic function
117 value range between 0 and 1. Each membership function is represented by a curve that indicates
118 the assignment of a membership degree in a fuzzy set to each value of a variable. Curves of the
119 membership functions can be linear, triangles, trapezoids, bell-shaped, or have more complicated
120 shapes (Figure 4) depending on the purpose of the subject (Demicco and Klir, 2003).

121

$$122 A_a = \{x \in X \mid \mu_A(x) \geq a\} \quad (Eq. 3)$$

123 Where A_a is called the a-cut or a-level set of A, and $\mu_A(x)$ represents membership degree of the
124 element x.

125

126 Figure 4. Fuzzy membership functions (After Mancini, 2012)

127

128 Fuzzy systems are mainly based on expert knowledge to formalize reasoning in natural language
129 mostly using sets of fuzzy inference rules or “if-then” rules (Eq. 4).

130

$$131 \textit{If } x \textit{ is } A \textit{ then } y \textit{ is } B \quad (Eq. 4)$$

132

133 As membership functions curve can easily be changed by small increments based on expert
134 knowledge, therefore, fuzzy logic can characterize and model geologic systems in an efficient
135 way (Klir, 2004;Demicco and Klir, 2003). Therefore, in this research using Fuzzy set, the

186 uncertainties in producing microzonation map of ground shaking can be managed by defining
187 fuzzy membership functions for each criterion. This happens by assigning meaningful values (0
188 to 1) to each individual (sub criteria) of each criterion. For the purpose of defuzzification, largest
189 of maximum method was applied. Based on this method the largest value of the fuzzy subset was
190 the output value (Mancini et al., 2012).

191

192 **2.3. Data gathering**

193 In order to identify influencing criteria in local seismic amplification the required data were
194 collected through a literature review and semi-structured interviews with 10 experts who were
195 involved in the geology, seismology, tectonic, structural engineering, and geomorphology fields.
196 They were asked about the criteria that can influence local seismic amplification, and then these
197 data were analyzed using AHP and FL methods as explained in the following:

198

199 **2.3.1. Determining the relevant criteria by reviewing literature**

200 The potential criteria influencing local seismic amplification susceptibility were determined
201 through a critical review of literature. By reviewing documents on earthquake engineering,
202 seismology, geology, tectonic and structural engineering, geomorphology and seismic
203 microzonation reports and guidelines (Fäh et al., 1997;Ding et al., 2004;Molina et al.,
204 2010;Mundepi et al., 2010;Marulanda et al., 2012;Hassanzadeh et al., 2013;Federal Emergency
205 Management Agency (FEMA), 2014;Fraume et al., 2014;Grelle et al., 2016;Grelle et al., 2014;SM
206 Working Group, 2015;Rehman et al., 2016;Nwe and Tun, 2016;Global Earthquake Model (GEM),
207 2017;CAPRA, 2017;Michel et al., 2017;Trifunac, 2016;Hassanzadeh and Nedovic-Budic, 2016),
208 and in total 14 influencing criteria were identified (Table 1).

209

210 Table 1.Relevant criteria that influence on local seismic amplification susceptibility

211

212

213 **2.3.2. Experts' Knowledge data**

214 *a) Interviewing disaster managers (semi-structured interviews) to determine the*
215 *important criteria*

216 The most important criteria were determined by conducting a semi-structured interview with 10
217 experts using the snowball or chain-referral sampling method (Biernacki and Waldorf, 1981). In
218 this study, all 10 interviewees were highly experienced and had been involved in seismic
219 microzonation studies. The average age of the sampled individuals was 43 years, and all of them
220 had a postgraduate degree.

221 A list of criteria that were identified by reviewing previous studies were given to the experts and
222 they were requested to add other criteria if they thought they were applicable. They were asked
223 to rank each criterion using a five-point Likert Scale (Likert, 1932), so respondents could choose
224 the option that best reflected their opinion on each criterion. When surveying many people on
225 the same criterion, the five codes could be summed up, averaged or calculate the mode, indicating
226 overall positive or negative orientation towards that criterion. This was the basis from which this
227 method was used to identify the degree of importance for each criterion in local seismic
228 amplification in a region. Therefore, in order to elicit the most relevant criteria, the significance
229 of specific factors were measured on a five-point Likert Scale where 1 represents ‘not important
230 at all’, 3 ‘of little importance’, 5 ‘of average Importance’, 7 ‘very important’, and 9 ‘extremely
231 important’ (Likert, 1932; Jamieson, 2004). The collected data were analysed and criteria with
232 mean ratings above ‘5’ (‘of average important’) were selected (Table 2). These have been then
233 considered for further analysis using the Analytic Hierarchy Process (AHP) method.

234
235 Table 2. The average importance criteria based on 5-point Likert Scale

236 *b) Interviewing disaster managers (structured interviews) in order to collect data for*
237 *computing the relative importance (weights) of the criteria*

238 A questionnaire based on AHP matrix (A) was developed for a pair-wise comparison of the
239 relative importance of the criteria for calculating the weights (priority ranking) of each criterion.
240 As AHP is a subjective method therefore a large sample size is not needed (Cheng and Li,
241 2002; Lam and Zhao, 1998). For this reason, data were collected by interviewing 10 experts (the
242 same experts who were interviewed in the first round) based on the structured questionnaire

۲۴۳ (closed-ended questions). They were asked to compare the relative importance of each criterion
۲۴۴ against all others, based on Saaty's scale by verbal preferences (Saaty, 1980). A pair-wise
۲۴۵ comparison that was carried out with an expert is shown in Table 3. These data are used by the
۲۴۶ AHP method to compute the weight of each criterion as explain previously.

۲۴۷
۲۴۸ Table 3.The results of pair-wise comparisons of the selected criteria with each other based on
۲۴۹ the AHP matrix

۲۵۰
۲۵۱ *c) Determining fuzzy set and fuzzification of thresholds of sub-criteria for each criterion*

۲۵۲ In the next step, since each criterion and its sub-criteria has different effect on local seismic
۲۵۳ amplification susceptibility in a region, fuzzy membership functions (MFs) for sub criteria of
۲۵۴ each criterion are defined. As, designed parameters of each membership function depends on
۲۵۵ experts knowledge, then number of memberships, the shape, the positioning, and the overlay area
۲۵۶ of memberships of each MFs for each criterion would be different. To conduct this analysis, 10
۲۵۷ experts were interviewed regarding membership degree of sub criteria of each criterion, and
۲۵۸ mode of each sub criteria was calculated and MFs for each criterion was depicted as **described** in
۲۵۹ the following:

۲۶۰ - Thickness of soil and sediments: an effective factor in site effect assessment is the thickness of
۲۶۱ sediments. Rezaei et al. (2009) stated that the soil thickness demonstrated a positive relationship
۲۶۲ to damage rate observations in the Bam earthquake. This layer was produced by 245 geophysical,
۲۶۳ geotechnical, and sedimentological sampling sites across the city. The alluvial thickness varies in
۲۶۴ different parts of the city. In the northern part of the city, the sediment (**marine to continental**
۲۶۵ **Quaternary deposits including alluvial plain gravels with interlayered clay, silt and sand**) thickness
۲۶۶ ranges from 0 m, where bedrock is exposed beneath Arg-e-Bam, to 90 m across most of the
۲۶۷ northern half of the study area. Toward the south and center of the study area, sediment thickness
۲۶۸ increases over a short distance, to more than 270 m. This defines a subsurface of high sediment
۲۶۹ thickness that extends across the entire study area from west to east and underlies south-central
۲۷۰ Bam. Therefore, based on a positive relationship between the damage rate and alluvial thickness
۲۷۱ (Rezaei et al., 2009;Marie Nolte, 2010), MF for this criterion is depicted in figure 5a.

۲۷۲
۲۷۳ - Consolidation and strength of soil and sediments: It has been frequently observed that earthquake
۲۷۴ damage is greater in settlements located on unconsolidated and soft soils than in those sited on
۲۷۵ stiff soils or hard rock. For example, in Bam earthquake strong amplification occurred due to the
۲۷۶ extremely soft clay layers that caused high-rise buildings to collapse (Jafari et al., 2005). Another
۲۷۷ example was the Loma Prieta earthquake that happened in 1989, where much of the damage
۲۷۸ occurred in the central San Francisco Bay area at sites underlain by thick deposits of soft clay soils
۲۷۹ (Stewart, 1997). The soil classification has been based on different thresholds for the average shear
۲۸۰ wave velocity (V_s) to a depth of 30m by the National Earthquake Hazard Reduction Program
۲۸۱ (NEHRP) to characterize sites for purposes of estimation amplification of seismic motions. This
۲۸۲ standard has applied in Unified Building Code (Dobry et al., 2000) and Eurocode8 (Sabetta and
۲۸۳ Bommer, 2002; Kanlı et al., 2006). Based on this classification in areas on unconsolidated
۲۸۴ sediments, shear wave velocity reduces, and expected amplification during earthquakes could be
۲۸۵ increased. Therefore, according to this MFs for each class have been calculated as shown in figure
۲۸۶ 5b.

۲۸۷
۲۸۸ - Type of soil and particle size distribution of sediments: It has long been recognized that the
۲۸۹ destructiveness of ground shaking during earthquakes can be significantly worsened by the type
۲۹۰ of local soil and subsurface sediment conditions. In past events, the observed variability in seismic
۲۹۱ intensity and structural damage severity has often been attributed to the variability of soil and
۲۹۲ subsurface sediment stratigraphy in a given area. Among the geotechnical properties of soil and
۲۹۳ sediments, grain size is one of the most important criteria (Assimaki et al., 2006; Phoon et al.,
۲۹۴ 2006). In the study area, Rezaei et al. (2009) identified eight sediment types: clay, silt, sand,
۲۹۵ granules, pebbles, cobbles, and boulders. They stated that the grain size in the shallow subsurface
۲۹۶ (<10 m) decreases across the city from south to north and increases with depth. Their investigation
۲۹۷ showed that fine-grained soils and sediments (clay, clayey sand, cohesive sandy mud, and cohesive
۲۹۸ muddy sand) dominated the northern part of the city at shallow depths. In the central part of the
۲۹۹ city, fine-grained sediments changed laterally to coarse-grained sediments (poorly sorted sand,
۳۰۰ well-rounded gravel, poorly sorted gravel, and muddy or sandy gravel) which dominated in the
۳۰۱ south part of the city. As a rule, it can be assumed that, the smaller the grain size of sediments, the
۳۰۲ less the shear waves velocity and therefore the greater the effect of the seismic wave on the

303 destruction level of buildings (Rezaei et al., 2009;Assimaki et al., 2006;Phoon et al., 2006).
304 Therefore, the MFs for each specific grain size are calculated in figure 5c.

305
306 - Depth of groundwater: Research on the effects of groundwater shows it can magnify an
307 earthquake's damage. The most well known effect is liquefaction. The geologic and hydrologic
308 factors that affect liquefaction susceptibility are the age and the type of sedimentary deposits, the
309 looseness of cohesions and the depth to the groundwater table (Tinsley et al., 1985;Cavallaro et
310 al., 2018). The liquefaction is mostly limited to water-saturated, cohesions less sediments and
311 granular sediments at depths less than 15m (Iguchi and Tainosho, 1998;Sitharam, 2010). Noack
312 and Fah (2001) categorized it by the depth of the water table, which is split into three classes where
313 the weight of the class increases while the groundwater table decreases (Fäh et al., 1997).
314 Therefore, due to the geological conditions in Bam, liquefaction is considered of minor importance
315 because Talebian et al. (2004) and Rezaei et al. (2009) found water saturated sands in very few
316 places, however, they reported high amplification in areas that groundwater level was very close
317 to the ground surface by analyzing microtremore data. Accordingly, MFs for each class of
318 groundwater depth are computed as shown in figure 5d.

319 - Type of rock: Type of rocks can effect on local seismic amplification susceptibility in a region.
320 Three main types of rock based on their formation process include igneous, metamorphic, and
321 sedimentary rocks. Each type has its own sub-categories and what matter in this research is how
322 hard or soft and how dense the specific type of rocks is in comparison with the other types.
323 Geological Strength Index (GSI) of "rock masses depends on rock's material, the amount of joints
324 and their relations, alteration, and presence of water" (Hoek and Brown, 1997). There are many
325 rock types in the nature that GSI can be calculated for any of them based on their condition, and
326 then can be fuzzified addressing their effect on seismic microzonation level of ground shaking.
327 There are five classes of GSI including very good, good, fair, poor and very poor based on their
328 surface quality and interlocking of rock pieces from massive, blocky, very blocky, disintegrated,
329 and laminated/ sheered (Marinos et al., 2007). The GSI values categorized in five classes including
330 very low, low, medium, high and very high levels. These classes shows the geological strength of
331 rocks that the high and very high GSI demonstrate high to very high strength of rocks. Therefore,
332 previous studies demonstrates that in massive rocks, high GSI values, seismic waves passes

quickly and therefore have small influence in seismic microzonation level of ground shaking, and vice versa if GSI value gets to the lower values. Thus, in fuzzyfication process of surficial rocks, the rock with very high GIS assign 0 and the rocks with very low GSI assign 1 (Figure 6a). Furthermore, the criterion of type of bedrock acts the same as surficial rock type criterion as explained above. Type of bedrock rarely changed over a small extent with homogenous lithology. However, it was concern of experts in determining local seismic amplification susceptibility.

- Slope: The effects of slope angle on topographic amplification factor was investigated by Bisch et al. (2012), and they classified the slope angle into three categories with different effect level including: 0-15 with no effect, 15-30 degree with 1.2 (coefficient) and more than 30 degree with 1.4 amplification coefficient. **Although, Cavallaro et al. (2012) suggested that topographic amplification factor can be considerable for slope even less than 15 degree.** Furthermore, Bouckovalas and Papadimitriou (2005) investigated the influence of slope topography in amplifying the peak horizontal seismic ground acceleration suggesting high amplifications near the crest. Grelle et al. (2016) presented formulae for topographic amplification on slope surface. These studies indicated that with the increase in slope angle the amplification factor would increase. This can be a basis for depicting MFs of this criterion (Figure 6b).

- Topographic irregularities: **Seismic amplification has been witnessed in several earthquakes due to topographical changes (Geli et al., 1988;Paolucci, 2002;Cavallaro et al., 2012).** Bisch et al. (2012) classified the site in two classes of “isolated cliff and ridge with crest width significantly less than base width” (CEN European Committee for Standardisation, 1994, p 93). However, this seems simplistic, as it does not consider the elevation differences. Furthermore, Grelle et al. (2016) presented an equation that considered the local slope height, relief height, regional shear wave velocity and relief ratio. **In addition, several calibration constants should be calculated using 2d numerical analysis for each study area to compute topographic effects on local seismic amplification. Cavallaro et al. (2008) investigated 2d model for analysing site response of the Monte Po Hill in the City of Catania considering the effect of topographic and stratigraphic properties on the amplification factor in an area. They concluded that near to the slop crest, the effect of topographic properties on amplification factor is more relevant than stratigraphic property.** Lee et al. (2009) found out that the amplification on top of elevated surfaces with small extent was much higher than valleys and flat areas. Therefore, the elevation differences (dH m)

between the bases of a hill to the top of the hill, and the area ($A \text{ m}^2$) of the top part of the hill are the main driver in computing the amplification coefficient of seismic waves that can effect on local seismic amplification susceptibility level of ground. Therefore, the higher the elevation differences and the smaller the area of the elevated surface, the ground in this part will be more amplified. Here, using fuzzy logic and experts' knowledge the effect of topography in terms of elevation differences in determining local seismic amplification susceptibility in the study area is defined (Figure 6c).

Figure 5. Membership functions (MFs) based on fuzzy logic system: Thickness of soil and sediments (a), Consolidation and strength of soil and sediments (b), Type of soil and particle size distribution of sediments (c), Depth of groundwater (d).

Figure 6. Membership functions (MFs) based on fuzzy logic system: Type of rock and bedrock (a), Slope (degree) (b), Topographic irregularities (c).

2.3.3. *Preparing thematic data*

The required data were collected from relevant organizations and documents and they were converted to GIS files in that papered maps were scanned, geo-referenced and then digitized. These maps were imported into a geodatabase to validate topological rules and overlaying condition for all layers. To produce thematic maps, interpolation method such as IDW method was applied. The produced maps then were classified based on sub-criteria for each criterion, then they were reclassified and converted to raster layers enabling raster combination of all layers to each other. These thematic data included: alluvial thickness (Figure 7a), stiffness and strength of soil and sediments (Figure 7b), type of soil and particle size distribution of soil and sediments (Figure 8a and b), depth of groundwater (Figure 9a), type of rock (Figure 9b), topographic irregularities (Figure 10a), and slope (Figure 10b) layers.

Figure 7. Thematic Layers of Bam city: Alluvial thickness (m) (a), Stiffness and strength of soil and sediments (b).

۳۹۱ Figure 8. Thematic Layers of Bam city: Sediment type at depth of 1 meter (a) and at depth of 9
۳۹۲ meters (b).

۳۹۳ Figure 9. Thematic Layers of Bam city: Groundwater level (a), Type of rock (b).

۳۹۴ Figure 10. Thematic Layers of Bam city: Topographic irregularities (a) and Slope (b).

۳۹۵

۳۹۶ **2.3.4. Preparing control data**

۳۹۷ National Cartographic Center (2003) and Hisada et al.(2005) were collected data on the destruction
۳۹۸ level of buildings after math of the Bam earthquake (Figure 11 a and b). Lashkari Pour et al. (2006)
۳۹۹ and Motamed et al. (2007) were collected data on the dominant frequency of soil (Figure 12a and
۴۰۰ b) and amplification factor by Motamed et al. (2007) (Figure 13) using microtremor measurements
۴۰۱ in Bam city. These datasets were classified to 5 classes based on equal interval classification
۴۰۲ method including very low, low, moderate, high and very high classes. Then, they were applied to
۴۰۳ validate the model's output through a comparison analysis and calculating overall accuracy and
۴۰۴ kappa coefficient.

۴۰۵

۴۰۶ Figure 11. Control data: Actual building destruction level (Hisada et al., 2005) (a), percentage of
۴۰۷ damage to buildings caused by the Bam earthquake in 2003 (**National Cartographic Center of**
۴۰۸ **Iran (NCCI), 2003**) (b).

۴۰۹

۴۱۰ Figure 12. Control data: Dominant frequency by (LashkariPour et al., 2006) (a) and by Motamed
۴۱۱ et al. (2007) (b) using Microtremor field measurement.

۴۱۲

۴۱۳ Figure 13. Control data: Amplification factor by Motamed et al. (2007) using Microtremor field
۴۱۴ measurement.

۴۱۵

۴۱۶ **2.3. Spatial combination methods and overlay rules**

۴۱۷ The spatial Multi Criteria Decision Making (MCDM) approach is a decision-aid and a
۴۱۸ mathematical tool that combines and transforms spatially referenced data into a raster layer with

419 a priority score. (Roy, 1996;Malczewski, 2006). Several combination methods have been
420 developed, such as Boolean operations (Malczewski, 1999), weighted linear combination (WLC:
421 combining the normalized criteria based on overlay analysis) (Voogd, 1983;Drobne and Lisec,
422 2009;O'Sullivan and Unwin, 2010) (Eq. 5), ordered weighted averaging (OWA) (Yager,
423 1988;Rinner and Malczewski, 2002), and Analytical Hierarchy Process (AHP) based on the
424 additive weighting methods (Zhu and Dale, 2001). In this research, the AHP method (Saaty,
425 1980) was used to derive the weights associated with criteria and Fuzzy Logic method was
426 applied to compute sub-criteria's membership functions (MFs) in order to produce the local
427 seismic amplification. Then, the degree of membership of each sub-criteria (calculated by Fuzzy
428 Logic method) is assigned to the corresponding sub-criteria. Next, this is multiplied by the weight
429 of corresponding criteria (calculated by AHP method). Finally, they are summed up in a linear
430 manner using WLC method (Eq. 5) to develop the model (Larzesh model) for production of the
431 local seismic amplification in the study area.

$$A_i = \sum W_j * X_{ij} \quad (Eq. 5)$$

432 *Where: w_j = the calculated weight of criteria j , and X_{ij} = the degree of memebrship of the i th*
433 *sub-criteria with respect to the j th criteria, and A_i = the local seismic amplification index in i th*
434 *location.*

435

436 **2.4. Validation and comparison methods**

437 In order to validate the model, as categorical variables are the main driver of model development in
438 this research, therefore relevant measures such as Overall Accuracy and Kappa statistic will be
439 applied to measure the performance of the model.

440 **a) Overall accuracy (OA)**

441 Accuracy assessments determine the quality of the results derived from data analysis or a model,
442 in comparison with a reference or ground truth data (where ground truth data are assumed to be
443 100% correct) (Congalton and Green, 2009). The accuracy assessment can be obtained by
444 creating a contingency table of counts of observations, with calculated, estimated or predicted
445 data values as rows and with reference data values as columns. The values in the shaded cells
446 along the diagonal represent counts for correctly classified observations, where the reference data

447 matches the predicted value. This contingency table is often referred to as a confusion matrix,
448 misclassification matrix, or error matrix (Czaplewski, 1992; Congalton and Green, 2009) (Eq. 6).

$$OA = \frac{\sum_{k=1}^q n_{kk}}{n} \times 100 \quad (\text{Eq. 6})$$

449

450 Where: OA = Overall Accuracy, n_{kk} = Values in diagonal cell of the matrix (correctly classified
451 observations), and n = number of observations.

452 **b) Kappa analysis**

453 The kappa statistic (κ) (Sim and Wright, 2005; Congalton and Green, 2008) calculates degree of
454 agreement between classes of two independent observe measuring the same property. The degree
455 of Kappa would be 0 for a random classifies and 1 for classification. Degree of agreement of
456 Kappa interprets as follows: less than 0.4: poor agreement, 0.4 and 0.8: moderate agreement,
457 and greater than 0.80: strong agreement (Congalton and Green, 2008) (Eq. 7).

458

$$459 \quad k = \frac{P_o - P_e}{1 - P_e} \quad (\text{Eq. 7})$$

460 Where: P_o = the relative observed agreement among raters, P_e = the hypothetical probability of chance
461 agreement.

462

463 **Results and discussion**

464 In order to produce the local seismic amplification susceptibility the most important criteria were
465 identified and then were weighted using AHP pair-wise comparison method. The higher weight
466 belong to alluvial thickness (0.271), stiffness and strength of soil and sediments (0.207), type of
467 soil and particle size distribution of sediments (0.177), depth of groundwater (0.171), topographic
468 irregularities (0.054), type of rock (0.041), slope (0.040), and type of bedrock (0.040) were
469 considered. Then, based on Fuzzy Logic method sub-criteria of each criterion was fuzzified and
470 membership functions for them was defined. Next, these criteria were combined based on the
471 Weighted Linear Combination (WLC) (Drobne and Lisec, 2009) in GIS to develop the model for

472 producing the susceptibility map of local seismic amplification for the study area, as it is proposed
 473 in the following (Eq. 8):

474

$$475 \quad A_j = \sum(wS_s \cdot FS_{SS}) + (wT_A \cdot FS_{TA}) + (wS_A \cdot FS_{SA}) + (wD_{GW} \cdot FS_{D_{GW}}) + (wT_R \cdot FS_{TR})$$

$$476 \quad + (wT_{BR} \cdot FS_{TBR}) + (wT_S \cdot FS_{TS}) + (wS_L \cdot FS_{SL}) \quad (Eq. 8)$$

477 *Where: A_j = local seismic amplification susceptibility, weights of each criterion: wS_s = stiffness and*
 478 *strength of soil and sediments , wT_A = Alluvial thickness, wS_A = Type of soil and particle size distribution*
 479 *of sediments , wD_{GW} = depth of groundwater , wT_R = type of rock , wT_{BR} = type of bedrock, wT_S =*
 480 *topographic irregularities, wS_L = slope, and fuzzified sub-criteria of each criterion: FS_{SS} = stiffness and*
 481 *strength of soil and sediments, FS_{TA} = Alluvial thickness, FS_{SA} = Type of soil and particle size distribution*
 482 *of soil and sediments, $FS_{D_{GW}}$ = depth of groundwater, FS_{TR} = type of rock , FS_{TBR} = type of bedrock,*
 483 *FS_{TS} = topographic irregularities, and FS_{SL} = slope.*

484

485 Figure 14 displays the resulting microzonation map of ground shaking in Bam city. The areas
 486 with high to very high susceptibility to local seismic amplification are located in the north, east
 487 and northeast part of Bam city. This is due to the widespread unconsolidated sediments, low
 488 groundwater level in combination with high sediment thickness.

489 In order to validate the results, OA and Kappa methods were applied comparing the output of
 490 model with the measured predominant frequency (Askari et al., 2004;LashkariPour et al.,
 491 2006;Motamed et al., 2007) in the study area. The results demonstrated 73.6% and 82% (Table
 492 4a and b) for OA and 0.74 and 0.75 for Kappa (Table 5) indicating a good fit of the model's
 493 output with the measured data. Moreover, the overlay of the building destructions caused by the
 494 Bam earthquake in 2003 (Hisada et al., 2005;National Cartographic Center of Iran (NCCI), 2003)
 495 shows that high destruction levels happened in locations with high ground shaking which were
 496 located in central, north and northeast part of the city.

497

498 **Figure 14. Susceptibility map of local seismic amplification of Bam city**

499

500 **Table 4. Comparison between the model's output with the measured predominant frequency in Bam**
 501 **city by Motamed et al. (2007) (a)c and LashkariPour et al. (2006) (b).**

0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
1.0
1.1
1.2
1.3
1.4
1.5
1.6
1.7
1.8
1.9
2.0
2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9
3.0
3.1
3.2

Table 5. Kappa coefficient and OA

In this study, we have focused on the site effect and local geology properties of a site that have a massive influence on local seismic amplification susceptibility in the study area. To deal with related uncertainties in preparing seismic microzonation, the most important criteria were selected, weighted and then fuzzified. Criteria with high uncertainty degree such as distance of active fault to the site, depth and magnitude of the probable earthquake were not considered because there was no possibility to exactly find out where and how an earthquake will be triggered. Therefore, only the criteria with known location (x and y) and known characteristics were taken into consideration. Furthermore, to deal with uncertainties Fuzzy Logic is a suitable approach as we can define membership function of the effect of each criterion in the amplification of ground shaking by interviewing 10 experts and obtaining expert's knowledge. This can result in realistic output regarding the behavior of each criterion in ground shaking calculation.

The newly developed model uses AHP and Fuzzy Logic (Zadeh, 1965) to deal with complexities and uncertainties in data analyses in weighting the criteria and fuzzifying the sub-criteria of each criterion. Although, in studies for evaluating seismic microzonation in Bangalore (India) (Sitharam and Anbazhagan, 2008), Dehli (Mohanty et al., 2007), Haldia (India) (Mohanty et al., 2007), Erbaa (Turkey) (Akin et al., 2013) and Al-Madinah (Moustafa et al., 2016) only AHP method was applied to weight the criteria, and none of these studies considered weighting of sub criteria for each criterion even using other methods.

Few researchers have considered direct properties of influencing factors in assessing ground shaking amplification. Even, in evaluating seismic response developed models such as SiSeRHMap v1.0 (Grelle et al., 2016) and GIS Cubic Model (Grelle et al., 2014), the researchers have applied only lithodynamic, stratigraphic and topographic effects as influencing factors. Furthermore, [Aucelli et al. \(2018\)](#) suggested a method for producing susceptibility index to local seismic amplification in Isernia Province, Italy, and they have considered geological and geomorphological properties of studied areas. Although, they have not considered the use of multi-criteria decision-making methods (MCDM) in weighting and combining the influencing criteria which is the aim of current study. The current research considers direct properties of each criteria and tries to manage uncertainties in criteria and sub-criteria of each criterion via weighting and

033 fuzzification process using experts' knowledge and the use of direct properties of criteria. These
034 processes can be extended in more details, which are subject to more investigation in the future.

035

036 **Conclusions**

037 Larzesh model introduces a new method based on AHP and Fuzzy Logic rules that enables experts
038 to produce local seismic amplification susceptibility using direct properties of lithological,
039 sedimentological, geological, hydrological and topographical effects in a study area using experts'
040 knowledge in weighting and fuzzifying criteria and sub criteria that can be readily perceived and
041 consulted.

042 The application of the model was carried out in the urban area of the Bam city in Iran. The results
043 demonstrated high to very high ground shaking amplifications were located in central, east, and
044 northeast to north part of the city that was confirmed comparing with measured microtremor data
045 on predominate frequency in the study area. However, as the proposed model is a spatial
046 computational tool, the validation of output in producing local seismic amplification strictly
047 dependent on the quality and preparation of input data.

048 In conclusion, the model enable disaster managers, planners, and policy makers in producing local
049 seismic amplification susceptibility and making informed decision in urban planning and
050 designing appropriate plans for urban development, especially in areas with high seismic activities.

051

052 **Acknowledgements**

053 The authors would like to express their appreciation to Institute of Science and High Technology
054 and Environmental Sciences, Graduate University of Advanced Technology, Kerman, Iran for
055 financial support of this study under reference number of 7/C/95/2053.

056

057 **References**

058 Akin, M. K., Topal, T., and Kramer, S. L.: A newly developed seismic microzonation model of Erbaa
059 (Tokat, Turkey) located on seismically active eastern segment of the North Anatolian Fault Zone (NAFZ),
060 Natural Hazards, 65, 1411-1442, 10.1007/s11069-012-0420-1, 2013.

061 Askari, F., Azadi, A., M., D., and M.R. Ghayamghamian, E. H., H. Hamzehloo, M.K. Jafari, M. Kamalian,
062 M. Keshavarz, O. Ravanfar, A. Shafiee, A. Sohrabi-Bidar: Preliminary Seismic Microzonation of Bam,
063 Journal of Seismology and Earthquake Engineering, 5, 2004.

- 066 Assimaki, D., Steidl, J., and Liu, P.: Attenuation and Velocity Structure for Site Response Analyses via Downhole Seismogram Inversion, *Pure appl. geophys.*, 163, 81-118, 10.1007/s00024-005-0009-7, 2006.
- 067 Atkinson, G. M., and Boore, D. M.: Earthquake ground-motion prediction equations for eastern North America, *Bulletin of the Seismological Society of America*, 96, 2181-2205, 2006.
- 068 Atkinson, G. M., Ghofrani, H., and Assatourians, K.: Impact of induced seismicity on the evaluation of seismic hazard: Some preliminary considerations, *Seismological Research Letters*, 86, 1009-1021, 2015.
- 069
- 070 **Aucelli, P. P. C., Di Paola, G., Valente, E., Amato, V., Bracone, V., Cesarano, M., Di Capua, G., Scorpio, V., Capalbo, A., and Pappone, G.: First assessment of the local seismic amplification susceptibility of the Isernia Province (Molise Region, Southern Italy) by the integration of geological and geomorphological studies related to the first level seismic microzonation project, *Environmental earth sciences*, 77, 118, 2018.**
- 071
- 072
- 073
- 074 Beck, J. L., and Hall, J. F.: Factors contributing to the catastrophe in Mexico City during the earthquake of September 19, 1985, *Geophysical Research Letters*, 13, 593-596, 1986.
- 075
- 076 Biernacki, P., and Waldorf, D.: Snowball sampling: Problems and techniques of chain referral sampling, *Sociological methods & research*, 10, 141-163, 1981.
- 077
- 078 Bisch, P., Carvalho, E., Degee, H., Fajfar, P., Fardis, M., Franchin, P., Kreslin, M., Pecker, A., Pinto, P., and Plumier, A.: Eurocode 8: seismic design of buildings worked examples, Joint Research Centre European Union, Luxembourg, 2012.
- 079
- 080
- 081 Boore, D. M.: Simulation of ground motion using the stochastic method, in: *Seismic Motion, Lithospheric Structures, Earthquake and Volcanic Sources: The Keiiti Aki Volume*, Springer, 635-676, 2003.
- 082
- 083 Boostan, E., Tahernia, N., and Shafiee, A.: Fuzzy—probabilistic seismic hazard assessment, case study: Tehran region, Iran, *Natural Hazards*, 77, 525-541, 2015.
- 084
- 085 Bouckovalas, G. D., and Papadimitriou, A. G.: Numerical evaluation of slope topography effects on seismic ground motion, *Soil Dynamics and Earthquake Engineering*, 25, 547-558, 2005.
- 086
- 087 Campbell, K. W.: Prediction of strong ground motion using the hybrid empirical method and its use in the development of ground-motion (attenuation) relations in eastern North America, *Bulletin of the Seismological Society of America*, 93, 1012-1033, 2003.
- 088
- 089
- 090 Capilleri, P., Cavallaro, A., and Maugeri, M.: Static and dynamic soil characterization at Roio Piano (AQ), *Italian Geotechnical Journal*, 35, 2, 2014.
- 091
- 092 Probabilistic Risk Assessment (CAPRA): <https://www.ecapra.org/software>, access: 17 April 2017, 2017.
- 093
- 094 Castelli, F., Cavallaro, A., Grasso, S., and Lentini, V.: Seismic microzoning from synthetic ground motion earthquake scenarios parameters: the case study of the City of Catania (Italy), *Soil Dynamics and Earthquake Engineering*, 88, 307-327, 2016a.
- 095
- 096 Castelli, F., Cavallaro, A., Grasso, S., and Ferraro, A.: In situ and laboratory tests for site response analysis in the ancient city of Noto (Italy), *Proceedings of the 1st IMEKO TC4 International Workshop on Metrology for Geotechnics, Benevento, Italy*, 2016b, 17-18,
- 097
- 098

- 609 Cavallaro, A., Ferraro, A., Grasso, S., and Maugeri, M.: Site response analysis of the Monte Po Hill in the
 610 City of Catania, AIP Conference Proceedings, 2008, 240-251,
- 611 Cavallaro, A., Ferraro, A., Grasso, S., and Maugeri, M.: Topographic effects on the Monte Po hill in Catania
 612 (Italy), Soil Dynamics and Earthquake Engineering, 43, 97-113, 2012.
- 613 Cavallaro, A., Capillieri, P., and Grasso, S.: Site characterization by dynamic in situ and laboratory tests for
 614 liquefaction potential evaluation during Emilia Romagna earthquake, Geosciences, 8, 242, 2018.
- 615 CEN European Committee for Standardisation: Eurocode 8. Design Provisions for Earthquake Resistance
 616 of Structures—Part 5: Foundations, Retaining Structures and Geotechnical Aspects. ENV 1998-5, Brussels,
 617 1994.
- 618 Cheng, E. W. L., and Li, H.: Construction partnering process and associated critical success factors:
 619 quantitative investigation, Journal of Management in Engineering, October, 194–202, 2002.
- 620 Congalton, R. G., and Green, K.: Assessing the accuracy of remotely sensed data: principles and practices,
 621 CRC press, 2008.
- 622 Congalton, R. G., and Green, K.: Assessing the Accuracy of Remotely Sensed Data: Principles and
 623 Practices, CRC Press, Boca Raton, FL, USA, 2009.
- 624 Cornell, C. A.: Engineering seismic risk analysis, Bulletin of the seismological society of America, 58,
 625 1583-1606, 1968.
- 626 Czaplewski, R. L.: Misclassification bias in areal estimates, Photogrammetric engineering and Remote
 627 Sensing, 58, 189–192, 1992.
- 628 Demicco, R. V., and Klir, G. J.: Fuzzy logic in geology, Academic Press, 347 pp., 2003.
- 629 Ding, Z., Chen, Y., and Panza, G.: Estimation of site effects in Beijing City, Pure appl. geophys., 161, 1107-
 630 1123, 2004.
- 631 Dobry, R., Borcherdt, R. D., Crouse, C. B., Idriss, I. M., Joyner, W. B., Martin, G. R., Power, M. S., Rinne,
 632 E. E., and Seed, R. B.: New site coefficients and site classification system used in recent building seismic
 633 code provisions, Earthquake Spectra, 16, 41-67, 2000.
- 634 Drobne, S., and Lisec, A.: Multi-attribute Decision Analysis in GIS: Weighted Linear Combination and
 635 Ordered Weighted Averaging, Informatica (Slovenia), 33, 459-474, 2009.
- 636 Fähr, D., Rüttener, E., Noack, T., and Kruspan, P.: Microzonation of the city of Basel, Journal of
 637 Seismology, 1, 87-102, [10.1023/a:1009774423900](https://doi.org/10.1023/a:1009774423900), 1997.
- 638 Federal Emergency Management Agency (FEMA): Multi-hazard Loss Estimation Methodology,
 639 Earthquake Model, HAZUS®MH MR5, User Manual, Washington, D.C., 2014.
- 640 Figueira, J., Mousseau, V., and Roy, B.: ELECTRE methods, in: Multiple criteria decision analysis: State
 641 of the art surveys, Springer, 133-153, 2005.
- 642 Fraume, M., Cristina, M., Carreño Tibaduiza, M. L., Cardona Arboleda, O. D., Ordaz Schroeder, M. G.,
 643 and Barbat Barbat, H. A.: Probabilistic earthquake risk assessment of Barcelona using CAPRA, Second
 644 European Conference on Earthquake Engineering and Seismology, 2014, 1-3,

- 730 Geli, L., Bard, P.-Y., and Jullien, B.: The effect of topography on earthquake ground motion: a review and
736 new results, *Bulletin of the Seismological Society of America*, 78, 42-63, 1988.
- 737 Geological Survey of Iran: Geological Map of Iran, 1:100,000 Series, Sheet 7648, Bam, Iran, 1993.
- 738 Global Earthquake Model (GEM): The OpenQuake-engine User Manual. Global Earthquake Model (GEM)
739 Technical Report 2017-02., 193 2017.
- 740 Grelle, G., Bonito, L., Revellino, P., Guerriero, L., and Guadagno, F. M.: A hybrid model for mapping
741 simplified seismic response via a GIS-metamodel approach, *Natural Hazards and Earth System Sciences*,
742 14, 1703, 2014.
- 743 Grelle, G., Bonito, L., Lampasi, A., Revellino, P., Guerriero, L., Sappa, G., and Guadagno, F. M.:
744 SiSeRHMap v1. 0: a simulator for mapped seismic response using a hybrid model, *Geoscientific Model
745 Development*, 9, 1567-1596, 2016.
- 746 Hassanzadeh, R., Nedović- Budić, Z., Alavi Razavi, A., Norouzzadeh, M., and Hodhodkian, H.: Interactive
747 approach for GIS-based earthquake scenario development and resource estimation (Karmania hazard
748 model), *The international journal of Computers & Geosciences*, 51, 324-338, 10.1016/j.cageo.2012.08.016,
749 2013.
- 750 Hassanzadeh, R., and Nedovic-Budic, Z.: Where to go first: prioritization of damaged areas for allocation
751 of Urban Search and Rescue (USAR) operations (PI-USAR model), *Geomatics, Natural Hazards and Risk*,
752 7, 1337-1366, 10.1080/19475705.2015.1058861, 2016.
- 753 Hinlopen, E., Nijkamp, P., and Rietveld, P.: Qualitative discrete multiple criteria choice models in regional
754 planning, *Regional Science and Urban Economics*, 13, 77-102, 1983.
- 755 Hisada, Y., Shibayama, A., and Ghayamghamian, M. R.: Building damage and seismic intensity in Bam
756 city from the 2003 Iran, Bam, earthquake, *Bull. Earthquake Res. Inst., Univ. Tokyo*, 79 81–94, 2005.
- 757 Hoek, E., and Brown, E. T.: Practical estimates of rock mass strength, *International Journal of Rock
758 Mechanics and Mining Sciences*, 34, 1165-1186, 1997.
- 759 Iguchi, Y., and Tainosho, Y.: Characteristics of distribution of groundwater level in the seismic damaged
760 zone in eastern part of Kobe city due to the 1995 Hyogo-Ken Nanbu Earthquake, *Bulletin of the Faculty of
761 Human Development* 5, 403-415, 1998.
- 762 Jafari, M. K., Ghayamghamian, M. R., Davoodi, M., Kamalian, M., and Sohrabi-Bidar, A.: Site Effects of
763 the 2003 Bam, Iran, Earthquake, *Earthquake Spectra*, 21, 125-136, 10.1193/1.2098266, 2005.
- 764 Jamieson, S.: Likert Scales: How to (Ab)use Them, *Medical Education*, 38, 1217-1218, 2004.
- 765 Kanlı, A. I., Tildy, P., Prónay, Z., Pinar, A., and Hermann, L.: VS30 mapping and soil classification for
766 seismic site effect evaluation in Dinar region, SW Turkey, *Geophysical Journal International*, 165, 223-
767 235, 10.1111/j.1365-246X.2006.02882.x, 2006.
- 768 Keeney, R. L., and Raiffa, H.: *Decisions with multiple objectives: preferences and value trade-offs*,
769 Cambridge university press, 1993.

- ٦٧٠ Klir, G. J.: Chapter 2 - Fuzzy Logic: A Specialized Tutorial, in: Fuzzy Logic in Geology, Academic Press,
٦٧١ Burlington, 11-61, 2004.
- ٦٧٢ Lam, K., and Zhao, X.: An application of quality function deployment to improve the quality of teaching,
٦٧٣ International Journal of Quality Reliability Management, 15, 389–413, 1998.
- ٦٧٤ LashkariPour, G. R., Sadegh, H., and Sevizi, Z.: Comparison of predominant frequency of Bam city using
٦٧٥ seismic facies and ratio of H/V of foreshocks earthquakes., 10th Symposium of Geological Society of Iran,
٦٧٦ 2006.
- ٦٧٧ Lee, S.-J., Komatitsch, D., Huang, B.-S., and Tromp, J.: Effects of topography on seismic-wave
٦٧٨ propagation: An example from northern Taiwan, Bulletin of the Seismological Society of America, 99,
٦٧٩ 314-325, 2009.
- ٦٨٠ Likert, R.: A Technique for the Measurement of Attitudes, Archives of Psychology, 140, 1932.
- ٦٨١ Malczewski, J.: GIS and Multicriteria Decision Analysis, John Wiley and Sons, New York, 1999.
- ٦٨٢ Malczewski, J.: A GIS-based multicriteria decision analysis: A survey of the literature, International Journal
٦٨٣ of Geographical Information Science, 20, 703-726, 2006.
- ٦٨٤ Mancini, I. M., Masi, S., Caniani, D., and Lioi, D. S.: Fuzzy logic and neuro-fuzzy networks for
٦٨٥ environmental hazard assessment, in: Fuzzy Logic-Emerging Technologies and Applications, InTech,
٦٨٦ 2012.
- ٦٨٧ Marie Nolte, E.: Earthquake risk map development using GIS and optical satellite imagery: case study for
٦٨٨ rural areas on Java, Indonesia, Center for Disaster Management and Risk Reduction Technology
٦٨٩ Projektbericht Hertz, Karlsruhe 112, 2010.
- ٦٩٠ Marinos, P., Marinos, V., and Hoek, E.: Geological Strength Index (GSI). A characterization tool for
٦٩١ assessing engineering properties for rock masses, Underground works under special conditions. Taylor and
٦٩٢ Francis, Lisbon, 13-21, 2007.
- ٦٩٣ Marulanda, M., Carreño, M., Cardona, O., and Barbat, A.: Probabilistic assessment of seismic risk of
٦٩٤ Barcelona, Spain, using the CAPRA platform, Buletinul Institutului Politehnic din Iasi. Sectia Constructii,
٦٩٥ Arhitectura, 58, 9, 2012.
- ٦٩٦ MERM: Microzonation Manual, World Institute for Disaster Risk Management, 2003.
- ٦٩٧ Michel, C., Fäh, D., Edwards, B., and Cauzzi, C.: Site amplification at the city scale in Basel (Switzerland)
٦٩٨ from geophysical site characterization and spectral modelling of recorded earthquakes, Physics and
٦٩٩ Chemistry of the Earth, Parts A/B/C, 98, 27-40, 2017.
- ٧٠٠ Mohanty, W. K., Walling, M. Y., Nath, S. K., and Pal, I.: First Order Seismic Microzonation of Delhi, India
٧٠١ Using Geographic Information System (GIS), Natural Hazards, 40, 245-260, 10.1007/s11069-006-0011-0,
٧٠٢ 2007.
- ٧٠٣ Mohanty, W. K., and Walling, M. Y.: First Order Seismic Microzonation of Haldia, Bengal Basin (India)
٧٠٤ Using a GIS Platform, Pure appl. geophys., 165, 1325-1350, 10.1007/s00024-008-0360-6, 2008.

- ٧٠٥ Molina, S., Lang, D. H., and Lindholm, C. D.: SELENA – An open-source tool for seismic risk and loss
 ٧٠٦ assessment using a logic tree computation procedure, *Computers & Geosciences*, 36, 257-269,
 ٧٠٧ <http://dx.doi.org/10.1016/j.cageo.2009.07.006>, 2010.
- ٧٠٨ Monaco, P., Totani, G., Barla, G., Cavallaro, A., Costanzo, A., d’Onofrio, A., Evangelista, L., Foti, S.,
 ٧٠٩ Grasso, S., and Lanzo, G.: Geotechnical aspects of the L’Aquila earthquake, in: *Special topics in earthquake*
 ٧١٠ *geotechnical engineering*, Springer, 1-66, 2012.
- ٧١١ Moro, M., Saroli, M., Salvi, S., Stramondo, S., and Doumaz, F.: The relationship between seismic
 ٧١٢ deformation and deep-seated gravitational movements during the 1997 Umbria–Marche (Central Italy)
 ٧١٣ earthquakes, *Geomorphology*, 89, 297-307, 2007.
- ٧١٤ Motamed, R., Ghalandarzadeh, A., Tawhata, I., and Tabatabaei, S. H.: Seismic Microzonation and Damage
 ٧١٥ Assessment of Bam City, Southeastern Iran, *Journal of Earthquake Engineering*, 11, 110-132,
 ٧١٦ 10.1080/13632460601123164, 2007.
- ٧١٧ Moustafa, S. S. R., SN Al-Arifi, N., Jafri, M. K., Naeem, M., Alawadi, E. A., and A. Metwaly, M.: First
 ٧١٨ level seismic microzonation map of Al-Madinah province, western Saudi Arabia using the geographic
 ٧١٩ information system approach, *Environmental Earth Sciences*, 75, 251, 10.1007/s12665-015-5073-4, 2016.
- ٧٢٠ Mundepi, A., Galiana-Merino, J., and Lindholm, C.: Soil characteristics and site effect assessment in the
 ٧٢١ city of Delhi (India) using H/V and f–k methods, *Soil Dynamics and Earthquake Engineering*, 30, 591-599,
 ٧٢٢ 2010.
- ٧٢٣ Nath, S., and Thingbaijam, K.: Seismic hazard assessment-a holistic microzonation approach, *Natural*
 ٧٢٤ *Hazards and Earth System Sciences*, 9, 1445, 2009.
- ٧٢٥ **National Cartographic Center of Iran (NCCI): Report on the Bam earthquake, Tehran, 98, 2003.**
- ٧٢٦ Noack, T., and Fah, D.: Earthquake Microzonation: site effects and local geology; A case study for the
 ٧٢٧ Kanton of Basel-Stadt, 2001.
- ٧٢٨ Novák, V., Perfilieva, I., and Mockor, J.: *Mathematical principles of fuzzy logic*, Springer Science &
 ٧٢٩ *Business Media*, 2012.
- ٧٣٠ Nwe, Z. Z., and Tun, K. T.: Seismic Hazard Analysis using AHP-GIS, *Int'l Journal of Research in Chemical,*
 ٧٣١ *Metallurgical and Civil Engg.*, 3, 1442-1450, 2016.
- ٧٣٢ O’Sullivan, D., and Unwin, D. J.: *Putting Maps Together—Map Overlay*, in: *Geographic Information*
 ٧٣٣ *Analysis*, John Wiley & Sons, Inc., 315-340, 2010.
- ٧٣٤ Panza, G. F., La Mura, C., Peresan, A., Romanelli, F., and Vaccari, F.: Chapter three-seismic hazard
 ٧٣٥ scenarios as preventive tools for a disaster resilient society, *Advances in geophysics*, 53, 93-165, 2012.
- ٧٣٦ Paolucci, R.: Amplification of earthquake ground motion by steep topographic irregularities, *Earthquake*
 ٧٣٧ *Engineering & Structural Dynamics*, 31, 1831-1853, 10.1002/eqe.192, 2002.
- ٧٣٨ Petersen, M. D., Mueller, C. S., Moschetti, M. P., Hoover, S. M., Llenos, A. L., Ellsworth, W. L., Michael,
 ٧٣٩ A. J., Rubinstein, J. L., McGarr, A. F., and Rukstales, K. S.: Seismic-Hazard Forecast for 2016 Including
 ٧٤٠ Induced and Natural Earthquakes in the Central and Eastern United States, *Seismological Research Letters*,
 ٧٤١ 87, 1327-1341, 2016.

- ٧٤٢ Phoon, K., Nadim, F., Uzielli, M., and Lacasse, S.: Soil variability analysis for geotechnical practice, in:
 ٧٤٣ Characterisation and Engineering Properties of Natural Soils, Taylor & Francis, 2006.
- ٧٤٤ Ramazi, H., and Jigheh, H. S.: The Bam (Iran) Earthquake of December 26, 2003: From an engineering
 ٧٤٥ and seismological point of view, *Journal of Asian Earth Sciences*, 27, 576-584, 2006.
- ٧٤٦ Rehman, F., El-Hady, S. M., Atef, A., and Harbi, H. M.: PROBABILISTIC SEISMIC HAZARD
 ٧٤٧ ASSESSMENT METHODOLOGY AND SITE RESPONSE ANALYSIS APPLICATION TO SEISMIC
 ٧٤٨ MICROZONATION, *Science International*, 28, 2016.
- ٧٤٩ Rezaei, K., Guest, B., Friedrich, A., Fayazi, F., Nakhaei, M., Beitollahi, A., and Fatemi Aghda, S.: Feed
 ٧٥٠ forward neural network and interpolation function models to predict the soil and subsurface sediments
 ٧٥١ distribution in Bam, Iran, *Acta Geophys.*, 57, 271-293, 10.2478/s11600-008-0073-3, 2009.
- ٧٥٢ Rinner, C., and Malczewski, J.: Web-enabled spatial decision analysis using ordered weighted averaging,
 ٧٥٣ *J Geogr Syst*, 4, 385–403, 2002.
- ٧٥٤ Roy, B.: Multicriteria methodology for decision aiding, Kluwer Academic Publishers, Dordrecht, 1996.
- ٧٥٥ Saaty, T. L.: *The Analytic Hierarchy Process: planning, priority setting, resource allocation*, McGraw-Hill
 ٧٥٦ International, US, 1980.
- ٧٥٧ Saaty, T. L.: An Exposition of the AHP in Reply to the Paper “Remarks on the Analytic Hierarchy Process”,
 ٧٥٨ *Management Science*, 36, 259-268, 10.1287/mnsc.36.3.259, 1990.
- ٧٥٩ Sabetta, F., and Bommer, J.: Modification of the spectral shapes and subsoil conditions in Eurocode 8, 12th
 ٧٦٠ European Conference on Earthquake Engineering, London, UK, 2002.
- ٧٦١ Sen, Z.: Rapid visual earthquake hazard evaluation of existing buildings by fuzzy logic modeling, *Expert
 ٧٦٢ Systems with Applications*, 37, 5653-5660, 2010.
- ٧٦٣ Sim, J., and Wright, C. C.: The kappa statistic in reliability studies: use, interpretation, and sample size
 ٧٦٤ requirements, *Physical therapy*, 85, 257-268, 2005.
- ٧٦٥ Sitharam, T., and Anbazhagan, P.: Seismic microzonation: principles, practices and experiments, *EJGE
 ٧٦٦ Special Volume Bouquet*, 8, 2008.
- ٧٦٧ Sitharam, T. G.: *Technical Documat on Geotechnical and Geophysical Investigation for Seismic
 ٧٦٨ Microzonation Studies of Urban Centers in India*, National Disaster Management Authority (NDMA),
 ٧٦٩ Bhawan, Safdarjung Enclave, New Delhi, 123, 2010.
- ٧٧٠ SM Working Group: *Guidelines for Seismic Microzonation*, Civil Protection Department and Conference
 ٧٧١ of Regions and Autonomous Provinces of Italy, 2015,
- ٧٧٢ Stewart, J.: *Key Geotechnical Aspects of the 1989 Loma Prieta Earthquake*, National Information Service
 ٧٧٣ for Earthquake Engineering, University of California, Berkeley, California, Berkeley, 1997.
- ٧٧٤ Talebian, M., Fielding, E. J., Funning, G. J., Ghorashi, M., Jackson, J., Nazari, H., Parsons, B., Priestley,
 ٧٧٥ K., Rosen, P. A., Walker, R., and Wright, T. J.: The 2003 Bam (Iran) earthquake: Rupture of a blind strike-
 ٧٧٦ slip fault, *Geophysical Research Letters*, 31, n/a-n/a, 10.1029/2004gl020058, 2004.

- ٧٧٧ Tang, A. K.: Izmit (Kocaeli), Turkey, Earthquake of August 17, 1999 Including Duzce Earthquake of
 ٧٧٨ November 12, 1999: Lifeline Performance, ASCE Publications, 2000.
- ٧٧٩ Teramo, A., Termini, D., Marullo, A., and Marino, A.: Fuzzy interpolators for a quick seismic
 ٧٨٠ microzonation, CIMS. 2005 IEEE International Conference on Computational Intelligence for
 ٧٨١ Measurement Systems and Applications, 2005., 2005, 107-108,
- ٧٨٢ Tinsley, J. C., Youd, T. L., D.M., P., and Chen, A. T. F.: Evaluating liquefaction potential. In: Evaluating
 ٧٨٣ Earthquake Hazards in the Los Angeles Region - An Earth-Science Perspective, US Geological Survey,
 ٧٨٤ 263-315, 1985.
- ٧٨٥ Trifunac, M. D.: Site conditions and earthquake ground motion – A review, Soil Dynamics and Earthquake
 ٧٨٦ Engineering, 90, 88-100, <https://doi.org/10.1016/j.soildyn.2016.08.003>, 2016.
- ٧٨٧ Voogd, H.: Multicriteria Evaluation for Urban and Regional Planning, Pion, Ltd, London, 1983.
- ٧٨٨ Wald, D. J.: Slip history of the 1995 Kobe, Japan, earthquake determined from strong motion, teleseismic,
 ٧٨٩ and geodetic data, Journal of Physics of the Earth, 44, 489-503, 1996.
- ٧٩٠ Wang, Z., Carpenter, N. S., and Zhang, L.: Assessing Potential Seismic Hazards from Induced Earthquakes
 ٧٩١ in the Central and Eastern United States, AAPG Eastern Section Meeting, 2016,
- ٧٩٢ Wang, Z., Carpenter, N. S., Zhang, L., and Woolery, E. W.: Assessing Potential Ground-Motion Hazards
 ٧٩٣ from Induced Earthquakes, Natural Hazards Review, 18, 04017018, doi:10.1061/(ASCE)NH.1527-
 ٧٩٤ 6996.0000264, 2017.
- ٧٩٥ Yager, R. R.: On ordered weighted averaging aggregation operators in multi-criteria decision making, IEEE
 ٧٩٦ Transactions on Systems, Man and Cybernetics, B 18, 183-190, 1988.
- ٧٩٧ Zadeh, L. A.: Fuzzy sets, Information and control, 8, 338-353, 1965.
- ٧٩٨ Zadeh, L. A.: Fuzzy logic and approximate reasoning, Synthese, 30, 407-428, 1975.
- ٧٩٩ Zhu, X., and Dale, A. P.: JavaAHP: a Web-based decision analysis tool for natural resource and
 ٨٠٠ environmental management, Environmental Modelling and Software, 16, 251–262, 2001.
- ٨٠١
- ٨٠٢
- ٨٠٣
- ٨٠٤
- ٨٠٥
- ٨٠٦
- ٨٠٧

٨٠٨

٨٠٩

٨١٠

٨١١

Tables

٨١٢

Table 1.Relevant criteria that influence on seismic microzonation

1	Alluvial thickness	9	Thickness of bedrock
2	Stiffness and strength of alluvial deposits	10	Morphology of bedrock
3	Type of soil and particle size distribution of alluvial deposits	11	Topographic irregularities of bedrock
4	Depth of groundwater	12	Age of alluvial deposits
5	Topographic irregularities	13	Age of bedrock
6	Type of rock	14	Age of rock
7	Slope		
8	Type of bedrock		

٨١٣

٨١٤

٨١٥

Table 2.The average importance criteria based on 5-point Likert Scale

	Criteria for	Average
1	Alluvial thickness	8.5
2	Stiffness and strength of alluvial deposits	8
3	Type of soil and particle size distribution of alluvial deposits	7.5
4	Depth of groundwater	7.25
5	Type of rock	7
6	Topographic irregularities	5.25
7	Slope	5
8	Type of bedrock	5
9	Thickness of bedrock	4.5
10	Morphology of bedrock	4.5
11	Topographic irregularities of bedrock	4.5
12	Age of alluvial deposits	3.75
13	Age of bedrock	3.25

14	Age of rock	2.75
----	-------------	------

۸۱۶
 ۸۱۷
 ۸۱۸
 ۸۱۹
 ۸۲۰
 ۸۲۱

Table 3. The results of pair-wise comparisons of the selected criteria with each other based on the AHP matrix

Criteria	1	2	3	4	5	6	7	8	Weights
1- Alluvial thickness	1	1	2	2	5	5	7	4	0.271
2- Stiffness and strength of alluvial deposits		1	1	1	5	4	5	5	0.207
3-Type of soil, and particle size distribution of alluvial deposits			1	1	5	5	5	7	0.177
4-Depth of groundwater				1	5	7	3	5	0.171
5-Type of rock					1	2	1/2	1/2	0.041
6-Topographic irregularities						1	1/2	3	0.054
7-Slope							1	4	0.040
8-Type of bedrock								1	0.040
Lambda = 8.60 CI = 0.05									

۸۲۲
 ۸۲۳
 ۸۲۴
 ۸۲۵
 ۸۲۶
 ۸۲۷
 ۸۲۸
 ۸۲۹
 ۸۳۰
 ۸۳۱
 ۸۳۲
 ۸۳۳
 ۸۳۴
 ۸۳۵
 ۸۳۶
 ۸۳۷
 ۸۳۸
 ۸۳۹
 ۸۴۰

۸۴۱
 ۸۴۲
 ۸۴۳
 ۸۴۴
 ۸۴۵
 ۸۴۶
 ۸۴۷
 ۸۴۸
 ۸۴۹

Table 4. Comparison between the model's output with the measured predominant frequency in Bam city by Motamed et al. (2007) (a) and LashkariPour et al. (2006) (b).

a)

Predicted	Predominant Frequency (Measured)					
	1	2	3	4	5	Total
1	1	1			1	3
2		3		3		6
3	1		6	1		8
4		1		9		10
5			2		9	11
Total	2	5	8	13	10	38
Av_Ac = 73.6 %						

۸۵۰
 ۸۵۱

b)

Predicted	Predominant Frequency (Measured)					
	1	2	3	4	5	Total
1	1					1
2		1				1
3			3			3
4				1		1
5	1			1	2	4
Total	2	1	3	2	2	10
Av_Ac = 80 %						

۸۵۲
 ۸۵۳
 ۸۵۴

Table 5. Kappa coefficient and OA

Comparison of the model's output and measured data	Predominant frequency (Motamed et al., 2007)	Predominant frequency (LashkariPour et al., 2006)
Kappa coefficient	0.74 (0.000)	0.75 (0.000)
OA	73.6%	80%

۸۵۵
 ۸۵۶
 ۸۵۷

 ۸۵۸

 ۸۵۹


۸۶۰

۸۶۱

۸۶۲

۸۶۳ **Figures**

۸۶۴



۸۶۵

۸۶۶

Figure 1. The case study area of Bam City, Iran

۸۶۷
 ۸۶۸
 ۸۶۹
 ۸۷۰




Figure 2. The methodological approach of the model

871
 872
 873
 874
 875
 876
 877
 878
 879
 880
 881
 882
 883
 884

$$A = \begin{bmatrix} a_{11} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{n1} & a_{n2} & \dots & a_{nn} \end{bmatrix}$$

Where: $a_{ij} = 1$, if $i = j$, and $a_{ij} = \frac{1}{a_{ji}}$, if $i = \overline{1, n}$ and $j = \overline{1, n}$.

Figure 3.AHP matrix (A)

885
 886
 887
 888
 889
 890
 891
 892
 893
 894
 895
 896
 897
 898
 899
 900
 901
 902





Figure 4. Fuzzy membership functions (After Mancini, 2012)

۹۰۳




a)




b)

۹۰۴



c)



d)

Figure 5. Membership functions (MFs) based on fuzzy logic system: Alluvial thickness (a), Stiffness and strength of soil and sediments (b), Type of soil and particle size distribution of sediments (c), Depth of groundwater (d).

۹۰۵

۹۰۶

۹۰۷

۹۰۸

۹۰۹

۹۱۰

۹۱۱

۹۱۲


۹۱۳

۹۱۴


۹۱۵

۹۱۶

917



918



919


920

921

Figure 6. Membership functions (MFs) based on fuzzy logic system: Type of rock and bedrock (a), Slope (degree) (b), Topographic irregularities (c).

۹۲۲

a)



۹۲۳

۹۲۴

۹۲۵

۹۲۶

b)





Figure 7. Thematic Layers of Bam city: Alluvial thickness (m) (a), Stiffness and strength of soil and sediments (b).

۹۲۷

a)



۹۲۸

۹۲۹

۹۳۰

۹۳۱

b)





Figure 8. Thematic Layers of Bam city: Sediment type at depth of 1 meter (a) and at depth of 9 meters (b).

۹۳۲

a)




۹۳۳

۹۳۴

۹۳۵


b)



- Main Streets
- Old Fault line
- New Fault line
- ⋯⋯⋯ Extent of the city
- Lithology**
- Alluvium in stream channels.
- Ash flow tuffs.
- Ash-flow tuffs, well bedded.
- Basaltic lavas.
- Dacite; and subordinate rhyolite and andesite lavas.
- Limestone, massive and thick-layered.
- Older gravel fans.
- Silt of argil.
- Siltstone, sandstone.
- Younger gravel fans.

Figure 9. Thematic Layers of Bam city: Groundwater level (a), Geological map (type of rocks) (b).


۹۳۶



a)

۹۳۷

۹۳۸




b)

۹۳۹

۹۴۰


۹۴۱

Figure 10. Thematic Layers of Bam city: Topographic irregularities (a) and slope (b).



۹۴۲

a)



۹۴۳

b)

۹۴۴


Figure 11. Control data: Actual building destruction level (Hisada et al., 2005) (a), percentage of damage to buildings caused by the Bam earthquake in 2003 (National Cartographic Center of Iran (NCCI), 2003) (b).

۹۴۵


۹۴۶

۹۴۷

۹۴۸



a)



b)

Figure 12. Control data: Dominant frequency by Lashkaripour (a) and by Motamed et al (Motamed et al., 2007) (b) using Microtremor field measurement.

۹۴۹


۹۵۰

۹۵۱

۹۵۲

۹۵۳


۹۵۴



۹۰۰
 ۹۰۶
 ۹۰۷
 ۹۰۸

e)

Figure 13. Control data: Amplification factor by Motamed et al. (2007) using Microtremor field measurement.



۹۰۹
 ۹۶۰

Figure 14. The susceptibility of local seismic amplification map in Bam city