

## Summary of changes

Dear Editor,

The manuscript has been modified following your suggestions and comments, as well as the ones of the two reviewers.

Please, find below the responses to each comment.

In particular, as requested in your last report, we made the following changes:

- we added the suggested reference in the literature review (Cohen et al.);
- we further elaborated on the differences between our approach and existing ones, especially in the conclusion section;
- we provided information about sensitivity of the assumptions made in our procedure in the discussion section.

Best regards,

Fabio Cian

## Referee 1

The authors proposed a method to estimate the flood depth using SAR images and DEM data. The results were compared with the aerial photos, field-based measurement and the results of hydrodynamic modeling. The manuscript was well written. However, the verification is a little weak.

Line 58-59 There are many researches about mapping flood in urban areas, e. g. Nico et al., 2000, Chini et al., 2012. Please add more the state-of-the-art in this part.

We would add the following references to flood mapping works: Horritt 2001; Matgen et al., 2007; Brisco et al., 2011; Henry et al., 2006; Cossu et al., 2009; Martinis et al., 2015; Chini et al., 2012; Dasgupta et al., 2018; Giordan et al., 2018; Nico et al., 2000; Pierdicca et al., 2018

Page 3 Many algorithms of detecting flood depth have been mentioned in the introduction. However, the advantage of the proposed method comparing to the previous algorithms was not clarified

Intense

We would add in the second to last paragraph of the introduction section the following sentence explaining the advantages of the proposed method: *In contrast to many existing methods proposed in the literature, the presented method requires only two inputs (i.e., the flood extent map and a DEM), it is based on a simple yet precise algorithm, it does not require intense manual interaction and strong computing capacity.*

Section 2.1 In the previous study (Cian et al., 2018), two indices (NDFI and NDVFI) were proposed. Why the NDFI was adopted in this study.

We decided to use only the NDFI index, which allows to extract open water bodies, and not the NDVFI, which allows to detect flooded areas in short vegetation, because the latter is still not validated. As described in the cited paper, using the NDFVI we were able to extract flood in short vegetation, however we could not find any reliable source of information to properly validate the result. We believe in its correctness, but we preferred to leave the NDFVI out of this study as long as its quality is not quantitatively assessed.

Section 2.2 The estimation of water surface elevation was carried out in polygon based. What is the minimum size of the valid polygon? Is it time-consuming when the polygon number is large?

At the end of section 2.1 we specify three steps of post-processing employed in the flood mapping methods. Among these, the second says '*exclusion of clusters smaller than 10 pixels*', which basically determines the minimum size of the polygons. Accordingly, being Sentinel-1 pixel size 10x10 m, this equals to exclude polygons with size smaller than  $10 \times 10 \text{ m}^2 = 100 \text{ m}^2$ .

Of course, the higher the number of polygons, the higher the time needed for the statistical analysis. However, even when we applied the method to areas with more than 100.000 polygons, the task was performed in few hours (at most 3) using a standard desktop computer. If requested, we could add this information in the conclusion section.

Line 256-260 The flooded dates of the three study areas were confused by the description. Please indicate the period of flood in each area.

We thank the Reviewer for this comment; indeed, we realized that the description could in fact lead to confusion. To make it more clear, we would rephrase the beginning of Section 3.1 as: "*Heavy rain concurrent with other adverse effects from October 31 to November 2, 2010, in the Veneto Region (North-East Italy), led to the flooding of 140 km<sup>2</sup> of land with major damages on properties and infrastructures.*" The heavy rain started on October 31 and continued to November 2. This led to a flooding on November 1 in Vicenza and later to the other areas as explained in the description. Therefore, the start of the flooding occurred at different dates depending on the specific area. Eventually, we can also specify the starting date of the flood event for each of the investigated areas in Figure 3.

Additionally, to further clarify the its dynamic we would also improve the flood description as it follows:

*"The first levee rupture in the study region occurred south of Vicenza in the afternoon of November 1. Afterwards, the flood propagated South-East to Veggiano, where the banks of the Bacchiglione River were broken in the night between November 1 and 2. During November 2 the Bacchiglione banks broke also in the area of Bovolenta, while the area of Saleto started to be flooded due to the rupture of the Frassine River banks on the same day (see **Error! Reference source not found.**). Based on the analysis of SAR imagery (Cian et al., 2018), in the area of Vicenza and Veggiano the peak of the flood event was estimated between November 2 (north-west of frame A in Figure 3) and November 3 (placeholder "A1" in Figure 3). Instead, in the Bovolenta (frame B in Figure 3) and Saleto (frame C in Figure 3) areas it occurred on November 4.*

*Figure 2 shows the measurements of hydrometers along the Bacchiglione River (hydrometers 1 to 5) and along the Frassine River (hydrometers 6 and 7) (ARPAV, 2010). We can notice how the flood wave moved from Vicenza (hydrometer 1) to Bovolenta (hydrometer 5), in accordance with the analysis of SAR data, which estimated the maximum extent after the highest measurement of the hydrometers. Concerning the Frassine River (hydrometers 6 and 7), we observe a similar behavior."*




Figure 1 Overview of the area affected by the 2010 flood event occurred in the Veneto region (Italy). The main areas of interests are highlighted by the three frames: A) Vicenza, B) Bovolenta and C) Saletto. Placeholder A1 refers to the Veggiano area covered by the hydrodynamic modeling used for comparison purposes. The numbers in orange circles indicate the location of the hydrometers, whose measurements are reported in Figure 4. For each frame the flood start date is reported along with the direction of the flood wave (blue arrows).




Figure 2 Measurements of hydrometers during the period of the investigated flood event. The flow of the Bacchiglione River (hydrometers 1 to 5) goes towards South-East, i.e. from hydrometer 1 to 5. The flow of the Frassine River (hydrometers 6 and 7) goes towards East, i.e. from hydrometer 6 to 7. In both cases, the measurements show the dynamic of the flood, which followed the stream of the river.

Table 1 Five flooded SAR images were shown in this table. The image on Nov. 1 was counted as flood, however, there is no result shows the flood condition on Nov. 1th.

Yes, we have no results because as indicated in the description, in the study area covered by SAR data the first levee breach occurred in the afternoon of November 1. The SAR image collected on the very same day was actually acquired in the early morning (i.e., 6 a.m. local time) and did not capture the flood. However, to perform a change detection with high reliability, we considered the image as flooded since the high soil moisture at the time of the acquisition could cause critical inaccuracies and because some small areas may have already been flooded (indeed upstream in Vicenza the event started around 7:30 a.m.).

Figure 8 “Wan see by : : :” Do you mean “We can see by: : :”?


Yes, there was a typo. Thanks for noticing it.

Line 437-440 Why the flood depth decreased in Vicenza and increased in Saletto? Without the description of the whole flood condition, it is difficult to understand these differences.

See the reply to point 5, where we indicated how we would modify the description of the flood dynamic.

Figure 11 Please add more description about this figure. When of the water depth shown in this figure? The color legend should be added.

We would change the image description as: “*Distribution of the validation points selected for flood depth assessment: a total of 120 validation points collected in the Vicenza and Saletto areas (i.e., 25 and 95, respectively) have been selected based on recognizable features in the aerial / fieldwork photos available for November 1 and 2. The reported SAR-based flood depth map used for the assessment refers to November 3.*” In the figure we would also add the date and the same color bar employed in all the previous figures.



Section 5.2 As mentioned in the manuscript, the hydrodynamic model needs more information than the proposed method, and its results were overestimated. It is difficult to verify the proposed method by comparing with the results from the hydrodynamic from Table 2 and 3. I suggest to add the quantities comparisons of area and depth in Section 5.1 using the aerial photos and the data of measure points, and remove this section.

We agree with the comment from the Reviewer. Indeed, it is difficult to verify our method by comparing with the result of the hydrodynamic model but we believe that it is very important to show the differences between the two approaches. Accordingly, we would prefer to leave the section as it is. The model is simulating the flood in the exact same moment of the SAR acquisition. We know that the SAR-based flood maps have uncertainties, but we think that it is useful to show a comparison with the results of model (as an example of current real-world practice), which are also affected by uncertainty (in this case evident).

Line 481 I think “Table 2 and” and “Table 3 confirm: : :” are the same paragraph.

Yes, this was an error create in the conversion to pdf.

## Anonymous Referee #2

The paper presents an interesting work that joins SAR remote sensing and DEM in order to asses extension and the water depth in the area affected by the flood with a user-friendly methodology. The paper is clearly written, and the topic appropriate for NHESS, but some points that need a better explanation I don't feel qualified to evaluate English I suggest that minor revisions are needed before the publication


General questions

1. cap 3.1 data used. There are some data from river gauge stations that allow understanding the flood dynamic? ( e.g. when occurred the flood peak?)

Yes, there are data of river gauge stations (see Figure below). We would also change the description of the flood as it follows, in order to explain its dynamic more clearly:

*"The first levee rupture in the study region occurred south of Vicenza in the afternoon of November 1. Afterwards, the flood propagated South-East to Veggiano, where the banks of the Bacchiglione River were broken in the night between November 1 and 2. During November 2 the Bacchiglione banks broke also in the area of Bovolenta, while the area of Saletto started to be flooded due to the rupture of the Frassine River banks on the same day (see Error! Reference source not found.). Based on the analysis of SAR imagery (Cian et al., 2018), in the area of Vicenza and Veggiano the peak of the flood event was estimated between November 2 (north-west of frame A in Figure 3) and November 3 (placeholder "A1" in Figure 3). Instead, in the Bovolenta (frame B in Figure 3) and Saletto (frame C in Figure 3) areas it occurred on November 4.*

*Figure 2 shows the measurements of hydrometers along the Bacchiglione River (hydrometers 1 to 5) and along the Frassine River (hydrometers 6 and 7) (ARPAV, 2010). We can notice how the flood wave moved from Vicenza (hydrometer 1) to Bovolenta (hydrometer 5), in accordance with the analysis of SAR data, which estimated the maximum extent after the highest measurement of the hydrometers. Concerning the Frassine River (hydrometers 6 and 7), we observe a similar behavior."*



**Figure 3** Overview of the area affected by the 2010 flood event occurred in the Veneto region (Italy). The main areas of interests are highlighted by the three frames: A) Vicenza, B) Bovolenta and C) Saletto. Placeholder A1 refers to the Veggiano area covered by the hydrodynamic modeling used for comparison purposes. The numbers in orange circles indicate the location of the hydrometers, whose measurements are reported in Figure 4. For each frame the flood start date is reported along with the direction of the flood wave (blue arrows).




Figure 4 Measurements of hydrometers during the period of the investigated flood event. The flow of the Bacchiglione River (hydrometers 1 to 5) goes towards South-East, i.e. from hydrometer 1 to 5. The flow of the Frassine River (hydrometers 6 and 7) goes towards East, i.e. from hydrometer 6 to 7. In both cases, the measurements show the dynamic of the flood, which followed the stream of the river.

2. Questions about "detected flood polygon" Which is the min and max dimensions of the polygon that you consider with the same water level? In addition, the procedure to create polygons it seems not so simple "to use also for non-GIS and RS experts". To create a gradient of water level it should be a more easy solution? In the conclusion, you suggested "Another improvement may come from the method for creating the water elevation plane", eventually this improvement required much time to be included in this work?

At the end of section 2.1 we specify three steps of post-processing employed in the flood mapping methods. Among these, the second says; '*exclusion of clusters smaller than 10 pixels*', which basically determines the minimum size of the polygons. Accordingly, being Sentinel-1 pixel size 10x10 m, this equals to exclude polygons with size smaller than  $10 \times 100 \text{ m}^2 = 1000 \text{ m}^2$ .

Regarding the simplicity of the methodology, we do not believe that generating polygons from a raster image is a challenging task for anyone. Overall, we think that the method is very simple to apply; indeed, only a flood map in vector format and a DEM shall be provided as input, then the algorithm does it all. It is not clear to us what the Reviewer means with "gradient of water level" and how, where, or in substitution to what we should apply it. Could the Reviewer please be more specific?

We believe that the suggested improvement might lead to an increased accuracy of the flood depth maps in specific circumstances. Nevertheless, it would still require a lot of time and effort to be properly developed, tested and validated, accordingly it is out-of-scope in the framework of this specific work.

### Specific comments

Introduction: About flood mapping, methodology, water depth estimation, SAR flood mapping in an urban and vegetated area maybe consider also some recent works (e.g. Dasgupta et al., 2018; Giordan et al., 2018; Pierdicca et al., 2018)

We would cite the works suggested by the Reviewer along with some others: Horritt 2001; Matgen et al., 2007; Brisco et al., 2011; Henry et al., 2006; Cossu et al., 2009; Martinis et al., 2015; Chini et al., 2012; Dasgupta et al., 2018; Giordan et al., 2018; Nico et al., 2000; Pierdicca et al., 2018

Line 50: "SAR data at high spatial resolution are continuously acquired by many satellites": It should better to specify that nowadays, only Sentinel-1 provide free, global and constant acquisition while CSKM and TSX provide constant acquisition only on some areas (e.g., CSKM provide continuous data only for Italy and some main cities)

We would change the paragraph as: *"SAR data at high spatial resolution are continuously acquired by many satellites in low Earth orbits, such as the German TerraSAR-X (TSX), the Italian COSMO-SkyMed (CSK) and more recently the ICEYE and the European Space Agency (ESA)'s Sentinel-1 (S1) constellations. These sensors can provide images up to a resolution of a fraction of a meter (e.g., TSX, CSK) and are able to promptly monitor disaster within few hours from their occurrence (e.g., CSK in urgent mode activation). However, up to now only S1 provide free, global and constant acquisition. ICEYE acquires globally and constantly but its data are not freely accessible, as well as the images acquired by TSX and CSK, which in addition are not even acquired systematically at a global scale."*

Figure 12: I suggest for the colour scale to use a different colour to point out the areas where the difference of water depth between SAR and model is negligible (e.g. +/- 10 cm).

To avoid confusion we decided to keep the same colour scale for all the images. We think that areas with +/- 10 cm difference are still evident. If requested we can modify the colour scale, but for consistency we would prefer to maintain the same.

Figure 10 A and B): It should be better to discuss more the errors related to strong backscatter urban area i.e. the group of buildings in the North sector was probably flooded as results from the model, but not from SAR data, it is correct?

The group of buildings referred by the Reviewer may have been flooded, as appears on the DEM fill results, but we do not have results of the model in this area nor evidence from aerial photos/ground truth. We would add the following paragraph at line 432 to better explain the results: *"Buildings in the central-north side of the image are categorized as flooded by the DEM-fill method in contrast to the SAR-based maps. It is worth noting that SAR data does not allow to extract flooded areas between buildings, where a mechanism of double bounce occurs making the radar backscatter to increase rather than decrease. However, we have no evidence that this specific area was actually flooded."*

Line 480 - 490 and Figure 13: add some more clear considerations about the overestimation of a hydraulic model and under-estimation of SAR: I suppose that some area that should be flooded according to model was protected by a breach and not flooded in truth; while the SAR underestimate flood in the area with buildings/vegetations and when the pass is after flood peak.

We would add the following sentence at line 486 to better explain the difference between the model and the SAR-based flood map: *"The reasons of this difference can be various. On the one hand, areas reported as flooded in the simulation could have been in truth protected by barriers not taken into consideration by the model, hence leading to an overestimation of the simulated flood extent. On the other hand, the SAR-based maps might experience some underestimation in the presence of urban and vegetated flooded areas (where the radar backscattering might increase due to specific multiple bouncing)."*

As concerns potential underestimation in the SAR-based maps due to observations available after the flood peak, this does not apply in this case since the model simulation was run for the exact same time of the SAR acquisition.

Line 482: remove headspace –

This space was generated while creating the pdf document. We will make sure that it will not happen again.

Conclusion. Line 515-522: In my opinion, another factor is to take into account: A flood map should be representative of the maximum extension and water depth reached during the inundation stage. It is important to remind that SAR satellite or other images represent the flooded area and water depth at a certain date and time and, if they don't acquire at the moment of maximum flood peak, the flood maps contain underestimations. As consequence it should be necessary to take as reference the data more close to the flood peak time: For instance in this specific case, in the area of Vicenza, the aerial photo represent better the real flooded area, while in the case of Saletto is the SAR data that best fit the ground truth.

We thank the Reviewer for this comment. Accordingly, we would add at the end of line 522, the following paragraph: *"However, it must be taken into consideration that satellite observations allow to outline the flooded areas and estimate the water depth at the specific date and time of their acquisition, which are not necessarily corresponding to the maximum flood extent and water depth. If the images are acquired far from the flood peak (either before or after), the estimated extent and depth will underestimate the worst situation occurred during the event."*

Line 534: "Another improvement may come from the method for creating the water elevation plane" see my considerations at point 2.

We replied at point 2.

# Flood depth estimation by means of high-resolution SAR images and LiDAR data

Fabio Cian<sup>1</sup>, Mattia Marconcini<sup>2</sup>, Pietro Ceccato<sup>3</sup>, Carlo Giupponi<sup>1</sup>

<sup>1</sup>Department of Economics, University of Venice Ca' Foscari, Venice, 30121, Italy

<sup>2</sup>DFD German Aerospace Center (DFD-DLR), Wessling, 82234, Germany

<sup>3</sup>International Research Institute for Climate and Society (IRI), Columbia University, New York, USA

*Correspondence to:* Fabio Cian (fabio.cian@unive.it)

**Abstract.** When floods hit inhabited areas, great losses are usually registered both in terms of impacts on people (i.e., fatalities and injuries) as well as economic impacts on urban areas, commercial and productive sites, infrastructures and agriculture. To properly assess these, several parameters are needed among which flood depth is one of the most important as it governs the models used to compute damages in economic terms. This paper presents a simple yet effective semi-automatic approach for deriving very precise inundation depth. First, precise flood extent is derived employing a change detection approach based on the Normalized Difference Flood Index computed from high resolution Synthetic Aperture Radar imagery. Second, by means of a high-resolution Light Detection And Ranging Digital Elevation Model, water surface elevation is estimated through a statistical analysis of terrain elevation along the boundary lines of the identified flooded areas. Experimental results and quality assessment are given for the flood occurred in the Veneto region, North-Eastern Italy, in 2010. In particular, the method proved fast and robust and, compared to hydrodynamic models, it requires sensibly less input information.

## 1 Introduction

Climate science foresees a future where extreme weather events could happen with increased frequency and strength as a consequence of anthropogenic activities. Specifically, climate change would favour extreme precipitations, which could cause riverine, flash and coastal floods (i.e., the main source of losses in the world as reported by MunichRE (2014)) to occur more and more often. The higher probability of these events to happen is also exacerbated by land-use change and in particular, by settlement growth which increases soil sealing and, hence, water runoff. The ultimate consequence would be an increase of fatalities and injuries, but also of economic losses in urban areas, commercial and productive sites, infrastructures and agriculture.

Flood risk and impacts are not sufficiently understood and documented and need to be monitored systematically with improved precision as underlined by the European Flood Directive (European Commision, 2007). This is particularly important to support climate change adaptation policies, as well as to develop robust public disaster relief funds, risk profile for financial institutes, risk portfolio for re-insurance companies and risk in supply chain for multinational companies (Mysiak, 2013; UNISDR, 2015). In order to assess flood impacts, besides their extent, several other parameters shall be monitored during the event, such as flow velocity, debris factor and inundation depth. Here, flood depth is particularly important since it governs the damage functions (or vulnerability curves or loss functions), which define the expected loss given a certain flood depth (Mojtahed, 2013; Scorzini, 2015).

Therefore, in ex-post assessment deriving flood depth is essential to quantify impacts and damages, to better characterize flood risk, as well as to implement disaster risk reduction measures. Furthermore, it also has a key role in supporting emergency response, assessing accessibility and designing suitable intervention plans, calculating water volumes and allocating resources for water pumping, as well as rapidly estimating the costs for intervention and reconstruction.

In Veneto, North-Eastern Italy, several floods caused major damages in the past decade as the one occurred in 2010 in  
40 the city of Vicenza and its surroundings, which was the most serious in the area over the last 50 years (ARPAV, 2010). Moreover, extreme weather events are expected to increase in the future due to climate change (Zollo, Rillo, & Buccignani, 2015) in the entire region, where therefore there is a great interest in monitoring floods.

To this purpose, remote sensing and in particular Synthetic Aperture Radar (SAR) data have been playing an important role since decades allowing, during crises, the derivation of flood extent maps like those provided by the European Copernicus  
45 Emergency Management Service (Copernicus EMS) or the International Charter on Space and Major Disaster (International Charter) (Martinis 2015). In fact, SAR sensors are particularly suitable for this task due to their capability of observing through clouds (thanks to microwaves all-weather capabilities) and during night (having their own source of illumination). Moreover, water surfaces are generally characterized by a very low backscattering (the portion of the outgoing radar signal that the target  
50 redirects directly back towards the radar antenna) due to the specular reflection of microwaves (O'Grady, Leblanc, & Gillieson, 2011), hence making water mapping relatively easy. SAR data at high spatial resolution are continuously acquired by many satellites in low Earth orbits, such as the German TerraSAR-X (TSX), the Italian COSMO-SkyMed (CSK) and more recently the ICEYE and the European Space Agency (ESA)'s Sentinel-1 (S1) constellations. These sensors can provide images up to a resolution of a fraction of a meter (e.g., TSX, CSK) and are able to promptly monitor disaster within few hours from their occurrence (e.g., CSK in urgent mode activation). However, up to now only S1 provide free, global and constant acquisition.  
55 ICEYE acquires globally and constantly but its data are not freely accessible, as well as the images acquired by TSX and CSK, which in addition are not even acquired systematically at a global scale.

Several types of algorithms have been developed to map floods using SAR data (Horritt 2001; Matgen et al., 2007; Brisco et al., 2011; Henry et al., 2006; Cossu et al., 2009; Martinis et al., 2015; Chini et al., Pulvirenti, & Pierdicca, 2012; Dasgupta et al., Grimaldi, Ramsankaran, Pauwels, & Walker, 2018; Giordan et al., 2018; Nico et al., Pappalepore, Pasquarello, Refice, & Samarelli, 2000; Nazzareno Pierdicca et al., Pulvirenti, & Chini, 2018). Among the most used, largely-employed  
60 thresholding techniques aim at identifying a backscattering value below which a pixel is categorized as water. Specifically, such threshold can be determined using automated procedures but it might consistently vary depending on e.g. environmental factors or the specific satellite acquisition geometry (Giustarini et al., 2015; Henry, 2006; Martinis, 2009; Pierdicca, 2013). Another very common solution relies on the use of change-detection techniques, which compute the difference between an  
65 image acquired during the flood and one acquired before the event. In particular, flooded areas can be identified as they are associated with a decrease in the backscattering. On the one hand, this allows to discriminate permanent water bodies (mostly characterized by low and stable backscattering values) from temporary water surfaces; on the other hand, it might occur that land-cover changes associated with different backscattering values at the two considered time steps (as typically occurs for crops) can lead to overestimation of flooded areas (Giustarini, 2015; Giustarini, 2013; Long, 2014; Matgen, 2007).

70 The abovementioned approaches generally fail to detect floods occurring in vegetated areas where the water surface is obscured by tree branches and leaves. This might become a critical issue in regions characterized by a large amount of woodland and medium to tall vegetation and requires users to be extra-vigilant to interpret the results. Furthermore, due to lack of details in medium/low resolution SAR data and to the multiple scattering and signal returns in high resolution images, mapping flood in urban areas may be very difficult if not impossible (Schumann et al., 2011).

75 A new methodology (Cian et al., 2018), developed by the authors and also used in this work for deriving flood maps, is based on the use of the Normalized Different Flood Index (NDFI). The index is based on the multi-temporal statistical analysis of two sets of images, one containing only the images before the event, and another one containing images both of the event and before the event. Through the computation of the NDFI, a change detection is performed, and flood maps are derived. The index highlights flooded areas and allows to easily separate flooded pixels by non-flooded ones by means of a constant  
80 threshold.

**Field Code Changed**

**Formatted:** Italian (Italy)

Once derived the flood extent, flood depth can be assessed using Digital Elevation Models (DEMs). In this context, several approaches have been developed in the past yet from the 1980s. Gupta & Banerji (1985) used 60m spatial resolution Landsat Multispectral Scanning System (MSS) imagery to derive the water volume of a dam reservoir in the Himalayas and estimated the water level superimposing the boundary line of the water surface to a topographic map. Ten years later, 85 Oberstadler et al. (1996) employed 12.5m resolution ERS-1 data for outlining the flood extent and overlaid the resulting map plotted with transparency to a map with topographic contours; next, water levels were manually registered at 500 m steps. Mason et al. (2001) derived the inter-tidal shoreline with ERS SAR data and estimated its height using a model based on depth-averaged hydrodynamics including the effects of tides and meteorological forcing. Matgen et al. (2007) used ENVISAT-ASAR multitemporal scenes and a Light Detection And Ranging (LiDAR) DEM (at 12.5m and 2m resolution, respectively) to derive 90 the water depth for the 2003 flood of the Alzette river in Luxembourg. Specifically, flood edges obtained from ASAR imagery were intersected with LiDAR data to estimate the elevation at the boundary line of water polygons. In particular, the water surface was computed using two different interpolation modeling: Triangulated Irregular Network (TIN) generation and multiple linear regression; then, the depth was calculated subtracting the DEM to the water elevation. This study was further improved by Schumann et al. (2007) where the authors retrieved the water elevation combining the regression model with the 95 TIN generation. Furthermore, the same methodology was also employed by Schumann et al. (2008) to compare the results obtained using different elevation information, namely topographic contours, Shuttle Radar Topographic Mission (SRTM) DEM and LiDAR-based DEM. Best results were obtained with 2m resolution LiDAR data but good performances could be achieved even with the 90m resolution SRTM DEM. Zwenzner & Voigt (2008) proposed a similar technique based on a model fitting the water elevation separately derived for the left and right riverbanks by combining the flood extent estimated from 100 SAR data with DEM data. Here, to estimate the water level a sequence of densely spaced river cross sections is shifted and adjusted individually.

All abovementioned approaches assume that the water level during the flood event is the same at both sides of the river cross section, thus assuming that the riverbanks are perfectly symmetric and that river flow and floodplain dynamics are not conditioning the overflow and the following stream. Nevertheless, while this hypothesis accounts for the river slope and defines 105 an equilibrium condition at the ends of the cross-section (i.e., they exhibit the same elevation), it may actually not fit many types of floods caused e.g. by riverbanks ruptures, asymmetric river banks or complex inundation dynamics.

More recently, Huang et al. (2014) derived flood depth by combining Landsat and LiDAR data under the assumption that the water plane can be considered flat if the flooded area is sufficiently small. Accordingly, they split the flood extent map obtained from Landsat data into 750x750m squared tiles. Then, for each of them they “filled” the LiDAR DEM up to the level 110 for which the resulting water extent was closest to the Landsat-based map (measured in terms of Kappa coefficient (Cohen, 1968)). For tiles completely covered by water, the average height of the 8 neighbour tiles is taken. Finally, the water surface is calculated using an interpolation method (i.e., Kriging) and the depth computed as the difference with respect to the DEM. A similar approach was also presented by Matgen et al. (2016). Brown et al. (2016) derived a flood extent map from SAR using a semi-automated method (thresholding, manual interpretation and correction). At 100-m intervals, elevation values 115 along the flood edges were detected by means of a LiDAR. Elevation points were inspected, in certain cases corrected or added manually by an operator, in order to improve the water surface elevation estimation. The water surface was then created using TIN interpolation. [\(Cohen et al., 2018\) derived flood depth maps from SAR images and DEMs, where the elevation of the flood water surfaces is estimated by a nearest neighbour algorithm starting at the boundaries of flooded areas.](#)

Instead, Iervolino et al. (2015) describes a model of SAR backscattering in case of flood (post-event) and in case of no 120 flood (pre-event). From the inversion of the model and the comparison between pre- and post-event condition, they derive the flood depth. They propose two methods: i) “Single Image Object Aware”, which allows to estimate the level of the water next to a building whose characteristics must be known (i.e. Object Aware), given that two gauges’ measurements are available in

its premises; and ii) "Two Images Areas Aware", which uses a pre-event and a during/post-event image to retrieve the water levels for the whole area, using an unflooded area in the during/post-event image for calibration (*i.e.* Area Aware). Even though 125 an interesting and promising approach, the two methods look complex and difficult to be implemented. Furthermore, ancillary data of difficult retrieval are needed, such as data from gauge stations and information about building affected by the flood.


As already mentioned, flood depth is important not only for emergency response, but also for impact assessment. Purely economic works use flood depth (usually retrieved from third parties) for assessing direct and indirect impacts of floods by means of depth-damage functions. However, if flood depth information is not available, often the whole range of possible 130 values is taken into account, hence resulting in extremely different scenarios. As an example, in Carrera et al. (2013) for a quite vast event (1182 Km<sup>2</sup>) spreading all over northern Italy a range in the depth from 1 to 6m resulted in a damage estimate varying from 4 billion € to roughly 10 billion €. In a similar work, Amadio et al. (2016) could obtain ~~better-precise~~ estimate 135 of the losses caused by the 2014 flood in Emilia Romagna, Italy, employing a simulated maximum flood depth computed by D'Alpaos et al. (2014) by means of hydraulic models. Nevertheless, this required several input information, as well as high processing power.

In this paper, a new methodology is proposed for rapid computation of flood depth by means of SAR data and high-resolution DEM. Firstly, a flood map is derived from SAR data using the algorithm proposed in (Cian et al., 2018). Secondly, a statistical analysis is performed on the terrain elevation values detected on the boundary lines of the flooded polygon, to estimate the correct water elevation, needed to compute the flood depth. The hypothesis is that all the detected water surfaces 140 are flat and theoretically showing a constant elevation value along their boundaries. As explained in detail in the methodology section, several sources of error make these values non-constant and the statistical analysis is a key step to estimate the correct water elevation.

The objective of this work is to present a semi-automatic, fast and reliable method to estimate a precise flood depth in support of economic impact assessment methods for a rapid estimation of losses (and precise in case of high-resolution 145 elevation data available) as well as the development of emergency plans. In contrast to many existing methods proposed in the literature, the presented proposed method requires only two inputs (*i.e.* the flood extent map and a DEM), it is based on a simple yet precise algorithm, it does not require intense manual interaction and strong computing capacity. Moreover, the algorithm is able to deal with uncertainties deriving from the flood extent map by means of statistical analysis and it is able to consider the change in elevation in different areas of the flood, in particular the variation of elevation along rivers, due to their natural 150 slope.

In Section 2 the proposed methodology is given. Section 3 describes the data used in the experimental analysis and the investigated study area, while Section 4 presents the results obtained. In Section 5 quality assessment and discussion are reported, whereas Conclusions are drawn in Section 6.

## 2 Methodology



155

**Figure 1 Flood Depth Estimation Methodology:** 1) flood maps are derived using the methodology presented in Cian et al. (2018); 2) by means of a high resolution Digital Elevation Model the elevation of the water surface is estimated, through a statistical analysis of elevation values along the boundary line of each flooded area; 3) flood depth is computed by subtracting the elevation values to the estimated elevation of water surface

160 The novel methodology proposed for estimating flood depth is composed of three main steps, namely i) flood mapping (extent estimation), ii) water surface elevation estimation and iii) flood depth estimation. They are explained in detail in the following three subsections.

### 2.1 Flood mapping

165 Flood mapping (block 1 in Fig. 1) is based on the use of the Normalized Different Flood Index developed by the authors and explained in details in (Cian et al., 2018). The method is based on the multi-temporal statistical analysis of two stacks of SAR images: one containing only images before the flood, i.e. reference images ("Reference" stack) and another one containing reference images and images of the event ("Reference + flood" stack). The mean temporal backscattering for each pixel throughout the "Reference stack" is computed together with the minimum backscattering value of each pixel throughout the "Reference + flood" stack. The two statistics are used to derive the new Normalized Difference Flood Index (NDFI), which

170 is the normalized difference between the mean(reference) and the minimum(reference + flood) value. The computation of the NDFI corresponds to a change detection step. In fact, the index highlights flooded areas and allows to easily separate flooded pixels by non-flooded ones by means of a constant threshold.

Therefore, in this step of the proposed system, after the computation of temporal statistics and of the NDFI index, a constant threshold on the NDFI value is applied ( $NDFI = 0.7$ ) to extract flooded areas. Following the methodology presented in (Cian et al., 2018), three steps of post-processing are applied to the resulting flood maps to reduce the effect of speckle and to reduce spurious flooded areas: i) application of morphological filters (dilate and closing filter with a 3 by 3 pixels windows); ii) exclusion of clusters smaller than 10 pixels; iii) exclusion of the pixels falling in a slope of  $>5^\circ$  (where a flood would be unlikely). The final flood maps are used as input of block 2 (Fig. 1).

### 2.2 Water surface elevation estimation

180 In this step, we take as input the flood map previously generated and a high-resolution DEM of the area affected by the flood. The flood map is used to extract the boundaries of each flooded polygons to perform a statistical analysis of their elevation values by means of the DEM. Despite any DEM can be used in this methodology, it should exhibit a resolution of a fraction of a meter to obtain significant flood depth values for economic impact assessment.

The objective of this step is to estimate the elevation of the water surface for each detected flooded polygon, analysing  
185 the DEM elevation they exhibit along their boundaries. Similarly to Huang et al. (2014) and Brown et al. (2016), we suppose  
that the water surface of the flooded areas is flat. This can be considered a fair assumption in those cases where the slope of  
the affected area is gentle, and the velocity of the flood stream is modest. More precisely, we do not assume a single constant  
elevation value for the whole flood map, but a constant water elevation inside each detected flooded polygon, which thus  
allows taking into consideration the usual decrease of the water surface elevation along a river. Under this assumption, each  
190 polygon shall then exhibit a constant DEM elevation along its boundary, which corresponds to the elevation of the entire water  
surface contained in the polygon itself; nevertheless, this is not happening due to different error sources.




Figure 2 a) Example of a detected flood polygon (light blue transparency) and relative flood boundary (red line). The dashed light blue line indicates the actual flood boundary, not correctly detected by the SAR-based flood map due to presence of vegetation obscuring the flood (cases indicated by letter A) or due to radar shadow (cases indicated by letter B). In the errors indicated by A, the elevation values detected are lower than the actual ones. Vice-versa, in the errors indicated by B, the elevation values detected are higher than the actual ones. b) Plot depicting the distribution function of the elevation along the boundary (red line). Areas indicated with A and B represent the values associated to the errors as explained above. The two threshold values (at the 5<sup>th</sup> and the 95<sup>th</sup> percentiles) are used to exclude outliers.

Figure 2(a) shows an example of a detected flooded polygon (light blue transparency). Based on our theoretical assumptions, this water surface should have a constant elevation. In practice, this may not happen due to some sources of error (Fig. 2(a)). Specifically, the detected flood boundary (red line) may not correspond to the real boundary of the flood (dashed light blue line) due to: A) vegetation obscuring flooded areas leading to omission errors, and B) the nature  
195

**Formatted:** Font: Times New Roman, Font color: Auto, English (United Kingdom)

**Formatted:** Font: Times New Roman, Font color: Auto, English (United Kingdom)

of SAR images (speckle, radar shadow, layover (Franceschetti & Lunari, 2018)) that can lead to false alarms or omission errors. Uncertainties in the SAR-based flood map, errors in the DEM and misalignment between the SAR data and the DEM can lead to further uncertainty in the detection of elevation values along the boundary lines, resulting in outlier values under- or overestimating the real water elevation value. The plot reported in Fig.<sup>ure</sup> 2(b) shows the distribution (percentiles) of the 200 DEM elevation values along the boundary lines. The above-mentioned errors (over- or/and underestimation) can be associated to the values contained in areas A and B. It is more likely to find outliers on the lower end of the elevation value distribution, since an underestimation is more likely due the sources of error abovementioned.

Therefore, if we want to reliably estimate the correct water elevation for each flooded polygon, we need to identify and exclude outliers associated with omission errors (e.g. flood covered by vegetation), to commission errors (e.g. radar shadow 205 included in the flood map) or misalignments between SAR and DEM data.

First, elevation values are extracted from the available input DEM in correspondence to the boundary of each flooded polygon individually. Then, the corresponding percentiles are computed (i.e., where a percentile denotes the value below which a given percentage of observations falls in the investigated group of observations) and values below the 5<sup>th</sup> and above the 95<sup>th</sup> percentile are removed since, from extensive experimental analysis, this generally proved rather effective for removing under- 210 and overestimation errors.

Next, given our hypothesis of a flat water surface, we have to check if the elevation value distribution is stable. Knowing that locally we can find a non-stable distribution (due to the abovementioned sources of error), starting from n=95 we iteratively compute, with step 1, the difference between the DEM value corresponding to the  $n^{th}$  and the  $(n-5)^{th}$  percentile, respectively. If the difference is greater than 10 cm, then the process continues; otherwise we stop and compute the water elevation as the 215 mean value between the extremes of the 5-percentile interval analysed at the last iteration. The idea is to identify a plateau in the distribution that can represent the correct water elevation.

We start looking for the correct elevation from the high-end of the distribution for two reasons: i) statistically there are less outliers on this side of the distribution and ii) because it is the highest correct value of water elevation that determines the overall water elevation for the considered flooded polygon. The 95<sup>th</sup> percentile represents a good starting point, able in most 220 cases to exclude all the outliers present in one single polygon.

A step of five percentiles was found to be an optimal indicator of stability compared to the comparison of consecutive percentiles. This adaptive threshold takes care of the different conditions of each single polygon and allows increasing the precision of the method. As expected, the statistical distribution of elevation values is not identical for each boundary line. Therefore, a fixed threshold would have led to and increased uncertainty in the final water surface elevation estimation, 225 especially in those cases where flood polygons have a non-regular geometry, which can overlap a complex topography or can encompass vegetation, roads, built-up areas.

A threshold check is set on the 50<sup>th</sup> percentile, allowing us to spot possible wrong estimations. In fact, an elevation of the water surface below the 50<sup>th</sup> percentile is indicating an exceptional behaviour of the analysed boundary line, which would need dedicated investigation.

230 The water surface elevation estimation step is carried out using a Python<sup>TM</sup> script including the  *arcpy* library (ArcPy). In this script, we provide as inputs the flood map (shapefile format) and the DEM (raster format). The DEM is clipped using the boundary line of a flood polygon by means of the  *arcpy* function  *ExtractByMask*. Then, the elevation values of this newly created raster are analysed and their distribution (percentiles) is computed. The procedure is repeated for each flooded polygon in the flood map and the distribution values of each polygon are added in the attribute table of the shapefile. Finally, the 235 algorithm selecting the optimal water elevation value is summarized by the following:

$n = 95$

```

240      for i = 0 to (n-5)
241          if [Pn-i - P(n-5)-i] ≤ 10 cm then
242              Water Surface Elevation = [Pn-i + P(n-5)-i] / 2
243          Else
244              i = i +1
245          endif
246      if (n-5-i) = 50 then warning
247  endfor

```

with  $P$  indicating the percentile and  $n$  the upper percentile threshold.

### 2.3 Flood depth estimation

Finally, depth is determined for each flooded pixel as the difference between its DEM value and the water elevation  
250 estimated for the corresponding flooded polygon.

In few cases, where the polygon geometry or the topography is non-regular, the estimation of the water level can be  
unprecise. However, if this is not yet detected by the threshold check, it can be easily detectable by analysing at the resulting  
flood depth values. If, inside a given polygon several negative values are obtained, this indicates an underestimation of the  
water elevation. Instead, if a given pixel is associated with a flood depth much higher than its neighbours, then the water level  
255 may have been overestimated. Therefore, we select the polygons showing unexpected behaviours and we compare them with  
a DEM-fill approach. The DEM is filled up to the estimated water surface elevation. If the resulting polygon extent does not  
match with the observed flooded polygon, we manually look for the elevation value that best approximated the flood extent  
and set it as the water elevation. Then we compute again the flood depth and reiterate the steps until we have a satisfying result.

## 3 Data Used and Case Study

### 3.1 Veneto Flood 2010

Heavy rain concurrent with other adverse effects From October 31 to November 2, 2010, in the Veneto Region, North-East Italy, led to the flooding of 140 km<sup>2</sup> of land have been flooded with major damages on properties and infrastructures. The event was originated by an Atlantic perturbation, which caused intense precipitation over the whole area, with extremes in the pre-alps and piedmont areas. Local rainfall accumulation exceeded 500 mm and the average widely surpassed 300 mm, leading  
265 to a serious hydraulic stress, especially in the area of Vicenza and the south of Padua. Sirocco wind, persistent on sea and inland, slowed the discharge of rivers into the sea. Early snow melted due to the warm temperature also added water to the rainfall.

The first levee rupture in the study region occurred south of the city of Vicenza in the afternoon of November 1. Afterwards, the flood then propagated to the south eastwards toward Veggiano, where the banks of the Bacchiglione River  
270 were broken in during the night between November 1 and 2. During November 2 the Bacchiglione banks broke also in in the areas of Bovolenta, while and the area of Saletto started to be flooded due to the rupture of the Frassine River banks in the same day (see Figure 3 Figure 3 Figure 3). Based on the analysis of SAR imagery (Cian et al., 2018), in the area of Vicenza  
and Veggiano Concerning the extent of the flood, based on SAR observations (Cian et al., 2018), on the area of Vicenza and Veggiano, the peak of the flood event was estimated was reached in between November 2 (Nnorth-Wwest of framearea A in Fig. 3) and November 3 (placeholder for area “A1” in Fig. 3)), with a consequent decrease of the flood intensity afterwards.  
275 Instead, in the area of Bovolenta area (framearea B in Fig. 3) reached the flood extent peak was reached on November 4,

**Formatted:** Font: (Default) +Body (Times New Roman)

**Formatted:** Font: (Default) +Body (Times New Roman)

with a consequent decrease of water levels in the following days. The area of Saletto reached a maximum flood extent on November 3.

Figure 4 Fig. 4 shows the measurements of hydrometers along the Bacchiglione River (hydrometers 1 to 5) and along the Frassine river (hydrometer 6 and 7) (ARPAV, 2010). We can notice how the flood wave moved from Vicenza (hydrometer 1) to Bovolenta (hydrometer 5), in accordance with the analysis of SAR data-observations, which estimated the observed a maximum flood-extent after the highest measurement of the hydrometers. Concerning the Frassine River (hydrometers 6 and 7), we observe a similar behavior.

Overall 262 municipalities were affected leading to roughly half billion Euros damage, three fatalities, 3500 displaced and more the 500 thousand people affected. The flood also triggered hundreds of landslides in the mountainous surroundings, which led to more than 500 warnings of instability phenomena received by the province soil protection division (Floris et al., 2012; Scorzini, 2015). This paper analyses three main areas as shown in Figure 3 Figure 3 Fig. 3: Vicenza and its surrounding (A), the Bovolenta area at the south of Padua (B) and the Saletto area at the south of Colli Euganei (a group of hills of volcanic origin that rise to heights of 300 to 600 m a few km south of Padua) (C).

290

**Formatted:** Font: (Default) +Body (Times New Roman)  
**Formatted:** Font: (Default) +Body (Times New Roman)




Figure 3 Overview of the area affected by the 2010 flood event occurred in the of 2010, Veneto region, (Italy). The three main areas of interests are highlighted by the three frames: A) Vicenza, B) Bovolenta and C) Saletto. Placeholder Area A1) refers to the Veggiano area covered by the hydrodynamic modeling used for comparison purposes as an assessment dataset. The numbers in orange circles indicate the location of the hydrometers, whose measurements are indicated reported in Figure 4. For each areas frame the figure reports the start of the flood start date is reported along with and the direction of the flood wave (blue arrows).




Figure 4 Measurements of hydrometers during the period of the investigated flood event. The flow of the Bacchiglione River (hydrometers 1 to 5) goes towards South-East, i.e. from hydrometer 1 to 5. The measurements show the dynamic of the flood, which followed the stream of the river. The flow of the Frassine River (hydrometer 6 and 7) goes towards East, i.e. from hydrometer 6 to 7. In both cases, the measurements show the dynamic of the flood, which followed the stream of the river.

300

### 3.2 Data Used

Flood maps were derived using CSK data, provided by the Italian Space Agency, following the methodology proposed by Cian et al. (2018). Table 1Table 1Table 4 reports the complete list of scenes used.

305

**Formatted:** Font: (Default) +Body (Times New Roman)

**Formatted:** Font: (Default) +Body (Times New Roman)

**Table 1** List of COSMO-SkyMed SAR data (Stripmap 3 m) used for deriving flood maps of the event

Date	Status	Acquisition Time (UTC)
31/Oct/2008	Reference	17:35
28/Apr/2010	Reference	17:30
29/Aug/2010	Reference	5:01
01/Nov/2010	Flood	5:01
03/ Nov /2010	Flood	17:22
04/ Nov /2010	Flood	18:10
06/ Nov /2010	Flood	17:28
07/ Nov /2010	Flood	5:13

Additionally, different DEMs were used for estimating the flood depth:

310

- the LiDAR Digital Terrain Model (DTM) from the Venice River Basin Authority at 2m resolution produced in 2004, which was employed for the Vicenza area of interest;
- the LiDAR DTM from the ministry of Environment at 1m resolution produced in 2012, which has been used for the areas of Bovolenta and Saletto;
- the 5m resolution DTM at 5 available from the Veneto Region geodatabase, which was used for the whole area of interest for the cross-comparison with the hydrodynamic model.

315 To validate the results, in absence of proper ground truth, we made use of different datasets that allowed us a qualitative assessment of our maps:

320

- A simulation of the event by means of a hydrodynamic model, where flood extent was estimated for November 3 and 4 using the 2DEF finite elements model (Viero et al., 2014) and flood depth was obtained as described by Viero et al. (2013). The simulation was computed in order to correspond to the exact moment of the SAR acquisition and it was performed using the DTM of the Veneto Region at 5 m resolution;
- A set of aerial photographs acquired on November 1 taken by the Firemen Department of Vicenza covering mainly the Vicenza area of interest;
- A set of in situ photographs taken from the Civil Protection on November 1 and 2 covering the area of Saletto.
- A set of in situ photographs taken by the authors in 2017.

325 **4 Results**

**4.1 Elevation values distribution**

As discussed above, the proposed methodology is based on the statistical analysis of the elevation values along the boundary lines of the estimated flooded polygons. [Figure 5](#)[Figure 5](#)[Fig. 5](#)[Figure 4](#) shows the distribution (percentiles) of elevation values for 18 randomly selected polygons in the Vicenza area of interest on November 3. As discussed in Section 2, 330 on the tails of the distribution (below the 5<sup>th</sup> and above the 95<sup>th</sup> percentile) we can notice some irregularities, i.e. non-flat profiles, in contrast to more stable behaviours in most of the cases in the central part of the profiles. The thresholds on the 5<sup>th</sup> and 95<sup>th</sup> percentile cut out most of the outliers. By means of the adaptive threshold starting from the 95<sup>th</sup> percentile, the method is able to estimate the elevation of the water surface looking for a plateau on the distribution. It prevents to overestimate water elevation since it gets rid of upper outliers, it prevents to underestimate it posing a limit on the lower percentile and setting a 335 condition on the slope of the profile (elevation difference equal or lower than 10 cm in a step of five percentiles). Less regular profiles can be seen in the plot, like the one indicated by the arrows A and B in Fig. [5](#)[Figure 5](#)[Fig. 5](#)[Figure 4](#). The irregularity is due to errors in the flood map, such as the case when vegetation obscures part of the flooded area, when there is a misalignment between the flood map and the DEM, when flooded polygons exhibit a non regular geometry or when the DEM along the flood boundaries has a complex topography. In these cases (less than 3%), the proposed methodology might not result in reliable estimations. 340 In fact, the elevation can exhibit two problems: i) it never shows a stable value along the distribution (no plateau is found) and the water elevation is associated with the 50<sup>th</sup> percentile; and ii) it presents a plateau at a higher elevation with respect to the real water surface elevation, resulting in an overestimation of the flood depth (this may rarely happen for example when the flood map crosses over roads or river banks at higher elevation due to inaccuracies of the flood map or misalignment between the flood maps and the DEM). The threshold check set at the 50<sup>th</sup> percentile detects the first problem, while the second is 345 detected by looking at high value of flood depth (> 2m) or by finding discontinuities between neighbouring polygons in the estimated surface water elevation. For those few cases, it is necessary to intervene manually as it is not possible to estimate the right elevation simply looking at this statistic, as described at the end of Section 2.




Figure 5 Elevation values distribution (percentiles) for a random selection of flood polygon's boundaries in the Vicenza area on November 3. The 95<sup>th</sup> and 5<sup>th</sup> percentile thresholds are highlighted. Arrows "A" and "B" indicate less regular profiles, for which the proposed methodology is less effective. In these cases (less than 3% of the total) it is necessary a manual intervention.

#### 4.2 Flood Depth Estimation

Flood depth was computed for the three areas of interest indicated in Figure 3. Flood depth was estimated for the whole flooded area except for a small portion of Veggiano area (a portion of the A.1 area indicated in Figure 3), where LiDAR data was not available. Figure 6 shows the results for the Vicenza area of interest. Specifically, Figure 6(a) shows the flood maps for November 3 and 5(b) the LiDAR extent, which covers the entire flood with the exception of the central part of the map (the portion of the Veggiano area mentioned above). Figures 6(c) and 6(e) show respectively water surface elevation and flood depth for November 3. Figures 6(d) and (f) show water surface elevation and flood depth for November 4. The dynamics of the event, i.e. the receding of water from November 3 to 4, can be noticed where extent and depth of the flood decrease. The flooded area extends for several kilometers along the Bacchiglione river where the terrain elevation decreases gradually from the north-west to the south-east. Since we estimate water elevation for each single polygon, we are able to take into consideration also the slope of the river. This can be noted in the overall decreasing of water surface elevation values in Figure 6(c) and (d).

For types of floods similar to this, the hypothesis of a flat water surface inside a single polygon is a good approximation since the flood evolution is slow and therefore water surface can be considered flat. This is especially true in case of the Bovolenta and Saletto area of interest where the flood extent was limited and the topography relatively simple.


Figure 7 shows the flood depth for the Bovolenta area of interest on (a) November 4 and (c) 6. Also in this case, we can notice the receding of flood extent between the two dates. Figures 7(b) and (d) show a zoom of the results where the high level of detail can be appreciated.

Figure 8 shows the results for the Saletto area of interest on (a) November 3, (b) 4, (c) 6 and (d) 7. In this case, the evolution of the event, in particular the decrease of flood extent and depth is even clearer given the higher number of observations available.


Formatted: Font: (Default) +Body (Times New Roman)  
 Formatted: Font: (Default) +Body (Times New Roman)

Formatted: Font: (Default) +Body (Times New Roman),  
 Bold, Font color: Auto  
 Formatted: Font: (Default) +Body (Times New Roman),  
 Bold, Font color: Auto  
 Formatted: Font: (Default) +Body (Times New Roman),  
 Bold, Font color: Auto  
 Formatted: Font: (Default) +Body (Times New Roman),  
 Bold, Font color: Auto  
 Formatted: Font: (Default) +Body (Times New Roman),  
 Bold, Font color: Auto  
 Formatted: Font: (Default) +Body (Times New Roman),  
 Bold, Font color: Auto

As it is evident from the depth maps and the relative scales, there can be negative values of flood depth, which in most of the cases occur at the proximity of the boundaries of flooded polygons. These indicate most likely an underestimation of 375 the water surface elevation, even if also false alarms in the flood map can induce to the same problem. However, the negative values are in most of the case in the order of few centimeters (less than 10 cm) and these pixels can be considered as very shallow water.




380 **Figure 6 Water Surface Elevation and Flood Depth estimation for Vicenza area of interest on November 3 and 4.** (a) shows the flood map for November 3 and (b) the extent of the LiDAR data, which does not completely cover the flooded areas. (c) and (d) show water surface elevation, (e) and (f) show flood depth, respectively for November 3 and 4. Reddish values in (e) and (f) indicate negative flood depth, therefore an error in the estimation of the water surface elevation (underestimation).



**Figure 7** Flood Depth for the Bovolenta area of study on (a) November 4, and (c) November 6. (b) and (d) show a zoom of the results highlighting the high level of detail achievable. Reddish pixels represent the error in the water level estimation.

385



**Figure 8** Flood Depth for the area of interest of Saletto on (a) November 3, (b) 4, (c) 6 and (d) 7

## 5 Assessment and Discussions

390

### 5.1 Assessment with Aerial Photos


Ground truth data consist of aerial photographs taken on November 1 right after the beginning of the event, and of field pictures taken on November 1 and 2 by civil protection. Unfortunately, they do not match the dates and time of satellite acquisitions, therefore they cannot be used as a proper validation dataset. However, given the slow dynamic of the flood, they can provide very useful information about the water level, which can be estimated and compared with the results of our method

395

and therefore provide an assessment of the results. To prove this, in [Figure 9](#) [Figure 9](#) [Figure 8](#) we show a comparison of flood extents derived for November 2 from 25m resolution Radarsat-2 data, and for November 3 from 5m resolution CSK imagery. The lower resolution of Radarsat-2 does not allow extracting the same level of detail of the map based on CSK data, but it is enough to show that the status of the flooded areas in the two consecutive days is very similar. Therefore, it makes sense to use the available aerial photographs for assessing the results, keeping in mind a possible change in the flood status

400

between the two situations. In particular, from the image we can notice that for the Vicenza area (Fig. 98a and 98b) the flood has receded from November 2 to 3, while for the Saletto area (Fig. 98c and 98d) it has expanded.



**Figure 9** Comparison between Radarsat-2- (November 2, 2010) and COSMO-SkyMed-based flood maps (November 3, 2010). Radarsat-2 has a lower resolution (25 m) compared to COSMO-SkyMed (5 m), which provides a coarser flood map. We can see by the comparison of the two maps that the flood has comparable extent in the two days. In particular, from the image we can notice that for the Vicenza area (Fig. 98a and 98b) the flood has receded from November 2 to 3, while for the Saletto area (Fig. 98c and 98d) it has expanded.

405

The assessment is carried out in three different steps: 1) estimation of water elevation corresponding to the dates of the aerial photos acquisition; 2) analysis of water elevation obtained using the proposed SAR-based method; and 3) cross-comparison of the two values.

**Formatted:** Font: Times New Roman, Font color: Auto, English (United Kingdom)

**Formatted:** Font: Times New Roman, Font color: Auto, English (United Kingdom)

**Formatted:** Font: Times New Roman, Font color: Auto, English (United Kingdom)

Concerning step 1, we made use of i) a DEM-fill technique and ii) of data acquired during a fieldwork of late 2017. DEM-fill consists of “filling” the DEM up to the elevation that gives a flood extent similar to the one displayed by the photos, which will be the estimated water elevation. In the fieldwork, we measured the height of the water plane on features recognizable in the aerial photos. These measurements added to the DEM value in the same location, allows the estimation of 410 water elevation. Averaging these two values allows the estimation of the water elevation at the moment of acquisition of the aerial photos, which can be compared with the results given by the proposed SAR-based method.

Concerning step 2, SAR-based results are analysed in comparison with a DEM-fill method to understand the consistence of flood depth values in relation to the extent of DEM-based simulated flood.

Concerning step 3, the cross-comparison is done by comparing water elevation obtained in step 1 and 2.

415 The assessment was performed for the flood depth maps of November 3, the date of the first high resolution SAR image available after the acquisition of the aerial photos.

In **Panel I** of Fig. [109](#), [Figure 10](#)[Figure 10](#)[Fig. 10](#)[Figure 9](#)(a) shows flood extent and depth on November 3 at 17:22 UTC on the area of Ponti di Debba, south of the city of Vicenza, derived from the CSK SAR image shown in Fig. [109](#)(b). **Panel II** 420 of Fig. [109](#) shows aerial photo and fieldwork of the same area. Fig. [109](#)(c) shows the aerial photo acquired on November 1 at 14:00 UTC, where three areas are highlighted: area 1 (zoom in 1.A) for which the proposed method detect no flood on November 3 and the DEM-fill method estimate a water elevation of 28 m; area 2 (zoom in 2.A) for which our method estimates a water level of 26.98 m and the fieldwork data 27.46 m (27.06 m elevation given by the DEM plus 0.4 m of flood depth estimated from fieldwork); area 3 (zoom in 3.A) for which our method detect no flood and the fieldwork data 27.45 m (27 m 425 elevation given by the DEM plus 0.45 m of flood depth estimated from fieldwork). **Panel III** of Fig. [109](#) shows the flood extent derived with the DEM-fill method for different water levels: Fig. [109](#)(d) with water level equal 26.98 m corresponding to the level estimated by our method; Fig. [109](#)(e) with water level equal to 27.45 m, corresponding to the water level estimated by fieldwork data; Fig. [109](#)(f) with water level equal to 28 m, corresponding to the level estimated by the DEM-fill method in order to obtain the same flood extent of the aerial photo.

430 Fig. [109](#)(f) shows that with a water elevation of 28 m, based on the DEM we obtain a very similar water extent of the one observed in the aerial photo. If we set a water level of 27.45 m (Fig. [109](#)(e)), the value estimated from fieldwork, we would obtain a slightly underestimated flood extent compared to the one observed in the aerial photo. From this analysis, we can estimate a water level on November 1 of 27.72 (average between 27.45 to 28 m).

435 Looking at Fig. [109](#)(d), we can observe that the flood extent resulting with a water level of 26.98 m, the same estimated with our method, is very similar to the extent extracted from the SAR image. A similar extent confirms the goodness of the SAR-based flood map, while the estimation of the water level, 26.98 m, is comparable to the value estimated from the aerial photo and relative to 2 days before the SAR acquisition. This would mean a decrease of the water level of 0.74 m in two days. The reduction of flood extent in this area from November 2 to 3 is confirmed also by Radarsar-2 acquisition as we can see in Fig. [98](#)a and b.



Figure 10 Flood depth on November 3 over Ponti di Debba in the Vicenza area of interest; panel I shows (a) flood depth on the area analysed; (b) CSK image acquired on November 3 at 17:22 UTC from where the flood map has been derived; panel II shows (c) aerial view of the event acquired on November 1 at about 14:00 UTC with zooms on three areas (1.A, 2.A, 3.A) with relative fieldwork images (2.B and 3.B); panel III shows the flood extent derived with the DEM-fill method for different water levels: (d) with water level equal 26.98 m corresponding to the level estimated by the proposed method; (e) with water level equal to 27.45 m, corresponding to the water level estimated by fieldwork data; (f) with water level equal to 28 m, corresponding to the level estimated by the DEM-fill method in order to obtain the same flood extent of the aerial photo.

450 In **Panel I** of Fig. 110, Fig. 110(a) shows flood extent and depth on November 3 at 17:22 UTC on the area of Via Isole, in the Saletto area, derived from the CSK SAR image shown in Fig. 110(b). **Panel II** of Fig. 110 shows aerial photo and fieldwork of the same area. Fig. 110(c) shows the aerial photo acquired on November 1 at about 14:50 UTC, where two areas are highlighted: area 1 (zoom in 1.A) for which the proposed method detects a water elevation of 11.6 m, the DEM-fill method estimates a water elevation of 11.4 m and the fieldwork data 11.38 m (10.7 m elevation given by the DEM plus 0.68 m of flood depth estimated from fieldwork); area 2 (zoom in 2.A) for which the proposed method estimates a water elevation of 11.6 m and the fieldwork data 11.33 m (10.93 m elevation given by the DEM plus 0.4 m of flood depth estimated from fieldwork). **Panel III** of Fig. 110 shows the flood extent derived with the DEM-fill method for different water levels: Fig. 110(d) with water level equal to 11.6 m corresponding to the elevation estimated by the proposed method; Fig. 110(e) with water level equal to 11.38 m, corresponding to the water elevation estimated by field work; Fig. 110(f) with water level equal to 11.4 m, corresponding to the level estimated by the DEM-fill method in order to obtain the same flood extent of the aerial photo.

460 Fig. 110(f) shows that with a water elevation of 11.4 m, based on the DEM we obtain a very similar water extent of the one observed in the aerial photo. If we set a water level of 11.38 m (Fig. 110(e)), the value estimated from fieldwork, we would obtain the same flood extent compared to the one observed in the aerial photo. From this analysis, we can estimate a water level on November 1 of 11.38 m.

465 Looking at Fig. 110(d), we can observe that the flood extent resulting with a water level of 11.6 m, the same estimated with the proposed method, is very similar to the one observed in the SAR image.

Also in this case, an increase of 0.2 m from November 2 to 3 is consistent with the situation observed in from SAR acquisitions as shown in Fig. 98(c) and (d).

470 ~~BFor the buildings in the central north side of the image are categorized as flooded by, we can observe that the DEM-fill method reports them to be flooded in contrast to what the SAR-based maps reports. It is worth noticing that This is due to the limit of SAR data does not allow to extract flooded areas in between buildings, where a mechanism of double bounce occurs making the radar backscatter to increase rather than instead of decreasing. However For the specific case however, we have no evidence that of this specific area was to be actually flooded.~~

475 The same approach was followed for a total of 120 points distributed in the Vicenza (25 points) and Saletto area of study (95 points) as shown in Fig. 124. These points were selected based on recognizable features in the aerial or fieldwork photos of November 1 and 2. These points belonged to different flood polygons in the SAR-based flood map. For each point, we computed the difference between the water elevation estimated for November 1 or 2 based on aerial or fieldwork photos (step 1 of the assessment process) and the water elevation estimated from the SAR image for November 3. For the area of Vicenza we obtained an average difference of +53 cm. This difference is consistent with the observed change of flood depth (decrease) from November 1 and November 3. For the area of Saletto we obtained an average difference of -47 cm, a value that is 480 consistent with the increase of flood depth observed from November 1 and November 3.

485 The differences are mainly due to the different timing of observation between the SAR image and the aerial and fieldwork photos. However, a source of errors is also intrinsic of the SAR method. In fact, we can have false alarms or false negative in the flood map (overestimation of flood extent due to radar shadow, or flood underestimation due to vegetation on top of flood areas) or misalignment between the DEM and the SAR data, which could be a geolocation error or an effect of different resolutions between the two datasets.




Figure 11 Flood depth on November 3 over via Isole in the Saletto area of interest; panel I shows (a) flood depth on the area analysed; (b) CSK image acquired on November 3 at 17:22 UTC from where the flood map has been derived; panel II shows (c) aerial view of the event acquired on November 1 at about 14:50 UTC with zooms on two areas (1.A, 2.A) with relative fieldwork images (2.B and 3.B); panel III shows the flood extent derived with the DEM-fill method for different water levels; Fig. 110(d) with water level equal to 11.6 m corresponding to the elevation estimated by the proposed method; Fig. 110(e) with water level equal to 11.38 m, corresponding to the water elevation estimated by fieldwork for area 1; Fig. 110(f) with water level equal to 11.4 m, corresponding to the level estimated by the DEM-fill method in order to obtain the same flood extent of the aerial photo.



495 **Figure 12 Distribution of the validation points Overview of selected point used for flood depth assessment points; a total of 120 validation points collected distributed in the Vicenza (25 points) and Saleto areas of study (i.e. 25 and 95, respectively points) have been selected based on recognizable features in the aerial /or fieldwork photos available for November 1 and 2. The reported SAR-based flood map shown is the one used for the assessment refers to, of November 3, 2010.**

500 **5.2 Cross comparison: hydrodynamic modeling**

Flood depth obtained with the presented methodology was compared with the one derived using a hydrodynamic model presented in Viero et al. (2013). The simulation was available for the area of Veggiano (area A1 in Fig. 3) and Bovolenta (area B in Fig. 3) on November 3 and 4 at the same time of the SAR acquisitions over the same areas. It made use of the DTM at 5 m resolution of the Veneto Region geodatabase, therefore the same DTM has been used with the proposed methodology to 505 derive meaningful results for comparison.

The first row of [Figure 13](#)[Figure 13](#)[Fig. 13](#)[Figure 12](#) shows the simulated flood depth (a), the SAR-based estimated flood depth (b) and the difference between the two (c) for Veggiano area on November 3, 2010. The second row, Fig. 132(d-f), shows the same series of results for the same area on November 4. The third row, Fig. 132(g-i), shows the same series of results for Bovolenta area on November 4.


510 Differences of two types can be seen between the two approaches: i) different flood extent and ii) different flood depth values between the model-based result and the SAR-based one. Concerning the first type of difference, [Figure 14](#)[Figure 14](#)[Fig. 14](#)[Figure 13](#) shows the SAR image (a) from where the SAR-based flood extent (b) was derived and the flood extent derived by the hydrodynamic model (c). The red box in Fig. 143(b) and (c) delineates the boundary of the hydrodynamic modeling. From the comparison of these two extents, as well as the ones in Fig. 132, it is clear that the hydrodynamic model is 515 overestimating the flood extent compared to the SAR observation. This leads to the second type of difference, *i.e.* the different values of flood depth. A different extent leads to a different estimation of the water surface, which in turn can be different depending on the methodology employed and therefore provides different flood depth value.

Analysing the two results, differences in flood extents seem to be the main driver of discrepancies. In fact, generally we 520 can observe an overestimation of flood depth by the hydrodynamic model, which is overestimating the flood extent. In the case of Veggiano on both dates (Fig. 132(c) and (f)), the difference is greater than 1 m only in small portion of the image (< 0.3

km<sup>2</sup>), while in the rest of the image the difference in mainly between 10 and 50 cm. In the case of Bovolenta (Fig. 132(i)) the difference is bigger, with an area of about 1 km<sup>2</sup> with a difference greater than 1 m. In this case, we can also see an overestimation of depth by our method on the south east of the flood, which is almost in all the cases well below 1 m.

Table 2 and Table 3 confirm this analysis. In fact, Table 2 compares the flood extent obtained by the model with the one derived from the SAR image showing the area reported only by the model, only by the SAR-based approach and the agreement between the two. If for the Veggiano area the difference between the two extents for both dates is limited to about 1 km<sup>2</sup>, in the Bovolenta area the difference is more consistent, about 7 km<sup>2</sup>, *i.e.* the model is reporting about two times the extent of the SAR observation. These numbers confirm the overestimation of the hydrodynamic model. The reasons of this difference can be various. On the one hand, areas reported as flooded in the simulation could have been in truth protected by a-barriers; not taken into consideration by the model, hence leading to an overestimation of the simulated flood extent. On the other hand, or the SAR-based maps might experience some underestimation in the presence of flood extent may not report as flooded urban or vegetated flooded areas (where the radar backscattering might increases due to specific multiple bouncing), that had actually been flooded, resulting in an underestimation of the SAR-based flood map.

Table 3 instead compares numerically the flood depth obtained with the two methods. The Root Means Square Difference (RMSD) shows a value of 55 cm in the area of Veggiano on November 3, 73 cm on November 4 and a value of 79 cm in the area of Bovolenta on November 4. Once again, the numbers confirm the qualitative analysis and were expected given the overestimation of the flood extent by the model.



540 **Figure 13 Comparison between the estimated flood extent and depth from hydrodynamic model and the proposed system based on the same DTM at 5 m resolution. (a-c): simulated flood depth, SAR-based flood depth and difference between the two for Veggiano area on November 3; (d-f): simulated flood depth, SAR-based flood depth and difference between the two for Veggiano area on**

November 4; (g-i): simulated flood depth, SAR-based flood depth and difference between the two for Bovolenta area on November 4.




Figure 14 Comparison between SAR-based flood extent and simulated flood extent for the Veggiano area on November 3. (a) shows the CSK SAR image of November 3 2010; (b) shows the flood extent derived from the SAR image; (c) shows the simulated flood extent, which was calculated only for the area delimited by the red box. The difference between the two extents is very clear.

Table 2 Flood extent cross-comparison between SAR-based extent and hydrodynamic model-based extent.

Date - Area	Only hydrodynamic Model extent [km <sup>2</sup> ]	Only SAR-based extent [km <sup>2</sup> ]	Agreement between the two extents [Km <sup>2</sup> ]
3 Nov - Veggiano	6.81	5.86	4.33
4 Nov - Veggiano	4.87	3.82	2.77
4 Nov - Bovolenta	15.63	8.48	7.98

Table 3 Comparison between flood depth obtained with the hydrodynamic model and the proposed methodology

Date - Area	Mean Difference [cm]	Mean Absolute Difference [cm]	RMSD [cm]
3 Nov - Veggiano	-27	42	55
4 Nov - Veggiano	-63	68	73
4 Nov - Bovolenta	-37	62	79

## 6 Conclusions

In this paper, we showed a methodology for assessing flood depth based on a statistical analysis of elevation data along 555 the boundary lines of flooded areas. Starting from flood extent maps and using high resolution DEM, water elevation can be estimated and therefore flood depth computed. The methodology may become suitable for operational mode. In fact, it meets the ideal requirements as indicated by Brown et al. (2016): accurate, simple to use also for non-GIS and RS experts, easily applicable to different satellite data (SAR and optical) and quick to apply.

The results have been assessed through aerial and fieldwork images acquired during the event. The assessment, carried 560 out on 120 points distributed in the area of Vicenza and Saletto, shows: i) an average underestimation of 53 cm for the area of Vicenza, due mainly to the decrease of water level from November 1 (date of aerial images) to November 3 (date of SAR acquisition); ii) an average overestimation of 47 cm, for the area of Saletto, due mainly to the increase of water level from November 1 (date of aerial images) to November 3 (date of SAR acquisition) in this part of the flood.

565 In comparison with hydrodynamic models, this methodology is more easily implemented since less information is needed: a stack of SAR images (before and after the event) and a DEM. Hydrodynamic models need additional information in order to derive depth, such as precipitation volumes, information about the soil, number and location of water pumps, etc.

The comparison with results obtained with a hydrodynamic model gives relatively good correspondence, the main difference being the different flood extent estimated by the model, which leads to a generally higher depth estimation. The model shows less accuracy together with a more complex utilization due to the additional data required to run it.

570 However, it must be remembered taken into consideration that satellite observations allow to outline represent the flooded area and estimate the water depth at the specific date and time of their acquisition a certain date and time, which are not necessarily corresponding are close to the maximum flood extent and water depth. If the images are acquired far from the flood peak (either before or after), the estimated extent and depth estimated will underestimate always be an underestimation of the worst situation occurred during the event.

575 In comparison to existing methodologies in the literature based on SAR data, the method we present is simple since it requires only the flood extent map and a DEM as inputs, it is based on an algorithm that does not require strong capacity in terms of computation and manual interaction, and it is able to handle the uncertainties of the SAR-based flood maps.

580 The proposed approach is based on the main hypothesis that water surfaces are flat and exhibit a constant elevation along their boundaries. This has been considered fair where the area affected by the flood is characterized by a flat terrain or a gentle slope and where the considered river and riverine flood show a slow dynamic.

585 The area under analysis in this study presents these characteristic and the obtained results proved to be particularly accurate, hence confirming the goodness of the abovementioned assumptions. However, the methodology, even though not suitable to be applied in the presence of steeper terrain or fast river and flood dynamic, allows to identify where this occurs. Indeed, the statistical analysis of the terrain elevation at the boundary of the flooded areas detects when we are in the presence of pretty unstable distributions and, in such cases, the algorithm would produce a warning and prevent the computation of a wrong flood depth.

590 Furthermore, we also showed that in some cases, despite true, the assumption of flat water does not find an actual correspondence in the data. For instance, we might not retrieve constant elevation values along the boundaries of flooded areas when there are errors in the initial SAR-based flood map (i.e., errors in the flood extent or misalignments of the SAR image and the DEM). However, making use of statistical analysis, we are able to handle these outlier values and to obtain results which proved accurate according to in-situ measurements.

595 Besides the employment of a detailed flood extent, a key requirement for obtaining reliable flood depth maps is the availability of accurate height information. Here, the proposed method supports DEMs at any spatial and vertical resolution; however, results may strongly vary depending on the specific dataset available. In particular, the access to a high-resolution DEM may be the discriminant for deciding whether to apply or not the technique. For example, to the original purpose for which we implemented the methodology (i.e., flood economic impact assessment), a high precision is required and a vertical resolution of 1m may not be sufficient to precisely estimate the damages caused by a given flood. In fact, damage functions may already saturate at 2m; thus, if the estimated depth would be e.g.  $1m \pm 1m$ , then the resulting damage would have the same uncertainty that one can obtain without using our technique.

600 Finally, by treating each flooded area individually, the method is able to take into consideration the natural variation of water elevation of a river, due to its slope, possible asymmetries of riverbanks and river flow, and floodplain dynamics, which can cause different flood conditions at the two sides of the river.

605 Despite the very good results obtained, the methodology can be further improved and automatized. Future work may consider to integrate a DEM filling procedure for improving water level estimation (Huang et al., 2014). The use of a vegetation index such as NDVI, may be used to exclude wrong points along the boundary lines. In fact, in case vegetation is found along

**Formatted:** Line spacing: 1.5 lines

**Formatted:** English (United Kingdom)

**Formatted:** English (United Kingdom)

**Formatted:** English (United Kingdom)

**Formatted:** English (United States)

the boundary, that may indicate an error in the flood map and therefore the correspondent elevation would be an information to be discarded. Similarly, slope can be computed from the DEM and used to exclude errors due to radar shadow or misalignment between SAR and DEM data. In fact, in case the elevation measured is greater than a certain threshold, that may indicate that the point is on a steep area (e.g. river banks) and with high probability the point was wrongly included in the 610 flood map (radar shadow), or the pixel in the flood map does not exactly overlap the DEM. Excluding these possible sources of error would improve the statistics and therefore the estimation of the water level.

Moreover, shallow water in short vegetation could be mapped (Cian et al., 2018) and used to improve the SAR-based flood map from the omission errors caused by vegetation.

Another improvement may come from the method for creating the water elevation plane. Instead of relying simply on 615 the elevation values distribution, the plane that minimizes the RMSE could be found using the points on the boundary line left after the exclusion of outliers. The plane created could also take into consideration the slope of the river in a better way compared to the current method. By means of a shape index and the relative position between the river and the flooded area, the slope of the polygons can be estimated and imposed to the water plane. This would take into account the slope of the river and therefore the dynamics of the flood allowing to derive better results also for floods with a fast dynamic.

620 In conclusion, the proposed methodology shows great potential in support of rapid economic flood damage assessment. In fact, being able to rapidly estimate the flood depth, allows the computation of economic damage using available damage functions, which given a certain flood depth, returns the percentage of damage suffered by the economic asset considered. The precise estimation of flood depth value, increases the accuracy of the estimation of a flood impact, extremely important in the emergency response phase of a disaster.

## 625 Acknowledgement

The authors would like to thank the Italian Space Agency (ASI), which provided the SAR data for producing the flood maps, A. Metz, German Aerospace Center, who provided support to write the script in Python, D. P. Viero, University of Padua, which kindly provided the hydrodynamic modeling of the event and support in evaluating our results and M. Martone, German Aerospace Center for the precious comments and suggestions that helped improving this work.

## 630 References

Amadio, M., Mysiak, J., Carrera, L., & Koks, E. (2016). Improving flood damage assessment models in Italy. *Natural Hazards*, 82(3), 1–14. <http://doi.org/10.1007/s11069-016-2286-0>

ArcPy. (n.d.). Retrieved from <http://pro.arcgis.com/en/pro-app/arcpy/get-started/what-is-arcpy-.htm>

ARPAV. (2010). SCHEDA EVENTO “PLUVIO”:, (Figura 2), 1–16.

635 Brown, K. M., & Brownett, J. M. (2016). Progress in operational flood mapping using satellite synthetic aperture radar (-SAR ) and airborne light detection and ranging ( LiDAR ) data. <http://doi.org/10.1177/0309133316633570>

Carrera, L., Standardi, G., Bosello, F., & Mysiak, J. (2013). Assessing direct and indirect economic impacts of a flood event through the integration of spatial and computable general equilibrium modelling. *CMCC Research*, 63, 1–27. <http://doi.org/10.1016/j.envsoft.2014.09.016>

640 Chini, M., Pulvirenti, L., & Pierdicca, N. (2012). Analysis and interpretation of the COSMO-SkyMed observations of the 2011 Japan tsunami. *IEEE Geoscience and Remote Sensing Letters*. <http://doi.org/10.1109/LGRS.2011.2182495>

Cian, F., Marconcini, M., & Ceccato, P. (2018). Normalized Difference Flood Index for rapid flood mapping: Taking advantage of EO big data. *Remote Sensing of Environment*, 209(March), 712–730.

Formatted: Italian (Italy)

Formatted: Italian (Italy)

Formatted: Italian (Italy)

Formatted: Italian (Italy)

http://doi.org/10.1016/j.rse.2018.03.006

645 Cohen. (1968). WEIGHTED KAPPA. *Psychological Bulletin*, 257–72. Retrieved from <http://www.ncbi.nlm.nih.gov/pubmed/19586159>

Cohen, S., Brakenridge, G. R., Kettner, A., Bates, B., Nelson, J., McDonald, R., ... Zhang, J. (2018). Estimating Floodwater Depths from Flood Inundation Maps and Topography. *Journal of the American Water Resources Association*. <http://doi.org/10.1111/1752-1688.12609>

650 D'Alpaos, L., Brath, A., & Fioravante, V. (2014). Relazione tecnico-scientifica sulle cause del collasso dell'argine del fiume Secchia avvenuto il giorno 19 gennaio 2014 presso la frazione San Matteo. Formatted: Italian (Italy)

Dasgupta, A., Grimaldi, S., Ramsankaran, R. A. A. J., Pauwels, V. R. N., & Walker, J. P. (2018). Towards operational SAR-based flood mapping using neuro-fuzzy texture-based approaches. *Remote Sensing of Environment*. <http://doi.org/10.1016/j.rse.2018.06.019>

655 Eu. (2007). Directive 2007/60/EC of the European Parliament and of the Council. *Official Journal of the European Union*, 288(2455), 27–34. <http://doi.org/English>

European Commission. (n.d.). Copernicus Emergency Management Service. Retrieved from <http://emergency.copernicus.eu/mapping/copernicus-emergency-management-service>

660 Floris, M., D'Alpaos, A., De Agostini, A., Stevan, G., Tessari, G., & Genevois, R. (2012). A process-based model for the definition of hydrological alert systems in landslide risk mitigation. *Natural Hazards and Earth System Science*, 12, 3343–3357. <http://doi.org/10.5194/nhess-12-3343-2012> Formatted: Italian (Italy)

Franceschetti, G., & Lunari, R. (2018). *Synthetic aperture radar processing*. CRC press. Formatted: Italian (Italy)

665 Giordan, D., Notti, D., Villa, A., Zucca, F., Calò, F., Pepe, A., ... Allasia, P. (2018). Low cost, multiscale and multi-sensor application for flooded area mapping. *Natural Hazards and Earth System Sciences*. <http://doi.org/10.5194/nhess-18-1493-2018>

Giustarini, L., Hostache, R., Matgen, P., Schumann, G. J., Bates, P. D., & Mason, D. C. (2013). A Change Detection Approach to Flood Mapping in Urban Areas Using TerraSAR-X. *IEEE Transactions on Geoscience and Remote Sensing*, 51(4), 2417–2430. <http://doi.org/10.1109/TGRS.2012.2210901>

670 Giustarini, L., Vernieuwe, H., Verwaeren, J., Chini, M., Hostache, R., Matgen, P., ... De Baets, B. (2015). Accounting for image uncertainty in SAR-based flood mapping. *International Journal of Applied Earth Observation and Geoinformation*, 34, 70–77. <http://doi.org/10.1016/j.jag.2014.06.017> Formatted: Italian (Italy)

Gupta, R. P., & Banerji, S. (1985). Monitoring of reservoir volume using LANDSAT data. *Journal of Hydrology*, 77(1–4), 159–170. [http://doi.org/10.1016/0022-1694\(85\)90204-5](http://doi.org/10.1016/0022-1694(85)90204-5) Formatted: Italian (Italy)

675 Henry, J. B., Chastanet, P., Fellah, K., & Desnos, Y. L. (2006). Envisat multi-polarized ASAR data for flood mapping. *International Journal of Remote Sensing*, 27(9–10), 1921–1929. <http://doi.org/10.1080/01431160500486724>

Huang, C., Chen, Y., Wu, J., Chen, Z., Li, L., Liu, R., & Yu, J. (2014). Integration of remotely sensed inundation extent and high-precision topographic data for mapping inundation depth. *2014 The 3rd International Conference on Agro-Geoinformatics, Agro-Geoinformatics 2014*, 1–4. <http://doi.org/10.1109/Agro-Geoinformatics.2014.6910580>

680 Jervolino, P., Guida, R., Iodice, A., & Riccio, D. (2015). Flooding Water Depth Estimation With High-Resolution SAR. *53(5)*, 2295–2307. Formatted: Italian (Italy)

International Charter. (n.d.). International Charter on Space and Major Disasters. Retrieved from <https://www.disasterscharter.org> Formatted: Italian (Italy)

Long, S., Fatoyinbo, T. E., & Policelli, F. (2014). Flood extent mapping for Namibia using change detection and thresholding with SAR. *Environmental Research Letters*, 9(3), 035002. <http://doi.org/10.1088/1748-9326/9/3/035002>

685 Martinis, S., Kersten, J., & Twele, A. (2015). A fully automated TerraSAR-X based flood service. *ISPRS Journal of*

*Photogrammetry and Remote Sensing*, 104, 203–212. <http://doi.org/10.1016/j.isprsjprs.2014.07.014>

Martinis, S., Twele, a., & Voigt, S. (2009). Towards operational near real-time flood detection using a split-based automatic thresholding procedure on high resolution TerraSAR-X data. *Natural Hazards and Earth System Science*, 9(2), 303–314. <http://doi.org/10.5194/nhess-9-303-2009>

690 Mason, D. C., Davenport, I. J., Flather, R. a., Gurney, C., Robinson, G. J., & Smith, J. a. (2001). A Sensitivity Analysis of the Waterline Method of Constructing a Digital Elevation Model for Intertidal Areas in ERS SAR scene of Eastern England. *Estuarine, Coastal and Shelf Science*, 53(6), 759–778. <http://doi.org/10.1006/ecss.2000.0789>

Matgen, P., Giustarini, L., Chini, M., Hostache, R., Wood, M., & Schlaffer, S. (2016). Creating a water depth map from SAR flood extent and topography data. *International Geoscience and Remote Sensing Symposium (IGARSS), 2016–Novem*, 695 7635–7638. <http://doi.org/10.1109/IGARSS.2016.7730991>

Matgen, P., Schumann, G., Henry, J.-B., Hoffmann, L., & Pfister, L. (2007). Integration of SAR-derived river inundation areas, high-precision topographic data and a river flow model toward near real-time flood management. *International Journal of Applied Earth Observation and Geoinformation*, 9(3), 247–263. <http://doi.org/10.1016/j.jag.2006.03.003>

Mojtahed, V., Giupponi, C., Biscaro, C., Gain, A. K., & Balbi, S. (2013). Integrated Assessment of Natural Hazards and 700 Climate Change Adaptation : II . The SERRA Methodology, (07).

MunichRE. (2014). *Loss events worldwide 2014 Percentage distribution*.

Mysiak, J., & Luther, J. (2013). Towards a potential European flood impact database. EEA – JRC – ETC/CCA Joint Technical Paper.

Nico, G., Pappalepore, M., Pasquariello, G., Refice, a., & Samarelli, S. (2000). Comparison of SAR amplitude vs. coherence 705 flood detection methods - a GIS application. *International Journal of Remote Sensing*, 21(8), 1619–1631. <http://doi.org/10.1080/014311600209931>

O’Grady, D., Leblanc, M., & Gillieson, D. (2011). Use of ENVISAT ASAR Global Monitoring Mode to complement optical data in the mapping of rapid broad-scale flooding in Pakistan. *Hydrology and Earth System Sciences*, 15(11), 3475–3494. <http://doi.org/10.5194/hess-15-3475-2011>

710 Oberstadler, R., H?nsch, H., & Huth, D. (1996). Assessment of the mapping capabilities of ERS-1 SAR data for flood mapping: A case study in Germany. *European Space Agency, (Special Publication) ESA SP*, 11(383), 247–252. [http://doi.org/10.1002/\(SICI\)1099-1085\(199708\)11:10<1415::AID-HYP532>3.0.CO;2-2](http://doi.org/10.1002/(SICI)1099-1085(199708)11:10<1415::AID-HYP532>3.0.CO;2-2)

Pierdicca, N., Pulvirenti, L., & Chini, M. (2018). Flood Mapping in Vegetated and Urban Areas and Other Challenges: Models and Methods. In C. Springer Remote Sensing/Photogrammetry. Springer (Ed.), *Flood Monitoring through Remote 715 Sensing* (pp. 135–179). [http://doi.org/10.1007/978-3-319-63959-8\\_7](http://doi.org/10.1007/978-3-319-63959-8_7)

Pierdicca, N., Pulvirenti, L., Chini, M., Guerriero, L., & Candela, L. (2013). *Observing floods from space : Experience gained from COSMO-SkyMed observations*. *Acta Astronautica*, 84, 122–133. <http://doi.org/10.1016/j.actaastro.2012.10.034>

Schumann, G., Hostache, R., Puech, C., Hoffmann, L., Matgen, P., Pappenberger, F., & Pfister, L. (2007). High-resolution 3-D flood information from radar imagery for flood hazard management. *IEEE Transactions on Geoscience and Remote 720 Sensing*, 45(6), 1715–1725. <http://doi.org/10.1109/TGRS.2006.888103>

Schumann, G. J., Neal, J. C., Mason, D. C., & Bates, P. D. (2011). Remote Sensing of Environment The accuracy of sequential aerial photography and SAR data for observing urban flood dynamics , a case study of the UK summer 2007 floods. *Remote Sensing of Environment*, 115(10), 2536–2546. <http://doi.org/10.1016/j.rse.2011.04.039>

Schumann, G., Matgen, P., Cutler, M. E. J., Black, A., Hoffmann, L., & Pfister, L. (2008). Comparison of remotely sensed 725 water stages from LiDAR, topographic contours and SRTM. *ISPRS Journal of Photogrammetry and Remote Sensing*, 63(3), 283–296. <http://doi.org/10.1016/j.isprsjprs.2007.09.004>

Scorzini, A. R., & Frank, E. (2015a). Flood damage curves : new insights from the 2010 flood in Veneto , Italy, 1–12.

Formatted: Italian (Italy)

Formatted: Italian (Italy)

Formatted: Italian (Italy)

<http://doi.org/10.1111/jfr3.12163>

730 Scorzini, A. R., & Frank, E. (2015b). Flood damage curves: New insights from the 2010 flood in Veneto, Italy. *Journal of Flood Risk Management*, 1–12. <http://doi.org/10.1111/jfr3.12163>

**Formatted:** Italian (Italy)

UNIDSR. (2015). *Making Development Sustainable: The Future of Disaster Risk Management. Global Assessment Report on Disaster Risk Reduction.*

Viero, D. P., Peruzzo, P., Carniello, L., & Defina, A. (2014). Integrated mathematical modeling of hydrological and hydrodynamic response to rainfall events in rural lowland catchments. *Water Resources Research*, 50(7), 5941–5957.

735 <http://doi.org/10.1002/2013WR014293>

Viero, D. Pietro, D'Alpaos, A., Carniello, L., & Defina, A. (2013). Mathematical modeling of flooding due to river bank failure. *Advances in Water Resources*, 59, 82–94. <http://doi.org/10.1016/j.advwatres.2013.05.011>

**Formatted:** Italian (Italy)

Zollo, A. L., Rillo, V., & Bucchignani, E. (2015). Extreme temperature and precipitation events over Italy: assessment of high-resolution simulations with COSMO-CLM and future scenarios. <http://doi.org/10.1002/joc.4401>

740 Zwenzner, H., & Voigt, S. (2008). Improved estimation of flood parameters by combining space based SAR data with very high resolution digital elevation data. *Hydrology and Earth System Sciences Discussions*, 5, 2951–2973. <http://doi.org/10.5194/hessd-5-2951-2008>