

Efficacy of using Radar Derived Factors in Landslide Susceptibility Analysis: case study of Koslanda, Sri Lanka.

A.K.R.N. Ranasinghe¹, R. Bandara¹, U.G.A. Puswewala², T.L. Dammalage¹

5 ¹Department of Surveying and Geodesy, University of Sabaragamuwa, Belihuloya, 70140, Sri Lanka

²Department of Civil Engineering, University of Moratuwa, Moratuwa, 10400, Sri Lanka

Correspondence to: A.K.R.N. Ranasinghe (nishamanie@geo.sab.ac.lk)

Abstract. Through the recent technological developments of radar and optical remote sensing in (i) the areas of temporal, spectral, spatial, and global coverage, (ii) the availability of such images either at a low cost or free of charge, and (iii) the advancement of tools developed in image analysis techniques and GIS for spatial data analysis, there is a vast potential for landslide studies using remote sensing and GIS as tools. Hence, this study aimed to assess the efficacy of using Radar Derived Factors (RDF) in identifying landslide susceptibility using bivariate, Information Value method (InfoVal method) and multivariate, Multi Criteria Decision Analysis based on Analytic Hierarchy Process statistical analysis. Using identified landslide causative factors, four landslide prediction models as bivariate without and with RDF, multivariate without and with RDF were generated. Twelve factors as topographical, hydrological, geological, land cover and soil plus three RDF are considered. The weight of index for landslide susceptibility is calculated by using landslide failure map and susceptibility regions are categorized into four classes as very low, low, moderate, and high susceptibility to landslides. With the integration of RDF, boundary detection between high and very low susceptible regions are increased by 7%, and 4% respectively.

20 1 Introduction

Landslides are one of the major types of geo-hazards in the world as approximately 09% of global natural disasters are recorded as landslides (Chae et al., 2017, Chalkias et al., 2014). The recent statistics on landslide disasters per continent, from year 2000 to 2017, summarized in the Emergency Disaster Database (EM-DAT). The database indicates that landslides cause around 16500 deaths and affect 4.5 million people worldwide, with property damages of about US \$3.5 million (OFDA/CRED, 2016). The spatial prediction of landslide disasters, incorporating statistical analysis to identify areas that are susceptible to future land sliding is one the important areas of geo-scientific research. These studies are based on the knowledge of past landslide events, topographical parameters, geological attributes, and other possible environmental factors (Park et al., 2013).

Presently, remote sensing has been used extensively to provide landslide-specific information for emergency managers and policy makers in terms of disaster management activities in the world (Baroň et al., 2014, Martha, 2011). The spatial resolution of space-borne optical data is now less than 1m in panchromatic images, and at the same time, Synthetic Aperture Radar (SAR) sensors and related processing techniques has also increased. Radar is considered to be unique among the remote sensing systems, as it is all-weather, independent of the time of day, and is able to penetrate into the objects. Additionally, radar images have been shown to depend on several natural surface parameters such as the dielectric constant and surface roughness. The dielectric constant is highly dependent on soil moisture due to the large difference in dielectric constant between dry soil and water (Kseneman et al., 2012). It is accepted in the scientific community that remote sensing techniques do offer an additional tool for extracting information on the causes of landslides and their occurrences. Especially for deriving various parameters related to the landslide predisposing and triggering factors at global and regional scales, remote sensing plays a vital role

(Corominas et al., 2014, Muthu et al., 2008, Pastonchi et al., 2018). Most importantly, landslide susceptibility analysis has greatly aided the prediction of future landslide occurrences, which is important for humans who reside in areas surrounded by unstable slopes. It is therefore identified that remote sensing techniques are significant in order to extract the landslide susceptibility regions by providing most suitable landslide predisposing factors at smaller scale.

5

There is massive potential for applicational research in the area of disaster management, if, conventional remote sensing data and radar are integrated. This is because each method has its inherent disadvantages and shortcomings, as well as advantages, and integrating the two potentially complement each other. As such, this study combines the predisposing factors derived from both optical and radar satellite data for landslide susceptibility analysis. Furthermore, significant landslide predisposing factors like soil moisture, surface roughness, and forest biomass are derived from radar images, and the impacts of these factors on landslide susceptibility are examined.

10

1.1 Methods for Landslide Susceptibility Analysis

There are inherent limitations and uncertainties in landslide susceptibility analysis, and yet, several methods have been utilized and successfully applied in the past (Kanungo et al., 2009). These methods have been of both qualitative and quantitative nature. Generally, qualitative methods are based on expert opinions while the quantitative approaches, such as statistical and probabilistic approaches, depend on the past landslide experiences.

15

Qualitative methods simply make use of landslide inventories to identify areas with similar geological and geomorphologic properties that show susceptibility for land failures. These methods can be divided into two groups as geomorphologic analysis, and map combination. In geomorphologic analysis, the landslide susceptibility is determined directly either in the field or by the interpretation of images through geomorphologic analysis (Bui et al., 2011). Map combination is based on combining a number of predisposing factor maps for landslide susceptibility analysis. However, map combination analysis comprises of a semi-quantitative nature by integrating the ranking and weighting of landslide susceptibility (Ayalew et al., 2004, Kavzoglu et al., 2014, Saaty, 1980). The analyses based on the quantitative approaches depend on numerical data and statistics, expressing the relationship between instability or predisposing factors with landslides (Reis et al., 2012). These methods are categorized into two groups as bivariate and multivariate statistical analysis. Within the context of this work, popular Information Value method (InfoVal) as bivariate and Multi-Criteria Decision Analysis (MCDA) based on Analytic Hierarchy Process (AHP) as multivariate methods are compared with respect to their performances in landslide susceptibility analysis.

20

25

30

1.2 Landslide predisposing factors

It is understood that landslides may occur as consequences of complex predisposing and triggering factors. Topographical and geological factors, together with local climatic conditions, lead to landslide occurrences. The selection of these factors, and preparation of corresponding thematic data layers, are vital for models used in landslide susceptibility analysis (Jakob et al., 2006, Lee et al., 2017). There are no universal guidelines regarding the selection of predisposing factors in landslide susceptibility analysis. Some parameters may be important factors for landslide occurrences in a certain area but not for another one. Scientists (van Westen, 1997, van Westen and Getahun, 2003, van Westen et al., 2003) show that every study area has its own particular set of predisposal factors which condition landslides. Determination of appropriate causal factors is a difficult task, and no specific rule exists to define how many factors are sufficient for a specific landslide susceptibility analysis. Hence, the selection of predisposing factors are dependent on the nature of the study area, opinions of the experts, and the availability of data for generating the appropriate spatial and thematic information (Kavzoglu et al., 2015, Shahabi and Hashim, 2015).

35

40

2 Study Area

Koslanda in Sri Lanka is located at the geographical coordinates of 06° 44' 00" North and 81° 01' 00" East, and the elevation is around 700 – 1000 m above Mean Sea Level (MSL). It is a remote, hilly area with harsh weather conditions, where the monthly rainfall ranges from 60 mm to 200 mm, and average temperature is 20⁰ C. The area has rains for most of the year, with very short, dry period during the months of February to April. The population is around 5000 people, and the study area has an extent of 19 km² within the Koslanda area. Koslanda has been the site for of several massive landslides over the years, and both the Naketiya landslide in the year 1997, and Meeriyabedda landslide in the year 2014, are very distinct in Fig. 1, and within a span of two years, major landslides have occurred three times at the same location. When considering the typology of landslides in this study area, falling, toppling, subsidence, lateral displacements, and debris flows are prominent (NBRO, 2016).

The geomorphology of the area is described as a gently inclined talus slope, with a thick, loosely compacted colluvium deposit at the foot of the near vertical rocky scarp. Koslanda is situated at the middle part of the slope, with the lower area showing a fairly steep surface as well. The composition of the colluvium deposit in the area includes a randomly arranged mixture of weathered clayey and sandy materials, with the organic matter making the deposit act as a highly absorbing entity with high water content. The study area was an abandoned tea land in which the properly maintained surface drainage system has been neglected” (Somaratne, 2016). Geology refers to the physical structure and the substance of the Earth. The study area consists mainly of undifferentiated charnockitic biotite gneisses and Quartzites, according to the 1:10000 geological map from the Geological Survey Mines Bureau (GSMB), Sri Lanka. Such geomorphological and geological formation, together with improper land use management practices, has made the area extremely vulnerable for landslide events.

FIGURE 1

3 Data and methodology

3.1 Data

The most important phases in landslide prediction analyses are the collection of data from different sources, and the construction of a spatial database on a common platform (Lan et al., 2004). The data utilized for the landslide prediction analysis include the topographical, hydrological, geological, soil, and land cover factors. All factors are derived from optical images (Landsat-8, Sentinel-2), radar images (Sentinel-1, TerraSAR-X), Digital Elevation Model (DEM) derived from aerial triangulation and other available data sources (geology, rainfall). Stereo aerial photographs from 1993 are used to generate the 7 m resolution DEM using aerial triangulation. The landslide inventory map for the study area was constructed by integrating the interpreted multi-temporal aerial photographs, satellite images, and some temporal images from the Google Earth (Figure 2). Verifications are carried out through field investigations. In this research, the predisposing factors were selected from among the most widely considered factors in literature and opinion from the experts.

Most data are derived as primary data from remote sensing techniques for a large area with up-to-date information. As such, fifteen predisposing factors are selected for the landslide susceptibility analysis by using bivariate and multivariate statistical techniques. Of these, twelve factors (elevation, slope, aspect, planar curvature, profile curvature, Topographical Wetness Index (TWI), land use, lineament density, distance to water bodies, soil moisture, geology, and rainfall) are derived from optical images, DEM and auxiliary data, while three more factors (soil moisture from Delta Index, surface roughness, and forest

biomass) are derived from radar images. These factors were then combined in order to analyse the performance of this integration for landslide susceptibility analysis.

5 3.1.1 Topographical Factors

The topographical factors include elevation, slope, aspect, planar curvature, profile curvature and surface roughness of the terrain. The first four factors are derived from the 7 m resolution DEM, and surface roughness is derived using Sentinel 1 radar image. The elevation is important to study the local relief of the terrain and ranges from 446 -1537 m above MSL in the study area. Since the area contains high mountains, more than a 1000 m difference in elevation can be observed. The basic parameter for the slope stability analysis is the slope angle. The slope angle of the study area ranges from 0^0 to 80^0 , showing a significant increase of slope within a relatively small area. Additionally, the area with steep slopes ranging from 60^0 - 80^0 can be seen in the northern part of Koslanda. Aspect is defined as the direction of maximum slope of the terrain surface, or the compass direction of a particular slope. The curvature is theoretically defined as the rate of change of slope (or slope), of the focused slope. Planar curvature describes convergence and divergence of the flow across a surface, while the profile curvature refers to acceleration or deceleration of the flow across a surface.

Under radar configuration, the magnitude of radar backscatter is defined as a function of surface roughness and moisture content. Similar studies from Rahman et al., 2008 and Septiadi and Nasution, 2009 emphasized the extraction of surface roughness from radar data using textural analysis. Hence, to estimate the surface roughness without the use of any ancillary field data, a Sentinel-1 radar image on 12th March 2015 under the dry climatic condition was used to reduce the effect of the moisture component from the radar backscatter. The texture is the structure, or appearance, of the surface, and as such, describes the coarseness or the homogeneity of the image structure. One of the most prominent methods for texture analysis is Grey Level Co-occurrence Matrix (GLCM), which is based on the second order probability density function. The GLCM describes how often a grey level occurs at a pixel located at a fixed geometric position relative to its neighbourhood pixels. The surface roughness is normally a measure of finer surface irregularity in the surface texture. These texture features extracted from the GLCM would be the best descriptors for quantifying the state of surface roughness (Septiadi and Nasution,2009). Hence, the GLCM texture analysis is performed using a window size of 9*9 pixels and the homogeneity or dissimilarity criterion is used to determine the surface roughness of the study area.

30 3.1.2 Hydrological Factors

Distance to hydrological features, rainfall, and TWI defined by Eq. (1) are selected as the hydrological factors for this landslide susceptibility analysis. Proximity to the hydrological features is an important factor when considering the landslide susceptible analyses (Sar et al., 2016, Shahabi and Hashim, 2015). TWI is a solid index that is capable of predicting areas susceptible to saturation or wetness of land surfaces, and the areas that have the potential to produce an overland flow. Within the Sri Lankan context, heavy and prolonged rainfall is the main triggering factor for the landslides. The monthly average rainfall data for the years 2014 to 2016 from 10 nearby stations to Koslanda were used in this study. Monthly rainfall data from 10 rain gauge stations are averaged, and the average rainfall map for the study area is generated using the Inverse Distance Weighting (IDW) interpolation method within the ArcGIS environment. TWI has been used to study the spatial scale effects, or topographic control, on hydrological processes. This index was developed by Beven and Kirkby, 1979 and can be defined in Eq. (1) as;

40

$$TWI = \ln[\alpha/\tan \beta] \quad (1)$$

where α is the local upslope area draining through a certain point per unit of contour length, and β is the gradient of the local slope in degrees. The applicability of the TWI in the calculation and validation of landslide susceptibility analysis has been shown by Kavzoglu et al., 2014 and Sørensen et al., 2006 among others.

5

3.1.3 Soil Factors

The Soil Moisture Index (SMI) defined in Eq. (2) and Delta Index defined in Eq. (5) are the soil factors focused upon in this research. Surface soil moisture is one of the most important parameters in land susceptibility analysis (Carlson et al., 1994, Zhan et al., 2002). Several methods have been proposed to estimate the surface soil moisture conditions accurately with insitu
 10 measurements. However, these methods are time consuming and costly when the area of interest is large, and the scale of work is small. Hence, this research uses the Universal Triangle relationship between Soil Moisture, Normalized Difference Vegetation Index (NDVI) and Land Surface Temperature (LST) derived from Landsat-8 image bands as an optical remote sensing approach, and the Delta Index derived from two radar images, as wet and dry conditions, as a radar remote sensing approach. Band 5 (Near Infrared (NIR), 30 m resolution), band 4 (Red, 30 m resolution) and band 11 (Thermal, TIR-2, 100 m
 15 resolution) of Landsat-8 image of 3rd July 2015 is processed for extracting the soil moisture index in the Thermal-NDVI space. The SMI is "0" along the dry edge and "1" along the wet edge. According to the studies from (Wang and Qu, 2009, Zenga et al., 2004), SMI can be defined in Eq. (2) as;

$$SMI = \frac{(T_{max} - T)}{(T_{max} - T_{min})} \quad (2)$$

20 where T_{max} , T_{min} are the maximum and minimum surface temperature for a given NDVI, and T is the remotely sensed derived surface temperature at a given pixel for a given NDVI. The simple regression relationship between T and NDVI is formulated in Eq. (3) and Eq. (4) as;

$$T_{max} = a_1 \cdot NDVI + b_1 \quad (3)$$

$$T_{min} = a_2 \cdot NDVI + b_2 \quad (4)$$

where, $a_1 = -5.2362$, $b_1 = 300.14$, $a_2 = 2.9254$, and $b_2 = 289.11$. Radar remote sensing provides advantages for extracting near surface soil moisture (0-5 cm), including timely coverage with repeat passes during day and night, under all weather
 25 conditions. Radar imagery from space can provide broad scale information on near surface soil moisture as radar signal return is responsive to changes in soil moisture. Technically, the surface roughness and vegetation affect radar backscatter much more than soil moisture. Hence, both the surface roughness and vegetation have to remain unchanged during the image acquisition for soil moisture estimation (Thoma et al., 2006). Delta Index is a modified, image differencing technique, and many studies (Barrett et al., 2009, Sano et al., 1998, Thoma et al., 2004) have proven it to be a good predictor for near surface
 30 soil moisture extraction. This index describes the change of wet scene backscatter relative to the dry scene backscatter, and is defined by Thoma et al., 2004 in Eq. (5) as;

$$Delta\ Index = \left| \frac{\sigma_{wet}^0 - \sigma_{dry}^0}{\sigma_{dry}^0} \right| \quad (5)$$

where, σ_{wet}^0 is the radar backscatter (decibels) from a pixel in the radar image representing wet soil conditions, and σ_{dry}^0 is the
 35 radar backscatter (decibels) from a pixel in the same geographic location representing dry soil conditions at a different time.

Sentinel-1 images with 10m spatial resolution and VV polarization is used in the presented study. The dry reference image was acquired on 12th March 2015 and the wet image was acquired on 24th November 2014 after the landslide in Meeriyabedda, Sri Lanka. Therefore, the topographical changes like roughness and vegetation density showed no significant changes during these four months' time.

5

3.1.4 Land Use

The major land uses existing in this study area are identified as tea, scrub, forest, rock, rice, water, and residential. The Sentinel-2A image from 10th October 2016 is used to extract the desired land uses from the study area by applying supervised classification. Scrub areas are typically the tea estates that are in abundance, while the residential areas are the rooms of tea workers. It is noted that most of the devastating landslides in this area had occurred within the extensive tea estates. Hence, the main reason for the continuous occurrence of these landslides can be identified as the lack of proper land use management in the area.

Forest biomass is a significant factor that can control the landmass failures or landslides. The main limitations of using optical remote sensing for forest biomass estimation is the near constant tropical cloud cover, and the insensitivity of reflectance to change of the biomass in older and mixed forests. Radar has potential to overcome the above limitations due to its all-weather, day and night capability, with the positive relationship of radar backscatter and forest biomass. The spatial, spectral, temporal, and polarization characteristics of radar backscatter has known influence with the forest biophysical properties. Kuplich et al., 2005 and Caicoya et al., 2016 related the radar image texture derived from GLCM to the forest biomass. An experiment was conducted by Kuplich et al., 2005 with seven texture measures, but only the GLCM derived contrast increased the correlation between the backscatter and the log of biomass in Eq. (6) as;

$$\text{Log of Biomass} = 2.24 + 0.33b + 0.0001c \quad (6)$$

where, b is the radar back scatter and the c are the GLCM contrast texture for the particular radar image. TerraSAR-X spot light image from 2nd November 2014, with 3 m resolution and dual polarization (HH and VV), was used to estimate the forest biomass in this research.

25

3.1.5 Geological Factors

Geology refers to the physical structure and the substance of the Earth. In order to investigate the land mass failures, the geological structure of that particular area have to be analysed carefully. In addition to the Geology of the area, lineament density has also been considered as a factor. The geological information of the particular area is obtained from the geological map available at the Geological Survey Mines Bureau (GSMB), Sri Lanka at 1:100,000 scale, and seven types of different geological structures are contained in the selected study region. Primarily the undifferentiated charnockitic biotite gneisses and Quartzites are prominent with Garnet-sillimanite and Garnetiferous quartzofeldspathic gneiss in the study area. Lineaments are extractable linear features which are correlated with the geological structures of the earth. When considering the analysis of lineaments with respect to the landslide potentiality, lineaments exhibit the zones of weakness surfaces as faults, fractures, and joints (Adiri, et al., 2017, Kati, et al., 2018, Mandal and Maiti, 2015). This study uses the Sentinel-2 optical satellite image, with 10 m resolution, for the extraction of lineaments of the study area.

35

3.2 Methodology

The InfoVal method determines the susceptibility at each point or pixel, jointly considering the weight of influence of all predisposing factors. The weight of influence is based on the landslide inventory map of the particular area. When constructing a probability model for landslide prediction, it is necessary to assume that the landslide occurrence is determined by landslide-related factors, and that future landslides will also occur under the same, or almost similar, conditions as past landslides (Remondo et al., 2013, Saha et al., 2005). Hence, at the beginning of the analysis, the landslide inventory map is divided into two samples as training and validation, enabling the use of this data for landslide susceptibility analysis and validation of results respectively as in Fig 2. Log function is used to control the large variation of weights in calculations. Larger the weight of influence, the stronger the relationship between landslide occurrence and the given factor's attribute.

FIGURE 2

This method overlays all individual predisposing factors as thematic maps with the landslide inventory map to calculate the density of the landslide detachment zones for each class of the selected factors. The density of landslide pixels represents the weight of influence of each predisposing factor in Eq. 7 as;

$$W_i = \text{Log} \left(\frac{\text{Densclass}}{\text{Densmap}} \right) = \text{Log} \left(\frac{N_{pix}(S_i)/N_{pix}(N_i)}{\sum_{i=1}^n N_{pix}(S_i)/\sum_{i=1}^n N_{pix}(N_i)} \right) \quad (7)$$

Where, W_i is the weight given to the parameter class, Densclass is the landslide density within the parameter class and Densmap is the landslide density within the entire map. $N_{pix}(S_i)$ is the number of landslide pixels within parameter class i , and $N_{pix}(N_i)$ is the total number of pixels in the same parameter class. It means that, if the parameter class contains no landslide occurrence, it will have no correlation with the landslide inventory map (Bui et al., 2011, Kavzoglu et al., 2015).

The MCDA method integrates all the independent predisposing factors with the inclusion of relative contribution of each factor by putting more emphasis on the predisposing factors that contribute to landslide occurrence. The same predisposing factors without or with radar, are used to investigate the landslide susceptibility regions from AHP technique within the GIS domain. In AHP, each pair of factors in a particular factor group is examined at one time, in terms of their relative importance. Relative weights for each factor are calculated based on a questionnaire survey from experts in the field. These relative weights are then used to generate a pair-wise comparison matrix which is the basic measurement mode when applying the AHP procedure. The selected predisposing factors, and relevant relative weights, are used to generate the normalized matrix with final average weights. However, expert knowledge could be subjective at times, or may cause to assign different weights for each factor, when dealing with a large number of causative factors. Hence, in order to avoid this inconsistency, Consistency Ratio (CR) is calculated. For better predictive models, the CR should be less than 0.01, else each factor has to be generated with the proper pairwise comparison.

The calculated final weights for twelve landslide predisposing factors without RDF as elevation, slope, aspect, planar curvature, profile curvature, TWI, land use, lineament density, distance to water bodies, soil moisture, geology, and rainfall were 0.030, 0.172, 0.022, 0.018, 0.014, 0.074, 0.149, 0.052, 0.045, 0.094, 0.185, and 0.145, respectively. The CR is 0.089, making it less than the 0.1, the value showed the reasonable level of consistency in the pairwise comparison. The final weights for fifteen predisposing factors with RDF as elevation, slope, aspect, planar curvature, profile curvature, TWI, land use, lineament density, distance to water bodies, SMI in NDVI-T domain, geology, rainfall, soil moisture (Delta index), surface

roughness, and forest biomass are 0.022, 0.145, 0.016, 0.013, 0.011, 0.053, 0.126, 0.039, 0.033, 0.065, 0.153, 0.124, 0.088, 0.088, and 0.027, respectively. When considering the fifteen predisposing factors, the CR is calculated as 0.092, which is less than the 0.1 thereby showed a realistic level of consistency in the pairwise comparison matrix.

5 After decisive analysis of the types of predisposing factors, the presented work proceeded to consider fifteen predisposing factors that are derived from optical, radar and other available auxiliary data sources. Three significant causative factors as surface roughness, soil moisture from Delta Index, and forest biomass were estimated by using radar satellite images. Thus, this work investigated the performance of landslide susceptibility analysis using bivariate and multivariate methods with the inclusion of RDF and described the processing steps in Fig.3.

10

The weight of influence of all predisposing factors as thematic maps are added in bivariate and multivariate nature to obtain the contribution of all predisposing factors for landslide susceptibility analysis. After calculating the cumulative percentage of failures of the weighted susceptibility maps, value ranges for each percentage of failure are obtained from quantile classification for 10 classes. The entire study area of each landslide susceptibility map is then discretized in to four classes as
15 0%, 10%, 30% and 60% of failure regions for very low, low, moderate, and high susceptibility classes, respectively.

FIGURE 3

4 Results

Four Landslide prediction models, (i) bivariate without RDF (BiNR), (ii) bivariate with RDF (BiWR), (iii) multivariate without
20 RDF (MNR), and (iv) multivariate with RDF(MWR) are discussed. The region has been analysed and classified into four (04) landslide susceptibility regions as; high, moderate, low, and very low.

4.1 Bivariate InfoVal method Without and With RDF

Susceptible regions are identified from the bivariate InfoVal method without RDF as 12% for high, 45% for moderate, 38%
25 for low, and 5% for very low as shown in Fig.4(a). Hence, 57% areas from the total study area are predicted as having high and moderate susceptibility for the landslide hazard. Very steep slope mountains in the North, North West, and East regions are identified as very low susceptibility areas, given that the area was free from historical landslides. The middle regions with 30⁰-50⁰slope are detected as having a high probability for landslide occurrences. The bivariate InfoVal method with RDF identified 19% of failure regions for high susceptibility, 39% for moderate, 33% for low, and 9% for very low susceptible
30 regions as presented in Fig.4(b). Therefore, 58% of the total study area is predicted as having high and moderate susceptibility for landslides. Very steep slope mountains in the North, North West, East, and South East regions, the area near the Eruwendumpola Oya, are identified as having very low susceptibility for landslides. Similar to the bivariate analysis without RDF, the middle regions with 30⁰-50⁰slope are detected as having high probability for landslide occurrences and the reason for this is mainly with the past experience from Naketiya and Meeriyabedda landslides that had taken place in the same area.

35

FIGURE 3

4.2 Multivariate MCDA based on AHP Without and With RDF

All fifteen weighted predisposing factors were grouped as without and with RDF, and weighted overlay is performed separately in order to obtain the landslide susceptibility regions.

5 Figure 4(c) illustrates the landslide susceptibility map from the multivariate method without RDF and is able to identify 18% for high, 44% for moderate, 36% for low and 2% for very low susceptible regions. Hence, 62% of areas from the total study area are predicted to be of high and moderate susceptibility for the landslide hazard. In the landslide susceptibility map from the multivariate method with RDF, from the total area, 21% of the area show a high susceptibility to landslides, with 40% of area as moderate, 34% area as low, and 5% of area as having very low susceptibility as shown in Fig.4(d). Hence, 61% of areas from the study area are predicted as having high and moderate susceptibility for the landslide hazard. In a similar manner to the InfoVal method, the top of the mountains in the North, North West, East, and South East regions, area near to the Eruwendumpola Oya, are identified as having a very low susceptibility to landslide hazards, while the middle regions with 30⁰-50⁰ slopes are detected as having high and moderate probability for landslide occurrences.

5 Discussions

15 The area identified as having high and moderate susceptibility classes in these four approaches (57%, 58%, 62%, and 61% respectively in BiNR, BiWR, MNR, and MWR) are close in value, but shows an increase in multivariate analysis when compared with bivariate analysis as tabulated in Table 1. Moderate and low landslide susceptibility areas show very small ((1-2)%) changes between these four types of analysis. With the integration of RDF as surface roughness, near surface soil moisture from Delta Index, and forest biomass in bivariate and multivariate analysis, the high and very low susceptible areas are increased significantly (high: 7% - bivariate, 3% - multivariate and very low: 4% - bivariate, 3% - multivariate). However, when comparing the high and very low susceptibility areas from bivariate and multivariate analysis, high susceptibility areas show a considerable increase (without radar: 6% and with radar: 2%) while, very low susceptibility areas have a noteworthy decrease (without radar: 3% and with radar: 4%).

TABLE 1

5.1 Results Validation

30 The landslide susceptibility maps derived from the bivariate and multivariate analysis are validated using the selected validation samples from the landslide failure map. The most commonly used and scientifically recognized Receiver Operating Characteristics (ROC) curves are used to analyse the prediction and validation performances. ROC is a graphical plot that illustrates the performance of classification, and is considered as a powerful tool for the validation of landslide susceptibility analysis for many years (Neuhäuser et al., 2012). The Area Under Curves (AUC) for the four different approaches, as bivariate and multivariate without and with RDF, are calculated and graphed in Fig.5.

FIGURE 4

35 The areas under the success rate curves measure how the landslide prediction analysis fit with the training data set, while the areas under the prediction rate curves measure how well the landslide prediction models and landslide causative factors predict

the landslides. If the area under the ROC curve is closer to 1, the result of the test is excellent and vice versa, and when AUC is closer to 0.5, the result of the test is fair or acceptable (Kamp et al., 2008).

The AUC of all the success rates are more-or-less near 0.80, indicating good prediction performances according to the definition. The AUC of all the prediction rates are having values above 0.50, thereby indicating that they are within the acceptable range as per the definition. As such, they indicate that the accuracy of prediction rate of land susceptibility and the selection of land causative factors are acceptable, but not excellent, even though the fit between the landslide prediction and the training data set are excellent as compared in Table 2. The incompleteness of the available landslide inventory map, as well as an insufficient number of validation samples in the study area can be shown as reasons for the discrepancy. As a whole, better prediction and validation capabilities are shown by the bivariate analysis when compared with the multivariate approaches.

TABLE 2

6 Conclusions

This study focused on the applicability of remote sensing and GIS for rapid landslide prediction analysis at finer scale. Further, by considering the significance of radar data for landslide analysis, this study mainly investigates the efficacy of radar derived factors for landslide prediction analysis which is not well experimented in the current researches. Most significant predisposing factors as surface roughness, soil moisture, and forest biomass derived from radar are incorporated to examine the landslide prediction analysis. The prediction analysis is performed by using bivariate and multivariate statistical analysis.

The main difference between bivariate and multivariate analysis is that in multivariate analysis, selected predisposing factors are weighted by considering, how each of them are influenced for landslide susceptibility. This study investigated fifteen landslide predisposing factors as elevation, slope, aspect, planar curvature, profile curvature, TWI, land use, lineament density, distance to hydrology, SMI in NDVI-T domain, geology, rainfall, soil moisture (Delta Index), surface roughness, and forest biomass. Most of the factors are derived from radar and optical remote sensing techniques, where smaller scale studies with up-to-date information allows the work to be conducted at the meter-level accuracy, and repeated analysis simultaneously.

From the results obtained, it can be concluded that the bivariate and multivariate statistical analysis, without and with RDF, can be used for landslide prediction analysis. However, with the integration of RDF as surface roughness, near surface soil moisture from Delta Index, and forest biomass, the detection of the boundary between the high and very low susceptibility regions is increased. When comparing the bivariate analysis with multivariate, the increase of high and very low susceptibility regions are high in bivariate than multivariate. In landslide prediction analysis, the most important susceptibility classes are high and very low classes, as they provide significant information about the danger from a disaster. Hence, with the integration of radar derived factors, by increasing the accuracy of prediction for high susceptibility regions, the possibility of mitigating dangers can be considerably improved. When the accuracy and prediction of very low susceptibility regions are increased, the use of such lands can be encouraged for residential, community places, and safe areas when a landslide occurs.

Successful prediction and validation of prediction analysis via ROC curves are achieved. Even though this study was tested for a sample area, the same methodology can be applied for any landslide prone area to investigate the landslide prediction analysis using radar derived factors by using bivariate and multivariate analysis. This is because the radar derived factors can be derived for any area, as long as the data are available, and at any time under whatever the weather conditions as radar are weather independent. Additionally, the technology can be learned easily and anyone can be trained to use this methodology to

predict landslide susceptibility areas, and this is especially helpful for developing countries who do not have up-to-date data at fine resolutions. With the increasing availability of free data in optical, radar, and DEM, it is possible to derive more landslide predisposing factors as thematic maps. Further, there are many statistical analyses developed in qualitative and quantitative natures for spatial data analysis. Hence, further investigations have to be performed for landslide susceptibility analysis even focusing the changing nature of the environments.

Team List

10 A.K.R.N. Ranasinghe
R. Bandara
U.G.A. Puswewala
T.L. Dammalage

Author Contribution

15 A.K.R.N. Ranasinghe performed the Conceptualization, Data curation, Formal analysis, Funding acquisition, Investigation, Methodology, Validation, Visualization, and Writing – original draft and R. Bandara accomplished the Supervision, and writing - review and editing. U.G.A. Puswewala and T.L. Dammalage executed the Supervision.

Competing Interests

20

The authors declare that we have no conflict of interest.

Acknowledgement

25 Authors wish to acknowledge the Sabaragamuwa University of Sri Lanka for offering an opportunity for this research and the HETC project, Ministry of Higher Education, Sri Lanka, for providing financial support under the grant number SUSL/O-Geo /N2 and the University of Siegen, Germany, for providing their support in collecting and initial processing of the TerraSAR-X images from DLR, Germany. The DLR, Germany, is remembered with appreciation for providing radar images for free of charge, and the GSMB, Sri Lanka for providing freely, the geological data necessary for this research work.

30

References

- Adiri, Z., Harti, A. E., Jellouli, A., Lhissou, R., Maacha, L., Azmi, M., Zouhair, M., and Bachaoui, E. M.: Comparison of Landsat-8, ASTER and Sentinel 1 satellite remote sensing data in automatic lineaments extraction: A case study of Sidi Flah-Bouskour inlier, Moroccan Anti Atlas, *Advances in Space Research*, 60, 2355-2367, 2017.
- 35 Ayalew, L., Yamagishi, H., and Ugawa, N.: Landslide susceptibility mapping using GIS-based weighted linear combination, the case in Tsugawa area of Agano River. *Niigata Prefecture, Japan, Landslides*, 1, 73-81, 2004.
- Baroň, I., Bečkovský, D., and Míča, L.: Application of infrared thermography for mapping open fractures in deep-seated rockslides and unstable cliffs, *Landslides*, 11, 15-27, 2014.
- Barrett, B. W., Dwyer, E., and Whelan, P.: Soil Moisture Retrieval from Active Spaceborne Microwave Observations: An Evaluation of Current Techniques, *Remote Sensing*, 1, 210-242, 10.3390/rs1030210, 2009.
- 40 Beven, K. J., and Kirkby, M. J.: A physically based, variable contributing area model of basin hydrology, *Hydrology*, 24, 43–69, 1979.
- Bui, D. T., Lofman, O., and Revhaug, I. D., O. : Landslide susceptibility analysis in the HoaBinh province of Vietnam using statistical index and logistic regression. , *Natural Hazards*, 59, 1413–1444, 2011.

- Caicoya, A. T., Kugler, F., Hajnsek, I., and Papathanassiou, K. P.: Large Scale Biomass Classification in Boreal Forests with TanDEM-X Data., *IEEE Transactions on Geoscience and Remote Sensing* 54, 5935-5951, 2016.
- Carlson, T., Gillies, R., and Perry, E.: A method to Make use of Thermal Infrared Temperature and NDVI Measurements to Infer Surface Soil Water Content and Fractional Vegetation Cover. , *Remote Sensing Review* 9, 161-173, 1994.
- 5 Chae, B. G.; Park, H. J.; Catani, F.; Simoni, A.; Berti, M.: Landslide Prediction, monitoring, and early warning: a concise review of state-of-the-art. In *Journal of Geosciences*, 21(6), pp 1033-1070, 2017.
- Chalkias, C., Ferentinou, M., and Polykretis, C.: GIS-Based Landslide Susceptibility Mapping on the Peloponnese Peninsula, Greece, *Geosciences*, 4, 176-190, 2014.
- 10 Corominas, J., van Westen, C., Frattini, P., Cascini, L., Malet, J. P., and Fotopoulou, S.: Recommendations for the quantitative analysis of landslide risk, *Engineering Geology and the Environment*, 73, 209-263, 2014.
- Jakob, M., Holm, K., Lango, O., and Schwab, J.: Hydrometeorological threshold for landslide initiation and forest operation shutdowns on the north coast of British Columbia, *Landslides*, 03, 228-238, 2006.
- Kamp, U., Growley, B. J., Khattak, G. A., and Owen, L. A.: GIS-based landslide susceptibility mapping for the 2005 Kashmir earthquake region, *Geomorphology* 101, 631–642, 2008.
- 15 Kanungo, D. P., Arora, M. K., Sarkar, S., and Gupta, R. P.: Landslide susceptibility zonation (LSZ) mapping, *Journal of South Asia Disaster Studies*, *Journal of South Asia Disaster Studies*, 2, 81-105, 2009.
- Kati, I. E., Nakhcha, C., Bakhchouch, O. E., and Tabyaoui, H.: Application of ASTER and Sentinel 2-A images for geological mapping in arid regions: the Safsafate Area in the Neogen Guercif basin, Northern Morocco, *International Journal of Remote Sensing and GIS*, 7(1), 2782-2792, 2018.
- 20 Kavzoglu, T., Sahin, E. K., and Colkesen, I.: Landslide susceptibility mapping using GIS-based multi-criteria decision analysis, support vector machines, and logistic regression, *Landslides*, 11, 425-439, 2014.
- Kavzoglu, T., Sahin, E. K., and Colkesen, I.: An assessment of multivariate and bivariate approaches in landslide susceptibility mapping: a case study of Duzkoy district, *Natural Hazards*, 76, 471–496, 10.1007/s11069-014-1506-8, 2015.
- 25 Kseneman, M., Gleich, D., and Potočnik, B.: Soil-moisture estimation from TerraSAR-X data using neural networks, *Machine Vision and Applications* 23, 937–952, 10.1007/s00138-011-0375-3, 2012.
- Kuplich, T. M., Curran, P. J., and Atkinson, P. M.: Relating SAR image texture to the biomass of regenerating tropical forests, *International Journal of Remote Sensing* 26, 4829-4854, 2005.
- Lan, H. X., Zhou, C. H., Wang, L. J., Zhang, H. Y., and Li, R. H.: Landslide hazard spatial analysis and prediction using GIS in the Xiaojiang watershed, Yunnan, China, *Engineering Geology* 76, 109–128, 2004.
- 30 Lee, S., Hong, S. M., and Jung, H. S.: A Support Vector Machine for Landslide Susceptibility Mapping in Gangwon Province, Korea, *Journal of Sustainability* 9, 10.3390/su9010048, 2017.
- Mandal, S., and Maiti, R.: Geo-spatial Variability of Physiographic Parameters and Landslide Potentiality, in: *Semi-quantitative Approaches for Landslide Assessment and Prediction*, 1 ed., Springer Singapore, 2015.
- 35 Martha, T.: Detection of landslides by object - oriented image analysis, PhD, Faculty of Geo-Information and Earth Observation, University of Twente, The Netherlands, 187 pp., 2011.
- Muthu, K., Petrou, M., Tarantino, C., and Blonda, P.: Landslide possibility mapping using fuzzy approaches, *IEEE Transactions on Geoscience and Remote Sensing*, 46, 1253-1265, 2008.
- NBRO (National Building Research Organization),Landslide Research and Risk Management Division, Ministry of Disaster management, Sri Lanka,<http://www.nbro.gov.lk>, access: May 08, 2016.
- 40 Neuhäuser, B., Damm, B., and Terhorst, B.: GIS-based assessment of landslide susceptibility on the base of the weights-of-evidence model, *Landslides*, 9, 511–528, 2012.
- EM-DAT, International Disaster Database. - University of Catholique de Louvain, Brussels, Belgium: <http://www.em-dat.net>, access: May 04, 2016.
- 45 Park, S., Choi, C., Kim, B., and Kim, J.: Landslide susceptibility mapping using frequency ratio, analytic hierarchy process, logistic regression, and artificial neural network methods at the Inje area, Korea, *Environmental Earth Sciences*, 68, 1443-1464, 2013.
- Pastonchi, L.; Barra, A.; Monserrat, O.; Luzi, G.; Solari, L.; Tofani, V.: Satellite Data to Improve the Knowledge of Geohazards in World Heritage Sites. In *journal of Remote Sensing*10, DOI:10.3390/rs10070992, 2018.
- 50 Reis, S., Yalcin, A., Atasoy, M., Nisanci, R., Bayrak, T., Erduran, M., Sancar, C., and Ekercin, S.: Remote sensing and GIS-based landslide susceptibility mapping using frequency ratio and analytical hierarchy methods in Rize province (NE Turkey), *Environmental Earth Sciences*, 66, 2063–2073, 2012.

- Remondo, J., Gonz'alez-D'iez, A., D'iaz de Ter'an, J. R., Cendrero, A., Fabbri, A., and Chung, C. F.: Validation of landslide susceptibility maps; examples and applications from a case study in Northern Spain, *Natural Hazards*, 30, 437–449, 2013.
- Saaty, T. L.: *The analytic hierarchy process*, McGraw-Hill, New York, 1980.
- 5 Saha, A. K., Gupta, R. P., Sarkar, I., Arora, M. K., and Csaplovics, E.: An approach for GIS-based statistical landslide susceptibility zonation – with a case study in the Himalayas, *Landslides*, 2, 61-69, 2005.
- Sano, E. E., Huete, A. R., Troufleau, D., Moran, M. S., and Vidal, A.: Relation between ERS-1 Synthetic Aperture Radar data and Measurements of Surface Roughness and Moisture Content of Rocky Soils in a semiarid rangeland, In *Water Resource Research* 34, 1491-1498, 1998.
- 10 Sar, N., Khan, A., Chatterjee, S., Das, A., and Mipun, B. S.: Coupling of analytical hierarchy process and frequency ratio based spatial prediction of soil erosion susceptibility in Keleghari river basin, India, *International Soil and Water Conservation Research*, 2016.
- Shahabi, H., and Hashim, M.: Landslide susceptibility mapping using GIS based statistical models and Remote sensing data in tropical environment, *Scientific Reports*, 5, 9899, 10.1038/srep09899, 2015.
- 15 Challenges to Overcome: An Overview of Koslanda Landslide: <http://www.gsslweb.org/challenges-to-overcome-an-overview-of-koslanda-landslide/>, access: February 10, 2016.
- Rahman, M. M.; Moran, M. S.; Thoma, D. P.; Bryant, R.; Holifield-Colins, C. D.; Jackson, T.: Mapping Surface Roughness and Soil Moisture using Multi-angular radar imagery without ancillary data. In *Remote Sensing of Environment* 112, pp 391-402, 2008.
- 20 Septiadi, D.; Nasution, A. M. T.: Determine Surface Roughness Level Based on Texture Analysis. ICACSI-09. University of Indonesia, Jakarta, Indonesia, 7 - 8 December. International Conference on Advanced Computer Science and Information Systems, 2009.
- Somarathne, M.: Challenges to Overcome: An Overview of Koslanda Landslide. Geological Society of Sri Lanka. Available online at <http://www.gsslweb.org/challenges-to-overcome-an-overview-of-koslanda-landslide/>, access: February 15, 2016.
- 25 Sørensen, R., U. Zinko, U., and Seibert, J.: On the calculation of the topographic wetness index: evaluation of different methods based on field observations, *Hydrology and Earth System Sciences* 10, 101–112, 2006.
- Thoma, D., Moran, M., Bryant, R., Holifield-Colins, C., Rahman, M., and Skirvin, S.: Comparison of Two Methods for Extracting Surface Soil Moisture from C-band Radar Imagery, *IEEE Transactions on Geoscience and Remote Sensing* 4, 827-830, 2004.
- 30 Thoma, D. P., Moran, M. S., Bryant, R., Rahman, M., and Holifield-Colins, C. D.: Comparison of four models to determine surface soil moisture from C-band radar imagery in a sparsely vegetated semiarid landscape, *Water Resource Research* 42, W01418, 10.1029/2004WR003905, 2006.
- van Westen, C. J.: Statistical landslide hazard analysis. In: *Application guide, ILWIS 2.1 for Windows*, ITC, Enschede, The Netherlands, pp 73-84, 1997.
- van Westen, C. J., and Getahun, F. L.: Analysing the evolution of the Tessina Landslide using aerial photographs and digital elevation models, *Geomorphology*, 54, 77-89, 2003.
- 35 van Westen, C. J., Rengers, N., and Soeters, R.: Use of geomorphological information in indirect landslide susceptibility assessment, *Natural Hazards* 30, 399–419, 2003.
- Wang, L., and Qu, J. J.: Satellite Remote Sensing applications for Surface Soil Moisture Monitoring: A review, *Frontiers of Earth Science in China*, 3, 237–247, 10.1007/s11707-009-0023-7, 2009.
- 40 Zenga, Y., Fengb, Z., and Xiang, N.: Assessment of soil moisture using Landsat ETM+ temperature/vegetation index in semiarid environment, *Geoscience and Remote Sensing Symposium, IGARSS '04*, Anchorage, AK, 4306-4309, 2004.
- Zhan, X.; Miller, S.; Chauhan, N.; Di, L.; Ardanuy, P.; Running, S.: *Soil Moisture Visible/Infrared Imager/Radiometer Suite Algorithm Theoretical Basis Document. Version 5*, 2002.




Figure 1 :Topographical formation of Koslanda, Sri Lanka with its previous Landslides Signatures



5

Figure 2 : Landslide failure map of the Koslanda area with two different training and validating samples







Figure 3 : Methodological flow of the Landslide susceptibility analysis using Bivariate and Multivariate approaches




(a)



(b)



(c)



(d)

Figure 4 : Landslide susceptibility maps from bivariate and multivariate analysis without and with RDF. (a)- bivariate without RDF, (b)- bivariate with RDF, (c)- multivariate without RDF, and (d)- multivariate with RDF




Figure 5 : Success rate and Prediction rate curves with AUC for the bivariate and multivariate analysis without and with RDF. X axis denotes the Cumulative percentage of Susceptibility regions and Y axis denotes the Cumulative percentage of training samples. From left to right and top to bottom BiNR- bivariate analysis without RDF, BiWR- with RDF, and MNR- multivariate analysis without RDF, and MWR- with RDF

5

5 **Table 1: Landslide susceptible area comparison from bivariate and multivariate analysis without and with RDF, BiNR -Bivariate analysis without RDF, BiWR -Bivariate analysis with RDF, MNR -Multivariate analysis without RDF, MWR -Multivariate analysis with RDF**

	BiNR	BiWR	MNR	MWR
High	12%	19%	18%	21%
Moderate	45%	39%	44%	40%
Low	38%	33%	36%	34%
Very Low	05%	09%	02%	05%

10

Table 2 : Comparison of area under Success rate and Prediction rate curves for bivariate analysis without RDF (BiNR), with RDF (BiWR), and multivariate analysis without RDF (MNR), and without RDF (MWR).

AUC	BiNR	BiWR	MNR	MWR
Success rate	0.8315	0.8560	0.7986	0.8023
Prediction rate	0.6692	0.6804	0.5882	0.5901