

# ***Interactive comment on “Analysis of instability conditions and failure mode of a special type of translational landslide using a long-period monitoring data: a case study of the Wobaoshi landslide (Bazhong city, China)” by Yimin Liu et al.***

**Felix Darve**

felix.darve@grenoble-inp.fr

Received and published: 24 July 2019

NHESS discussion on paper by Y. Liu, C. Wang, G. Gao, P. Wang, Z. Hou, Q. Jiao

The Authors discuss in their paper devoted to instability conditions and failure mode of a translational landslide – a case study, whose main interest lies on its careful long term monitoring. The characteristics of this landslide are remarkably described and these results will certainly constitute a very valuable data bank for future studies. Moreover the basic mechanical analysis of the related boundary value prob-

[Printer-friendly version](#)

[Discussion paper](#)



lem has been conducted in a very convincing manner and the failure mechanism is clearly exhibited. So all the ingredients have been collected to form a perfect basis for the modelling. Let us insist here on the fact that a numerical or analytical mechanical model of natural hazards - to be fruitful - has to take into account as properly as possible the discriminant or critical features, exhibited by preliminary geological/mechanical/pluviometric analyses. These analyses have to be based on a well designed monitoring campaign and the issueing data bank. This is clearly the case here and the Authors have to be congratulated for having achieved that – particularly the correlation between rainfall intensity and block motion.

So what is interesting to be discussed now is the choice of the modelling strategy. The analytical model is based on limit equilibrium method, whose limits have to be recalled: - this is a purely static method, - it ignores the influence of strain history, while it is well recognised that soils present an important hardening regime involving large plastic strains before failure, - a coulombian friction is taken into account, while the soil can fail before reaching Mohr-Coulomb plastic limit condition according to the second order work criterion, which is a more general material instability criterion. This is particularly important here, since the sliding surface has a very low slope angle of 6-8 degrees. Thus the instabilities are certainly appearing before Mohr-Coulomb criterion. - the hydro-mechanical constitutive relation of the sliding zone, which plays here a central role, can not be taken into account.

Having in mind these drastic limits, the reader is waiting for a deeper and more realistic finite element computation. However the finite element modelling is presented with very few details. According to the values of parameters as given on table 4, it seems that all involved geomaterials ( rocks and soils) have been considered as associate plastic materials. Thus their dilatancy angle is assumed to be equal to their friction angle, what is clearly not verified experimentally. Let us note that the constitutive elasto-plastic matrix is symmetric for associate materials, preventing to describe all instabilities and bifurcations occurring before the Mohr-Coulomb plastic limit surface. This is probably the

[Printer-friendly version](#)[Discussion paper](#)

reason why it has been necessary to choose a so low friction angle of  $11.2^\circ$  for clay – what seems unrealistic.

---

Interactive comment on Nat. Hazards Earth Syst. Sci. Discuss., <https://doi.org/10.5194/nhess-2019-133>, 2019.

[Printer-friendly version](#)

[Discussion paper](#)

