

Interactive comment on “La Palma landslide tsunami: computation of the tsunami source with a calibrated multi-fluid Navier–Stokes model and wave impact assessment with propagation models of different types” by Stéphane Abadie et al.

Stéphane Abadie et al.

stephane.abadie@univ-pau.fr

Received and published: 10 February 2020

Authors' responses:

The comments of the first reviewer concerned five main points listed below:

1. Slide and wave generation results: The requested snapshots showing quantitative (slide plan view and thickness evolution with time) and therefore reproducible results on the slide and the wave generation are now provided in Figure 8. (Note that run-out contours are not included because the slide is still flowing at the time the Navier–

C1

Stokes simulation is stopped. Nevertheless, the figure provided fully covers the energetic transfer from slide to free surface). In addition to the existing SEANOE repository (DOI 10.17882/61301) which contains wave data for the source, we have also added a directory with the necessary information for interested readers to be able to perform their own simulations with the same initial conditions as the current paper.

2. Dispersive effects: We agree with the remarks of this reviewer on the role of dispersive effects. Therefore, the Boussinesq model FUNWAVE-TVD used for propagation is now presented as the reference model as it is the only one taking dispersive effects into account from the source to the coast. Only results obtained with this model are presented in the results section to provide quantitative information on the tsunami features on the selected gauges for this case. The other models are now presented in a specific section entitled “other models used” with the only objective to compare with the reference model and between each other.

3. Presentation of the propagation models: Equations have been removed, information on model resolution, coordinate type (spherical, Cartesian), Manning coefficient distribution, wetting-drying algorithms schemes at the shore, and breaking wave modeling is now provided. Purpose of the comparison is also clarified.

4. Wave impact and run-up: In La Guadeloupe, new SCHISM computations have been performed using FUNWAVE-TVD results off the island as an input signal (hotstart) as suggested by the reviewer. Maximum flow depth calculations at isobath -5 m are also presented for three areas along the French Atlantic coastline covered with fine grids. This calculation is based on the Boussinesq version of the Calypso code for propagation and shallow water version for inundation. We showed in the paper that the results obtained with this nested model agrees very well with FUNWAVE-TVD results.

Nevertheless, maximum run-up and flow velocity using the formula given by Madsen and Fuhrman (2008) are still provided but only as an additional tool to help the reader make a quick assessment of tsunami hazard where flow depth is not provided or true

C2

inundation is not calculated.

5. Miscellaneous (typos, figure quality, references, English): The remarks from the reviewer have been taken into account.

Responses to specific comments and related text changes are indicated below.

Review comments: (specific responses from the authors in bold characters)

In introduction, the paper lists some earlier work on CVV tsunami modeling and far-field impact but does not really quantitatively summarize all the important findings. Some references also are missing, for instance Grilli et al. (2016).

Response : This part has been modified accordingly, and references added.

In introduction, the paper should better discuss why various propagation models are used to simulate the same cases (for instance to assess epistemic uncertainty). It seems that models were used only based on their availability or the experience within a certain group and not because they really featured the necessary physics.

Response : Done - see first paragraph section "Other models used".

As early as Løvholt et al. (2008), it was made clear that CVV collapses generate highly dispersive wavetrains. This was also reported in the far-field by Tehranirad et al. (2015). Here, both dispersive and non-dispersive models are used and although some of the results presented (particularly in and around Guadeloupe) clearly show significant dispersive effects that in a standard way reduce the leading wave elevation and enhance that of the second and/or third waves and then shed a larger tail of oscillation, the conclusion is more or less that all models are acceptable to simulate this event, as this were a forgone conclusion ?

Response : See new results and conclusions on dispersive effects in section 3.3, 3.4, 4 and 5.

C3

Also, the conclusions wrongly imply that dispersive effects only express themselves early in the event, during the THETIS and FUNWAVE near-field simulations which are both dispersive, and hence it is fine using a non-dispersive model for the transoceanic propagation. This contrary to established effects of dispersion, which a train of short enough waves, will go growing with time and distance. See for instance the discussion and dispersion indicators (which could be computed here) detailed in Glimsdal et al. (2013), and also applied in Schambach et al (2019) for landslide tsunamis. In this reviewer's opinion, the results presented here would lead to conclude using TELEMAC-2D or SCHISM for anything other than the nearshore inundation should be ruled out. See for instance Grilli et al. (2016) for which the transoceanic propagation of the CVV tsunami was done with FUNWAVE and the local impact on Hispaniola was computed with TELEMAC-2D in an unstructured grid.

Response : In the new manuscript, the effect of dispersive effect is acknowledged and illustrated for instance in Figure 21. As well, this sentence has been added to the conclusion: "After 15 minutes of propagation in a Boussinesq model, the wave signal is still dispersive and therefore Boussinesq models should be recommended to use the source provided."

Here the authors present new, more realistic, CVV sources, but the comparison between the old sources and the new ones is quite limited. More details would be desirable for both the wave generation and the slide. To begin with, the initial topography and geometry used for each source (both old and new ones and all the considered volumes), such as shown in Fig. 1, should be better described (is it fully available on some data storage site ?).

Response : In addition to the existing SEANOE repository (DOI 10.17882/61301) which contains wave data for the source, we have added a directory with the necessary information for interested readers to be able to perform their own simulations with the same initial conditions as the current paper.

C4

Then, it would be desirable to clearly show stages of the slide development underwater, for the old inviscid source and the new ones. In this respect, Figs. 8 and 9 are hard to get any information from. Having both comparative cross section and planview of slide flow and runout as a function of time would be desirable. For the generated tsunami, only Fig. 10 shows some measure of comparison but there as well more comparison allowing the reader to understand the nature of the tsunami source and how it is affected by viscosity would be helpful. P5 l8, it is mentioned the landslide continues to move for a very long time as in Abadie et al (2012) but this should be illustrated in a figure.

Response : See Figure 8 and associated text.

There is no real review of other models that have been used for simulating subaerial or submarine landslide tsunamis, for dense fluid or granular mediums. I suggest for instance to refer to and at least briefly discuss models of Horrillo et al. (2013), Ma et al. (2015) and Kirby et al. (2016) and Løvholt et al. (2017). See also the recent application of the Ma et al. and Kirby et al. models to a volcanic collapse tsunami in Grilli et al. (2019).

Response : Review added in the third paragraph of section 2.1.

Model grids are not clearly enough defined. Better (more readable, less dark) figures of grids on a global map, plus some regional zoom outs, and tables of parameters are required.

Response : Better and lighter figures with label grids, and a table with grids parameters were added.

Lines 22-29 p 5 are too implicit. For instance, for SCHISM it is said that “the resolution is adapted to accurately reproduce wavetrains of 2 minutes or more with at least 20 nodes per wavelength in deep ocean”. Is this applicable to all 4 models ? How was this decided about ? Please explicitly explain models and grid used and how.

C5

Response : Done – see section “other models used”.

L32 p5, saying all models use the same basic equations is meaningless. Please specify common physical assumptions and differences among models. Listing eqs. for 3 out of 4 of the models without background is meaningless. Equations are not necessary here but model physics, features and limitations are. If the authors do want to list eqs., they should do it for all models and in appendix.

Response : As already mentioned, the presentation of the model has been modified in this new version. Equations have been removed and main differences between models clarified.

The end of section 2.3 would be a good discuss anticipated dispersive effects based on earlier work on landslide tsunamis and on CVV. Regarding Calypso, saying that it switches between NSW and Boussinesq equations if “the area of simulation shows dispersive effects” is not sufficient. Please explain how this is done (on the basis of which criterion).

Response : Done – see section 2.2.2 “other models used”.

For Telemac-2D and SCISM, eqs. Are given but it is not clear how these are expressed in spherical coordinates (which is necessary for transoceanic propagation).

Response : This aspect is clarified - see section “Other models used”.

More details of the $\mu(I)$ rheology should be added (e.g., top of p4) as many readers may not be familiar with it. Also, the use of $\mu(I)$ appears more as an afterthought and it should be clearly said from the onset that 2 rheologies (Newtonian and $\mu(I)$) were simulated for each source (say on p3 line 23).

Response : Done – see section 2.1 “Navier-Stokes simulation of wave source”.

Section 2.5 should be more about “Tsunami impact (or hazard) assessment”.

Response : Risk replaced by hazard as suggested.

C6

Hazard can be expressed as a function of runup, but also flow depth (maximum surface elevation), velocity, momentum force, etc. . . Regarding runup, the use of the analytical solution for a plane slope in areas of coarse grid seems far-fetched. As stated later in the paper, focusing-defocusing and friction effects, will dramatically change the runup estimated this way. I suggest eliminating this part entirely from the paper as it seems to this reviewer to bias the tsunami hazard assessment for CVV. Uniformly computing and comparing flow depth for some isobath (even at the shore) would be more meaningful.

Response : Flow depths at isobath -5m has been computed at three locations along the French Atlantic coastline. See Figure 25.

Regarding friction, if this adjusted as a function of land use for some areas (e.g., Guadeloupe), this should be documented in the paper with a map of land use and a table of corresponding friction coefficient.

Response : New figure provided (a table would be too large to be provided).

About slide results, l14 p10, as these are discussed in the text, slide cross- and along - sections should be provided in figures, plus runout contours for the various rheology cases so they can be compared.

Response : See the new Figure 8.

Sentence on l24 p10 is fully implicit. Instead, one should explicitly discuss slide results and related wave generation, for each scenario, and then point out that wave elevations significantly vary, etc. . .

Note the $t=5$ min (300s) is not a case in Fig. 11.

Other figs are needed as discussed before.

Response : All the information requested by the reviewer has been summarized in the new Figure 8.

Saying l18 that MSL drastically lowers in the inviscid case as compared to the present

C7

viscous cases should be shown on a figure.

Response : This is now fully observable on the new Figure 8.

Fig. 12 (which by the way is highly distorted ? - Response : wrong figure aspect ratio fixed.

shown in filter could be discussed in previous section when explicitly presenting results for slide and waves for each volume scenario.

Response : The authors decided not to explicitly present and discuss all the different slide scenarios but rather discuss them implicitly as the paper has already many figures, and snapshots would show very similar pattern but of lower amplitudes (which is indicated in the text).

L10 p11, again an example of an important discussion that should both be explicit and expanded. Say that Fig. 14 clearly shows well developed wavetrains is illustrative of the high dispersive effects.

Response : Dispersive effect is fully acknowledged and discussed in this new version.

Some results cannot really be seen on some figures which are poor in terms of color shade/scheme, brightness, etc.. Fig. 15 for instance does not allow seeing some "waves" (or amplitudes ? or surface elevations ?) are larger than 5 m as stated L20 p11.

Response : Done.

Fig. 17 is another one with poor color scheme. Also make sure that all the names of localities listed L25-31 p11 are marked on the figure in a visible manner (most are in Fig. 6), with a separate table providing their geographic coordinates. Table 1 caption is not explicit as of where gauges 1-6 are and what they are; it seems to be stations n Fig. 7, but then caption for each table/figure should refer to the other one.

Response : New figure has been provided.

C8

L6-7 p 12 not only is a weak discussion regarding the SCHISM-FUNWAVE comparison in Fig 19 but is not quite right based on results. Here is a case where dispersive effects for long distance propagation of an initially identical train of (quite dispersive waves) are very well illustrated with dispersion causing a marked redistribution of the elevation/energy of the leading wave onto the 2nd and/or 3rd-4th waves. SCISM likely has some numerical dispersion that causes high frequency oscillations in the tail of the wavetrain compared to FUNWAVE. An energy spectrum would also be useful here in comparing where energy is located as a function of frequency.

Response : Fourier transforms are now provided for almost every gauge and used for discussion of dispersive effects.

Differences between model results in the tail also results from different wetting-drying algorithms schemes at the shore and dissipation in breaking waves that may cause vastly different reflected wave trains that interact with the incident wavetrain in the tail. FUNWAVE-TVD in particular features an improved shoreline algorithm following results of a benchmarking workshop. What is the status of the 3 other models in this respect ? None of this is properly discussed anywhere in the paper.

Response : See new section other model used regarding these questions.

In any case, this reviewer's opinion is that results in Fig. 19 show SCHISM is not applicable (or an appropriate) model for the transoceanic propagation of CVV wavetrains. Other results shown later confirm this opinion. A more adequate modeling, if SCHISM needs to be used nearshore, would have been to nest a SCHISM grid (around Guadeloupe or similar), within the ocean basin grid in which waves would have been simulated using a dispersive model.

Response : Done: tsunami hazard assessment in Guadeloupe is now performed by SCHISM using FUNWAVE-TVD as a hotstart.

Likewise, with Telemac-2D, which is non-dispersive, it is fully expected to see large dis-

C9

crepancies (as mentioned in L20 p12) of results with those of Calypso and FUNWAVE-TVD) in Figs. 21-24. Clearly the same conclusion as for SCISM applies to Telemac-2D, which should only be used in a nearshore nested domain to compute onshore inundation, but is not appropriate for the long distance propagation of dispersive wavetrains.

Response : The use of NSW models for propagation is now clearly justified as a benchmarking exercise to quantify the respective effect of dispersion and resolution, as further specified in the conclusions.

Statement in L26-28 p 12 is not apparent to this reviewer, unlike stated in the text. Be more explicit or use better support. L29- discussion of gauge 3; as indicated before, model results are also influenced by differences and implementation of breaking dissipation and wetting-drying shoreline algorithms (affecting reflection), and also open boundary conditions/sponge layers if any (not discussed here) that, if insufficient) may reflect some waves back into the domain.

L1-2 p13 is another case where a Fourier transform would help clarifying results and their interpretation.

Response : Done.

In section 3.4, the runup discussion includes many coarse grid areas where comparing flow depth at the shore would have been sufficient. This reviewer's believes the analytical runup computation and discussion in 3.4.1 does not really apply or is useful here. I suggest removing section 3.4.1. Another argument in support of the latter is statement on L9 p14 that the analytical formula overpredicts results due to lack of friction that "drastically influence(s) inundation patterns".

Response : As already indicated, maximum run-up and flow velocity formula given by Madsen and Fuhrman (2008) are still provided, but only as an additional tool to help the reader make a quick assessment of tsunami hazard where flow depth is not provided, or where actual inundation is not calculated.

C10

L12-13 p14, this work is tsunami hazard assessment not risk. The paper uses those terms alternately as if they were synonymous. They are not.

Response : Done.

L24 p14. How can the extreme 450 km³ scenario be entirely ruled out by a simple statement and how is 80 km³ more believable. Day (personal communication) still thinks this is a potential collapse scenario should a large enough earthquake/eruption affect the island.

Response : We agree that this scenario cannot be ruled out. See the new section of remarks in the discussion.

L5-25 p15, clearly for reasons of their own and certainly not based on results, the authors are trying to claim that all 4 models have equal skills in predicting the far-field impact of the CFF tsunami. This is clearly not the case and this discussion is quite moot. For this reviewer it is clear from results that SCHISM and Telemac 2D are not proper model to compute the propagation of the CVV tsunamis (eg see Figs 19, 21-24).

response : See corresponding new text in the discussion.

Differences between model results are not only due to resolution (L12 p15), but besides dispersive physics, also to the shoreline and breaking algorithms. I strongly disagree with the discussion of L20-23 p15 and conclusions of L13-15 p16 and L16-20 (see Figs. 19, 21-24). These conclusions are misleading and should not be a recommendation for the modeling community to adopt.

Response : Recommendations and conclusions changed in the new version.

Also, please compute the dispersion index of Glimsdal et al (2013) and see for yourself.

Response : See discussion on wave frequencies present in the spectrum after 15 min. of propagation in Section 3.3: "Propagation : FUNWAVE-TVD Results".

Editorial comments Inconsistency of terminology in the text to refer to surface elevation,

C11

such as wave, wave amplitude, height, tsunami amplitude, etc. . . I suggest using surface (or maximum surface) elevation in the ocean up to the coast, then flow depth at the coast, and runup onshore. It should be also clearly defined what hazard and risk (i.e., exposure to hazard) mean and that these terms are not interchangeable. Use of a term indicating return period should be uniform. The paper uses frequency or probability or probable or more frequent, source, etc. . . This reviewer suggest long or short return period events.

response : Done whenever possible.

There are many acronyms in the text, some of these not defined (e.g., SHOM). They should all be defined the first time they are used and I suggest adding a "table of acronyms" at the end. Note, accepted acronym for Nonlinear Shallow Water eqs. Is usually NSW.

Response : All the NLSW acronyms have been replaced by NSW. All the acronyms are now clearly defined.

Figures have inconsistent format and color schemes and also some are difficult too read (i.e., very dark color scheme etc..). This is likely due to different modelers producing different figures with different software but it would really be important to improve the figures as they report the key findings of the work. Using a single software and color scheme to produce figures would be important.

Response : Done whenever possible.

There are some improper use in the text of English words and grammar that would warrant a final editing by a native speaker.

Response : Revised manuscript checked by a native speaker.

Some rewordings are suggested below.

Fig. 3 caption, please replace eta by mu.

C12

response : Done.

Figs. 4 and 5 (and also Fig. 6,7): use brighter more discriminant color scheme, also show a measure of bathymetry (contours). Label grids and give a table with grid characteristics.

Response : The maps have been redrawn (Figures 4, 5 and 6-new) with a different software, and a table with grid characteristics has been added. Figure 6-old has been deleted, and the gauges that it indicated have been added to Figures 4 and 5.

Figs 8-9 are more qualitative than quantitative. Actual cross-sections (vertical and horizontal) should be shown with a metric scale. Color scheme in Figs. 10-14 should also be used in following figures showing surface elevation rather than the red-pink/blue or blue/gray schemes.

Response : As suggested, color schemes in Figures 15-new and 19-new have been adapted from color scheme in Figures 10-14-old.

Also, in general, color scheme should be selected to make figures more readable in terms of having nicely spread out colors which does not occur in most figures which are based on the maximum value.

Fig. 17 is a good example of this where one can't really see much of the tsunami elevation as the scheme goes to too high a maximum. Fig 17 is another example of a difficult to read color scheme in the low values

Response : Done.

Figs. 18,19: make figure more readable by removing the first 5h or so where nothing happens, and moving legend to caption.

Response : Done.

This is the case in Fig. 15 where colors should be selected based on making the far-field impact more visible rather than having it in more or less a uniform color. Panel on

C13

the left is unreadable in this respect.

Response : Done.

Caption of Fig. 15 says 2.7 km resolution. Aren't these spherical coordinate grids for transoceanic propagation. This is not clear since grids are not clearly defined

Response : Information on coordinate system added in the model section.

Additional references Glimsdal, S., Pedersen, G. K., Harbitz, C. B., & Løvholt, F. (2013). Dispersion of tsunamis: Does it really matter? *Natural Hazards and Earth System Sciences*, 13, 1507–1526. <https://doi.org/10.5194/nhess-13-1507-2013>. Grilli, S.T., Grilli A.R., David, E. and C. Coulet 2016. Tsunami Hazard Assessment along the North Shore of Hispaniola from far- and near-field Atlantic sources. *Natural Hazards*, 82(2), 777-810, doi: 10.1007/s11069-016-2218-z Grilli S.T., D.R. Tappin, S. Carey, S.F.L. Watt, S.N. Ward, A.R. Grilli, S.L. Engwell, C. Zhang, J.T. Kirby, L. Schambach and M. Muin 2019. Modelling of the tsunami from the December 22, 2018 lateral collapse of Anak Krakatau volcano in the Sunda Straits, Indonesia, *Scientific Reports*, 9, 11946 (open access) doi:10.1038/s41598-019-48327-6. Horrillo, J., Wood, A., Kim, G. B., & Parambath, A. 2013. A simplified Navier-Stokes numerical model for landslide-tsunami: Application to the Gulf of Mexico. *Journal of Geophysical Research: Oceans*, 118(12), 6934-6950. Kirby, J. T., Shi, F., Nicolisky, D. & Misra, S 2016. The 27 April 1975 Kitimat, British Columbia, submarine landslide tsunami: a comparison of modeling approaches. *Land-slides* 13, 1421–1434, <https://doi.org/10.1007/s10346-016-0682-x>. Løvholt, F., Bondevik, S., Laberg, J. S., Kim, J., & Boylan, N. 2017. Some giant submarine landslides do not produce large tsunamis. *Geophysical Research Letters*, 44(16), 8463-8472. Ma, G., Kirby, J. T., Hsu, T.-J. & Shi, F 2015. A two-layer granular landslide model for tsunami wave generation: Theory and computation. *Ocean Modelling* 93, 40–55, <https://doi.org/10.1016/j.ocemod.2015.07.012>. Schambach L., Grilli S.T., Kirby J.T. and F. Shi 2019. Landslide tsunami hazard along the upper US East Coast: effects of slide rheology, bottom friction, and frequency dispersion. *Pure and Applied*

C14

Geophys., 176(7), 3,059-3,098,doi.org/10.1007/s00024-018-1978-7 (published online 09/03/18).

All the above references except the first and the last one are now quoted in the manuscript.

Please also note the supplement to this comment:

<https://www.nat-hazards-earth-syst-sci-discuss.net/nhess-2019-225/nhess-2019-225-AC1-supplement.pdf>

Interactive comment on Nat. Hazards Earth Syst. Sci. Discuss., <https://doi.org/10.5194/nhess-2019-225>, 2019.