

Author's reply

Manuscript for Natural Hazards and Earth System Sciences

Title: Global scale benefit-cost analysis of coastal flood adaptation to different flood risk drivers using structural measures

5 Authors

Timothy Tiggeloven, Hans de Moel, Hessel C. Winsemius, Dirk Eilander, Gilles Erkens, Eskedar Gebremedhin, Andres Diaz Loaiza, Samantha Kuzma, Tianyi Luo, Charles Iceland, Arno Bouwman, Jolien van Huijstee, Willem Ligetvoet, Philip J. Ward

General response

10 We would like to thank both the referees and the editor for the time taken to critically review our manuscript. We are very pleased that the referees find the manuscript to be interesting, a step forward and providing new insights on the topic of adaptation strategies at the global scale. The referees raised a number of small issues, limitations and modest corrections. One of the most important is with regards to contextualization of the results, which was largely missing in the manuscript. Based on this, we have included a section dedicated to the contextualization and included information in the text to strengthen this.

15 Both referees comment on the need to more explicitly state the innovative aspects and distinction of this study from previous assessments. We have addressed this concern along with detailed comments about the approach and methodology of this assessment. We believe that these revisions to the manuscript, and those detailed below, have led to a significant improvement in our manuscript. In the following pages, we respond to the comments of each referee point by point. Our responses are shown in italics. Hereafter, we included the revised manuscript with track changes.

20

Referee: 1

General comments

The manuscript "Global scale benefit-cost analysis of coastal flood adaptation to different flood risk drivers" assesses the benefits and costs of four structural adaptation objectives at global scale until 2080. It further attributes the contribution of different flood risk drivers to the total adaptation costs under the 'Optimize' adaptation objective. For this analysis, the authors first assess coastal flood risk expressed in Expected Annual Damages (EAD), followed by the estimation of adaptation costs, before conducting a benefit-cost analysis (BCA) for each adaptation objective. The study finds that all adaptation objectives have a high potential for reducing flood risk in a cost-effective manner; further, the contribution of sea-level rise (SLR) dominates adaptation costs in most regions.

30

The study provides first estimates of the benefits of different structural adaptation objectives, taking into account a range of SLR and socioeconomic scenarios. It uses well-established methods and data and extends these for the purpose of this study, therefore providing new insights into the cost-effectiveness of adaptation strategies at the global scale. However, the manuscript in its current form has a number of limitations and I therefore propose to reconsider the manuscript for publication upon revision of the following issues:

35

- *Many thanks for the encouraging words. We are very pleased that the referee finds the manuscript to provide new insights into the cost-effectiveness of adaptation objectives at the global scale.*

Specific comments

40

1. As the study accounts for structural adaptation measures only, I would suggest adding this piece of information to the title of the manuscript.

- *Thank you: we have added 'using structural measures' to the title of the manuscript.*

45 2. While the introduction section cites the relevant background literature regarding coastal flood risk assessments, the current
research gap is not pointed out clearly (l. 49-55). Consequently, the innovative aspects of this study do not become entirely
clear. Similarly, previous work that has accounted for subsidence in assessing coastal flood risk has not been cited (e.g. Hinkel
et al. 2014, Nicholls et al. 2008, Hallegatte et al. 2013). Therefore, I suggest adding more detail to the respective sections.

50 • *Thank you: we have addressed this in the revised manuscript by adding information about the innovative aspects of
this study. We have also included the references with regards to subsidence in assessing coastal flood risk in previous
assessments. Now this section reads: 'Recent studies have shown that adaptation measures hold a large potential for
significantly reducing this future flood risk (Diaz, 2016; Hinkel et al., 2014; Lincke and Hinkel, 2018). However, the
number of global scale studies in which the benefits and costs of disaster risk reduction and adaptation are explicitly
and spatially accounted for remains limited. Existing studies have assessed the effect of climate change, subsidence
55 and/or socioeconomic change (Hallegatte et al., 2013; Hinkel et al., 2014; Nicholls et al., 2008; Vousdoukas et al.,
2016), but have not included adaptation objectives or attributed flood risk drivers to adaptation costs. Lincke & Hinkel
(2018) assessed the cost-effectiveness of structural protection measures against sea-level rise and population growth
using the DIVA model. They found that structural adaptation measures are for 13% of the global coastline feasible to
invest in. However, they did not include subsidence and attribution of drivers in their modelling scheme.
60 In this paper, we develop a model to evaluate the future benefits and costs of structural adaptation measures at the
global scale. We use it to address the limitations of current studies addressed above, and thereby extend the current
knowledge on the cost-effectiveness of structural adaptation measures in several ways. Firstly, we include subsidence
due to groundwater extraction. Secondly, we assess the benefits and costs of several adaptation objectives. Thirdly,
we attribute the costs of adaptation to different drivers (namely sea-level rise, subsidence and change in exposure).'*

65 3. L. 95: Please elaborate where the enriched GTSR data were acquired and how they were extended.

70 • *Thanks – we have included the following sentences to the manuscript in order to elaborate on the enrichment of GTSR
with regards to tropical cyclone tracks: 'All tracks over the period 1979-2004 are used and converted into wind and
pressure fields using the parametric Holland model (Delft3D-WES, 2019) in order to simulate alternative water
levels using GTSM. These water levels are combined with the time series of GTSR by using the highest water level
at each GTSM cell for each time step. Extreme values are estimated using a Gumbel extreme value distribution fit on
the annual extremes.'*

75 4. L. 116-119: How have the SLR projections been regionalized? Please provide more information.

• *Thanks – We have added this piece of information in section 2.1.1 to provide information about the regionalization
of the SLR projections: 'We use gridded datasets of regional sea-level rise estimates developed by Jackson and
Jevrejeva (2016). These data were derived by combining spatial patterns of individual sea-level rise contributions in
a probabilistic.'*

80 5. To assess current exposure, you refer to the methodology of Huizinga et al. 2017. It remains unclear how exactly damages
have been assessed without consulting the study of Huizinga et al. 2017. Please provide sufficient detail.

85 • *We have included additional information in the manuscript, which clarifies the study without consulting it. It now
reads: 'Current maximum economic damages are estimated using the methodology of Huizinga et al. (2017). They
used a root function to link GDP per capita to construction costs for each country. To convert construction costs to
maximum damages, several adjustments are carried out using the suggested factors by Huizinga et al. (2017) for the
different occupancy types. Such factors include depreciation and undamageable parts of buildings As a proxy for an
approximation of percentage area per occupancy type, we set the urban grid cells of the layers from the HYDE*

90 database to 75% residential, 15% commercial and 10% industrial, based on a study by (BPIE, 2011) and a comparison of European cities' share of occupancy type of the CORINE Land Cover data (EEA, 2016). Following Huizinga et al. (2017), the density of buildings per occupancy types are set to 20% for residential and 30% for commercial/industrial.'

95 6. It is not clear to me why the HYDE database was used to assess current exposure as it has a coarse resolution and is rather outdated. In the discussion section (l. 477), the Global Human Settlement Layer (GHSL) is mentioned, which provides built-up land data of 2015 at resolutions of 30m, 250m, and 1km. Further, the GHSL data provide spatial population distributions at resolutions of 250m, 1km, 9 arcsecs, 30 arcsecs (<https://ghsl.jrc.ec.europa.eu/download.php?ds=pop>). Both GHSL datasets could be used in combination for assessing current exposure, which would increase consistency of the results while avoiding the use of correction factors if base year data do not align (l. 148-149).

- 100 • *Thank you for the suggestion. We use the HYDE database to keep consistency between current and future built-up area data, because it provides current and future landuse data . We believe that having a consistency in the dataset between future and current exposure data improves the robustness of the produced results. It is true that the HYDE database is a coarse resolution, but to our knowledge no such dataset yet exists given the mentioned requirements.*

105 7. The SSPs are introduced rather abruptly in l. 147, but further details are missing. Please provide a brief description of the SSPs along with the relevant literature (e.g. O'Neill et al., 2014; O'Neill et al., 2017; van Vuuren et al., 2014). These pieces of information are also important to contextualize the results of the study (see also comment 18).

- 110 • *Thank you: we have included the following information in the future exposure section of 2.1.2 in the revised manuscript: 'These simulations include five narrative descriptions of future societal development associated with SSP1-5 (O'Neill et al., 2014). Such descriptions include sustainability associated with low challenges (SSP1), middle of the road associated with intermediate challenges (SSP2), regional rivalry associated with high challenges (SSP3), inequality associated with dominance of adaptation challenges (SSP4) and Fossil-fueled development where the mitigation challenges are dominating (SSP5) (O'Neill et al., 2017).'*

115 8. Some data for assessing exposure were downloaded from the SSP database, while others were not (e.g. GDP values). As the SSPs are the current state-of-the-art socioeconomic scenarios, I suggest using the national-level population projections as well as the GDP projections from the SSP database for the entire study period. Furthermore, spatial population projections based on the SSPs are available from Jones and O'Neill, 2016 at a resolution of 1/8 degree, downscaled to 30 arcsecs by Gao, 2017, and from Merkens et al., 2016, also at a resolution of 30 arcsecs. These may serve as a suitable basis for producing future simulations of built-up land, using the methodology of Winsemius et al 2016 (l. 151-153).

- 120 • *Thanks. We use gridded GDP layers from Van Huijstee et al. (2018) that uses GDP estimates from the SSP database as input to create those layers. This means that we have a consistency between the SSP data we use throughout our methodology. We see that we have not made this clear in the manuscript, so we adjusted the future exposure section in 2.1.2, which now reads: 'In order to calculate future risk relative to GDP, future gridded GDP values are taken from Van Huijstee et al. (2018), which uses the national GDP per capita from the SSP database as input'.*

125 9. Section 2.1.5 provides a description of the results of FLOPROS rather than how the modeling approach was applied. I suggest stating the use of the FLOPROS data, and moving further explanation to the SI.

- 130 • *Thank you for the suggestion. We have amended this information to the SI. In the main manuscript it now reads: 'In order to assess the benefits and costs of adaptation objectives, information on current protection standards is needed. We use the FLOPROS modelling approach (Scussolini et al., 2016) to estimate these protection standards using current exposure data and EAD data from the GLOFRIS model as input. Figure 2d shows the estimated FLOPROS*

flood protection standards for each coastal sub-national unit. Further information about the FLOPOS estimates together with a validation of the results can be found in the Supplementary Information.'

- *And in the supplementary information it now reads:* 'This section contains a brief description of the coastal protection standards estimated with the FLOPROS modelling approach. Higher protection standards can be found at regions with high economic activity and high asset exposure. Regions with low risk have lower estimated protection standards. Regions without modelled risk in the GLOFRIS model are excluded. This occurs in regions where we have no data on exposure or no coastal inundation is simulated. These protection standards are used in our paper as the current protection, on top of which the future costs of dike heightening are calculated. The protection standards for The Netherlands are manually set to 1000-year return period. This is because, for whole of The Netherlands protection standards are known to be higher than 1000-year return period.'

10. The scenario combinations (RCPs-SSPs) used for the analysis are briefly described in the results section (1. 292-296). I suggest moving the reasoning for using these scenario combinations to the methods section, along with additional background information.

- *Amended. We have moved the information together with some additional information to the methods section, specifically section 2.3. It now reads:* 'The benefit-cost analysis is carried out for two different sea-level rise scenarios (RCPs) and five different socioeconomic scenarios (SSPs). All the results are shown for two scenario combinations (van Vuuren et al., 2014), namely RCP4.5/SSP2 and RCP8.5/SSP5. The former is used for a 'middle of the road' scenario with medium challenges and adaptation (Riahi et al., 2017) that can broadly be aligned with the Paris agreement targets (Tribett et al., 2017), while the latter is used as a 'fossil-fuel development' world (Kriegler et al., 2017). Results of the other combinations can be found in the supplementary data.'

11. Figure 3: It would be helpful if the results were contextualized in the text with regard to the respective drivers contributing to coastal flood risk under current and future conditions. Please also provide the country names for each ISO code.

- *Thanks – we have included the following information in section 3.4 in order to contextualize the drivers contributing to coastal flood risk:* 'The results show that climate change is not the most dominant driver in 4 of the 5 countries that have the highest share of future EAD if no adaptation takes place (e.g. China, Bangladesh, India, and Indonesia)'. *Also, we have included information about the ISO codes we used in the caption of the corresponding figures (ISO 3166-1 alpha-3 codes).*

12. In Figure 2 and Figures 5-8, a legend of the regions in gray color (i.e. no data?) is missing. Further, the scalebar of the BCR plot (panel b) does not allow for differentiating between BCRs > 1 and < 1. Additionally, the scalebar of the NPV plot (panel c) does not provide a signature for NPV = 0. The same holds true for panels b-e in Figure 9. I suggest adjusting the figures accordingly in order to increase the information conveyed by the figures. Furthermore, the administrative units in South Africa and Namibia (all panels) seem odd as they include areas of Botswana, which is a landlocked country. Please also revise the administrative unit data.

- *Thank you for the suggestions. We have adjusted the scalebar so that NPV below 0 is indicated as a separate group. Also, we have included information in the captions of the figures with regards to the grey colour and no data. We have not adjusted the differentiation between BCR 0.5 and 2, because in practice decision-makers will not implement a large scale project when the BCR is just over (or under) 1. Therefore, we have decided that because of this and the uncertainty of future projections, we keep the original BCR categories. However, all data for all units can be found in the data files in the Supplementary Data. With regards to the administrative units, we have double-checked the units and find that they are correct and the borders between South Africa, Namibia and Botswana are preserved in our figures.*

13. Figure 8: It would be interesting if the change in risk (panel d) was contextualized in more detail, providing explanations of increases and decreases in flood risk in the text (see also comment 18).

- *Thanks – we have included the following sentences in section 3.3 focussing on the ‘optimize’ adaptation objective: ‘While most sub-national regions show a positive return on investment, there is still an increase in relative risk in 32% of the sub-national regions assessed, under the ‘optimize’ adaptation objective. In these cases, it is economically efficient to implement protection measures up to a certain level, yet the economic costs of keeping EAD as a percentage of GDP constant would exceed the avoided damages. Regions where this is especially the case include: Europe, North America, South America, Japan and Australia, as shown in Figure 8d. Many sub-national regions with decreases in relative risk can be found in South Asia, Southeast Asia, parts of the Gulf coast of the USA, New South Wales in Australia, several sub-national regions in Africa, and some parts of South America, among others. In these regions, the increase in risk is generally very high, which means that the costs of investment in protection are lower than the avoided damages relative to GDP. Generally, in these regions, protection standards and/or absolute dike heights increase the most.’*

14. Figure 10: Some of the colors used for the World Bank regions are misleading as they align with those used for the flood risk drivers. Please revise the colors used.

- *Amended – we revised the colours used.*

15. Table 2: You mention in l. 120 that the 5th and 95th percentiles of the SLR projections are used for the sensitivity analysis. Do SLR low and SLR high refer to these percentiles?

- *Indeed. We have clarified this in the caption of Table 2.*

16. Section 3.6 provides useful insights into the results of other studies, but lacks detailed explanation of the reasons for differences between this study and previous work. The results of this study are considerably higher than those of previous work despite the more refined inundation modeling approach used. I would suggest extending this section accordingly, by providing more context.

- *Thank you – in this section we compare our results to three different studies that use similar approaches as our study. Firstly, we find that we simulate higher values for current global EAD than Hallegatte et al. (2013) and reason that this can be attributed to the extent of their study. They use 136 major coastal cities, whilst we use all global coastlines. For future simulations of 2050 our values are in the same range of Hallegatte et al. (2013). Then, we compare our findings of adaptation costs to the findings of Hinkel et al. (2010) and Hinkel et al. (2014), and find that our results are higher than their findings. We reason that it should be noted that they use a demand-function for adaptation, while we do not use that function, but rather maximize NPV. This adaptation objective allows dynamic optimization per sub-national region and can result in higher adaptation costs as long as the net benefits increase. Additionally, we use different scenarios than those used in Hinkel et al. (2010) and Hinkel et al. (2014). Lastly, we compare our results of economic feasibility for sub-national regions and coastlines to the findings of Lincke & Hinkel (2018). Although in 89% of sub-national regions assessed in this study it is economically feasible to adapt, we find that the total coastline that is protected in these sub-national regions amount up to 3.4% of global coastline, compared to 13% of the coast globally that Lincke & Hinkel (2018) find. We reason that this difference is a result of the difference in spatial aggregation. They optimize transects ranging from 0.009 to 5213 kilometre with a mean of 85 kilometre, while we use 1 kilometre horizontal resolution at the equator. This can explain why we have lower percentage of coast that is feasible to protect than Lincke & Hinkel (2018).*

220 17. L. 477 please provide a reference for the GHSL data.

- *Amended.*

18. Contextualization of the results is largely missing in the discussion section (see also comments 7 and 16). It would be helpful for the reader if the different adaptation objectives were discussed in more detail, addressing questions such as: What do different adaptation objectives mean/entail? Which would be more desirable based on the BCRs? Why does flood risk increase in certain regions under certain objectives (see also comment 13)? I suggest adding a section that elaborates these aspects to the discussion. Connected to this point, it would also be insightful if the benefits of the study were elaborated in more detail, for instance how other scholars and/or decision-makers could use the results.

230 • *Thank you. We agree that the contextualization can be improved. Therefore we added a section dedicated to the contextualization along with additional information in section 3.3: 'In the middle of the road scenario of RCP4.5/SSP2, where the world will face intermediate adaptation and mitigation challenges, we see that most of the sub-national regions assessed would economically benefit from adaptation. We further see that the adaptation objectives differ in changes in relative risk and the level of adaptation that would take place. For instance, in the 'protection constant' adaptation objective we see that although the protection standards stay the same, the relative risk increases for most sub-national regions. This can be explained by the increase of the severity and frequency of the flood hazard due to sea-level rise and subsidence, and the increase of exposure of assets due to socioeconomic change. Compared to the 'optimize' adaptation objective, the 'protection constant' adaptation objective under-protects in most sub-national regions. In the 'absolute risk constant' adaptation objective we see that relative risk decreases in most sub-national regions while protection standards increase greatly. Due to climate change, socioeconomic change and subsidence, we see an increase in GDP exposed to flooding. Therefore, protection standards must increase vastly in order to meet the same level of absolute risk. In this adaptation objective, most sub-national regions are over-protected compared to the 'optimize' adaptation objective. In the 'relative risk constant' adaptation objective, we see that some sub-national regions are over-protected while other sub-national regions, for instance in Southeast Asia are under-protected. The 'optimize' adaptation objective shows the most economically feasible results in terms of maximizing NPV, and has the highest BCR in most regions. In the fossil-fuel based scenario of RCP8.5/SSP5, where adaptation will face high challenges and costs (van Vuuren et al., 2014), we see that higher protection standards are required in order to keep risk constant and to maximize NPV (see Supplementary Figures S3-6). The results of the adaptation objectives can be used as a first proxy to indicate in which sub-national regions adaptation through structural measures may be economically feasible. Moreover, the results indicate regions where adaptation is needed in order to maximize NPV and which objectives are under or over protecting sub-national regions compared to the 'optimize' adaptation objectives. Due to the scope of this study, local scale models and assessments should be used for the design and implementation of individual adaptation measures.'*

Technical corrections

255 19. List of typos/mistakes found:

- L. 26: 'compared to' stated twice
- L. 27: remove '.' after Raftery et al. (2017)
- L. 100: hydrologically
- L. 129: 30" x 30"
- 260 - L. 212: remove ',' after Jevrejeva et al. 2014
- L. 380: add ',' after South Asia
- L. 473: locations

20. The manuscript uses British English and American English interchangeably, one example being

‘optimize’, ‘optimise’, ‘optimisation’ etc in section 2.3.

- Thanks -- all amended.

Referee: 2

Overall this is an interesting paper. The approach undertaken is robust and I commend the authors for their nice study. The work builds on several previous assessments, and presents an incremental step forward, rather than a step change. However, I think it has some novel elements and is certainly worthy of publication in NHESS and results will be of interest to many. I have listed 5 modest corrections that I would like to see addressed and several minor ones.

- *Many thanks for the encouraging comments. We have addressed and clarified the modest and minor corrections in the manuscript, as described below.*

Modest corrections:

- In lines 50-55, you discuss the previous studies, and then go onto say what the objectives of your paper are. I think you need to make it clearer how your paper is distinct from these previous assessments. At the moment this does not come across strongly enough.

Thank you – we have addressed this in the revised manuscript by adding information about the distinction of this study. It now reads: ‘Recent studies have shown that adaptation measures hold a large potential for significantly reducing this future flood risk (Diaz, 2016; Hinkel et al., 2014; Lincke and Hinkel, 2018). However, the number of global scale studies in which the benefits and costs of disaster risk reduction and adaptation are explicitly and spatially accounted for remains limited. Existing studies have assessed the effect of climate change, subsidence and/or socioeconomic change (Hallegatte et al., 2013; Hinkel et al., 2014; Nicholls et al., 2008; Vousdoukas et al., 2016), but have not included adaptation objectives or attributed flood risk drivers to adaptation costs. Lincke & Hinkel (2018) assessed the cost-effectiveness of structural protection measures against sea-level rise and population growth using the DIVA model. They found that structural adaptation measures are for 13% of the global coastline feasible to invest in. However, they did not include subsidence and attribution of drivers in their modelling scheme.

In this paper, we develop a model to evaluate the future benefits and costs of structural adaptation measures at the global scale. We use it to address the limitations of current studies addressed above, and thereby extend the current knowledge on the cost-effectiveness of structural adaptation measures in several ways. Firstly, we include subsidence due to groundwater extraction. Secondly, we assess the benefits and costs of several adaptation objectives. Thirdly, we attribute the costs of adaptation to different drivers (namely sea-level rise, subsidence and change in exposure)..’

- Please provide, on lines 94 to 99, more details of how exactly you have included the tropical cyclones. Over what period was this done? How did you convert along track data into spatially varying wind and pressure fields?

Thanks -- we have included the following information in section 2.1.1: ‘All tracks over the period 1979-2004 are used and converted into wind and pressure fields using the parametric Holland model (Delft3D-WES, 2019) in order to simulate alternative water levels using GTSM. These water levels are combined with the time series of GTSR by using the highest water level at each GTSM cell for each time step. Extreme values are estimated using a Gumbel extreme value distribution fit on the annual extremes.’

- Lines 124 to 133: I am not clear if these subsidence rates include glacial isostatic adjustment or not. Do they? Can you make this clear. I assume you are accounting for these effects. If not, then it significantly undervalues your results.

310

Thanks – in this study we only use groundwater extraction as a driver of subsidence, however, glacial isostatic adjustment is included in the regional sea-level approach. We have further clarified that in this study only groundwater extraction is used as a driver for subsidence.

315

- Lines 172 – 185: I found the description of the protection standards confusing. Please can you improve this section. Has this approach been validated, in regions for example, where the protection standards are known exactly. How does this compare to what Hallegatte et al (2013) used in coastal cities? You cite the Netherlands as having a value of 1000. What are the units? Years? Please add these.

320

Apologies for not referring to the validation of the coastal FLOPROS values, which can be found in the Supplementary Information. This is now amended. We have further clarified this section and moved information to the SI as suggested by referee 1. Indeed the units are in years and we have amended this.

- Why is your analysis based on 2080, and not 2100? To me, it would seem much more sensible to go to 2100?

325

Thanks – the timeframe of the benefit-cost analysis is 2100 – we discount and accumulate all costs and benefits to this date. However, we have projections of climate and socioeconomic change at several points in time (2010, 2030, 2050 and 2080). Between these time-periods (and indeed after 2080) we extrapolate these values.

Minor corrections:

Line 25 – I would maybe update to the special IPCC report in 2019, which is a bit more up to date.

330

Line 27 – there is an extra full stop after the Raftery reference.

Line 29 – you could add 'and change in in tides.

Thanks – all are amended.

Global scale benefit-cost analysis of coastal flood adaptation to different flood risk drivers using structural measures

335

Timothy Tiggeloven¹, Hans de Moel¹, Hessel C. Winsemius^{2,5}, Dirk Eilander^{1,2}, Gilles Erkens², Eskedar Gebremedhin², Andres Diaz Loaiza^{1,6}, Samantha Kuzma⁴, Tianyi Luo⁴, Charles Iceland⁴, Arno Bouwman³, Jolien van Huijstee³, Willem Ligetvoet³, Philip J. Ward¹

¹Institute for Environmental Studies (IVM), Vrije Universiteit Amsterdam; The Netherlands

²Deltares, Delft, The Netherlands

340

³PBL Netherlands Environmental Assessment Agency; The Hague, The Netherlands

⁴World Resources Institute; Washington DC, USA

⁵Water Management Department, Delft University of Technology, Delft, The Netherlands

⁶Hydraulic Structures and Flood Risk, Delft University of Technology, Delft, The Netherlands

Correspondence to: Timothy Tiggeloven (timothy.tiggeloven@vu.nl)

Formatted: Dutch (Netherlands)

Deleted: .

Deleted: .

Deleted: .

345

Abstract. Coastal flood hazard and exposure are expected to increase over the course of the 21st century, leading to increased coastal flood risk. In order to limit the increase in future risk, or even reduce coastal flood risk, adaptation is necessary. Here,

350 we present a framework to evaluate the future benefits and costs of structural protection measures at the global scale, which accounts for the influence of different flood risk drivers (namely: sea-level rise, subsidence, and socioeconomic change). Globally, we find that the estimated expected annual damage (EAD) increases by a factor of 150 between 2010 and 2080, if we assume that no adaptation takes place. We find that 15 countries account for approximately 90% of this increase. We then explore four different adaptation objectives and find that they all show high potential to cost-effectively reduce (future) coastal flood risk at the global scale. Attributing the total costs for optimal protection standards, we find that sea-level rise contributes the most to the total costs of adaptation. However, the other drivers also play an important role. The results of this study can be used to highlight potential savings through adaptation at the global scale.

1 Introduction

In recent years, the effects of climate change on coastal flood hazards and its impacts on society have been studied extensively.

360 The Intergovernmental Panel on Climate Change (IPCC) reports that it is likely that we will face a global mean sea-level rise by the end of the 21st century in the range of approximately 0.43 – 0.84 meter compared to 1986-2005 and that impacts on society will be vast (Oppenheimer et al., 2019). According to a recent study by Raftery et al. (2017), it is unlikely that the Paris agreement's aim of keeping global warming below a 2°C increase by the end of the 21st century will be met. This may lead to changes in storm surges (Tebaldi et al., 2012), extreme sea levels (Vousdoukas et al., 2017), and tides (Pickering et al., 2012).

365 Together, these increases in sea-level and a possible change in storminess will lead to increased flood hazards, as well as threats to shorelines, wetlands, and coastal development (Ericson et al. 2006; Hinkel et al., 2013). Moreover, flood hazard is expected to increase as a result of subsidence. In many deltas and estuaries, groundwater extraction is a major factor contributing to this subsidence (Hallegatte et al., 2013). During the 20th century, the coasts of Tokyo, Shanghai and Bangkok subsided by several meters (Nicholls et al., 2008) and subsidence is expected to continue to affect coastal flood risk in the future (Dixon et al., 2006). Global coastal flood risk is also expected to increase in the future as a result of increasing exposure, due to growth in population and wealth, and economic activities in flood-prone areas (Güneralp et al., 2015; Jongman et al., 2012; Neumann et al., 2015; Pycroft et al., 2016).

375 Today, on average 10% of the world population and 13% of the total urban area in low elevation coastal zones is located less than 10 meters above sea level (McGranahan et al., 2007). In addition, 1.3% of global population is estimated to be exposed to a 1 in 100-year flood (Muis et al., 2016). In the coming century, these people and areas are projected to face increases in coastal flood risk (Brown et al., 2018; Hallegatte et al., 2013; Hinkel et al., 2014; Jongman et al., 2012; Merkens et al., 2018; Neumann et al., 2015).

380 In order to prevent this increase in coastal flood risk, or even to reduce risk below today's levels, adaptation measures are necessary. The importance of climate change adaptation and disaster risk reduction is recognized in several global agreements, such as the Paris Agreement (United Nations Framework Convention on Climate Change, 2015) and the Sendai Framework for Disaster Risk Reduction (United Nations Office for Disaster Risk Reduction, 2015). The Sendai Framework sets specific

Deleted: he Fifth Assessment Report (AR5) of t

Deleted: compared to

Deleted: .

Deleted: an

Deleted: increase

Deleted: and

Formatted: Dutch (Netherlands)

Field Code Changed

Formatted: Dutch (Netherlands)

Field Code Changed

Formatted: Dutch (Netherlands)

Formatted: Dutch (Netherlands)

targets for reducing risk by 2030, such as reducing the direct disaster economic loss in relation to GDP and substantially reducing the number of affected people globally.

390 Recent studies have shown that adaptation measures hold a large potential for significantly reducing this future flood risk (Diaz, 2016; Hinkel et al., 2014; Lincke and Hinkel, 2018). However, the number of global scale studies in which the benefits and costs of disaster risk reduction and adaptation are explicitly and spatially accounted for remains limited. Existing studies have assessed the effect of climate change, [subsidence](#) and/or socioeconomic change (Hallegatte et al., 2013; Hinkel et al., 2014; Nicholls et al., 2008; Voudoukas et al., 2016), [but have not included adaptation objectives or attributed flood risk drivers to adaptation costs](#). Lincke & Hinkel (2018) assessed the cost-effectiveness of structural protection measures against sea-level rise and population growth using the DIVA model. They found that structural adaptation measures are for 13% of the global coastline feasible to invest in. [However, they did not include subsidence and attribution of drivers in their modelling scheme](#).

395 [In this paper, we develop a model to evaluate the future benefits and costs of structural adaptation measures at the global scale. We use it to address the limitations of current studies addressed above, and thereby extend the current knowledge on the cost-effectiveness of structural adaptation measures in several ways](#). Firstly, we include subsidence due to groundwater extraction. Secondly, we assess the benefits and costs of several adaptation objectives. Thirdly, we attribute the costs of adaptation to different drivers (namely sea-level rise, subsidence and change in exposure).

2 Methods

405 The overall methodological framework is summarized in Figure 1, and consists of the following main steps: (1) flood risk estimation; (2) adaptation costs estimation; (3) benefit-cost analysis for four adaptation objectives; and (4) attribution of the total costs to the different drivers. Each of these steps is described in detail in the following subsections. In brief, flood risk is estimated as a function of hazard, exposure and vulnerability (United Nations Office for Disaster Risk Reduction, 2016). In the risk model, Expected Annual Damage (EAD) is calculated for different scenarios with and without adaptation, with the difference between these two representing the benefits. The costs are calculated by estimating the dimensions of the required dikes (height and length) and multiplying these by their unit costs. Maintenance costs are also included in the cost model. A benefit-cost analysis is performed for four adaptation objectives, and finally the costs of adaptation are attributed to several risk drivers. The methodological steps taken are explained in detail in Ward et al. (2019), on which the following descriptions are based.

Formatted: English (United States)

Deleted: a

Formatted: English (United States)

Field Code Changed

Formatted: English (United States)

Formatted: English (United States)

Deleted: In this paper, we develop a model to evaluate the future benefits and costs of structural adaptation measures at the global scale. We use it to extend the current knowledge on the cost-effectiveness of structural adaptation measures in several ways

Deleted:

Deleted: ¶





Figure 1: Overview of models and data layers for assessing flood risk, costs of adaptation and attribution of different drivers.

2.1 Flood risk estimation

425 We use hydrodynamic simulations of tide and surge, and scenarios of regional sea-level rise, as input to a coastal inundation
 model, in order to generate hazard maps for several return periods (2, 5, 10, 25, 50, 100, 250, 500 and 1000 years). These
 are combined with exposure maps and vulnerability curves (depth-damage functions) in the impact assessment model, using a
 setup similar to the GLOFRIS impacts module developed by Ward et al. (2013) and extended for future simulations by
 Winsemius et al. (2016). The global coastal flood impacts are assessed at a horizontal resolution of 30" × 30" and simulated
 430 for the different return periods. After calculating the impacts for the different return periods, EAD is calculated by taking the
 integral of the exceedance probability-impact curve (Meyer et al., 2009). Figure 2 shows the different input layers for the flood
 risk assessment and benefit-cost analyses (note that different sea-level rise and socioeconomic scenarios are used, and just one
 is shown in Figure 2 as example). The following section describes the flood risk simulations in detail.

Deleted:



435 **Figure 2: Input layers for the benefit-cost analyses: (a) sea level rise for the RCP4.5 scenario in 2080; (b) subsidence in 2080; (c) Change in GDP for the SSP2 scenario in 2080; and (d) current protection standards estimated with the FLOPROS modelling approach.**

2.1.1 Flood hazard

440 **Current flood hazard.** In order to simulate coastal inundation hazard, we use extreme sea levels from the Global Tide and Surge Reanalysis (GTSR) dataset by Muis et al. (2016) as input to an inundation model. GTSR has been shown to perform well (Muis et al., 2017) for extratropical regions and contains a database of extreme water levels for different return periods, based on the Global Tide and Surge Model (GTSM). Surge is simulated using wind and pressure fields from the ERA-Interim reanalysis (Dee et al., 2011), and tide is simulated using the Finite Element Solution 2012 (FES2012) model (Carrère and Lyard, 2003). In this modelling scheme, wind (or surface) waves are not included. As tropical cyclones are poorly represented in the input climate dataset, we use a version of GTSR enriched using a historical storm track archive to represent tropical cyclones. These tropical cyclones were simulated using the IBTrACS (International Best Track Archive for Climate Stewardship) archive, which provides a dataset of historical best tracks. [All tracks over the period 1979-2004 are used and converted into wind and pressure fields using the parametric Holland model \(Delft3D-WES, 2019\) in order to simulate alternative water levels using GTSM. These water levels are combined with the time series of GTSR by using the highest water level at each GTSM cell for each time step. Extreme values are estimated using a Gumbel extreme value distribution fit on the annual extremes.](#)

450 To calculate overland inundation from near-shore tide and surge levels we used a GIS-based inundation routine, similar to Vafeidis et al. (2019). Extreme sea levels from the nearest GTSR location are projected at the coastline. Then, inundation takes

455 place in areas that are hydrologically connected to the sea for that extreme sea level. The model uses the Multi-Error-Removed Improved-Terrain (MERIT) DEM (Yamazaki et al., 2017) at a 30" x 30" resolution as underlying topography. We accommodate three important factors in the inundation routine that are not regularly taken into account in global scale coastal inundation modelling:

Deleted: aulic

- 460 • We use a resistance factor to simulate the reduction of flooding land inwards as tides and storm surges have a limited time span. We apply this factor over a Euclidean distance from the nearest coast line point. The resistance factor was set to 0.5m/km. Haer et al. (2018) showed the maps to perform well against past flood events in their study in Mexico. Several other studies also use attenuation factors varying between 0.1 and 1.0 m/km (Vafeidis et al., 2019).
- 465 • We multiply the resistance factor by a weight, proportional to the amount of permanent water in each cell within the Euclidean pathway towards a land cell under consideration. In this way, grid cells that are marked as land within the terrain model, but in fact represent areas with large amounts of open water are correctly simulated as cells with low resistance. We estimate fractions of permanent water using a 30-year monthly surface water mask dataset at 30 meter resolution, derived from LandSAT archive (Pekel et al., 2016).
- 470 • We apply a spatially varying offset between Mean Sea Level according to the FES2012 model, and the datum used by the terrain model MERIT (EGM96) to ensure that the zero datum of our terrain and our extreme sea levels from GTSR are the same.

Future flood hazard. For future hazard simulations we use sea level changes, to simulate future extreme sea levels, and subsidence estimates [due to groundwater extraction](#) to estimate how the terrain may change. [Global mean sea-level rise](#) projections for RCP4.5 and RCP8.5 are obtained from the RISES-AM project (Jevrejeva et al., 2014). The sea-level rise for this [study](#) is simulated as a range of probabilistic outcomes. For this [study, we use the 50th percentile](#), and to assess the sensitivity of the results we also use the 5th and 95th percentiles as input for the inundation model. [We use gridded datasets of regional sea-level rise estimates developed by Jackson and Jevrejeva \(2016\). These data were derived by combining spatial patterns of individual sea-level rise contributions in a probabilistic manner.](#) We include sea-level rise in the inundation routine by adding this additional water level to the extreme sea level. Sea-level rise in 2080 for the RCP4.5 scenario and 50th percentile is shown in Figure 2a. In this simulation, most of the regions will face a sea-level rise between the 0.3 and 0.5 meters. Close to the poles, sea level may decrease due to a decline in gravitational forces of the melting ice caps.

Deleted: ridded regional

Deleted: r

Deleted: m

Deleted: project

Deleted: paper

Deleted: is used

Deleted: (

Deleted: .

480 Subsidence rates are taken from the SUB-CR model by Kooi et al. (2018), which models subsidence using three existing models, namely the hydrological model PCR-GLOBWB integrated with the global MODFLOW groundwater model (de Graaf et al., 2017; Sutanudjaja et al., 2018), and a land subsidence model (Erkens and Sutanudjaja, 2015), focussing on groundwater levels and resulting subsidence. In this approach, subsidence is modelled due to groundwater extraction, which is the dominant factor of human-induced subsidence in many coastal areas (Erkens et al., 2015; Galloway et al., 2016). The effects of subsidence, simulated at the resolution of 5' x 5' and spatially interpolated to 30" x 30" resolution, are included in the inundation model by adding the subsidence estimates to the MERIT terrain. Subsidence in 2080 is shown in Figure 2b and

Deleted: '

Deleted: '

reaches up to 5-7m in regions in China. Unlike sea level rise, subsidence does not take place along every coastline and is instead projected as a regional phenomenon.

2.1.2 Flood exposure

In our modelling scheme, exposure is represented by maps of built-up area and estimates of maximum damage for three different land use classes in built-up areas. The GLOFRIS model uses current and future built-up area, current and future GDP, and maximum damages on the country level as input. The FLOPROS modelling approach (see section 2.1.5) has current data on built-up area, population and GDP as input. In the following sections, we describe the exposure data for the current and future simulations.

Current exposure. Current built-up area with a resolution of 5' x 5' are taken from the HYDE database (Klein Goldewijk et al., 2010) and later regridded to the 30" x 30" resolution. Built-up area refers to all kinds of built-up areas and artificial surfaces. Current maximum economic damages are estimated using the methodology of Huizinga et al. (2017). They used a root function to link GDP per capita to construction costs for each country. To convert construction costs to maximum damages, several adjustments are carried out using the suggested factors by Huizinga et al. (2017) for the different occupancy types. Such factors include depreciation and undamageable parts of buildings As a proxy for an approximation of percentage area per occupancy type, we set the urban grid cells of the layers from the HYDE database to 75% residential, 15% commercial and 10% industrial, based on a study by (BPIE, 2011) and a comparison of European cities' share of occupancy type of the CORINE Land Cover data (EEA, 2016). Following Huizinga et al. (2017), the density of buildings per occupancy types are set to 20% for residential and 30% for commercial/industrial.

In order to normalize current risk we use GDP per capita taken from the Shared Socioeconomic Pathways (SSP) database of IIASA, distributed spatially according to the ORNL LandScan 2010 population count map (Bright et al., 2011). As the total population per country in this map is different to the 2010 population stated in the SSP database, we use a correction factor per country to adjust the population per cell.

Future exposure. Future simulations of built-up area are taken from Winsemius et al. (2016) at a resolution of 30" x 30". Using the method described by Jongman et al. (2012), these simulations were computed using changes in gridded population and urban population for different SSPs derived from the GISMO/IMAGE model (Bouwman et al., 2006). These simulations include five narrative descriptions of future societal development associated with SSP1-5 (O'Neill et al., 2014). Such descriptions include sustainability associated with low challenges (SSP1), middle of the road associated with intermediate challenges (SSP2), regional rivalry associated with high challenges (SSP3), inequality associated with dominance of adaptation challenges (SSP4) and Fossil-fueled development where the mitigation challenges are dominating (SSP5) (O'Neill et al., 2017).

To estimate future maximum damages, we scale the current values with the GDP per capita per country from the SSP database. Boundaries of countries are derived from the Global Administrative areas dataset (GADM, 2012). In order to calculate future

Deleted: (
Field Code Changed
Deleted: .

Field Code Changed
Formatted: Dutch (Netherlands)
Formatted: Dutch (Netherlands)
Deleted: Using the method described by Jongman et al. (2012), these simulations were computed using changes in gridded population and urban population for different SSPs derived from the GISMO/IMAGE model (Bouwman et al., 2006).
Formatted: Dutch (Netherlands)
Formatted: Dutch (Netherlands)

risk relative to GDP, future [gridded](#) GDP values are taken from Van Huijstee et al. (2018), [which uses the national GDP per capita from the SSP database as input](#).

2.1.3 Flood vulnerability

540 Vulnerability to flood depth of urban areas is estimated by using different global flood depth-damage functions for each occupancy type and are taken from Huizinga et al. (2017). The resulting damages are represented as percentage of the maximum damage, reaching maximum damages at a water level depth of 6 meters.

2.1.4 Integration to EAD

545 With the urban damages, calculated for the different return periods, risk is computed and expressed in terms of expected annual damages (EAD). We use a commonly used method in risk assessment to calculate EAD by taking the integral of the exceedance probability-impact (risk) curve (Meyer et al., 2009) and can be written as

$$EAD = \int_{p=0}^1 D_{\theta}(p) dp, \quad (1)$$

550 where *EAD* is 'risk' per year, *D* is the urban damage (or impact), θ the vulnerability, and *p* denotes the annual probability of non-exceedance (protection standard divided into 1). To fit a protection standard of a coastal region in the risk computation, the risk curve is truncated at the exceedance probability of the protection standard (expressed as a return period). To estimate the definite integral, we use the trapezoidal approximation. As data on protection standards of coastal regions are not available for many regions, we estimate current protection standards for coastal regions using the FLOPROS modelling approach (Scussolini et al., 2016), as is described in section 2.1.5.

2.1.5 FLOPROS modelling approach

555 In order to assess the benefits and costs of adaptation objectives, information on current protection standards is needed. We use the FLOPROS modelling approach (Scussolini et al., 2016) to estimate these protection standards [using current exposure data and EAD data from the GLOFRIS model as input](#). [Figure 2d shows the estimated FLOPROS flood protection standards for each coastal sub-national unit](#). [Further information about the FLOPROS estimates together with a validation of the results can be found in the Supplementary Information](#).

560 2.1.6 Estimating the benefits of adaptation

In order to calculate the benefits of adaptation, EAD is calculated for every year of the lifetime of the dike for a certain return period and subtracted from the EAD for every year without adaptation. The lifetime of the dike is set to expire in 2100 and the building period is set to 20 years. During this period EAD is assumed to increase linearly. The results are summed to get the total benefits of adaptation.

Deleted: . This section contains a brief description of the coastal protection standards estimated with the FLOPROS modelling approach.¶
U

Deleted: , the current protection standards are estimated using the FLOPROS modelling approach. Figure 2

Deleted: Higher protection standards can be found at regions with high economic activity and high asset exposure. Regions with low risk have lower estimated protection standards. Regions without modelled risk in the GLOFRIS model are excluded. This occurs in regions where we have no data on exposure or no coastal inundation is simulated. These protection standards are used in our paper as the current protection, on top of which the future costs of dike heightening are calculated. The protection standards for The Netherlands are manually set to 1000. This is because, for whole of The Netherlands protection standards are known to be higher than 1000.

2.2 Cost estimation

To estimate the costs associated with the different adaptation objectives, we use the same methodology as Ward et al. (2017), which calculates the costs of flood protection by summing the maintenance and investment costs over time for raising dikes to prevent flooding. The following section describes the calculation of costs of adaptation and the adaptation objectives in more detail.

In order to calculate the costs of adaptation, first dike heights need to be calculated. The current dike height calculations are taken from a recent study by van Zelst et al. (2019). Their methodology is to first derive coastal segments and perpendicular coast-normal transects (766,034 transects in total). For each transect, bed levels are constructed and subsequently, hydrodynamic conditions and wave attenuation are derived. Lastly, the resulting sea water levels are translated into dike heights. The coastlines are derived from OpenStreetMap (OSM) and moved 100 m land inwards to smoothen the coast lines and to position the lines at a likely place to establish a dike system. Transects are derived perpendicular to the coastlines for each $1' \times 1'$ -cell that has a coastline segment. Each transect is described by its slope, ocean bathymetry, foreshore, elevation and surge levels among other things. To capture most foreshores, the transects are stretched 4 km land inward and seaward.

The main source of bed level data is the Earth Observation (USGS Landsat and Copernicus Sentinel 2) based high resolution intertidal elevation map (20 m horizontal and 30-50 cm vertical accuracy) of Calero et al. (2017). As this dataset does not contain data for all bed levels along the transects, the gaps are filled by ocean bathymetry data from GEBCO (30'', 10 m vertically) and topography data from MERIT (3'', 2 m vertically). The water levels are derived from the GTSR dataset (Muis et al., 2016) and corresponding wave conditions at different return periods from the ERA-Interim reanalysis (Dee et al., 2011).

With a lookup-table, consisting of numerical modelling results, the wave attenuation over the foreshore is determined. Due to the unknown direction, incoming waves are assumed to run perpendicular to the coast. Finally, current dike heights in respect to the surge level are calculated with the empirical EuroTop formulations (Pullen et al., 2007) and are based on a standard 1:3 dike profile without berms and with a maximum allowed overtopping discharge of $1 \text{ L/m}^2/\text{s}$. This is representative for a low-cost dike. We exclude coastlines where there is no built-up area or no inundation is simulated.

In order to calculate future dike heights, sea-level rise from the RISES-AM project (Jackson and Jevrejeva, 2016) is used in the calculation of the crest heights for different return periods. This is done by adding sea level rise directly to the crest height. Next to sea level rise, future dike heights are calculated with subsidence levels (see section 2.1.1.). Subsidence is assumed to take place directly on the dike and therefore computed on the crest height, which is similar for sea level rise calculations.

The costs of raising dikes are estimated by calculating the total length of dike heightening per grid cell and multiplying by a unit cost set to USD 7 million km-m based on reported costs in New Orleans (Bos, 2008). This value of US\$ 7 million km-m is within a reasonable range when compared to various studies (Aerts et al., 2013; Jonkman et al., 2013; Lenk et al., 2017). This includes investment cost, groundwork-, construction- and engineering costs, property or land acquisition, environmental compensation, and project management. Subsequently, the costs are converted to US\$2005 Power Purchasing Parity (PPP) using GDP deflators from the World Bank and average annual market exchange rates from the European Central Bank for

Deleted: "

Deleted: "

Deleted: (Jevrejeva et al., 2014)

Deleted: .

each country. Construction index multipliers, based on civil engineering construction costs, adjust the construction costs to account for differences between countries (Ward et al., 2010). The lengths of the dikes are estimated using the 766,034 coastline transects. Maintenance costs are represented as percentages of investment costs and are set to 1% per year.

2.3 Benefit-cost analysis

Finally, a benefit-cost analysis is performed by calculating the benefits and costs for adaptation until 2100 for sub-national regions. These regions are defined as the next administrative unit below national scale in the Global Administrative Areas Database (GADM). The benefits and costs are discounted with a discount rate of 5% until 2100 (lifespan of investment) and with Operation and Maintenance (O&M) costs of 1%. It is assumed that investments are made in 2020 and construction is finished in 2050. During this time period, benefits and costs for investment are assumed to increase linearly. We use Net Present Value (NPV) shown in Eq. (2) and Benefit-Cost Ratios (BCR) shown in Eq. (3) as indicators of economic efficiency.

$$NPV = \sum_{t=1}^n \frac{B_t - C_t}{(1+r)^t} - C_0 \quad (2)$$

$$BCR = \frac{\sum_{t=1}^n \frac{B_t}{(1+r)^t}}{\left(\sum_{t=1}^n \frac{C_t}{(1+r)^t} + C_0 \right)}, \quad (3)$$

where t denotes the time in years, n the lifespan of the investment, r the discount rate, B_t the benefits per year, C_t costs per year expressed as maintenance costs, and C_0 the initial investment costs.

The Benefit-cost analysis is carried out for two different sea-level rise scenarios (RCPs) and five different socioeconomic scenarios (SSPs). All the results are shown for two scenario combinations (van Vuuren et al., 2014), namely RCP4.5/SSP2 and RCP8.5/SSP5. The former is used for a ‘middle of the road’ scenario with medium challenges and adaptation (Riahi et al., 2017) that can broadly be aligned with the Paris agreement targets (Tribett et al., 2017), while the latter is used as a ‘fossil-fuel development’ world (Kriegler et al., 2017). Results of the other combinations can be found in the supplementary data.

2.3.1 Adaptation objectives

For the benefit-cost analysis, four future investment objectives are explored: (1) ‘Protection constant’, which keeps protection levels in the future the same as current protection levels; (2) ‘Absolute risk constant’, which calculates future protection standards when the absolute value for EAD is kept the same as current; (3) ‘Relative risk constant’, which calculates future protection standards when EAD as a percentage of GDP is kept the same as current; and (4) ‘Optimize’, which calculates future protection standards by maximizing NPV. The future protection standards for the four adaptation objectives are estimated at discrete intervals (2, 5, 10, 25, 50, 100, 250, 500 and 1000 years). The future protection standards when no adaptation takes place are calculated by assuming that dikes are maintained at the current height, but with no additional heightening. In the ‘optimize’ adaptation objective, only regions with BCR greater than 1 are included; no adaptation takes place for regions with BCR less than 1.

Formatted: English (United States)

Formatted: English (United States)

2.3.2 Attribution of costs

650 In order to attribute costs to different drivers, the following method is used. For the ‘optimize’ adaptation objective, the costs are attributed to four terms: (1) optimization under current conditions (CUR); (2) socioeconomic change (SEC); (3) sea level rise driven by climate change (SLR); and (4) subsidence driven by groundwater depletion (SUB). The following conceptual equations illustrate the attribution methodology:

$$A_{CUR} = NPV_{CUR}/NPV_{ALL}, \quad (4)$$

655 $A_{SEC} = (NPV_{SEC} - NPV_{CUR})/NPV_{ALL}, \quad (5)$

$$A_{SLR} = NPV_{SLR} \text{ (baseline protection SEC)}/NPV_{ALL}, \quad (6)$$

$$A_{SUB} = NPV_{SUB} \text{ (baseline protection SEC)}/NPV_{ALL} \quad (7)$$

Equation (4-7) show the attribution calculation with A the attribution and NPV the net present value calculated with Eq. (4). The subscripts denote the attribution terms: CUR refers to optimizing in current conditions; SEC refers to socioeconomic change; SLR refers to sea-level rise; and SUB refers to subsidence. ALL refers to when all risk drivers are taken into account.

660 In the subscript between brackets, the baseline protection standard used during the calculation of NPV is indicated. Because the ‘optimize’ adaptation objective is an optimization and not all regions have optimized their protection standards for the current climate, this last term must be accounted for. The optimization term is the costs of maximizing NPV with current conditions (NPV_{CUR}). Subsequently, the costs for socioeconomic change are computed by taking the difference in costs

665 between NPV_{CUR} and maximizing NPV when only socioeconomic change is taken into account (NPV_{SEC}). To determine the attribution of costs for climate change, the baseline protection is set to the protection standards associated with the NPV_{SEC} term. Subsequently, the costs are estimated by maximizing NPV when both sea-level rise and socioeconomic change are taken into account (NPV_{SLR}). The attribution of subsidence is the same procedure as with NPV_{SLR} , by swapping the sea-level rise driver with the subsidence driver (NPV_{SUB}). All attributions of costs are expressed in percentages with reference to maximizing NPV for future conditions (NPV_{ALL}), which is the same as the ‘optimize’ adaptation objective.

In some cases, the percentages of the different drivers do not add up to 100%. This is the case when absolute dike heights associated with NPV_{SEC} are higher than NPV_{ALL} (in other words: adding climate change and subsidence would actually result in lower optimal dike heights in the benefit-cost analysis). In these cases, we set attribution for ATR_{SEC} to 100%, and ATR_{SLR} and ATR_{SUB} to 0%. Another exception is when optimal protection standards for NPV_{SEC} are higher than NPV_{SLR} or NPV_{SUB} .

675 This occurs when the increase in absolute dike height in the optimization is lower than the effect of sea-level rise or subsidence, and results in a lower protection standard. For all other cases, except the two mentioned above, the sum adds to 100%.

3 Results and Discussion

In this section, we first present an assessment of current and future risk without adaptation. Next, we present global benefit-cost analyses for the different adaptation objectives. Then, we present the results of the benefit-cost analyses and the attribution

Deleted: s

Deleted: s

Deleted: s

Deleted: s

of costs to different drivers at the regional scale. Finally, we assess the sensitivity of the results to changes in various parameters.

3.1 Overview of future flood risk assuming no adaptation.

Globally, the estimated EAD increases by a factor of 150 between 2010 and 2080, if we assume that no adaptation takes place in the middle of the road scenario RCP4.5/SSP2. Figure 3 shows the top 15 countries that contribute to this coastal flood risk, in 2010 (Figure 3a) and 2080 (Figure 3b) – note the different scales on the x-axis. China, Bangladesh, and India have the highest flood risk in absolute terms in 2010. In 2080, these three countries remain in the top four if no adaptation takes place, and are joined by the Netherlands. The 15 countries shown account for 89% of coastal flood risk worldwide in 2010 (US\$19.6 billion per year globally). Although the countries in the top 15 change between current and future assuming no adaptation, the total share of EAD residing in the top 15 countries remains approximately the same: 87% of global flood risk in 2080 if no adaptation takes place (US\$3 trillion per year globally for RCP4.5/SSP2 and US\$6.8 trillion for RCP8.5/SSP5).




Figure 3: Top 15 countries with coastal flood risk in (a) current conditions; and (b) 2080 if no adaptation takes place for the scenario RCP4.5/SSP2. Note that the countries and value on the x-axis change for each graph. The countries are denoted by ISO 3166-1 alpha-3 codes.

3.2 Global scale assessment of flood risk under the different adaptation objectives.

For all four adaptation objectives, a globally aggregated overview of the benefits, costs, BCR, and NPV is provided in Table 1. All objectives have a positive NPV and BCR higher than 1, indicating that globally the benefits in terms of reduced risk would exceed the investment and maintenance costs. Note that only regions with positive NPV are included for the 'optimize' adaptation objective. The 'absolute risk constant' adaptation objective has the lowest BCR, while the 'optimize' adaptation objective has, by definition, the highest BCR. Higher costs and benefits are found for the RCP8.5/SSP5 scenario compared to the RCP4.5/SSP2 scenario, as a result of the larger EAD (and therefore avoided EAD) under this scenario. On average, the costs are ca. 25% larger in the former, and the benefits roughly double.

Table 1: Global overview of benefit-cost analysis for the different adaptation objectives (benefits, costs, and NPV are in billion US\$2005).

Benefits	Costs	BCR	NPV
----------	-------	-----	-----

Deleted: The flood damage simulations were carried out for two different sea-level rise scenarios (RCPs) and five different socioeconomic scenarios (SSPs). All the results are shown for two scenarios, namely RCP4.5/SSP2 and RCP8.5/SSP5. The former is used for a 'middle of the road' scenario with medium challenges and adaptation (Riabi et al., 2017) that can broadly be aligned with the Paris agreement targets (Tribett et al., 2017), while the latter is used as a 'fossil-fuel development' world (Kriegler et al., 2017). Results of the other combinations can be found in the supplementary data.¶

‘Protection constant’	RCP4.5/SSP2	9,705	144	67	9,561
	RCP8.5/SSP5	18,729	176	106	18,552
‘Absolute risk constant’	RCP4.5/SSP2	11,550	307	38	11,243
	RCP8.5/SSP5	23,020	399	58	22,620
‘Relative risk constant’	RCP4.5/SSP2	11,027	186	59	10,840
	RCP8.5/SSP5	22,101	224	99	21,878
‘Optimize’	RCP4.5/SSP2	11,550	152	76	11,398
	RCP8.5/SSP5	23,031	208	111	22,823

The top 15 countries that contribute the most to coastal flood risk for the four adaptation objectives for RCP4.5/SSP2 in 2080 are shown in Figure 4. The total share of EAD residing in the top 15 countries remains approximately the same: 94% of global flood risk in the ‘protection constant’ adaptation objective (US\$ 767 billion per year globally); 93% in the ‘absolute risk constant’ adaptation objective (US\$238 billion per year); 90% in the ‘relative risk constant’ adaptation objective (US\$421 billion per year); and 91% in the ‘optimize’ adaptation objective (US\$242 billion per year globally). Note that EAD can increase in the future for the ‘absolute risk constant’ adaptation objective in certain regions as we cap protection standards at 1000. The simulated optimal protection standards of the Netherlands are lower than in the ‘protection constant’ adaptation objective, resulting in a high future EAD of US\$60.9 billion per year. This is because the simulated marginal costs of dike heightening up to a protection standard of 1000 years outweigh the marginal benefits. However, it should be noted that the benefits do exceed the costs up to a 1000-year protection standard, and that if this were implemented, the future EAD for the Netherlands in the ‘optimize’ adaptation objective would therefore be much lower than shown in Figure 4. Supplementary Figure S2 shows the top 15 countries for RCP8.5/SSP5.

Deleted: 1




Figure 4: Top 15 countries with coastal flood risk in (a) 2080 if protection standards are kept constant; (b) 2080 if absolute risk is kept constant; (c) 2080 if relative risk is kept constant; and (d) 2080 if protection standards are optimized for the scenario RCP4.5/SSP2. Note that the countries and value on the x-axis change for each graph. [The countries are denoted by ISO 3166-1 alpha-3 codes.](#)

3.3 Regional scale assessment of flood risk under the different adaptation objectives.

In order to show spatial patterns of the four adaptation objectives, the following results are shown at the sub-national scale in Figures 5-8. Here, results are shown for RCP4.5/SSP2 only. The same results for RCP8.5/SSP5 can be found in Supplementary Figures S2-S5, and the data for all scenario combinations can be found in Supplementary Data. Although there are some differences between the results for RCP4.5/SSP2 and RCP8.5/SSP5, the overall patterns are very similar.

In the ‘**protection constant**’ adaptation objective, the benefits outweigh the costs for the majority of the regions (82%; 643 of the 784 sub-national regions assessed). Nevertheless, this would still lead to an increase in relative risk (i.e. EAD as a percentage of GDP) in the future for 82% (641) of the regions assessed. Therefore, only raising dikes to keep up with the current protection standard would lead to a substantial increase in future risk in the majority of the world’s regions for scenario RCP4.5/SSP2. Sub-national regions in South Asia, Southeast Asia, eastern Australia, the east and west coast of North America, and parts of Europe have the highest BCR and NPV (Figure 5). Note that the protection standards (Figure 5a) are the same as the current protection standards (Figure 2d).






Figure 5: ‘Protection constant’ adaptation objective results of (a) protection standards; (b) BCRs; (c) total NPV; and (d) change in risk relative to GDP for RCP4.5/SSP2. Note that the protection standards (a) are the same as FLOPROS estimates. Regions with no data are indicated with grey colour.


In the ‘absolute risk constant’ adaptation objective (Figure 6), it is clear that dikes would need to be upgraded to have high protection standards (usually between 100 and 1000 years) in order to keep risk constant at current levels. The costs to achieve this are high (globally, more than twice as high as under the ‘protection constant’ adaptation objective) and therefore a lower number of sub-national regions (79%; 623) have a positive BCR, although this is still very high. In most sub-national regions, the risk relative to GDP decreases in the future if this adaptation objective is implemented, although 5% (38) of the sub-national regions show an increase in risk relative to GDP.





760 **Figure 6: ‘Absolute risk constant’ adaptation objective results of (a) protection standards; (b) BCRs; (c) total NPV; and (d) change**
 765 **in risk relative to GDP for RCP4.5/SSP2. Regions with no data are indicated with grey colour.**

In the ‘relative risk constant’ adaptation objective (Figure 7), the protection standards required are generally lower than in the ‘absolute risk constant’ adaptation objective. The highest protection standards required are found in East Asia and parts of North America. A similar number of sub-national regions have a BCR higher than 1 as is the case for ‘absolute risk constant’, namely 79% of the sub-national regions assessed. To keep relative risk constant or absolute risk constant some sub-national regions need to have a future protection standard that is higher than 1000-year (the highest return period assessed in this study). Because of this, the relative change in risk in the ‘Relative risk constant’ adaptation objective increases for 5% (36) of the regions assessed.









Figure 7: ‘Relative risk constant’ adaptation objective results of (a) protection standards; (b) BCRs; (c) total NPV; and (d) change in risk relative to GDP for RCP4.5/SSP2. Regions with no data are indicated with grey colour.

In the ‘optimize’ adaptation objective (Figure 8), the highest optimal protection standards are generally found in East Asia, Southeast Asia, South Asia, and the Gulf coast of the USA. High protection standards are also found in parts of Europe and other parts of the USA, parts of western and eastern Africa, some parts of South America, and south-eastern Australia. The highest change in protection standards compared to current are found in South Asia and Southeast Asia. In most sub-national regions, the benefits exceed the costs when upgrading protection standards (89%). However, in some sub-national regions the BCR is less than 1 (indicated with hatched lines). The highest values of NPV (Figure 8c) are found in parts of South and Southeast Asia, North America, and northwest Europe. While most sub-national regions show a positive return on investment, there is still an increase in relative risk in 32% of the sub-national regions assessed, under the ‘optimize’ adaptation objective.

In these cases, it is economically efficient to implement protection measures up to a certain level, yet the economic costs of keeping EAD as a percentage of GDP constant would exceed the avoided damages. Regions where this is especially the case include: Europe, North America, South America, Japan and Australia, as shown in Figure 8d. Many sub-national regions with decreases in relative risk can be found in South Asia, Southeast Asia, parts of the Gulf coast of the USA, New South Wales in Australia, several sub-national regions in Africa, and some parts of South America, among others. In these regions, the increase in risk is generally very high, which means that the costs of investment in protection are lower than the avoided damages relative to GDP. Generally, in these regions, protection standards and/or absolute dike heights increase the most.





Deleted:

Formatted: Caption

790 **Figure 8: ‘Optimize’ adaptation objective results of (a) optimal protection standards; (b) BCRs; (c) total NPV; and (d) change in risk relative to GDP for RCP4.5/SSP2. Regions where no optimal protection standards are found are indicated with hatched lines and regions with no data are indicated with grey colour.**

In the middle of the road scenario of RCP4.5/SSP2, where the world will face intermediate adaptation and mitigation challenges, we see that most of the sub-national regions assessed would economically benefit from adaptation. We further see that the adaptation objectives differ in changes in relative risk and the level of adaptation that would take place. For instance, in the ‘protection constant’ adaptation objective we see that although the protection standards stay the same, the relative risk increases for most sub-national regions. This can be explained by the increase of the severity and frequency of the flood hazard due to sea-level rise and subsidence, and the increase of exposure of assets due to socioeconomic change. Compared to the ‘optimize’ adaptation objective, the ‘protection constant’ adaptation objective under-protects in most sub-national regions. In the ‘absolute risk constant’ adaptation objective we see that relative risk decreases in most sub-national regions while protection standards increase greatly. Due to climate change, socioeconomic change and subsidence, we see an increase in GDP exposed to flooding. Therefore, protection standards must increase vastly in order to meet the same level of absolute risk. In this adaptation objective, most sub-national regions are over-protected compared to the ‘optimize’ adaptation objective. In the ‘relative risk constant’ adaptation objective, we see that some sub-national regions are over-protected while other sub-national regions, for instance in Southeast Asia are under-protected. The ‘optimize’ adaptation objective shows the most economically feasible results in terms of maximizing NPV, and has the highest BCR in most regions. In the fossil-fuel based scenario of RCP8.5/SSP5, where adaptation will face high challenges and costs (van Vuuren et al., 2014), we see that higher protection standards are required in order to keep risk constant and to maximize NPV (see Supplementary Figures S3-6). The results of the adaptation objectives can be used as a first proxy to indicate in which sub-national regions adaptation through

[structural measures may be economically feasible. Moreover, the results indicate regions where adaptation is needed in order to maximize NPV and which objectives are under or over protecting sub-national regions compared to the ‘optimize’ adaptation objectives. Due to the scope of this study, local scale models and assessments should be used for the design and implementation of individual adaptation measures.](#)

815

Deleted: .

3.4 Attribution of costs to different drivers of risk

In Figure 9, we show the percentage of the total costs of the ‘optimize’ adaptation objective (Figure 9a) that can be attributed to each of the following risk drivers: climate change (in this case sea-level rise) (Figure 9b); optimizing current protection standards (Figure 9c); socioeconomic change (Figure 9d); and subsidence (Figure 9e). The results are shown for the RCP4.5/SSP2 scenario and only for sub-national regions that have a BCR higher than 1 in the ‘optimize’ adaptation objective.

820

The total costs exceed US\$1 billion for 4% of the sub-national regions assessed and exceed US\$1 million for 87%. For most parts of the globe, climate change (in this case sea level rise) contributes the most to the costs of adaptation, exceeding 50% of the total costs in 98% of the sub-national regions (Figure 9a), and exceeding 90% of the total costs in 58% of the sub-national regions. However, the other drivers can also play an important role, but are dwarfed in absolute terms by the costs related to sea-level rise. For example, in South Asia, Southeast Asia, and East Africa optimizing to current conditions and socioeconomic change are important drivers and, in some cases, the most important driver. There are some other regional exceptions where climate change is not the most dominant driver of adaptation costs. Moreover, locally land subsidence due to groundwater extraction can cause huge flood problems and bring large costs in some areas (Dixon et al., 2006; Yin et al., 2013), but are not seen when aggregated to the sub-national regions of this study. However, there are a few regions where

825

subsidence is a more dominant driver (i.e. parts of India, China, Japan, and Taiwan). [The results show that climate change is not the most dominant driver in 4 of the 5 countries that have the highest share of future EAD if no adaptation takes place \(i.e. China, Bangladesh, India, and Indonesia\). Generally, the same patterns are found in the attribution results for the RCP8.5/SSP5 scenario, which can be found in the Supplementary Figure S7.](#)

830

Deleted: T

Deleted: 6




Figure 9: Attribution of costs overview for RCP4.5/SSP2 with (a) total costs; (b) attribution of sea-level rise (ATR_{SLR}); (c) attribution of current optimizing (ATR_{CUR}); (d) attribution of socioeconomic change (ATR_{SEC}); and (e) subsidence (ATR_{SUB}). Note that the attribution of SLR is on a different scale and regions with no data are indicated with grey colour.

Figure 10 shows the attribution of the costs for the same scenario and adaptation objective, aggregated to the World Bank regions. In all the regions (except South Asia), sea-level rise is the most dominant driver, accounting for between 27% (South Asia) and 79% (Europe & Central Asia) of the costs of adaptation. The costs of increasing dike height to achieve optimal protection under current conditions are highest in the Global South. This is especially the case for the East Pacific & Asia and South Asia regions, with values of 22% and 38% respectively. The relative contribution of socioeconomic change is largest in East Asia & Pacific, South Asia and Sub-Saharan Africa, with values of 20%, 26% and 27% respectively. Of all drivers, subsidence is the least dominant with values up to 9% (East Asia & Pacific) and 10% (Middle East & North Africa). Supplementary Figure S8 shows the attribution aggregated to the World Bank regions for RCP8.5/SSP5.

Deleted: .

Deleted: 7




Figure 10: Attribution of costs of adaptation for World Bank regions under the 'optimize' adaptation objective and RCP4.5/SSP2 for optimizing to current conditions (CUR), socio-economic change (SEC) subsidence (SUB), and sea-level rise (SLR).


3.5 Sensitivity analysis

855 In this section, we show the sensitivity of the results to the use of different: SSPs, sea-level rise projections, discount rates, and operation and maintenance (O&M) costs. In Table 2, we show results (of BCR) standardized to a baseline scenario with the following assumptions: RCP4.5, SSP2 (middle of the road), discount rate of 5%, and O&M of 1%. We employed a one-at-a-time sensitivity analysis, so for each row in the table only one parameter has changed, and the values shown are standardized by calculating the relative change. All associated BCRs for the standardized values shown in Table 2 are still higher than 1.

860 Globally, BCRs range between 45 and 119 for the different model runs (73 for the reference). At the global scale the BCRs are most sensitive to the use of the different SSPs and discount rates. They cause the largest changes in BCR, with standardized values of 0.44 and 2.17 found in South Asia and Sub-Saharan Africa. Differences in SLR input affect the BCR by a factor of up to 0.38. Europe & Central Asia and North America are the least sensitive to the changes in input parameters. The O&M costs show BCRs that are more in line with the reference model run, higher or lower values up to 0.18.

865 Table 2: Sensitivity analysis of model runs with different input parameters. BCRs are standardized to the model run with RCP4.5/SSP2, discount rate of 5%, and O&M costs of 1%. SLR low refers to sea-level rise using the 5th percentile and SLR high to the 95th percentile.

East Asia & Pacific	Europe & Central Asia	Latin America & Caribbean	Middle East & North Africa	North America	South Asia	Sub-Saharan Africa	Global



Deleted:

Formatted: Font color: Auto

Deleted: s

Deleted: s

Deleted: s

Deleted: s

Deleted: s

Formatted: Superscript

Formatted: Superscript

Reference BCR	90	99	13	77	29	199	35	73
<i>Sensitivity to SSP projection</i>								
SSP1	1.35	1.02	1.21	1.06	0.97	1.60	1.66	1.33
SSP3	0.66	0.88	0.73	0.75	0.76	0.45	0.45	0.65
SSP4	1.02	0.98	0.94	0.93	1.01	0.84	0.47	0.95
SSP5	1.70	1.11	1.52	1.26	1.19	2.15	2.20	1.64
<i>Sensitivity to SLR projection</i>								
SLR low	1.07	1.38	1.06	1.04	1.11	1.00	1.13	1.13
SLR high	0.93	0.74	0.92	0.85	0.89	0.97	0.92	0.86
<i>Sensitivity to discount rate</i>								
r 3%	1.55	1.13	1.61	1.45	1.38	1.79	1.76	1.50
r 8%	0.62	0.82	0.57	0.62	0.70	0.49	0.50	0.62
<i>Sensitivity to O&M rate</i>								
O&M 0.1%	1.14	1.12	1.16	1.10	1.15	1.18	1.16	1.14
O&M 2%	0.88	0.88	0.89	0.86	0.86	0.86	0.86	0.88

3.6 Comparison to previous studies

875 Hallegatte et al. (2013) performed a study on future flood risk for 136 major coastal cities. They estimated an EAD of US\$6 billion for current conditions, while in our study we find an EAD of US\$19.6 billion. Our estimates of EAD is higher, which is to be expected given that we estimate risk for all coastlines as opposed to 136 major coastal cities. Hallegatte et al. (2013) projected future risk increasing up to US\$60-63 billion if protection standards are kept constant by 2050. In our study we find an EAD of US\$84 billion by 2050 when keeping protection standards constant (RCP4.5/SSP2 scenario). If no adaptation is implemented in 2050, Hallegatte et al. (2013) estimate EAD over US\$1 trillion, where we find US\$1.1 trillion.

880 Hinkel et al. (2010) attributed adaptation costs to sea-level rise using dikes for the European Union. They estimated this to be between US\$2.6-3.5 billion. In our results we find values between US\$12.9 billion and US\$22.7 billion for the European Union for the scenarios RCP4.5 and RCP8.5 respectively. In a follow-up study, Hinkel et al. (2014) estimate global costs of protecting the coast with dikes. They estimate a range of US\$12-71 billion, while our study estimates the global costs of adaptation for the 'optimize' adaptation objective between US\$152 billion and US\$208 billion for the RCP4.5/SSP2 and RCP8.5/SSP5 respectively. It should be noted that Hinkel et al. (2010) and Hinkel et al. (2014) use a demand function for safety where dikes are raised following relative sea-level rise and socioeconomic development, while we optimize protection standards by maximizing NPV. Moreover, the scenarios used in the studies are different.

A recent study by Lincke & Hinkel (2018) found that it is economically feasible to invest in protection for 13% of the coast globally. Using their method they found a lower share of protected coastline compared to previous studies (Nicholls et al.,

890

Deleted: s

2008; Tol, 2002). In our study, we found that for the ‘optimize’ adaptation objective 698 out of the 784 sub-national regions have a BCR higher than 1, indicating that it is economically feasible to implement adaptation in many regions through raising dikes. In our study, the benefit-cost analysis is carried out at the sub-national scale, whereby dikes are only raised on coastal reaches where our transects show there to be potential hazard (inundation) and urban exposure. If we calculate the percentage of the entire global coastline for which this leads to dike heightening in our model with a BCR higher than 1, it amounts to 3.4% of the global coastline. This is lower than the value in Lincke & Hinkel (2018), but this can be explained by the fact that the distance between our transects is 1 kilometre horizontal resolution at the equator, whilst Lincke & Hinkel (2018) raise dikes along the coast of entire coastal segments, which have lengths ranging from 0.009 to 5213 kilometre, with a mean of 85 kilometre.

3.7 Limitations and future research

While our model scheme does not include dynamic inundation modelling, it does include resistance factors similar to those used by Vafeidis et al. (2019), in order to account for water-level attenuation. It therefore represents an advance on previous studies that have used planar inundation modelling methods (i.e. bathtub models). An improvement could be made by using a dynamic inundation modelling scheme (Vousdoukas et al., 2016), but at the cost of increased computing time. Another improvement can be made by including waves in our inundation modelling, which is found to be an important component in inundation modelling (Vousdoukas et al., 2017). The inundation modelling scheme can be further improved by increasing the resolution from 30” to a higher resolution in order to better understand local scale signals and patterns, since the scale of assessment and resolution of input data has a significant implication on flood risk model results (Wolff et al., 2016). However, we stress that this study aims to understand global flood risk and general patterns on the sub-national scale, and this study can be used as a first proxy indicating feasibility of adaptation through structural measures, such as dikes.

For this study, results are shown for the scenario RCP4.5/SSP2 and RCP8.5/SSP5 in supplementary information. The range of sea-level rise input values (between the 5th percentile of RCP4.5 and the 95th percentile of RCP8.5) cover a wide range of sea-level rise uncertainty (approximately 0.3 – 0.7m at the equator in the Atlantic Ocean). While in reality the effects of climate change will continue to rise beyond 2100 even if Paris Agreement is met (Clark et al., 2016), our study examines adaptation objectives until 2100. Results for all combinations of these two RCPs together with all five SSPs can be found in the supplementary data.

Several uncertainties exist on the cost calculation side. The first is the monetary value we assumed for the costs of dike heightening. Although we account for differences in costs between countries by using different construction factors and market exchange rates, in reality the costs might differ between regions and may be higher due to local conditions (both physical and socioeconomic). We also use a linear cost function for dike heightening. Using this linear cost function for large scale studies has been found a reasonable assumption according to (Lenk et al., 2017).

Another important uncertainty in this study is the current protection standards estimated with the FLOPROS modelling approach, as data on flood protection along the global coastlines are not available. These only provide a first order estimate of

925 current protection standards per sub-national region. In the Supplementary Figure S1, a validation of the coastal protection standards estimated with the FLOPROS modelling approach is provided. Values are shown for several locations for which reliable reported estimates of protection standards are available. These reported values are either shown as a range (minimum and maximum reported values) or a single value. Overall, the model performs well. The only location for which the reported values provide a range, and the FLOPROS model lies outside this range, is Durban. However, note that reported values are for the city of Durban, whilst the FLOPROS model value is for the state in which it is located. An improvement to this study could be made by, for instance, mapping flood protections globally by using Earth Observation-based methods.

In this study, several uncertainties exist with assumptions on expected damages per occupancy type. First, we assumed the percentage of occupancy type per grid cell to be the same for all locations, whilst in reality it is spatially heterogeneous, and secondly, we assumed the building density per occupancy type. An improvement could be made by using Machine Learning to improve accuracy of urban land cover and building types (Hecht et al., 2015; Huang et al., 2018). We also used depth-damage curves per occupancy type, but in reality, these curves also differ between buildings in these occupancy types. To further improve the exposure data of our framework, the Global Human Settlement layer (Pesaresi et al., 2016) can be used for high-resolution population mapping.

The sub-national regions where no adaptation objective shows a positive BCR, should not be interpreted that no adaptation to coastal flood risk should take place. In fact, other adaptation measures (or a combination of multiple measures) besides raising dikes might be more economically feasible in any regions studied, including those with BCRs higher than 1. In this study we only assumed grey infrastructure as adaptation measures, but there are also other measures to reduce flood risk. For instance, the vulnerability can be improved by wet or dry proofing buildings (Aerts et al., 2014) or people and assets can be moved to less flood prone areas in order to reduce the exposure to floods (McLeman and Smit, 2006). Lastly, several local studies show the benefits of nature-based or hybrid adaptation measures (Cheong et al., 2013; Jongman, 2018; Temmerman et al., 2013). Vegetation on the foreshore has a significant role in the breaking of waves (Shepard et al., 2011) and attenuates storm water levels (Zhang et al., 2012). An improvement could be made by including other adaptation measures besides grey infrastructure as adaptation measures.

4 Conclusion

950 In this study, four adaptation objectives for reducing (future) coastal flood risk through structural measures have been explored and a benefit-cost analysis has been performed on the sub-national scale for the entire globe. Furthermore, the costs of adaptation have been attributed to different drivers of flood risk: sea-level rise, socio-economic change, subsidence, and optimizing to current conditions. Globally, we find that EAD increases by a factor of 150 between 2010 and 2080, if we assume that no adaptation takes place, and find that 15 countries account for approximately 90% of this increase.

955 We find that all four adaptation objectives show high potential to reduce (future) coastal flood risk at the global scale in a cost-effective manner. The 'optimize' adaptation objective shows the highest NPV (more than US\$11 trillion) with a BCR of 76,

Deleted: 8

while the 'protection constant' adaptation objective shows the lowest NPV (US\$9.5 trillion) with a BCR of 67 for the RCP4.5/SSP2 scenario.

960 At the regional scale, we show that the adaptation objectives can be achieved with a BCR more than 1 for most of the sub-national regions. This ranges from 89% for the 'optimize' adaptation objective to 79% for the 'absolute risk constant' adaptation objective. However, we also show that under the 'optimize' adaptation objective, relative risk would still increase compared to current values in 32% of the sub-national regions assessed.

We assess the sensitivity of the results by performing a one-at-a-time sensitivity analysis to various assumptions and find that, given the uncertainties, implementing structural adaptation measures is a feasible solution to reduce (future) coastal flood risk. Although differences in BCR exist, we show that changes in parameters still result in positive BCRs (between 45 and 120 globally) for the 'optimize' adaptation objective.

Attributing the total costs for the 'optimize' adaptation objective, we find that sea-level rise contributes the most and exceeds 50% of the total costs in 98% of the sub-national regions assessed, and exceeds 90% of the total costs in 58% of the sub-national regions. However, the other drivers also play an important role, but are dwarfed in absolute terms by the total costs related to the attribution.

The results of this study can be used to highlight potential savings through adaptation at the sub-national scale. Clearly, local scale models and assessments should be used for the design and implementation of individual adaptation measures, but our results can be used as a first proxy indicating regions where adaptation through structural measures may be economically feasible. To increase the accessibility of the results to the risk community, results of this study will be integrated into the Aqueduct Global Flood Analyzer webtool (www.wri.org/floods).

Supplementary data availability. The results of this study for all RCP and SSP combinations for protection standards, change in risk relative to GDP, B:C ratio and NPV for all four adaptation objectives are available at: <https://doi.org/10.5281/zenodo.3475120>. Figures of the results of RCP8.5/SSP5 combination are available at the supplementary material.

Author contribution. TT, PJW and HdM conceived the study. All co-authors contributed to the development and design of the methodology. TT analysed the data and prepared the manuscript with contributions from all co-authors.

985 *Competing interest.* The authors declare no conflict of interest.

Acknowledgement. The research leading to these results received funding from: The Netherlands Organisation for Scientific Research (NWO) in the form of a VIDI grant (grant no. 016.161.324); the Aqueduct Global Flood Analyzer project, via subsidy 5000002722 from the Netherlands Ministry of Infrastructure and Water Management - the latter project is convened by the

World Resources Institute; and the Future Water Challenges 2 project, funded by the Netherlands Ministry of infrastructure and Water Management.

References

- 995 Aerts, J., Botzen, W. and De Moel, H.: Cost estimates of flood protection and resilience measures, *Ann. N. Y. Acad. Sci.*, 1294(39–48), 2013.
- Aerts, J. C. J. H., Botzen, W. J. W., Emanuel, K., Lin, N., de Moel, H. and Michel-Kerjan, E. O.: Evaluating flood resilience strategies for coastal megacities., *Science*, 344(6183), 473–5, doi:10.1126/science.1248222, 2014.
- Bos, A. J.: Optimal safety level for the New Orleans East polder; A preliminary risk analysis, 2008.
- Bouwman, A. F., Kram, T. and Klein Goldewijk, K.: Integrated modelling of global environmental change: an overview of
1000 Image 2.4. [online] Available from: www.mnp.nl/en, 2006.
- BPIE: Europe's Buildings under the Microscope - a country by country review of the energy performance of buildings, 2011.
- Bright, E.A., Coleman, P.R., Rose, A.N., Urban, M. L.: LandScan 2010 High Resolution Global Population Data Set [dataset], [online] Available from: <http://web.ornl.gov/sci/landscan/>, 2011.
- 1005 Brown, S., Nicholls, R. J., Goodwin, P., Haigh, I. D., Lincke, D., Vafeidis, A. T. and Hinkel, J.: Quantifying Land and People Exposed to Sea-Level Rise with No Mitigation and 1.5°C and 2.0°C Rise in Global Temperatures to Year 2300, *Earth's Futur.*, 6(3), 583–600, doi:10.1002/2017EF000738, 2018.
- Calero, J., Hendriksen, G., Dijkstra, J. and Lelij, A. van der: FAST MI-SAFE platform: Foreshore assessment using space technology, Deltares, Delft., 2017.
- Carrère, L. and Lyard, F.: Modeling the barotropic response of the global ocean to atmospheric wind and pressure forcing -
1010 comparisons with observations, *Geophys. Res. Lett.*, 30(6), doi:10.1029/2002GL016473, 2003.
- Cheong, S.-M., Silliman, B., Wong, P. P., van Wesenbeeck, B., Kim, C.-K. and Guannel, G.: Coastal adaptation with ecological engineering, *Nat. Clim. Chang.*, 3(9), 787–791, doi:10.1038/nclimate1854, 2013.
- Clark, P. U., Shakun, J. D., Marcott, S. A., Mix, A. C., Eby, M., Kulp, S., Levermann, A., Milne, G. A., Pfister, P. L., Santer, B. D., Schrag, D. P., Solomon, S., Stocker, T. F., Strauss, B. H., Weaver, A. J., Winkelmann, R., Archer, D., Bard, E., Goldner,
1015 A., Lambeck, K., Pierrehumbert, R. T. and Plattner, G.-K.: Consequences of twenty-first-century policy for multi-millennial climate and sea-level change, *Nat. Clim. Chang.*, 6(4), 360–369, doi:10.1038/nclimate2923, 2016.
- Dee, D. P., Uppala, S. M., Simmons, A. J., Berrisford, P., Poli, P., Kobayashi, S., Andrae, U., Balmaseda, M. A., Balsamo, G., Bauer, P., Bechtold, P., Beljaars, A. C. M., van de Berg, L., Bidlot, J., Bormann, N., Delsol, C., Dragani, R., Fuentes, M., Geer, A. J., Haimberger, L., Healy, S. B., Hersbach, H., Hólm, E. V., Isaksen, I., Kållberg, P., Köhler, M., Matricardi, M.,
1020 McNally, A. P., Monge-Sanz, B. M., Morcrette, J.-J., Park, B.-K., Peubey, C., de Rosnay, P., Tavalato, C., Thépaut, J.-N. and Vitart, F.: The ERA-Interim reanalysis: configuration and performance of the data assimilation system, *Q. J. R. Meteorol. Soc.*, 137(656), 553–597, doi:10.1002/qj.828, 2011.

- Delft3D-WES: Delft3D-WES User Manual., , 46 [online] Available from: https://content.oss.deltares.nl/delft3d/manuals/Delft3D-WES_User_Manual.pdf, 2019.
- 1025 Diaz, D. B.: Estimating global damages from sea level rise with the Coastal Impact and Adaptation Model (CIAM), *Clim. Change*, 137(1–2), 143–156, doi:10.1007/s10584-016-1675-4, 2016.
- Dixon, T. H., Amelung, F., Ferretti, A., Novali, F., Rocca, F., Dokka, R., Sella, G., Kim, S.-W., Wdowinski, S. and Whitman, D.: Subsidence and flooding in New Orleans, *Nature*, 441(7093), 587–588, doi:10.1038/441587a, 2006.
- EEA: Corine Land Cover 2012 seamless 100m raster database (Version 18.5), [online] Available from: <https://land.copernicus.eu/pan-european/corine-land-cover/clc-2012/>, 2016.
- 1030 Ericson, J. P., Vörösmarty, C. J., Dingman, S. L., Ward, L. G. and Meybeck, M.: Effective sea-level rise and deltas: Causes of change and human dimension implications, *Glob. Planet. Change*, 50(1–2), 63–82, doi:10.1016/J.GLOPLACHA.2005.07.004, 2006.
- Erkens, G. and Sutanudjaja, E. H.: Towards a global land subsidence map, *Proc. Int. Assoc. Hydrol. Sci.*, 372, 83–87, doi:10.5194/piahs-372-83-2015, 2015.
- 1035 Erkens, G., Bucx, T., Dam, R., De Lange, G. and Lambert, J.: Sinking coastal cities, in *Proceedings of the International Association of Hydrological Sciences*, vol. 372, pp. 189–198., 2015.
- GADM: GADM database of Global Administrative Areas, 2012.
- Galloway, D. L., Erkens, G., Kuniansky, E. L. and Rowland, J. C.: Preface: Land subsidence processes, *Hydrogeol. J.*, 24(3), 547–550, doi:10.1007/s10040-016-1386-y, 2016.
- 1040 de Graaf, I. E. M., van Beek, R. L. P. H., Gleeson, T., Moosdorf, N., Schmitz, O., Sutanudjaja, E. H. and Bierkens, M. F. P.: A global-scale two-layer transient groundwater model: Development and application to groundwater depletion, *Adv. Water Resour.*, 102, 53–67, doi:10.1016/J.ADVWATRES.2017.01.011, 2017.
- Güneralp, B., Güneralp, İ. and Liu, Y.: Changing global patterns of urban exposure to flood and drought hazards, *Glob. Environ. Chang.*, 31, 217–225, doi:10.1016/J.GLOENVCHA.2015.01.002, 2015.
- 1045 Haer, T., Botzen, W. J. W., van Roomen, V., Connor, H., Zavala-Hidalgo, J., Eilander, D. M. and Ward, P. J.: Coastal and river flood risk analyses for guiding economically optimal flood adaptation policies: a country-scale study for Mexico, *Philos. Trans. R. Soc. A Math. Phys. Eng. Sci.*, 376(2121), 20170329, doi:10.1098/rsta.2017.0329, 2018.
- Hallegatte, S., Green, C., Nicholls, R. J. and Corfee-Morlot, J.: Future flood losses in major coastal cities, *Nat. Clim. Chang.*, 1050 3(9), 802–806, doi:10.1038/nclimate1979, 2013.
- Hecht, R., Meinel, G. and Buchroithner, M.: Automatic identification of building types based on topographic databases – a comparison of different data sources, *Int. J. Cartogr.*, 1(1), 18–31, doi:10.1080/23729333.2015.1055644, 2015.
- Hinkel, J., Nicholls, R. J., Vafeidis, A. T., Tol, R. S. J. and Avagianou, T.: Assessing risk of and adaptation to sea-level rise in the European Union: an application of DIVA, *Mitig. Adapt. Strateg. Glob. Chang.*, 15(7), 703–719, doi:10.1007/s11027-010-9237-y, 2010.
- 1055 Hinkel, J., Nicholls, R. J., Tol, R. S. J., Wang, Z. B., Hamilton, J. M., Boot, G., Vafeidis, A. T., McFadden, L., Ganopolski,

- A. and Klein, R. J. T.: A global analysis of erosion of sandy beaches and sea-level rise: An application of DIVA, *Glob. Planet. Change*, 111, 150–158, doi:10.1016/J.GLOPLACHA.2013.09.002, 2013.
- Hinkel, J., Lincke, D., Vafeidis, A. T., Perrette, M., Nicholls, R. J., Tol, R. S. J., Marzeion, B., Fettweis, X., Ionescu, C. and
1060 Levermann, A.: Coastal flood damage and adaptation costs under 21st century sea-level rise., *Proc. Natl. Acad. Sci. U. S. A.*,
111(9), 3292–7, doi:10.1073/pnas.1222469111, 2014.
- Huang, B., Zhao, B. and Song, Y.: Urban land-use mapping using a deep convolutional neural network with high spatial
resolution multispectral remote sensing imagery, *Remote Sens. Environ.*, 214, 73–86, doi:10.1016/J.RSE.2018.04.050, 2018.
- Van Huijstee, J., Van Bommel, B., Bouwman, A. and Van Rijn, F.: Towards and Urban Preview: Modelling future urban
1065 growth with 2UP, Background Report, PBL, Den Haag., 2018.
- Huizinga, J., Moel, H. de and Szewczyk, W.: Global flood depth-damage functions: Methodology and the database with
guidelines, JRC Work. Pap., JRC105688, 2017.
- Jackson, L. P. and Jevrejeva, S.: A probabilistic approach to 21st century regional sea-level projections using RCP and High-
end scenarios, *Glob. Planet. Change*, 146, 179–189, doi:10.1016/j.gloplacha.2016.10.006, 2016.
- 1070 Jevrejeva, S., Grinsted, A. and Moore, J. C.: Upper limit for sea level projections by 2100, *Environ. Res. Lett.*, 9(10), 104008,
doi:10.1088/1748-9326/9/10/104008, 2014.
- Jongman, B.: Effective adaptation to rising flood risk, *Nat. Commun.*, 9(1), 1986, doi:10.1038/s41467-018-04396-1, 2018.
- Jongman, B., Ward, P. J. and Aerts, J. C. J. H.: Global exposure to river and coastal flooding: Long term trends and changes,
Glob. Environ. Chang., 22(4), 823–835, doi:10.1016/J.GLOENVCHA.2012.07.004, 2012.
- 1075 Jonkman, S. N., Hillen, M. M., Nicholls, R. J., Kanning, W. and van Ledden, M.: Costs of Adapting Coastal Defences to Sea-
Level Rise— New Estimates and Their Implications, *J. Coast. Res.*, 290, 1212–1226, doi:10.2112/JCOASTRES-D-12-
00230.1, 2013.
- Klein Goldewijk, K., Beusen, A. and Janssen, P.: Long-term dynamic modeling of global population and built-up area in a
spatially explicit way: HYDE 3.1, *The Holocene*, 20(4), 565–573, doi:10.1177/0959683609356587, 2010.
- 1080 Kooi, H., Bakr, M., de Lange G., den Haan E., Erkens, G.: A user guide to SUB-CR: A modflow land subsidence and aquifer
system compaction package that includes creep, 2018.
- Kriegler, E., Bauer, N., Popp, A., Humpenöder, F., Leimbach, M., Strefler, J., Baumstark, L., Bodirsky, B. L., Hilaire, J.,
Klein, D., Mouratiadou, I., Weindl, I., Bertram, C., Dietrich, J.-P., Luderer, G., Pehl, M., Pietzcker, R., Piontek, F., Lotze-
Campen, H., Biewald, A., Bonsch, M., Giannousakis, A., Kreidenweis, U., Müller, C., Rolinski, S., Schultes, A., Schwanitz,
1085 J., Stevanovic, M., Calvin, K., Emmerling, J., Fujimori, S. and Edenhofer, O.: Fossil-fueled development (SSP5): An energy
and resource intensive scenario for the 21st century, *Glob. Environ. Chang.*, 42, 297–315,
doi:10.1016/J.GLOENVCHA.2016.05.015, 2017.
- Lenk, S., Rybski, D., Heidrich, O., Dawson, R. J. and Kropp, J. P.: Costs of sea dikes – regressions and uncertainty estimates,
Nat. Hazards Earth Syst. Sci., 17(5), 765–779, doi:10.5194/nhess-17-765-2017, 2017.
- 1090 Lincke, D. and Hinkel, J.: Economically robust protection against 21st century sea-level rise, *Glob. Environ. Chang.*, 51, 67–

- 73, doi:10.1016/J.GLOENVCHA.2018.05.003, 2018.
- McGranahan, G., Balk, D. and Anderson, B.: The rising tide: assessing the risks of climate change and human settlements in low elevation coastal zones, *Environ. Urban.*, 19(1), 17–37, doi:10.1177/0956247807076960, 2007.
- McLeman, R. and Smit, B.: Migration as an Adaptation to Climate Change, *Clim. Change*, 76(1–2), 31–53, doi:10.1007/s10584-005-9000-7, 2006.
- 1095 Merkens, J.-L., Lincke, D., Hinkel, J., Brown, S. and Vafeidis, A. T.: Regionalisation of population growth projections in coastal exposure analysis, *Clim. Change*, 151(3–4), 413–426, doi:10.1007/s10584-018-2334-8, 2018.
- Meyer, V., Haase, D. and Scheuer, S.: Flood Risk Assessment in European River Basins—Concept, Methods, and Challenges Exemplified at the Mulde River, *Integr. Environ. Assess. Manag.*, 5(1), 17, doi:10.1897/IEAM_2008-031.1, 2009.
- 1100 Muis, S., Verlaan, M., Winsemius, H. C., Aerts, J. C. J. H. and Ward, P. J.: A global reanalysis of storm surges and extreme sea levels, *Nat. Commun.*, 7(1), 11969, doi:10.1038/ncomms11969, 2016.
- Muis, S., Verlaan, M., Nicholls, R. J., Brown, S., Hinkel, J., Lincke, D., Vafeidis, A. T., Scussolini, P., Winsemius, H. C. and Ward, P. J.: A comparison of two global datasets of extreme sea levels and resulting flood exposure, *Earth’s Futur.*, 5(4), 379–392, doi:10.1002/2016EF000430, 2017.
- 1105 Neumann, B., Vafeidis, A. T., Zimmermann, J. and Nicholls, R. J.: Future Coastal Population Growth and Exposure to Sea-Level Rise and Coastal Flooding - A Global Assessment, edited by L. Kumar, *PLoS One*, 10(3), e0118571, doi:10.1371/journal.pone.0118571, 2015.
- Nicholls, R., Hanson, S., Herweijer, C. and Patmore, N.: Ranking port cities with high exposure and vulnerability to climate extremes, [online] Available from: <https://www.oecd-ilibrary.org/content/workingpaper/011766488208> (Accessed 15 February 2019a), 2008.
- 1110 Nicholls, R. J., Tol, R. S. J. and Vafeidis, A. T.: Global estimates of the impact of a collapse of the West Antarctic ice sheet: an application of FUND, *Clim. Change*, 91(1–2), 171–191, doi:10.1007/s10584-008-9424-y, 2008b.
- O’Neill, B. C., Kriegler, E., Riahi, K., Ebi, K. L., Hallegatte, S., Carter, T. R., Mathur, R. and van Vuuren, D. P.: A new scenario framework for climate change research: The concept of shared socioeconomic pathways, *Clim. Change*, 122(3), 387–400, doi:10.1007/s10584-013-0905-2, 2014.
- 1115 O’Neill, B. C., Kriegler, E., Ebi, K. L., Kemp-Benedict, E., Riahi, K., Rothman, D. S., van Ruijven, B. J., van Vuuren, D. P., Birkmann, J., Kok, K., Levy, M. and Solecki, W.: The roads ahead: Narratives for shared socioeconomic pathways describing world futures in the 21st century, *Glob. Environ. Chang.*, 42, 169–180, doi:10.1016/j.gloenvcha.2015.01.004, 2017.
- Oppenheimer, M., Glavovic, B. C., Hinkel, J., van de Wal, R., Magnan, A. K., Biesbroek, R., Buchanan, M. K., Abe-Ouchi, A., Gupta, K., Pereira, J., Glavovic, B., Hinkel, J., van de Wal, R., Magnan, A., Abd-Elgawad, A., Cai, R., Cifuentes-Jara, M., DeConto, R., Pörtner, H., Roberts, D., Masson-Delmotte, V., Zhai, P., Tignor, M., Poloczanska, E., Mintenbeck, K., Alegría, A., Nicolai, M., Okem, A., Petzold, J., Rama, B. and Weyer, N.: Sea Level Rise and Implications for Low-Lying Islands, Coasts and Communities. In: *IPCC Special Report on the Ocean and Cryosphere in a Changing Climate* [H.-O. Pörtner, D.C. Roberts, V. Masson-Delmotte, P. Zhai, M. Tignor, E. Poloczanska, K. Mintenbeck, A. Poh Poh Wong., 2019.

- 1125 Pekel, J.-F., Cottam, A., Gorelick, N. and Belward, A. S.: High-resolution mapping of global surface water and its long-term changes, *Nature*, 540(7633), 418–422, doi:10.1038/nature20584, 2016.
- Pesaresi, M., Ehrlich, D., Florczyk, A. J., Freire, S., Julea, A., Kemper, T. and Syrris, V.: The global human settlement layer from landsat imagery, in *International Geoscience and Remote Sensing Symposium (IGARSS)*, vol. 2016-November, pp. 7276–7279, Institute of Electrical and Electronics Engineers Inc., 2016.
- 1130 Pickering, M. D., Wells, N. C., Horsburgh, K. J. and Green, J. A. M.: The impact of future sea-level rise on the European Shelf tides, *Cont. Shelf Res.*, 35, 1–15, doi:10.1016/J.CSR.2011.11.011, 2012.
- Pullen, T., Allsop, N. W. H., Bruce, T., Kortenhaus, A., Schüttrumpf, H. and Van der Meer, J. W.: *EurOtop, European Overtopping Manual - Wave overtopping of sea defences and related structures: Assessment manual*, also Publ. as Spec. Vol. *Die Küste* [online] Available from: <https://repository.tudelft.nl/islandora/object/uuid:b1ba09c3-39ba-4705-8ae3-f3892b0f2410/> (Accessed 5 December 2018), 2007.
- 1135 Pycroft, J., Abrell, J. and Ciscar, J.-C.: The Global Impacts of Extreme Sea-Level Rise: A Comprehensive Economic Assessment, *Environ. Resour. Econ.*, 64(2), 225–253, doi:10.1007/s10640-014-9866-9, 2016.
- Raftery, A. E., Zimmer, A., Frierson, D. M. W., Startz, R. and Liu, P.: Less than 2 °C warming by 2100 unlikely, *Nat. Clim. Chang.*, 7(9), 637–641, doi:10.1038/nclimate3352, 2017.
- 1140 Riahi, K., van Vuuren, D. P., Kriegler, E., Edmonds, J., O'Neill, B. C., Fujimori, S., Bauer, N., Calvin, K., Dellink, R., Fricko, O., Lutz, W., Popp, A., Cuaresma, J. C., KC, S., Leimbach, M., Jiang, L., Kram, T., Rao, S., Emmerling, J., Ebi, K., Hasegawa, T., Havlik, P., Humpenöder, F., Da Silva, L. A., Smith, S., Stehfest, E., Bosetti, V., Eom, J., Gernaat, D., Masui, T., Rogelj, J., Strefler, J., Drouet, L., Krey, V., Luderer, G., Harmsen, M., Takahashi, K., Baumstark, L., Doelman, J. C., Kainuma, M., Klimont, Z., Marangoni, G., Lotze-Campen, H., Obersteiner, M., Tabeau, A. and Tavoni, M.: The Shared Socioeconomic
- 1145 Pathways and their energy, land use, and greenhouse gas emissions implications: An overview, *Glob. Environ. Chang.*, 42, 153–168, doi:10.1016/J.GLOENVCHA.2016.05.009, 2017.
- Scussolini, P., Aerts, J. C. J. H., Jongman, B., Bouwer, L. M., Winsemius, H. C., De Moel, H. and Ward, P. J.: FLOPROS: an evolving global database of flood protection standards, *Nat. Hazards Earth Syst. Sci.*, 16(5), 1049–1061, doi:10.5194/nhess-16-1049-2016, 2016.
- 1150 Shepard, C. C., Crain, C. M. and Beck, M. W.: The Protective Role of Coastal Marshes: A Systematic Review and Meta-analysis, edited by J. Clifton, *PLoS One*, 6(11), e27374, doi:10.1371/journal.pone.0027374, 2011.
- Sutanudjaja, E. H., Van Beek, R., Wanders, N., Wada, Y., Bosmans, J. H. C., Drost, N., Van Der Ent, R. J., De Graaf, I. E. M., Hoch, J. M., De Jong, K., Karssenbergh, D., López López, P., Peßenteiner, S., Schmitz, O., Straatsma, M. W., Vannamettee, E., Wissler, D. and Bierkens, M. F. P.: PCR-GLOBWB 2: A 5 arcmin global hydrological and water resources model, *Geosci. Model Dev.*, 11(6), 2429–2453, doi:10.5194/gmd-11-2429-2018, 2018.
- 1155 Tebaldi, C., Strauss, B. H. and Zervas, C. E.: Modelling sea level rise impacts on storm surges along US coasts, *Environ. Res. Lett.*, 7(1), 014032, doi:10.1088/1748-9326/7/1/014032, 2012.
- Temmerman, S., Meire, P., Bouma, T. J., Herman, P. M. J., Ysebaert, T. and De Vriend, H. J.: Ecosystem-based coastal defence

Formatted: Dutch (Netherlands)

in the face of global change, *Nature*, 504(7478), 79–83, doi:10.1038/nature12859, 2013.

1160 Tol, R. S. J.: Estimates of the Damage Costs of Climate Change. Part 1: Benchmark Estimates, *Environ. Resour. Econ.*, 21(1), 47–73, doi:10.1023/A:1014500930521, 2002.

Tribett, W. R., Salawitch, R. J., Hope, A. P., Canty, T. P. and Bennett, B. F.: Paris INDCs, pp. 115–146, Springer, Cham., 2017.

United Nations Framework Convention on Climate Change: COP21 Paris agreement., 2015.

1165 United Nations Office for Disaster Risk Reduction: Sendai framework for disaster risk reduction 2015–2030, UNISDR, Geneva, Switzerland. [online] Available from: <http://www.unisdr.org/we/inform/publications/43291>, 2015.

United Nations Office for Disaster Risk Reduction: Report of the open-ended intergovernmental expert working group on indicators and terminology relating to disaster risk reduction, 2016.

Vafeidis, A. T., Schuerch, M., Wolff, C., Spencer, T., Merkens, J. L., Hinkel, J., Lincke, D., Brown, S. and Nicholls, R. J.:

1170 Water-level attenuation in global-scale assessments of exposure to coastal flooding: a sensitivity analysis, *Nat. Hazards Earth Syst. Sci.*, 19(5), 973–984, doi:10.5194/nhess-19-973-2019, 2019.

Vousdoukas, M. I., Voukouvalas, E., Mentaschi, L., Dottori, F., Giardino, A., Bouziotas, D., Bianchi, A., Salamon, P. and Feyen, L.: Developments in large-scale coastal flood hazard mapping, *Nat. Hazards Earth Syst. Sci.*, 16(8), 1841–1853, doi:10.5194/nhess-16-1841-2016, 2016.

1175 Vousdoukas, M. I., Mentaschi, L., Voukouvalas, E., Verlaan, M. and Feyen, L.: Extreme sea levels on the rise along Europe’s coasts, *Earth’s Futur.*, 5(3), 304–323, doi:10.1002/2016EF000505, 2017.

van Vuuren, D. P., Kriegler, E., O’Neill, B. C., Ebi, K. L., Riahi, K., Carter, T. R., Edmonds, J., Hallegatte, S., Kram, T., Mathur, R. and Winkler, H.: A new scenario framework for Climate Change Research: scenario matrix architecture, *Clim. Change*, 122(3), 373–386, doi:10.1007/s10584-013-0906-1, 2014.

1180 Ward, P. J., Strzepek, K. M., Pauw, W. P., Brander, L. M., Hughes, G. A. and Aerts, J. C. J. H.: Partial costs of global climate change adaptation for the supply of raw industrial and municipal water: a methodology and application, *Environ. Res. Lett.*, 5(4), 044011, doi:10.1088/1748-9326/5/4/044011, 2010.

Ward, P. J., Jongman, B., Weiland, F. S., Bouwman, A., Van Beek, R., Bierkens, M. F. P., Ligetvoet, W. and Winsemius, H. C.: Assessing flood risk at the global scale: Model setup, results, and sensitivity, *Environ. Res. Lett.*, 8(4), doi:10.1088/1748-9326/8/4/044019, 2013.

1185 Ward, P. J., Jongman, B., Aerts, J. C. J. H., Bates, P. D., Botzen, W. J. W., Diaz Loaiza, A., Hallegatte, S., Kind, J. M., Kwadijk, J., Scussolini, P. and Winsemius, H. C.: A global framework for future costs and benefits of river-flood protection in urban areas, *Nat. Clim. Chang.*, 7(9), 642–646, doi:10.1038/nclimate3350, 2017.

1190 Ward, P. J., Winsemius, H. C., Kuzma, S., Luo, T., Bierkens, M. F. P., Bouwman, A., de Moel, H., Diaz Loaiza, A., Eilander, D., Enghardt, J., Erkens, G., Gebremedhin, E., Iceland, C., Kooi, H., Ligetvoet, W., Muis, S., Scussolini, P., Sutanudjaja, E. H., van Beek, R., van Bommel, B., van Huijstee, J., van Rijn, F., van Wesenbeeck, B., Vatvani, D., Verlaan, M. and Tiggeoven, T.: Aqueduct Floods Methodology Technical Note, Washington, D.C., 2019.

Formatted: Dutch (Netherlands)

- 1195 Winsemius, H. C., Aerts, J. C. J. H., Van Beek, L. P. H., Bierkens, M. F. P., Bouwman, A., Jongman, B., Kwadijk, J. C. J.,
Ligtvoet, W., Lucas, P. L., Van Vuuren, D. P. and Ward, P. J.: Global drivers of future river flood risk, *Nat. Clim. Chang.*,
6(4), 381–385, doi:10.1038/nclimate2893, 2016.
- Wolff, C., Vafeidis, A. T., Lincke, D., Marasmi, C. and Hinkel, J.: Effects of Scale and Input Data on Assessing the Future
Impacts of Coastal Flooding: An Application of DIVA for the Emilia-Romagna Coast, *Front. Mar. Sci.*, 3, 41,
doi:10.3389/fmars.2016.00041, 2016.
- 1200 Yamazaki, D., Ikeshima, D., Tawatari, R., Yamaguchi, T., O'Loughlin, F., Neal, J. C., Sampson, C. C., Kanae, S. and Bates,
P. D.: A high-accuracy map of global terrain elevations, *Geophys. Res. Lett.*, 44(11), 5844–5853, doi:10.1002/2017GL072874,
2017.
- Yin, J., Yu, D., Yin, Z., Wang, J. and Xu, S.: Modelling the combined impacts of sea-level rise and land subsidence on storm
tides induced flooding of the Huangpu River in Shanghai, China, *Clim. Change*, 119(3–4), 919–932, doi:10.1007/s10584-013-
0749-9, 2013.
- 1205 van Zelst, V. T. M., Dijkstra, J. T., van Wesenbeeck, B. K., Eilander, D., Morris, E. P., Winsemius, H. C., Ward, P. J. and de
Vries, M. B.: Cutting the costs of coastal protection: how vegetation reduces global flood hazard, *Rev.*, 2019.
- Zhang, K., Liu, H., Li, Y., Xu, H., Shen, J., Rhome, J. and Smith, T. J.: The role of mangroves in attenuating storm surges,
Estuar. Coast. Shelf Sci., 102–103, 11–23, doi:10.1016/J.ECSS.2012.02.021, 2012.