

Spatialised flood resilience measurement in rapidly urbanized coastal areas with complex semi-arid environment in Northern Morocco

Narjiss Satour¹, Otmame Raji², Nabil El Moçayd³, Ilias Kacimi¹, Nadia Kassou¹

5 ¹ Geosciences, Water and Environment Laboratory, Mohammed V University in Rabat, Morocco.

²Geology & Sustainable Mining, University Mohammed 6 Polytechnic, Benguerir, Morocco.

³International Water Research Institute, University Mohammed 6 Polytechnic, Benguerir, Morocco.

Correspondence to: Narjiss SATOUR (narjiss.satour@gmail.com)

10 **1. Abstract.** Enhancing resilience is critical for coastal urban systems to cope with and minimize flood disaster risks. The global increase in the frequency of floods is a significant concern for many areas in Africa. With this regard, urban planners need accurate approaches to set up a standard for measuring the resilience to floods. In Morocco, this issue is still not fully covered by the scientific community, despite the obvious need for a new approach adapted to local conditions. This study applied a composite index and geographic information system approach to measure and map resilience to floods in three northern coastal municipalities. The approach is also based on a linear ranking of resilience parameters, offering a more optimal classification of spatial resilience variation. The findings allowed to identify specific areas with different resilience levels and revealed the relationship between urban dimensions and the flood resilience degree. This approach provides an efficient decision support tool to facilitate flood risk management, especially in terms of prioritization of protective actions.

Keywords: Resilience, floods, composite index, Africa, Morocco.

20 **2. Introduction**

Climate change is a major challenge for the development of African countries. Several studies highlighted the severe impact of global change in Africa (Bates et al., 2008). The pattern of precipitation (Born et al., 2008; Giorgi & Lionello, 2008; Paeth, 2011), temperature (Fisher, 2015), and evapotranspiration (Speth et al., 2010) are more likely to change, which will alter the hydrological cycle, in many regions causing a change in the occurrence of extreme events such as drought and flooding (Karanja et al., 2016), especially in arid and semi-arid areas.

In particular, coastal zones situated in semi-arid are considered among the most threatened areas by the increase of flood occurrence and rapid urbanization (Leal Filho et al., 2018). Population concentration impacts flooding. Consequently, as population growth increases, exposure to floods will be a real societal problem (Kundzewicz et al., 2014). 9642 persons died out of 19,939,000 affected by floods in Africa between 1993-2002 (Conway, 2009). Moreover, it is expected that coastal

30 African cities will experience a higher rate of population growth and urbanization over the 21st century (UN–Habitat,2008; Lutz & Samir, 2010; Neumann et al., 2015). The rapid coastal development will exacerbate the already high vulnerability of many African coastal areas (Hinkel et al., 2011) since coastal cities are the most developed urban areas in Africa with residential, industrial, commercial, educational, and military opportunities (UN–Habitat, 2015).

Morocco, situated in the North West of Africa, reveals a trend towards a decrease in average annual rainfall, as well as an
35 increase in average annual temperature (Hoffman et Vogel, 2008; Terink et al., 2013; El Moçayd et al., 2020). The intensity of floods will increase over time (Vicuña et al., 2011; Doocy et al., 2013; Roy et al., 2018) while the main economic activities are located in coastal zones, where 60 % of the total Moroccan population are living (Snoussi et al., 2009). During recent years, several new policies have been implemented (Barthel and Planel, 2010; Ducruet et al., 2011; Kanai and Kutz, 2011), to improve the economic growth of these areas and reduce the negative effect of local migration. In this regard, the main drivers of the
40 economy are based on tourism and free zones industries, which will increase the vulnerability of these zones to climate change (Perelli, 2018). Adaptation to climate change is an important factor to consider in order to achieve sustainability in such areas. As, the combinations of environmental change, demographic growth, and urban complexity challenges will put the urban environment under pressure (Marana et al., 2019). There are several ways to tackle adaptation issues limiting the impact of a climate-related disaster and especially flooding, which is considered the most challenging disaster (UNDRR, 2019). The
45 classical proposed methods to deal with such issues involve implementing structural systems (Plate, 2002; Papadopoulos et al., 2017; Bertilsson et al., 2019). Sizing these systems remain subject to ubiquitous uncertainty. Climate variability will affect the reliability of such complex coastal area systems. Therefore, adaptation should also focus on resilience (Sustainable Development Goals) (Chen and Leandro, 2019; Miguez and Verol, 2016), rather than only structural measures. Resilience approaches aim to understand and manage the capacity of a system to adapt, cope with, and shape uncertainty (Adger et al.,
50 2005; Folke et al., 2002).

Since the work of Holling (1973), where the resilience concept originates from the ecology field, the concept has gained increasing interest and recognition (Cretney, 2014; Weichselgartner and Kelman, 2014; Patel et al., 2017; Kontokosta and Malik, 2018). Resilience concept has been considered, in different ways, by various research fields: psychology (Westphal and Bonanno, 2007), geography (Pike, 2010; Cutter, 2010), archaeology (Redman, 2005), and physics (Cohen et al., 2000).
55 Recently including natural disasters, risk management, and climate change adaptation (Godschalk, 2003; Cutter et al., 2008; Gaillard, 2010; Nelson Adger& Brown, 2007; Serre et al., 2018, among others.

Within the context of disasters, and climate change, many definitions of the resilience concept have emerged. Some are focusing on the ability of system, community, or city to absorb disturbances, retaining the same basic structures and normal ways of functioning, with self-organization capacity, and adaption to stress and change (e.g. Pelling, 2003; Pendall et al.,2007,
60 IPCC, 2007;). The bouncing back to the original state (equilibrium) after a disaster is undesirable (Klein et al. 2003), social systems are in a continuous state of change. Adaptation to some changing trends (Paton &Johnston, 2006) or several states of equilibrium (Walker et al., 2004; Pendall et al., 2007), becomes one of the main characteristics of resilience depending on being prepared for the unprecedented and unexpected changes (Ahern,2011). This is determined by the capacity of the system

to organize itself, to learn from past disasters, and to improve risk reduction measures (UNISDR, 2015). Some previous work
65 (Meerow et al., 2016,) linked the concept to the temporal and spatial scales, considering resilience as the ability of urban
system components (ecological and socio-technical) to maintain or rapidly return to desired functions, adapting to change in
the face of disturbance and quickly transform systems that limit current or future adaptive capacity. Resilience has a systemic
property and implies greater consideration of the time variable (Reghezza, 2015). Furthermore, some works (Chen N, &
Graham P. 2011; Colding J., & Barthel S, 2013) describe the resilience of the system as the ability of short-term absorbing,
70 self-organizing, and long-term learning and adaptation. The abundance of definitions makes it difficult to have a common
concept (Carpenter et al., 2001). Therefore, set a resilience definition concept could be an appropriate basis.

In this work, the resilience of the urban system to floods is the capacity of urban-flooded areas to maintain the activities during
and after floods. Simply put, a resilient coastal urban area will be able to absorb the disaster (at an acceptable level) and adapt
to the changes. Besides, urban resilience is a complex and multidimensional concept (Sharifi, 2016). The resilience of the
75 urban system to floods includes several dimensions of an urban system. Social, economic, physical, natural, and institutional
dimensions equally important (Batica, 2015; Qasim et al., 2016). The social dimension explores flexibility, health status,
knowledge, while the economic dimension is related to the economic capacities, income resources, and connections devices
within the community. The physical dimension may include urban density, building materials, and infrastructure (Qasim et al.,
2016) or quantified based on physical indicators such as flood depth or flood duration extracted from flood simulation data
80 (Mugume et al., 2015; Chen and Leandro, 2019). Areas located at low elevations or near rivers are more sensitive to flood
disasters, which constitutes the natural component of resilience (Hung et al., 2016). Thus,, institutions efforts aiming at coping
with disasters through better planning, awareness programs prefer integrated approaches by considering all these dimensions
in the evaluation of resilience. This may help to have a global perspective , which will lead to create suitable management
tools that can be very useful in the decision-making process (Bertilsson et al., 2019). Supporting this decision-making process
85 on strategies, actions, and measures to be taken, planning for the long-, medium- and short-terms and assessing the progress,
start with the assessment of the current and expected future status of resilience, to know where urban resilient areas are, and
to identify their strengths and weaknesses (Cardoso et al., 2020).

Because of its multidimensional aspect, it remains challenging to quantify resilience (Bertilsson et al., 2019). Many works
have shown the need to have some metrics allowing to have some measure of resilience. Yet there is no consensus about a
90 single metric of evaluation, and the literature (e.g. Meerow et al., 2016; Asadzadeh et al., 2017; Rus et al., 2018) refers to the
need for measures. Furthermore, making resilience tangible and practical for cities, through a transition from theory to practice
is challenging (Kontokosta & Malik, 2018; Meerow et al., 2016). Quantitative approaches through composite indicators
provide a synthetic measurement of a complex, and) multidimensional phenomena (Changdeok et al., 2019). Those indicators
are developed based on the aggregation of multiple individual indicators (OECD, 2008). The choice of method to construct
95 composite indices dependent upon the type of problem, the nature of the data, and the goals (Nardo et al., 2005). Several
composite indices to assess resilience of urban areas and to compare their resilience levels within specific geographical regions
have been proposed in recent years (e.g. Sharifi et al., 2016; Asadzadeh et al., 2017). For example, the work of Cutter et al.

(2014) using BRIC (Baseline Resilience Indicators for Communities) as the first attempt to the operationalized version of the conceptual framework “DROP model (Cutter et al., 2008). Within a socio-ecological approach, BRIC was calculated for multi-hazard context. Among other analysts, Joerin et al., (2014) state CDRI (Climate Disaster Resilience Index) gauges the different capabilities needed for communities in an urban system to regain an equilibrium state after climate-related disasters such as cyclones, droughts, floods, and heatwaves. Following the same holistic spirit, this index was adopted in Climatic Hazard Resilience Indicators for Localities (CHRIL) (Hung et al., 2016). (Mayunga.2007) also proposed a Community Disaster Resilience Index (CDRI). All of those previous indicators were applied to quantify community resilience to multi natural hazards. (Qassim et al.2016) determined community resilience to a particular hazard “floods”, and specific community “urban areas”, as recently proposed also by Cariolet et al., (2019). Although, many particular indicators were developed for a specific case of urban resilience to a specific hazard like floods.

Based on time-dependent characteristics, FResI was constructed to assess future resilience responses relative to the present situation (Miguez and Verol. 2016). Further, Chen and Leandro (2019) quantified the flood resilience of households in urban areas by FRI (Flood Resilience Index) as a time-dependent method. More examples of specific indicators are available (Kotzee and Reyers, 2016) using Geographic Information Systems (GIS) and stressing the need to move towards diversifying resilience assessment approaches.

Regardless of several challenges associated with data quality and availability constraint (Moghadas et al., 2019; Cai et al., 2018), and standard procedure for composite indicator development (Asadzadeh et al., 2017), particular attention has been paid to composite indicators (Heinzlef et al., 2019a), regarding their ability to analyze the urban, social and technical resilience of a city. However, a lack of resilience measurement tools developed by local authorities and organizations in the developing countries was reported in a critical review by Sharifi.A., & Yamagata, Y. (2016).

The Mediterranean region will suffer from severe impact due to climate change (Tuel and Eltahir,2020). Particularly Morocco is mentioned as a hotspot for climate change in several works (Born et al. ,2008; Driouech et al. ,2009; Ouhamdouch & Bahir, 2017). Moreover, the seasonal distribution of the precipitation influence strongly the Mediterranean river hydrology (Thornes et al., 2009). Assessing the intensity of the impact, Regional Climate Models (RCM) simulations over this area, all agree that Morocco might experience an increase in temperature and a decrease in precipitation (Driouech et al., 2010). Which will have a severe impact on water (Bahir et al., 2020), and natural hazards (Satta et al., 2016), among others. Consequently, increasing resilience against flooding is, therefore, of utmost importance to achieve sustainability (Snoussi et al., 2008). However, a knowledge gap for a better understanding of resilience has been identified at national and local levels (Price, R.A. 2017) in Morocco. It is highly recommended to provide policymakers with a simple approach and ways to enhance resilience to floods in the local area (OCDE 2016).

The present study is the first attempt to provide a methodological way to measure flood resilience for Northern coastal municipalities in Morocco: Martil, M'diq and Fnideq. In this work, flood resilience refers to the resilience of these coastal urban areas (Martil, M'diq and Fnideq) to floods. These areas were selected because they show 18 hot spots highly exposed to floods (ABHL 2016). Moreover, the area is particularly highly vulnerable to multi-hazards types including floods (Karrouchi

et al., 2016; Taouri et al., 2017), sea-level rise (Niazi, 2007; Snoussi et al., 2010), and coastal erosion (Satta et al., 2016; Nachite, 2009). However, the littoral is nowadays very urbanized, and tourist activities are the main economic resources in the area (Anfuso et al., 2010).

135 **2. Methods: study area and index development**

2.1. Fnideq, M'diq, and Martil municipalities

Related to M'diq-Fnideq prefecture, Fnideq, M'diq and Martil municipalities have a population of “984hab/km²” (RGPH 2014). Precipitation regime characterized by seasonality, annual average rainfall of 679 mm (ABHL 2016). Rainfall variability is based on altitude and the geographic situation (Karrouchi et al., 2016). Rivers flowing into the Mediterranean Sea (Martil, 140 Mellah, Smir, Negro and Fnideq) drain slowly during the rainy months and highly in a short time during flash floods (Niazi, 2007). While, the frequency of flood events and related damages increased gradually over time (e.g. on 26 December 2000, Martil Floods have invaded more than 2400 ha in the Martil plain) (Fig.1). Urbanization is concentrated in coastal zones and puts pressure on coastal ecosystems with high touristic value (Snoussi et al.,2010). It is pitiable that municipalities are also vulnerable to multiple climate and non-climate hazards such as erosion and morphological changes (Satta et al., 2016).

145 **2.2. Theoretical comprehensiveness for composite index development**

To produce an aggregate measure of resilience, through manipulation of individual variables, constructing a “Composite indicator” is often applied. It is a mathematical combination of thematic sets of variables that represent different dimensions of a concept that cannot be fully captured by any individual indicator alone (Nardo et al., 2008). An indicator is a quantitative or qualitative measure derived from observed facts revealing the relative position of the phenomena being measured. “It can 150 illustrate the magnitude of change (a little or a lot) as well as the direction of change over time (up or down; increasing or decreasing)” (Cutter et al., 2010). Moreover, considerable attention is increasingly given to composite indices as useful tools for decision-making and public communication. They simplify and communicate easily the reality of complex situations (Freudenberg, 2003) and convey more precise information (Saisana et al.,2005). However, through different geographical contexts and scales, these indices may encompass many theoretical perspectives (Cutter et al.,2008). Also,the quality of the 155 framework, the data, and the used methodology can significantly influence the qualities of a composite index and the soundness of the messages that convey.

Flood Resilience Index is explored and calculated differently in several works. Kotzee and Reyers (2016) used PCA as a method to construct this index and define its component weights. For Batika (2015) It has been built taking into account different spatial scales and focusing on urban functions. Using time series indicators (event phase and recovery phase), Chen 160 and Leandro(2019) computed FRI at time t as the product of the recovery factor and the FRI at the previous time step $t-1$. By

defining resilience as time-dependent, based on two phases (event and recovery), Leandro et al., (2020) shown also the ability of the developed FRI for assessing climate change adaptation. Despite the already existing studies on flood resilience assessment, there is still a need to develop methods for a specific case of study, where data availability remains a challenge, and the need for a tangible and simple way to better understand resilience is increasing.

165

In this study, we adopt the specific Flood Resilience Index to quantify the resilience of coastal urban areas to floods. FRI was divided into four sub-indicators: Social, Physical, Economic, and Natural sub-indexes, so as to enable sufficient flexibility to include or not each sub-index in global composite index (Fig.2). Three indicators were chosen for each sub-index (Tab1) based on data availability and their contribution to persistence, recovery, or adaptive capacity (the main components of the adopted resilience definition): Households Density (HD), Illiteracy Rate (IR), and Vulnerable Individuals Indicator (VII) were taken into consideration as the mean indicators that affect the social resilience negatively and construct the social sub-index. The physical sub-index included the Old Buildings Rate (OBR), the Modernly Built Houses (MBH), and the Connection to Water Infrastructure (CWI). This sub-index is important because it improves the physical capacity of individual and common properties against floods, and thus minimizes their vulnerability degree. The Economic resilience sub-index also includes three indicators: Unemployment Rate (UR), Building Density (BD), and Communication Capacity (CC). Finally, Elevation (E), Stream Network Density (SND), and Distance from Depressions (DD) are the indicators selected to determine the natural resilience sub-index.

170

175

2.3. Selecting indicators: Scoring and classification

Based on their relevance, analytical, representativeness, and accessibility, 16 indicators (variables) were selected (Tab.1). The data used was mainly drawn from the National Population and Housing Census (RGPH, 2014). The Arc Hydro and Line Density modules of ArcGIS© were used to generate a stream network density from an ASTER digital elevation model (30 meters of spatial resolution), while Google high-resolution satellite imagery was used for digitizing the building area. This was converted firstly into points, and then their density was calculated using the ArcGIS© Point Density module.

180

2.4. Normalisation

Indicators integration into sub-indicators needs data normalization. Respecting the theoretical framework and the data characteristics, a Min-Max normalization was applied. Subsequently, each variable was normalized from 0 to 100 according to the following equations (1) and (2):

185

$$V^+ = \left(\frac{\text{real value} - \text{minimum value}}{\text{maximum value} - \text{minimum value}} \right) * 100 \quad (1)$$

$$V^{-} = \left(1 - \left(\frac{\text{real value} - \text{minimum value}}{\text{maximum value} - \text{minimum value}} \right) \right) * 100 \quad (2)$$

190 Equation (1) was applied for variables that positively influence resilience while Eq. (2) was applied to those that are negatively correlated with resilience. When the scores are attributed, each of these indicators was gridded and then a geodatabase was created to calculate the sub-indexes by using the GIS. Each sub-index is the mean value of all correspondent indicators.

2.5. Weighting and aggregation

The existing methods for determining weights are not always reflecting the priorities of decision-makers (Esty et al., 2005), which are subjective (Cutter et al., 2010). Equal-weighting is the most common for composite indices with several sub-
 195 indicators (OECD, 2008). Thus, several arguments listed by Greco et al., 2019 (“i” simplicity of construction, “ii” a lack of theoretical structure to justify a differential weighting scheme, “iii” no agreement between decision-makers, “iv” inadequate statistical and/or empirical knowledge, and, finally “v” alleged objectivity). Moreover, the weighting method selection depends on the local factors where the method is applied (Mayunga, 2007; Reisi et al., 2014). Allocating equal importance across
 200 different indicators is better suited when no knowledge exists about the interactions among the sub-indicators/indices and the corresponding composite index at the local scale (Cutter et al.2014; Asadzadehet al.2017). All variables are given equal weight (EW) in our case of study. The main reason is to allocate equal importance across indicators. Because of the lack of knowledge, and justification about the existing interactions among the sub-indicators and composite index at the local level, avoiding a large concentration of few indicators and making it is easy to communicate.

205 The simple method of aggregation supposed to be transparent and easy to understand, is a critical criterion for potential users (Cutter et al.,2010). All individual indicators have the same measurement unit. Therefore, using linear aggregations is preferred over geometric aggregation. The linear aggregation formula of the FRI takes the following form Eq. (3).

$$FRI = \frac{SRI+PRI+ERI+NRI}{4} \quad (3)$$

Social Resilience Index (SRI); Physical Resilience Index (PRI); Economical Resilience Index (ERI); Natural Resilience Index
 210 (NRI); Zero is considered as low resilience level, 100 as high resilience level, and 50 medium resilience level.

2.6. Links to other indicators

To assess the correlation between the composite index and corresponding sub-indices/variables, a statistical analysis was performed, using the program SPSS 23. Data presented as a mean and standard deviation (st.dev) were statistically analyzed using multi-variance to confront data of natural, physical, economic, and social conditions with the Flood Resilience Index.
 215 Furthermore, to identify which variables differ significantly between the three case-study sites. The significant differences

were distinguished by posthoc Tukey's Honestly Significant Difference (HSD) test at $p < 0.05$. The Spearman's rho coefficient was used for correlations between variables. Only significant correlation coefficients at a level of 0.05 are considered.

2.7. Visualization and validation

Particular attention has been paid to the visualization given its relevance in helping and enhancing interpretability. Maps facilitate further exploration of spatial data trends (Kotzee and Reyers, 2016). For that purpose, Geographic Information Systems (GIS) was adopted to visualize FRI and sub-indicators. After visualizing the composite index results, validation was the last step. Acting like a 'quality assurance', this step will highly reduce the possibilities to convey a misleading message (Saisana et al., 2005). Unfortunately such step is often skipped for the vast majority of the composite indices (OECD, 2008). External validation has been the most used to validate several indicator results (CDRI 2009, BRIC 2012, CDRI 2013, and BRIC 2014).

In our case, the validation based on actual outcomes of the municipalities is possible using cross-validation type. It was performed to test and compare the reliability of FRI results using the results of other studies interested in hydro-climatic hazards as suggested by Satta et al., (2016). This is possible through the opposite correlation between risk and resilience (Cutter et al., 2014; Sherrieb et al., 2010). Seeking optimization by considering social and economic pathways, and combining flood resilience and flood risk, measures can be effective against a broader range of hazards than when considering either method alone (Disse et al., 2020).

3. Results

3.1. Sub-indices

Each sub-index was observed separately to get additional insights about Flood resilience Index. For the social resilience (Fig. 3D), produced based on the three indicators of social resilience (Fig. 3A, B and C). The highest values of social resilience are more related to a few urban areas than rural and less developed sectors ones. In terms of mean value, the social resilience sub-index was higher in Martil (69.03 ± 11.24) followed by Fnideq and the coastal area of M'diq showing similar values (57.11 ± 9.26 and 57.17 ± 11.44 respectively).

Higher physical resilience scores (Figure 4A, B, C and D) are concentrated in the urban center areas with a spatial tendency towards the coastal area. Even though pockets of lower scores exist in the central area and some less developed sectors indicating low physical resilience levels. Therefore, the central area had a bit low level of physical resilience as compared to Fnideq, M'diq and Martil urban centres and the coastal zone (Fig. 4 D).

Results (Fig.5D) show a concentration of the low and moderate level of economic resilience in the three urban centers. However, this does not exclude that some coastal urban sectors showed high levels of Economic resilience sub-index. The overall map of Natural Resilience Index shows a spatial variability between the lowest and the medium level of NRI in the whole study area (Fig.6 D). However, the high level of natural resilience is more prevalent in areas with high altitudes, such as Capo-Negro (Fig.6 AC).

3.2. Total Flood Resilience Index

The results reveal a marked spatial variability of resilience to floods (Fig.7). Overall, 31% of the study area varies from low to very low, which equals 45 km² (Fig.8a). 43% of the studied area, which equivalent to 52 km², was classified as moderately resilient and only 17% of the studied area (17 km²) was classified as highly resilient and the remaining 3% with very high resilience. The central area shows the lowest levels of FRI, including sensitive coastal sites such as Smir Lagoon, Kabila beach, and Restinga beach. In contrast, M'diq and the North of Martil have relatively moderate to high values in terms of resilience to floods. However, the significant disparities between rural and urban areas, especially in terms of socioeconomics, highly influences the flood resilience index values.

In order to avoid any confusion related to flood management priorities between the rural and the urban areas. The resilience map corresponding to urban areas were extracted, and the index values using GIS were reclassified to have the priority areas without taking into account the rural part. Using this tool to overlay the spatial distribution of households (RGPH 2014) and FRI map, it turns out that 1151 households (around 2.4%) are in areas of very low resilience and more than 7800 households (about 16%) in low-resilience areas. On the other hand, 7402 households are in a high resilience situation, and only 177 can be qualified as very high resilient (Fig.8b).

3.3. Statistical analysis

In order to evaluate the contribution of the sub-dimensions (Social, Economic, Physical and natural dimensions) for the resilience analysis, the statistical relationship between the total Flood Resilience Index (FRI) and its sub-indices was estimated for each municipality (Tab.2).

The SRI is positively correlated to the FRI index in the three municipalities ($p < 0.001$), particularly in the urban areas where it is proven to be important as an FRI component. Regarding the ERI sub-index, it shows a moderate correlation at the Fnideq and Martil municipalities ($p < 0.01$), or even a low correlation at the M'diq level ($p < 0.05$). Unlike SRI and ERI, the correlation to the PRI sub-index is different from one municipality to another. It is strong at the level of Martil ($p < 0.001$), weak at the level of Fnideq ($p < 0.01$) and absent at the level of M'diq. In the case of the NRI sub-index, it displays a strong correlation at the level of Fnideq and moderate at the level of Martil and M'diq.

4. Discussion

275 Within the current context of global climate change associated with an increase of flood damage, the efficient use of available data is, in most cases, the primary source of judgment control decision-making for flood risk management (Ouma et al., 2014). Producing flood resilience maps has thus become a crucial issue for local flood management planners (Godschalk, 2003). However, these products require generally detailed knowledge about all resilience components in time and space to be effective. They should be designed in such a way that can help the decision-making by using ranking and prioritization process (Chitsaz et al., 2015). Accordingly, the choice of a good methodology to assess and quantify the resilience attains its utmost
280 importance and relevance. Indeed, the adopted methodological approach as well as the quality of the data has a significant influence on the obtained results, and hence on the final decision making (Suárez et al., 2016).

In this paper, the adopted methodology is adaptable according to the study case and the available data. Moreover, the adapted ranking process is based in a linear scoring, which offers the advantage to be more sensitive to changes compared to the usual methods based on assigning scores according to intervals (e.g. Angeon et al., 2015). It also provides a more reliable and
285 objective spatial comparison of resilience parameter values which will finally allow obtaining effective prioritization of resilient areas.

It should be noted that significant components for the resilience analysis have been considered and the obtained resilience map allowed to classify the study area according to four resilience degrees to floods: very low, low, moderate, and high.

The difference in the social resilience sub-index between urban and rural areas could be explained by the fact that human
290 development indicators are generally lower in rural and less developed areas, especially those related to school attendance and people vulnerability, which affect social resilience negatively. However, the difference in SRI between municipalities may occur because of the great growth rate of Martil municipality rather than Fnideq and M'diq (HCP, 2018)

The low physical resilience in the central area and the less developed sectors may exist because of the low population and urbanization (e.g. At the central area access to water infrastructure, as basic service is still low (Figure 4C). Unlike in the case
295 of the urban centers with high physical resilience scores.

Meanwhile, the high level of Economic resilience sub-index in some coastal urban sectors may be explained by tourism and economic activities. An expected result given the characteristics of the wealthy residents living there (Tempelhoff et al., 2009; Kotzee et Reyers. 2016). Unlike in the three urban centers having low and moderate economic resilience. That could be explained by the high unemployment rate “17.9 %”(HCP, 2018) and the high urban density. These findings support our
300 hypotheses and the suggestions from Cutter et al. (2010) and H.-C. Hung et al. (2016). Further, the results of (Irajifar et al. 2016) show that the association of high population density and high incomes make a recovery after disaster quicker.

The overall picture of natural resilience shows that all three municipalities have lower natural resilience. Martil had a bit low level of the NRI as compared to Fnideq and M'diq. This is because of the lowest values of elevation indicator and distance from depressions. The findings are fully corresponded to the existing literature (H.-C. Hung et al.,2016), supporting the
305 relationship between elevation, flood-prone areas, and the least resilience.

The areas with very low and low Flood Resilience Index seem to be generally associated with the areas showing unstable social conditions. This observation is confirmed by the statistical analysis, and studies (Godschalk, 2003; Cutter et al., 2010; Kotzee et Reyers, 2016; Moghadas et al., 2019) showing that social resilience is strongly correlated to flood resilience degree. Moreover, the disparities highlighted between rural and urban areas revealed that rural areas display the lowest resilience to floods.

Economic and natural resilience which is tightly linked in the sites, is the second most statistically significant indicators linked to the total FRI. Disparities between municipalities are less significant. This means that areas having low or moderate resilience to floods need equal attention (Qasim et al., 2016).

The risk and vulnerability-oriented studies (Niazi, 2007; Snoussi et al., 2010; Nejari, 2014; Satta et al., 2016) in the coastal area were used for validation. The results are consistent, showing that coastal sites such Restinga plain, kabila beach, Smir lagoon and Martil-Alila plain having a low resilience are highly vulnerable to the flash floods and sea-level rise impacts (Snoussi et al., 2010; Niazi, 2007; Satta et al., 2016). Considering all the output, this confirms that the flood resilience index is relatively valid and can be adapted and tested in other geographical areas. Moreover, this robustness analysis makes the FRI in this case of study support the idea that areas with higher vulnerability levels examined have lower resilience levels (H.-C. Hung et al., 2016).

In this context, there is a need to prioritize the actions contributing to enhancing the social and economic communities' levels. Providing support and strengthen actions promoting social and economic level in the municipalities.

Further, the statistical analysis shows a significant link between the natural characteristics and resilience degrees. In that situation, it is recommended to establish best practices and measures to avoid urban development in flooded areas and to provide more efforts to manage the risk of floods in urbanized areas, with a strong focus on the contingency plans in case of power or drinking water failure in the three municipalities.

Therefore, there is a need to incorporate disaster management education in college to explain hazards adaptation. Also, educate people through communication devices, seminars and workshops involve citizens to be aware of the damages and the climate change effects.

The obtained results highlight the importance of using a multidimensional approach to assess flood resilience. Furthermore, GIS is also highly recommended as a solution to complex situations and as a decision support tool that offers an interactive use and continuing improvement (Ouma et al., 2014; Mayunga, 2007).

5. Conclusion

Building and enhancing resilience to floods becomes critical, as the urban development in a coastal area in Africa is increasingly stressed. Especially for the coastal zones situated in semi-arid threatened areas. Nevertheless, in the local contexts of Morocco, where this study is the first attempt focusing on enhancing the understanding of resilience to floods highlighting the application of the tangible approach to summarize and present complex components linked to resilience to floods.

Flood resilience assessment was piloted using a composite index and a GIS. The spatial and statistical analysis gave further insights into the geographic distribution of FRI across Fnideq, M'diq and Martil municipalities. Moreover, clarify the presentation of a complex set of components linked in a reproducible way.

The findings indicate that different factors can vary spatial patterns of resilience to floods. The framework is flexible enough to allow the proposed index, in future work, to take into consideration the institutional component. Including the institutional component could advance our understanding of flood resilience, and provide useful results to suggest floods adaptation strategies in a coastal area. The robustness of flood resilience indicator was tested by comparing the results against additional case studies and operationalized measures of resilience. Some of the main limitation of the developed FRI are: starting with tackling the main limitations from considering real/simulate flood inundation maps, to integrating climatic data (flood data or flood simulation data). Besides, for robust validation, date of resilience assessment and validation tool date should be highlighted to take the specific changes in land covers between the two periods of time. Further work will use other methodologies developing FRI in the same coastal area, to provide further insights about indicators assessments and the relationships among flood resilience and flood risk.

Acknowledgments

The authors would like to thank the Office of the High Commission for Planning (HCP) and Hydraulic Basin Agency of Loukkos in Morocco for making their data available for our study. We acknowledge the inputs from the reviewers (including Dr. Leandro) and the editor as they have been very helpful to improve the quality of the present work. Special thanks are to Dr Mohammed BEN-DAOUED, Dr Mounir Ouzir and Mr Margaa Khalid for their meaningful insights provided.

References

- ABH: Hydraulic Basin Agency of Loukkos, Typology and inventory of sites at flooding risk ABHL2, www.abhloukkos.ma/abhl/index.php/fr/, 2016.
- Angeon, V., & Bates, S.: reviewing composite vulnerability and resilience indexes: A sustainable approach and application. *World Development*, 72, 140-162. <https://doi.org/10.1016/j.worlddev.2015.02.011>, 2015.
- Anfuso, G., Martinez, J. A., & Nachite, D.: Coastal vulnerability in the Mediterranean sector between Fnideq and M'diq (North of Morocco). *Co Ren de l'Aca bulgare des Sci, Géom. phy. Géomo.* 63 (4), 561-570, 2010.
- Andersson, E.: Urban landscapes and sustainable cities. *Ecology and Society* 11(1): 34. [online] URL: <http://www.ecologyandsociety.org/vol11/iss1/art34/>, 2006.
- Adger, W. N., Hughes, T. P., Folke, C., Carpenter, S. R., & Rockström, J.: Soc-eco Res.to. *Coa. disa. Sc*, 309(5737), 1036-1039. DOI: 10.1126/science.1112122, 2005.
- Ahern, J.: From fail-safe to safe-to-fail: Sustainability and resilience in the new urban world. *Landscape and urban Planning*, 100(4), 341-343. doi.org/10.1016/j.landurbplan.2011.02.021, 2011.

- Asadzadeh, A., Kötter, T., Salehi, P., & Birkmann, J.: Operationalizing a concept: The systematic review of composite indicator building for measuring community disaster resilience, *Inter J. of Dis. Risk Red*, 25, 147-162. <https://doi.org/10.1016/j.ijdr.2017.09.015>, 2017.
- Bahir, M., Ouhamdouch, S., Ouazar, D. & El Moçayd, N.: Climate change effect on groundwater characteristics within semi-arid zones from western Morocco. *Groundwater for Sustainable Development*, 100380. doi.org/10.1016/j.gsd.2020.100380 , 2020.
- 375 Barthel, P. A., & Planel, S., Tanger-Med and Casa-Marina, prestige projects in Morocco: new capitalist frameworks and local context. *Built environment*, 36(2), 176-191. <https://doi.org/10.2148/benv.36.2.176> ,2010.
- Batica, J. Methodology for flood resilience assessment in urban environments and mitigation strategy development. Diss. Université Nice Sophia Antipolis, 2015.
- Bates, B.C., Z.W. Kundzewicz, S. Wu and J.P. Palutikof, Eds.,: *Climate Change and Water*. Technical Paper of the Intergovernmental Panel on Climate Change, IPCC Secretariat, Geneva, 210 pp. ISBN: 978-92-9169-123-4, 2008.
- 380 Bertilsson, L., Wiklund, K., de Moura Tebaldi, I., Rezende, O. M., Veról, A. P., & Miguez, M. G.: Urban flood resilience—A multi-criteria index to integrate flood resilience into urban planning. *J of Hy*, 573, 970-982. <https://doi.org/10.1016/j.jhydrol.2018.06.052>, 2019.
- Born, K., Fink, A. H., & Paeth, H. . Dry and wet periods in the northwestern Maghreb for present day and future climate conditions. *Meteorologische Zeitschrift*, 17(5), 533-551. doi. 10.1127/0941-2948/2008/0313, 2008.
- 385 Cai, H., Lam, N. S., Qiang, Y., Zou, L., Correll, R. M., & Mihunov, V.: A synthesis of disaster resilience measurement methods and indices. *International journal of disaster risk reduction*, 31, 844-855. doi.org/10.1016/j.ijdr.2018.07.015, 2018.
- Cardoso, M.A.; Brito, R.S.; Pereira, C.; Gonzalez, A.; Stevens, J.; Telhado, M.J. RAF Resilience Assessment Framework—A Tool to Support Cities’ Action Planning. *Sustainability* 12, 2349. doi.org/10.3390/su12062349, 2020.
- 390 Carpenter, S., Walker, B., Anderies, J. M., & Abel, N.: From metaphor to measurement: resilience of what to what?. *Ecosystems*, 4(8), 765-781. doi.org/10.1007/s10021-001-0045-9, 2001.
- Cariolet, J. M., Vuillet, M., & Diab, Y.: Mapping urban resilience to disasters—A review. *Sustainable cities and society*, 51, 101746. doi.org/10.1016/j.scs.2019.101746, 2019.
- Changdeok Gim, Clark A. Miller, Paul W. Hirt: The resilience work of institutions *Environ. Sci. Policy*, 97, pp. 36-43, [10.1016/j.envsci.2019.03.004](https://doi.org/10.1016/j.envsci.2019.03.004), july, 2014.
- 395 Chen, N., & Graham, P.: Climate change as a survival strategy: soft infrastructure for urban resilience and adaptive capacity in Australia’s coastal zones. In *Resilient Cities* (pp. 379-388). Springer, Dordrecht, [doi.10.1007/978-94-007-0785-6_38](https://doi.org/10.1007/978-94-007-0785-6_38), 2011.
- Chen, K. F., & Leandro, J.: A conceptual time-varying flood resilience index for urban areas: Munich city. *Water*, 11(4), 830. doi.org/10.3390/w11040830 ,2019.
- 400 Chitsaz, N., & Banihabib, M. E. Comparison of different multi criteria decision-making models in prioritizing flood management alternatives. *Water Resources Management*, 29(8), 2503-2525. doi.org/10.1007/s11269-015-0954-6, 2015.
- Cohen, R., Erez, K., Ben-Avraham, D., & Havlin, S. Resilience of the internet to random breakdowns. *Physical review letters*,

- PhysRevLett.85.4626 85(21), 4626. <https://doi.org/10.1103/>, 2000.
- Colding, J., & Barthel, S.: The potential of 'Urban Green Commons' in the resilience building of cities. *Ecological economics*, 86, 156-166. <https://doi.org/10.1016/j.ecolecon.2012.10.016>, 2013.
- 405 Conway, G. The science of climate change in Africa: impacts and adaptation. Grantham Institute for Climate Change Discussion Paper, 1, 24. <http://www.ask-force.org/web/Global-Warming/Convay-Science-Climate-Change-Africa-2008.pdf> , 2009.
- Cretney Raven. Resilience for Whom? Emerging Critical Geographies of Socio-ecological Resilience. *Geography Compass* 410 8/9 (2014): 627–640, 10.1111/gec3.12154, 2014.
- CRED, E. EM-DAT. In: The OFDA/CRED International Disaster Database, Université Catholique de Louvain, Brussels Belgium. www.emdat.be, 2010.
- Cutter, S. L., Barnes, L., Berry, M., Burton, C., Evans, E., Tate, E., & Webb, J.: A place-based model for understanding community resilience to natural disasters. *Global environmental change*, 18(4), 598-606. 415 doi.org/10.1016/j.gloenvcha.2008.07.013, 2008.
- Cutter, S. L., Burton, C. G., & Emrich, C. T. Disaster resilience indicators 517 for benchmarking baseline conditions. *Journal of Homeland Security and Emergency Management*, 7(1). doi.org/10.2202/1547-7355.1732, 2010.
- Cutter, S. L., Ash, K. D., & Emrich, C. T: The geographies of community disaster resilience. *Global environmental change*, 29, 65-77. <https://doi.org/10.1016/j.gloenvcha.2014.08.005>, 2014.
- 420 Disse, M., Johnson, T. G., Leandro, J., & Hartmann, T.: Exploring the relation between flood risk management and flood resilience. *Water Security*, 9, 100059. doi.org/10.1016/j.wasec.2020.100059, 2020.
- Driouech, F., Déqué, M., & Mokssit, A.: Numerical simulation of the probability distribution function of precipitation over Morocco. *Climate dynamics*, 32(7-8), 1055-1063. doi.org/10.1007/s00382-008-0430-6, 2009.
- Driouech, F., Déqué, M., & Sánchez-Gómez, E.: Weather regimes—Moroccan precipitation link in a regional climate change 425 simulation. *Global and Planetary Change*, 72(1-2), 1-10. doi.org/10.1016/j.gloplacha.2010.03.004, 2010.
- Doocy, S., Daniels, A., Packer, C., Dick, A., & Kirsch, T. D. The human impact of earthquakes: a historical review of events 1980-2009 and systematic literature review. *PLoS Currents*, 5. <https://doi.org/10.1371/currents.dis.67bd14fe457f1db0b5433a8ee20fb833>, 2013.
- Ducruet, C., Mohamed-Chérif, F., & Cherfaoui, N.: Maghreb port cities in transition: the case of Tangier. *Portus Plus*, 1 (1), 430 <http://www.reteonline.org/fhshs-00553040f>, 2011.
- El Moçayd, Nabil, Suchul Kang, and Elfatih A. B. Eltahir. "Climate change impacts on the Water Highways project in Morocco." *Hydrology and Earth System Science*, 24, 3, 1467-1483. © The Author(s) <https://hdl.handle.net/1721.1/125159>, 2020.
- Esty, D. C., Levy, M., Srebotnjak, T., & De Sherbinin, A.: Environmental sustainability index: Benchmarking national 435 environmental stewardship. New Haven: Yale Center for Environmental Law & Policy, 47-60. [doi: 10.1017/S1355770X05002275](https://doi.org/10.1017/S1355770X05002275), 2005.

- Fisher, M., Abate, T., Lunduka, R. W., Asnake, W., Alemayehu, Y., & Madulu, R. B. . Drought tolerant maize for farmer adaptation to drought in sub-Saharan Africa: Determinants of adoption in eastern and southern Africa. *Climatic Change*, 133(2), 283- 299 . DOI 10.1007/s10584-015-1459-2.2015.
- 440 Freudenberg, M. : « Indicateurs composites de performances des pays : Examen critique », Documents de travail de l'OCDE sur la science, la technologie et l'industrie, n° 2003/16, Éditions OCDE, Paris, <https://doi.org/10.1787/405566708255>, 2003.
- Folke, C., Carpenter, S., Elmqvist, T., Gunderson, L., Holling, C. S., & Walker, B. : Resilience and sustainable development: building adaptive capacity in a world of transformations. *AMBIO: A J of the human environment*, 31(5), 437-440. [dx.doi.org/10.1579/0044-7447-31.5.437](https://doi.org/10.1579/0044-7447-31.5.437),2002.
- 445 Gaillard, J. C. Vulnerability, capacity and resilience: perspectives for climate and development policy. *Journal of International Development: The Journal of the Development Studies Association*, 22(2), 218-232. <https://doi.org/10.1002/jid.1675>. 2010.
- GIORGI, Filippo et LIONELLO, Piero. Climate change projections for the Mediterranean region. *Global and planetary change*, vol. 63, no 2-3, p. 90-104.[doi:10.1016/j.gloplacha.2007.09](https://doi.org/10.1016/j.gloplacha.2007.09). , 2008.
- Godschalk, D. R. Urban hazard mitigation: creating resilient cities. *Natural hazards review*, 4(3), 136-143. [doi.org/10.1061/\(ASCE\)1527-6988\(2003\)4:3\(136\)](https://doi.org/10.1061/(ASCE)1527-6988(2003)4:3(136)), 2003.
- 450 Greco, S., Ishizaka, A., Tasiou, M., & Torrisi, G.: On the methodological framework of composite indices: A review of the issues of weighting, aggregation, and robustness. *Social Indicators Research*, 141(1), 61-94. , 2019.
- HCP, Haut-Commissariat Au Plan. Monographie de la préfecture de M'diq-Fnideq, Direction régionale de Tanger-Tétouan-al Hoceima. Kingdom of Morocco. 2018.
- 455 Heinzlef, C., Becue, V., & Serre, D.: Operationalizing urban resilience to floods in embanked territories–Application in Avignon, Provence Alpes Côte d’azur region. *Safety science*, 118, 181-193. doi.org/10.1016/j.ssci.2019.05.003, 2019.
- Hinkel, J. “Indicators of vulnerability and adaptive capacity”: towards a clarification of the science–policy interface. *Global Environmental Change*, 21(1), 198-208. <https://doi.org/10.1016/j.gloenvcha.2010.08.002>, 2011.
- Hoffman, T., & Vogel, C.: Climate change impacts on African rangelands. *Rangelands*, 30(3), 12-17, [doi.org/10.2111/1551-501X\(2008\)30\[12:CCIOAR\]2.0.CO;2](https://doi.org/10.2111/1551-501X(2008)30[12:CCIOAR]2.0.CO;2) , 2008.
- 460 Holling, C. S. Resilience and stability of ecological systems. *Annual review of ecology and systematics*, 4(1), 1-23. <http://www.jstor.org/stable/2096802>, 1973.
- Hung, H. C., Yang, C. Y., Chien, C. Y., & Liu, Y. C. Building resilience: Mainstreaming community participation into integrated assessment of resilience to climatic hazards in metropolitan land use management. *Land Use Policy*, 50, 48-58. doi.org/10.1016/j.landusepol.2015.08.029, 2016.
- 465 Leal Filho, W., Balogun, A. L., Ayal, D. Y., Bethurem, E. M., Murambadoro, M., Mambo, J.,... & Mugabe, P. Strengthening climate change adaptation capacity in Africa-case studies from six major African cities and policy implications. *Environmental Science & Policy*, 86, 29-37. <https://doi.org/10.1016/j.envsci.2018.05.004>, 2018.
- Leandro, J., Chen, K. F., Wood, R. R., & Ludwig, R.: A scalable flood-resilience-index for measuring climate change adaptation: Munich city. *Water Research*, 173, 115502, doi.org/10.1016/j.watres.2020.115502, 2020.
- 470

- Leila Irajifar Neil Sipe Tooran Alizadeh: The impact of urban form on disaster resiliency: a case study of Brisbane and Ipswich, Australia, *International Journal of Disaster Resilience in the Built Environment*, Vol. 7 Iss 3 pp. <http://dx.doi.org/10.1108/IJDRBE-10-2014-0074>, 2016.
- 475 Lutz, W., & KC, S.: Dimensions of global population projections: what do we know about future population trends and structures? *Philosophical Transactions of the Royal Society B: Biological Sciences*, 365(1554), 2779-2791. [doi.org/10.1098/rstb.2010.0133](http://dx.doi.org/10.1098/rstb.2010.0133), 2010.
- Joerin, J., Shaw, R., Takeuchi, Y., & Krishnamurthy, R. The adoption of a climate disaster resilience index in Chennai, India. *Disasters*, 38(3), 540-561. <https://doi.org/10.1111/disa.12058>, 2014.
- 480 Kanai, M., & Kutz, W.: Entrepreneurialism In The Globalising City-Region Of Tangier, Morocco. *Tijdschrift voor economische en sociale geografie*, 102(3), 346-360 [doi.org/10.1111/j.1467-9663.2010.00622.x](http://dx.doi.org/10.1111/j.1467-9663.2010.00622.x), 2011.
- Karrouchi.M, Ouazzani.M, Touhami.M, Oujidi.M, and Chourak.M. : “Mapping of flooding risk areas in the Tangier-Tetouan region: Case of Martil Watershed (Northern Morocco),” *International Journal of Innovation and Applied Studies*, vol. 14, no. 4, pp. 1019–1035. <http://www.ijias.issr-journals.org/>, 2016.
- 485 Kontokosta, C. E., & Malik, A: The Resilience to Emergencies and Disasters Index: Applying big data to benchmark and validate neighborhood resilience capacity. *Sustainable cities and society*, 36, 272-285. <https://doi.org/10.1016/j.scs.2017.10.025>, 2018.
- Kotzee, I., & Reyers, B. Piloting a social-ecological index for measuring flood resilience: A composite index approach. *Ecological Indicators*, 60, 45-53. <https://doi.org/10.1016/j.ecolind.2015.06.018>, 2016.
- Kundzewicz, Z. W., Kanae, S., Seneviratne, S. I., Handmer, J., Nicholls, N., Peduzzi, P., ... & Muir-Wood, R. Flood risk and climate change: global and regional perspectives. *Hydrological Sciences Journal*, 59(1), 1
- 490 28. <https://doi.org/10.1080/02626667.2013.857411>. 2014.
- Marana P, Eden C, Eriksson H, Grimes C, Hernantes J, Howick S, Labaka L, Latinos V, Lindner R, Majchrzak T, Pyrko I, Radianti J, Rankin A, Sakurai M, Sarriegi JM, Serrano N, Towards a resilience management guideline—Cities as a starting point for societal resilience, *Sustainable Cities and Society* , doi.org/10.1016/j.scs.2019.101531, 2019.
- 495 Mayunga, J. S. Understanding and applying the concept of community disaster 603 resilience: a capital-based approach. *Summer academy for social vulnerability and resilience building*, 1, 16. www.ucursos.cl/usuario/3b514b53bcb4025aaf9a6781047e4a66/mi_blog/r/11._Joseph_S._Maynga.pdf, 2007.
- Meerow, S., Newell, J. P., & Stults, M. : Defining urban resilience: A review. *Landscape and urban planning*, 147, 38-49. <http://dx.doi.org/10.1016/j.landurbplan.2015.11.011>, 2016.
- 500 Miguez, M. G., & Veról, A. P.: A catchment scale Integrated Flood Resilience Index to support decision making in urban flood control design. *Environment and Planning B: Urban Analytics and City Science*, 44(5), 925-946. [doi.org/10.1177/0265813516655799](http://dx.doi.org/10.1177/0265813516655799), 2016.
- Moghadas, M., Asadzadeh, A., Vafeidis, A., Fekete, A., & Kötter, T. A multi-criteria approach for assessing urban flood resilience in Tehran, Iran. *International Journal of Disaster Risk Reduction*, 35, 101069. doi.org/10.1016/j.ijdrr.2019.101069, 2019.

- 505 Mugume, S. N., Gomez, D. E., Fu, G., Farmani, R., & Butler, D. A global analysis approach for investigating structural resilience in urban drainage, *Water Research* . doi.org/10.1016/j.watres.2015.05.030, 2015.
- Nachite, D. : Le developpement touristique du littoral de la region Tanger-Tetouan: une evolution vers des scenarios non desirables ? In: Domínguez Bella, S., Maate, A.(Eds.), *Geología y Geoturismo en la Orilla Sur Del Estrecho De Gibraltar*. MCN - UCACadiz, ISBN 978-84-9828-224-5, pp. 59e78. 2009.
- 510 Nardo, M., M. Saisana, A. Saltelli and S. Tarantola: *Handbook on Constructing Composite Indicators: Methodology and User Guide*. Paris,France: OECD Publishing, citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.958.2519&rep=rep1&type=pdf 2008.
- Nejjari.,A.: Vulnérabilité environnementale et planification urbaine, états des lieux : cas du littoral M'diq-F, *Revue AFN Maroc*, N° : 12-14, 2014.
- 515 Nelson, D. R., Adger, W. N., & Brown, K. Adaptation to environmental change: contributions of a resilience framework. *Annu. Rev. Environ. Resour.*, 32, 395-419. https://doi.org/10.1146/annurev.energy.32.051807.090348, 2007.
- Neumann, B., Vafeidis, A. T., Zimmermann, J., & Nicholls, R. J.: Future coastal population growth and exposure to sea-level rise and coastal flooding-a global assessment. *PloS one*, 10(3), e0118571.doi.org/10.1371/journal.pone.0118571, 2015.
- Niazi. S. Evaluation des impacts des changements climatiques et de l'élévation du niveau de la mer sur le littoral de Tétouan (Méditerranée occidentale du Maroc) : Vulnérabilité et adaptation, Phd thesis. Mohamed V, Rabat, Maroc <http://toubkal.imist.ma/handle/123456789/1774>, 2007.
- Karanja Ng'ang'a, S., Bulte, E. H., Giller, K. E., McIntire, J. M., & Rufino, M. C.: Migration and self-protection against climate change: a case study of Samburu County, Kenya. *World Development*, 84, 55-68, doi.org/10.1016/j.worlddev.2016.04.002, 2016.
- 525 Klein, R. J., Nicholls, R. J., & Thomalla, F. : Resilience to natural hazards: How useful is this concept?. *Global environmental change part B: environmental hazards*, 5(1), 35-45. doi.org/10.1016/j.hazards.2004.02.001, 2003.
- Lutz, W., & Samir, K. C: Dimensions of global population projections: what do we know about future population trends and structures? <https://doi.org/10.1098/rstb.2010.0133>, 2010.
- OCDE, Organisation de coopération et de développement économiques, 'Rapport sur la gestion-des-risques-maroc-principaux-résultats.<http://www.oecd.org/fr/gov/risques/gestion-des-risques-maroc-principaux-resultats.pdf>, 2016.
- 530 Ouhamdouch, S., & Bahir, M.: Climate change impact on future rainfall and temperature in semi-arid areas (Essaouira Basin, Morocco). *Environmental Processes*, 4(4), 975-990. doi.org/10.1007/s40710-017-0265-4, 2017.
- Ouma, Y., & Tateishi, R.: Urban flood vulnerability and risk mapping using integrated multi641 parametric AHP and GIS: methodological overview and case study assessment. *Water*, 6(6), 1515-1545. <https://doi.org/10.3390/w6061515>, 2014.
- 535 Paeth, H., Hall, N. M., Gaertner, M. A., Alonso, M. D., Moumouni, S., Polcher, J., .. & Gaye, A. T. : Progress in regional downscaling of West African precipitation. *Atmospheric science letters*, 12(1), 75-82. doi.org/10.1002/asl.306. 2011.
- Pagano, A., Pluchinotta, I., Giordano, R., & Vurro, M.: Drinking water supply in resilient cities: Notes from L'Aquila earthquake case study. *Sustainable cities and society*, 28, 435-449. doi.org/10.1016/j.scs.2016.09.005, 2017.

- Pallard, B., Castellarin, A., & Montanari, A.: A look at the links between 645 drainage density and flood statistics. *Hydrology and Earth System Sciences*, 13(7), 1019- 1029. <https://doi.org/10.5194/hess-13-1019-2009>, 2009.
- Papadopoulos, T., Gunasekaran, A., Dubey, R., Altay, N., Childe, S. J., & Fosso-Wamba, S. : The role of Big Data in explaining disaster resilience in supply chains for sustainability. *Journal of Cleaner Production*, 142, 1108-1118. <https://doi.org/10.1016/j.jclepro.2016.03.059>, 2017.
- Patel, S. S., Rogers, M. B., Amlôt, R., & Rubin, G. J.: What do we mean by “community resilience”? A systematic literature review of how it is defined in the literature. *PLoS currents*, 9. <https://doi.org/10.1371/currents.dis.db775aff25efc5ac4f0660ad9c9f7db2>, 2017.
- Pelling, M.: *The vulnerability of cities: natural disasters and social resilience*. Earthscan, ISBN 1853838306 , 2003.
- Perelli, C. A. R. L. O : Case Study Morocco: Mediterranean Morocco, a Vulnerable Development Called into Question. In *Global Climate Change and Coastal Tourism. Recognizing Problems, Managing Solutions and Future Expectations*. CABI International, ISBN 9781780648453 (ePDF), 2018.
- Pendall, R., Foster, K. A., & Cowell, M.: *Resilience and Regions: Building Understanding of the Metaphor*. Retrieved from <https://escholarship.org/uc/item/4jm157sh> , 2007.
- Pike, A., Dawley, S., & Tomaney, J.: Resilience, adaptation and adaptability. *Cambridge journal of regions, economy and society*, 3(1), 59-70. doi.org/10.1093/cjres/rsq001, 2010.
- Plate, E.J.: Flood risk and flood management. *Journal of Hydrology*, 267(1-2), 2-11. [https://doi.org/10.1016/S0022-1694\(02\)00135-X](https://doi.org/10.1016/S0022-1694(02)00135-X), 2002.
- Price, R.A.: *Climate change and stability in North Africa*. K4D Helpdesk Report 242. Brighton, UK: Institute of Development Studies. <https://opendocs.ids.ac.uk/opendocs/handle/20.500.12413/13489>, 2017.
- Qasim, S., Qasim, M., Shrestha, R. P., Khan, A. N., Tun, K., & Ashraf, M.: Community resilience to flood hazards in Khyber Pukhthunkhwa province of Pakistan. *International Journal of Disaster Risk Reduction*, 18, 100106. <https://doi.org/10.1016/j.ijdr.2016.03.009>, 2016.
- Redman, C. L. Resilience theory in archaeology. *American Anthropologist*, 107(1), 70-77. doi.org/10.1525/aa.2005.107.1.070, 2005.
- Reisi, M., Aye, L., Rajabifard, A., & Ngo, T.: Transport sustainability index: Melbourne case study. *Ecological Indicators*, 43, 288-296. <https://doi.org/10.1016/j.ecolind.2014.03.004>, 2014.
- RGPH, Recensement Général de la Population et de l’Habitat. https://rgph2014.hcp.ma/downloads/Publications-RGPH-2014_t18649.html, 2014.
- Reghezza-Zitt, M., Lhomme, S., & Provitolo, D. : Defining Resilience: When the Concept Resists. In *Resilience Imperative* (pp. 1-27). Elsevier. doi.org/10.1016/B978-1-78548-051-5.50001-2, 2015.
- Roy, P.T., El Moçayd, N., Ricci, S. et al.: Comparison of polynomial chaos and Gaussian process surrogates for uncertainty quantification and correlation estimation of spatially distributed open-channel steady flows. *Stoch Environ Res Risk Assess* 32, 1723–1741, [doi: 10.1007/s00477-017-1470-4](https://doi.org/10.1007/s00477-017-1470-4), 2018.


- Rus, K.Kilar, V., &Koren, D. Resilience assessment of complex urban systems to natural disasters: a new literature review. *International journal of disaster risk reduction*.<https://doi.org/10.1016/j.ijdrr.2018.05.015>, 2018.
- 575 Sanabria-Fernandez, J. A., Lazzari, N., & Becerro, M. A.: Quantifying patterns of resilience: What matters is the intensity, not the relevance, of contributing factors. *Ecological Indicators*, 107, 105565. doi.org/10.1016/j.ecolind.2019.105565, 2019.
- Saisana, M., Saltelli, A., & Tarantola, S.: Uncertainty and sensitivity analysis techniques as tools for the quality assessment of composite indicators. *Journal of the Royal Statistical Society: Series A (Statistics in Society)*, 168(2), 307-323. doi.org/10.1111/j.1467-985X.2005.00350.x, 2005.
- 580 Satta, A., Snoussi, M., Puddu, M., Flayou, L., &Hout, R.: An index-based method to assess risks of climate-related hazards in coastal zones: The case of Tetouan. *Estuarine, Coastal and Shelf Science*, 175, 93-105.<https://doi.org/10.1016/j.ecss.2016.03.021>, 2016.
- Serre, D., Barroca, B., Balsells, M., & Becue, V.: Contributing to urban resilience to floods with neighbourhood design: the case of Am Sandtorkai/Dalmannkai in Hamburg. *Journal of Flood Risk Management*, 11, S69-S83. doi.org/10.1111/jfr3.12253, 2018.
- 585 Sharifi, A., & Yamagata, Y. :On the suitability of assessment tools for guiding communities towards disaster resilience, *Inter J of Disr Risk Re*, 18, 115-124. <http://dx.doi.org/10.1016/j.ijdrr.06.006>, 2016.
- Sherrieb, K., Norris, F. H., & Galea, S.: Measuring capacities for community resilience. *Social indicators research*, 99(2), 227-247.[doi 10.1007/s11205-010-9576-9](https://doi.org/10.1007/s11205-010-9576-9), 2010.
- 590 Suárez, M., Gómez-Baggethun, E., Benayas, J., &Tilbury, D.: Towards an urban resilience Index: a case study in 50 Spanish cities. *Sustainability*, 8(8), 774.<https://doi.org/10.3390/su8080774>, 2016.
- Snoussi, M., Ouchani, T., Khouakhi, A., & Niang-Diop, I.: Impacts of sea-level rise on the Moroccan coastal zone: quantifying coastal erosion and flooding in the Tangier Bay. *Geomorphology*, 107(1-2), 32-40. doi.org/10.1016/j.geomorph.2006.07.043, 2009.
- 595 Snoussi, M., Niazi, S., Khouakhi, A., &Raji, O. Climate change and sea-level rise: a GIS694 based vulnerability and impact assessment, the case of the Moroccan coast. *Geomatic Solutions for Coastal Environments Book*. Nova Publishers, ISBN 978-1-61668-140-1, 2010.
- Speth, P., Christoph, M., & Diekkrüger, B.: Impacts of global change on the hydrological cycle in West and Northwest Africa. Springer Science & Business Media. [Doi.10.1007/978-3-642-12957-5](https://doi.org/10.1007/978-3-642-12957-5), 2010.
- 600 Taouri.O , El Ghammat.A , HILAL.I., stitou. J , Hassani Zerrouk. M, Drraz. C.: Flood management: Case of the city of M'diq and Fnideq. *JOWSET*, (02), N°02, 259-264, [http p:// revues.imist.ma/?journal = JOWSET](http://revues.imist.ma/?journal=JOWSET), 2017.
- Tempelhoff, J., Hoag, H., Ertsen, M., Arnold, E., Bender, M., Berry, K., ... & Ur, J.: Where has the water come from? [10.1007/s12685-009-0003-6](https://doi.org/10.1007/s12685-009-0003-6), 2009.
- Terink Wilco,Walter Willem Immerzeel and Peter Droogers ,: Climate change projections 715 of precipitation and reference evapotranspiration for the Middle East and Northern 716 Africa until 2050. *Int. J. Climatol.* 33: 3055–3072 (2013). [doi: 10.1002/joc.3650](https://doi.org/10.1002/joc.3650), 2013.

- Thornes JB.: Land degradation. In: Woodward JC (ed) *The physical geography of the Mediterranean*. Oxford University Press, Oxford, pp 563–581, 2009.
- Tuel, A., & Eltahir, E. A. B.: Why Is the Mediterranean a Climate Change Hot Spot?. *Journal of Climate*, 33(14), 5829-5843. doi.org/10.1175/JCLI-D-19-0910.1, 2020.
- 610 UNISDR, Sendai Framework for Disaster Risk Reduction <https://www.unisdr.org/we/coordinate/sendai-framework/> 2015, (Accessed: 28-Jan-2016).
- UN-Habitat , "Cities at risk from rising sea levels", in UN-Habitat, *State of the World's Cities 2008/2009*, Earthscan, London , 224 pages, pages 140-155. 2008.
- 615 UN-Habitat , *Habitat III*, U. N.: Issue papers 22–informal settlements. In *United Nations Conference on Housing and Sustainable Urban Development*. New York. 2015.
- UNDRR. *Global Assessment Report on Disaster Risk Reduction*; United Nations Office for Disaster Risk Reduction (UNDRR): Geneva, Switzerland, 2019
- Vicuña, S., Dracup, J. A., & Dale, L.: Climate change impacts on two high-elevation hydropower systems in California. *Climatic Change*, 109(1), 151-169. doi.org/10.1007/s10584-011-0301-8, 2011.
- 620 Walker, B., Holling, C. S., Carpenter, S. R., & Kinzig, A.: Resilience, adaptability and transformability in social–ecological systems. *Ecology and society*, 9(2). <http://www.ecologyandsociety.org/vol9/iss2/art5> , 2004.
- Weichselgartner, J., & Kelman, I.: Challenges and opportunities for building urban resilience. *A/Z ITU Journal of the Faculty of Architecture*, 11(1), 20-35. <https://discovery.ucl.ac.uk/id/eprint/1437000>, 2014.
- 625 Westphal, M., & Bonanno, G. A.: Posttraumatic growth and resilience to trauma: Different sides of the same coin or different coins? *Applied Psychology*, 56(3), 417-427. doi.org/10.1111/j.1464-0597.2007.00298.x, 2007.

630

635

640



655 **Figure 2: Procedure used to assess flood resilience in the three municipalities**

Dimensions	Indicators	Description, effect on resilience & justification
<i>Social</i> (SD)	Households Density (HD)	Cities with higher building density in developing countries tend to be densely populated, with many areas that have grown fast, (Andersson, 2006), often with insufficient infrastructure, resulting in environmental degradation and high damaging floods. Studies have found that high resilient sites had low population density (Sanabria-Fernandez et al., 2019).
	Illiteracy Rate (IR)	The persons who have never learned to read. That can make the emergency and public awareness processes challenging. (Cutter et al., 2010)
	Vulnerable Individuals Indicator (VII)	It refers to all vulnerable people (0-14 year olds, 60 year olds and disabled people) who can creates hindrances in mobility during floods and operations of evacuation (Hung et al., 2016; Qasim et al.,2016).
<i>Physical</i> (PD)	Old Buildings Rate (OBR)	Is the percentage of buildings that are over 50 years old, it expresses the fragility that increases with building materials age.
	Modernly Built Houses (MBH)	Based on the building material factor (by Reinforced concrete and bricks with mortar) modernly built houses will suffer less exterior damage during floods events in the local state (Cutter et al., 2010).

	Connection to Water Infrastructure (CWI)	The rate of connection to the sewage system and drinking water distribution strength resilience community (Cutter et al., 2010). A not being guaranteed access to water during and after emergency (Pagano et al., 2017) will aggravate the situation.
<i>Economic</i> (ED)	Unemployment Rate (UR)	It expresses the decrease in the individual economic capacity. Unemployed people are faced with difficulties related to their disability to recover or rebuild their damaged property (Cutter et al., 2010; Sherrieb et al., 2010).
	Building Density (BD)	It reflects the concentration of building per area. People are more concentrated in low quality urban housing, infrastructure and services the impact of natural disaster is higher (Pallard et al., 2009).It was selected based in the fact that an area with high building density is less resilient to floods.
	Communication Capacity (CC)	Is the rate of persons having communication devices (Television, Mobile phone and Internet).It express communication facilities availability , during, after and before flood hazards. strengthen resilience (Cutter et al., 2010).
<i>Natural</i> (ND)	Elevation (E)	It was selected based on the fact that lands with low elevation, are more risked to flooding and exposed to damages compared to high elevation areas.
	Stream Network Density (SND)	It describes the degree of drainage network development and was recognised to be significantly linked with the formation of flood flows (Pallard et al., 2009).
	Distance from Depressions (DD)	It expresses the distance from flood-prone areas or flood risk areas (ABH databases 2016) including natural depressions of high flow accumulation.

660 **Table 1: Indicators descriptions selected to assess the flood resilience in Fnideq, M'diq and Martil area; (compiled from different sources)**






Figure 4: Spatial distribution of A: Old Buildings Rate, B: Brick Houses Rate, C: Connection to water infrastructure and D: Physical Resilience Index (obtained from © Google map image in 2018).



675

Figure 5: Spatial distribution of A: Unemployment Rate, B: Building Density 2017, C: Communication Capacity and D: Economic Resilience Index (obtained from © Google map image in 2018)




680 **Figure 6: Spatial distribution of A: Elevation, B: Stream Network Density, C: Distance from Depressions and D: Natural Resilience Index (obtained from © Google map image in 2018)**

		SRI	ERI	PRI	NRI
FRI	Fnideq	0.643 ^{***}	0.441 ^{**}	0.378 [*]	0.650 ^{***}
	Martil	0.764 ^{***}	0.425 ^{**}	0.589 ^{***}	0.470 ^{**}
	M'diq	0.800 ^{***}	0.408 [*]	-	0.544 ^{**}

*p<0.05; **p<0.01; ***p<0.001.

Table 2: Spearman's rho Correlation between the total Flood Resilience Index (FRI) and its dimensions.



685

Figure 7: Distribution of Total Flood Resilience Index. (obtained from © Google map image in 2018)





Figure 8: a) Total Flood Resilience scores distribution according to the surface of the study area; b) Total Flood Resilience scores distribution according to Households numbers in the study area.