Nat. Hazards Earth Syst. Sci. Discuss., https://doi.org/10.5194/nhess-2019-432-AC1, 2020 © Author(s) 2020. This work is distributed under the Creative Commons Attribution 4.0 License.



NHESSD

Interactive comment

Interactive comment on "A model for interpreting the deformation mechanism of reservoir landslides in the Three Gorges Reservoir area, China" by Zongxing Zou et al.

Zongxing Zou et al.

tanghm@cug.edu.cn

Received and published: 29 July 2020

Dear Editor and Reviewer, Thank you for editor's efforts on dealing our manuscript and reviewer's constructive comments on this manuscript. We have studied these comments carefully and made point-by-point corrections, which have enabled us to improve the manuscript. Now we present point-by-point response to reviewer's comments, followed by the revised manuscript. The revised portions are marked in RED in new manuscript (MS). Below we list every comment received (in italics), followed by our response in regular font.

General comment 1. As a whole, the manuscript is valuable and presents robust data

Printer-friendly version



for publication. However, some parts of the manuscript are completely useless and uncorrect from a theoretical point of view, while some other parts require modifications. Therefore, this reviewer suggests a strong re-structuring of the manuscript as well as an improvement of the parts that need corrections. English is generally fine and no significant typing errors have been detected. Response: Thanks for reviewer's comments and suggestions. 2. In the introduction section, the authors should better describe, from a theorical point of view, the problem of rapid drawdown and rainfall infiltration in the landslide equilibrium, and in particular the role of permeability of the landslide soils and the rate of drawdown. Is this problem related to the type of the soils involved or not? Response: Yes, the problem is related to the type of the soils; landslides with lower permeability are more susceptible to be affected by the drawdown. We now add content as reviewer suggested to describe the effect of rapid drawdown and landslide permeability on landslide stability (new Lines: 61-65). The added contents are as below: These phenomena are more obvious in the landslides with lower permeability and in the situations of rapid drawdown and heavy rainfall. In the low permeability landslide, the groundwater is not easy to be discharged from the slope in the process of rapid drawdown and rainfall infiltration, which results in the formation of pressure difference between inside and outside of the landslide and reduces the stability of the landslide. 3. In the driving-locking model (Section 2), the authors do not completely account for the general equilibrium of the landslide mass, since they reduce all the equilibrium condition to the single unit vertical slice without considering the inter-slice forces, which do have a role in the equilibrium of the single slice. This is uncorrect, since it affects the location of the locking section. All this section, and the equations here proposed, seems to be a neglection of the slice methods historically proposed in the limit equilibrium approach and in general of the equilibrium theory (the problem being undetermined from a statical point of view and the need of integrative equations to balance unknowns- equations. . .). Moreover, in the limit equilibrium analysis proposed by the authors in the following sections, they use the Morgenstern-Price method, which is a well-known rigorous method and of course takes into account the inter-slice

NHESSD

Interactive comment

Printer-friendly version



forces. Therefore, the first part of the manuscript is not in agreement with the approach followed in the second part. This reviewer suggests to completely remove Section 2 from the manuscript and eventually to extend the second part (seepage and LE analysis) by including new field or analytical data and relative discussion. Response: Yes, the limit equilibrium method has developed from simplified limit equilibrium methods to rigorous limit equilibrium (LE) methods, and we agree with reviewer that a rigorous LE method would give more precise result about the location of the locking section. But we still choose the simplified limit equilibrium method for analysis here for following reasons. The locking section is defined as the lower-front part of the slide mass, where each unit vertical slice (Fig. 3) can be self-stabilized under its self-weight. In the unit vertical slice of locking section, the difference between the forces on the two vertical sides is very tiny because the width of the unit vertical slice is very small, and the slide surface underlying the lower-front part of the slide mass is relatively gentle; so the interslice forces were ignored for convenience of analysis. Moreover, the second reviewer says "Interestingly, they concluded that the boundary is near the thickest part of the landslide, consistent with the findings of this manuscript", which demonstrates that our used LE method here is acceptable. So we insist to preserve the Section 2. In the Section 5, the rigorous limit equilibrium method (M-P method) is employed to analyze the Shuping landslide, which is not consistent with that used in the Section 2. Because we want to use rigorous LE to check the results from the simplified LE method used in the Section 2. To address this comment, we added an explanation to clarify why we choose the simplified LE method in the section 2 (on Lines: 124-127). 4. The distinction between driving section and locking section (I would suggest "resisting section" rather than "locking", if necessary) is not rigorous and can have only a gualitative meaning. Even in the driving section, there is some mobilised strength component along the corresponding portion of the sliding surface, as well as even in the locking section the driving forces, in some circumstances, can prevail over the resisting ones. Response: We agree with reviewer's opinion. We now change the term "locking section" into "resisting section" in the whole manuscript as suggested.

NHESSD

Interactive comment

Printer-friendly version



Specific comments: 1. In the figures proposed the term "deformations" is used to indicate displacements, which have mm as measurement unit. Please, use the term "displacements". Response: Thanks for catching this error. "deformation" was changed to "displacement" in the new MS (Figure 12). 2. The comment presented at lines 456-461 is questionable, since a displacement of 5 m is not so large to justify a change in the landslide body geometry, especially for a landslide size as that here examined. Apart from the change in the curve trends, a limit equilibrium analysis with the post-movement landslide geometry should be performed to verify the actual change in the factor of safety. Response: The accurate calculation of the safety factor of the landslide with the change of the landslide body geometry is unavailable here, because the accurate post-movement landslide geometry is difficult to be obtained. To address this comment, we removed this questionable content.

3. The cohesion value adopted for the sliding surface should be justified more in detail. The landslide is moving and has experienced quite a large displacement; therefore, probably the cohesion value proposed is not operative anymore and, in general, postfailure strength conditions would apply in this situation. A comment from the authors on this choice is necessary. Response: We agree with reviewer's opinion. Shuping landslide is a reactivated landslide and had experienced large deformation before the reservoir impoundment; therefore the post-failure strength was applied in the calculation in this study. 4. A more detailed description of the engineering treatment performed in the slope is necessary. It is mentioned, but not described. Response: Thanks for reminding. We presented the detailed description of the engineering treatment in the Section 6 (on Lines: 480-486). 5. Since a transient seepage analysis is carried out, the authors should describe also some more data on the hydraulic properties of the soils used in the seepage calculations, as required by the software code used (retention curves, permeability coefficient variation with suctions). Response: Thanks for reminding. We added the necessary hydraulic properties in Tab 1. 6. Line 338: what does it exactly mean "rainfall threshold" as expressed in terms of rainfall intensity? Being clay materials, rainfall data in terms of long-term cumulative rainfalls should be more

NHESSD

Interactive comment

Printer-friendly version



important than rainfall intensity. Response: Yes, the "rainfall threshold" is expressed in the terms of the monthly rainfall here, which represents monthly cumulative rainfall. 7. Dam impoundment has also an external loading (i.e.stabilizing) function on the landslide equilibrium. The external impoundment load affects the overall equilibrium of the landslide body. This is never mentioned by the authors. Response: The external impoundment load affect has been considered within the SLOPE/W module of GEOSTUDIO software. To address this comment, we mentioned this factor in the new MS (on Lines: 366-367) 8. Since the authors explain the change in the equilibrium conditions of the landslide in terms of seepage forces (inward or outward, with respect to the slope), they should plot the output of the seepage analysis in terms of flow vectors (during a drawdown stage and an impoundment stage, for example) in order to corroborate their comments. Response: It needs a lot of space to present the flow vectors in the whole process of drawdown stage and impoundment stage, because in the every state, it needs a separated figure. While, the phreatic lines, which is closely relevant to the seepage force in the LE analysis, can be overlap displayed and reflect the whole process in one figure. Therefore, the phreatic lines are still used here. 9. How is chosen the location of the section dividing the driving and locking portions based on the results of the analyses proposed? Response: We analyzed this issue in Section 2.2, and the conclusion is that the boundary between the locking and driving sections can be approximated as the position where the slope angle $\theta 1$ equals the internal friction angle φ (on Lines 1489-157).

Thanks again for editor's and reviewer's effort on our manuscript! Best regards,

Zongxing Zou, Huiming Tang, Robert E. Criss, Xinli Hu, Chengren Xiong, Qiong Wu, Yi Yuan

Please also note the supplement to this comment: https://nhess.copernicus.org/preprints/nhess-2019-432/nhess-2019-432-AC1supplement.pdf

NHESSD

Interactive comment

Printer-friendly version



Interactive comment on Nat. Hazards Earth Syst. Sci. Discuss., https://doi.org/10.5194/nhess-2019-432, 2020.

NHESSD

Interactive comment

Printer-friendly version

