

# Landslide risk management analysis on expansive residential areas. Case study of La Marina (Alicante, Spain)

Isidro Cantarino<sup>1</sup>; Miguel Angel Carrion<sup>2</sup>; <sup>3</sup>Jose Sergio Palencia-Jimenez<sup>3</sup>; Víctor Martínez-Ibáñez<sup>4</sup>

<sup>1,2,4</sup> Department of Geological and Geotechnical Engineering, Universitat Politècnica de València, Camino de Vera, s/n, 46071, Valencia, Spain

<sup>3</sup> Department of Urban Planning, Universitat Politècnica de València, Camino de Vera, s/n, 46071, Valencia, Spain

Correspondence to: Víctor Martínez-Ibáñez (vicmarib@trr.upv.es)

**Abstract.** Urban expansion is a phenomenon that has been observed since the mid-20th century in more developed regions. One aspect of it is the urban development of holiday resorts with second homes that generally appeared following world political stabilisation. This residential expansion has often happened with scarce control, especially in its early stages, allowing areas to be occupied that are not so suitable in terms of the environment, culture and landscape, not to mention the very geological risks of flooding, earthquakes and landslides. Indeed, the risk of landslides for buildings occupying land in zones at such risk is not a matter solely attributable to the geomorphological characteristics of the land itself, nor is it simply a question of chance; it is also due to its management of such land, generally because of a lack of specific regulations. This study aims to lay down objective criteria to find how suitable a specific local entity's risk management is by looking at the evolution of its urban development procedures. It also aims to determine what causes the incidence of landslide risk (geomorphology, chance, land management, etc.), and finally to suggest control tools for the public bodies tasked with monitoring such matters.

## 1 Introduction

Landslide risk evaluation, management and mitigation are aspects that have been dealt with profusely in recent decades in the literature specialising in such matters. There is a multitude of studies on these matters, notably the summary put forward by Dai et al. (2002) with a critical review of landslide research and the strategies for reducing damages and losses, as well as the relevant publications by Lee and Jones (2004) and Glade et al. (2006) with a multidisciplinary perspective on landslide management. The recent review of quantitative methods for analysing landslide risk by Corominas et al. (2014) is also very noteworthy.

It is important to consider that the risk associated with landslides is changing as a consequence of environmental change and social developments. Climate change, the increased susceptibility of surface soil to instability, anthropogenic activities, growing (and uncontrolled) urban development and changes in land use with increased vulnerability for the population and infrastructure as a result, all contribute to the change—and in most cases the increase—in the risk of landslide (Gallina et al., 2016).

Urban expansion is a phenomenon associated with an increase in living standards and improvement in transport, communication and services outside the traditional population hubs. Among the many aspects of this phenomenon being studied, there is one that stands out as absolutely essential: the organisation and regulation of this urban growth. Indeed, in the classic work by De Terán (1982), the desired approach to urban planning is described as the need to establish order in developing it, in view of the damage and inconveniences caused by spontaneous urban development.

It is clear that urban expansion using unsuitable planning aggravates the incidence of geological risks. Specifically, landslides are one of the most dangerous natural disasters in terms of their frequency and the seriousness of the damage they do, leading

40 to loss of human life and social infrastructure in practically the whole world, which has been increasing in recent decades (Lee  
et al., 2017; Sandić et al., 2017; Cascini et al., 2005).

One of the main causes that explain the rise in geological risks in residential areas is expansive urban development processes,  
with a growing trend observed in these risks on a global scale, especially as regards landslides (Zhou and Zhao, 2013). These  
45 expansionary activities have significantly increased the pressure on the land and consequently its effect on the population due  
to the occupation of land unsuitable for residential buildings (Fernández et al., 2016). This situation indicates improper  
management of the land, caused by a lack of suitable zoning of risks that hinders good planning for the use of the land (Cascini  
et al., 2005; and Cascini, 2008).

50 In other words, residential land usage may be exposed to greater natural risks precisely because such phenomena are not  
included in urban planning. When such planning is properly applied, it may help reduce exposure to the risk within urban  
areas. Indeed, it is considered to be a powerful tool in helping efficient, equitable adaptation between land occupation and  
natural risks (Hamma and Petrișor, 2018; Macintosh, 2013). There is a plethora of references that agree on the link between  
landslides and urban development. In some cases, there are rules on uses in said circumstances but they have not been taken  
55 into account, thereby allowing for illegal and irregular occupation, as happened in the region of Campagna, Italy (Di Martire  
et al., 2012). In other cases, the course of rivers has been changed as a result of an increase in urban land, leading to negative  
effects on landslides as seen on the coast of Genoa (Faccini et al., 2015) and the city of Doboj in Bosnia and Herzegovina  
(Sandić et al., 2017).

60 The great demand for residential land to develop tourism in particular has caused similar situations. One example is the case  
cited by Katsigianni and Pavlos-Marinos (2017) on the Greek island of Santorini. A similar situation is seen in Mengshan,  
China (Peng and Wang, 2015), where engineering measures have been introduced a posteriori in a mountain tourist resort with  
a high risk of landslides. So, when drawing up and implementing urban planning, these types of factors must be taken into  
account amongst many others in order to suitably regulate the territory and prevent disorganised urban sprawl.

65 Faced with this situation, which has been widely recognised around the world, there is a need for risk governance to be duly  
included in urban planning (Renn and Klinke, 2013), improving the resilience of urban developments implemented and their  
possible growth (Zhai et al., 2015). It is also necessary to carry out suitable zoning of the risks to help reduce disasters (Wang  
et al., 2008). The great challenge is faced precisely in applying urban governance, attempting to define effective systems and  
70 tools adapted to the new context of natural risks (Birkmann et al., 2014). Some experiences have shown the need to include  
the population's participation in tackling this problem, encouraging the adoption of solutions and management of them, as  
mentioned by Gough (2000) in New Zealand.

For all these reasons, it is surprising that the effectiveness and results of management of zones exposed to landslide risk have  
75 received less attention. In the end, it is not only necessary to know how to quantify and locate the risks, as well as to put  
forward steps to avoid or mitigate them, but also to lay down procedures that can determine whether the management by  
technicians and politicians is effective and if the risk has truly been mitigated.

Thus, the main goal of this work is to determine whether the pace at which zones at risk are being occupied has a point of  
80 inflection where it begins to steadily decrease. This point of inflection should be the result of a comprehensive application of  
specific regulations for the land that hinder or restrict residential construction in that type of area. It is along these lines that  
this paper suggests control tools for the public bodies tasked with monitoring such matters. Finally, it also aims to determine

what causes an increase in landslide risk, for example by considering geomorphological dynamics, inadequate land management, even bad luck, etc.

85

To ascertain the importance of these control tools, a case on the Mediterranean coast has been studied in this work. Significant construction of new buildings has sprawled along said coastline, flouting planning regulations and thus proving the complete inefficiency of such regulations in containing this phenomenon (Malvárez and Pollard, 2004). That is why it is essential to enforce the government regulations developed, as well as to activate pertinent control mechanisms to ensure compliance.

## 90 2 General methodology

### 2.1 Objectives

Given the background described above, it is necessary to determine the extent to which residential areas are at risk of landslides, to understand the causes of these risks and to improve the planning for them. The basis for this should be a study of the behaviour of the risk taken upon building them and the factors determining it. To do so, it is necessary to begin with a map of the risk distribution and the annual residential construction data in a long time series. By knowing this risk and construction data, one can estimate its progress over time and whether a greater or lesser relative risk is being taken. Specifically, it is understood that this evolution in risk must not be exclusively a matter of the land's orographic characteristics, or even of chance, but it should also be greatly influenced by the pertinent territorial management.

100 The first task to be carried out is to gather residential building data as an annual summary for each local entity into which the zone of study is divided. Studying temporal series can then provide a lot of dynamic information about the evolution of a set of data. The series do not have to follow constant growth patterns since, as will be seen, they may undergo seasonal and other changes. This happens especially in the main data series to be analysed, which is the evolution of residential construction over time. Of course, it is also affected by the vagaries of big economic cycles, but such supra-annual seasonality is not going to be studied in depth.

The second data set must arise from the geolocalised map of risk distribution. Normally, this is based on a landslide susceptibility map (LSM) that ~~is has been deemed stable for a specific territory and does not especially evolve over time. However during the period analysed. Indeed,~~ the risk map is calculated based on the temporal nature of construction and must be approximately in sync with this process. Moreover, the occurrence of a landslide is generally linked to trigger mechanisms that respond to events subject to a specific return period. The probability calculation also uses feedback from the appearance of these events, whose frequency is being modified as a result of climate change ~~(Gallina et al., 2016). In this work, that latter dynamic aspect of risk calculation is not going to be taken into account. However, according to Gariano and Guzzetti (2016), the effects of climate change on the type, extent, magnitude and direction of the changes in the slopes' stability conditions, and on the location, abundance and frequency of the landslides, are not completely clear. In the end, climate change is not going to be taken into account specifically in this work..~~

The main goal of this research is to seek risk modification patterns throughout a time series in local entities (hereinafter referred to as urban administrative divisions, UAD). Three main, non-exclusive hypotheses are proposed that enable the causes of the evolution in risk to be explained via a specific line of reasoning:

1. Random reason, with no clear reason explaining the phenomenon;
2. Geomorphological land characteristics: slope, lithology, land cover, etc.

### 3. Management by local or regional public bodies responsible for land planning.

Simple observation of the annual evolution of risk in a specific zone is not by itself very conclusive in determining whether it is due to one of the causes described above. The trend has to be connected to the evolution of construction, verifying the temporal correlation between the two series within a local entity and among neighbouring local entities. This aspect will be analysed in the section dealing with the evolution of risk.

In keeping with the objectives described, it is necessary to have two fundamental types of georeferenced data: the data on residential construction evolving over time, and the data concerning the risk as a result of occupying the land, with the risk's distribution over time being variable depending on the pace of construction.

Logically, it is necessary to have data on the residential plots or parcels, specifically the data on the built-up area of each residential parcel (as "gross floor area", hereinafter GFA), year of construction and geographic location. These types of data are beginning to be easily obtainable in some countries thanks to the development of public access digital cadastres (USA, Australia, France, Germany and others), which also appear to be near completion in many others. Currently, such data in Spain can be downloaded sequentially by municipalities via the Spanish Cadastral Agency (DGC).

## 2.2 Risk evaluation

The quantitative risk evaluation is to be carried out by applying the known general equation of risk (1), which includes the terms Hazard or probability, elements affected and their value (Exposure), and the seriousness of the damage (Vulnerability), based on the classic definitions from the Office of the United Nations Disaster Relief Organization (UNDRO, 1979).

$$\text{Risk} = \text{Hazard} \times \text{Exposure} \times \text{Vulnerability} \text{ (1)}$$

The value of risk is generally calculated in monetary units (€), though other types of unit may also be used (built-up m<sup>2</sup>, casualties, etc.). In this work, the type of risk analysed is economic loss due to landslide damage to residential buildings.

HAZARD: This is the probability of occurrence of a potentially damaging natural phenomenon such as a landslide within a specific period of time in a specific area. Calculation of this is normally based on a susceptibility map. Specifically, for each level of susceptibility the hazard must be calculated in units of probability, for which it is necessary to turn to inventory data of landslides. These two types of probability—temporal and spatial—are in keeping with equation (2):

$$\text{Hazard} = \text{Spatial probability} \times \text{Temporal probability} \text{ (2)}$$

EXPOSURE: People, property, systems, or other elements present in hazard zones that are thereby subject to potential losses. Therefore, exposure indicates the extent to which the elements at risk are actually located in the path of a particular landslide (Corominas et al., 2014).

VULNERABILITY: The degree of loss to a given element or set of elements within the area affected by the landslide hazard. It is expressed on a scale of 0 (no loss) to 1 (total loss). Vulnerability is probably the most difficult aspect to assess, due to the complexity and the wide-ranging variety of landslide processes (Glade, 2003). Following a technical/engineering approach, the seriousness of the damage done is a function of the magnitude or intensity of the landslide and the studied building's capacity for resistance.

### 2.3 Temporal evolution of risk

~~As commented above,~~ The essential purpose of this work is to define a reliable, simple method that will enable the risk's dynamics to be described. One strategy would be to recognise if the risk taken increases or decreases at the same pace as the construction of residential buildings. It would seem logical that this variation of risk should be estimated not as an absolute value, but in relation to ~~t~~<sup>the</sup> volume of construction at a given time, ascertaining whether there is a temporal correlation between these two variables or not.

An ideal situation pattern can be put forward of working with a long series of at least 40-50 years, since the beginning of the urban development boom in a specific zone. Three main sections can be found in this series. In the early years of this example situation pattern, there is disorganised construction occupying the most profitable spaces, but at the same time in not very suitable areas from the point of view of geological risk and the impact on the environment and the landscape. During the intermediate section, the occupation of zones at risk begins to change pace as urban development legislation begins to appear, along with land planning, environmental awareness, etc. The last section sees a very clear drop in the pace of the risk's growth, as the land regulation restrictions contemplated are directly applied. This theoretical behaviour is shown in Figure 1.

**Figure 1. Theoretical evolution of risk accumulated over time for a one-year series pattern**

For dynamic analysis of the data shown in Figure 1, the two main annual data series must be used; one based on the evolution of the residential built-up area, and the other on the risk affecting part of that built-up area. The former is the Gross Floor Area (GFA, in m<sup>2</sup>), calculated every year  $y$  based on cadastral parcel data (CPi) by means of equation (43):

$$GFA(y) = \sum_{i=1}^n GFA_{(CP)i} \quad (43)$$

Once the value of GFA(y) has been obtained, the simple moving average of order 3 for each year  $y$ , [MAvGFA(y)], is applied according to equation (24):

$$MAvGFA(y) = \text{mean } GFA(y - 1, y, y + 1) \quad (24)$$

Applying the general equation of the risk (see equation 91) gives the risk value (RV) in € for each cadastral parcel CP affected, in accordance with the susceptibility map (equation (35)):

$$RV_{CP} = H_{CP} \times E_{CP} \times V_{CP} \quad (35)$$

Similarly, the simple moving average is calculated for the risk value MAvRV(y) via equations (46) and (57):

$$RV(y) = \sum_{i=1}^n RV_{(CP)i} \quad (46)$$

$$MAvRV(y) = \text{mean } RV(y - 1, y, y + 1) \quad (57)$$

A relationship is sought between the two series to explain the trend towards a model of residential construction with increasing, stable or decreasing risk with relation to the built-up area. It is proposed that the relationship between risk and the built-up area should be used as an indicator of the evolution of risk and the construction associated with it.

Within a specific period of time, in the two moving average series a monotonically increasing interval can be selected that is limited by the years  $[y_1, y_2]$  where  $y_2 > y_1$ . Two functions are defined for the risk values and for the built-up area:  $f(y) = RV(y)$ ;  $g(y) = GFA(y)$ .

It has been confirmed that the way growth in risk with time directly relates to the pace of construction is determined by the behaviour of the quotient between functions  $f(y)$  and  $g(y)$ . Thus, for example, proposing two growth ratios  $rRV$  and  $rGFA$  during the chosen period, which are approximately constant and where  $rRV > rGFA$ , it is easily shown that the quotient function is growing. In the opposite case,  $rRV \leq rGFA$ , the quotient function is falling.

The adimensional (relative) Risk Ratio (RR) between years  $y_1$  and  $y_2$  is defined in the following equation: (8):

$$RR(y_2, y_1) = \frac{\frac{RV(y_2)}{RV(y_1)}}{\frac{GFA(y_2)}{GFA(y_1)}} = \frac{rRV}{rGFA} \quad (6)(8)$$

To sum up, it is concluded that  $f(y)/g(y)$  is a function whose growth slope is defined by the Risk Ratio value (RR) for the chosen interval  $[y_1, y_2]$ . The different options are summed up in Table 1.

**Table 1. Characteristics of the Risk Ratio RR.**

It is preferable to use the absolute values from the relationship between RV and GFA in order to be able to compare their magnitudes between the different municipalities. In addition, working with functions of accumulated values  $RV_{accum}$  and  $GFA_{accum}$ , it is ensured that the two base curves are monotonically increasing for the entire period being studied. It is easily demonstrated that the quotient function of the accumulated series  $RV_{accum}/GFA_{accum}$  also meets the characteristics determined for the RR value in Table 1.

These annual values can be transferred to a graph showing the resulting curve in order to analyse its ascending or descending trend, Figure 2.

**Fig. 2 Curve trend of different types of Risk Ratio**

Equation 9 shows the calculation of the accumulated RR values for each year

$$RR(y) = \frac{RV_{acc}}{GFA_{acc}} = \frac{\sum_{i=y_0}^y RV_i}{\sum_{i=y_0}^y GFA_i} \quad (9)$$

This equation is applied for the entire time series available, always starting from an original year  $y_0$ . In these quotient functions, a simple deterministic trend is going to be assumed.

In these quotient functions, a simple deterministic trend is going to be assumed. Two specific indicators can be extracted from these functions. The first of these would be to calculate the trend of the curve  $RR(y)$  simply by means of equation (710), which gives the slope of the straight line  $m$  that joins the two points of the curve  $RR(y)$  between moments  $s$  and  $t$  with periods of  $n$  years.

$$mRR(t,s) = \frac{[\text{mean}(RR_t \dots RR_{t+n}) - \text{mean}(RR_s \dots RR_{s+n})]}{(t-s)}, \quad \forall t > s \quad (7)(10)$$

These reference points should be located in the temporal series at the moments prior to and after decisive changes in land management policy. It can also be used at the start of the series in order to learn the behaviour of risk in the early years of residential expansion.

250 Within the analysis of the temporal series of risk, it is worth noting that it may also be important to study the synchronisation of their peaks to explain certain types of behaviour. Firstly, this may be done among the different geographically neighbouring local entities. For example, a specific type of municipal management would stand out if big differences are found with the neighbouring entity, especially if their geomorphological characteristics are very similar. To do so, three causes can be put forward to explain an external temporal correlation among neighbours, which fit with the hypotheses put forward in 2.1:

255

1. With a total lack of synchronisation and without demonstrating behavioural patterns, the cause must occur randomly as a result of not very notable effects that cannot be analysed globally.
2. With synchronisation among neighbouring entities, the cause must be due to geomorphological characteristics of the terrain, since they are autocorrelated by geographic proximity.
- 260 3. With differing synchronisation in nearby areas but with certain patterns of behaviour in wider areas, the cause must be sought in the different ways of managing the land.

260

Secondly, the internal synchronisation of construction peaks with the risk peaks for the same local entity should coincide in time under theoretical conditions. However, another two situations may also occur, which show that the construction and risk assumed are not necessarily governed by logic. Their possible reasons could be:

265

1. Risk peak brought forward: Buildings with a greater level of risk may be of greater commercial interest (e.g. due to dominant locations with the best views) and are thus built sooner.
2. Risk peak delayed: Suitable parcels begin to become scarce after a period of intense building activity, so that the last buildings are in a worse location and thus a greater risk is assumed.

270

### 2.3 Risk and construction indicators

~~A global view of the process is necessary, together with~~ a complete study of the temporal series ~~provides a lot of information, but a global view of the process can sometimes be lost.~~ It is usually preferable to summarise it in specific indicators that directly reflect the situation of the comprehensive temporal series for each of the urban administrative divisions (UAD, municipality equivalent) into which the study area is divided.

275

These indicators enable direct comparisons to be made, and analogies and differences to be seen more easily between different UADs. To do so, variables should be used that are not affected by the area of the UADs analysed. One solution is to calculate specific variables distributed homogeneously over the land's area.

280

The most relevant factor is without a doubt the RR, derived from the quotient function  $RR(y)$ , calculated as a summary of the complete series in equation (811):

$$RR = \frac{\sum RV(\epsilon)}{\sum GFA(m^2)} \times 1000 \quad (11)$$

285 where  $\sum GFA$  and  $\sum RV$  are total values for the complete period per UAD.

The Risk Ratio defined in (811) allows us to know how much risk has been assumed throughout the period under study and to be able to relate it to the other territorial units by specifying if it is greater or lesser than the average for the zone of work. It is thus possible to highlight the units that are assuming an excessive risk.

A summary of other indicators that can be calculated for each UAD is shown in Table 2.

**Table 2. Global indicators per UAD**

### 3 Case study: La Marina

The work by Cantarino *et al.* (2014) emphasises that Alicante was the province most affected by ~~total~~landslide risk value on residential buildings in the Valencia Community region (Spain), with more than one million euros in 2005 and 2009 each. This is chiefly due to the coastal zones in the northwest of the province (La Marina administrative division) with a high demand for housing, which is an area susceptible to higher landslide risks.

Thus, the area selected for this study is located in this area of Alicante (south-eastern Spain) bordering the Mediterranean Sea (Figure 23). The area includes 50 municipalities, covers 1,335 km<sup>2</sup> and has a population of 201,442 inhabitants according to the 2011 census (Spanish National Institute of Statistics, INE). This population has seen a notable increase since the 1990s (over 50%) basically due to tourist activity, though today it has fallen to 171,826 inhabitants in the last census (INE, 2018) as a result of the economic crisis. It is a populated mountainous environment rising from sea level to around 1,500 m. Its profile is shaped by its proximity to the sea, with a river system that deeply dissects the territory.

**Fig. 3. La Marina area. Location of some municipalities mentioned in the text.**

La Marina is located in the province of Alicante, which is the Valencia Community region's province with the highest landslide rate per unit of surface area (Hervás, 2017). Its extensive mountainous ~~terrain means~~orography reaches the coastal strip itself, which is not ~~exempt~~free from risk, ~~a~~. This situation ~~that~~ is aggravated by ~~its high value~~being highly attractive for tourism and its residential occupation.

This territory is typical of urban expansion around the Mediterranean basin, which is becoming increasingly intensive and no longer necessarily fostered or supported by the main coastal cities (EFAEEA, 2006). It is an example of the so-called "rural sprawl" generated by second homes for the local population (in some cases first homes too), and of "residential tourism" for people from northern Europe, who spend long periods on the Mediterranean coast. Although initially there was a move towards recovery and restoration of traditional rural constructions, strong demand has led to a proliferation of new-build housing units (Pardo-García and Mérida-Rodríguez, 2018).

#### 3.1 Data used

##### BASIC MAPPING

The official maps from the Spanish Geographic Institute (IGN) provided the borders and areas for the municipal territories to calculate the UADs. They also gave the 5×5m DEM (Digital Elevation Model) to calculate the mean slope of each municipality.

##### LANDSLIDE DATABASE



The national Spanish database for landslides BD-MOVES from the Spanish ~~Geomining~~-Institute of Geology and Mining (IGME) was used, which follows the INSPIRE regulations (Infrastructure for Spatial Information in the European Community). BD-MOVES, created in 2014, is made up of two blocks or sets of georeferenced spatial information: one referring to the description of the intrinsic, relatively invariable characteristics of landslides, and another referring to different activity events that led to said landslides, including morphometrics, triggering factors, damage and other data.

The other source of data is the landslide map to 1:50 000 scale in vector format drawn up by the Valencia Government's Regional Department of Public Works in the project entitled "Lithology, exploitation of industrial rocks and landslide risk in the Valencia Community" (COPUT, 1998). This map uses geological and geotechnical data from the IGME, 1:50 000 scale topographical maps and aerial photographs available at that time.

#### CADASTRAL PARCELS

The information referring to cadastral plots or parcels was obtained from the cadastral mapping available from the DGC according to European INSPIRE guidelines. This cadastral information is provided by interoperable services (WMS and WFS) and can be downloaded in three datasets: Cadastral Parcels, Buildings and Addresses. For this study, the former has been chosen because it contains the main item defining the building. Within this item, we can find the data necessary for each parcel: built-up area (GFA), year of construction and type of usage. Only functional and residential parcels have been used for the series 1960-2017.

#### CLASSES OF SUSCEPTIBILITY TO LANDSLIDES

To calculate the level of hazard, the starting point was the landslide susceptibility map (LSM) ~~with a resolution of 25 x 25 m in La Marina~~, drawn up in a previous study (Cantarino *et al.*, 2019). Its characteristics are: pixels of 25 x 25 m as the unit of surface area and the spatial-multicriteria method (SCME) to weight the factors for obtaining the susceptibility values. The three significant factors used were: slope gradient, lithology and land cover.

Specifically, the thresholds of susceptibility classes defined by Cantarino *et al.* were used. These thresholds were obtained by means of objective, meticulous classification based on a ROC analysis (Receiver Operating Characteristic), which uses the intrinsic variability of the data and is one of the first applications of this type of map. ~~In this study, the aforementioned thresholds are used to evaluate the risk in different cadastral parcels at any moment, as well as to determine their evolution over time and finally to calculate the level of hazard..~~ For this study, the spatial probability for each class has been determined by comparing these susceptible areas with the ones indicated in the inventory. This information, together with the temporal probability, has enabled the hazard and finally the risk to be calculated

Table 3 shows the susceptibility levels established via the susceptibility indices (LSI) that define them, together with the number of pixels affected.

#### Table 3. Land Susceptibility Index (LSI) values for the classes under consideration

Figure 4 with some data used is attached, indicating the three highest levels of susceptibility, together with the location of landslides according to the Spanish Geological Survey (BD-MOVES) and the areas with instabilities according to the Valencia Regional Government (COPUT).

#### Fig 4. La Marina area. Susceptibility, landslides location and areas with instabilities

370 **3.2 Implementation of the method**

Figure 35 shows the flowchart indicating the method followed, which is explained in the above sections. It involves analysing the evolution over time of the residential parcel areas and landslide risks assumed in the urban expansion period in the La Marina area of Alicante province, from 1960 to 2017. Within this interval, a period of intense construction activity can be seen between 2000 and 2008, followed by a period of slowdown caused by the general economic crisis that occurred at the end of the decade of 2000 and which has not yet clearly ended.

**Fig. 5. Flowchart of the work procedure.**

Following the method described, firstly the cadastral parcels with their built-up gross floor area (GFA) were analysed, and then it was seen how the latter evolved over time together with the surface area affected by landslide risk. The final calculation used one-year periods to summarise the values dealt with individually for each parcel and as a moving average, MAV of order 3, according to equations (24) and (57).

**3.3 Risk evaluation**

~~The quantitative risk evaluation is to be carried out by applying the known general equation of risk (9), which includes the terms Hazard or probability, elements affected and their value (Exposure), and the seriousness of the damage (Vulnerability), based on the classic definitions from the Office of the United Nations Disaster Relief Organization (UNDRO, 1979).~~

~~$$\text{Risk} = \text{Hazard} \times \text{Exposure} \times \text{Vulnerability} \quad (9)$$~~

~~The value of risk is generally calculated in monetary units (€), though other types of unit may also be used (built up m<sup>2</sup>, casualties, etc.).~~ The process followed for risk evaluation was based on locating the peak value of the three high susceptibility levels (between 3 and 5 class, see Table 3) for each cadastral parcel, affected by a buffer of 20 m around it. All cadastral parcels of an area of less than 10 m<sup>2</sup> were eliminated beforehand. The risk per parcel was then calculated, based on its maximum LSI value.

As mentioned, possible changes in some of the factors involved in calculating the risk (such as those due to climate change) are not taken into account. The variation in real risk that may arise due to these changes is considered to be of little significance and does not therefore affect the final results.

By applying the equation to calculate the Risk Value (RV) shown in (35) for each cadastral parcel, it is possible to calculate the risk in monetary units (€) at the 2018 value. ~~They~~The year of construction is not considered, since in general the value is for the cost of reconstruction at the current value if affected by a landslide.

**HAZARD**

~~This is the probability of occurrence of a potentially damaging natural phenomenon such as a landslide within a specific period of time in a specific area. Calculation of this is normally based on a susceptibility map. Specifically, for each level of susceptibility the hazard must be calculated in units of probability, for which it is necessary to turn to inventory data of landslides. There are really two types of probability—temporal and spatial—in keeping with equation (10):~~

~~$$\text{Hazard} = \text{Spatial probability} \times \text{Temporal probability} \quad (10)$$~~

For the temporal probability [in equation \(2\)](#) (see Fell *et al.*, 2008), one has to turn to databases such as BDMOVES from the IGME, which indicates the landslides and the date. For the spatial probability, work has been done with the COPUT's risk mapping for the zone under study.

In BD-MOVES, 13 landslides over the last 20 years are listed, though 5 of them are small slips. Summarising, it is possible to estimate 8 landslides for this period, with an annual probability (Pa) of 8/20. This annual probability should be adjusted downwards by an adjustment factor of *Faj*, but this value has been maintained since the inventory is not complete and the landslides that have not been included should be accounted for (Lee, 2009). Said probability was calculated in equation (4-12).

$$Pa = \left( \frac{\text{number of recorded events}}{\text{number of years in the record}} \right) \times \text{Faj} \quad (11) \quad (12)$$

To calculate the spatial probability  $P_s$ , landslides were selected that appear in COPUT's aforementioned map (1998), describing their limits and cross-referencing this information with susceptibility levels 3, 4 and 5 of the map listed in Table 3.

The results are shown in Table 4.

Classes 1 and 2 of the susceptibility map (LSM) are not taken into account because they do not show a probability of being affected by risk of landslide. Thus, for each level L of the LSM shown in Table 4, the value of hazard level is obtained using equation (13).

$$H_{CP} = f(\text{LSI}_{\text{max}}) = \frac{S_{RL}}{S_I} \times Pa = Ps \times Pa \quad (12)(13)$$

Where  $S_L$  is the total surface area of level L, and  $S_{RL}$  is the surface area of level L affected by risk of landslides.

The value of these elements only takes into account the gross floor (built-up) area, not the value of land that is not affected by landslides. Taking into account only the cost of constructing the building to calculate the Building Execution Unit Cost, the tables of the Institut Valencià de l'Edificació are used, IVE (website: <http://www.five.es/>, see online in *Productos/Herramientas*). To do so, the definition of Basic Building Module (BBM; € / built-up m<sup>2</sup>) is used, which represents the material cost of implementation per built-up square metre of the Reference Building, implemented under conventional worksite conditions and circumstances.

The BBM for December 2018 for single-family detached houses of fewer than 3 floors with an inhabitable surface area of over 70 m<sup>2</sup> and with high quality finishings and fittings, is €829/m<sup>2</sup>. This value remained practically constant throughout 2018, and even as of 2008 it has been above €800/m<sup>2</sup>. Open-plan buildings of 3 floors or more, up to 80 homes and an inhabitable surface area of between 45 and 70m<sup>2</sup>, are valued at €780/m<sup>2</sup>. To a large extent, the homes affected are of the single family type, so the value of reconstruction has been taken to be constant at €800/m<sup>2</sup>.

The value for reconstructing each cadastral parcel is calculated according to equation (13.14), without taking into account the value of the land.

$$E_{CP} (\text{€}) = \text{GFA} (m^2) \times \text{BBM} (\text{€/m}^2) \quad (13.14)$$

## VULNERABILITY

~~Vulnerability is probably the most difficult aspect to assess, due to the complexity and the wide-ranging variety of landslide processes (Glade, 2003). Following a technical/engineering approach, the seriousness of the damage done is a function of the magnitude or intensity of the landslide and the studied building's capacity for resistance.~~

In order to determine landslide magnitude (LM) in a geographical area, it is crucial to create a landslide inventory to know the main landslide types, landslide morphometric parameters, landslide velocity and observed damage. This data is not provided by the available landslide databases such as BDMOVES and COPUT.

In the La Marina area, the predominant failure mechanism for shallow slides is along the existing dip planes of the Cretaceous limestone geological formations. According to Fell (1994), these landslides are defined as small landslides. The shallow slides occurring in the study area are rapid landslides, according to the velocity scale proposed by Cruden and Varnes (1996), with a typical velocity ranging from 1.8 m/h to 3 m/min. In La Marina, damage or loss caused by past landslides is poorly documented and this is a major constraint in drawing up vulnerability curves. However, field observations have shown that shallow slides that have occurred in the study area did not have enough energy to completely destroy a building. Typical damage produced by shallow slides in the study area is shown by cracks opening up in the buildings' walls. This type of damage caused by landslides in buildings is classified by Leone (1996) at level III (from I to V), which corresponds to a structural damage of 0.4–0.6 on a scale ranging from 0 to 1. Taking into account the previous example and the fact that shallow slide characteristics in the study zone do not vary too much in terms of affected area, depth of the slip surface, velocity, volume and typical damage, we assumed a single fixed value for LM (in accordance with the level of susceptibility). Therefore, the LM was assumed to be 0.6 for the area of study on a heuristic scale ranging from 0 to 1 (Silva and Pereira, 2014) (see Table 5).

The other factor to evaluate the final vulnerability, FV, is to estimate the considered residential buildings' resistance (BR) taking into account the type, materials, age and height of the building (Kappes *et al.*, 2012). Within the zone under study, the construction techniques, materials used (mainly concrete) and structure are quite similar and are considered to be sufficiently resistant with a generally good state of conservation seen in the buildings. The biggest difference one can find is in the mean number of floors for each building, though the type of home affected has a low number on average (see NFm in Table 2) with not very significant variations.

Papathoma-Köhle *et al.* (2017) ~~identifies~~identify a list of indicators for ~~the one particular kind of landslide~~ (debris flow) physical vulnerability assessment of buildings. One of them, the height of the building, directly influences the degree of loss. In accordance with Papathoma-Köhle *et al.*, the higher the building, the fewer the expected losses, so a greater BR is considered in these cases (Table 5).

Equation (14.15) enables the final vulnerability FV to be calculated, in which the BR depends solely on the number of floors NF, and Table 5 gives the values obtained by applying it.

$$FV = LM \times (1 - BR_{NF}) \quad (14)$$

(15)

**Table 5. Vulnerability related to the number of floors.**

## RISK

500 The final calculation of risk for each cadastral parcel is the result of applying equation (3). Thus, in accordance with the equations shown above, the final expression for the calculation of the risk value for each CP is:

$$RV_{CP}(\epsilon) = \left( \frac{S_{RL}}{S_L} \times Pa \right) \times (GFA \times BBM) \times [LM \times (1 - BR_{NF})] \quad RV_{CP}(\epsilon) = \left( \frac{S_{RL}}{S_L} \times Pa \right) \times (GFA \times BBM) \times [LM \times (1 - BR_{NF})] \quad (15)$$

505 ~~It should be remarked~~ (16)

510 As a final reflection on the ~~risk calculation methods, that it does not seem to be essential here to carry out a very comprehensive, exhaustive application. In this vein, it should be repeated that the main aim of this work or any other method for calculating risk, it should be noted that there is to analyse how the risk evolves, not its~~ some difficulty in obtaining precise results due to the lack of official data and specific values, up-to-date studies in the sphere being studied. Some of these procedures are based on data that is not very exact, and even on subjective evaluations, which means some error must be assumed in the results obtained, though this does not invalidate the objectives or the validity of the index originally proposed in our study. For this reason, the global calculation of equation (15) has been carried out using the main factors without including ones considered to be less relevant.

### 3.4.3 Risk curve and trend

520 The year the temporal series begin is determined in Spain and in the Valencia Community region as 1960, which marked the start of tourism expansion on the Mediterranean coast. The year approximately coincides with when the Law on Centres and Zones of National Interest to Tourism was passed (year 1963), which notably fostered residential construction in coastal areas without taking into account geological risks.

525 As has been mentioned, to study the evolution of risk, the proposal is to use a complete analysis of the temporal series of the Risk Ratio value (RR) as the basis. Indeed, the shape of the RR(y) curve, as well as the behaviour of the two annual series of GFA(y) and RV(y), enable the characteristics of the evolution of risk to be established for the entire period.

When the RR(y) has been calculated, its three singular points are extracted to define the straight lines and calculate their slope via equation (7). Specifically, the mean points of the curve were used for the two different periods that include the decades 1960-69, 1980-1989 and 2000-2009 for a time interval of 20 years. The slopes calculated have been called *mRR Lo* for the lower (earlier) period (60s and 80s) and *mRR Hi* for the higher (later) period (80s and 2000s).

530 The first period analysed explains the historical evolution, marking the beginning of the trend, which is why the mean points have been selected from the 1960s and 1980s. For the second period, the decades of the 1980s and 2000s were used. This period acts as a reference for the substantial change in land policy, which should have brought about a clear change in trend. Indeed, it was in the 1990s that the first official study on the risk of landslides appeared (COPUT, 1998). Such work continued with legislative activity that fostered the prevention of natural or induced risk.

## 4 Results

A series of annual values were calculated for the La Marina area as a whole, many of which coincide with the indicators listed in Table 2 above. The total values and The values of these indicators calculated for the 50 municipalities that make up La Marina are shown in Table 6, accompanied by their variation interval. A series of annual values were calculated for the 50 municipalities of La Marina area as a whole. The total values for the built-up area (GFA) and risk (RV) are shown in Table 6. The mean values are listed in the same table, as well as their interval of variation of the global indicators in the previous Table 2

**Table 6. Total values and global indicators per municipality. For indicators, means and variation intervals.**

The values of these indicators can be explained logically and are subsequently used to classify the municipalities via a cluster analysis. On drawing up the graphs, the ratios between the total values of GFA and RV from Table 6 were used, which is approximately 8:1 (GFA:RV).

As a result of the analysis of the RR, GFA and RV graphs (see the available research data), some interesting behaviour can be found. The comparative graphs of GFA and RV are particularly useful. In general, a marked stability can be seen in the final stretch of the last 10 years, possibly caused by the slowdown in construction after the 2008 crisis. This enables us to affirm that acquisition of residential land with low risk has not been exhausted.

The annual risk peak values are also seen to appear usually after the construction peaks, or at least they are seen very clearly in municipalities with the greatest construction activity. Recalling the possible causes for this situation (listed in section 2.23), this may be due to the fact that after an intense construction period the last parcels to be allotted are usually in zones of greater risk, since those of lesser risk have been allotted first. However, in municipalities with less construction, the construction peaks are more synchronised and even appear before the risk peaks.

Lastly, there is no synchronisation found between the different curves in neighbouring municipalities (as seen in Figure 4). Nevertheless, a few behavioural patterns have been obtained in the geographic area under study. Hence, as explained in 2.23 for the so-called internal synchronisation, the most probable cause should be sought in the differing land management, and not in geomorphological or random causes.

Figure 46 shows the evolution of two neighbouring coastal municipalities that represent those with greatest residential construction with a slope close to the average, but which have very different characteristics in assuming risk. They are Calpe and Altea (see locations in Fig. 23 and 4); the former with RR = 79.8 and the latter with RR = 463.3.

**Figure 6. Evolution of the annual series of GFA, RV and RR in the municipalities of Calpe (a, b, c) and Altea (d, e, f).**

Calpe is a mountainous coastal municipality with a high construction rate but a clearly low risk, with a lower risk than the average according to Figure 4a6a. In terms of cumulative value, 46(b) also shows the construction as being more significant than risk, with a sharper slope for the former. Graph 46.c shows there is an early stage in the 1970s with a risk peak, which then gradually falls. The RR indicator is very low and everything seems to indicate suitable management over the last 20 years, taking on a comparatively low risk.

In Altea, on the other hand, a greater risk is seen to be assumed in the second half of the series, which is above average (46(d)). Moreover, Figure 46(e) shows risk more significantly than construction. Figure 46(f) indicates an appropriate beginning for

the RR value, but later the relative risk grows. As the indicator value is very high, it can be concluded that this municipality's management should clearly be revised, with a change in trend sought. In both cases we can see risk peaks that come after their corresponding construction peaks. ~~The possible explanation for this has been given above.~~

The possible explanation could be that the plots at greatest risk of landslide begin to be used at a greater pace once the best plots have been occupied following a period of intensive building activity. In other words, it is possible that when suitable plots become scarce, the next buildings are constructed in a worse location and thus a greater risk is taken on.

For the other municipalities, a similar criterion has been followed. High RR values and a straight line with an increasing trend in the second half of the period point to a necessary revision of the protocols in granting construction licences, in view of the growing risk assumed. On the other hand, RR values lower than the average coupled with a decreasing trend indicate a lowering risk and improved land management.

To conclude, Figure 5.7 shows the joint evolution of the whole La Marina area (excluding Altea and Benitachell due to the bias they would introduce). Figure 5.7(a) shows continual growth in construction and risk almost simultaneously, indicating a clear similarity with the curve pattern shown in Fig. 1 in the three intervals. These curves show a marked jump in the decade of 2000, coinciding with a period of clear economic boom associated with intense construction activity (known as the "Spanish property bubble" from 1998 to 2008). Finally, 5.7(b) shows fast growth in risk during the first part of the period under consideration, levelling out and becoming comparable to the growth in residential area in the second part of this period. To sum up, no generalised drop is seen in the risk growth rate, so it is hoped that in coming years the urban development regulations in force will end up serving their purpose.

**Figure 7. Evolution of the annual series of GFA, RV and RR for the La Marina area.**

## 5 Discussion

The analysis of the graphs for municipalities is very revealing in learning the effectiveness of their management in lowering the risk of landslides. However, it is important to observe how the municipalities studied are organised and what type of association there may be among them. To do so, a cluster analysis was applied in order to determine the types of groupings that can be found in the area being studied. This type of analysis is a tool that has widely shown its usefulness in grouping urban areas by means of indicators (Huang *et al.*, 2007; Stewart and Janssen, 2014; Goerlich *et al.*, 2017).

The variables to be included in the cluster analysis as explanatory variables were the indicators for each municipality in keeping with Table 6. They are variables for the period from 1960 until today. However, some of them were discarded *a priori*. Firstly, this includes the mean number of floors NFm, as there is little variability in this. The mean distance to the historical centre, Dh<sub>c</sub>, is intended to be a measurement of residential expansion, but it is excessively related to the size of municipality and the location of its historical centre, so that it was also used little. Lastly, mRR<sub>Lo</sub> was not considered as it is not a main variable and behaves as secondary in the current evolution of risk.

Hence, the variables initially selected for the cluster analysis were: Mean slope SL<sub>m</sub>, mRR<sub>Hi</sub>, SpGFA, D<sub>c</sub>, SpRV, ~~RRRR<sub>t</sub>~~, RR<sub>m</sub>, previously standardised. Nevertheless, on carrying out an analysis of prior correlations to avoid variables that do not explain variance as a whole so much, it was found that SpGFA has a very strong linear relationship with the variables SL<sub>m</sub>, D<sub>c</sub>, RR<sub>m</sub> and SpRV. This means that the rate of construction increases in flat and coastal areas, leading to less risk. Thus, it was decided to eliminate this group of variables from the cluster analysis.



Finally, the analysis was carried out only with the indicators SpGFA, mRR Hi and ~~RRtot~~RRt. These indicators have proven to be sufficiently explanatory variables to be able to establish groups with homogeneous characteristics. In this analysis, all hierarchical methods were tested with different numbers of clusters. Ward's method and the Manhattan distance gave the best results. Various attempts were made to find the optimum cluster number, finally choosing a solution with the greatest number of clusters in order to isolate singularities, with 14 in total. The results (centroids) are shown in Table 7, where the 14 clusters have been organised into four sets A, B, C and D (from smallest to biggest in magnitude) according to the values of the three variables chosen for the analysis. These variables are: the rate of built-up area SpGFA (in m2/km<sup>2</sup> of UAD). The evaluation of management (reviewable / improvable / suitable / neutral) is indicated only for the final segment; if the trend is different for the first segment, then), the name of the municipality is marked at the end with an asterisk (\*). The mean slope is also indicated (SLm in °total Risk Ratio RRt (€/1000 m2 GFA)) and the specific risk rate (SpRV in €/km<sup>2</sup>); final section of slope of the straight trend line mRR Hi (degrees).

Each of these classes is defined as the result of a new grouping into four clusters for each variable. Table 7 also includes two indicators that provide information relevant to the established clusters. Those two indicators are the mean slope (SLm in degrees) and the specific risk rate (SpRV in €/km<sup>2</sup>), previously defined in Table 2. Table 8 explains each cluster's most relevant characteristics and the municipalities within each of them. The evaluation of the risk building management (reviewable / improvable / suitable) is indicated only for the final curve section according to the mRR Hi value; if the trend is different for the first section, then the name of the municipality is marked at the end with an asterisk (\*).

Table 7. Cluster centroids and their levels organised from A (max) to D (min)

Table 8. List of clusters with their characteristics and assigned municipalities grouped by construction intensity ratio (SpGFA) from high to low.

As can be seen in ~~Table~~Tables 7 and 8, the municipalities with high RR (above the average, RR>200) and very high RR (90<sup>th</sup> percentile, RR>400) have been differentiated. This situation only occurs with municipalities with a high rate of construction in zones at risk, or in inland, very mountainous municipalities where residential buildings are positioned more easily in risk zones, leading to a higher RR. In municipalities with improvable or reviewable management, these high RR values seem to be due to the fact they have been taking on higher risk rates over the last 20 years than in the rest of the historical series. On the other hand, if there is suitable management, these are municipalities that took on greater risks in their first 30 years than they currently do.

Table 78 is shown in map form in Figure 68. These maps show the municipal distribution of the groups obtained by means of the cluster analysis, as well as their specific risk values (SpRV).

Fig. 8. Map of La Marina: (a) with cluster groups\*, (b) with the SpRV value. (\*) Clusters D1: DAA, DBA, DCB; Clusters D2: DAD, DBD, DCC

Based on the results obtained, it is seen that many of the municipalities with suitable management today began with overexposure of residential construction in risk zones (marked with “\*\*”) in the early decades of the series. This is also seen in the fact that the mRR Lo value (41.5°) exceeds the mRR Hi value (16.9°) (see Table 6). This is logical because during the individual period the protection policies were not so developed. Taking advantage of this lack of control, together with the urban development initiative proposed by tourism legislation, it was possible to construct a greater number of buildings in unsuitable areas.



In the maps in Fig. 68, the municipalities of Altea and Benitachell clearly stand out (see location in Fig. 24), where a growing occupation of risk zones can be seen. Indeed, according to Table 7, cluster B+BBA has the highest RR value of all the municipalities in level 1 groups A, B and C (SpGFA > mean, see Table 6), as well as its SpRV and the clearest upward trend. These are therefore the clearest examples of coastal municipalities that should review their criteria for considering land as apt for urban development. Both municipalities are in the process of reviewing their municipal approaches, since in their previous plans established in the aforementioned first period there were no limits established as regards use based on geological risks.

At the other extreme, there are the mountainous municipalities in group D (see the maps in Fig. 68) with a high mean slope (19.6°). Their location can be clearly seen in the inland strip with broad unstable areas where it is more probable for construction to occur in them. This seems to be the reason why this group has many municipalities with a high RR value, sometimes burdened with this since the beginning of the series due to the effect of homes in the urban hub itself. Furthermore, since these are municipalities with low populations (under 5,000 inhabitants), they do not usually have the means to draw up land regulation plans or the technical staff to update them.

Perhaps Confrides (see location in Fig. 24) is the paradigm among these mountainous municipalities, since it has the second lowest construction rate but a high RR and a growing trend towards risk. It is also the one with the parcels furthest from the coast. It does not have land planning and according to COPUT (1998) it is one of the municipalities with the greatest density of landslides per unit of area in La Marina. Although this does not affect a significant number of homes in absolute values, in these conditions an improvement in the trend values and risk indicators would seem to be far off. Indeed, this is a singular case in which the municipality has not expressed urban development intentions in any of the three previous periods, but will necessarily have to adapt to the land planning regulations in force.

## 6. Conclusions

~~In general, the studies on the risks produced by landslides do not take into account an evaluation of the effectiveness of risk prevention methods. However, as a result of this study, ascertaining the evolution of this risk in relation to the construction rate of residential buildings enables one to know whether suitable criteria are being applied that will lead to sustainable, risk-free construction.~~

~~It is strongly advisable to have complete databases on landslides available in order to quantify the value of risk properly. Such databases are fundamental to calculate its components (hazard, vulnerability, exposure) in the greatest possible detail, and to be able to apply advanced methods (e.g. Palmisano *et al.*, 2018). The Valencia Community region needs to get full information of this type, so the regional or state government must make an effort to attain it in order to identify problem areas, propose structural measures and ensure proper management of the territory.~~

~~In this vein~~ As a final reflection, it would seem reasonable to think that studies on the mechanics and distribution of landslides, the growth in information about behaviour of the ground, the restrictions imposed on residential expansion, etc., should progressively improve the effectiveness in tackling the risks. However, it has been shown that not all municipalities are capable of reducing the incidence of these risks over time and that, according to Fig. 58, this incidence is still generally high. So why is this happening?

In Section 2.1, three possible hypotheses have been put forward to explain this situation. Firstly, the analysis cluster does not enable a direct relationship to be seen between the land's geomorphological characteristics (mainly the mean slope SLm) and

the variation in risk. In other words, there are contradictory cases. The same could be said about municipalities with a greater or lesser volume of construction, proximity to the coast, etc. Hence, a greater or lesser risk value and a growing or falling trend cannot be attributed to the intrinsic qualities of the municipalities studied. Nor can they be attributed to strictly random factors, since there is coherent behaviour within the clusters analysed.

The above conclusions are bolstered when one considers the lack of temporal correlation found for the data in neighbouring series, together with the existence of global behaviour patterns (see Section 2.23). As a result of all of this, the assumption of greater or lesser risk and its temporal evolution seems to be exclusively due to the third hypothesis initially put forward in the aforementioned Section 2.1; i.e. land management. In this study, procedures have been proposed that are based on analyses of graphs and risk indicators in order to find trends and behaviours that may subsequently help to improve this land management.

The Risk Ratio (RR) developed in this article stands out as a robust indicator for directly finding the relationship between residential construction and its associated risk. It is especially useful for coastal municipalities with a high rate of construction, since it differentiates between those that take on a higher risk than those that do not. Nevertheless, in municipalities located in the inland mountainous strip, with a low residential construction density, high susceptibility and which do not usually have land planning, the values are also high. In these cases it is not possible to strictly attribute these values to unsuitable management.

In general, it is seen that coastal municipalities are more prone to assume greater specific risk (see Fig. 68), although the pace of growth in risk is lower than for construction. In mountainous municipalities in the inland strip, precisely the opposite happens. Of course there are a fair number of exceptions to this rule, but two coastal municipalities especially stand out, where their great construction intensity is exceeded by the growing pace of occupation of zones at risk. This is group B1, which includes Altea and Benitachell. The characteristics of Altea have already been specified. Although their land occupation has not reached the level of Calpe or Benidorm (the biggest in La Marina), both municipalities are characteristic for having a very high RR (500), which shows a growing occupation of locations at risk.

Benidorm is precisely an example worth highlighting (Fig. 24). It is a coastal municipality that is internationally known as a holiday destination with a notably mountainous profile. It has one of the biggest construction rates in the area, but this has not led to occupation of extensive risk areas, although there is a slight upward trend. It is not surprising, then, that this is the only example of “vertical” construction, where the mean number floors per building (5.85) is significantly greater than in the other municipalities in the study (2.09). Hence, it can be considered a suitable policy if the objective is to provide a greater amount of built-up area in relation to the risk taken ( $RR = 85.7$ , found in the first quartile).

To sum up, none of the basic risk parameters in any municipality seems to be determined by randomness, and only in the most mountainous ones is it determined by the orographic conditions of the land. Monitoring and restriction of building in risk zones must be applied mainly in the coastal municipalities with a greater rate of construction. Residential construction’s avoidance of zones at risk of landslide will depend on the municipal technicians having complete, up-to-date information in their urban development regulation planning; in other words, they should have been reviewed in the last decade. Only in this way will it be possible to have objective criteria in order to enforce urban development regulations and their implicit “precautionary principle” in order to guarantee the greatest possible level of protection.

The risks of landslide are a result of human activity itself, and it is also of great human concern to minimise them. The mechanisms for monitoring and control that should be working to reduce them must not be solely the responsibility of the

municipality, but also of public bodies of greater hierarchy that may ensure they are applied by using their best resources and regulatory capacity. Tools have been developed in this work to take objective decisions to suitably adapt land management, and this can be extended to other residential areas. Applying them does not guarantee that the problem will be eliminated, but at least it will help alleviate them and act as a guide to solve them.

*Data availability.* Borders and areas for the municipal territories and 5×5m DEM (Digital Elevation Model) are available on the Spanish Geographic Institute (IGN) website (<https://www.ign.es/web/ign/portal>). Database for landslides was processed from BD-MOVES, available on the Spanish Geomining Institute (IGME) ([http://mapas.igme.es/gis/rest/services/BasesDatos/IGME\\_BDMoves\\_ES/MapServer](http://mapas.igme.es/gis/rest/services/BasesDatos/IGME_BDMoves_ES/MapServer)), also from project entitled “Lithology, exploitation of industrial rocks and landslide risk in the Valencia Community”, available online on [http://www.cma.gva.es/areas/urbanismo\\_ordenacion/infadm/publicaciones/pdf/litologia/](http://www.cma.gva.es/areas/urbanismo_ordenacion/infadm/publicaciones/pdf/litologia/). The information referring to cadastral plots or parcels was obtained from the cadastral mapping available from the Spanish Cadastral Directorate (DGC) (<http://ovc.catastro.meh.es/INSPIRE/wfsCP.aspx?>). Landslide susceptibility map (LSM) with a resolution of 25 x 25 m in La Marina, can be found in Cantarino *et al.* (2019). Further information can be made available upon request to the corresponding author.

*Author contribution.* All authors contributed to conceptualization, leaded by IC, who also conducted formal analysis and initial draft. JS had a leading role on urban planning perspective. MA contributed to validation and data visualization. VM critically reviewed the paper and conducted pre- and post-publication stage.

*Competing interests.* The authors declare that they have no conflict of interest.

*Acknowledgements.* Authors acknowledge funding from Department of Geological and Geotechnical Engineering, Universitat Politècnica de València.

## References

- Revisiting planning systems and tools for adaptive and strategic planning. Urban Climate, vol. 7, 115–133. <https://doi.org/10.1016/j.uclim.2014.01.006>
- Birkmann J., Garschagen M., Setiadi N., (2014), New challenges for adaptive urban governance in highly dynamic environments: Revisiting planning systems and tools for adaptive and strategic planning. Urban Climate, vol. 7, p. 115–133. <https://doi.org/10.1016/j.uclim.2014.01.006>
- Cantarino, I., Gielen, E., Palencia, S. Torrijos, J. (2014). Assessing residential building values in Spain for risk analyses – application to the landslide hazard in the Autonomous Community of Valencia. Nat. Hazards Earth Syst. Sci., 14, 3015–3030
- Cantarino, I., Carrión, M.A., Goerlich, F., Martínez, V. (2019). A ROC analysis-based classification method for landslide susceptibility maps. Landslides 16: 265-282. DOI 10.1007/s10346-018-1063-4
- Cascini, L. (2008). Applicability of landslide susceptibility and hazard zoning at different scales. Engineering Geology, 102, 164-177. Doi: 10.1016/j.enggeo.2008.03.016
- Cascini, L., Bonnard, C., Corominas, J., Jibson, R., Montero-Olart, J. (2005). Landslide hazard and risk zoning for urban planning and development. Landslide risk management. Taylor and Francis, London, 199–235
- COPUT (1998). Litología, aprovechamiento de rocas industriales y riesgo de deslizamiento en la Comunidad Valenciana. Conselleria d’Obres Publiques, Urbanisme i Transports. Gobierno Valenciano.

- Corominas, J., Van Westen, C., Frattini, P., Cascini, L., Malet, J. P., Fotopoulou, S., Catani, F., Van Den Eeckhaut, M., Mavrouli, O., Agliardi, F., Pitilakis, K., Winter, M. G., Pastor, M., Ferlisi, S., Tofani, V., Hervás, J., and Smith, J. T. (2014). Recommendations for the quantitative analysis of landslide risk. *B. Eng. Geol. Environ.*, 73, 209–263, doi:10.1007/s10064-013-0538-8, 2014.
- Cruden, D., Varnes, D.J. (1996). Landslide types and processes. A.K. Turner, R.L. Schuster (Eds.), *Landslides Investigation and Mitigation*, Special Report, 247, Transportation Research Board, National Academy of Sciences, Washington D.C, 36-75
- Dai, F.C., Lee, C.F., Ngai, Y.Y. (2002). Landslide risk assessment and management: an overview. *Engineering Geology*, 64, 1, 65-87
- De Terán, F. (1982). *El problema urbano*. Salvat. Barcelona.
- Di Martire, Diego & Rosa, M. & Pesce, V. & Santangelo, M. & Calcaterra, Domenico. (2012). Landslide hazard and land management in high-density urban areas of Campania region, Italy. *Natural Hazards and Earth System Sciences*. 12. 905-926. 10.5194/nhess-12-905-2012.
- EEA - European Environment Agency (2006). Urban sprawl in Europe: The ignored challenge. European Environment Agency, Copenhagen
- Faccini, F., Luino, F., Sacchini, A., Turconi, F., De Graff, J.V. (2015). Geohydrological hazards and urban development in the Mediterranean area: an example from Geonova (Liguria, Italy). *Nat Hazards Earth Syst. Sci.* 15, 2631–2652, doi:10.5194/nhess-15-2631-2015
- Fell, R. (1994). Landslide risk assessment and acceptable risk. *Can. Geotech. J.*, 31, 261–272
- Fell, R., Corominas, J., Bonnard, Ch., Cascini, L., Leroi, E., and Savage, W. Z. (2008). Guidelines for landslide susceptibility, hazard and risk zoning for land use planning. *Eng. Geol.*, 102, 85–98
- Fernández Arce, M., Méndez Ocampo, I., Muñoz Jiménez, R. (2016). Impacto de los deslizamientos y asentamientos del suelo en el cantón Moravia. *Revista En Torno a la Prevención*, 17, 7-16
- Gallina, V., Torresan S., Critto A., Sperotto A., Glade T., Marcomini, A. (2016). A review of multi-risk methodologies for natural hazards: Consequences and challenges for a climate change impact assessment. *Journal of Environmental Management*, 168, 123-132, <https://doi.org/10.1016/j.jenvman.2015.11.011> <https://doi.org/10.1016/j.jenvman.2015.11.011>.
- Gariano, S.L., Guzzetti, F (2016), Landslides in a changing climate, *Earth-Science Reviews*, Volume 162, Pages 227-252
- Glade, T. (2003). Vulnerability assessment in landslide risk analysis. *Die Erde*, 134, 121–138
- Glade, T., Anderson, M., Crozier, M.J. (2006). *Landslide hazard and risk*. Wiley-Blackwell
- Goerlich, F.J., Cantarino, I., Gielen, E. (2017). Clustering cities through urban metrics analysis. *Journal of Urban Design*, 22:5, 689-708, DOI: 10.1080/13574809.2017.1305882
- Gough, J. (2000). Perceptions of risk from natural hazards in two remote New Zealand communities. *The Australasian Journal of Disaster and Trauma Studies*, Volume 2
- Guzzetti, F., Reichenbach, P., Cardinali, M., Galli, M., and Ardizzone, F. (2005). Probabilistic landslide hazard assessment at the basin scale. *Geomorphology*, 72, 272–299, <https://doi.org/10.1016/j.geomorph.2005.06.002>.
- Hamma, W., Petrișor, A.I., (2018). Urbanization and risks: case of Bejaia city in Algeria. *Journal of Studies and Research in Human Geography*. 12, 1, 97-114
- Hervás J. (2017). El inventario de movimientos de ladera de España ALISSA: Metodología y análisis preliminar. In: Alonso E, Corominas J, Hürlimann M (Eds.), *Taludes 2017. Proc. IX Simposio Nacional sobre Taludes y Laderas Inestables*, Santander, CIMNE, Barcelona, 629–639
- Huang, J. Lu, X.X, Sellers, J.M., (2007). A global comparative analysis of urban form: Applying spatial metrics and remote sensing. *Landscape and Urban Planning*, 82, 4, 184-197, <https://doi.org/10.1016/j.landurbplan.2007.02.010>.
- Kalsnes, B., Nadim, F., Hermanns, R., Hygen, H., Petkovic, G., Dolva, B., Berg, H., Høgvold, D. (2016). Landslide risk management in Norway. In: *Slope Safety Preparedness for Impact of Climate Change* 10.1201/9781315387789-9.1

- 830 Kappes, M.S., Papathoma-Köhle, M., Keiler, M. (2012). Assessing physical vulnerability for multi-hazards using an indicator-based methodology. *Appl. Geogr.* 32, 2, 577–590
- Katsigianni, X., Pavlos-Marinos, D. (2017). The interrelation between spatial planning policies and safety in the multi-risk insular setting of Santorini. Conference: 'Cities and regions in a changing Europe: challenges and prospects' - 54th Colloquium of the ASRDLF / 15th Conference of the ERSa Greek section At: Athens
- 835 Leone, F. (1996). Concept de vulnérabilité appliqué à l'évaluation des risques générés par les phénomènes de mouvements de terrain. Thèse de doctorat de l'Université Joseph Fourier, Grenoble I.
- Lee, E. M., Jones, D. K. C. (2004). *Landslide risk assessment*. Thomas Telford Books, London
- Lee, E. (2009). Landslide risk assessment: The challenge of estimating the probability of landsliding. *Quarterly Journal of Engineering Geology and Hydrogeology*, 42, 445-458. Doi.10.1144/1470-9236/08-007.
- 840 Lee, J., Lee, D. K., Kil, S-H., Kim, H. G. (2017). Risk-based analysis of monitoring time intervals for landslide prevention. *Nat. Hazards Earth Syst. Sci. Discuss.* <https://doi.org/10.5194/nhess-2017-356>
- Macintosh, A. (2013). Coastal climate hazards and urban planning: how planning responses can lead to maladaptation. *Mitigation and Adaptation Strategies for Global Change*, 18, 7, 1035-1055. DOI 10.1007/s11027-012-9406-2.
- Malvárez, G., Pollard, J. (2004). The planning and practice of coastal zone management in Southern Spain. B. Bramwell (Ed.),
- 845 Coastal mass tourism: Diversification and sustainable development in southern Europe, Aspects of tourism, 12, Channel View Publications, Clevedon, 200-219
- Palmisano, F., Vitone, C., Cotecchia, F., (2018). Assessment of Landslide Damage to Buildings at the Urban Scale. *J. Perform. Constr. Facil.*, 32, 4, 040180055
- Papathoma-Köhle, M., Kappes, M., Keiler, M., Glade, T. (2011). Physical vulnerability assessment for alpine hazards: state
- 850 of the art and future needs. *Nat. Hazards*, 58, 645–681
- Papathoma-Köhle, M., Gems, B., Sturm, M., Fuchs, S. (2017). Matrices, curves and indicators: A review of approaches to assess physical vulnerability to debris flows. *Earth-Science Reviews*, 171, 272-288
- Pardo-García, S., Mérida-Rodríguez, M. (2018). Physical location factors of metropolitan and rural sprawl: Geostatistical analysis of three Mediterranean areas in Southern Spain. *Cities*, 79, 178-186, <https://doi.org/10.1016/j.cities.2018.03.007>.
- 855 Peng, S.H., Wang, K. (2015). Risk evaluation of geological hazards of mountainous tourist area: a case study of Mengshan, China. *Nat. Hazards*, 78, 517–529. <https://doi.org/10.1007/s11069-015-1724-8>
- Pereira, S., Zêzere, J.L., Bateira, C. (2012). Technical note: assessing predictive capacity and conditional independence of landslide predisposing factors for shallow landslides susceptibility models. *Nat Hazards Earth Syst. Sci.*, 12, 979–988
- Renn, O., Klinke, A. (2013). A Framework of Adaptive Risk Governance for Urban Planning. *Sustainability*, 5, 5, 2036-2059.
- 860 doi:10.3390/su5052036.
- Sandić, C., Abolmasov, B., Marjanović, M., Marjanović, M., Begović, P., Jolović, B. (2017). Landslide Disaster and Relief Activities: A Case Study of Urban Area of Doboj City. Springer International Publishing, M. Mikoš et al. (eds.), *Advancing Culture of Living with Landslides*, 383-393, DOI 10.1007/978-3-319-53487-9\_45
- Silva, M., Pereira, S. (2014). Assessment of physical vulnerability and potential losses of buildings due to shallow slides. *Nat*
- 865 *Hazards*, 72, 10-29. <https://doi.org/10.1007/s11069-014-1052-4>
- Stewart, T.J., Janssen, R. (2014). A multiobjective GIS-based land use planning algorithm. *Computers, Environment and Urban Systems*, 46, 25-34, <https://doi.org/10.1016/j.compenvurbsys.2014.04.002>
- UNDRO (1979). *Natural Disasters and Vulnerability Analysis*. Report of Expert Group Meeting. Office of United Nations Disaster Relief Co-Ordinator (UNDRO), Geneva, Switzerland..
- 870 Wang, J.A., Shi, P.J., Yi, X.S., Jia, H.C., Zhu, L.Y. (2008). The regionalization of urban natural disasters in China. *Nat Hazards*, 44, 169–179. DOI 10.1007/s11069-006-9102-1

Zhai, G., Li, S., Chen, J. (2015). Reducing Urban Disaster Risk by Improving Resilience in China from a Planning Perspective. Human and Ecological Risk Assessment: An International Journal, 21, 5, 1206-1217. <https://doi.org/10.1080/10807039.2014.955385>.

875 Zhou, N.Q., Zhao, S. (2013). Urbanization process and induced environmental geological hazards in China. Natural Hazards, 67, 2, 797-810. DOI: 10.1007/s11069-013-0606-1

**Table 1. Characteristics of the Risk Ratio (RR).**

RR value	Type of curve	Characteristic	Discussion
>1	Monotonically increasing	Growth rate of the risk value greater than that of the built-up area.	Disproportionate risk growth, without restrictions or planning. Unfavourable situation. This must occur in section 1 of Fig. 1.
≈ 1	Monotonically constant	Growth rate of the risk value similar to that of the built-up area.	No well-defined evolution. Situation not clearly favourable.
<1	Monotonically decreasing	Growth rate of the risk value less than that of the built-up area	Growth of risk restricted, which must be due to some type of criterion. Favourable situation. This must occur in section 3 of Fig. 1.

**Table 2. Global indicators per UAD**

Name	Formula	Notes
Total Risk Ratio, $\overline{RRR}_t$ (€/1000 m <sup>2</sup> of GFA)	$\overline{RRR}_t = \Sigma RV / \Sigma GFA \times 1000$	Already commented in the text- (Eq xx).
Mean RR, $\overline{RR}_m$ (€/1000 m <sup>2</sup> of GFA)	$\overline{RR}_m = \Sigma \overline{RR}_m / n_y$	Less useful as it is an average of averages.
Mean no. of floors per CP, $\overline{NF}_m$	$\overline{NF}_m = (\Sigma (GFA/S_{CP})) / n_y$	Interesting to know the type of buildings in the UAD.
Mean no. of floors in CP affected by risk, $\overline{NF}_{mr}$	$\overline{NF}_{mr} = (\Sigma (GFA_r/S_{CP})) / n_y$	Interesting to know the type of buildings affected in the UAD.
Mean distance from the CP to the UAD's Historical Centre in a straight line, $\overline{D}_{hc}$ (m.)	$\overline{D}_{hc} = (\Sigma D_{hc} (CP_i)) / n_{CP}$	Quantifies the importance of the residential expansion.
Mean distance from CP to the coast in a straight line, $\overline{D}_c$ (m.)	$\overline{D}_c = (\Sigma D_c (CP_i)) / n_{CP}$	Establishes the proximity of the UAD to the sea.
Average slope of the UAD, $\overline{SL}_m$ (degrees)	$\overline{SL}_m = \text{mean Slope cells } (5 \times 5 \text{ m})$ [GIS calculated]	Indicates the type of profile (mountainous, flat, etc.).
Built-up area per unit of surface area, $\overline{SpGFA}$ (m <sup>2</sup> of GFA per km <sup>2</sup> of UAD)	$\overline{SpGFA} = GFA / S_{UAD}$	Rate or intensity of residential construction for the total of the UAD.
Risk per unit of surface area, $\overline{SpRV}$ (€ per km <sup>2</sup> of UAD)	$\overline{SpRV} = RV / S_{UAD}$	Rate or intensity of risk (specific risk) for the total of the UAD.
Slope of the straight trend line, $\overline{mRR}$ (degrees)	See equation (9xx)	Determines the trend of the RR value in a specific period.

CP: Cadastral Parcel;  $S_{CP}$ : surface area of the CP [GIS calculated];  $n_{CP}$ : number of CPs;  $n_y$ : number of years in the series;  $S_{UAD}$  = Urban administrative division Surface area (km<sup>2</sup>)

885 Table 3. Land Susceptibility Index (LSI) values for the classes under consideration

Class	Level	LSI interval	No. pixels
1	Very low	10 - 35	526 777
2	Low	35 - 60	359 376
3	Medium	60 - 95	692 863
4	High	95 - 149	350 051
5	Very high	149 - 340	201 170
TOTAL			2 130 237

Source: Cantarino *et al.* (2019)

Table 4. Probability of occurrence and associated hazard by susceptibility level

Class	Level (L)	Level Surface area (SL, has)	Risk Surface area (SRL, has)	Spatial Prob. (Ps)	<del>Temp.</del> Temporal Prob. (Pa)	Hazard (H)
1	Very low	32 923.6	0	0	--	0
2	Low	22 461.0	0	0	--	0
3	Medium	43 303.9	25 529	0.000589530005895	0.4	0.00024
4	High	21 878.2	233 675	0.010680720106807	0.4	0.00427
5	Very high	12 573.1	406 913	0.032363720323637	0.4	0.01295
Total		133 139.8	666 120			

890 Table 5. Vulnerability related to the number of floors.

Number of Floors (NF)	Landslide Magnitude (LM)	Building Resistance (BR)	Final Vulnerability (FV)
> 8	0.6	30%	0.42
8 - 4	0.6	20%	0.48
4 - 2	0.6	10%	0.54
≤ 2	0.6	0%	0.6



Table 6. Total values and global indicators per municipality. For indicators, means and variation intervals.

Name	Value	Name	Value
Total GFA (m²)	41 642 352	Total Risk Value <del>totalRV</del>	5 013 178
		(€)	
Total Risk Ratio	192.5 [0.21 – 869.3]	Dhc <sub>r</sub> (metres)	1 490.1 [95 – 3 954]
<del>RR-RRt</del>			
Mean RR <del>RRm</del>	208.5 [0.3 - 988]	Dc <sub>r</sub> (metres)	8 728.1 [1 047 – 19 466]
Mean Risk <del>RVm</del> (€)	2154.7 [31 – 23 252]	SLm (in degrees)	16.23 [9.8 – 24.6]
NFm	2.09 [1.41 – 5.85]	SpGFA <sub>r</sub> in (m² per km² of UAD)	26 643 [470 – 152-268170 659]
NFmr	1.87 [1.07 – 5.95]	SpRV <sub>r</sub> in € (€ per km² of UAD)	3388 [ 11 - 37412 ]
mRR Lo (degrees)	41.5 [83.7 ~ -89.2]	mRR Hi (degrees)	16.9 [86.5 ~ -87.8]

895 Table 7. ~~List of clusters with~~ Cluster centroids and their characteristics. High RR values in bold and highlighted levels organised from A (max) to D (min)

Cluster centroids								Other indicators (mean)	
Cluster numbe r	SpGFA x1000	RRLeve l	MunicipalitiesRR t	OthersLeve l	mR R Hi	Leve l	Cluste r CODE	SLm	SpR V x100 0
A11	170-659.7	A	86	Benidorm (*)C	38	B	ACB	SLm= 11.3 SpRV= 14-624	14.62
A22	152-268.3	A	80	Calpe (*)C	-58	D	ACD	SLm= 13.8 SpRV= 12-146	12.15
B13	69-492.5	B	500	Altea, Benitachell B	86	A	BBA	SLm= 14.5 SpRV= 35-000	34.34
B24	62-722.7	B	146	TeuladaC	53	B	BCB	SLm= 10.7 SpRV= 9-170	9.17
B35	75-089.1	B	52	Alfaz, Xabia (*), La Nucía (*), Denia (*)	-18	C	BCC	SLm= 10.8 SpRV= 3-740	3.74


Cluster centroids								Other indicators (mean)	
Cluster number	SpGFA x1000	RRLevel 1	Municipalities t	OthersLevel 1 2	mR R Hi	Level 1 3	Cluster CODE	SLm	SpRV x100 0
B46	50488.2	B	0.22	Villajoyosa C Ondara, VergelD	1	C	BDC	SLm=6	0.01
E17	18642.6	C	154	Callosa, Polop, Pedreguer, Pego, Sanet y NegralC	71	A	CCA	SLm=14.3	2.81
C28	20853 20040.4	62 164C	Beniarbeig, Benidoleig (*), Benissa (*), Finestrat (*), Gata de Gorgos (*), Orba (*), Rafol d'Almunia98	C	-19	C	CCC	SLm=14.2	1.96
D19	Improvable0.2	940D	679	ConfridesA	82	A	DAA	SLm=22.1	0.94
D110	3532.6	D	296	Alcalalí, Benifato, Benigembla , Benimantell , Lliber, Orxeta, Rellev (*), XalóB	77	A	DBA	SLm=19.6	0.93
D111	4384.4	D	88	Bolulla, Castell de Castells, Vall d'Ebo, Murla, Senija, Formos,	54	B	DCB	SLm=18.8	0.41

<u>Cluster centroids</u>								<u>Other indicators</u> (mean)	
<u>Cluster number</u>	<u>SpGFA</u> <u>x1000</u>	<u>RRLeve</u> <u>l</u> <u>1</u>	<u>MunicipalitiesRR</u> <u>t</u>	<u>OthersLeve</u> <u>l</u> <u>2</u>	<u>mR</u> <u>R Hi</u>	<u>Leve</u> <u>l</u> <u>3</u>	<u>Cluste</u> <u>r</u> <u>CODE</u>	<u>SLm</u>	<u>SpR</u> <u>V</u> <u>x100</u> <u>0</u>
D212	1-649.6	D	821	Vall de Laguarda, XalóC, Castell de Guadalest, Sella(*)A	-72	D	DAD	SLm=23.2	1.36
D213	2-508.5	D	324	Adsubia, Beniardá (*), Tárbenab	-66	D	DBD	SLm=22.3	0.79
D214	4-522.5	D	105	Benimeli (*), Vall de Alcalá (*), Pareent (*), Sagra (*), Vall de Gallinera (*)C	-39	C	DCC	SLm=16.7	0.52


**Table 8. List of clusters with their characteristics and assigned municipalities grouped by construction intensity ratio (SpGFA) from high to low.**

<b><u>Cluster CODE</u></b>	<b><u>Noteworthy Characteristics</u></b>	<b><u>Risk building management</u></b>	<b><u>Municipalities</u></b>
<u>ACB</u>	<u>High Spec. Risk</u>	<u>Improvable</u>	<u>Benidorm (*)</u>
<u>ACD</u>	<u>High Spec. Risk</u>	<u>Suitable</u>	<u>Calpe (*)</u>
<u>BBA</u>	<u>High RR. VHigh growth trend and Spec. Risk</u>	<u>Reviewable</u>	<u>Altea, Benitachell</u>
<u>BCB</u>	<u>High Spec. Risk</u>	<u>Improvable</u>	<u>Teulada</u>
<u>BCC</u>		<u>Suitable</u>	<u>Alfaz, Xabia (*), La Nucía (*), Denia (*), Villajoyosa</u>
<u>BDC</u>	<u>VLow RR. Coast plain area</u>	<u>Suitable</u>	<u>Ondara, Vergel</u>
<u>CCA</u>	<u>VHigh growth trend</u>	<u>Improvable</u>	<u>Callosa, Polop, Pedreguer, Pego, Sanet y Negrals</u>
<u>CCC</u>		<u>Suitable</u>	<u>Beniarbeig, Benidoleig (*), Benissa (*), Finestrat (*), Gata de Gorgos (*), Orba (*), Rafol d'Almunia</u>
<u>DAA</u>	<u>VHigh RR and growth trend. Inland hilly area</u>	<u>Improvable</u>	<u>Confrides</u>
<u>DBA</u>	<u>High RR &amp; VHigh growth trend. Inland hilly area</u>	<u>Improvable</u>	<u>Alcalalí, Benifato, Benigembla, Benimantell, Lliber, Orxeta, Relleu (*), Xaló</u>
<u>DCB</u>	<u>Inland hilly area</u>	<u>Improvable</u>	<u>Bolulla, Castell de Castells, Vall d'Ebo, Murla, Senija, Tormos, Vall de Laguart, Xaló</u>
<u>DAD</u>	<u>VHigh RR. Inland hilly area</u>	<u>Suitable</u>	<u>Castell de Guadalest, Sella (*)</u>
<u>DBD</u>	<u>High RR. Inland hilly area</u>	<u>Suitable</u>	<u>Adsubia, Beniardá (*), Tárbena</u>
<u>DCC</u>	<u>Inland hilly area</u>	<u>Suitable</u>	<u>Benimeli (*), Vall de Alcalá (*), Parcent (*), Sagra (*), Vall de Gallinera (*)</u>


(\*) Municipalities with a change in trend from the first part of a series to the second.




905 **Figure 1. Theoretical evolution of risk accumulated over time for a one-year series pattern**




**Fig. 2. Curve trend of different types of Risk Ratio**



**Fig. 3. La Marina area. Location of some municipalities mentioned in the text. Base map of**



**Fig 4. La Marina region provided by the Spanish Geographic Institute ([www.ign.es](http://www.ign.es)).area. Susceptibility, landslides location and areas with instabilities**



**Fig. 5**

**Figure 3. Flowchart of the work procedure.**




Figure 46. Evolution of the annual series of GFA, RV and RR in the municipalities of Calpe (a, b, c) and Altea (d, e, f).






Figure 57. Evolution of the annual series of GFA, RV and RR for the La Marina area.




Figure 6Fig. 8. Map of La Marina: (a) with cluster groups, (b) with the SpRV value. Municipalities borders provided by the Spanish Geographic Institute ([www.ign.es](http://www.ign.es)). (\*) Clusters D1: DAA, DBA, DCB; Clusters D2: DAD, DBD, DCC