

Challenging the timely prediction potential of landslide early warning systems with multispectral remote sensing: a novel conceptual approach tested in the Sattelkar, Austria

Doris Hermle¹, Markus Keuschnig², Ingo Hartmeyer², Robert Delleske² and Michael Krautblatter¹

¹Technical University of Munich, Chair of Landslide Research, Munich, Germany

²GEORESEARCH Forschungsgesellschaft mbH, Puch, Austria

Correspondence to: Doris Hermle (doris.hermle@tum.de)

Abstract

While optical remote sensing has demonstrated its capabilities for landslide detection and monitoring, spatial and temporal demands for landslide early warning systems (LEWS) were not met until recently. We introduce a novel conceptual approach for comprehensive to structure and quantitatively assess lead time assessment and optimisation for LEWS. We analysed “time to warning” as a sequence; (i) time to collect, (ii) to process and (iii) to evaluate relevant optical data. The difference between “time to warning” and “forecasting window” (i.e. time from hazard becoming predictable until event) is the lead time for reactive measures. We tested digital image correlation (DIC) of best-suited spatiotemporal techniques, i.e. 3 m resolution PlanetScope daily imagery, and 0.16 m resolution UAS derived orthophotos to reveal fast ground displacement and acceleration of a deep-seated, complex alpine mass movement leading to massive debris flow events. The time to warning for UAS and PlanetScope totals 31h/21h and is comprised of (i) time to collect 12/14h, (ii) process 17/5h and (iii) evaluate 2/2h, which is well below the forecasting window for recent benchmarks and facilitates lead time for reactive measures. We show optical remote sensing data can support LEWS with a sufficiently fast processing time, demonstrating the feasibility of optical sensors for LEWS.

1 Introduction

Landslides are a major natural hazard leading to human casualties and socio-economic impacts, mainly by causing infrastructure damage (Dikau et al., 1996; Hilker et al., 2009). They are often triggered by earthquakes, intense short-period or prolonged precipitation, and human activities (Hungr et al., 2014; Froude and Petley, 2018). In a systematic review Gariano and Guzzetti (2016) report in a review study that 80 % of the papers examined papers show causal relationships between landslides and climate change. The ongoing warming of the climate (IPCC, 2014) is likely to decrease slope stability and increase landslide activity (Huggel et al., 2012; Seneviratne et al., 2012), which indicates a vital need to improve the ability to detect, monitor and issue early warnings of landslides and thus to reduce and mitigate landslide risk. Early warning, as defined by the UN International Strategy for Disaster Reduction (UNISDR), refers to a set of capacities for the timely and effective provision of warning information through institutions, such that individuals, communities and organisations exposed to a hazard are able to take action with sufficient time to reduce or avoid risk and prepare an effective response (UNISDR, 2009). According to UNISDR (2006), an effective early warning system consists of four elements: (1) risk knowledge, the systematic data collection and risk assessment; (2) the monitoring and warning service; (3) the dissemination and communication of risk as well as early warnings; and (4) the response capabilities on local and national levels. Incompleteness or failure of one element can lead to a breakdown of the entire system (ibid.). Lead time as defined in the context of LEWS is the interval between the issue of a warning (i.e. dissemination) and the forecasted landslide onset (Pecoraro et al. 2019) and thus crucially depends on time requirements in phases (1)–(3). The success of an EWS therefore requires measurable pre-failure motion (or slow slope displacement) to allow for sufficient lead time for decisions on reactions and counter measures (Grasso, 2014; Hungr et al., 2014).

Kommentiert [DH1]: Correction of typo following comment by RC1 (J. Blöthe).

Kommentiert [DH2]: Modified following comment by Editor (M. Motagh)

Editor (M. Motagh) wrote:
I think the title needs to be changed. In the discussion and results you carefully addressed all shortcomings that may arise when using optical remote sensing for early warning. Therefore, I would not call it a novel approach. Rather you evaluated the potential that exists in optical remote sensing for early warning.

Kommentiert [DH3]: Modified following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
The used data sources (planet and UAV) do not allow optimization of lead time in the context of early warning because of the scarcity of their availability which is reflected in the small number of only three multitemporal data takes between July and September analyzed in this study (Table 3)

Kommentiert [DH4]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L1: Landslide

Kommentiert [DH5]: Modified following comment by RC1 (J. Blöthe) further below

RC1 (J. Blöthe) wrote:
L22/23: While this is certainly true, the authors should elaborate in the introduction that events instantaneously triggered by earthquakes or heavy precipitation are beyond what their proposed framework can deliver an early warning for. The necessity of gathering and evaluating data prior to issuing a warning limits the analysis to mass movements that indeed show a pre-failure acceleration on the order of days.

Kommentiert [DH6]: Author's revision in order to be more concise.

Kommentiert [DH7]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L25/26: Is this really just attributable to the warming of the climate?

Kommentiert [DH8]: Author's revision in order to be more concise.

Kommentiert [DH9]: Modified and moved this quite following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
The missing sound conceptual approach is also reflected in the introduction in form of a lengthy summary of in principle available remote sensing methods and data showing no clear line of arguments (L20-100). Moreover, the new conceptual approach presented in Fig. 1 is very general and not specific to landslide and does not qualify as a novelty in the current form.

Kommentiert [HD10]: Author's revision in order to be more concise.

Kommentiert [DH11]: Added definition following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
Concept of lead time and need for best possible reduction is not new.

... [1]

Kommentiert [DH12]: Modified following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
The missing sound conceptual approach is also reflected in the introduction in form of a lengthy summary of in principle available

... [2]

40 This definition of an early warning system (EWS) contains a time component but includes no exact time scale reference. 'Early' suggests that events are detected before harm or damage occurs and thus stands in contrast to events which are only detected once they have begun (e.g. snow avalanches). Thus, it is necessary to know sensor capabilities and limitations for pre-event mass movement observations (Desrues et al., 2019). The success of a warning requires that information is provided with enough lead time for decisions on reactions and counter measures (Grasso, 2014). The success of an EWS

45 therefore requires measurable prefailure motion (or slow transport velocities) to allow for sufficient lead time for decisions on reactions and counter measures (Grasso, 2014). While remote sensing has been established for early warnings, remote sensing is not yet used for real early warnings of the onset of landslides in steep–alpine terrain (with a few exceptions), where geotechnical instruments are still preferred. Exceptions include terrestrial InSAR (Pesci et al., 2011; Walter et al., 2020) and terrestrial laser scanning with high repetition rates. However, repeated UAS (unmanned aerial systems) and

50 optical satellite images (PlanetScope) with high repetition rates have so far not been applied for landslide early warning in steep-alpine catchments. In this regard, knowledge of sensor capabilities and limitations is essential, as it determines which rates and magnitudes of pre-failure motion can potentially be identified (Desrues et al., 2019). Our proposed framework refers to mass movements in steep–alpine catchments with significant pre-failure motion operating over a sufficient time periods and thus excludes instantaneous events triggered by processes such as heavy rainfalls or earthquakes. According to

55 UNISDR (2006), an effective early warning system consists of four elements: (1) risk knowledge, the systematic data collection and risk assessment; (2) the monitoring and warning service; (3) the dissemination and communication of risk as well as early warnings; and (4) the response capabilities on local and national levels. Incompleteness or failure of one element can lead to a breakdown of the entire system (ibid.).

This study presents a new concept to systematically evaluate remote sensing techniques to optimise estimate and increase

60 lead time for landslide early warnings in these catchments. We do not start from the perspective of available data; instead, we define necessary time constraints to successfully employ remote sensing data for providing early warnings. This approach reduces the to a small number of suitable remote sensing products to a small number with high temporal and spatial resolution. With these constraints, we investigated the application of data from satellites and unmanned aerial systems (UAS) to allow the assessment of the data, after a spaceborne area-wide but low-resolution acquisition, into a downscaled

65 detailed image recording. In so doing, we analysed the capability of these different passive remote sensing systems focusing on spatiotemporal capabilities for ground motion detection and landslide evolution to provide early warnings.

Until Recently, the spatial and temporal resolution of optical satellite imagery has significantly improved requirements for accurate early warning purposes have not been met by optical satellite imagery (Scaioni et al., 2014) and has allowed

70 substantial advances in the definition of displacement rates and acceleration thresholds to approach requirements for early warning purposes. This is essential since spatial and temporal resolution determines whether landslide monitoring is possible with the detection allows defining of displacement rates and approximate enables approximating acceleration thresholds, both of which are lacking if information is based solely on post-event studies (Reid et al., 2008; Calvello, 2017). Landslide monitoring therefore not only deepens the understanding of landslide processes but also has offers the potential to

75 significantly advance landslide early warning systems (LEWS) (Chae et al., 2017; Crosta et al., 2017). Previously, high spatial resolution satellite data was obtained at the expense of a reduction in the revisit rates (Aubrecht et al., 2017). Consequently, the return period between two images increased, limiting ground displacement assessment and the range of observable motion rates. The number of useful images was further reduced due to natural factors such as snow cover, cloud cover and cloud shadows. High-resolution remote sensing data was long restricted due to high costs and data volume

80 (Goodchild, 2011; Westoby et al., 2012). Today Commercial very high resolution (VHR) optical satellites exist, but tasked acquisitions make them inflexible and very cost intensive, thus limiting research (Butler, 2014; Lucieer et al., 2014). There is a vast spectrum of available remote sensing data with high spatiotemporal resolution (Table 1). Complementary use of

Kommentiert [DH13]: Modified following comments by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
The study site (starting at L175) represents a very complex landslide case leading to rather erratic mass movements in form of debris flows initiated by changing slope water conditions related to increased atmospheric precipitation. This situation is another obstacle for an early warning approach which is solely based on optical remote sensing data and thus making it impossible to make full use of the in principle daily temporal resolution of the planet data. Taking into account these natural conditions and the constraints introduced by the used imaging constellations, leaves no room for true optimization of lead time in the sense as stated in the overall scientific goal of this paper.

and

Any sensible early warning approach for slope movements requires a continuous and reliable high temporal resolution input of observation data related to parameters which are relevant for triggering the potential mass movements. Such information are mostly provided by ground based measurements. In this context, it is surprising that no relevant ground based monitoring information seem to be available to this study despite the longterm history of scientific work at this study site.

Kommentiert [DH14]: Modified following comment by RC1 (J. Blöthe) for previous L22/23

Kommentiert [DH15]: Modified following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
Concept of lead time and need for best possible reduction is not new.

and

The used data sources (planet and UAV) do not allow optimization of lead time in the context of early warning because of the scarcity of their availability which is reflected in the small number of only three multitemporal data takes between July and September analyzed in this study (Table 3)

Kommentiert [DH16]: Modification following comment by RC2 (S. Roessner) to be more concise

RC2 (S. Roessner) wrote:
The missing sound conceptual approach is also reflected in the introduction in form of a lengthy summary of in principle available remote sensing methods and data showing no clear line of arguments (L20-100). Moreover, the new conceptual approach presented in Fig. 1 is very general and not specific to landslide and does not qualify as a novelty in the current form. Sattel.

Kommentiert [DH17]: Modified following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
Remote sensing techniques themselves are not the bottleneck for shortening the lead time.

Kommentiert [HD18]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
I would think that also the rate of landslide movement defines whether or not it can be detected by optical imagery.

Kommentiert [DH19]: Modification by the authors to be brief.

different remote sensing sources can significantly improve landslide assessment as demonstrated by Stumpf et al. (2018) and Bontemps et al. (2018), who draw on archive data and utilise different sensor combinations to analyse the evolution of ground motion.

Table 1 Overview of different optical multispectral remote sensors with their corresponding resolution [m] and revisit rate [days]. The sensors are categorised into commercial and free data policy. ¹free quota via Planet Labs Education and Research Program, ²PlanetScope Ortho Scene Product, Level 3B/Ortho Tile Product, Level 3A (Planet Labs, 2020b), ³reached end of life, 3/2020, archive data usable, ⁴5 m Ortho Tile Level 3A (Planet Labs, 2020a), ⁵0.5 m colour pansharpened, ⁶self-acquired. Source: (ESA, 2020).

Sensor	Temporal resolution [d]	Spatial resolution [m]	Free/Commercial
UAS	flexible	0.08	F ⁶
WorldView 2	1.1	1.84	C
WorldView 3	<1	1.24	C
WorldView 4	<1	1.24	C
GeoEye 2	5	1.24	C
SkySat	1	1.5	C
GeoEye-1	3	1.64	C
Pléiades 1A/B	1	2.0 (0.5) ⁵	C
PlanetScope	1	3.0/3.125 ²	C/F ¹
RapidEye ³	5.5	5 ⁴	F
Sentinel-2 A/B	5	10	F
Landsat 8	16	30	F

The latest developments in earth observation programs include both the new Copernicus' Sentinel fleet operated by the ESA, and a new generation of micro cube satellites, sent into orbit in large numbers by PlanetLabs Inc. These PlanetScope micro cube satellites, known as 'Doves'/PlanetScope (from now on referred to as PlanetScope satellites), and Sentinel-2 a/b offer very high revisit rates of 1–5 days and high spatial resolutions from 3–10 m, respectively (Table 1), for multispectral imagery (Drusch et al., 2012; Butler, 2014; Breger, 2017). This opens up unprecedented possibilities based on these high spatiotemporal resolutions open up unprecedented possibilities to study a wide range of landslide velocities and natural hazards through remote sensing. Future-Continuing data access is fostered by PlanetLabs and by Copernicus (via its open data policy) providing affordable or free data for research. This leads to unprecedented possibilities for studying natural hazards through remote sensing. Examples of landslide activity such multi-temporal studies employing multi-temporal datasets of landslide activities based on this access to high spatiotemporal data are include Lacroix et al. (2018), using Sentinel-2 scenes to detect motions of the 'Harmalière' landslide in France, and Mazzanti et al. (2020), who applied a large stack of PlanetScope images for the active Rattlesnake landslide, USA.

As foreeasted landslides tend to accelerate beyond the deformation rate observable with radar systems before failure, we concentrate on optical image analysis (Moretto et al., 2016). One advantage of optical imagery is its temporally dense data (Table 1) compared to open data radar systems with sensor visits-repeat frequency more than every six days and revisit frequency between three days at the equator, about two days over Europe and less than one day at high latitudes (Sentinel-1, ESA). Optical data allows direct visual impressions-impression from the multispectral representation of the acquisition target and the option to employ this data for further complementary and expert analyses. While active radar systems overcome constraints posed by clouds and do not require daylight, data voids can be significant due to layover or shadowing effects in steep mountainous areas (Moretto et al., 2016; Mazzanti et al., 2012; Plank et al., 2015; Moretto et al., 2016). Moreover, north/south facing slopes are less suitable, thus limit the range of investigation (Darvishi et al., 2018). In general, sensor choice depends on the landslide motion rate with radar at the lower and optical instruments at the upper motion range (Crosetto et al., 2016; Moretto et al., 2017; Lacroix et al., 2019).

However, As flexible, cost-effective alternative to spaceborne optical data are airborne optical images taken by UASs (unmanned-aerial-system). Freely selectable flight routes and acquisition dates prevent-enable avoiding shadows from clouds and topographic obstacles, and-as well asHow-avoiding unfavourable weather conditions and summer time snow cover, all

Kommentiert [DH20]: Modification by the authors in order to enhance understanding.

Kommentiert [DH21]: Modification by the authors in order to be more concise.

Kommentiert [DH22]: Modification by the authors in order to be more concise.

Kommentiert [DH23]: Added literature source by the authors.

Kommentiert [DH24]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L79/80: This is the maximum revisit time at the equator, right? For the study area shown here, revisit time should be shorter.

Kommentiert [DH25]: Spelling correction by the authors.

Kommentiert [DH26]: Added literature source by the authors.

Kommentiert [DH27]: Modification by the authors in order to be more concise.

of which frequently impair satellite images (Giordan et al., 2018; Lucieer et al., 2014). UAS-based surveys provide accurate very high resolution (few cm) orthoimages and digital elevation models (DEM) of relatively small areas, suitable for detailed, repeated analyses and geomorphological applications (Westoby et al., 2012; Turner et al., 2015).

In recent years, data provision for users has increased and today data hubs provide easy accessibility to rapid, pre-processed imagery. ~~Knowledge of the most useful remote sensing data options is vital for complex, time-critical analyses such as ground motion monitoring and landslide early warning.~~ Nonetheless, technological advances can be misleading as they promise high spatiotemporal data availability, which frequently does not reflect reality (Sudmanns et al., 2019). One key problem is the realistic net temporal data resolution which is often significantly reduced due to technical issues, such as image errors and non-existent data (i.e. data availability, completeness, reliability). Other problems include data quality and accuracy in terms of geometric, radiometric and spectral factors (Batini et al., 2017; Barsi et al., 2018). ~~Knowledge of the most useful remote sensing data options is vital for complex, time-critical analyses such as ground motion monitoring and landslide early warning.~~ Timely information extraction and interpretation are critical for landslide early warnings yet few studies have so far explicitly focused on time criticality and the influence of the net temporal resolution of remote sensing data.

In this investigation we propose both a conceptual approach to evaluating lead time as a time difference between the “time to predict” and the “forecasting time” and assess the suitability of UAS sensors (0.16 m) and PlanetScope (3 m) imagery (the latter with temporal proximity to the UAS acquisition) for LEWS. For this we have chosen the 'Sattelkar', a steep, high-alpine cirque located in the Hohe Tauern Range, Austria (Anker et al., 2016). We estimate times for the three steps (i) collecting images, (ii) pre-processing and motion derivation by digital image correlation (DIC) and (iii) evaluating and visualizing. The results from the Sattelkar site – and from historic landslide events – will be discussed in terms of usability and processing duration for critical data source selection which directly influences the forecasting window. Accordingly, we try to answer the following research questions:

1. How can we evaluate lead time as a time difference between the “time to predict” and the forecasting time for high spatiotemporal resolution sensors?
2. How can we quantify “time to warning” as a sequence of (i) time to collect, (ii) to process and (iii) to evaluate relevant optical data?
3. How can we practically derive profound “time to warning” estimates as a sequence of (i), (ii) and (iii) from UAS and PlanetScope high spatiotemporal resolution sensors?
4. Are estimated “times to warning” significantly shorter than the forecasting time for recent well-documented examples and able to generate robust estimations of lead time available to enable reactive measures and evacuation?

2 Lead time – a conceptual approach

2.1. The conceptual approach

Natural processes and ~~natural~~ their developments constantly take place independently, thus dictate the technical approaches and methodologies researchers ~~must can and must~~ apply within a certain time period. For that reason, we hypothesise the forecasting window t_{external} is externally controlled, consequently the applicability of LEWS methods (t_{internal}) is restricted because they must be shorter than t_{external} . This approach is the framework of our time concept (Fig. 1).

Kommentiert [DH28]: Sentence moved by the authors, see comment further below.

Kommentiert [HD29]: Restructured following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
Remote sensing techniques themselves are not the bottleneck for shortening the lead time.


Kommentiert [DH30]: Modified to comment by RC1 (J. Blöthe), please see also answer to comment in response

RC1 (J. Blöthe) wrote:
L103/105: Check grammar

Kommentiert [DH31]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L121: What do you mean by “natural developments” and how are these conditioned or different from natural processes?

Kommentiert [HD32]: Author's revision in order to be more concise.



155 **Figure 1** The novel conceptual approach for lead time, time to warning and the forecasting window for optical image analysis.

The forecasting window is started (t_{external} , green dashed outline) following significant acceleration exceeding a set displacement threshold, leading to a continuous process. Simultaneously with the forecasting window, time to warning (t_{warning}) starts (grey outline). Time to warning is divided into a three-phase-process to allow time estimations for a comparative assessment of different types of remote sensing data. This process consists of the phases (1) time to collect, (2) time to process and (3) time to evaluate, each with their individual durations. Confidence in the forecasted event increases with time as process acceleration becomes more certain. Once a warning is released (orange box), the lead time begins (t_{lead}) and is terminated by the following release and subsequent impact (red box). The lead time is the difference between the forecasting window and the time to warning. During the lead time, reaction time (t_{react}) starts when appropriate counter measures are taken to prepare for and reduce risks ahead of the impending event, and ends with the final impact.

165 The time to warning period (t_{warning}) is defined by the time necessary to systematically collect data, analyse the available information and to evaluate it. Hence, the greater the lead time, the more extensive countermeasures can be implemented prior to the event. An imperative for an effective EWS, the required time to take appropriate mitigation and response measures has to be within the lead time interval (t_{lead}) (Pecoraro et al., 2019) with $t_{\text{lead}} \geq t_{\text{react}}$.

2.2. Practical implementation of multispectral data in the concept General applicability to optical data

170 The time to warning consists of a three-phase-process (see Sect. 2.1. and Fig. 1) to allow rough time estimations for a comparative assessment of different types of remote sensing data. Nevertheless, to realise this temporal concept an established, operating system is required, which includes reference data (DEM, previous results), experience from past field work and ready UAS flight plans with preparation for a UAS flight campaign, satellite data access, experience in the single software processing steps including final classification and visualisation templates and, if utilised for UAS, installed and measured ground control points.

Kommentiert [DH33]: Answer and modified Fig. 1 in line to comment by RC1 (J. Blöthe) please see response

Figure 1: While I like the idea behind this conceptual figure, I would recommend the authors add a time axis and limit the area of "significant acceleration" to a vertical line that coincides with $t = 0$. In the present form, the conceptual figure contradicts statements in the text, such as "The forecasting window is started [...] following significant acceleration [...]" (L126), or "Simultaneously with the forecasting window, time to warning (t_{warning}) starts (grey outline)" (L128/129).

Kommentiert [DH34]: Modified following suggestion by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
Figure 1: While I like the idea behind this conceptual figure, I would recommend the authors add a time axis and limit the area of "significant acceleration" to a vertical line that coincides with $t = 0$. In the present form, the conceptual figure contradicts statements in the text, such as "The forecasting window is started [...] following significant acceleration [...]" (L126), or "Simultaneously with the forecasting window, time to warning (t_{warning}) starts (grey outline)" (L128/129).

Kommentiert [DH35]: Our comment to the suggestion by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L133/134: This also does not match what Fig. 1 is showing

Kommentiert [DH36]: Answer to comment by RC1 (J. Blöthe) in response letter.

RC1 (J. Blöthe) wrote:
L139: This also does not match what Fig. 1 is showing. In Fig. 1, $t_{\text{lead}} < t_{\text{react}}$.

Kommentiert [HD37]: Modified in response to comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:
L140: This subheading does not fit the content of this section comprising a compilation of rather basic and general steps of remote sensing data processing.

The first phase includes the collection of data starting from the acquisition by the sensor, the data transfer, image pre-processing and provision to the end user. The user selects images online from the data hub, downloads and organises them. For a UAS campaign, the user must obtain flight permits, check flight paths and conduct the UAS flight. The second phase encompasses time to process for the complete data handling from the downloaded data to final analysis-ready image stacks in a GIS or a corresponding software. These preparatory steps may include image selection and renaming, atmospheric correction, co-registration, resampling and translation to other spatial resolutions and geographic projection systems, adjustments such as clipping, stacking of single bands into one multispectral image or the division into single bands, calculation of hillshade from DEM among others, depending on the requirements. Following this preparation, the data is processed with the appropriate software tools to derive ground motion, calculate total displacement and derive surface changes, e.g. volume calculations or profiles. In the third and last phase, time to evaluate, the results are compared to inventory data and, if available, ground truth data, displacement results of other sensors or different spatial resolutions, different time interval variations to observe changes in sensitivity to meteorological conditions. Additionally, filters may be applied to eliminate noise. Finally, the results are analysed and evaluated. In each phase quality management is carried out for data access and pre- and post-processing. In time to collect, the images must be selected manually prior to any download from the data hub, as its filter tool options on cloud and scene coverage are of limited help. Accordingly, the areal selection may be misleading as the region of interest (RoI) might not be fully covered, though the sought-for, smaller area of interest (AoI) is covered but not returned from the request. Concerning cloud filters, first, the filter refers to the RoI as a whole in terms of percentage of cloud coverage. The AoI can still be free of clouds or else be the only area covered by clouds in the total RoI. Therefore, an image is either not returned although usable, or returned but not useable. Second, clouds can create shadows for which no filter is available. As a result, affected images have to be manually removed by the user. Images which are of low quality due to snow cover have to be discarded, too. These actions indirectly represent first quality checks in the collection phase. In the following processing phase, the images in a GIS, are checked for quality and accuracy. Depending on the data provider, some pre-processing such as radiometric, atmospheric and/or geometric corrections may have been conducted. During this phase, additional user-based steps will be checked if necessary. Finally, the results are compared to other data (e.g. DEM, dGPS), reviewed for their validity and may be supplemented by statistical evaluation.

3 Study Site

The Sattelkar is a steep, high-alpine, deglaciated west-facing cirque at an altitude of between 2 130–2 730 m asl in the Obersulzbach valley, Großvenedigergruppe, Austria (Fig. 2a). Surrounded by a headwall of granitic gneiss, the cirque infill is characterised by massive volumes of glacial and periglacial debris as well as rockfall deposits (Fig. 2b, c). Near-surface temperature data indicates sporadic permafrost distribution in the upper part of the cirque. Since 2003 surface changes have taken place as evidenced by a massive degradation of the vegetation cover and the exposure and increased mobilisation of loose material. A terrain analysis revealed that a deep-seated, retrogressive movement in the debris cover of the cirque had been initiated (Anker et al., 2016; GeoResearch, 2018). High water (over)saturation is assumed to be causing the spreading and sliding of the glacial and periglacial debris cover on the underlying, glacially smoothed bedrock cirque floor forming a complex landslide (Hungr et al., 2014). Detailed aerial orthophoto analyses, witness reports and damage documentations indicate a steady increase in mass movement and debris flow activity over the last decade (Anker et al., 2016).

Kommentiert [DH38]: Added by the authors to be in line with the introduction and conclusion.

Kommentiert [HD39]: Deleted by the authors and detailed description further below.




Figure 2 (a) Overview map Austria (Österreichischer Bundesverlag Schulbuch GmbH & Co. KG and Freytag-Berndt & Artaria KG, Vienna/Wien). (b) Sattelkar, 30.6.2019 with the debris cone of the 2014 debris flow event and (c) UAS orthophoto (04.09.2019, 1:1.000) showing boulder sizes of 5–10 m used for manual motion tracking, (d) active boulder blocks from the central AoI.

In August 2014, heavy ongoing precipitation triggered massive debris flow activity of 170 000 m³ in volume, of which approximately 70 000 m³ derived from the catchment above 2 000 m. A further 100 000 m³ was mobilised in the channel within the cone. The consequence was that the Obersulzbach river was blocked leading to a general flooding situation in the catchment, resulting in substantial destruction in the middle and lower reaches (Fig. 3).




Figure 3 Obersulzbach valley, flood event September 2014. (a) Flooding situation in the Obersulzbach valley with the Sattelkar landslide cone deposit (image centre). (b) Flood area at the valley mouth in Sulzau and Schaffau. The Salzach river is at the bottom of the image. ©Salzburger Nachrichten/Anton Kaindl.

The Sattelkar has been the focus of international research projects such as “PROJECT Sattelkar” (GeoResearch, 2018) and AlpSenseBench (TUM, Chair of Landslide Research, 2020) since 2018. In 2015 preliminary findings revealed a mass movement coverage of 130 000 m² with approximately 1 mio. m³ of debris and displacement rates of more than 10 m a⁻¹. The debris consists of boulders up to 10 m in diameter (Fig. 2c, d) allowing visual block tracking [and delimiting the active process area](#). High displacement was measured between 2012 and 2015 with up to 30 m a⁻¹.

In the Sattelkar cirque, several monitoring components are installed to provide ongoing and long-term monitoring. [Nine permanent ground control points \(GCPs\) measured with a dGPS to provide stable and optimal conditions to derive orthophotos from highly accurate UAS images \(GeoResearch, 2018\)](#). A total number of 15 near surface temperature loggers (buried at 0.1 m depth) recorded annual mean temperatures slightly above the freezing point (1–2 °C) in the period 2016 to 2019. Ground thermal conditions at depth react with significant lag times to recent warming and therefore are primarily determined by climatic conditions of the past (Noetzli et al., 2019). Significantly cooler climatic conditions in previous decades and centuries (Auer et al., 2007) thus likely contributed to the formation of (patchy) permafrost at the Sattelkar

Kommentiert [HD40]: Modified in response to comment by RC1 (J. Blöthe) by changing Vienna to Wien. Otherwise this is according to the publishing company and the copyright statement from the online map.

RC1 (J. Blöthe) wrote:
L185: Is this really the source the authors need to cite for the location map?

Kommentiert [HD41]: Correction by the authors.

Kommentiert [DH42]: Revision by the authors to be more concise following the deletion later in text.

Kommentiert [HD43]: Author's modification to enhance site specific understanding.

cirque. Recent empirical–statistical modelling of permafrost distribution in the Hohe Tauern Range confirms possible permafrost presence at the study site (Schrott et al., 2012).

These components include 30 near surface temperature loggers (NSTLs) and nine permanent ground control points (GCPs) measured with a dGPS to provide stable and optimal conditions for the derivation of orthophotos from highly accurate UAS images (GeoResearch, 2018). Field-based mapping and measurements help to delimit the active process area.

The Sattelkar is a suitable case study as it is in the early stages of the landslide development and thus fits best to this conceptual approach. Here, processes take place on time scales appropriate for long-term observation to provide sufficient warning time. The active part of the cirque has accelerated in recent years allowing the analysis of EWS concepts based on multispectral optical remote sensing data supported by complementary block tracking.

4 Materials and Methods

4.1. Optical imagery

Optical satellite imagery is more appropriate for high deformation studies than radar applications due to the high spatial resolution as well as the short time span between acquisitions (Delacourt et al., 2007). Although the west-facing slope is favourable for the application of radar derivatives (InSAR/DInSAR), the choice to use optical imagery is based on the observed high displacement rates, which cause decorrelation when using radar technologies as they are more sensitive than optical technologies. Complex and/or large displacement gradients make the phase ambiguity difficult to solve for radar interferometry (Kääb et al., 2017). Revisit times of current radar satellites (e.g. Sentinel-1) are longer than those of optical satellites, and if time periods between image acquisition become too long, ground motion may accumulate such that the displacement is too high to be measured. Several studies on displacements of faults and landslides have shown the potential of optical data to provide detailed displacement measurements based on image correlation techniques (DIC) (Leprince et al., 2007; Rosu et al., 2015). A further advantage of optical images for geomorphological processes in steep terrain is their viewing geometry (close to nadir) (Lacroix et al., 2019). Here we employ DIC to compare the spatiotemporal resolution of multispectral optical imagery (UAS and PlanetScope) and to assess its suitability for early warning purposes. UAS images offer excellent spatial resolution and accuracy at the centimetre scale (Turner et al., 2015) and complement large scale satellite or airborne acquisitions (Lucieer et al., 2014). PlanetScope imagery provides the highest temporal resolution among available sensors with daily acquisitions, guaranteed data availability, and free and open access for research purposes. In this study the PlanetScope Analytic Ortho Scene SR (surface reflectance) imagery (16-bit, geometric-, sensor- and radiometric corrections) was employed (Planet Labs, 2020b) and was supported by the Planet Labs Education and Research Program.

4.2. Data availability of PlanetScope

Research on the availability and usability of PlanetScope imagery was conducted on the Planet Explorer data hub for the time span from the beginning of April to the end of October in 2019, as during these months snow cover should be negligible. Filter parameters were solely set for 4-band PlanetScope Ortho Scenes and the Sattelkar AoI. In order to obtain all available images, no filters (e.g. sun azimuth, off nadir angle) were applied. We defined four categories i) meteorological constraints due to snow cover, cloud cover and cloud shadow; ii) image (coverage) errors made by the provider, iii) no data availability and iv) the remainder of usable data (Table 2). The output request was evaluated according to the defined categories and was compared to the provider's guaranteed daily image provision, which is comprised of 213 days for the time period (01.04.2019–31.10.2019). We calculated percentages for the above categories based on days per month as well as a seven-month sum and percentage average. The availability analysis did not include an examination of the data with regard to its spatial usability: positional accuracy and/or image shifts.

Kommentiert [HD44]: Author's revision: deleted and improved earlier in text.

Kommentiert [DH45]: Author's revision: deleted and improved earlier in text.

Kommentiert [DH46]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L215/L27: In theory yes, but as you show later (Tab. 2), the effective revisit time of optical imagery might in fact be very similar.

Kommentiert [DH47]: Added to facilitate understanding following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
B)
• Use a hillshade not a DEM for tracking (not clear if this was done)
• Resample the DEM to a slightly coarser resolution (0.5 m²)

Kommentiert [DH48]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L229: beginning of April

Table 2 PlanetScope 4–band data availability and usability for Sattelkar AoI for April to October 2019.

Month	April (%)	May (%)	June (%)	July (%)	August (%)	September (%)	October (%)	7 month sum	7 month avg (%)
usable	0.0 %	0.0	20.0	22.6	9.7	13.3	9.7	23	10.7
unusable									
cloud cover/shadow	16.7	6.5	0.0	19.4	32.3	16.7	9.7	31	14.5
snow cover	10.0	0.0	33.3	0.0	0.0	3.3	3.2	15	7.0
image errors	23.3	25.8	16.7	12.9	29.0	20.0	19.4	45	21.0
no coverage/data voids	10.0	12.9	16.7	32.3	16.1	20.0	32.3	43	20.1
not available									
no upload	40.0	54.8	13.3	9.7	12.9	26.7	25.8	56	26.2

Unfavourable meteorological influences of cloud cover/shadow and snow cover affected up to 32.3 % and up to 33.3 %, respectively, on all 213 days; on average 14.5 % and 7 % of the days were not usable (Table 2). For 10 days in June snow influence had the greatest negative share (33.3 %), for April there were three days of snow coverage and the months September and October each had one day of snow coverage. Cloud cover/shadow exerted a higher impact on data usability by 14.5 %. Problems on the part of PlanetLabs made much of the data unusable due to image errors; between four and nine images per month were not usable (21 %). On average for 26.2 % of the analysed time period no image data was available.

In this seven-month period, 43 images (20.1 %) had data voids or did not cover the AoI, thus the overall usability is limited to about 11 %.

4.3. Data Acquisition and Processing

In line with the concept in Fig. 1 (Sect. 1), the following processing steps are categorised and described.

(1) t_{collect} : UAS data acquisition was preceded by detailed flight route planning and checks of local weather and snow conditions. UAS flights were carried out with a DJI Phantom4 UAS on 13.07.2018, 24.07.2019 and 04.09.2019 (see Table 3, Fig. 4, [Fig. 6b, c](#)).

Table 3 Acquisition dates of UAS and PlanetScope images, in chronological order.

Acquisition set	UAS	PlanetScope
(1)	13.07.2018 13 July 2018	02.07.2018 02 July 2018 (a), 19.07.2018 19 July 2018 (b)
(2)	24.07.2019 24 July 2019	24.07.2019 24 July 2019
(3)	04.09.2019 04 September 2019	04.09.2019 04 September 2019

For each acquisition, the total area was covered by four flights which were started on different elevations (Table 4). Flight planning was done with UgCS maintaining a high overlap (front: 80 %, side: 70 %) and a target ground sampling distance (GSD) of 7 cm. The area covered was approximately 3.4 km² and with a flight speed of about 8 m/s total flight time took 3.5 hours. The images were captured in RAW format. In the Planet Explorer Data Hub, PlanetScope Ortho Scenes were selected for usability; imagery affected by snow cover, cloud cover, cloud shadow and partial AoI coverage was discarded (Table 5).

Table 4 UAS Flight plans.

Flight plan parts	Length of flightpath [km]	Flight time [min]	Passes	No. of images	GSD [cm]	Altitude start point [m]	Highest flight position [m]	Lowest terrain point [m]
Top	6.8	17	6	121	7	2630	3120	2365
Middle	7.5	19	6	135	7	2200	2682	1820
Low 1	7.3	17	6	130	7	1768	2115	1620
Low 2	5.6	14	6	81	7	1768	2110	1620

Kommentiert [DH49]: Added by the authors after modification of Fig. 6 according to RC2 (S. Roessner)

Kommentiert [DH50]: Modified following comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
Table 3: Here you use a different date format than in the text

Kommentiert [DH51]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L257: UgCS-Software?

Kommentiert [DH52]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
Table 4: Unit for GSD missing

Total	27.2	67	24	467	7	3120	1620
-------	------	----	----	-----	---	------	------

Table 5 Planet Scope Ortho Scenes.

Acquisition Date	Acquisition time (local)	Identifier	Incidence Angle [deg]
02.07.2018	11:34	20180702_093434_0f3f_3B_AnalyticMS_SR	2.18E-01
19.07.2018	11:35	20180719_093512_0f3f_3B_AnalyticMS_SR	2.36E-01
24.07.2019	11:42	20190724_094200_1014_3B_AnalyticMS_SR	5.57E+00
04.09.2019	11:36	20190904_093632_0e20_3B_AnalyticMS_SR	4.24E+00

Formatierte Tabelle

Kommentiert [DH53]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L273/274: Add this information to Table 5 and delete here

Kommentiert [DH54]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:
Thank you for clarifying this. Please, include this in the manuscript and replace the ambiguous term "spectral colour problems" with the much more precise spatial offset or "shifts in the individual bands".

Kommentiert [DH55]: Modified following comment by RC1 (J. Blöthe), additional information please see our response.

RC1 (J. Blöthe) wrote:
L267/269: Please elaborate how you filtered for "errors of location, shift and spectral colour problems" (are the latter spectral differences between images?).

Kommentiert [DH56]: Modified in line with comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L273/274: Add this information to Table 5 and delete here

(2) t_{process} : In phase two (time to process) the PlanetScope images were visualised in QGIS. Thereafter, a second selection (visually with the 'Map Swipe Tool' plugin) from the downloaded images was filtered for errors of location, inter-tile shift and shifts in the individual bands spectral colour problems which were previously not clearly discernible in the online data hub. The final selection of images was made based on the temporal proximity to the UAS data to guarantee the best comparability. For acquisition set (1), there are two PlanetScope images (02.07.2018 and 19.07.2018) which differed from the UAS acquisition date (13.07.2018) by 11 and 6 days, respectively. For acquisition sets (2) and (3), PlanetScope and UAS acquisition dates were identical (24.07.2019 and 04.09.2019). The acquired data sets were categorised in chronological intervals I/Ia/Ib and II (see Fig. 4). The PlanetScope images (19.07.2018, 24.07.2019 and 04.09.2019) were taken between 11:35 and 11:42 local time.




Figure 4 Acquisition dates of UAS and PlanetScope images within the investigated time period. Calculated interval I for UAS images (13.07.2018–24.07.2019, 376 d) and interval Ib for PlanetScope images (19.07.2018–24.07.2019, 370 d), interval II for UAS and PlanetScope images (24.07.2019–04.09.2019, 42 d). Note: Ia PlanetScope interval was discarded.

The UAS images in RAW format were modified using Adobe Exposer to improve contrast, highlights, shadows and clarity.

Thereafter, they were exported as JPG (compression 95 %) and processed with Pix4Dmapper to 0.08 m resolution and orthorectified based on nine permanent ground control points (GCP, 30 x 30 cm). These were repeatedly (1000 measurements/position) registered with the TRIMBLE R5 dGPS and corrected via the baseline data of the Austrian Positioning Service (APOS) provided by the BEV (Bundesamt für Eich- und Vermessungswesen). Horizontal root-mean-squared errors (RMSE) range from 0.05 m to 0.10 m for vertical RMSE. These GCPs were employed for georeferencing and further rectification of all the UAS images surveys.

Next, the data was clipped to a common area of interest (AoI) and resampled with GDAL and the cubic convolution method to 0.16 m to enhance processing time and increased reliability of image correlation. PlanetScope Satellite images were co-registered in Matlab relative to a reference image (<https://gitlab.lrz.de/tobi.koch/satelliteregistration.git>). A feature point detection step was applied to estimate a geometric similarity transformation between the reference (master) and all target (slave) image pairs excluding the AoI with its terrain motion. Thereafter feature point outliers were statistically removed (RANSAC) and the similarity transformation of the slave images to the master image was performed. After removing the outliers, more than 500 feature matches were found for the entire image pair dataset. The mean distance of transformed inlier

Kommentiert [DH57]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L281/285: Please specify the accuracy of dGPS coordinates as measured for the GCPs and also include an accuracy information for the DEMs and their derivatives that were produced from UAS surveys.

feature points from the target image to their corresponding feature matches in the reference image ranged between 0.6 and 0.8 pixels, confirming the high registration accuracy (see OSM Fig. 14).

We used digital image correlation (DIC) to measure the displacement for the active landslide body of the Sattelkar and to assess the suitability of the PlanetScope and UAS data. This method employs optical and elevation data and calculates the distance between an image pair, based on the spatial distance of the highest correlation peaks between an initial search and a final reference window location changes of common pixels. The result provides displacement and ground deformation in 2 D on a sub-pixel level. COSI-Corr (Co-registration of Optically Sensed Images and Correlation), a widely used software in landslide and earthquake studies was used for sub-pixel image correlation (Stumpf, 2013; Lacroix et al., 2015; Rosu et al., 2015; Bozzano et al., 2018). COSI-Corr is an open source software add-on developed by CALTECH (Leprince et al., 2007), for ENVI classic. There are two correlators; in the frequency domain based on FFT algorithm (Fast Fourier Transformation) and a statistical one. Applying the more accurate frequential correlator engine, recommended for optical images, different parameter combinations of window sizes, direction step sizes and robustness iterations were tested. Parameter settings include the initial window size for the estimation of the pixelwise displacement between the images and the final window size for subpixel displacement computation s in x , y ; a direction step in x , y between the sliding windows; and several robustness iterations (Table 6). There are two correlators; in the frequency domain based on FFT (Fast Fourier Transformation) and a statistical one. Applying FFT, different parameter combinations of window sizes, direction step sizes and robustness iterations were tested. We utilised recommended window sizes as suggested by Leprince et al. (2007) and Bickel et al. (2018). Step size one showed good results while keeping the original spatial resolution for the output; robustness iterations of two to four were sufficient for our purposes. Initial and final window sizes were systematically tested (see Table 6). For computing a state-of-the-art powerstation was employed (AMD Ryzen 9 3950X 16-core processor, 3.70 GHz, 128 GB RAM).

Table 6 COSI-Corr input parameters for intervals of UAS and PlanetScope.

Sensor Resolution	Input interval	Initial window [pix]	Final window [pix]	Robustness iteration	Step size
UAS [0.16 m]	I: 13.07.2018-13 July 2018–24.07.2019-24 July 2019 II: 24.07.2019-24 July 2019–04.09.2019-04 September 2019	128x128	32x32	2	1x1
UAS [3.0 m]	I: 13 July 2018–24 July 2019 II: 24 July 2019–04 September 2019	32x32	16x16	2	1x1
PlanetScope [3.0 m]	Ib: 19.07.2018-19 July 2018–24.07.2019-24 July 2019 II: 24.07.2019-24 July 2019–04.09.2019-04 September 2019	64x64	32x32	4	1x1

The results of each correlation computation returns a signal-to-noise ratio map (SNR) and displacement fields in east-west and north-south directions. These results the signal-to-noise ratio (SNR), east-west and north-south displacements were exported from ENVI classic as GTiff and the total displacement was then calculated with QGIS.

(3) t_{evaluate} : In the last phase (time to evaluate) the results of various parameter settings were compared in QGIS and ArcGIS along with different combinations of visualisation. Displacement below a 4 m threshold was discarded from the PlanetScope datasets due to aberrant values (noise, outliers). The threshold definition was defined on (i) the value distribution in both the total displacement and the corresponding SNR result, and (ii) a visual comparison of the maps for the total displacement and the SNR. This definition allowed us to identify outliers and unlikely displacement. Apart from this threshold, no other filters were employed, and we maintained kept the output raw (see for raw DIC on PlanetScope OSM Fig. 13). Very few inconsistencies were present in the UAS-derived displacement results, which were accepted without modification.

Additional analyses were performed to estimate the DIC outputs of both, the UAS orthophotos and PlanetScope satellite imagery. Visual tracking of 36 single blocks, identifiable in the UAS orthophoto series allowed deriving direction and

Kommentiert [DH58]: Modified in response to suggestion by RC1 (J. Blöthe) in review no. 1 and review no. 2

RC1 (J. Blöthe) wrote in review no. 1:
L285/286: Please elaborate how image co-registration was achieved and state here the residual mismatch between co-registered images.

RC1 (J. Blöthe) wrote in review no. 2:
Thank you for the detailed answer. My comment was intended to motivate the authors not only to provide me with these details, but to include them in the revised version of the manuscript. Please include this explanation, or a short version of it, in the text. Regarding the residual mismatches stated here and shown in Fig. 14 of the OSM: this already gives a measure of the amount of significant displacement, i.e. beyond a level of detection, that can be detected with DIC between these images. If your residual mismatch after coregistration (as shown in Fig. 14 OSM) averages to 0.6 - 0.8 pixel, everything below that cannot be treated as significant motion. But still, this would be much lower than your arbitrary 4 m and would be based on a reproducible quantification approach.

Kommentiert [DH59]: Modified following suggestion by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L288/289: Usually matching between consecutive images is not achieved by matching "common pixels", but by maximizing the correlation between pixel-value distributions of patches of pixels (i.e. your windows of different sizes in Tab. 6).

Kommentiert [DH60]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L299/300: I guess this is only relevant if you explicitly mention the image-processing times.

Kommentiert [DH61]: Modified for Table 6 as well following comment by RC1 (J. Blöthe) on Table 3

RC1 (J. Blöthe) wrote:
Table 3: Here you use a different date format than in the text

Kommentiert [DH62]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
It is my impression that the authors have understood my above comment differently than it was intended. Figs. 5 a) and e) as well as b) and f) show the results of the first and second interval, respectively. While a) and e) result from DIC of 0.16 m resolution orthoimages, b) and f) result from the same images, but resampled to 3m. Yet the pattern and magnitude of e) and f) do in no way match the data in a) and b), while it is the same data over the same time interval. My point is that this does not make sense from a tech ... [3]

Kommentiert [DH63]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L304/305: What is the uncertainty of these east-west and north-south displacement estimates? Did you check whether the bearing of the displacement matches the general slope of the Sattelkar?

Kommentiert [DH64]: Answer to comment by RC1 (J. Blöthe) in review 1 and added description following comment by RC1 based on review 2

RC1 (J. Blöthe) wrote in review 1:
L307/308 and L440/442: This seems a bit arbitrary. How did you determine a cutoff-value of 4m displacement? How did you distinguish outliers from non-outliers? What is the confidence of your estimates? ... [4]

Kommentiert [DH65]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L308/309: This contradicts the descriptions of Fig. 5a, where you point out that "ambiguous, small-scale patterns with highly variable displacement rates" (L332/333) dominate the western part of the mass movement.

amount of movement; this supported the verification confirmation process of for (i) the total displacement and (ii) the results of automated and manual tracking. In the next section we employed present this approach only for the time interval II. In order to assess the information value and validity of the satellite imagery, UAS orthophotos were downsampled to 3 m (cubic convolution) for comparison purposes prior image correlation.

5. Results

In Sect. 5.1. we present ground motion results from DIC for the original input resolution for i) UAS, 0.16 m and ii) PlanetScope, 3 m input resolution based on parameters in Table 6. Second, for iii) DIC results of UAS downsampled to 3 m and of PlanetScope are compared. In Sect. 5.2. DIC results for UAS, 0.16 m are analysed with regard to displacement of visual single block tracking. Finally, in Sect. 5.3. required times for $t_{\text{collection}}$, $t_{\text{processing}}$ and $t_{\text{evaluation}}$ for each sensor are presented.

5.1. Total displacements Displacement Rates




Figure 5 Results of DIC total displacement of orthoimages UAS for (a) and (b) at 0.16 m resolution, and PlanetScope (c) and (d) at 3 m resolution. Time intervals for UAS image pairs (a) and (b) are I (13.07.2018–24.07.2019, 376 d), (b) and (c) are II (24.07.2019–04.09.2019, 42 d), for PlanetScope (c) Ib (19.07.2018–24.07.2019, 370 d) and (d) II (24.07.2019–04.09.2019, 42 d). Explanation of inconsistently tracked features (a), a and b, and (b), b and the northwestern landslide head, are described in 5.2. The solid black line represents the boundary of the active landslide based on field mapping. Background: hillshade of Lidar DEM, 1 m resolution (© SAGIS).

Figure 5a and Fig. 5b show the total displacements rates derived from UAS orthophotos at 0.16 m resolution for time intervals I and II (see Table 6). Apart from several minor displacement patches, no motion is visible outside the active body in either period. Time interval I (376 d) (Fig. 5a) shows mean displacement values from 6 to 14 m for a coherent area in the eastern half of the lobe from the centre (c) to the eastern boundary of the active area. The highest displacement rates (up to 20 m) are observed within small high-velocity clusters in the northwest section (d). Lower velocities occur along the southern boundary (e, f), ranging from zero to 6 m with smooth transitions. Ambiguous, small-scale patterns with highly variable displacement rates are present in the western half (a) and along the northern boundary (b). No motion is detected along the western fringe (i.e. at the landslide head) which is 20 m in width. South of the landslide (g) there is a small patch of

Kommentiert [DH66]: Answer to comment by RC1 (J. Blöthe) in review 1 in response and revised description following comment by RC1 based on review 2

RC1 (J. Blöthe) wrote in review 1:
L311/312: I am not convinced that manually tracking boulders in the same images that were used for image correlation can verify the results of this correlation. You can use these data to check if manual and automated tracking give consistent results. Comparing manually tracked boulders from UAS imagery could however be used to compare against the displacement estimates from satellite imagery.

RC1 (J. Blöthe) wrote in review 2:
While I do agree that visually tracking boulders in orthoimages gives reliable results that underpin the displacement that was obtained with digital image correlation in the same images, the term verification implies that these displacements come from independent data.

Kommentiert [DH67]: Modified by the authors in order to be more concise.

Kommentiert [DH68]: Removed following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Kommentiert [DH69]: Removed following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Kommentiert [DH70]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote: ... [5]

Kommentiert [DH71]: Modified figure and deleted (e) and (f), results of 3 m downsampled UAS DIC results following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2: ... [6]

Kommentiert [DH72]: Added to facilitate understanding following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
Use a hillshade not a DEM for tracking (not clear if this was done). Resample the DEM to a slightly coarser resolution (0.5 m?)

Kommentiert [DH73]: Deleted accordingly to modified figure. See comment above for figure 5.

Kommentiert [DH74]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2: This is a crucial point. While you acknowledge here that in the area of decorrelated values, matching did in essence not work, this is not stated as explicit ... [7]

Kommentiert [DH75]: Added missing article by the authors.

Kommentiert [DH76]: Modified following comment by RC1 (J. Blöthe) for L320

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr⁻¹ or cm d⁻¹.

Kommentiert [DH77]: RC1 (J. Blöthe) wrote:
L308/309: This contradicts the descriptions of Fig. 5a, where you point out that "ambiguous, small-scale patterns with highly variable displacement rates" (L332/333) dominate the western part of the mass movement.

395 minor displacement with continuous (up to 3.5 m) and ambiguous signals. Furthermore, we observed small-scale patterns of
ambiguous signals in the east (*j*) and in the west of the active area in the drainage channels (*h*, *i*).
Time interval II (42 d) (Fig. 5b) shows great similarity to time interval I with ambiguous signals in the same areas such as
the drainage channels (*h*, *i*) and within the western half of the active area (*b*). In contrast to interval I (Fig. 5a), within the
active area a homogenous higher velocity patch (up to 6 m) near the landslide head is evident (*a*). In the eastern half large
400 homogenous patches extend from the landslide centre (*c*) to the root zone (*d*) showing coherent displacement values of zero
to 4 m. During this shorter time interval II, no displacement is detected along the south eastern boundary (*e*) and for large
parts of the root zone (*f*) previously covered in I. Similar to I, the landslide head has a 20 m rim free of signal (also see Fig. 6
x, y). In the central part of the lobe (*c*) total displacements rates are significantly reduced.
Figure 5c and Fig. 5d demonstrate total displacement for similar time intervals to UAS (see Table 3 and Fig. 4). For
405 interval Ib (370 d) (Fig. 5c) wide fringes with no motion were detected around an actively moving core area, which consists
of small-scale clusters with variable total displacement in the western part, coherent high velocities in the middle, and
coherent low velocities east of this core area. Outside the landslide, northeast and immediately south (*j*), high-velocity
patches are observed.
In interval II (42 d) (Fig. 5d) the detected displacement is restricted to the western half of the landslide (*a*) and shows the
410 same significant fringes with no motion as in I. Compared to interval I the motion pattern of this core area is more
homogeneous with increasing displacement towards the east. Outside the active area several patches show medium to high
total displacement, the largest of which is located 300 m northwest of the landslide (*i*).
In Fig. 5e and Fig. 5f displacement results of UAS downsampled to 3 m are compared to PlanetScope at 3 m for both time
intervals, I and II. Overall, the results demonstrate high rates (~18–20 m) across the entire landslide interrupted by scattered
415 speckles of low to medium displacement (*a*, *b*, *e*). No motion was present in a fringe zone along the landslide front (west
boundary), similar to results in Fig. 5a and Fig. 5b. In general, the displacement patterns are less smooth than at 0.16 m input
resolution. Outside the landslide significant displacements exist at the eastern image border (Fig. 5e) and towards the west
(*h*, *i*) (Fig. 5f). In comparison, displacement rates derived from PlanetScope cover in large parts the active area for Ib
(Fig. 5c); however, for II only the core area of the landslide shows displacement. In both results the core areas of the
420 landslide are surrounded by wide fringes with no data.

5.2. Single Block Tracking

Figure 6a illustrates the total displacement rates derived from the UAS data at high resolution (0.16 m) for interval II (42 d).
UAS orthoimages were used to manually measure single block displacement for 36 clearly identifiable boulders on the
landslide surface. Block displacements of 1 m are visible in the eastern part (*f*), whereas DIC does not reveal any
425 displacement below 1 m. Boulder tracks longer than 2 m in the central and western part of the landslide are reflected by
DIC-derived displacement values. Near the front a 6 m displacement of one block (*a*) is represented in the DIC result. The
highest values (6 m, 10 m, 16 m) were observed in regions where DIC delivered ambiguous, small-scale patterns of highly
variable displacements. Displacement vectors show consistent bearings in the downslope direction of the landslide motion
for homogeneous areas of the DIC result (*a*, *c*, *d*); there are short vectors with chaotic bearings in areas of ambiguous
430 patterns (*b*), some of which are pointing upslope. The vectors show no displacement in stable areas outside the active area
and where no DIC signal is returned.

Kommentiert [DH78]: Answer to comment by RC1 (J. Blöthe) in response and please see OSM

RC1 (J. Blöthe) wrote:
L335/336 and L366: Did you check the direction of displacement for the areas of smallscale patterns of ambiguous signals? I would suspect that these are very heterogenous here as well. It would also be worth looking into the quality information (correlation coefficients) for these regions.

Kommentiert [DH79]: Modified following comment by RC1 (J. Blöthe) for L320

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr-1 or cm d-1.

Kommentiert [DH80]: Modified in line with comment by RC1 (J. Blöthe) for L320

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr-1 or cm d-1.

Kommentiert [DH81]: Modified in response to comment by RC1 (J. Blöthe) for L320

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr-1 or cm d-1.

Kommentiert [DH82]: Modified following comment by RC1 (J. Blöthe) for L320

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr-1 or cm d-1.

Kommentiert [DH83]: Modified in line with comment by RC1 (J. Blöthe) for L320

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr-1 or cm d-1.

Kommentiert [DH84]: Modified in line with comment by RC2 (S. Roessner)

RC2 (S. Roessner):
L355: The authors state that core areas of the landslide are surrounded by wide fringes with no data. In this context the meaning of the term 'no data' is not clear to me. Please, explain, what do you mean by 'no data' – either missing results or zero deformation.

Kommentiert [DH85]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted [... [8]

Kommentiert [DH86]: Added by the authors after modification of Fig. 6 according to RC2 (S. Roessner)

Kommentiert [DH87]: Modified following comment by RC1 (J. Blöthe) for L320

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr-1 or cm d-1.

Kommentiert [DH88]: Answer to comment by RC1 (J. Blöthe) in response and please see OSM

RC1 (J. Blöthe) wrote:
L335/336 and L366: Did you check the direction of displacement for the areas of smallscale patterns of ambiguous signals? I would ... [9]

Kommentiert [DH89]: Added description following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2 ... [10]




Figure 6 (a) Displacement derived from UAS data at 0.16 m resolution for interval II (24.07.2019–04.09.2019, 42 d) combined with boulder trajectories (in metres) manually measured in the UAS orthophotos in the same time period. Displacement vectors showing landslide flow (black). Origin of inconsistently tracked features (a) for b and the northwestern landslide head are described in 5.2. The solid black line represents the boundary of the active landslide based on field mapping. Background: UAS hillshade, 24.07.2019 (0.08 m), orientation -3° from north. UAS orthophotos at 0.16 m resolution for the master (b) and slave image (c) of the corresponding time interval.

5.3. Time required for collection, processing and evaluation

In Sect. 2 we introduced a novel concept to extend lead time, consisting of three phases within the warning time window (see Fig. 1). This concept is based on DIC results, thus every step comprised in each phase has been previously undertaken. On this basis, knowledge of required time for a further process iteration of the three phases is given.

Time required for collection, processing and evaluation of UAS and PlanetScope data are estimated and summed in Fig. 7. PlanetLabs specifies 12 hours from image acquisition to the provision in the data hub, which includes to a large amount data pre-processing (Planet Labs, 2020b). Adding two hours for the selection, order and download process, we assume that time required for the collection phase is approximately the same for both sensors, with 14 hours for PlanetScope and 12 hours for

Kommentiert [DH90]: Modified Fig. 5 (a) following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:

I would recommend to include the bearing information more prominently in the manuscript itself, as this is a very important information on the data quality.

Kommentiert [HD91]: Modified caption and Fig. 5 (b) and (c) in response to comment by RC2 (S. Roessner) in review no. 1 and RC1 (Jan Blöthe) in review no. 2

RC2 (S. Roessner) wrote:

L370: Fig 6. The obtained deformation results show a very different degree of detail throughout the landslide. For better evaluation of the reasons for these differences the inclusion of an RGB UAV image of the same area would be helpful in order to be able to include surface texture properties in the evaluation of the obtained differences in the deformation patterns.

RC1 (J. Blöthe) wrote in review no. 2:

In my view, it might be advisable to plot the manually tracked boulder displacements against the mean displacement obtained by your DIC for the surrounding pixels (and not just one pixel). As image correlation for tracking is based on matching of value distributions, i.e. matching patches of pixels, adjacent pixels should show similar displacement magnitude and bearing. With this, you could strengthen the argument that the boulder tracking actually backs the DIC tracking - maybe not for all regions, but for the majority.

Kommentiert [HD92]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:

L468/470: Again, I would not trust the displacement estimates of the resampled UAS data. While it is true that your manual boulder tracking identified 2 boulders with displacement of 10 or more meters, the remaining 34 boulders show something different.

Kommentiert [DH93]: Modified following comment by RC1 (J. Blöthe) in review no. 2


RC1 (J. Blöthe) wrote in review no. 2: This is a crucial point. While you acknowledge here that in the area of decorrelated values, matching did in essence not work, this is not stated as explicitly in the manuscript. In my view, it would be necessary to clearly highlight the decorrelated areas as such in the Fig. 5 and explicitly mention the division in reliably tracked regions and those regions that are unreliable (i.e. random) and cannot be interpreted. In my impression this is not done in the present revised manuscript.

Kommentiert [HD94]: Added description by the authors.

UAS. With regard to the time needed for the processing phase, the sensors differ with UAS requiring 17 hours and PlanetScope five hours. Time for the evaluation phase is estimated to be about two hours. In sum, t_{warning} for UAS is approximately 31 hours compared to 21 hours for PlanetScope.

Time to warning:

UAS 31 h



PlanetScope 21 h




Figure 7 Time to warning is composed of three phases: time to collect, to process and to deliver. Time to warning (subsequent to acceleration) is 21 h for PlanetScope and 31 h for UAS. Thus, any hazard process that takes longer than 21/31 h to prepare the release and impact can be forecasted.

6 Discussion

To systematically analyse the predictive power of the UAS and PlanetScope data, we will (i) evaluate [ambiguous signals](#), [error sources](#) and output performance, (ii) assess obtainable temporal and spatial resolution and (iii) derive a systemic estimate of the minimum obtainable warning times.

6.1. Error sources and output performance

To evaluate error sources and output performance, we compared results of digital image correlation results from optical data with (i) high resolution UAS orthophotos, (ii) mapped mass movement boundary and (iii) visual block tracking for UAS orthophotos. The approximately one year evaluation period encompassed all seasons, hence freezing/thawing conditions and a wide range of meteorological influences, e.g. thunderstorms and heavy rainfall, are included. The two investigated time intervals are I/Ib and II, covering 376/370 days and 42 days (typical high-alpine summer season), respectively (Fig. 4). Interval II exclusively covers (high-alpine) summer conditions, with negligible to no contribution from freezing conditions. As these inclusion periods are inconsistent, [the amount of total displacement cannot be directly compared; however the relative motion patterns can be](#). Accordingly, we can confirm the suggested parameter settings of earlier studies on window sizes, steps and robustness iterations (Ayoub et al., 2009; Bickel et al., 2018).

In terms of the mass movement boundary, the total displacement derived from the DIC of the UAS data generally matches the field-mapped landslide boundary for both intervals (I, II) (Fig. 5a, b), and is supported by the absence of significant noise outside the AoI. [Mapped boulder trajectories for interval II \(see Fig. 6\) are consistent with the calculated total displacement and thus confirm COSI-Corr as a reliable DIC tool to derive ground motion for this study site and UAS orthophotos as suitable input data.](#) Nevertheless, there are several areas with ambiguous signals. [Here we follow Leprince et](#)

Kommentiert [DH95]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:
This is a crucial point. While you acknowledge here that in the area of decorrelated values, matching did in essence not work, this is not stated as explicitly in the manuscript. In my view, it would be necessary to clearly highlight the decorrelated areas as such in the Fig. 5 and explicitly mention the division in reliably tracked regions and those regions that are unreliable (i.e. random) and cannot be interpreted. In my impression this is not done in the present revised manuscript.

Kommentiert [DH96]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr⁻¹ or cm d⁻¹.

Kommentiert [HD97]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L398: can be compared

Kommentiert [DH98]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L398/399 and L402/404: Given the large differences in total displacement between sensors and resolutions used for image cross-correlation, I do not think that you can make this claim. Please use an appropriate measure to quantify the agreement between manual boulder tracking and the three different approaches used for digital image correlation.

Kommentiert [DH99]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L398/399 and L402/404: Given the large differences in total displacement between sensors and resolutions used for image cross-correlation, I do not think that you can make this claim. Please use an appropriate measure to quantify the agreement between manual boulder tracking and the three different approaches used for digital image correlation.

al. (2007) describing a correlation loss as ‘decorrelation’ with signal-to-noise values of low/null (i.e. no convergence of the correlation algorithm) and/or large offsets, either unrealistic in nature or beyond the valid matching window distance.

Decorrelation in our understanding exhibits a salt-and-pepper appearance in the DIC result with random displacement vectors, related to inconsistently tracked features. The software is not able to find the corresponding, correlated surface pattern, leading to a misfit (i.e. misrepresentation) and/or mismatch (i.e. blunders) of the matching windows and finally resulting in noise (Debella-Gilo, 2011; Guerriero et al., 2020). Nevertheless, this decorrelation signal is still a valuable observation that might be related to surface processes and not only to erroneous limitations of the DIC method. There are three main reasons that might cause these effects: (i) significant temporal change of the surface, i.e. revolving and/or rotational deformation, (ii) high displacements exceeding the matching window size being smaller than the offset, (iii) land cover changes such as snow cover, vegetation cover and alluvial processes, among others, and (iv) changes related to illumination (e.g. shadow) or image errors (e.g. orthorectification, shifts in individual bands) (Leprince, 2008; Debella-Gilo, 2011; Lucieer et al., 2014; Stumpf et al., 2016). Leprince (2008) describes snow cover, vegetation cover and alluvial processes, among others, as potential explanations for these decorrelations. In our study, the decorrelated areas salt-and-pepper areas include to a large degree the landslide head (a), the drainage channel (h) (Fig. 5a, b), a larger patch south of the active area boundary (g) (Fig. 5a), and some smaller ones in little depressions (g) (Fig. 5a) and (j) (Fig. 5a, b). Most of the patches (j) and east of (j) are identified as snow fields in the orthophotos and the noise results from decorrelation. In Fig. 5a, the large southern patch (g) shows clear displacement values for the rear part and decorrelation for the front region resulting from significant morphological changes within an image pair of interval I (see OSM Fig. 12), limiting the ability to measure ground displacements. This is due to a gain between 1 and 2 m for an area of about 250 m². The decorrelation in the drainage channel (h) could stem from massive changes in pixel values, similar to the decorrelation on the basis of alluvial processes, as described by Leprince et al. (2007). Decorrelations in the areas with the fastest ground motions also lead to high pixel changes (Stumpf et al., 2016). These are observable in the active landslide area within the lobe, where large areas of decorrelation may be explained by high displacements in the leading part-landslide head (a) with redetected, hence correlated pixels in the trailing part-areas (c, d, e, f). These findings can be transferred to the landslide interior area (a, b), the frontal western regions and the northern margin (b). The observation is confirmed by geomorphological mapping (see OSM Fig. 11) and measured boulder block trajectories from the orthophotos (Fig. 6a). Several patches of correlation (c, f) with corresponding boulder trajectories up to 4 m (34.8 m yr⁻¹) (d) are can be detected in the rear part-areas. A correlated patch with a 16 m (34.8 m yr⁻¹) trajectory (a) is located in the flow direction behind the foremost boulder. In this case the method was able to partially capture the displacement partially as the distinct boulder block supported the detection, hence which probably led to correlation. Similarly there is another example with a trajectory of This allows us to conclude that displacements exceeding approximately 10 m (86.9 m yr⁻¹) outside a homogeneous correlated area. This leads to the assumption that for the calculated time period, thus with 63 pixels or more at a resolution of 0.16 m, are definitely outside of a possible correlation and no pixel matching is possible and probably reached the correlation capacity due to the too high displacement. With a correlation window smaller than the displacement, the algorithm is not able to cannot capture the displacement (Stumpf et al., 2016). However as field observations provide evidence that the rock masses are deforming, and the surface is altering due to the high mobility and rotational behaviour of some boulder blocks. This, which leads to changed pixel values and spectral characteristics of the block surface and the surrounding area, which can also result in poor correlations, and even random errors and mismatches (Debella-Gilo and Käb, 2011). This finding is similar to observations in a rock glacier study by Debella-Gilo and Käb (2011). Similar results were observed by Lucieer et al. (2014), who described a loss of recognisable surface patterns if revolving and rotational displacements occur, causing decorrelation and a noise as output. These results show that with COSI-Corr and UAS orthophotos of 0.16 m, it is possible to detect the total displacement of the landslide in both extent and internal process behaviour even in this steep, heterogeneous terrain.

Nevertheless, high displacement rates and rotational surface behaviour in the cirque limit the DIC method. A decrease of the

Kommentiert [DH100]: Added following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:
Please indicate clearly in the figures and the text that these data are erroneously matched pixels, or provide a different plausible explanation for the pattern. Furthermore, in my view the term decorrelated is misleading in the following way: technically, the patches that the DIC matches are correlated to another patch (see your reply to my comment L288/289), else no vector should be produced by the matching procedure. The pattern in these "decorrelated" areas of the landslide indicates that the matching did not find the corresponding patches and therefore does not produce a smooth displacement pattern, but random noise. In other words, despite the correlation the DIC finds, it correlates the wrong locations (images patches), i.e. produces wrong displacement vectors.

and

This is very true and from a image processing point of view, it is the same reason why shadow and snow cover effects induce erroneous correlations. The changed pixel values inhibit rigorous matching. Please include more than just the speed of the landslide in your discussion of errors in matching between images - I also state that in another comment further.

Kommentiert [DH101]: Modified following comment by RC1 (J. Blöthe) after proval of volumetric calculations. Please see OSM.

RC1 (J. Blöthe) wrote:
L409/410: resulting from significant morphological changes?

Kommentiert [DH102]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:
Again, I fear this misses the point. In the text you state that false-positive displacements were observed and I was just interested in the analysis conducted to identify these. Please elaborate.

Kommentiert [DH103]: Modified in response to comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L397: For a comparison (and also for a better readability) you could convert your total displacement to average rates of m yr⁻¹ or cm d⁻¹.

Kommentiert [DH104]: Answer to comment by RC1 (J. Blöthe) in response and OSM

RC1 (J. Blöthe) wrote:
L419/422: This might be the case, though you tested larger patch sizes (Tab. 6) that should have given you consistent results for this region then.

Kommentiert [DH105]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2: This is a crucial point. While you acknowledge here that in the area of decorrelated values, matching did in essence not work, this is not stated as explicitly in the manuscript. In my view, it would be necessary to clearly highlight the decorrelated areas as such in the Fig. 5 and explicitly mention the division in reliably tracked regions and those regions that are unreliable (i.e. random) and cannot be interpreted. In my impression this is not done in the present revised manuscript.

time interval for this particular highly mobile study site would likely reveal an enhanced correlation since for shorter time periods the total displacement decreases, and surface changes are reduced, which can be controlled by shortening the temporal baseline (Debella-Gilo and Käab, 2011). In sum, though the results contain heterogeneous, noisy, decorrelated areas, the combination with homogeneous displacement areas still offers valuable insights into this and other internal landslide structures and complex behaviours.

6.2. Comparison of temporal and spatial resolution

We compared the COSI-Corr total displacement results of PlanetScope (Ib and II, Fig. 5c, d) and UAS images (I and II, Fig. 5a, b and Fig. 6a) for the same time periods at different spatial resolutions (see Table 6). For the PlanetScope DIC result the main part of the landslide is detected, and its area is generally consistent with the results of the UAS DIC, which is additionally confirmed by boulder trajectories. The frontal part (a) reveals correlation signals (I and II); while for the same time intervals and parts, the UAS DIC results show a decorrelation (Ib and II). The correlation is likely to be attributable to the coarser spatial resolution of 3 m PlanetScope input data, hence a smaller number of pixels to be captured at this site with the DIC method. Similar texture of rock clast surfaces could lead to false positives resulting in correlation as patches appear similar in matching windows. However, in contrast to the UAS result (Fig. 5a, b), the outcome on a large scale fails to detect the entire actual active area (b), (f) as well as its internal motion behaviour. Nevertheless, for the visualisation and analysis of the PlanetScope results, the range of total displacements had to be restricted to values equal to and greater than 4 m due to noise and outliers over large areas, as applied and described by Bontemps et al. (2018). Even then, noise and several misrepresented displacement patches are observed for (i, j) and in the northeast image corner (Fig. 5). We can identify several reasons for these large clusters of high motion values. Massive cloud and snow coverage hampered both first images of interval Ib (19.07.2018) (Fig. 5c) and II (24.07.2019) (Fig. 5d), leading to a 20 m fringe of false displacements in the north-eastern part of the image. Minor snow fields as visible in the images from 24.07.2019 for both, the UAS and PlanetScope, could likely explain the big cluster of incorrect displacement southeast of the lobe (j); nonetheless, in the satellite image they are smaller than the resulting DIC displacement. High cloud coverage in two input images with large areas of white pixels may exert an influence leading to high gains due to sensor saturation (Leprince, 2008). Illumination changes in interval II (Fig. 5d) may cause unrealistic displacements outside the boundary with slightly darker colours due to shadows in the first satellite image (24.07.2019) and large parts within the second image (04.09.2019) are also in the shade. A comparison of the acquisition times and true sun zenith, e.g. for the second image, reveals a difference of 01:34 h between the image acquisition at 11:36 LT (local time) and the true local solar time at 13:10 LT. As the study site is located in a high-alpine terrain with a west facing cirque, at this time of day there are shadows of considerable length which have a significant influence on the result of digital image correlations. One clear advantage of the UAS images is that their acquisition is plannable according to the best illumination conditions with the sun at its zenith. Moreover, the UAS flight path as well as the system itself remained the same for all three acquisitions, while PlanetScope employs various satellites. Despite similar input resolutions and time intervals (Ib vs. I and II vs. II, see Table 3) with different sensors (UAS, PlanetScope), considerably divergent DIC outputs (Fig. 5c vs. e, d vs. f) are returned. To a large degree the active ground motion inside the mapped landslide boundary is represented by the 3 m UAS DIC result, while the same fringe remains free of signal for both UAS DIC results at different input resolutions (Fig. 5a, b vs. Fig. 5e, f). Despite different input resolutions and time intervals (Ib vs. I and II vs. II, see Table 3) with different sensors (UAS, PlanetScope) there is a similarity for the landslide head which indicates with overall good agreement indicates that the displacement is restricted to a smaller area than the previously demarcated boundary, based on our field investigations. This is clearer for the time interval I (376/370 d) (Fig. 5a vs. c) as for the longer temporal baseline the total displacement accumulation is higher, thus better captured by COSI-Corr for PlanetScope 3 m resolution. Due to the shorter interval II (42 d) (Fig. 5b vs. d) with less accumulated total displacement, the rear of the landslide is not represented; no signal is shown as the total displacement for

Kommentiert [DH106]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:
I strongly doubt that you can make this statement. The image processing algorithm matches pixel value distributions from patches in consecutive images. When the pixel value distribution changes between images, the algorithm does not find the "true" corresponding area, but matches to the most similar patch it finds. Whether the pixel value distribution changes in reaction to snow cover, shadows, or vegetation, or if large displacements induce the spectral differences is not discernable for the DIC software.

Kommentiert [DH107]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L433/434: This should be backed by a statistical measure. From a close look to Fig. 5, I rather get the impression that the only patches you can make this statement for is location a in Fig. 5 (b) and (d) and location c in Fig. 5 (a) and (c), but to a lesser extent.

Kommentiert [DH108]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L437/447: The size of the snow patches does not play an important role. The presence of snow in one image hampers correlation between images and leads to false patchmatching results.

Kommentiert [DH109]: Modified in line with comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L443: bracket missing?

Kommentiert [DH110]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L445/447: The size of the snow patches does not play an important role. The presence of snow in one image hampers correlation between images and leads to false patchmatching results.

Kommentiert [DH111]: Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L 460: check figure reference

Kommentiert [DH112]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L457/462: To be frank, I do not see much similarity between Fig. 5 (c) and (e) nor (d) and (f). I would be very cautious in interpreting these results as is. This is especially true for the resampled UAS results.

Kommentiert [DH113]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Kommentiert [DH114]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

PlanetScope was restricted to values above 4 m. Values below 4 m had to be discarded for PlanetScope DIC results as they were lost in noise, i.e. for the entire DIC results there is total displacement between 0 m and 4 m (cf. the online supplementary material (OSM) Fig. 13). Hence, when applying a minimum threshold of 4 m, the satellite image detects large parts of the main active core area but widths of 50–80 m from the boundary show no displacement. However, false large clusters of high total displacement are within the PlanetScope result interval I for (j) and the northeast image corner (Fig. 5c) and interval II for (i) (Fig. 5d). False displacement is indicated for a cluster outside of the boundary to the image border in the east for UAS interval I (Fig. 5e) and in the north-western area (h, i) for interval II (Fig. 5d). Apart from these false signals, there is minor noise compared to false large clusters of high displacement within the PlanetScope result interval I for (j) and northeast image corner (Fig. 5c) and interval II (i) (Fig. 5d). However, two striking differences with correlation/decorrelation and ground motion values are observed for the two UAS input resolutions: the coarser resolution of 3 m returns a correlation signal with values typically exceeding 18 m of displacement as the value range is extended, due to previous high factor downsampling. Measured ground motion of block tracking and PlanetScope results indicate and support existing high ground motions. In addition there are morphologically significant volumetric turnovers with areas of large gains and losses between ± 5 m (see OSM Fig. 11). These observations might be the explanation for the observed resulting decorrelation at the finer resolution of 0.16 m for the landslide head: the matching window is smaller than the offset and texture surface changes are too complex to be re-detected, i.e. matched, and thus correlated, leading to decorrelation and noise. Homogeneous correlated patches are in the front of the landslide body for the shorter time interval; there may have been some displacement just below the detection threshold for this high ground motion or some boulders and their surroundings might have been matched, or both (Fig. 6a (a)). For this case for the complex ground motion with high spatial resolution data this reason, the previous assumption using based on a shorter time interval likely leading to improved detection of inherent process behaviour (see Sect. 6.1). can be complemented with a coarser resolution showing a clear improvement in the form of better correlations and returned signals. Generally, with high resolution images, such as UAS, we recommend first calculating displacements based on a coarser input resolution (1–3 m) to examine the overall situation and detect changes, and second to calculate displacements at a finer resolution in order to focus on relevant details of the AoI. With regard to PlanetScope data, a 3 m resolution seems to be in a good spatial range to assess ground displacements even of this steep and heterogeneous study site with its high motion. Nonetheless, constraints such as illumination due to early daytime acquisitions leading to shadows, meteorological influences by clouds, cloud shadows and snow decrease the quality of the satellite images and reduce their applicability. Sensor saturation, shadow length, size and direction as well as changes in snow, cloud or vegetation cover impose limitations (Delacourt et al., 2007; Leprince et al., 2008) and accord with our observations. The authors identify additional limitations such as radiometric noise, sensor aliasing, man-made changes and co-registration errors (ibid.). All these limitations have a negative impact on the input image, which leads to impaired DIC calculations and results, and (partially or wholly) inaccurate analysis of the displacement. These might have played a role in our results. In our experience, the usability of the DIC result may be influenced by the input image quality. This restricts the application of PlanetScope images to a certain degree. They can be employed as input data to detect displacements, but as there are in the present setting too many signals of false-positive displacements, which can solely be discarded on the basis of field evidence, this data is currently of limited use. It should be handled with caution and we recommend, and combining it with complementary data and ground truth is recommended.

6.3. Estimating time to warning

Early warning is essentially defined as being earlier than the event and thus puts high external time constraints on observation and decision. The time window between the detection of an accelerating movement preparing for final failure and the final failure itself is determined by the environment. Therefore, two sensors with the highest available spatiotemporal resolution were evaluated and compared with regard to their applicability to the early warning of landslides. We made rough

Kommentiert [DH115]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:
Thank you for the detailed answer. My comment was intended to motivate the authors not only to provide me with these details, but to include them in the revised version of the manuscript. Please include this explanation, or a short version of it, in the text. Regarding the residual mismatches stated here and shown in Fig. 14 of the OSM: this already gives a measure of the amount of significant displacement, i.e. beyond a level of detection, that can be detected with DIC between these images. If your residual mismatch after coregistration (as shown in Fig. 14 OSM) averages to 0.6 - (... [11]

Kommentiert [DH116]: Modified after deletion following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible (... [12]

Kommentiert [DH117]: Correction by the authors.

Kommentiert [DH118]: Modified in response to comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L463/464: As the GCPs for referencing the UAS data are probably located close to the landslide, it is not surprising, but neither (... [13]

Kommentiert [DH119]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible (... [14]

Kommentiert [DH120]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible (... [15]

Kommentiert [DH121]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible (... [16]

Kommentiert [DH122]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L468/470: Again, I would not trust the displacement estimates of the resampled UAS data. While it is true that your manual boulders (... [17]

Kommentiert [DH123]: Modified in response to comment by RC1 (J. Blöthe) in review 2

RC1 (J. Blöthe) wrote in review 2:
I strongly doubt that you can make this statement. The image processing algorithm matches pixel value distributions from (... [18]

Kommentiert [DH124]: Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:
There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible (... [19]

Kommentiert [DH125]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L471/476: While it might be true that the results obtained from image correlation of resampled 3m UAS data are better (internally) (... [20]

Kommentiert [HD126]: Modified and restructured this sentence to emphasise our recommendation following comment by RC1 (J. Blöthe). In addition, please see answer in response.

RC1 (J. Blöthe) wrote: (... [21]

assumptions and assessed the time needed for the phases of time (i) to collect, (ii) to process, and (iii) to evaluate relevant data (summarised in the time to warning window, see Fig. 7).

Despite different underlying technologies the time required for the collection phase is approximately the same for both sensors. For UAS, we estimated about 12 hours under ideal circumstances, while for PlanetScope 12 hours (Planet Labs, 2020b) plus two hours for image selection, download and initial analysis, adding up to 14 hours in total (see Sect. 5.3.). In the second phase, time to process, deriving orthophotos from raw UAS images is time consuming. The subsequent DIC calculations demand significantly more processing time for the UAS images than for lower resolution PlanetScope images. The final phase, time to deliver, takes about two hours for each sensor. In our case study, the estimated time to warning (t_{warning}) was 10 h longer for the UAS approach (31 h) in comparison to the Planet Scope approach (21 h). These time calculations are based on ideal environmental conditions and data availability. Assuming good conditions exist to conduct the UAS flight and no constraints limit the utilisation of satellite images, in theory a daily deployment is possible. In reality, unfavourable weather conditions, cloud and snow cover as well as limited data availability will increase the actual t_{warning} significantly. From the available images in the Planet Data hub (besides other exclusions) meteorological influences reduced for April–October 2019 the usability by 14.5 % and 7 % for cloud cover and snow cover, respectively (Table 2). The flexibility of a UAS can serve as a practical remote sensing tool for the investigation of ground motion behaviour in a spatiotemporal context. Nonetheless, weather influences can make a UAS flight impossible or impractical as the result might be useless. Depending on the level of illumination, the same may apply for satellite images. Regardless of any meteorological constraints, the promised daily availability by PlanetScope is unrealistic, due to data gaps and provider issues; our study showed that for the Sattelkar from April to October 2019 only 11 % of the captured images during this time were usable. Hence, PlanetScope data has a temporal availability similar to Sentinel-1 with a 6-day revisit time. In time-critical early warning scenarios, when time is running out, all available even partly usable images will be utilised and fieldwork may be conducted, even if the prevailing conditions are suboptimal but will increase data availability. The comparison of two selected remote sensing options demonstrates that the comprehensive knowledge on the available remote sensing data sources and their respective time requirements can substantially reduce the time to warning (t_{warning}) and to extend the lead time (t_{lead}).

Significant observations of the temporal evolution of historic landslides are presented in Table 7 and described below. These include (i) the Preonzo rock slope failure, CH (Sättele et al., 2016; Loew et al., 2017), (ii) the Vajont rock slide, ITA (Petley and Petley, 2006) and (iii) the Sattelkar complex slide, AUT (Anker et al., 2016). These landslides have specific evolution histories, e.g. early observed crack developments, increased movement and minor events like Preonzo (2002 and 2010) (Sättele et al., 2016); Sattelkar, with large volume mass wasting processes since 2005 and a debris slide event in 2014 (see Sect. 3 Study Site) (Anker et al., 2016); and Vajont, with ductile failures in 1960 and 1962 and a transition from ductile to brittle behaviour in 1963 (Petley and Petley, 2006; Barla and Paronuzzi, 2013).

Table 7 Relevant dates for historic failures of Vajont (ITA), Preonzo (CH) and Sattelkar (AUT). Time period in *italics*–bold used for Fig. 9. Time intervals in days (~ for rough estimations) and years in square brackets; sum of days based on the first day of the month, if only month as reference is available from literature (Petley and Petley, 2006; Anker et al., 2016; Sättele et al., 2016; Loew et al., 2017). Further explanation below.

Vajont [days, yrs]			Preonzo [days, yrs]			Sattelkar [days, yrs]		
10/1960	large crack		1989	onset crack	~730			
04.11.1960	700.000 m³ block detachment		1991	increasing movement	[2]	~4138		
11/1960	11 mm/d		05/2002	minor event		[11]	~2922	
04/1963	ductile to brittle transformation	153	05/2010	minor event		[8]	~731	
09/1963	35 mm/d	[-]	01.05.2012	critical displacement		[2]	15	01/2003 enhanced dynamic mass wasting ~731
09.10.1963	260 mio. m³ event	[-]	15.05.2012	300.000 m³ event		[-]	31.07.2014	begin of active ground motion [2] ~3498
								170.000 m³ event [9] ~4229 [11]

Figure 9 is the extension of our concept (see Sect. 1, Fig. 1) systematically supplemented with our estimated time to warning (UAS, PlanetScope), and compared to the few data series predating larger slope failures.


Kommentiert [DH127]: Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:
Exactly. That is why I commented that in theory, planet offers a big advantage here with daily data availability. But very practically, as you show with Tab. 2, only ~10% of the planet scenes were usable. Effectively you end up with rather similar revisit times between planet and sentinel 1, if you want to use these examples here. But don't get me wrong, optical imagery has a lot of other advantages...

Kommentiert [HD128]: Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:
L552/554 / Table 7 / Figure 9: I do like the idea behind this, where the authors show that their proposed workflow would enable a timely warning in the case of historic landslides. However, in the case of Vajont, I think you should include a critical factor. While it is theoretically true that a "forecasting window" would allow for your workflow to be completed well before the failure, the slow deformation of Vajont (35 mm d-1) in the 30 days will be well below the level of detection of your image correlation analysis, if you collect an image directly after the onset of "significant acceleration". In order to be detectable, movement must have accumulated a critical distance before data collection of your workflow can set in (30 days = 1.05 m total displacement) – a factor that in my view would be important to include here.

640 Following a significant acceleration, the forecasting window is opened and t_{warning} starts, which is composed of phases (i) time to collect, (ii) time to process and (iii) time to evaluate. To ascertain a significant acceleration one further observation is required. Hence, one complete cycle of the three phases, previous analyses and processing iterations are given. Our analysis showed that UAS and Planet Scope can approach times as short as 31/21 h, as a result t_{lead} is increased and so is t_{react} .



645 **Figure 8** Conceptual approach with estimated t_{warning} for UAS and PlanetScope. Phases of collection, processing and evaluation (indicated as arrows of relative length in orange, blue and green, respectively) (see phases in Fig. 1 and Fig. 7) with their total duration time (grey dashed arrows). In t_{warning} , one additional observation requires in sum 31 h for UAS and 21 h for PlanetScope data. Above, major landslides are compared from the onset or displacement detection (solid line) (Petley and Petley, 2006; Anker et al., 2016; Sättele et al., 2016).

650 Assuming both sensors reliably estimate ground motion, solely based on their time requirement, this concept was applied to the temporal development of historic landslide events, thus from measured increased displacements and/or massive accelerations to the final event (Table 7). On this basis we simplified the graph and what we defined as “significant acceleration” using dates of observations such as increased crack opening (Vajont), critical displacement (Preonzo) and the beginning of active ground motion (Sattelkar). Therefore, the opening of t_{warning} and forecasting window are concrete observations of the particular site, independent of any intensity described by the corresponding authors and allows more freedom for temporal evaluations without going into details.

655 For the Preonzo case, the entire 2012 spring period was characterised by high displacement rates. We defined the first of May 2012, when geologists operating the warning system informed local authorities and assembled a crisis team, as the onset or ‘increased movement’ and the 15.05.2012 with 300 000 m³ as the impact (Sättele et al., 2016), in total approximately 15 days. For Vajont, the 1/velocity plot by Petley and Petley (2006) (based on data from Semenza and Ghirotti (2000)) shows an increase in movement at about day 60 along with a transition from a linear to an asymptotic trend at approximately day 30, defined as a transition from ductile to brittle. Therefore, we assumed 30 days of forecasting window for t_{warning} and t_{lead} until the impact of the hazardous event on 09.10.1963. However, it has to be kept in mind- note that velocities of about 35 mm d⁻¹ are still low and at the minimum of the displacement recognition capability for the digital image correlation method. For the Sattelkar site, the observed mass displacement increase is presumed to have started in 2005 with the 170 000 m³ debris flow event on 31.07.2014 as the impact, thus about 3 498 days (Anker et al., 2016).

Kommentiert [HD129]: Modified in response to comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:
L552/554 / Table 7 / Figure 9: I do like the idea behind this, where the authors show that their proposed workflow would enable a timely warning in the case of historic landslides. However, in the case of Vajont, I think you should include a critical factor. While it is theoretically true that a “forecasting window” would allow for your workflow to be completed well before the failure, the slow deformation of Vajont (35 mm d⁻¹) in the 30 days will be well below the level of detection of your image correlation analysis, if you collect an image directly after the onset of “significant acceleration”. In order to be detectable, movement must have accumulated a critical distance before data collection of your workflow can set in (30 days = 1.05 m total displacement) – a factor that in my view would be important to include here.

Even for the Preonzo event, with its short forecasting window of 15 days, the ground motion assessment based on the evaluated optical remote sensing images, would have been possible under the assumption of reasonably good UAS flying conditions and the provision of usable PlanetScope images. For t_{warning} there is enough temporal leeway to repeat at least three to four successive measurements comprising the three phases. However, as single accelerations are possible in very short time intervals of less than two days, it is impossible to capture these accelerations by means of optical remote sensing methods, given a time requirement of 31 hours for UAS and 21 hours for PlanetScope. Nevertheless, this comparison shows that for larger and long-preparing slope failures the technical t_{warning} may well be shorter than the forecasting window starting at the time at which the process becomes predictable. For this type of slope failures recent developments such as the ESA's Geohazards Exploitation Platform (GEP), developed and operated by Terradue, supports on-demand services such as the Thematic Exploitation Platforms (TEPs) and has the potential to decrease t_{warning} . The service provides an archive of Copernicus' Sentinel-1 and -2, Pléiades and Spot 6/7 data, and access to cloud computing resources to support large scale geohazard mapping and monitoring (Volat et al., 2017; Fournel et al., 2019; Lacroix et al., n.d.). Therefore, the time critical phases of time to collect and time to process, which in our example are attributed to the larger share of the total time requirement for t_{warning} , could be significantly reduced as the data is directly accessible through high performance cloud computing. What remains is the third phase, time to evaluate, where a relatively short time is required, thus t_{lead} is extended.

7 Conclusions and outlook

This paper presents an innovative concept to compare the lead time for landslide early warnings, utilising of two optical remote sensing systems. We tested this temporal concept by applying UAS and PlanetScope images of temporal proximity as these are currently the sensors with the best spatiotemporal resolution. We assessed the sensors' capability to identify hot spots and to recognise behaviour by delineating ground motion employing digital image correlation (DIC). In so doing, knowing the necessary processing time enabled us to estimate the time requirement and finally to incorporate it into the concept to evaluate sensors with regard to ongoing landslide processes of the Sattelkar as well as historic landslide events.

Our findings derived from DIC for this steep high-alpine case study show that high resolution UAS data (0.16 m) can be employed to identify and demarcate the main landslide process and reveal its heterogeneous motion behaviour as confirmed by single block tracking. Thus, validated total displacement ranges from 1–4 m and up to 14 m for 42 days. PlanetScope Ortho Scenes (3 m) can detect the displacement of the landslide central core, however, cannot accurately resolve-represent its extent and internal behaviour. The signal-to-noise ratio, including multiple false-positive displacements, complicates the detection of hotspots at least in this very steep and heterogeneous alpine terrain.

Coarse temporal data resolution, such as in the case study investigated here, represents an important restriction to the use of optical remote sensing data for landslide early warning applications. Acceleration (and the resulting failure) over short periods of time will likely go unnoticed due to large data acquisition intervals. However, for prolonged acceleration periods, such as observed at the Sattelkar slide and many other relevant hazard sites, the chosen data sources have been demonstrated to represent a formidable early warning approach capable of contributing to an improved risk analysis and evaluation in steep high-alpine regions.

With regard to the temporal aspect for early warning purposes, PlanetScope satellite images require less time compared to UAS for the time phases of collection, processing and analysing. As a consequence, when time is of the essence, the UAS acquisition cannot compete with the high frequency of PlanetScope daily revisit rates. In general, both are limited in their use as they are passive optical sensors dependent on favourable weather conditions. Nevertheless, with a realistic 10 % of usable data for our study site, PlanetScope cannot provide daily data as promised.

To conclude, in methodological terms DIC is a reliable tool to derive total displacement of gravitational mass movements even for steep terrain. Given the high reliability of UAS data, its temporal resolution is the key in future attempts to

Kommentiert [DH130]: Added information in response to comment by the Editor (M. Motagh):

Editor (M. Motagh) wrote:
Moreover, please elaborate on the discussion how the t_{warning} could be shortened using cloud-processing solutions such as Geohazard GEP. Although it is based on Sentinel-2, but the platform could be exploited for big landslides and reduces t_{warning} significantly.

Kommentiert [DH131]: Author's revision to be more clear.

Kommentiert [DH132]: Author's revision in order to be more concise and in line with the introduction and study site section.

Kommentiert [DH133]: Author's revision to be more clear.

Kommentiert [DH134]: Modified following comment by RC2 (S. Roessner)

RC2 (S. Roessner):
The used data sources (planet and UAV) do not allow optimization of lead time in the context of early warning because of the scarcity of their availability which is reflected in the small number of only three multitemporal data takes between July and September analyzed in this study (Table 3)

and
The study site (starting at L175) represents a very complex landslide case leading to rather erratic mass movements in form of debris flows initiated by changing slope water conditions related to increased atmospheric precipitation. This situation is another obstacle for an early warning approach which is solely based on optical remote sensing data and thus making it impossible to make full use of the in principle daily temporal resolution of the planet data. Taking into account these natural conditions and the constraints introduced by the used imaging constellations, leaves no room for true optimization of lead time in the sense as stated in the overall scientific goal of this paper.

overcome decorrelation due to high ground motions. In addition, a slightly coarser resolution reduces the time needed for total processing, enhances correlation while maintaining spatial accuracy and reliability. PlanetScope is especially interesting as a complementary sensor when UAS employment is restricted e.g. inaccessible and/or dangerous sites or for areas too extensive to be covered. For continuous monitoring and early warning, the warning time window could be shortened by on-site drone ports with autonomous acquisition flights and automatic processing. Our systematic evaluation of the sensor ~~potency-capability~~ can be applied ~~and transferred~~ to other optical remote sensing sensors, ~~and~~ the same is true for our conceptual approach ~~optimising-which~~ ~~extending~~ the lead time. Future studies should focus on the applicability of complementary optical data to confirm the detection of landslide displacement and adjust UAS output resolution as this significantly increases the validity of DIC internal ground motion behaviour.

Kommentiert [DH135]: Modified following comment by RC2 (S. Roessner)

RC2 (S. Roessner):
The used data sources (planet and UAV) do not allow optimization of lead time in the context of early warning because of the scarcity of their availability which is reflected in the small number of only three multitemporal data takes between July and September analyzed in this study (Table 3)

Data availability

720 PlanetScope data are not openly available as and PlanetLabs Inc. is a commercial company. However, scientific access schemes to these data exist.

Author contribution

Doris Hermle developed the study together with Markus Keuschnig and Michael Krautblatter, analysed the data and wrote the paper. Markus Keuschnig and Michael Krautblatter supported the writing and editing of the paper. Ingo Hartmeyer
725 provided critical proof reading with valuable suggestions. Robert Delleske is responsible for UAS flight campaigns and processing the images.

Competing interests

The authors declare that they have no conflict of interest.

Acknowledgements

730 This work is supported by a scholarship of the Hanns-Seidel-Foundation. The authors are grateful to PlanetLabs for their cubesat data via Planet's Education and Research Program. We thank Tobias Koch for the support in fine co-registering satellite images.

References

- Anker, F., Fegerl, L., Hübl, J., Kaitna, R., Neumayer, F., and Keuschnig, M.: Geschiebetransport in Gletscherbächen der Hohen Tauern: Beispiel Obersulzbach, Wildbach- und Lawinenverbauung, 80, 86–96, 2016.
- Aubrecht, C., Meier, P., and Taubenböck, H.: Speeding up the clock in remote sensing: identifying the ‘black spots’ in exposure dynamics by capitalizing on the full spectrum of joint high spatial and temporal resolution, Nat Hazards, 86, 177–182, <https://doi.org/10.1007/s11069-015-1857-9>, 2017.
- Auer, I., Böhm, R., Jurkovic, A., Lipa, W., Orlik, A., Potzmann, R., Schöner, W., Ungersböck, M., Matulla, C., Briffa, K., Jones, P., Efthymiadis, D., Brunetti, M., Nanni, T., Maugeri, M., Mercalli, L., Mestre, O., Moisselin, J.-M., Begert, M., Müller-Westermeier, G., Kveton, V., Bochnicek, O., Stastny, P., Lapin, M., Szalai, S., Szentimrey, T., Cegnar, T., Dolinar, M., Gajic-Capka, M., Zaninovic, K., Majstorovic, Z., and Nieplova, E.: HISTALP—historical instrumental climatological surface time series of the Greater Alpine Region, Int. J. Climatol., 27, 17–46, <https://doi.org/10.1002/joc.1377>, 2007.
- 740 Ayoub, F., Leprince, S., and Keene, L.: User's Guide to COSI-CORR Co-registration of Optically Sensed Images and Correlation, California Institute of Technology, Pasadena, CA 91125, USA, 38 pp., 2009.
- Barla, G. and Paronuzzi, P.: The 1963 Vajont Landslide: 50th Anniversary, Rock Mechanics and Rock Engineering, 46, 1267–1270, <https://doi.org/10.1007/s00603-013-0483-7>, 2013.
- Barsi, Á., Kugler, Z., László, I., Szabó, G., and Abdulmutalib, H. M.: ACCURACY DIMENSIONS IN REMOTE
750 SENSING, Int. Arch. Photogramm. Remote Sens. Spatial Inf. Sci., XLII-3, 61–67, <https://doi.org/10.5194/isprs-archives-XLII-3-61-2018>, 2018.

- Batini, C., Blaschke, T., Lang, S., Albrecht, F., Abdulmutalib, H. M., Barsi, Á., Szabó, G., and Kugler, Z.: Data Quality in Remote Sensing, *Int. Arch. Photogramm. Remote Sens. Spatial Inf. Sci.*, XLII-2/W7, 447–453, <https://doi.org/10.5194/isprs-archives-XLII-2-W7-447-2017>, available at: <https://www.int-arch-photogramm-remote-sens-spatial-inf-sci.net/XLII-2-W7/447/2017/>, 2017.
- 755 Bickel, V., Manconi, A., and Amann, F.: Quantitative Assessment of Digital Image Correlation Methods to Detect and Monitor Surface Displacements of Large Slope Instabilities, *Remote Sensing*, 10, <https://doi.org/10.3390/rs10060865>, 2018.
- Bontemps, N., Lacroix, P., and Doin, M.-P.: Inversion of deformation fields time-series from optical images, and application to the long term kinematics of slow-moving landslides in Peru, *Remote Sensing of Environment*, 210, 144–158, <https://doi.org/10.1016/j.rse.2018.02.023>, 2018.
- 760 Bozzano, F., Mazzanti, P., and Moretto, S.: Discussion to: ‘Guidelines on the use of inverse velocity method as a tool for setting alarm thresholds and forecasting landslides and structure collapses’ by T. Carlà, E. Intrieri, F. Di Traglia, T. Nolesini, G. Gigli and N. Casagli, *Landslides*, 15, 1437–1441, <https://doi.org/10.1007/s10346-018-0976-2>, 2018.
- 765 Breger, P.: The Copernicus Full, Free and Open Data Policy, 2017, 2017.
- Butler, D.: Many eyes on Earth, *Nature*, 505, 143–144, <https://doi.org/10.1038/505143a>, 2014.
- Calvello, M.: Early warning strategies to cope with landslide risk, *Rivista Italiana di Geotecnica*, 2, 63–91, <https://doi.org/10.19199/2017.2.0557-1405.063>, 2017.
- Chae, B.-G., Park, H.-J., Catani, F., Simoni, A., and Berti, M.: Landslide prediction, monitoring and early warning: a concise review of state-of-the-art, *Geosciences Journal*, 21, 1033–1070, <https://doi.org/10.1007/s12303-017-0034-4>, 2017.
- 770 Crosetto, M., Monserrat, O., Cuevas-González, M., Devanthéry, N., and Crippa, B.: Persistent Scatterer Interferometry: A review, *ISPRS Journal of Photogrammetry and Remote Sensing*, 115, 78–89, <https://doi.org/10.1016/j.isprsjprs.2015.10.011>, 2016.
- Crosta, G. B., Agliardi, F., Rivolta, C., Alberti, S., and Dei Cas, L.: Long-term evolution and early warning strategies for complex rockslides by real-time monitoring, *Landslides*, 14, 1615–1632, <https://doi.org/10.1007/s10346-017-0817-8>, 2017.
- 775 [Debella-Gilo, M.: Matching of repeat remote sensing images for precise analysis of mass movements. PhD Thesis, Department of Geosciences Faculty of Mathematics and Natural Sciences, University of Oslo, Oslo, 2011.](#)
- [Debella-Gilo, M. and Kääb, A.: Sub-pixel precision image matching for measuring surface displacements on mass movements using normalized cross-correlation, Remote Sensing of Environment, 115, 130–142, https://doi.org/10.1016/j.rse.2010.08.012, 2011.](#)
- 780 Darvishi, M., Schlögel, R., Kofler, C., Cuozzo, G., Rutzinger, M., Zieher, T., Toschi, I., Remondino, F., Mejia-Aguilar, A., Thiebes, B., and Bruzzzone, L.: Sentinel-1 and Ground-Based Sensors for Continuous Monitoring of the Corvara Landslide (South Tyrol, Italy), *Remote Sensing*, 10, 1781, <https://doi.org/10.3390/rs10111781>, 2018.
- 785 Delacourt, C., Allemand, P., Berthier, E., Raucoules, D., Casson, B., Grandjean, P., Pambrun, C., and Varel, E.: Remote-sensing techniques for analysing landslide kinematics: a review, *Bulletin de la Societe Geologique de France*, 178, 89–100, <https://doi.org/10.2113/gssgfbull.178.2.89>, 2007.
- Desrues, M., Lacroix, P., and Brenguier, O.: Satellite Pre-Failure Detection and In Situ Monitoring of the Landslide of the Tunnel du Chambon, French Alps, *Geosciences*, 9, <https://doi.org/10.3390/geosciences9070313>, 2019.
- 790 Dikau, R., Brunsden, D., Schrott, L., and Ibsen, M.-L. (Eds.): Landslide recognition: Identification, Movement and Courses, Publication / International Association of Geomorphologists, no. 5, John Wiley & Sons, New York, xii, 251, 1996.
- Drusch, M., Bello, U. D., Carlier, S., Colin, O., Fernandez, V., Gascon, F., Hoersch, B., Isola, C., Laberinti, P., Martimort, P., Meygret, A., Spoto, F., Sy, O., Marchese, F., and Bargellini, P.: Sentinel-2: ESA’s Optical High-Resolution Mission for GMES Operational Services, *Remote Sensing of Environment*, 120, 25–36,

795 <https://doi.org/10.1016/j.rse.2011.11.026>, available at:
<http://www.sciencedirect.com/science/article/pii/S0034425712000636>, 2012.

ESA: eoPortal: Satellite Missions Database, <https://directory.eoportal.org/web/eoportal/satellite-missions/>, last access: 4
December 2020, 2020.

800 [Foumelis, M., Papadopoulou, T., Bally, P., Pacini, F., Provost, F., and Patruno, J.: Monitoring Geohazards Using On-Demand And Systematic Services On Esa's Geohazards Exploitation Platform, in: IGARSS 2019 - 2019 IEEE International Geoscience and Remote Sensing Symposium, Yokohama, Japan, 28.7.-2.8.2019, 5457–5460, 2019.](#)

Froude, M. J. and Petley, D. N.: Global fatal landslide occurrence from 2004 to 2016, *Nat. Hazards Earth Syst. Sci.*, 18, 2161–2181, <https://doi.org/10.5194/nhess-18-2161-2018>, 2018.

Gariano, S. L. and Guzzetti, F.: Landslides in a changing climate, *Earth-Science Reviews*, 162, 227–252,
805 <https://doi.org/10.1016/j.earscirev.2016.08.011>, available at:
<http://www.sciencedirect.com/science/article/pii/S0012825216302458>, 2016.

GeoResearch: Projekt Sattelkar.: Zwischenbericht 1: 2018, NP Hohe Tauern Salzburg, Klimasensitive, hochalpine Kare:, 2018.

Giordan, D., Hayakawa, Y. S., Nex, F., and Tarolli, P.: Preface: The use of remotely piloted aircraft systems (RPAS) in
810 monitoring applications and management of natural hazards, *Nat. Hazards Earth Syst. Sci.*, 18, 3085–3087,
<https://doi.org/10.5194/nhess-18-3085-2018>, available at: <https://nhess.copernicus.org/articles/18/3085/2018/>, 2018.

Goodchild, M. F.: Scale in GIS: An overview, *Geomorphology*, 130, 5–9, <https://doi.org/10.1016/j.geomorph.2010.10.004>,
available at: <http://www.sciencedirect.com/science/article/pii/S0169555X10004332>, 2011.

Grasso, V. F.: The State of Early Warning Systems, in: *Reducing Disaster: Early Warning Systems For Climate Change*,
815 edited by: Singh, A. and Zommers, Z., Springer Netherlands, Dordrecht, 109–, 2014.

[Guerriero, L., Di Martire, D., Calcaterra, D., and Francioni, M.: Digital Image Correlation of Google Earth Images for Earth's Surface Displacement Estimation, Remote Sensing, 12, https://doi.org/10.3390/rs12213518, available at: https://www.mdpi.com/2072-4292/12/21/3518, 2020.](#)

Hilker, N., Badoux, A., and Hegg, C.: The Swiss flood and landslide damage database 1972–2007, *Nat. Hazards Earth Syst.*
820 *Sci.*, 9, 913–925, <https://doi.org/10.5194/nhess-9-913-2009>, 2009.

Huggel, C., Clague, J., and Korup, O.: Is climate change responsible for changing landslide activity in high mountains?,
Earth Surface Processes and Landforms, 37, 77–91, <https://doi.org/10.1002/esp.2223>, 2012.

Hungr, O., Leroueil, S., and Picarelli, L.: The Varnes classification of landslide types, an update, *Landslides*, 11, 167–194,
<https://doi.org/10.1007/s10346-013-0436-y>, available at: <https://doi.org/10.1007/s10346-013-0436-y>, 2014.

825 IPCC (Ed.): *Climate change 2014: Synthesis report*, Synthesis Report. Contribution of Working Groups I, II and III to the
Fifth Assessment Report of the Intergovernmental Panel on Climate Change, Intergovernmental Panel on Climate
Change, Geneva, Switzerland, 151 pp., 2014.

Kääb, A., Altena, B., and Mascaro, J.: Coseismic displacements of the 14 November 2016 Mw 7.8 Kaikoura, New Zealand,
earthquake using the Planet optical cubesat constellation, *Nat. Hazards Earth Syst. Sci.*, 17, 627–639,
830 <https://doi.org/10.5194/nhess-17-627-2017>, 2017.

[Lacroix, P., Pham, M. Q., and Araujo, G.: MuDsLIdES: Monitoring and Detection of Landslides from optical Images time-Series, Executive Summary, ESA-Alcantara initiative No 15/P26., n.d.](#)

Lacroix, P., Araujo, G., Hollingsworth, J., and Taipei, E.: Self-Entrainment Motion of a Slow-Moving Landslide Inferred
From Landsat-8 Time Series, *J. Geophys. Res. Earth Surf.*, 124, 1201–1216, <https://doi.org/10.1029/2018JF004920>,
835 2019.

- Lacroix, P., Bièvre, G., Pathier, E., Kniess, U., and Jongmans, D.: Use of Sentinel-2 images for the detection of precursory motions before landslide failures, *Remote Sensing of Environment*, 215, 507–516, <https://doi.org/10.1016/j.rse.2018.03.042>, 2018.
- 840 Lacroix, P., Berthier, E., and Taïpe Maquerhua, E.: Earthquake-driven acceleration of slow-moving landslides in the Colca valley, Peru, detected from Pléiades images, *Remote Sensing of Environment*, 165, 148–158, <https://doi.org/10.1016/j.rse.2015.05.010>, available at: <http://www.sciencedirect.com/science/article/pii/S0034425715300080>, 2015.
- Leprince, S.: Monitoring Earth Surface Dynamics with Optical Imagery, PhD Thesis, California Institute of Technology, 2008.
- 845 Leprince, S., Berthier, E., Ayoub, F., Delacourt, C., and Avouac, J.-P.: Monitoring Earth Surface Dynamics With Optical Imagery, *Eos*, 89, <https://doi.org/10.1029/2008EO010001>, 2008.
- Leprince, S., Barbot, S., Ayoub, F., and Avouac, J.-P.: Automatic and Precise Orthorectification, Coregistration, and Subpixel Correlation of Satellite Images, Application to Ground Deformation Measurements, *IEEE Trans. Geosci. Remote Sensing*, 45, 1529–1558, <https://doi.org/10.1109/TGRS.2006.888937>, 2007.
- 850 Loew, S., Gschwind, S., Gischig, V., Keller-Signer, A., and Valenti, G.: Monitoring and early warning of the 2012 Preonzo catastrophic rockslope failure, *Landslides*, 14, 141–154, <https://doi.org/10.1007/s10346-016-0701-y>, 2017.
- Lucieer, A., Jong, S. de, and Turner, D.: Mapping landslide displacements using Structure from Motion (SfM) and image correlation of multi-temporal UAV photography, *Progress in Physical Geography*, 38, 97–116, <https://doi.org/10.1177/0309133313515293>, 2014.
- 855 [Mazzanti, P., Rocca, A., Bozzano, F., Cossu, R., and Floris, M.: Landslides Forecasting Analysis By Displacement Time Series Derived From Satellite INSAR Data: Preliminary Results, in: FRINGE 2011 Workshop: SP-697, Frascati, Italy, 19-23 September 2011, 2012.](#)
- Mazzanti, P., Caporossi, P., and Muzi, R.: Sliding Time Master Digital Image Correlation Analyses of CubeSat Images for landslide Monitoring: The Rattlesnake Hills Landslide (USA), *Remote Sensing*, 12, 592, <https://doi.org/10.3390/rs12040592>, 2020.
- 860 Moretto, S., Bozzano, F., Esposito, C., Mazzanti, P., and Rocca, A.: Assessment of Landslide Pre-Failure Monitoring and Forecasting Using Satellite SAR Interferometry, *Geosciences*, 7, 1–16, <https://doi.org/10.3390/geosciences7020036>, 2017.
- Moretto, S., Bozzano, F., Esposito, C., and Mazzanti, P.: Lesson learned from the pre-collapse time series of displacement of the Preonzo landslide (Switzerland), *ROL*, 41, 247–250, <https://doi.org/10.3301/ROL.2016.140>, 2016.
- 865 [Noetzi, J., Pellet, C., and Staub, B.: Permafrost in Switzerland 2014/2015 to 2017/2018: Glaciological Report Permafrost No. 16–19 of the Cryospheric Commission of the Swiss Academy of Sciences, Swiss Permafrost Monitoring Network \(PERMOS\), 2019.](#)
- Pecoraro, G., Calvello, M., and Piciullo, L.: Monitoring strategies for local landslide early warning systems, *Landslides*, 16, 213–231, <https://doi.org/10.1007/s10346-018-1068-z>, 2019.
- 870 [Pesci, A., Giordano, T., Casula, G., Loddo, F., Martino, P. de, Dolce, M., Obrizzo, F., and Pingue, F.: Multitemporal laser scanner-based observation of the Mt. Vesuvius crater: Characterization of overall geometry and recognition of landslide events, *ISPRS Journal of Photogrammetry and Remote Sensing*, 66, 327–336, <https://doi.org/10.1016/j.isprsjprs.2010.12.002>, 2011.](#)
- 875 Petley, D. N. and Petley, D. J.: On the initiation of large rockslides: perspectives from a new analysis of the Vaiont movement record, in: *Landslides from Massive Rock Slope Failure*, edited by: Evans, S. G., Scarascia-Mugnozza, G., Strom, A., and Hermanns, R. L., Springer Netherlands, Dordrecht, 77–84, 2006.

- Planet Labs: RapidEye Constellation to be Retired in 2020, <https://www.planet.com/pulse/rapideye-constellation-to-be-retired-in-2020/>, last access: 23 February 2020, 2020a.
- 880 Planet Labs: Planet Imagery Product Specification: PLANETSCOPE & RAPIDEYE, 2020b.
- Plank, S., Krautblatter, M., and Thuro, K.: Feasibility Assessment of Landslide Monitoring by Means of SAR Interferometry: A Case Study in the Ötztal Alps, Austria, in: *Engineering Geology for Society and Territory: Volume 2*, edited by: Lollino, G., Giordan, D., Crosta, G. B., Corominas, J., Azzam, R., Wasowski, J., and Sciarra, N., Springer International Publishing, Cham, 375–378, https://doi.org/10.1007/978-3-319-09057-3_58, 2015.
- 885 Reid, M. E., Baum, R. L., LaHusen, R. G., and Ellis, W. L.: Capturing landslide dynamics and hydrologic triggers using near-real-time monitoring, in: *Landslides and engineered slopes: From the past to the future*, edited by: Chen, Z., Zhang, J.-M., Ho, K., Wu, F.-Q., and Li, Z.-K., CRC Press, Boca Raton, Fla., 2008.
- Rosu, A.-M., Pierrot-Deseilligny, M., Delorme, A., Binet, R., and Klingner, Y.: Measurement of ground displacement from optical satellite image correlation using the free open-source software MicMac, *ISPRS Journal of Photogrammetry and Remote Sensing*, 100, 48–59, <https://doi.org/10.1016/j.isprsjprs.2014.03.002>, available at: <http://www.sciencedirect.com/science/article/pii/S0924271614000653>, 2015.
- 890 Sättele, M., Krautblatter, M., Bründl, M., and Straub, D.: Forecasting rock slope failure: how reliable and effective are warning systems?, *Landslides*, 13, 737–750, <https://doi.org/10.1007/s10346-015-0605-2>, 2016.
- Scaioni, M., Longoni, L., Melillo, V., and Papini, M.: Remote Sensing for Landslide Investigations: An Overview of Recent Achievements and Perspectives, *Remote Sensing*, 6, 9600–9652, <https://doi.org/10.3390/rs6109600>, 2014.
- 895 [Schrott, L., Otto, J.-C., and Keller, F.: Modelling alpine permafrost distribution in the Hohe Tauern region, Austria, *Austrian Journal of Earth Sciences*, 105, 169–183, 2012.](#)
- Semenza, E. and Ghirotti, M.: History of the 1963 Vaiont slide: The importance of geological factors, *Bulletin of Engineering Geology and Environment*, 59, 87–97, <https://doi.org/10.1007/s100640000067>, 2000.
- 900 Seneviratne, S. I., Nicholls, N., Easterling, D., Goodess, C. M., Kanae, S., Kossin, J., Luo, Y., Marengo, J., McInnes, K., Rahimi, M., Reichstein, M., Sorteberg, A., Vera, C., Zhang, X., Rusticucci, M., Semenov, V., Alexander, L. V., Allen, S., Benito, G., Cavazos, T., Clague, J., Conway, D., Della-Marta, P. M., Gerber, M., Gong, S., Goswami, B. N., Hemer, M., Huggel, C., van den Hurk, B., Kharin, V. V., Kitoh, A., Tank, A. M. K., Li, G., Mason, S., McGuire, W., van Oldenborgh, G. J., Orłowsky, B., Smith, S., Thiaw, W., Velegrakis, A., Yiou, P., Zhang, T., Zhou, T., and Zwiers, F. W.:
- 905 *Changes in Climate Extremes and their Impacts on the Natural Physical Environment*, in: *Managing the Risks of Extreme Events and Disasters to Advance Climate Change Adaptation: A Special Report of Working Groups I and II of the Intergovernmental Panel on Climate Change*, edited by: Field, C. B., Barros, V., Stocker, T. F., and Dahe, Q., Cambridge University Press, Cambridge, 109–230, <https://doi.org/10.1017/CBO9781139177245.006>, 2012.
- Stumpf, A., Michéa, D., and Malet, J.-P.: Improved Co-Registration of Sentinel-2 and Landsat-8 Imagery for Earth Surface Motion Measurements, *Remote Sensing*, 10, 160, <https://doi.org/10.3390/rs10020160>, 2018.
- Stumpf, A., Malet, J.-P., Puissant, A., and Travelletti, J.: Monitoring of Earth Surface Motion and Geomorphologic Processes by Optical Image Correlation: Chapter 5, in: *Land Surface Remote Sensing: Environment and Risks*, edited by: Baghdadi, N. and Zribi, F. M., ISTE Press - Elsevier, 147–190, <https://doi.org/10.1016/B978-1-78548-105-5.50005-0>, 2016.
- 915 Stumpf, A.: *Landslide recognition and monitoring with remotely sense data from passive optical sensors*, Dissertation, University of Strasbourg, Strasbourg, 2013.
- Sudmanns, M., Tiede, D., Lang, S., Bergstedt, H., Trost, G., Augustin, H., Baraldi, A., and Blaschke, T.: Big Earth data: disruptive changes in Earth observation data management and analysis?, *International Journal of Digital Earth*, 123, 1–19, <https://doi.org/10.1080/17538947.2019.1585976>, available at: <https://www.tandfonline.com/doi/full/10.1080/17538947.2019.1585976>, 2019.
- 920

TUM: AlpSenseBench: Alpine remote sensing of climate-induced natural hazards,

<https://www.bgu.tum.de/landslides/alpsensebench/projekt/>, last access: 22 September 2020, 2020.

Turner, D., Lucieer, A., and Jong, S. de: Time Series Analysis of Landslide Dynamics Using an Unmanned Aerial Vehicle (UAV), *Remote Sensing*, 7, 1736–1757, <https://doi.org/10.3390/rs70201736>, 2015.

925 UNISDR: UNISDR Terminology on Disaster Risk Reduction, United Nations Office for Disaster Risk Reduction, Geneva, Switzerland, 2009.

UNISDR: Basics of early warning, Platform for the Promotion of Early Warning, <https://www.unisdr.org/2006/ppew/whats-ew/basics-ew.htm>, 2006.

Volat, M., Lacroix, P., Bontemps, N., and Doin, M.-P.: Introducing “TIO”: Optical imagery time series analysis on the
930 Geohazards Exploitation Platform, in: MDIS ForM@Ter 2017, Besse en Chandesse, Oct. 20, 2017, 2017.

Walter, F., Amann, F., Kos, A., Kenner, R., Phillips, M., Preux, A. de, Huss, M., Tognacca, C., Clinton, J., Diehl, T., and Bonanomi, Y.: Direct observations of a three million cubic meter rock-slope collapse with almost immediate initiation of ensuing debris flows, *Geomorphology*, 351, 106933, <https://doi.org/10.1016/j.geomorph.2019.106933>, 2020.

Westoby, M. J., Brasington, J., Glasser, N. F., Hambrey, M. J., and Reynolds, J. M.: ‘Structure-from-Motion’
935 photogrammetry: A low-cost, effective tool for geoscience applications, *Geomorphology*, 179, 300–314, <https://doi.org/10.1016/j.geomorph.2012.08.021>, 2012.

Seite 1: [1] Kommentiert [DH11] Doris Hermle 27.04.2021 08:33:00

Added definition following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:

Concept of lead time and need for best possible reduction is not new.

and

The missing sound conceptual approach is also reflected in the introduction in form of a lengthy summary of in principle available remote sensing methods and data showing no clear line of arguments (L20-100). Moreover, the new conceptual approach presented in Fig. 1 is very general and not specific to landslide and does not qualify as a novelty in the current form.

Seite 1: [2] Kommentiert [DH12] Doris Hermle 30.04.2021 09:13:00

Modified following comment by RC2 (S. Roessner)

RC2 (S. Roessner) wrote:

The missing sound conceptual approach is also reflected in the introduction in form of a lengthy summary of in principle available remote sensing methods and data showing no clear line of arguments (L20-100). Moreover, the new conceptual approach presented in Fig. 1 is very general and not specific to landslide and does not qualify as a novelty in the current form.

Seite 11: [3] Kommentiert [DH62] Doris Hermle 16.07.2021 08:24:00

Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

It is my impression that the authors have understood my above comment differently than it was intended. Figs. 5 a) and e) as well as b) and f) show the results of the first and second interval, respectively. While a) and e) result from DIC of 0.16 m resolution orthoimages, b) and f) result from the same images, but resampled to 3m. Yet the pattern and magnitude of e) and f) do in no way match the data in a) and b), while it is the same data over the same time interval. My point is that this does not make sense from a technical point of view when automatically tracking features in the same images, with only a different resolution. I would think that the authors need to decide, which of the two solutions is closer to the truth, but in my view it has to be made absolutely clear in the manuscript that these data do not match. When pointing out that I do not see a plausible explanation for the data presented in e) and f) from a geomorphic point of view, I was hoping for a critical evaluation of this data.

Seite 11: [4] Kommentiert [DH64] Doris Hermle 05.03.2021 15:41:00

Answer to comment by RC1 (J. Blöthe) in review 1 and added description following comment by RC1 based on review 2

RC1 (J. Blöthe) wrote in review 1:

L307/308 and L440/442: This seems a bit arbitrary. How did you determine a cutoff-value of 4m displacement? How did you distinguish outliers from non-outliers? What is the confidence of your estimates?

RC1 (J. Blöthe) wrote in review 2:

It would be appropriate to include this description into the manuscript. As I pointed out in my comments in the first round of reviews, the error assessment is very important and just setting an arbitrary threshold of 4 m without elaborating the calculation of this values is insufficient.

Seite 12: [5] Kommentiert [DH70] Doris Hermle 01.03.2021 20:25:00

Modified following comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:

L320: As you present total displacement for different time intervals here, not rates in distance per unit time, I would suggest changing the title here. Same is true for L326, L346 and L361.

Seite 12: [6] Kommentiert [DH71] Doris Hermle 16.07.2021 08:40:00

Modified figure and deleted (e) and (f), results of 3 m downsampled UAS DIC results following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Seite 12: [7] Kommentiert [DH74] Doris Hermle 16.07.2021 16:05:00

Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2: This is a crucial point. While you acknowledge here that in the area of decorrelated values, matching did in essence not work, this is not stated as explicitly in the manuscript. In my view, it would be necessary to clearly highlight the decorrelated areas as such in the Fig. 5 and explicitly mention the division in reliably tracked regions and those regions that are unreliable (i.e. random) and cannot be interpreted. In my impression this is not done in the present revised manuscript.

Seite 13: [8] Kommentiert [DH85] Doris Hermle 16.07.2021 08:44:00

Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Seite 13: [9] Kommentiert [DH88] Doris Hermle 01.03.2021 20:36:00

Answer to comment by RC1 (J. Blöthe) in response and please see OSM

RC1 (J. Blöthe) wrote:

L335/336 and L366: Did you check the direction of displacement for the areas of smallscale patterns of ambiguous signals? I would suspect that these are very heterogenous here as well. It would also be worth looking into the quality information (correlation coefficients) for these regions.

Seite 13: [10] Kommentiert [DH89] Doris Hermle 18.07.2021 15:38:00

Added description following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2

I would recommend to include the bearing information more prominently in the manuscript itself, as this is a very important information on the data quality.

Seite 18: [11] Kommentiert [DH115] Doris Hermle 22.07.2021 19:29:00

Modified following comment by RC1 (J. Blöthe) in review no. 2

RC1 (J. Blöthe) wrote in review no. 2:

Thank you for the detailed answer. My comment was intended to motivate the authors not only to provide me with these details, but to include them in the revised version of the manuscript. Please include this explanation, or a short version of it, in the text. Regarding the residual mismatches stated here and shown in Fig. 14 of the OSM: this already gives a measure of the amount of significant displacement, i.e. beyond a level of detection, that can be detected with DIC between these images. If your residual mismatch after coregistration (as shown in Fig. 14 OSM) averages to 0.6 - 0.8 pixel, everything below that cannot be treated as significant motion. But still, this would be much lower than your arbitrary 4 m and would be based on a reproducible quantification approach.

Seite 18: [12] Kommentiert [DH116] Doris Hermle 16.07.2021 10:23:00

Modified after deletion following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Seite 18: [13] Kommentiert [DH118] Doris Hermle 02.03.2021 10:32:00

Modified in response to comment by RC1 (J. Blöthe)

RC1 (J. Blöthe) wrote:

L463/464: As the GCPs for referencing the UAS data are probably located close to the landslide, it is not surprising, but neither disturbing, that false displacement clusters appear outside the area of interest.

Seite 18: [14] Kommentiert [DH119] Doris Hermle 16.07.2021 08:48:00

Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Seite 18: [15] Kommentiert [DH120] Doris Hermle 16.07.2021 09:07:00

Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Seite 18: [16] Kommentiert [DH121] Doris Hermle 16.07.2021 10:22:00

Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Seite 18: [17] Kommentiert [DH122] Doris Hermle 05.03.2021 16:08:00

Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:

L468/470: Again, I would not trust the displacement estimates of the resampled UAS data. While it is true that your manual boulder tracking identified 2 boulders with displacement of 10 or more meters, the remaining 34 boulders show something different.

Seite 18: [18] Kommentiert [DH123] Doris Hermle 18.07.2021 19:33:00

Modified in response to comment by RC1 (J. Blöthe) in review 2

RC1 (J. Blöthe) wrote in review 2:

I strongly doubt that you can make this statement. The image processing algorithm matches pixel value distributions from patches in consecutive images. When the pixel value distribution changes between images, the algorithm does not find the "true" corresponding area, but matches to the most similar patch it finds. Whether the pixel value distribution changes in reaction to snow cover, shadows, or vegetation, or if large displacements induce the spectral differences is not discernable for the DIC software.

Seite 18: [19] Kommentiert [DH124] Doris Hermle 16.07.2021 09:08:00

Deleted following comment by RC1 (J. Blöthe) in review no. 1 and 2

RC1 (J. Blöthe) wrote in review no. 2:

There are a number of points indicating that the data presented in e) and f) is problematic here and that a) and b) are rather plausible. I have listed these concerns, numbered a) to d) and highlighted in the attachment, in the general comments of the first round of reviews and these still stand.

Answer to comment by RC1 (J. Blöthe) in response

RC1 (J. Blöthe) wrote:

L471/476: While it might be true that the results obtained from image correlation of resampled 3m UAS data are better (internally) correlated and show a more homogeneous deformation pattern, this does not mean that the result is correct. As I outlined above, I have serious doubts regarding the interpretability of this data, as there is no agreement with the manually tracked boulder velocities (except 2 boulders). Also, from a geomorphic perspective, I am not sure how you would explain a velocity pattern where high velocities dominate throughout the entire landslide, but are speckled with lower to zero movement within (Fig. 5 e and f).

Modified and restructured this sentence to emphasise our recommendation following comment by RC1 (J. Blöthe). In addition, please see answer in response.

RC1 (J. Blöthe) wrote:

L485/488: Did you evaluate the proportion of false-positive displacements to truepositive displacements and if so, how did you do this and can you please include this data? Based on the image correlation results shown here, you can make this statement, but I would be cautious to make a general claim on the usability of the data.