

Exploring the partial use of the Mo.S.E. system as effective adaptation to rising flood frequency of Venice

Riccardo A. Mel¹

¹Department of Environmental Engineering, University of Calabria, Rende (CS), 87036, Italy

5 Correspondence to: Riccardo A. Mel (riccardo_alvise.mel@unical.it)

Abstract.

~~In times of climate change the impact of coastal hazards should be mitigated by identifying and implementing effective adaptation strategies, encompassing a balanced mix of structural and non-structural measures based on high-level scientific knowledge. Due to its hydro-geological features, the~~ Venice lagoon (Italy) is particularly vulnerable to the impact of subsidence and sea level rise driven by climate change. Some structural measures have been adopted over time to protect Venice from flooding, among which a system of flap gates (Mo.S.E. system) has been operational under testing phase since October 2020. However, relative sea level rise and wind setup pose relevant management challenges, as a frequent closing of the lagoon would have negative impacts on flushing capacity, fishing industry and port activities. ~~Hence, optimal operation rules for the existing control structure are searched to anticipate and to adapt to a possible acceleration of sea level rise induced by climate change.~~ Here, the focus is on the hydrodynamic effects of a partial closure of the Mo.S.E. barriers that, ~~with respect~~compared to closing all the three inlets of the Lagoon, could play a role in reducing the economic and environmental impacts of the Mo.S.E. system. The main goal is to identify the flooding events that can be counteracted by closing only the Lido inlet, which is the closest to the city of Venice. Based on the tidal and meteorological dataset collected in the period 2000-2019, a robust modelling exercise ~~indicates that the closing of the Lido inlet only would protect the Venice~~identifies a linear relationship between tidal range and reduction of the sea level peaks, which results in the protection of all urban settlements within the lagoon from two third of the flooding events up to a relative sea level rise of + 0.4 m.

1 Introduction

Floods are a significant long-term risk to society (Wadey et al., 2012). While the population generally adapts to them (Van Koningsveld et al., 2008; ~~Dawson et al., 2011~~; Jongman, 2018), this is mostly accomplished as consequence of real events (Mel et al., 2021b; ~~under review~~), which can involve significant economic losses and deaths (Hinkel et al., 2014; Jongman et al., 2014; ~~Paprotny et al., 2018~~). In Europe coastal flooding is one of the most threatening natural hazard (e.g. Capobianco et al., 1999; ~~Battjes and Gerritsen, 2002~~; ~~Liquete et al., 2013~~; Drejza et al., 2019), and flood risk is expected to further increase

in the near future in all the acting components, as sea level (SL) rise, tides, waves, and storm surges (Semedo et al., 2013; Wang et al., 2014; Alfieri et al., 2015; Androulidakis et al., 2015; Marcos et al., 2012; Voudoukas et al., 2017; Jongman, 2018), with particular reference to extreme events (e.g. Haigh et al., 2011; Menéndez and Woodworth, 2010; Wahl et al., 2011; Woth et al., 2006; Pranzini et al., 2015; 2011; MedECC, 2020). Coastal flood hazard is exacerbated by climate change, anthropogenic modifications of the land and of the environment, and by socio-economic factors (Kundzewicz et al., 2014; Pycroft et al., 2016), driving morphological changes and erosion processes (Ciavola et al., 2011), as well as coastal protection failures (Oumeraci, 1994; Matias et al., 2008; Voudoukas et al., 2017), reducing the effectiveness of the traditional defence strategies (Brown et al., 2005; Few et al., 2007; OECD, 2016). As the flooding risk can never be entirely prevented fixed (Diez et al., 2011), effective adaptation strategies are needed (McCarthy et al., 2001; Klein et al., 2001; Hinkel et al., 2014; Meechler et al., 2014; Cutter and Gall, 2015; Diaz, 2016), based on a diversified approach of interventions, which may include structural and non-structural measures aimed at preserving the social, economic and environmental functions of coastal areas (Aerts et al., 2014; Lineke and Hinkel, 2018; Jongman, 2018; Tiggeloven et al., 2020). Structural measures (i.e., hard and soft flood defence works designed for long-term operating, see Maiolo et al., 2020) should be supported by non-structural measures, comprising laws, policies, regulations, planning instruments, optimal management protocols, risk assessment and informational systems for coastal ecosystems and resources management (Smith and Lenhart, 1996; Smit and Wandel, 1999; Kundzewicz, 2002; Moser et al., 2018; De Alenear et al., 2020; Elko and Briggs, 2020; Mel et al., 2020). Although several approaches and models have been proposed to optimize planning and management actions, implementing effective strategies requires complex decision-making processes and an innovative approach to flood defence (Few et al., 2007; Tobey et al., 2010), addressing the major institutional, economic, and environmental barriers (EC, 2009; Ward et al., 2017; Molinaroli et al., 2018).

Floods are a recurrent hazard for the iconic city of Venice (Mel and Lionello, 2014), a clear example of a huge historical, cultural, and environmental heritage at risk. Flood frequency has significantly worsened since the 1950s (Battistin and Canestrelli, 2006; Lionello et al., 2012; Mel et al., 2019a; Lionello et al., 2021) due to relative sea level rise (RSLR) which is caused by local subsidence and decadal-scale acceleration in the rate of global sea level rise driven by climate changes (Carbognin et al., 2004; Ferla et al., 2007; Lionello, 2012; IPCC, 2013; Zanchettin et al., 2020). This alarming trend is expected to continue and even accelerate within the present century (IPCC, 2013; 2021). The detrimental effect produced by storm surges in the Adriatic Sea has been shown by the events of 4 November 1966 (De Zolt et al., 2006; Lionello et al., 2021) and 12 November 2019 (Cavaleri et al., 2020; Ferrarin et al., 2020) which produced enormous severe loss and damage to the historical buildings, economic activities in the coastal settlements located within the Venice lagoon, and even deaths.

The resilience of the Venice lagoon has been permanently linked to the human presence since remote times. The Venetians altered the environment by building several hard structures, with the aim to preserve economic interests, for defence purposes and to maintain the very existence of the lagoon (Molinaroli et al., 2009; D'Alpaos, 2003; Sarretta et al., 2010; Ferrarin et al.,

ha formattato: Inglese (Stati Uniti)

ha formattato: Inglese (Stati Uniti)

60 2013). As non-structural measures adopted for prevention, preparedness and response to floods, the Venetians raised the
ground floors, placed steel barriers at the entrance to buildings and adapted the existent electrical systems (Indirli, 2014;
Molinarioli et al., 2018). Extreme storms were catalysts of the awareness rising that the Lagoon had lost much of its natural
resilience to floods (Samiolo, 2012), highlighting the need to build new flood defence structures and to invest more in
adaptation strategies (Munaretto et al., 2012). After the 1966 flood, the Italian government supported by the scientific
65 community and supranational organisations like the UNESCO (UNESCO, 1969) promoted several structural measures to
reduce the impact of flooding, erosion process and water pollution (e.g. Italian Law n. 171 of April 16, 1973; Italian Law n.
798 of November 29, 1984), as the Experimental Electromechanical Module (Mo.S.E.), a system of mobile barriers aimed at
closing the inlets temporarily to protect the Venice lagoon through a set of 78 ~~independently~~independent flap gates (Eprim,
2005; ~~Trineardi et al., 2016~~).
70 In response to the devastating flood event which occurred in 2019, safeguarding of the Venice lagoon became a pressing priority.
Works to build the Mo.S.E. system, ~~begun~~began in 2003. Since 3 October 2020, the Mo.S.E. system has been operating under
testing phase (see Mel et al., 2021b, under review). Within the first three months, the Mo.S.E. system was operated 20 times
during high tide conditions (see Appendix A for the ~~detail~~details of the ~~operation~~each operation). However, poor
meteorological forecast, novel management options, economic and environmental impact of the closures ~~raised~~raised a vast
75 debate about the optimal use of the system. According to recent studies, the use of the Mo.S.E. system on the one hand
contributes to lowering the short term monetary costs induced by the periodical flooding (Nunes et al., 2005); on the other
hand, if implemented too frequently or for too long a time, it could affect the water quality of the lagoon (Melaku et al., 2001;
Viero and Defina, 2016), and induce additional direct and indirect costs to fishing and port activities (Costa, 1993; ~~Chiabai~~
~~and Nunes, 2008~~; Vergano et al., 2010). As the need to close the barriers becomes more frequent in view of the ongoing
80 processes of land subsidence and RSLR, the optimal management of the Mo.S.E. system will play a crucial role in balancing
the needs of flood protection with the issues related to port activities and ecosystem preservation. According to Umgiesser
(2020) and Mel et al. (2021a), only + 0.3 m of RSLR would generate almost 100 closures/year, often involving multiple tidal
cycles, and disrupting a significant portion of vessel traffic (Brotto and Gentilomo, 1998; Umgiesser and Matticchio, 2006).
In addition, the flushing of the lagoon would be greatly reduced, building up toxic substances and damaging its delicate
85 ecosystem (AGU, 2002; UNESCO, 2011). In this context, a possible adaptation strategy consists in limiting the extent of the
closure of the inlets through a partial use of the Mo.S.E. system, (i.e., the closure of one or two inlets at a time or a partial
closure of each inlet). In particular, the closure of the Lido inlet only can mitigate the flood hazard without significantly
affecting the water quality and the economy of the Lagoon, since it is scarcely used for commercial traffic, as the Malamocco
inlet, or fisheries, as the Chioggia inlet. Hereinafter, such partial operation of the Mo.S.E. system is named as Partial Closure
90 of the Lagoon involving the Lido inlet only (PCL).

ha formattato: Colore carattere: Testo 1


Some recent studies that attempted to quantify the effects of the partial operation of the Mo.S.E. system (Cavallaro et al., 2017; Umgiesser et al., 2020) are affected by important limitations: the sea level thresholds associated to the partial closure of the barriers were kept fixed and equal to the thresholds associated to the full Mo.S.E. closure (Eprim, 2005), and the role of tidal range, wind setup and intragate infiltration was neglected. The present contribution aims to fill this knowledge gap by a systematic numerical investigation of the effects of the PCL on the hydrodynamic of the lagoon. Specifically, the main goals are (a) identifying a relationship between tidal range and reduction of the SL peak at the main settlements of the Venice lagoon, namely Venice, Burano, and Chioggia; (b) investigating the effects of wind setup and intragate infiltration on such relationship; (c) address the potential benefit of the PCL in reducing the frequency of full Mo.S.E. closures in the present and future scenarios. The results of the study can be beneficial for research and decision-making efforts toward an optimal management of the Mo.S.E. system.


2 Materials and method

2.1 Venice lagoon and Mo.S.E. system

The Venice lagoon, stretching for more than 60 kilometres from north to south and about 12-16 kilometres from west to east, is the largest Mediterranean brackish water body. It is connected to the Adriatic Sea through three inlets, namely, from north to south, Lido, Malamocco and Chioggia, whose widths range from 400 m to 800 m and depths between 6 m and 14 m. Note that the Lido inlet is divided in two parts by the Mo.S.E. infrastructure, named “Treporti canal” and “San Nicolò canal”, see Fig. 1. The Lagoon, characterized by an average water depth of about 3 m, consists of a complex system of channels, tidal flats, salt marshes and small islands, and a high heterogeneity in physical, and biogeochemical, and biological conditions of mutually interacting habitats (Carniello et al., 2009; Finotello et al., 2018; Molinaroli et al., 2018). The most prominent urban settlements are Burano, in the northern lagoon, Venice in the central lagoon, and Chioggia, located in the southern lagoon (Fig. 1). The main circulation forcing factors are a semidiurnal tidal regime and the wind. The average residence time ranges from 1 day for the areas located close to the inlets to 30 days for the inner areas (Viero and Defina, 2016). Nutrient and pollutants mostly originate from urban areas and from the drainage basin (Melaku et al., 2001). For each tidal cycle, the water exchanged through the inlets is about a third of the total volume of the lagoon (Gacic and Solidoro, 2004). In calm atmospheric conditions, when circulation is influenced ~~only~~ by the tide ~~only~~, the Venice lagoon is subdivided into three sub-basins, one for each inlet, separated by two watersheds through which the residual flow is minimum (D’Alpaos, 2003; Fig.1, see also Solidoro et al., 2004). The propagation of the tide is affected by the shape of the inlets and the morphology of the lagoon. The tidal range reduces proceeding from the inlets towards the lagoon interior, showing a progressive propagation lag. These alterations in tidal signal produce significant lagoonal currents, triggered by the prevailing SL differences between different regions of the

120 same sub-basin. Prevalent winds are north-easterly (Bora wind) and south-easterly (Sirocco), of speed up to 20-25 m/s (Mel et al., 2021a).





125 **Figure 1:** The Venice lagoon with the location of the watersheds (dashed grey lines) and the Mo.S.E. barriers (thick red lines). The bullets show the location of wind (green) and tide stations (blue, lagoonal gauges; yellow seaward gauges) used in the present work, coming from the database of the Tidal Forecast Centre of the Venice Municipality (Centro Previsioni e Segnalazioni Maree, CPSM).

For more than a millennium, Venice has endured by altering the environment of the lagoon (Brambati et al., 2003). Several hydraulic works, such as river diversion, building of large sea wall, digging new navigation canals, enabled the historical heritage of Venice and the related industrial and economic activities to survive, producing a significant impact on the morphology of the lagoon and on the local tidal regimes (Carniello et al., 2009; [D'Alpaos, 2010](#); Sarretta et al., 2010; Silvestri

130

et al., 2018). By the 1970s, more than half of the lagoonal surface had been reclaimed or cordoned off for business-related purposes, altering the natural morphological features and amplifying the tidal range (Molinaroli et al., 2018). As from the very beginning Venice has co-existed with the sea by adopting several measures to adapt to the flood hazard, at present the Mo.S.E. system is conceived to protect the lagoon by temporarily separating it from the sea during the flood events. The Mo.S.E. system consists of four separate storm surge barriers (Fig. 1) formed by some independent flap gates 20 m wide, 5 m thick and between 18 and 28 m high, hinged on the bottom of the inlets. The Lido inlet has two barriers with 21 (Treporti canal) and 20 (San Nicolò canal) elements, Malamocco and Chioggia a single barrier of 19 and 18 elements respectively (see <https://www.mosevenezia.eu/progetto/> for more technical details). In normal tidal conditions, the flap gates rest full of water on the bottom of the inlets. When a tide is expected to exceed the safeguard threshold, compressed air is pumped into the gates, allowing the barriers to rotate upwards interrupting the tidal flow (Gentilomo and Cecconi, 1997). The safeguard threshold, defined as the SL that should not be exceeded during high tides (Umgiesser, 2020), is set to 1.10 m above the local datum at Venice and Burano and 1.30 m at Chioggia, which is protected since 2012 by a local defence installed at both ends of the main canal crossing the historical centre. As an important note, during the present testing phase of the Mo.S.E. system no specific management protocols have been adopted. The barriers have been operated partially and/or asynchronously in order to estimate the time needed to raise and drop the gates, monitor the hydrodynamics of a regulated lagoon and highlight possible shortcomings (see Appendix A for the details of each operation).

In this work, SL elevations refer to the official local datum of the Punta della Salute (PS) SL gauging station, located in Venice city centre, whose zero is located 0.23 m below the national vertical level datum (IGM 1942) and 0.34 m below the present mean SL (Cavaleri et al., 2020).

2.1.12 Data and tidal characteristics characteristic

The SL, wind speed and wind direction data used in the present work come from the database of the Tidal Forecast Centre of the Venice Municipality (i.e., Centro Previsioni e Segnalazioni Maree, CPSM). A first dataset consists in two years (2019 - 2020) long records of SL, wind speed and direction collected every ten minutes, used to reproduce some recent flood events (all the gauges used in this work are reported in Fig. 1). From the same institution, SL peaks and troughs gauged within the period 2000-2019 (including a Metonic cycle) define the scope of the present work in terms of tidal range during the flood tide (i.e., the SL difference between the peak and the previous trough, hereinafter named as tidal range) and of tidal semi-period during the flood tide (hereinafter named as tidal period). Mean tidal range at PS is 0.60 m, with more than 20% of the data greater than 0.880 m (i.e., spring tide, see Fig.2a). Tidal period shows a lower variability of the distribution, with a mean value at PS of about 6h 20' and almost 90% of the data located between four and eight hours (Fig. 2b).

Formattato: Titolo 2




Figure 2: Dataset 2000-2019, Punta della Salute (PS). Frequency distribution of tidal range (a) and tidal semi-period (b). Data refer to flood tide.

2.2.3 Hydrodynamic model

Numerical simulations were carried out using the WWTM (Defina, 2000; Carniello et al., 2011), a two-dimensional mathematical model developed at the Department of Civil, Environmental and Architectural Engineering, University of Padova and successfully applied in the Venice lagoon and in other tidal environments (Carniello et al., 2005; Mariotti et al., 2010; Zarzuelo et al., 2018; Mel et al., 2019b; Pivato et al., 2020). WWTM is a coupled wind-wave-tide model that solves the full shallow water equations using a semi-implicit staggered numerical scheme based on the Galerkin's approach (Martini et al., 2004; D'Alpaos and Defina, 2007). The finite element method allows to employ elements with different shapes and sizes, providing high flexibility in the spatial discretization of complex geometries, typical of shallow water basins. WWTM describes the hydrodynamic flow field including the flooding and drying processes using a statistical, physics-based approach (Defina, 2000). The wind-wave generation and propagation are computed by solving the equation of wave action conservation, parameterized using the zero-order moment of the wave action spectrum in the frequency domain. The spatial variability of the wind field is accounted by adopting the interpolation technique proposed by Brocchini et al. (1995). WWTM has been used to reproduce tide propagation, wind setup and the effect of the closure of the Lido inlet (i.e., the Treporti and San Nicolò canals, see Fig. 1) by reproducing the raising of the flap gates of the Mo.S.E. system. The computational mesh used in this study reproduces the Venice lagoon and a portion of the Adriatic Sea in front of the three inlets, for a total area of about 600 km². It consists of about 51,000 nodes and 97,000 triangular elements of side-length of about 100 m for tidal flats and 10 m at the three inlets, where the spatial gradients of the velocity are significant even for small tidal ranges. The elevation of the computational elements is assigned on the basis on the most recent (2012)-bathymetry of the Venice lagoon provided by the

Venice Water Authority. The Strickler bed roughness coefficient (Ks) has been calibrated (Carniello et al., 2005; 2011) ~~in order~~ to represent the energy dissipation over the different, morphologically representative, portions of the lagoon. It is worthwhile pointing out that the capability of the model to reproduce the tide propagation within the lagoon and the flow rates across the three inlets has been widely tested by comparing WWTM results to data records (e.g. Carniello et al., 2011; Mel et al., 2019b), showing absolute errors generally comparable to measurement precision (i.e., lower than 0.02 – 0.03 m, see Appendix A for the simulation of all the events that involved the raising of the Mo.S.E. barriers occurred from 3 October 2020 to 11 February 2021).

In the present work WWTM is forced by imposing the tidal signal at the three inlets (i.e., Diga Sud Lido, Diga Nord Malamocco and Diga Sud Chioggia). The spatial and temporal distribution of the wind field is reconstructed following the approach described in Carniello et al. (2012) and considering the wind climate gauged at the Laguna Nord, Malamocco Porto and Chioggia Porto (see Fig. 1). The wind shear stress at the water surface has been widely calibrated and tested against data collected during the most prominent storms, including three recent events that occurred when the Mo.S.E. system was operational (Mel et al., 2021b, ~~under review~~).

2.3.4 Simulation set-up

The effect of the PCL has been addressed on three different scenarios, namely scenario (I), (II) and (III). In the scenario (I), the simulations were designed to reproduce tidal circulation with no wind, and the only forcing was a synthetic sinusoidal tide imposed at the three inlets. Different tidal ranges (from 0.1 m to 1.4 m) and different periods (from 4 h to 8 h) were investigated. All the forcing tides are characterized by a SL peak of 1.20 m, given that the PCL would be effective for peaks from 1.10 m (the safeguard threshold of PS and Burano) to 1.30 m (the safeguard threshold of Chioggia, which would marginally benefit from the closure of the Lido inlet). In the scenario (II), constant velocities (from 5 m/s to 20 m/s) of north-easterly wind (i.e., Bora, incoming direction of 45°N) and south-easterly wind (i.e., Sirocco, incoming direction of 165°N) have been superimposed to the same tidal forcings of scenario (I). The scenario (III) comprises all the 42 events ~~(n° 42)~~ occurred in the period 2019 – 2020 with gauged SL peak ≥ 1.10 m at PS, including some events when the Mo.S.E. system was operational (in such cases the safeguard threshold has been referred to the SL gauged at CNR platform). In this scenario, the model has been forced with the SLs gauged at the three inlets and the wind measured at Laguna Nord, Malamocco Porto and Chioggia Porto (Fig. 1). These events are characterized by different tidal ranges (from 0.3 to 1.5 m), different periods (from 3 to 8.5 hours, plus two events that involved two tidal cycles), different meteorological conditions (i.e., wind speed and direction), and different initial conditions (i.e., SL at the troughs and tidal range of the previous tidal cycle).

For all the three scenarios, and for each event, the tidal dynamics ~~has~~ have been reproduced through four different runs, namely:

- run (a), without any operation at the Mo.S.E. barriers (unregulated lagoon);

- run (b), by closing the Treporti and San Nicolò canals at the beginning of the flood tide, i.e., when the flow rate through the Lido inlet computed in run (a) is null;
- run (c), as run (b), but including the intragate infiltration through the Treporti and San Nicolò barriers estimated by using a classical formulation for orifice flows as proposed by Mel et al. (2021b, under review), on the basis of the SL difference computed in run (b) between control section 1 and 2 (Treporti) and between control section 1 and 3 (San Nicolò) (Fig. 1);
- run (d), as run (c), but opening the Treporti and San Nicolò canals when the SL difference computed in run (c) between control section 1 and 2 (Treporti) and between control section 1 and 3 (San Nicolò) is null.

The effect of the PCL has been addressed by comparing the SLs peaks computed at PS, Burano, and Chioggia between run (d) and (a).

3 Results and discussion

3.1 Scenario (I): reduction of the sea level peak

Figure 3 shows the reduction of the SL peak (i.e., the SL peak difference between run (a) and (d), hereinafter named as ΔH) due to the PCL under the scenario (I), i.e., a sinusoidal tide with no wind. Panels (a), (b) and (c) show the ΔH at PS, Burano, and Chioggia, for a forcing tide characterized by a period of 6 hours and different tidal ranges. A first, important, result, is the linearity of the relationship between tidal range and ΔH at the three gauges. Notably, a linear relationship is achieved only if the tidal range is referred to the tide signal imposed at the inlets (solid bullets, hereinafter named as seaward tidal range, H_{SW}) and not at the specific gauge (opaque bullets, hereinafter named as local tidal range). This can be explained by effect of tide propagation on the local tidal range, which can be significantly altered far from the inlets. The benefit of the PCL in terms on ΔH is significant:





$$\Delta H_{PS} = -0.20 \cdot H_{SW} \quad (1)$$

$$\Delta H_{BURANO} = -0.27 \cdot H_{SW} \quad (2)$$

$$\Delta H_{CHIOGGIA} = -0.04 \cdot H_{SW} \quad (3)$$

For a tidal range of 0.6 m, the PCL would reduce the SL peak of about 0.12 m at PS, 0.16 m at Burano and 0.02 m at Chioggia.

For tidal periods between 4 and 8 hours, results are not significantly affected by the tidal period, as shown in Fig. 3d for the period range of 4–8 hours. Drawing a linear relationship is fundamental for investigating the effectiveness of the PCL on a long dataset, as the ΔH can be estimated through the SL difference gauged between the SL peak and the previous trough. As a note, the contribution of the flow rate discharged into the lagoon due to leakage (run (c)) through the gates on the relationships (1), (2) and (3), is between 5 and 10% of the total ΔH , independently of the tidal range (not shown).











Figure 3: Synthetic sinusoidal tide; no wind condition (scenario (I)). Reduction of the sea level peak (ΔH) due to a partial use of the Mo.S.E. system (Lido inlet closed, PCL). (a-c) tidal **semi**-period of 6 hours. (a) Punta della Salute; (b) Burano; (c) Chioggia. Solid bullets refer to the seaward tidal range, opaque bullets to the tidal range computed at the specific gauge. (d) effect of the tide period on the slope of the linear regression (range 4 – 8 hours). Dashed lines refer to the relationships computed for a tidal **semi**-period of 6 hours at PS (blue, panel (a)), Burano (red, panel (b)) and Chioggia (green, panel (c)).

3.2 Scenario (II): the wind setup constraint

Mel et al. 2019a showed that the wind setup during the closure of the lagoon is significantly larger if compared to the unregulated condition. As the full use of the Mo.S.E. system could flood Chioggia during intense north-easterly winds (Mel et al., 2019a; Mel et al., 2021a), it is crucial to investigate the specific effect of the PCL on wind setup. Figure 4 compares the relationship between tidal range and ΔH if Bora (45 °N) and Sirocco (165 °N) winds are superimposed to a tide of 6 hours period. Panels (a), (b) and (c) illustrate the results at PS, Burano, and Chioggia for a wind speed of 15 m/s. The relationship is still linear (black bullets and solid lines). If compared to scenario (I) (dashed lines), the slope of the regression does not change, but the intercept is not null. In case of wind, the PCL would produce an additional variation of the SL peak with respect to scenario (I) (namely, ΔH_{WIND} , i.e., the distance between solid and dashed lines). ΔH_{WIND} can be positive or negative and

depends only on the characteristics of the wind (speed and direction) and not on the tidal range. Specifically, in case of Sirocco the PCL could be detrimental, producing SL peaks even higher with respect to the unregulated condition (up to 0.1 m, Fig. 4a and 4b). Conversely, Bora, which is the prevailing wind in the Venice lagoon, would reduce the SL peak at all the three gauges if the PCL is implemented. This result is very important, as the PCL does not enhance the wind setup at Chioggia, as occurs when all the three inlets are closed. Notably, in case of Bora, the PCL enhances the SL gradient between PS at Chioggia, but only by reducing the SL at PS and not by increasing the SL at Chioggia. Panel (d) shows the relationship between wind speed and ΔH_{WIND} for Bora and Sirocco, confirming an additional reduction of the SLs in the whole lagoon in case of north-easterly winds and a SL increase in case of south-easterly winds. This ~~phenomenon~~result can be explained by the hydrodynamic effect of a wind blowing over Venice lagoon on the flow rate across the three inlets (see Zecchetto et al., 1997; Mel et al., 2019a). In an unregulated lagoon, when Bora wind is blowing, SL increases in the southern part of the lagoon and decreases in its northern part. Therefore, an additional water volume flows into the lagoon through the northern Lido inlet and out of the lagoon through the southern Chioggia inlet. Conversely, Sirocco wind produces an additional volume entering the lagoon through the Chioggia inlet and an additional volume discharged toward the sea through the Lido inlet. In both the cases, the additional water volume flowing through the Lido inlet will disappear during the PCL. Therefore, in case of Sirocco, the net volume entering the lagoon will increase, enhancing the SLs in the lagoon. Conversely, Bora wind reduces the total water volume entering the lagoon, decreasing the SLs accordingly (Fig. 4d).





275 **Figure 4:** Synthetic sinusoidal tide, tidal semi-period of 6 hours, PCL. ΔH variation in case of wind ($\Delta HWIND$). (a) Punta della Salute; (b) Burano; (c) Chioggia. Dashed lines refer to the relationship obtained with no wind (scenario I, Fig. 3); solid thin lines to scenario (II), with Sirocco and Bora wind of 15 m/s. White bullets refer to the simulations performed with no tide. (d) ΔH variation with respect to the no wind condition ($\Delta HWIND$) computed at PS (blue lines), Burano (red) and Chioggia (green), ranging the speeds of Bora and Sirocco from 0 to 20 m/s.


280 **3.3 Scenario (III): 2019 – 2020 dataset**

The three linear relationships (1), (2) and (3) provided in Section 3.1 for estimating the ΔH referred to the seaward tidal range were verified considering data from the 42 storm events which occurred in the years 2019 and 2020 (Fig. 5). Results refer to the gauges of PS (blue), Burano (red) and Chioggia (green). Figure 5a and 5b compare the ΔH computed by the hydrodynamic model forced by the observed tidal and meteorological data (bullets) to the ΔH estimated by using the Eq. (1), (2) and (3) (dashed lines, scenario I). The bullets nicely match the dashed lines confirming the robustness of the linear regression. The mean error considering all the events is 2 cm for PS, 4 cm for Burano and 1 cm for Chioggia. The reliability of the linear regression can be improved if some events are excluded from the comparison. Specifically, the most important discrepancies affect (ai) events where a significant Bora (B) or Sirocco (S) wind blew over the lagoon ($U \text{ wind} > 10 \text{ m/s}$) at the SL peak

ha formattato: Non Apice / Pedice

(black bullets); (ii) events that involved two tidal cycles due to a prominent seiche wave in the Adriatic Sea, failing the hypothesis of sinusoidal tide (white bullets, see the example of 25 December 2019 in Fig. 5c); (iii) the exceptional storm that occurred on 12 November 2019 (rhombus, see Cavaleri et al., 2020 for more details about the singularity of such event). Remarkably, Bora (B) and Sirocco (S) respectively enhance and reduce the ΔH , as demonstrated in Section 3.2 (Fig. 4d). Figure 5c illustrates an example of the effect of the PCL on the SL peak at PS within the period 21-25 December 2019 (these events are labelled in Fig. 5a as 21 – 25). The five events falling within that period are characterized by different tidal and meteorological forcings. Specifically, on 21 December Sirocco reduces the ΔH by introducing a negativepositive $\Delta HWIND$, i.e., the discrepancy between the purple line, which represents the SL computed by the model, and the grey horizontal line, the SL computed at the peak by using Eq. (1). On 25 December, the tide signal was significantly altered by a longitudinal seiche affecting the Adriatic Sea, showing an inflection (highlighted by the orange circle in Fig. 5c) which reduces the benefit of the PCL. Notably, the events which occurred on 23 and 24 December, characterized by the highest tidal ranges (≥ 1.30 m), nicely fit the linear regression (Fig. 5a).


Results confirm the reliability of equations (1), (2) and (3), with particular reference to events not involving more than one tide cycle (which are very rare) and not affected by strong winds. Such equations can be conveniently applied to any surge based on the tidal and wind dataset (see Section 3.5).



305 **Figure 5:** Dataset 2019 – 2020. SL peaks ≥ 1.10 m at PS (or at CNR platform during the tests performed at the Mo.S.E. barriers since
 310 October 2020). Relationship between tidal range and ΔH at (a) Punta della Salute (blue); (b) Burano (red) and Chioggia (green). Black bullets
 indicate the events characterized by strong Bora (B) or Sirocco (S); white bullets the events where two tidal cycles were merged due to a
 prominent seiche wave in the Adriatic Sea; rhombus the event of 12 November 2019. (c) timeseries 21 – 25 December 2019 at PS. SL
 observed (black line) and computed by means of the hydrodynamical model (PCL, purple; unregulated condition, blue). SLs computed at
 the peak by Eq. (1) are represented by the grey horizontal lines; mean **gauged** seaward SL by the grey dashed line.

3.4 Flow rate through the inlets

The impact of the PCL on the lagoon hydrodynamics is significant (Fig. 6). The PCL **significantly** affects the velocity field during the flood tide and vanishes the Lido sub-basin, causing an enlargement of the Malamocco sub-basin and a slightly different position of the Chioggia sub-basin (Fig. 6, black solid lines).




315

Figure 6: Sinusoidal tide, no wind (scenario I). Tidal range 0.8 m, tidal period 6 h. The two panels represent the 2-D velocity field and watersheds location (solid black lines) during at the 5th hours of the seaward flood tide. (a) unregulated lagoon (b) PCL.

320

The effects of the PCL on the Venice lagoon hydrodynamics have been addressed in terms of alteration of flow rates through the three inlets. For each inlet and tidal range belonging to the scenario (I), the incoming fluxes during the flood tide have been compared to the conditions of an unregulated lagoon, in accordance with the method described in Section 2.3. Figure 7 shows the results for a tidal period of 6 hours. The comparison of the average and maximum flux evidences that the PCL enhances the flow rate through the Malamocco and Chioggia inlets for all the tidal ranges (Fig. 7a). The relationship is linear, with regression slopes of 1.14 (Malamocco inlet, yellow) and 1.02 (Chioggia inlet, green), for the maximum flow rate. Similar values (not shown) are obtained for the average flow rate. A wider difference is observed on the water volumes flowing into the lagoon (Fig. 7b), as the PCL increases the duration of the flood tide due to lower internal SLs. Specifically, a volume increase of 22% is evidenced through the Malamocco inlet and 8% through the Chioggia inlet. Conversely, the total volume flowing into the lagoon through the three inlets is reduced by 21% (blue squares).

325



330 **Figure 7:** Sinusoidal tide, no wind (scenario I). Tidal range from 0.1 to 1.4 m, period of 6 hours. Comparison of maximum flow rate (a) and water volume entering the lagoon (b) at the three inlets during the flood tide (x-axes unregulated lagoon, y-axes PCL).

These results indicate a modest effect of the PCL on the flux through the Malamocco and Chioggia inlets (i.e., the same difference could be achieved by increasing of 0.1 m the tidal range in an unregulated lagoon).

335 3.5 Operating the Lido inlet under climate change

The linear relationship described in Section 3.1 allows to estimate the number of PCL capable to limit the SL below the threshold at PS, Burano, and Chioggia. The hindcast dataset of tidal and meteorological observations of the period 2000 – 2019 has been analysed. For investigating possible future scenarios, SLs were increased by adding different values of RSLR up to + 0.5 m (i.e., slightly exceeding the projected RSLR in northern Adriatic Sea for the year 2100 under the IPCC RCP 2.6 scenario, see Zanchettin et al., 2020,2021) at steps of + 0.1 m, assuming that the mean SL does not significantly affect tidal range and surge characteristics, as shown by several studies (Bondesan et al., 1995; Umgieser and Matticchio, 2006; Mel et al., 2013). Figure 8 shows the annual number of events over threshold. Specifically, orange bars represent the unregulated condition, blue bars the residual events over threshold by implementing the PCL to all the events (unfiltered analysis). Nevertheless, strong winds and events that involve multiple tidal cycles can reduce the benefit of the PCL, as shown in 345 ~~Section~~Sections 3.2 and 3.3. Accordingly, in a second analysis some events have been excluded from the potential to implement the PCL (filtered analysis, green bars). Specifically, the filtered analysis omitted: (i) the events of period greater than 8 hours, filtering possible flood tides that involve two or more tidal cycles (see Section 3.3); (ii) the events showing significant southern winds at the SL peak (i.e., wind speed ≥ 10 m/s and wind direction in the range $150^\circ - 210^\circ$ at the Laguna Nord gauge), filtering possible lower ΔH s due to the wind setup (i.e. ~~negative~~positive ΔH WIND, see Section 3.2); (iii) the 350 events showing SL peaks ≥ 1.30 m at Diga Sud Chioggia, filtering possible water levels over threshold at Chioggia, as the small benefit of the PCL on Chioggia SLs had been neglected. Green bars represent the residual annual number of events over threshold if the PCL is implemented only in the events which do not show the abovementioned characteristics (i) – (iii) (filtered analysis). The filtered analysis provides a residual number of events over threshold ranging from 33% to 38% of the total events for a RSLR up to + 0.40 m, and of 50% for a RSLR of + 0.50 m. These residual events should be faced by closing all 355 the three inlets (full use of the Mo.S.E. system). Though the filters (i) – (iii) are very precautionary, a modest discrepancy between filtered and unfiltered analysis is evidenced.

Although the uncertainties regarding climate change are still large, this study confirms the efficiency of the PCL as adaption strategy to extend the lifetime of the Mo.S.E. system. Results (Fig. 8) show that the PCL would ~~have the same effect of increasing by 10–15 cm the safeguard threshold, keeping keep~~ the frequency of the full use of the Mo.S.E. to an acceptable number for few decades, gaining precious time to verify the ongoing evolution of the climatic scenarios, narrowing the actual 360 large uncertainty ranges.




Figure 8: 2000-2019 dataset with a RSLR ranging from +0.0 m (present condition) to +0.5 m. Comparison of the annual number of closures to the increasing RSLR. Orange bars illustrate the total number of SL peaks over threshold; green bars the residual events over threshold by implementing the PCL under the filtered scenario; blue bars the residual events if the PCL will be implemented during all the SL peaks.

365

This analysis focuses only on flood protection. As the PCL would significantly modify the lagoon hydrodynamics (Fig. 6), the long-term morphological and ecological consequences of such an operation strategy, which are beyond the scope of this work, surely deserve further investigations. The optimal adaptation and management strategy need to be carefully investigated and identified with the aim to balance flood protection with economic issues and the safeguarding of the lagoon ecosystem.

370 4 Conclusions

Structural measures, as well as high level of technical knowledge, are not necessarily the panacea for the long-term safety of the coast. Adaptation to climate change requires an effective and integrated management of coastal areas, with particular reference to the Venice lagoon, a World Heritage site enhanceingincreasingly threatened by flooding and erosion processes. Though the Mo.S.E. system has the potential to reduce the vulnerability of the Venice lagoon, serious questions arise whether it is beneficial to the morphology, the ecosystem, and to the wide range of uses of the lagoon. It is of paramount importance to integrate the management of the barriers into a strategic context that addresses the social, economic, and environmental issues raised in any coastal area. Accordingly, some measures should be undertaken to minimize the impacts of the operation of the Mo.S.E. system on water renewal, port activities and fishing industry. In order to reduce the number of simultaneous closures of the three inlets during flood events characterized by non-extreme SLs, the Malamocco and Chioggia inlets can be left open ensuring the flow of part of the water and the transit of vessels. Such solution requires to adapt the current management criteria of the barriers. Toward this goal, the present study shows the results of a hydrodynamic investigation in

375

380

which the partial use of the Mo.S.E. has been simulated by closing the only Lido inlet (PCL). Simulations were carried out considering both synthetic and realistic tide and wind scenarios. Results show that:

- a linear relationship was obtained between the tidal range of the seaward tide signal and the reduction of the sea level (SL) peak in the lagoon (ΔH). Specifically, the reduction has been estimated in 20% at Punta della Salute (Venice), 27% at Burano and 4% at Chioggia; the linear contribute (5-10%) of intragate infiltration has been accounted for. Tidal semi-period does not significantly affect the results;
- north-easterly winds would produce beneficial effects within all the lagoon, reducing the SL peaks. Conversely, in case of south-easterly winds, the Partial Closure of the Lagoon involving the Lido inlet only (PCL) could produce higher/increase the SLs respect to an unregulated lagoon;
- events that involve multiple tidal cycles often show inflections of the tide signal, reducing the effectiveness of the PLC;
- two third of the flood events can be effectively faced by the PCL under relative sea level rise scenarios up to + 0.4 m.

Besides this attempt to study some major hydrodynamic aspects related to the partial use of the Mo.S.E. barriers, many open issues remain to be analysed, as the possible long-term effects of such operation strategy on the bio-morphodynamic evolution of the Venice lagoon. A thorough cost-benefit analysis should be pursued to identify the optimal Mo.S.E. management strategy supporting the resilience of Venice and its lagoon to high tides. The Venice lagoon test case points out the importance of combining non-structural and structural measures to counteract flood risk in coastal areas, bearing in mind the need of investigating the long-term effects related to the strategies adopted to face present priorities.

400 **Acknowledgments.** Luca Carniello and Daniele Pietro Viero are gratefully acknowledged for fruitful discussions.

References

- Aerts, J. C. J. H., Botzen, W. J. W., Emanuel, K., Lin, N., and Moel, H.: De Evaluating Flood Resilience Strategies for Coastal Megacities. Sci. (80-.) 344, 473–475, 2014.
- 405 Alfieri, L., Burek, P., Feyen, L., and Forzieri G.: Global warming increases the frequency of river floods in Europe, Hydrol. Earth Syst. Sci., 19, 2247–2260, doi:10.5194/hess-19-2247-2015, 2015.
- American Geophysical Union: (AGU): Scientists Debate Wisdom of Plan To Save Venice From Flooding, ScienceDaily, 9 May 2002. www.sciencedaily.com/releases/2002/05/020509072937.htm.

- 410 Androulidakis, Y. S., Kombiadou, K. D., Makris, C. V., Baltikas, V. N., and Krestenitis, Y. N.: Storm surges in the
Mediterranean Sea: Variability and trends under future climatic conditions, *Dyn. Atmos. Oceans*, 71, 56–82, doi:
10.1016/j.dynatmoce.2015.06.001, 2015.
- ~~Battistin, D., and Canestrelli, P.: 1872–2004 La serie storica delle maree a Venezia, Internal report of Comune di Venezia –
Istituzione – CPSM. — <http://93.62.201.235/maree/DOCUMENTI/> — La serie storica delle maree a Venezia 1872–
2004_web_ridotto.pdf, 2006.~~
- 415 ~~Battjes, J. A., and Gerritsen, H.: Coastal modelling for flood defence, *Phil. Trans. R. Soc. Lond. A* 360, 1461–1475, 2002.~~
- Bondesan, M., Castiglioni, G., Elmi, C., Gabbianelli, G., Marocco, R., Pirazzoli, P. A., Tomasin, A.: Coastal areas at risk from
storm surges and sea-level rise in northeastern Italy. *Journal of Coastal Research* 11 (4), p.1354–1379, 1995.
- Brambati, A., Carbognin, L., Quaia, T., Teatini, P., and Tosi, L.: The Lagoon of Venice: Geological setting, evolution and land
subsidence. *Episodes* 26(3), 264–268. <https://doi.org/10.18814/epiugs/2003/v26i3/020>, 2003.
- 420 Brocchini, M., Wurtele, M., Umgiesser, G., and Zecchetto, S.: Calculation of a mass consistent two-dimensional wind-field
with divergence control. *J. Appl. Meteorol.* 34 (11), 2543–2555, 1995.
- Brotto, M. T., and Gentilomo, M.: The Venice Lagoon Project. The Barriers at the Lagoon Inlets for Controlling High Tides*,
in *Bulletin AIPCNIANC*, no. 98, 1998.
- Brown, K., Few, R., Tompkins, E., Tsimplis, M., and Sortti, T.: Responding to climate change: Inclusive and integrated coastal
analysis, Tyndall Centre Technical Report 24, Tyndall Centre for Climate Change Research, Norwich, UK, 2005.
- 425 Capobianco, M., De Vriend, H. J., Nicholls, R. J., and Stive, M. J. F.: Coastal Area Impact and Vulnerability Assessment: The
Point of View of a Morphodynamic Modeller, *J. Coast. Res.*, 15, 701–716, 1999.
- Carbognin, L., Teatini, P., and Tosi, L.: Eustacy and land subsidence in the Venice Lagoon at the beginning of the new
millennium. *J Marine Systems* 51(1–4 SPEC. ISS.):345–35, 2004.
- 430 Carniello, L., Defina, A., Fagherazzi, S., and D'Alpaos, L.: A combined Wind Wave-Tidal Model for the Venice lagoon, Italy,
J. Geophys. Res., 110, F04007, doi:10.1029/2004JF000232, 2005.
- Carniello, L., Defina, A., and D'Alpaos, L.: Morphological evolution of the Venice lagoon: Evidence from the past and trend
for the future, *J. Geophys. Res.*, 114, F04002, doi:10.1029/2008JF001157, 2009.
- 435 Carniello, L., D'Alpaos, A., and Defina, A.: Modeling wind-waves and tidal flows in shallow microtidal basins, *Estuarine
Coastal Shelf Sci.*, 92, 263–276, doi: 10.1016/j.ecss.2011.01.001, 2011.
- Carniello, L., Defina, A., and D'Alpaos, L.: Modeling sand-mud transport induced by tidal currents and wind waves in shallow
microtidal basins: Application to the Venice Lagoon (Italy). *Estuar. Coast. Shelf Sci.* 102–103, 105–115
<https://doi.org/10.1016/j.ecss.2012.03.016>, 2012.

ha formattato: Inglese (Stati Uniti)

- 440 Cavaleri, L., Bajo, M., Barbariolo, F., Bastianini, M., Benetazzo, A., Bertotti, L., Chiggiato, J., Ferrarin, C., Trincardi, F. and Umgiesser, G.: The 2019 Flooding of Venice and its implications for future predictions, *Oceanography*, 33(1), pp. 42-49, 2020.
- Cavallaro, L., Iuppa, C., Foti, E.: Effect of Partial Use of Venice Flood Barriers. *J. Mar. Sci. Eng.* 5(4), 58. <https://doi.org/10.3390/jmse5040058>, 2017.
- 445 Ciavola, P., Ferreira, O., Haerens, P., Van Koningsveld, M., Armaroli, C.: Storm impacts along European coastlines, Part 2: lessons learned from the MICORE project. *Environ. Sci. Pol.* 14, 924–933. <http://dx.doi.org/10.1016/j.envsci.2011.05.009>, 2011.
- Chiabai, A., and Nunes, P.A.L.D.: *Valutazione economica degli impatti del cambiamento climatico nell'Alto Adriatico*, in Carraro C. (a cura di), *Impatti dei cambiamenti climatici e strategie di adattamento in Italia. Una valutazione economica*, Il Mulino, Bologna, 2008.
- 450 Costa, P.: Venezia. Economia e analisi urbana, Etas., 1993.
- Cutter, S. L., and Gall, M.: Sendai targets at risk, *Nat. Clim. Change*, 5(8), 707–709, doi: 10.1038/nclimate2718, 2015.
- D'Alpaos, L.: *Conoscere il comportamento idrodinamico della laguna del passato per progettare la laguna del futuro*, Atti Istituto Veneto di Scienze, Lettere e Arti, Venice, Classe di scienze fisiche, matematiche e naturali, Tomo CLXII (2003-2004), 2003.
- 455 D'Alpaos L.: Fatti e misfatti di idraulica lagunare. La laguna di Venezia dalla diversione dei fiumi alle nuove opere delle bocche di porto, Istituto Veneto di Scienze, Lettere e Arti, Venice, ISBN: 9788895996219, 2010.
- D'Alpaos, L., and Defina A.: Mathematical modeling of tidal hydrodynamics in shallow lagoons: A review of open issues and applications to the Venice lagoon, *Comput. and Geosci.* 33, 476-496. <https://doi.org/10.1016/j.cageo.2006.07.009>, 2007.
- 460 Dawson, R. J., Ball, T., Werritty, J., Werritty, A., Hall, J.W., and Roche, N.: Assessing the effectiveness of non-structural flood management measures in the Thames estuary under conditions of socio-economic and environmental change, *Glob. Environ. Change*, 21, 628–646, 2011.
- De Alencar, N. M. P., Le Tissier, M., Paterson, S.K., and Newton, A.: Circles of Coastal Sustainability: A Framework for Coastal Management. *Sustainability*, 12, 4886. <https://doi.org/10.3390/su12124886>, 2020.
- Defina, A.: Two dimensional shallow flow equations for partially dry areas, *Water Resour. Res.*, 36(11), 3251–3264, 2000.
- 465 De Zolt S., Lionello P., Nuhu A., and Tomasin A.: The disastrous storm of 4 November 1966 on Italy, *Nat. Hazards Earth Syst. Sci.*, 6, 861–879, Doi:10.5194/nhess-6-861-2006, 2006.
- Diaz, D. B.: Estimating global damages from sea level rise with the Coastal Impact and Adaptation Model (CIAM), *Climatic Change*, 137, 143–156, <https://doi.org/10.1007/s10584-016-1675-4>, 2016.

ha formattato: Inglese (Stati Uniti)

ha formattato: Inglese (Stati Uniti)

ha formattato: Inglese (Regno Unito)

- 470 Diez, J. J., Paz, R., Esteban, M. D., López-Gutiérrez, J. S., and Negro, V.: Urban Coastal Flooding and Climate Change, *Journal of Coastal Research, SI 64 (Proceedings of the 11th International Coastal Symposium)*, 205–209. Szczecin, Poland, ISSN 0749-0208, 2011.
- Drejza S., Pascal B., Guillaume M., and Friesinger S.: Quantifying road vulnerability to coastal hazards: Development of a synthetic index, *Ocean & Coastal Management*. Doi: 10.1016/j.ocecoaman.2019.104894, 2019.
- 475 EC. 2009. White paper - Adapting to climate change: towards a European framework for action. <http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CELEX:52009DC0147:EN:NOT>.
- Elko, N., and Briggs T. R.: National coastal management challenges and needs, *Shore & Beach*, 88, 4, 2020.
- Eprim, Y.: Venice mobile barriers project: barrier caissons construction details. In: Fletcher, C.A., Spencer, T. (eds) *Flooding and environmental challenges for Venice and its lagoon: state of knowledge*, Cambridge University Press, Cambridge, 257–265, 2005.
- 480 Ferrarin, C., Ghezzi, M., Umgiesser, G., Tagliapietra, D., Camatti, E., Zaggia, L., and Sarretta, A.: Assessing hydrological effects of human interventions on coastal systems: numerical applications to the Venice Lagoon, *Hydrol. Earth Syst. Sci.*, 17, 1733–1748, <https://doi.org/10.5194/hess-17-1733-2013>, 2013.
- Ferrarin, C., Bajo, M., Barbariol, F., Bastianini, M., Benetazzo, A., Cavaleri, L., Chiggiato, J., Davolio, S., Lionello, P., Orlie, M., and Umgiesser, G.: Local and large-scale controls of the exceptional Venice floods of November 2019, *EGU General Assembly 2020, Online, 4–8 May 2020, EGU2020-4562*, <https://doi.org/10.5194/egusphere-egu2020-4562>, 2020.
- 485 Ferla, M., Cordella, M., Michielli, L., and Rusconi, A.: Long term variations on sea level and tidal regime in the lagoon of Venice, *Estuarine, Coastal and Shelf Science* 75, 214–222, 2007.
- Few, R., Brown, K., and Tompkins, E.: Climate change and coastal management decisions: Insights from Christchurch Bay, UK. *Coastal Management* 35 (2): 255–270, 2007.
- 490 Finotello, A., Lanzoni, S., Ghinassi, M., Marani, M., Rinaldo, A., and D'Alpaos, A.: Migration rates of tidal meanders, *Proceedings of the National Academy of Sciences* Feb 2018, 115 (7) 1463–1468; DOI: 10.1073/pnas.1711330115, 2018.
- Gacic, M., and Solidoro, C.: Lagoon of Venice - circulation, water exchange and ecosystem functioning -Introduction. *J. Mar. Syst.* 51 (1–4), 1–3, 2004.
- Gentilomo, M., and Cecconi, G.: Flood protection system designed for Venice. *Hydropower & Dams* 2 (IV): 46–52, 1997.
- 495 Haigh, I., Nicholls, R., and Wells, N.: Rising sea levels in the English Channel 1900 to 2100, *Proc. ICE Maritime Engineer.*, 164, 81–92, 21, 2011.
- Hinkel, J., Lincke, D., Vafeidis, A. T., Perrette, M., Nicholls, R. J., Tol, R. S. J., Marzeion, B., Fettweis, X., Ionescu, C., and Levermann, A.: Coastal flood damage and adaptation costs under 21st century sea-level rise, *P. Natl. Acad. Sci. USA*, 111, 3292–3297, <https://doi.org/10.1073/pnas.1222469111>, 2014.

- 500 Indirli, M., Knezic, S., Borg, R. P., Kaluarachchi, Y., Rangelov, B., Romagnoli, F., Rochas, C.: The ANDROID case study; Venice and its territory: a general overview. Proc. 4th International Conference on Building Resilience, 8-11 September 2014, Salford, United Kingdom, 2014.
- 505 [IPCC, 2013. Annex II: Climate System Scenario Tables, in: Prather, M., Flato, G., Friedlingstein, P., Jones, C., Lamarque, J. F., Liao, H., Rasch, P. \(eds.\), Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA, 2013.](#)
- Jongman, B., Hochrainer-Stigler, S., Feyen, L., Aerts, J. C. J. H., Mechler, R., Botzen, W. J. W., Bouwer, L. M., Pflug, G., Rojas, R., and Ward, P. J.: Increasing stress on disaster-risk finance due to large floods, *Nat. Clim. Change* 4, 264–268, 2014.
- 510 Jongman, B.: Effective adaptation to rising flood risk. *Nat. Commun.* 9, 1986. <https://doi.org/10.1038/s41467-018-04396-1>, 2018.
- Klein, R., Nicholls, R., Ragoonaden, S., Capobianco, M., Aston, J., and Buckley, E.: Technological options for adaptation to climate change in coastal zones. *Journal of coastal Research*, 17: 531–543, 2001.
- Kundzewicz, Z. W.: Non-structural flood protection and sustainability. *Water International* 27 (1): 3–13, 2002.
- 515 [Kundzewicz, Z. W., Kanae, S., Seneviratne, S. I., Handmer, J., Nicholls, N., Peduzzi, P., Meehler, R., Bouwer, L. M., Arnell, N., Maeh, K., Muir-Wood, R., Brakenridge, G. R., Kron, W., Benito, G., Honda, Y., Takahashi, K., and Sherstyukov, B.: Flood risk and climate change: global and regional perspectives. *Hydrol. Sci. J.* 59, 1–28. <https://doi.org/10.1080/02626667.2013.857411>, 2014.](#)
- [Lineke, D., and Hinkel, J.: Economically robust protection against 21st century sea level rise, *Global Environ. Chang.*, 51, 67–73, <https://doi.org/10.1016/j.GLOENVCHA.2018.05.003>, 2018.](#)
- 520 Lionello, P.: The climate of the Venetian and North Adriatic region: variability, trends and future change, *Phys Chem Earth* 40–41:1–8, 2012.
- Lionello, P., Cavaleri, L., Nissen, K. M., Pino, C., Raicich, F., and Ulbrich, U.: Severe marine storms in the Northern Adriatic: characteristics and trends, *Phys Chem Earth* 40–41:93–105. doi: 10.1016/j.pce.2010.10.002, 2012.
- 525 Lionello, P., Barriopedro, D., Ferrarin, C., Nicholls, R. J., Orlic, M., Raicich, F., Reale, M., Umgiesser, G., Vousdoukas, M., and Zanchettin, D.: Extremes floods of Venice: characteristics, dynamics, past and future evolution, *Nat. Hazards Earth Syst. Sci. Discuss. [preprint]*, 21, 2705–2731, <https://doi.org/10.5194/nhess-2020-359>, in review 21-2705-202, 2021.
- [Liquete, C., Zulian, G., Delgado, I., Stips, A., and Maes, J.: Assessment of coastal protection as an ecosystem service in Europe, *Ecol. Indic.*, 30, 205–217, 2013.](#)
- 530 Maiolo, M., Mel, R. A., and Sinopoli, S.: A Stepwise Approach to Beach Restoration at Calabaia Beach, *Water*, 12, 2677; doi:10.3390/w12102677, 2020.

- Marcos, M., Chust, G., Jorda, G., and Caballero, A.: Effect of sea level extremes on the western Basque coast during the 21st century, *Clim. Res.*, 51(3), 237–248, doi:10.3354/cr01069, 2012.
- Mariotti, G., Fagherazzi, S., Wiberg, P., McGlathery, K., Carniello, L., and Defina, A.: Influence of storm surges and sea level on shallow tidal basin erosive processes. *J. Geophys. Res. Oceans* 115, C11012. <https://doi.org/10.1029/2009JC005892>, 2010.
- ~~Martini, P., Carniello, L., and Avanzi, C.: Two dimensional modelling of flood flows and suspended sediment transport: the case of the Brenta River, Veneto (Italy), *Nat. Hazards Earth Syst. Sci.* 4, 165–181. <https://doi.org/10.5194/nhess-4-165-2004>, 2004.~~
- 540 Matias, A., Ferreira, O., Vila-Concejo, A., Garcia, T., and Dias J. A.: Classification of washover dynamics in barrier islands, *Geomorphology*, 97(3–4), 655–674, doi: 10.1016/j.geomorph.2007.09.010, 2008.
- ~~McCarthy, J., Canziani, O., Leary, N., Dokken, D., and White, K.: *Climate change 2001: impacts, adaptation, and vulnerability*, Cambridge: Cambridge University Press, 2001.~~
- ~~Meehler, R., Bouwer, L. M., Linnerooth-Bayer, J., Hochrainer-Stigler, S., Aerts, J. C. J. H., Surminski, S., and Williges, K.: Managing unnatural disaster risk from climate extremes, *Nat. Clim. Change*, 4(4), 235–237, doi:10.1038/nclimate213, 2014.~~
- 545 MedECC 2020 Summary for Policymakers. In: *Climate and Environmental Change in the Mediterranean Basin – Current Situation and Risks for the Future*. First Mediterranean Assessment Report [Cramer, W., Guiot, J., Marini, K. (eds.)] Union for the Mediterranean, Plan Bleu, UNEP/MAP, Marseille, France, 34pp.
- 550 Mel, R., Sterl, A., Lionello, P.: High resolution climate projection of storm surge at the Venetian coast. *Nat. Hazards Earth Syst. Sci.* 13, 1135–1142. <https://doi.org/10.5194/nhess-13-1135-2013>, 2013.
- Mel, R., and Lionello, P.: Verification of an ensemble prediction system for storm surge forecast in the Adriatic Sea, *Ocean Dynamics*, vol. 64, no. 12, pp. 1803–1814, 2014.
- Mel, R., Carniello, L., and D’Alpaos, L.: Addressing the effect of the Mo.S.E. barriers closure on wind setup within the Venice lagoon. *Estuar. Coast. Shelf Sci.* 225, 106249. <https://doi.org/10.1016/j.ecss.2019.106249>, 2019a.
- 555 Mel, R., Carniello, L., and D’Alpaos, L.: Dataset of wind setup in a regulated Venice lagoon. *Data Br.* 26, 104386. <https://doi.org/10.1016/j.dib.2019.104386>, 2019b.
- Mel, R., Carniello, L., and D’Alpaos, L.: How long the Mo.S.E. barriers will be effective in protecting all urban settlements within the Venice lagoon? The wind setup constraint. *Coastal engineering*, in press, doi: [10.1016/j.coastaleng.2021.103923](https://doi.org/10.1016/j.coastaleng.2021.103923), 103923, <https://doi.org/10.1016/j.coastaleng.2021.103923>, 2021a.
- 560 Mel, R., Carniello, L., Viero, D. P., Defina, A., and D’Alpaos, L.: The first operations of the Mo.S.E. system to prevent the flooding of Venice: insights on the hydrodynamics of a regulated lagoon. *Estuarine, Coastal and Shelf Sci.* (under review), Science, 261, 107547. <https://doi.org/10.1016/j.ecss.2021.107547>, 2021b.

- Melaku-Canu, D., Umgiesser, G., Solidoro, C.: Short-term simulations under winter conditions in the lagoon of Venice: a contribution to the environmental impact assessment of temporary closure of the inlets, *Ecological Modelling*, 138,1–3, 215-230, [https://doi.org/10.1016/S0304-3800\(00\)00403-8](https://doi.org/10.1016/S0304-3800(00)00403-8), 2001.
- Menéndez, M., and Woodworth, P.L.: Changes in extreme high-water levels based on a quasi-global tide-gauge data set. *J. Geophys. Res.*, 115, C10011, doi:10.1029/2009JC005997. 22, 2010.
- Molinaroli, E., Guerzoni, S., Sarretta, A., Masiol, M., and Pistolato, M.: Thirty-year changes (1970–2000) in bathymetry and sediment texture recorded in the lagoon of Venice sub-basins, Italy, *Marine Geology* 258, 115–125, 2009.
- Molinaroli, E., Guerzoni, S., and Suman, D.: Adaptations to Sea Level Rise: A Tale of Two Cities – Venice and Miami, *MarXiv*. doi:10.31230/osf.io/73a25, 2018.
- ~~Moser, S., Finzi Hart, J., Newton Mann, A., Sadrpour, N., and Grifman, P.: (Susanne Moser Research & Consulting and U.S. Geological Survey) Growing effort, growing challenge: Findings from the 2016 CA coastal adaptation needs assessment survey, California's Fourth Climate Change Assessment. Publication number: CCCA4 EXT 2018 009, 2018.~~
- Munaretto, S., Vellinga, P., and Tobi, H.: Flood Protection in Venice under Conditions of Sea-Level Rise: An Analysis of Institutional and Technical Measures, *Coastal Management*, 40:4, 355-380, 2012.
- Nunes P.A.L.D., Breil M., and Gambarelli G.: Economic Valuation of On Site Material Damages of High Water on Economic Activities based in the City of Venice: Results from a Dose-Response-Expert-Based Valuation Approach, *Feem WP*, Nota di Lavoro 53.05, 2005.
- OECD. *The Ocean Economy in 2030*; OECD Publishing: Paris, France, 2016.
- Oumeraci, H.: Review and analysis of failures of vertical breakwaters”, *Coastal Engineering*, 22, pp. 3-29, 1994.
- ~~Paprotny, D., Sebastian, A., Morales-Nápoles, O., and Jonkman, S. N.: Trends in flood losses in Europe over the past 150 years, *Nat. Commun.* 9. <https://doi.org/10.1038/s41467-018-04253-1>, 2018.~~
- Pivato M, Carniello L, Viero DP, Soranzo C, Defina A, Silvestri S.: Remote Sensing for Optimal Estimation of Water Temperature Dynamics in Shallow Tidal Environments. *Remote Sensing*; 12(1):51. <https://doi.org/10.3390/rs12010051>, 2020.
- ~~Pranzini, E., Wetzel, A., and Williams, A.: Aspects of coastal erosion and protection in Europe. *J. Coast. Conserv.*, 19, 445–459, 2015.~~
- Pycroft, J., Abrell, J., and Ciscar, J. C.: The Global Impacts of Extreme Sea-Level Rise: A Comprehensive Economic Assessment, *Environ. Resour. Econ.*, 64, 225–253, <https://doi.org/10.1007/s10640-014-9866-9>, 2016.
- Samiolo, R.: Commensuration and styles of reasoning: Venice, cost–benefit, and the defence of place. *Accounting, Organizations and Society*, 37, 6, 382-402, <https://doi.org/10.1016/j.aos.2012.04.001>, 2012.
- Sarretta A., Pillon, S., Molinaroli, E., Guerzoni, S., and Fontolan, G.: Sediment budget in the Lagoon of Venice, Italy. *Continental Shelf Research* 30, 934-949. DOI: 10.1016/j.csr.2009.07.002, 2010.

- Semedo, A., Weisse, R., Behrens, A., Sterl, A., Bengtsson, L., and Günther, H.: Projection of global wave climate change toward the end of the twenty-first century, *J. Clim.*, 26(21), 8269–8288, doi:10.1175/jcli-d-12-00658.1, 2013.
- Silvestri S., D'Alpaos, A., Nordio, G., and Carniello, L.: Anthropogenic modifications can significantly influence the local mean sea level and affect the survival of salt marshes in shallow tidal systems. *J. Geophys. Res. Earth Surf.* 123(5), 996–1012. <https://doi.org/10.1029/2017JF004503>, 2018.
- 600 Smit, B., and Wandel, J.: Adaptation, adaptive capacity and vulnerability. *Global Environmental Change* 16 (3): 282–292, 2006.
- Smith, J. B., and Lenhart, S. S.: Climate change adaptation policy options. *Climate Research* 6:193–201, 1996.
- Solidoro, C., Melaku Canu, D., Cucco, A., and Umgiesser, G.: A partition of the Venice Lagoon based on physical properties and analysis of general circulation, *Journal of Marine Systems*, Volume 51, Issues 1–4, 147-160, 605 <https://doi.org/10.1016/j.jmarsys.2004.05.010>, 2004.
- Tiggeloven, T., de Moel, H., Winsemius, H. C., Eilander, D., Erkens, G., Gebremedhin, E., Diaz Loaiza, A., Kuzma, S., Luo, T., Iceland, C., Bouwman, A., van Huijstee, J., Ligtoet, W., and Ward, P. J.: Global-scale benefit–cost analysis of coastal flood adaptation to different flood risk drivers using structural measures, *Nat. Hazards Earth Syst. Sci.*, 20, 1025–1044, 610 <https://doi.org/10.5194/nhess-20-1025-2020>, 2020.
- Trincardi, F., Barbanti, A., Bastianini, M., Benetazzo, A., Cavaleri, L., Chiggiato, J., Papa, A., Pomaro, A., Selavo, M., Tosi, L., Umgiesser, G.: The 1966 flooding of Venice: What time taught us for the future. *Oceanography* 2016, 29, 178–186. <https://doi.org/10.5670/oceanog.2016.87>, 2016.
- Tobey, J., Rubinoff, P., Robadue, D., Ricci, G., Volk, R., Furlow, J., and Anderson, G.: Practicing coastal adaptation to climate change: Lessons from integrated coastal management. *Coastal Management* 38:317-335, 2010.
- 615 Umgiesser, G., and Matticchio, B.: Simulating the mobile barrier (MOSE) operation in the Venice Lagoon, Italy: Global sea level rise and its implication for navigation. *Ocean Dyn.* 56, 320–332. <https://doi.org/10.1007/s10236-006-0071-4>, 2006.
- Umgiesser, G.: The impact of operating the mobile barriers in Venice (MOSE) under climate change. *Journal for Nature Conservation*, 54, 125783, <https://doi.org/10.1016/j.jnc.2019.125783>, 2020.
- 620 UNESCO: *Rapporto Su Venezia*. Milan: Mondadori, 1969.
- UNESCO: *From Global to Regional: Local Sea Level Rise Scenarios Focus on the Mediterranean Sea and the Adriatic Sea*. Workshop “The future of Venice and its lagoon”, Report 1, 15 pp. (<http://www.unesco.org/venice/thefutureofvenice>), 2011.
- Van Koningsveld, M. Mulder, J. P. M., Stive, M. J. F., van der Valk, L., and van der Weck, A. W.: Living with sea-level rise and climate change: A case study of the Netherlands, *J. Coast. Res.*, 24, 367–379, 2008.
- 625 Vergano, L., Umgiesser, G., and Nunes, P. A. L. D.: An economic assessment of the impacts of the MOSE barriers on Venice port activities. *Transportation Research Part D: Transport and Environment*, 15D (6), 343-349, 2010.

Viero, D.P., and Defina, A.: Water age, exposure time, and local flushing time in semi-enclosed, tidal basins with negligible freshwater inflow. *Journal of Marine Systems*, 156, 16-29, doi: 10.1016/j.jmarsys.2015.11.006, 2016.

630 ~~Vousdoukas, M. I., Mentaschi, L., Voukouvalas, E., Verlaan, M., and Feyen, L.: Extreme Sea levels on the rise along Europe's coasts, *Earth's Future* 5, 304–323, 2017.~~

Wadey, M. P., Nicholls, R. J., and Hutton, C.: Coastal Flooding in the Solent: An Integrated Analysis of Defences and Inundation, *Water*, 4, 430-459. <https://doi.org/10.3390/w4020430>, 2012.

635 Wahl, T., Jensen, J. Frank, T., and Haigh, I.: Improved estimates of mean sea level changes in the german bight over the last 166 years, *Ocean Dyn.*, 61, 701–715, 2011.

Wang, X. L., Feng, Y., and Swail, V. R.: Changes in global ocean wave heights as projected using multimodel CMIP5 simulations, *Geophys. Res. Lett.*, 41(3), 1026–1034, doi:10.1002/2013GL058650, 2014.

640 Ward, P. J., Jongman, B., Aerts, J. C. J. H., Bates, P. D., Botzen, W. J. W., Loaiza, A. D., Hallegatte, S., Kind, J. M., Kwadijk, J., Scussolini, P., and Winsemius, H. C.: A global framework for future costs and benefits of river-flood protection in urban areas, *Nat. Clim. Chang.* 17, 642-646, 2017.


~~Woth K., Weisse R., and Von Storch, H.: Climate change and North Sea storm surge extremes: an ensemble study of storm surge extremes expected in a changed climate projected by four different regional climate models, *Ocean Dynam.*, 56: 3–15. Doi: 10.1007/s10236-005-0024-3, 2006.~~

645 Zanchettin, D., Bruni, S., Raicich, F., Lionello, P., Adloff, F., Androsov, A., Antonioli, F., Artale, V., Carminati, E., Ferrarin, C., Fofonova, V., Nicholls, R. J., Rubineti, S., Rubino, A., Sannino, G., Spada, G., Thiéblemont, R., Tsimplis, M., Umgiesser, G., Vignudelli, S., Wöppelmann, G., and Zerbini, S.: Review article: Sea-level rise in Venice: historic and future trends, *Nat. Hazards Earth Syst. Sci.* ~~Discuss. [preprint], <https://doi.org/10.5194/nhess-2020-351>, in review, 2021.~~ <https://doi.org/10.5194/nhess-21-2643-2021>, 2021.


650 Zarzuelo C., López-Ruiz, A., D'Alpaos, A., Carniello, L., Ortega-Sánchez, M.: Assessing the morphodynamic response of human-altered tidal embayments. *Geomorphology* 320, 127–141. <https://doi.org/10.1016/j.geomorph.2018.08.014>, 2018.

Zecchetto, S., Umgiesser, G., and Brocchini, M.: Hindcast of a storm surge induced by local real wind fields in the Venice lagoon. *Cont. Shelf Res.* 17 (12), 1513–1538, 1997.


Appendix A. The Mo.S.E. system testing phase



655



660





665 Figure A.1: Events when the Mo.S.E. barriers have been raised under testing phase. (a) – (t) comparison between SLs observed at the CPSM gauge of PS (black lines) and computed by the WWTM model forcing the closure of the Mo.S.E. barriers (blue lines). Grey and brown lines represent respectively the SLs and the wind speeds observed at the CPSM gauge of CNR platform. Red line represents the safeguard thresholds at PS (1.10 m). Bars indicate the periods when the barriers of Lido (orange), Malamocco (yellow) and Chioggia (green) have temporarily closed the respective inlets. (u) and (v) seaward and lagoonal view of the flap gates raised under the test of 28 December 2020 (photos by R.A. Mel).