

Comparison analysis and the implications of sustainable Flood Risk Management in four different by four front-end countries: The United Kingdom, the Netherlands, the United States, & Japan, and the implications to for Asian coastal megacities

5 Faith Ka Shun Chan^{1,2*}, Liang Emlyn Yang^{3*}, Gordon Mitchell⁴, Nigel Wright⁵, Mingfu Guan⁶, Xiaohui Lu^{7*}, Zilin Wang⁸, Burrell Montz⁹ and Olalekan Adekola¹⁰

¹School of Geographical Sciences, University of Nottingham Ningbo Campus, Ningbo 315100, China; email: faith.chan@nottingham.edu.cn

²Water@Leeds Research Centre, University of Leeds, Leeds LS29JT, UK, email: k.s.chan@leeds.ac.uk

10 ³Department of Geography, Ludwig Maximilian University of Munich (LMU), email: emlyn.yang@lmu.de

⁴School of Geography and Water@Leeds Research Centre, University of Leeds, Leeds LS29JT, UK, email: g.mitchell@leeds.ac.uk

⁵Nottingham Trent University, 50 Shakespeare Street, Nottingham, Nottinghamshire, United Kingdom, email: nigel.wright@ntu.ac.uk

15 ⁶Department of Civil Engineering, The University of Hong Kong, Pok Fu Lam, Hong Kong, email: mfguan@hku.hk

⁷Key Lab of Urban Environment and Health, Institute of Urban Environment, Chinese Academy of Sciences, Xiamen 361021, China & Nottingham University Business School China, University of Nottingham Ningbo China, Ningbo 315100, China, email: xhlu@iue.ac.cn/xiaohui.lu@nottingham.edu.cn

20 ⁸School of Geographical Sciences, University of Nottingham Ningbo Campus, Ningbo 315100, China; email: wangzilin.0726@gmail.com

⁹Environmental Geography and Planning, email: montz@ecu.edu

¹⁰School of Humanities, York St John University, email: o.adekola@yorksj.ac.uk

25 Correspondence to: Faith Ka Shun Chan (faith.chan@nottingham.edu.cn/k.s.chan@leeds.ac.uk); Liang Emlyn Yang (emlyn.yang@lmu.de); Xiaohui Lu (xiaohui.lu@nottingham.edu.cn/xhlu@iue.ac.cn)

Abstract. Sustainable flood risk management (SFRM) has become popular since the 1980s. Many governmental and non-governmental organisations have been keen on implementing the SFRM strategies by integrating social, ecological, and economic themes into their flood risk management (FRM) practices. However, the justifications for SFRM are still somewhat embryonic and it is not yet clear whether this concept is influencing the current policies in different countries. This paper reviews the past and present-current flood management approaches and experiences from flood defence to SFRM in four developed countries with the aim of highlighting lessons for developing coastal megacities mega-deltas in development. The paper explored recent strategies such as “*Making Space for Water, PPS 25, and NPPF*” in the UK; and “*Room for the Rivers*” in the Netherlands which was promoted implemented to cope with mitigate flooding, integrate FRM with ideas on sustainability concepts, and deliver good sound FRM practice for next-future generations. The In this context, the United States has also established a sound National Flood Insurance Program (NFIP), and in a different approach, Japan has developed an advanced flood warning and evacuation contingency system to prepare for climatic extremes. These case

studies showed some good lessons to achieve long term SFRM direction to deliver sound flood management practices taking into account social-economic and environmental concerns. Most of developing coastal megacities especially in Asia, are still heavily reliant on a traditional hard-engineering approach, that may not be enough to mitigate substantial risks due to human factors (e.g. exist huge large populations, rapid socio-economic growth, subsidence from excessive groundwater extraction, etc.) and natural factors (e.g. climate change including sea level rise and land subsidence) factors. We It is clear that different countries and cities have their own interpretation of SFRM, but recommend this paper explores policy makers policymakers to how they can adopt "mixed options" towards long term thinking about long-term-and-sustainability that with social, economic, and environmental considerations.

Keywords: Coastal megacities, Flood risk, flood management paradigms, Sustainable Development.

1 Introduction

Flooding is a natural phenomenon which has occurred from time to time over a long period of human history (Plate, 2002; Yang, et al., 2019). Floods can be caused by an intense or a long duration precipitation event, wave surges or exceptionally high tide events or combined with surge and tidal events (from cyclonic monsoon effects), or by rapid snowmelt (Kundzewicz, 1999). In Asian coastal megacities, flood risk is especially high and still rising (Hanson et al., 2011; Hallegatte et al., 2013; Yang, et al. 2015; Chan, et al., 2021), through two routes. Firstly, flood hazard is increasing as climate change raises sea surface temperature, driving oceanic thermal expansion and increases increasing the intensity and frequency of precipitation events (Meehl et al., 2007; Hulme et al., 2002). Second, the assets exposed to flood hazards, including people and property, are growing through rapid land use change, urbanisation, and economic expansion (Yang, et al., 2010). Ways to mitigate flood risk in urban coastal areas are varied, and in principle could necessitate relocation of people and properties from high-risk areas. However, such measures are extreme and costly, and are likely seen as impractical, with few people and firms willing to relocate, particularly from within dense economically vibrant cities such as Guangzhou, Shanghai, Jakarta, Ho Chi Minh City, Bangkok, and Singapore. A major challenge for such cities is therefore to manage flood risks, whilst addressing development needs.

Looking elsewhere along with the Asian coastal cities in Asia, for example, cyclone Nargis flooded Yangon, Myanmar in 2008 and led to more than 140,000 casualties and US\$17 billion in economic impacts (Terry et al., 2012). In 2011, the Chao Phraya River catchment flood caused severe inundation in Bangkok, Thailand, flooded several districts of the city, and caused serious economic losses, exceeding US\$4 billion (Chan et al., 2018). These examples demonstrate that Asian coastal cities are exposed to several types or of combined types of floods often in combination (e.g. surface water/waterlogging, fluvial in urban catchments, and coastal, etc.), and the impacts and consequences are highly related to continuous growing economies and populations. In addition, these cities are also experiencing complex human-induced factors (e.g. reclamation of coastal areas without considering sea-level rise and surges, inadequate urban drainage system, and over-extraction of groundwater resources that enhances land subsidence, to name a few). Experience from other countries which have faced severe flooding suggests

lessons for dealing with ~~the~~ flood risk. Asian megacities tend to rely on a one-dimensional, hard engineering approach to protect
70 against flooding (Chan et al., 2018; Yang et al., 2020), whereas in many other places, this approach is increasingly seen as untenable, as it is financially unrealistic to protect against all floods.

Therefore, flood risk management (FRM) has developed, an approach that addresses not just structural defence, but preparation
75 (e.g. ~~land use~~^{land-use} zoning, adaptation), non-structural protective measures, population preparedness, and emergency response and recovery mechanisms to reduce flood risk (Samuels, 2006). FRM reflects a growing awareness of the uncertainties, vulnerabilities, and costs associated with flooding, and is the ~~flood flooding~~^{flood flooding} paradigm widely accepted in Europe and some other advanced economies (Janssen, 2008), but to a much lesser extent in Asian cities. With the intention of drawing lessons for Asian coastal megacities, in this paper, we review FRM experience in four economies which are at the front end in applying the FRM approach (the UK, NL, United States, and Japan) (section 2). It additionally explores the wider concept of Sustainable FRM that extends the scope of FRM to consider wider social and environmental goals (seetion-Section 3). This
80 ~~The~~ paper also reviews the development of flood management practices in five selected Asian coastal cities (Jakarta, Indonesia; Bangkok, Thailand; Ho Chi Minh City, Vietnam; Guangzhou, China, and Shanghai, China) to demonstrate the latest progress of FRM in these cities that are exposed to flooding from various sources and to understand the implications of SFRM elsewhere for effectively influencing their flood management practices.

~~Our~~^{The} overall aim ~~of in~~^{of} the paper is to contribute to the understanding of SFRM and practice, and to argue for consideration
85 of flood ~~oping~~^{oping}-~~mitigation~~^{mitigation} strategies for Asian coastal megacities developed through a consideration of sustainable development principles. Making such information available is of prime importance ~~due to the fact that~~^{because} Asian megacities already face massive flood management challenges, and flood damages – whether human or material – are growing rapidly.

2 Learning from the four ~~front-end~~^{front-end} countries

90 2.1 The road from traditional flood management to SFRM

Responses to flooding have historically developed through several distinct phases. Initially, (pre-1980's) responses were aimed at controlling and defending against floods by relying on “hard engineering solutions” (Penning-Rowsell et al., 2006). This paradigm of “flood control” (the 1950s to 1960s) sought to reduce flooding that might damage agricultural production and compromise food security ~~that and~~^{and} focused on the engineering approaches and materials used (e.g. concrete). Land drainage
95 constructions and channelization were used to quickly drain ~~and keep flood water~~^{floodwater} away from agricultural lands ~~by~~^{by} the driving principle of increasing in-channel conveyance. That is aims to reduce ~~and avoid~~^{and avoid} flood impacts on agriculture. Afterwards^{Later in the 1970s}, the paradigm of “flood defence” (the 1970s) was adopted, as the economic interest of flood control was widened to encompass manufacturing and tertiary industries. This “flood defence” phase sought to protect infrastructure, people, and ~~their~~^{their} property by using structural engineering measures such as seawalls, dykes, embankments,
100 breakwaters, and levees.

Through the 1980s a “*flood management*” approach emerged, which emphasised coping with flooding rather than solely controlling floods. This occurred as ~~policy makers~~policymakers realised it was increasingly difficult to defend against all flooding due to increasing climatic extremes (i.e. intensive precipitation), whilst social and environmental concerns were also recognised as important. This change in focus gave greater attention to flood preparedness and public awareness through, for 105 example, the flood forecasting and warning systems that were developed across Europe. Such changes have been the basis of further development of the FRM paradigm (Lumbroso et al., 2011; Parker and Fordham, 1996). In the 2000s, the focus changed again to more explicitly consider flood risk (Plate, 2002), including the probability of a given flood hazard (e.g. precipitation, storm frequency, sea-level rise) (Kundzewicz et al., 2002; Schanze et al., 2005; Tol et al., 2003) and the vulnerability of, and consequences for populations and economic assets exposed to that flood hazard (Brown and Damery, 2002; Schanze, 2006). 110 Thus, FRM now seeks to prevent damage by reducing the exposure and vulnerability of people and properties prone to flooding. It is not possible to eliminate flood risk, hence FRM considers the costs and benefits of flood risk mitigation for society at large (Butler and Pidgeon, 2011). The objective of FRM is thus to reduce the harmful consequences of flooding and to balance risk reduction alongside other political considerations and priorities. An important aspect of FRM ~~that is~~ is 115 encouraging to manage flood risk ~~with~~through engagement with wider stakeholders (e.g. households, practitioners, politicians, flood engineers, planners, and communities), ~~so as to~~ to identify multi-disciplinary perspectives and solutions (Pitt, 2008; Yang, 2020).

In this context, it is useful to reflect on the national experiences of FRM ~~with a view to identifying~~ to identify lessons for countries where flood defence and control continue to be the dominant response to flooding. Therefore, we next consider the 120 experience of flood management in the UK, ~~NL~~the Netherlands, the US, and Japan, where flood management practice has evolved significantly in recent decades, and we show how the practice has evolved from defending against flood to living with floods. ~~Despite Whilst acknowledging there are~~ dissimilarities of human-induced factors (e.g. urbanisation, population, etc.) and natural~~physical~~ factors (e.g. meteorological, hydrological, topography, etc.) ~~These~~, T, these valuable experiences offer lessons for FRM in Asian coastal megacities such as managing urban flooding through the integration of urban planning practices, addressing climate change and promoting sustainability.

125

2.2 The United Kingdom

From the early part of the twentieth century, clear phases of flood management history can be identified in the UK, with the first phase pre-1970s. During this period, flood policy was governed and implemented by the Ministry of Agriculture, Fisheries, and Food (MAFF), whilst the ~~Internal~~internal ~~Drainage~~drainage ~~Board~~boards (IDBs) ~~was~~were responsible for 130 carrying out flood alleviation ~~by engineering~~ practices (drainage, etc.) in the ~~low~~lying parts of ~~UK~~country ~~UK~~. In general, the UK Government adopted ~~The foci were on~~ land drainage and ~~hard engineered~~hard engineered defences such as river straightening, embankment construction ~~of embankments and levees~~in rural and urban flood policy responses during this era. The failure of this approach became evident following major floods in 1947 and 1953 which inundated 65,000 ha and 280,000

Commented [WN1]: In my view a levee is an embankment this may be redundant.

ha of farmland respectively, and which damaged agricultural output during the ~~post war~~^{post-war} period when many foodstuffs ~~were~~^{were in}

135 ~~short supply- and food production~~^{were still rationed} ~~was challenging~~^{(Penning-Rowsell and Chatterton, 1977).}

During the 1970s, the ~~UK G~~overnment adopted cost-benefit appraisal (CBA) to evaluate drainage projects. Where MAFF found high-yielding crops (particularly cereal, sugar, and potatoes) to be threatened, the IDB and local authorities would help farmers to develop measures to control flooding, usually through ~~the~~ construction of ~~levees-embankments~~ and drainage channels (Penning-Rowsell and Green, 2000). Johnson et al. (2007) argued that despite the application of CBA by ~~the~~ government, flood policy was biased in favour of farmers and ~~land owners~~^{landowners}, as they were the major (private) beneficiaries of public expenditure. However, the UK remained unusual in that it was one of few countries at the time to apply CBA to flood control measures.

During the 1980s, the priority of ~~the~~^{the} UK flood policy was to “*keep the water out*” (Johnson et al., 2007). The emphasis had moved from protecting farmland; to protecting a broader asset base that underpinned economic growth. Thus, ~~policy~~^{makers} ~~policy~~^{makers} were keen on implementing flood alleviation schemes and projects that defended people and property (homes and businesses) (Johnson and Priest, 2008). Criticism was however now directed at the use of CBA, for being overly focused on economic aspects. For example, flood measures/schemes tended to be approved if they protected ~~high-value~~^{high-value} properties in a floodplain (e.g. riverside houses) but ignored adverse ecological ~~effects-factors~~^{effects-factors} (e.g. fish and invertebrates affected by channelisation) and other environmental impacts caused by the flood defence projects themselves (Green et al.,

150 1991; Hey et al., 1994; Penning-Rowsell et al. 2006). Thus, through the 1980s and 1990s, flood defence was largely driven by CBA that considered net benefits (but not their distribution) and neglected external ~~ity~~^{ity} ~~effects-factors~~^{effects-factors} (e.g. ~~inflations~~^{inflations} and ~~market~~^{market} ~~prices of the construction and labour cost, etc.~~^{prices of the construction and labour cost, etc.}).

In England and Wales, more than 4 million people, and property valued at more than £200 billion are currently located in areas at risk of a 1-in-100-year flood (Lo and Chan, 2017). Forecast flood damages are currently £1.4 billion annually, but are 155 expected to rise to as much as £27 billion by 2100 (Evans et al., 2006). In 2002, the Institute of Civil Engineers emphasised that flood engineering measures remain important, but will no longer be enough, and advocated the approach of “*living with floods*” (Fleming, 2002). This gave impetus to a further paradigm shift in flood management policy, with concern for wider aspects, recognising socio-economic and environmental values, and impacts of climate change (Hall et al., 2003). Innovations in flood and coastal erosion risk management included the “*Making Space for Water*” (MSW) strategy (Defra, 2007) and

160 “*Planning Policy Statement 25*” (PPS25) (DCLG, 2007) which sought to implement elements of that strategy via the land use planning system ~~in different types of floods~~^{in different types of floods}.

The vision of MSW is that of making space for flood water rather than defending against it. Many coastal and inland areas have been regularly inundated, but defending against all flooding in these areas had become unaffordable. The MSW strategy is integrated with related regionally applicable policies including the “*Coastal Erosion Risk Management Evidence Plan*”, 165 “*Catchment Flood Management Plans*” and “*Directing the Flow: Priorities for Further Water Policy*” (Evans et al., 2004; Thorne, 2014) that encourage practitioners to deliver more sustainable flood management, which also considers water quality, biodiversity, and engagement with rural communities ~~on~~^{on} addressing fluvial, pluvial and coastal floods. PPS25 is a land use

planning policy, applicable at a site-specific level that provides guidance on guides how planners and developers should address flood risk. It includes a risk-based sequential test intended to direct development to areas of lower flood risk. PPS25, and the 2014 “*National Planning Policy Framework*” that superseded it, adopt a broader Sustainability Appraisal (SA) of flood management, considering economic, social, and environmental impacts. They require consideration of the spatial distribution of flood risk and how that risk distribution changes in response to proposed mitigation measures, so as maximise the net benefit of flood management. This is co-produced by the Local Planning Authority- (LPA), the Environment Agency (EA) and the relevant internal Drainage Board (HDB).

170 175 In From Since 2010, “*Surface Water Management Plans*” (SWMP) were as have been required by the government under the “*Flood and Water Act*”. The SWMP outlines a preferred surface water management strategy indicating how flooding from sewers, groundwater, and non-main rivers will be managed. The adoption of sustainable urban drainage systems (SuDs) is encouraged to deal with runoff following intensive rainfall (Defra, 2010). The SWMP works alongside PPS25, assessing flood risk to inform local authority planning decisions, which are now required to ensure that new development does not increase flood risk. Flood risk modelling and mapping are generally conducted by the environmental regulator, the Environment Agency (Environment Agency, 2014c), on behalf of local authorities who have been made the Lead Local Flood Authority (following the Pitt (2008) review which identified institutional complexity as a major barrier to addressing flooding in the UK). The maps of flood probability are used in flood risk assessment and input to strategic planning. These policies and practices also encourage the participation of public and NGOs-NGO stakeholders in the development of SWMPs.

180 185 190 195 200 The subsequently developed “*National Planning Policy Framework*” (NPPF) (DCLG, 2012) aims to restrict inappropriate development in areas at risk of flooding, directing development away from areas at highest risk, but where development is necessary, making it safe without increasing flood risk elsewhere. This requires a strategic flood risk assessment, an assessment by one or more local planning authorities to appraise the current and future flood risk from all sources (surface and ground waters, fluvial and coastal), and with consideration of possible impacts from climate change. The NPPF represents an extended version of PPS25 intended to more comprehensively assess the impact that land-use change and development will have on flood risk. For example, local planning authorities use flood risk information (i.e. Flood map for Planning – Rivers and Seas) provided by the EA (Environment Agency, 2014a), to consider opportunities for reducing flood risk to both existing communities and new developments. The NPPF also ensures that emergency planning capability is evaluated against the forecast flood risk (DCLG, 2012). The EA also provide-provides a live flood warning map (indicating flood alert, warning, and severe warning) showing locations at risk (Environment Agency, 2014b). Through this public release of flood risk information, the intention is that public awareness, preparedness, and participation will be enhanced. Current UK flood policy thus seeks to integrate FRM with land-use planning, considering future development and flood risk, which addresses social, economic, and environmental criteria. Whilst this may be an example of good practice in strategic and sustainable FRM, the UK still has room to improve in aspects such as cost and time effectiveness, and in its complex governance structure such as the fragmented responsibilities across institutions and stakeholders in UK flood management (Ashley et al., 2020; Green, 2014).

2.3 The Netherlands

The total land area of the Netherlands (NL) is about 34,000 km² of which more than 67% is situated below mean sea level (Beck, 2012). The safety standard of dike-rings and other measures is legislated for and reviewed every five years. The population is about 16.8 million with over 8.9 million properties located ~~on in flood-prone~~ flood-prone areas in 2012 (Jongman et al., 2014). As a result, ~~land-use~~ land use is intense, limiting flood management options, and placing great reliance on engineered ~~coastal~~ flood protection measures (Wesselink et al., 2007). It is vulnerable to coastal flooding and large parts of the country are ~~still~~ subsiding (van Stokkum et al., 2005). Spring ice melt from the mountainous region of the upper Rhine and Meuse rivers exposes the country to fluvial ~~and~~ and flash flooding, with major floods in 1993 and 1995 (Vis et al., 2003; Wind et al., 1999). The country has a millennial history of flood management including from the 14th century the building of dyke-rings around polders to protect land and settlements from flooding. Today ~~more than a thousand polders are protected~~ there are more than a thousand polders protecting 65% of the Dutch coast ~~country~~ in the Netherlands and some polders are located inland (Van Stokkum and Witter, 2008).

The 1953 North Sea Flood, which caused 1,800-836 deaths, spurred the NL-Netherlands to develop a high coastal flood safety protection standard. The country has the highest flood protection standards in the world, with 1-in-4,000 to 1-in-10,000-year flood return period infrastructure (i.e. coastal dike-rings), protecting populations and economic activities, especially in the West Coast cities of Rotterdam, ~~the~~ The Hague, and Amsterdam (Klijn et al., 2004; Gerritsen, 2005). Despite the efforts of the Dutch government, the 1993 Meuse and Rhine River flood required over 10,000 people to be evacuated, with damage costs ~~in excess of~~ over 10 billion Euros. The Dutch government understood it could not rely wholly on engineered flood defences to achieve an acceptable degree of risk (Olivier and Wytze, 2006; Wind et al., 1999) and in 1999 introduced a new water management policy, “*Room for the Rivers (Ruimte voor de Rivieren)*” (Böhm et al., 2004; Van Stokkum et al., 2005) (see Table 1). This required major changes in ~~FRM~~ flood risk management, including that: (i) water had to be guided in the landscape following an explicit spatial planning process, and (ii) water had to be retained, stored and when necessary, ~~the~~ land ~~had to be~~ drained.


Table 1: Features and functions of the “Room for Rivers” policy in the NL-Netherlands

Features	Functions
(i) Awareness	The Dutch government needs to improve communication on the nature and scope of risks and, in addition to its own efforts, to offer all citizens the opportunity to contribute or participate in risk reduction e.g. floods preparedness.
(ii) Three-steps-strategy	The need for a robust and resilient approach to ensure safety and reduce water-related problems, based on the following principles: ① Anticipating instead of responding. ② Not passing water management problems on to others, by following a three-step strategy (retention, storage, and discharge). ③ Allocating more space to water in addition to implementing technological measures.
(iii) Giving rooms to rivers	Encourage water storage.

(iv) Spatial planning	Adapting the spatial zoning strategy to prevent any human activities in the floodplains to interrupt the river discharge capacity
(v) Knowledge exchange	Encourage social learning and public education relating to water and river management.
(vi) Governing responsibilities	The provincial and local municipal authorities and water boards all need to share their responsibilities and ensure water related <ins>water-related</ins> safety problems i.e. flood risk. All institutions need to ensure the effectiveness in FRM.
(vii) Investments	It requires additional fund-funds and investment in FRM systems for the projected climate change and land subsidence.
(viii) International or transboundary co-operation	Co-operation with other shared-river basin countries (i.e. Deutschland and Luxemburg) on FRM should be intensified.

Sources: Adapted from Klijn et al., 2008 and Van Stokkum et al., 2005

230 Along with the long history of flood management, Dutch water boards ~~that are responsible for FRM~~ have an established engineering tradition which, it is argued biases them to management options with which they are familiar (Klijn et al., 2008). Some critics thus argue that the “*Room for the Rivers*” policy remains ~~over-reliant~~over-reliant on dike-rings, ~~levees~~embankment construction, and other river regulation engineering (see Figure 1) (Hudson et al., 2008; Ten Brinke and Bannink, 2004). Nevertheless, the “*Room for the Rivers*” approach does represent a major shift in FRM, with strategies aimed at ~~the~~ 235 integration of floodplain development and spatial land-use planning to meet socio-economic needs, ecological conservation and awareness of biodiversity, and wide stakeholder involvement. Collectively this novel approach is considered to represent a progression ~~from FRM to~~towards sustainable ~~FRM~~flood risk management (Van der Brugge et al., 2005; Van Stokkum and Witter, 2008).



240 Figure 1: Measures of “*Room for Rivers*” in the ~~NL~~Netherlands. Source: Room for Rivers Program office.

← Formatted: Normal

2.4 The United States

The United States (US) regularly experiences severe flooding. According to the US National Weather Service (NWS), there
245 has been an average of 87 deaths per year from flooding between 1989 and 2018 (National Weather Service, 2018) and 29
flood events during the same period that resulted in ~~greater than over~~ \$1 billion in economic losses, with an average event cost
of \$4.3 billion. This does not include flooding caused by tropical cyclones (42 during the same period with an average event
cost of \$21.9 billion). (National Atmospheric and Oceanic Administration, 2019).

~~Tropical cyclones are low-pressure systems that form over warm tropical waters. They typically form when the sea-surface
250 temperature is at or above 26.5°C. Tropical cyclones can continue for several days, weeks, and follow an erratic path. A
cyclone will dissipate once it moves over land or cooler oceans. The differences of tropical cyclones (i.e. storms, cyclones and
hurricanes) are varied from the wind speed in ascending order, and “typhoon” is the term that used the same feature as a
hurricane but is only used for intense low-pressure weather systems in the NW Pacific (Bureau of Meteorology, 2021). Not all
cyclones (typhoons) bring intensive rainstorms that cause heavy rainfalls to enhance fluvial and pluvial floods. However, the
255 storms are often evolved with rainstorms and generate storm surges as a combined effect. The Among the most disastrous events in this
time period period are are Hurricanes Katrina in 2005, Sandy in 2012, Harvey, Irma, and Maria in 2018, and Florence in 2019, along with
flooding in the Midwest US in 1993, 2008, and 2019, as these events significantly occurred as coastal or combined floods with
coastal and pluvial floods (Chan, 2004; Link, 2010; Xiao et al., 2011; Vance, 2012).~~

In the US, large populations are located along the banks of watercourses, lakes, and coasts. In coastal ~~flood prone~~ flood-prone
260 areas of Florida, California, Texas, Louisiana, and New Jersey, populations have expanded greatly since the 1980s (Niedoroda
et al., 2010); the US Census projects an additional 82 million residents by 2030, an increase of 29% of the current population
in coastal areas such as Florida, Virginia, New York States and New Jersey ~~in on~~ the East Coast ~~and~~, Mississippi in the ~~Mid~~
~~part~~ Midwest and California in the West Coast (Hamin et al., 2019; Maantay and Maroko, 2009). Demand for development
land remains high, and along with climate change, is likely to increase flood risk, especially ~~along in~~ coastal areas (Bagstad et
265 al., 2007; Aerts et al., 2013; Burgess et al., 2007).

The federal government has controlled the main flood management institutions since the 1920s when it took responsibility for
managing floods, primarily through flood control structures. However, at that time flood legislation was unclear, particularly
270 with respect to concerning the relationship between federal, state, and local government. Notably, the federal government
sought to share the financial burden of flooding and flood protection with state governments and local communities, and the
percentage to be covered by state and local governments has increased over time.

~~Even as more funds were committed to flood control, it was also believed that these were not the best way to manage flood risk, as they were often seen as a “carrot and stick” approach. The “carrot” was the provision of flood insurance in communities that regulate the development of the 100-year floodplain, the stick. This was followed in 1977 by Executive Order 11988: Floodplain~~

Commented [WN2]: What was the stick?

275 Management, issued by President Carter, which directed federal agencies to take the flood hazard into account when planning, funding, and implementing developments in ~~flood-prone~~ areas (Arnell, 1984). Further, the Federal Emergency Management Agency was established in 1979 ~~in order to~~ coordinate ~~under one agency~~ all of the tasks associated with emergency management, including mitigation and the National Flood Insurance Program (NFIP).

280 Even with all of this, the federal management strategy maintained a focus on hard-engineering solutions. ~~For example~~
~~Eventually, an impetus to review the approach was seen in~~ the 1993 Mississippi River flood, which led to the river flooding over 1,200km of ~~the river's length~~ ~~channel~~ and about 840,000 km² in area (Figure 2), ~~resulted~~ ~~resulting~~ in over \$15 billion in economic damages, ~~provided an impetus to review the US approach to flooding~~. The subsequent “*Galloway Report*” in 1994 proposed that development in the floodplain should be avoided unless no alternative locations existed (Galloway et al., 1999), similar to the “*MSW and Room for Rivers*” in the UK approaches described above. Yet, while the report was in preparation, reconstruction of damaged and breached levees was ongoing. However, the Galloway report indicated that whilst embankments and levees are important in protecting urban areas, they are insufficient on their own. Floodplains should be managed as part of the natural ecosystem, with risk-based forecasting used to inform flood management. These practices encouraged sharing of flood risk information with the public and improved awareness of and ~~preparedness against for preparation for~~ flood risk. From the ~~mid 1990s~~ there were improvements in practices of: (i) hydrological data collection during and after floods; (ii) development and installation of better instruments to evaluate coastal and river flood risk (e.g. Use of GIS, remote sensing, and GPS to identify and understand flood hazards in various locations); and (iii) development of hydrologic models for more precise flood monitoring and prediction (Changnon, 1998). Since then, among other publicly available risk information sources, the NWS provides river level data with maps showing potentially flooded areas through its Advanced Hydrologic Prediction System (AHPS; <https://water.weather.gov/ahps/>) and the United States Geological Survey (USGS) monitors river levels and discharges for thousands of rivers nationwide (water.usgs.gov).



Figure 2: Lower The lower image of the 1993 flood condition compares to the normal condition in the 1991 upper image in the lower Missouri, the Mississippi River. Source: (Allen J, NASA).

300 The NFIP marked a particularly significant development of flood management in the US. The scheme, the world's largest national flood insurance program, provides short- and long-term financial assistance to residents in flood zones (Arnell, 1984). The program enables property owners in-to purchase insurance protection, administered by the Federal government, against losses from flooding, and requires flood insurance on all properties in the designated 100-year floodplain as shown on "Flood Insurance Risk Maps" ([FIRMs](#)). Despite the requirement for flood insurance and the potential sanctions for not having it if 305 flooded (ineligibility for other federal disaster assistance), only approximately only 50% of properties in the designated 100-year floodplain carry have flood insurance (National Association of Insurance Commissioners, 2017). This may reflect several factors, including a misunderstanding ofby property owners of their flood risk and an expectation that disaster relief will be forthcoming despite the requirement.

The NFIP aims to provide flood protection for property owners and discourage development in substantial risk areas by limiting
310 access to insurance. The NFIP is sponsored by the ~~Federal~~federal government which also provides insured residents ~~also have~~with access to emergency financial relief aid should they suffer flood damage (Longenecker, 2008). The program was designed to be financially self-supporting, but the US Government Accountability Office reports that losses cost the taxpayers about ~~USD \$200 million~~USD 200 million annually, and that since 1978, the NFIP has paid more than ~~USD \$51 billion~~USD 51 billion in flood claims. ~~The~~ Congress originally intended that the NFIP program be supported by premiums, but ~~it is not this has not~~happened for various reasons including subsidised insurance rates for pre-existing structures and repetitive loss claims for many structures with no action to reduce their risk.

Further, sufficient funding from Congress for ~~FIRM~~flood insurance risk maps- updates has not been forthcoming ~~despite the fact that even though~~ many of the maps were created in the 1980s and thus do not reflect floodplain changes over time, whether from upstream development or climate change. Insurance is one means to mitigate flood risk but designing and delivering
320 successful schemes are ~~evidently~~ difficult, with issues arising relating not just to affordability, but ~~cost sharing~~cost-sharing, ~~the~~ sacrifice of very high-risk areas, and insurance industry returns and expertise (Ball et al., 2013; Crichton, 2008; Michel-Kerjan and Kunreuther, 2011).

As is the case in many places, attention to flood risk increased with an event that forces communities to recognize the nature of the risk it faces. For example, following Hurricanes Katrina and Sandy, US authorities responded with ~~flood sensitive~~flood-sensitive strategic plans. In the aftermath of Sandy, New York City adopted a “*rebuild by design*” coastal master plan that integrates climate change into an adaptive development planning process, ~~such as the implementation of climate adaptation plans merged with the long-term master plan for the New York City~~-(Rosenzweig and Solecki, 2014). This includes ~~the~~ production of flood risk maps to increase public awareness; ~~the~~ development of an emergency contingency plan for all city districts with specific attention on vulnerable social groups (e.g. minorities and the elderly); and raising flood protection for
330 particularly vulnerable (Aerts et al., 2013). These strategic actions, together with those described above, indicate the US has adopted a “mixed” options approach to dealing with rising flood risk.

2.5 Japan

Japan covers approximately 378,000 km² of which 70% is hilly or mountainous ~~land~~terrain, hence low-lying ~~flood prone~~flood-prone areas
335 have been preferentially developed for settlement. ~~In this past decade during the 2010s, across the country, as there are more than 49% of the population, about 60 million people (49% of the population)~~, reside on floodplains (Huang, 2014). The country ~~unfortunately, unfortunately~~, has ~~got~~ frequent flood hazards and disasters records as the topographic feature of Japan tends to have short steep rivers with little upstream storage. Hence, flash and pluvial and combined ~~type~~types of floods are particularly occurred in particular, in particular, occur often. Over the last 30 years, intensive rainfall events (>50mm/hr) have increased in frequency by about 50%, and those >100mm/hr have more than doubled (Yamada et al., 2011) and ~~this trend it is~~ expected ~~that this trend will~~ continue with climate change. Japan has flood hazards arising from typhoons, torrential rains, snowmelt, and tsunami~~-~~ and past floods have been associated with major impacts (Fujita and Hamaguchi, 2012). For example, in 2000 at

Tokai city in Nagoya, pluvial flooding killed 18 people and injured 115, and economic losses were about 978 billion JYP (c. ~~\$9.57 billion USD~~ USD 9.57 billion). Another example, in 2004 during the Niigata-Fukushima flood, a result of torrential rain, killed 20 people, and inundated 26,000 properties, making 5,800 homeless. In the same year, four strong typhoons (Songda, Meari, Ma-On, 345 and Tokage) hit the East coast of Japan between September and October causing sea surges, with 180 killed or missing and over 23,000 properties destroyed (Zhai et al., 2006).

Historically, flood management policy was ~~haphazard-not coordinated~~ in Japan, and it was not until the 1961 "Disaster Countermeasures Basic Act" that legislation provided the basis for an integrated disaster management strategy and clearly defined responsibilities across the government. Specific laws relevant to flood prevention, such as the "River Law" followed 350 in 1964 which reorganised river administration and improved flood governance. The Water Law was the catalyst for the 1977 "Comprehensive Flood Control Measures" policy that specifically focused on flood prevention, flood control, and response to flood events (Takahasi, 2009). Under this policy, rivers are divided into three classes (A-C); ~~class~~ Class A rivers, the largest in terms of area, length, and significance of their assets (economic and population in their basins), are managed by the Ministry of Land, Infrastructure, and Transport (MLIT)²⁵ River Bureau which reports directly to the Japanese Central Government. 355 Flood risk in the smaller Class B and ~~Class~~ C rivers ~~is-are~~ managed at municipal and local government levels, with MLIT support (MLIT, 2008). Ikeda et al. (2008) note that whilst flood fatalities fell after 1960 as new flood protection policies took effect (including an MLIT policy that 1% of national income be invested in flood measures from 1960–1990), economic losses from flooding have not fallen and ~~remain remained~~ high.

Kundzewicz and Takeuchi (1999) illustrated ~~that~~ since the River Law was enacted, the MLIT and related institutions employed 360 a hard engineering flood protection approach, with the main flood control strategy being to transport water quickly to the sea. Super levees, divergent canals, ~~flood ways~~ floodways, and bypasses were constructed. This approach was questioned after the 1977 Nagasaki flood where 375 people in the unprotected upstream area died following a 180mm/hr rainfall event. Two problems were particularly evident: (i) flood control or hard flood protection measures did not cover all parts of the river, due to the cost of such defences; and (ii) ~~class~~ Class A rivers and ~~class~~ Class B/C rivers were managed by different institutions 365 with inadequate communication between them and a lack of integrated flood risk appraisal (Ueno, 2002). ~~Afterwards~~ Afterwards, in the 1990s, the River Law recognised the complex nature of integrated catchment management, with the law seeking to address objectives related to flood risk, water resources, and environmental quality and legislated in 1997. "Article 1. The purpose of this Law is to contribute to land conservation and the development of the country, and thereby 370 maintain public security and promote public welfare, by administering rivers comprehensively to prevent ~~the~~ occurrence of damage due to floods, high tides, etc., utilize rivers properly, and maintain the functions of the river water by conserving the fluvial environment".

This amended River Law reflected that the government was advocating a more sustainable approach to flood risk, with ~~the~~ integration of social and environmental issues into FRM, as well as wider public engagement (MLIT, 2008):


"When river administrators intend to draft a river improvement plan, they shall consider opinions from persons with 375 experience or an academic background when necessary" (Article 16-2-3), and "In connection with the previous paragraph,

river administrators shall take necessary measures, such as public hearings, etc., to reflect the opinion of the people concerned whenever necessary.” (Article 16-2-4).

In the 2000s, the MLIT issued their “Effective Flood Management including Basin Responses” policy, which emphasised that flooding is/was unavoidable and accepted the nature-ability of flooding in water-prone areas (e.g. wetland) to enhance ecological value (Ikeda et al., 2008). This policy not only focused on the areas with high assets (e.g. urbanised floodplain), but extended to cover the rural areas in the river basin (i.e. upstream) (MLIT, 2008). Key to this policy is the integration of hard and soft flood protection measures, rather than reliance on traditional engineered defences. The Japanese authorities Whilst, Japan understood that the importance of flood protection measures and practices are necessarily considering especially to cities owing to flood consequences in Japanese cities, because of their by substantial populations and affiliated economic assets.

380 385 This effective flood management policy also coping with the “Act on Countermeasures against Flood Damage of Specific Rivers Running across Cities” (legislated in 2003) that particularly-targeted for reducing flood risk for various sized (large to small) rivers that running run across the cities and towns in Japan (MLIT, 2003). The Act has-was further amended in 2004 and further legislated-legislation passed through the “Flood Fighting Act”. These two amended Acts allocate ensure that the municipal governments understood-understand their roles in delivering according to FRM practice explicitly on-delivering 390 according to FRM practice (Yamada et al., 2011). For example, informing residents for gaining-increased awareness by issuing a “flood warning” for the communities to understand potential flood spots. WhilstFurther, the legislation, also providing provides emergency services (e.g. temporary shelters, evacuation medical services, etc.) for enhancing emergency response and recovery practices (OECD, 2006). Lately, towards the 2010s, the Japanese authorities further addressing addressed flood resilience approaches.

395 “Flood Resilience” refers to the ability of communities and sectors to withstand a flood event and the ability to recover from the disruption of floods (Environmental Protection Agency, 2014). In Japan lately, the government and especially tackling tackled the perception via issuing flood hazard maps (MLIT, 2008). The MLIT was further concerned about the intensive rainstorms that enhanced urban floods and legislated the-specific measures to reduce flood risk during heavy rainstorms (MLIT, 2013). After the Tsunami and coastal floods in the early 2010s, the MLIT has further implemented the “Act on Special Measures concerning 400 Urban Reconstruction” in 2018 to strengthen the-flood resilience, particularly tackling the prevention, emergency response, and recovery processes (see Figure 3). This is used to support development decision making by land-use land-use planners by setting up the land use regulation zone system, direct-directing the flood proofing floodproofing of existing urban facilities (e.g. the underground, railways, public services facilities); raise-raising flood awareness amongst the at-risk public (via flood warning system, hazard map, and future flood projection); and informing the emergency response and evacuation procedures (via relocation practice) of the civil emergency services (MLIT, 2018).



understood simply as the ability of society and ecosystems to cope with several types of flood risk whilst maintaining the level of well-being, whilst Chan et al., (2013b) attempt to characterise SFRM practice within a more explicit sustainability framework. Nevertheless, for the four countries we discussed above, progress from flood control, to FRM, and now towards SFRM is clearly evident (Lawson et al. 2020) (see Figure 4).




Figure 4: Flood management paradigms and major changes towards SFRM.

Examples of action taken towards SFRM include the open provision of flood risk information to aid participatory planning (post 2000 in NL), which has been implanted in the Netherlands and in the UK. For example, the local authorities (e.g. Local Planning and Water Bureaus) to deal with flood mitigation measures that considered addressing subject to wider social-economic assessments and appraisals. These authorities extended the Cost-Benefit Analysis and similar benchmarking practices that assess CBA considering economic environmental impacts (UK), social values; perceptions and opinions; cost sharing/cost-sharing through national flood insurance schemes, environmental consideration, natural capitals and design of flood mitigation with nature. Similarly, the United States has also considered these factors during the same era (1950s–1970s in US), considered both to protect the natural environment, and to recognise its value in mitigating flood risk (e.g. via sustainable drainage systems, wetlands, reintroduction of river meanders) (Butler and Pidgeon, 2011; Green,

2014; Porter and Demeritt, 2012; Scott et al., 2013). From our review, it is apparent that no country has FRM that
440 comprehensively addresses sustainability concerns (see Table 3).

Table 2: Definitions and principles of SFRM in different countries

Countries	Legislative documents	Definition of SFRM
UK: Scotland	FRM (Scotland) Act 2009 (the FRM Act)	“Sustainable flood management provides the maximum possible social and economic resilience* against flooding**, by protecting and working with the environment, in a way which is fair and affordable both now and in the future.”
UK: England and Wales	Flood and Water Act (2010)	“In exercising a flood or coastal erosion risk management function, an authority must aim to make a contribution towards contribute to the achievement of sustainable development.”
	Defra (2011)	Sustainable development in the context of <i>flood and coastal erosion risk management</i> (FCERM) includes: <ul style="list-style-type: none"> • <i>taking account of the safety and wellbeing of people and the ecosystems upon which they depend,</i> • <i>using finite resources efficiently and minimising waste,</i> • taking action <i>acting to avoid exposing current and future generations to increasing risk, and</i> • <i>improving the resilience of communities, the economy, and the natural, historic, built, and social environment to current and future risks.</i>
European Union	EU Floods Directive (2007)	The EU Floods Directive (2007) has aimed for: <ol style="list-style-type: none"> <i>ensuring the quality of life by reducing flood damages by being prepared for floods;</i> <i>mitigating the impact of risk management measures on ecological systems at a variety of spatial and temporal scales;</i> <i>the wise use of resources in providing, maintaining, and operating infrastructure and risk management measures; and</i> <i>maintaining appropriate economic activity (agricultural, industrial, commercial and residential) on the flood plain</i>

Note: (* ‘resilience’ means: ‘ability to recover quickly and easily’. The Scottish Executive uses it to deliver the ‘four as’: Awareness + Avoidance + Alleviation + Assistance.)

(**) flooding means all types of flooding: surface (pluvial), sewer, river, groundwater, estuarine and coastal)

Table 3: Strengthens and weaknesses of current FRM practices towards SFRM across 4 countries

Pillars	Strengthens of practices	Practices	Facts/examples	Weaknesses of practices	Arguments and reasons
Social-economic	Social justice and equity	UK: Pitt (2008) reported to address social justice and equity issues in FRM	Defra research (projects FD2605 and FD 2606) has looked at issues of inequity of FRM in England	Social injustice and inequity	UK: No exact implemented guideline to address issues of inequity of FRM, but most of <u>poors</u> <u>the poor</u> live in the flood zone (Johnson et al., 2007) US: Ethical minorities - A research showed the minorities in NYC mostly are not insured by the NFIP flood insurance scheme (Maantay and Maroko, 2009)
	Flood risk information on <u>social</u> - <u>economicsocial</u> - <u>economic</u> impacts	UK, NL: Flood risk mapping (EU, 2007; Environment Agency, 2014abc); US: Interactive flood information map (NOAA, 2014ab); JP: Flood hazard map (MILT, 2008)	Increase understanding of flooding, preparedness, and awareness; assess potential economic impacts (<u>the</u> UK and NL); showing flood histories (hazards), types of flooding, current flood risk, and level of protection (US); showing the post-flood emergency routes and contingency plan (JP)	Analysis and reporting of potential flood risk on possible <u>social</u> - <u>economicsocial</u> - <u>economic</u> impacts	UK: Flood risk mapping – may be too technical for the public to understand (Porter and Demeritt 2012), absence of the detailed information (e.g. protection measures) on the flood maps
Cost-benefit analysis (CBA)	UK, NL: Adopted CBA in NPPF and Room for Rivers (Carter et al., 2009; Eijgenraam, 2005)	Maximising the cost and value, and <u>create</u> - <u>creating</u> economic justification on <u>the</u> FRM process	Cost-benefit analysis (CBA)		UK, NL: Difficult to evaluate environmental and social aspects in the CBA
Flood insurance	US: NFIP (Arnell, 1984)	Most <u>of</u> -residents (who live within 1-in-100 years flood zone) are covered in the NFIP scheme	Flood insurance		US: Poor people and minorities are mostly not insured by the NFIP scheme (who live outside the insurance coverage boundaries - the risk is higher than 1-in-100 years) For example, some residents were the poorest community in New Orleans lived in the Lower Ninth Ward, which was flooded by a catastrophic breach (during Storm Katrina) that without NFIP coverage) (Chamlee-Wright and Storr, 2009; Burby, 2006)
Apply sustainable flood management practices	UK: Adopted Sustainable urban drainage systems (SuDs) (Mitchell, 2005; Coupe et al., 2013)	Reducing flood risk, surface water pollutant level, the pressure of the surface runoff discharge, improving amenity and environmental values (e.g. improve wildlife habitats)			

Other issues	Governance	UK: Better FRM governing structure	Complex institutional arrangement	UK: Time consuming and not <u>cost effective</u>
--------------	------------	---	-----------------------------------	---

For example, Maantay and Maroko (2009) show how in New York City, the national flood insurance scheme does not effectively reach some social groups, particularly ethnic minorities, who tend to be exposed to ~~above average~~above-average flood risk. Social equity issues tend also to be ~~under represented~~underrepresented in SFRM studies, although researchers and practitioners are increasingly alert on how resilience to flooding varies spatial-~~ly~~temporally (Yang, et al., 2021) and socially with ~~low income~~low-income households a particular concern. Similarly, economic appraisal of flood strategies ~~recognises~~recognizes environmental impacts, but ecosystem service values; and the wider benefits of nature-based flood management (Dadson et al. 2017) are nowhere routine in such economic appraisal. ~~With respect to~~Concerning flood management, the Pitt ~~review~~Review into a series of major floods in England (Pitt, 2008) highlighted that flood governance can be a major problem; ~~&~~ Pitt observed that so many organisations had responsibilities for FRM, and at a variety of geographic scales and flood types, that a high degree of institutional complexity resulted which acted as a barrier to effective FRM. ~~This problem is as~~ also seen in the US ([Rosenzweig and Solecki, 2014](#))(Rosenzweig and Solecki, 2014). Local authorities have since been given the lead role in FRM. Porter and Demeritt (2012) commend the openness and transparency of flood risk mapping but raise concerns over the degree of technical expertise needed for the public to understand and act appropriately on the information conveyed. These examples indicate that in the four countries ~~we~~ reviewed in this paper, challenges to SFRM exist. However, these tend to be challenges of an operational rather than philosophical nature, challenging the delivery of SFRM but not the principle. That is, there is now ~~a~~ widespread recognition of the need to address sustainability concerns and embed sustainability principles into FRM policy and practice.

465

3.2 Implementing SFRM in Asian coastal megacities

Currently, many Asian coastal megacities are operating predominantly within the flood control and defence paradigms, including Guangzhou, Shenzhen, and Hong Kong (Chan et al., 2013; Yang, et al., 2018), Shanghai (Balica et al., 2012), Bangkok (Keokhumcheng et al., 2012), Ho Chi Minh City (Storch and Downes, 2011; Nguyen, et al., 2021), Jakarta (Texier, 470 2008; Wannowitz and Garschagen, 2021) and Singapore (Chan et al., 2018; Chan et al., 2021). These cities all feature in the top coastal cities at risk by 2050s (Hallegatte et al., 2013), due to their growing populations, economies, and rising flood hazard. Limited room to expand has resulted in development on floodplains, wetlands, and reclaimed coastal areas (Chan et al., 2014; Ji, et al., 2021), a practice common in Asian coastal cities (Fuchs et al., 2011) and we discuss the progress of their flood management strategies in this section (see Table 4).

475 Looking at the past (before ~~the~~ 1990s), Singapore has suffered from severe ~~flood-floods~~ due to urbanisation since ~~the nationhood~~independence in 1965 (Chan et al., 2018). The Drainage Department ~~at~~of Singapore was established in 1972 in order ~~to~~to prevent floods. ~~The Government of~~ Singapore ~~government~~ invested heavily to construct ~~a~~ dense networks of drains and canals ~~is-as~~ the major approach for flood management before the 1990s (Lim, 1997), ~~which was effectively- and this~~ reduced ~~flood prone~~flood-prone areas from 6900 ha in ~~the~~ 1960s to 207 ha in the 1990s (Lim and Lu, 2016). Owing to economic 480 development, ~~Singapore was pioneered adopted~~ a Low Impact Development~~s~~ (LID~~s~~) approach (similar to SuDs in the UK) in

Formatted: Highlight

the 1990s that is the evident evidence the flood management practice has been transformed as discussed in line with the changes made in other countries, for example. This included constructed constructing stormwater retention ponds for stormwater storage and reuse at Kallang district (Lim and Lu, 2016).

Indeed, the neighbourhood coastal cities such as Bangkok, Jakarta and Ho Chi Minh City are also facing the similar issues (on urban floods) afterwards, particularly towards in their fast urbanisation and the developmental period during the early 1980s. Rapid landuse land use changes transform green spaces (e.g. agricultural and farmland, forest, wetland, etc.) into an urban area, but land drainage and flood measures were unable coping to cope with the urban runoff (Takeuchi, 1993; Jha et al., 2012; Huu, 2011; Katzachner et al., 2016). Mostly, the flood management practices before the 1990s in these cities were mainly driven by flood control and defense defence measures. Jakarta was jurisdiction under Dutch influence on for flood engineering foci in the early 1920s, which is demonstrated by the East Flood Canal Project which was constructed during the Dutch Colonial period at in 1924 and that was an extension of the Western Floodway at the city of Jakarta to alleviate urban peak discharge (Jha et al., 2012). Bangkok was dominated by the engineering approaches such as engineering works for agricultural irrigation, embankments, reservoirs, and drainage systems in the 1980s and 1990s (Bouriboun, 1998). Across the Mekong, Ho Chi Min City has also been dominated by agricultural engineering works for the agricultural production (e.g. rice and poultry, etc.) and crop protection during the storms (e.g. typhoons) before the 1990s (Huu, 2011). Likewise, Chinese coastal cities similarly faced urban floods that were enhanced by urbanisation and rapid fast developments during the "Open Door Policy" established in the late 1970s, such as urban floods in Shanghai during 1981, and later events in 2020 and 2021 because of typhoons (Chan et al., 2021; Dou, 1991). Guangzhou experienced frequent urban floods due to condensed increased population density in the major district areas e.g. such as Tianhe, Baiyun, etc. (Zou, 2012). Engineering approaches (e.g. flood walls, dykes, drainage canals, pumping stations, and dredging engineering works) were popular and applicable before the 1990s in both cities (Zou, 2012; Meng and Dubrowski, 2016).

During the 2000s, these coastal cities also gradually transformed moved to considering wider aspects on of social socio-economic risk and health issues of in the communities and these have started to be considered in the FRM policy implementation. For example, in Jakarta, the municipal authorities initiated non-structural measures including an early warning system, health service capacity building, and contingency planning including relocation and compensation schemes after the 2002 and 2007 floods, having as realised having realised that engineering works was were insufficient to protect the communities (WHO, 2007; World Bank, 2009). In Bangkok, the Thai government still favoured preferred using engineering works to further strengthen the flood engineering works defence (e.g. dykes, drainage system, canals, and retention area) that focusing focussed on improving the engineering technology of flood mitigation, but also established the emergency response measures such as identified evacuation areas in Bangkok Metropolitan districts (Chen, 2007; Phamompol, 2011). In Ho Chi Minh City, social economy social economic implementation started was initiated reform started in the late 1980s. The Vietnamese authorities and enhanced opted for rapid urban expansion and deforestation due to the pressure of economic growth. During that period, the authorities have a limited that was with limited consideration on urban floods flood consideration, and still rely on engineered measures on flood issues (Krystian and Nguyen, 2005; Labbé, 2010), and later in

the 1990s started considering flood relocation and relocated over 1 million people away from frequent flood zone (Danh and Mushtaq, 2011).

515 Across China, taking account into Shanghai, for example In Shanghai, the authorities started to recognise a “risk-based” flood management strategy. FRM approach flood risk has been recognised as a step-ahead as the municipality government understood the importance of learning “flood risk” analyses and information to evaluate the hazards and potential responses on measures because of frequent typhoons and relevant disasters (e.g. 2 to 3 times per year) (Lu, 2010). For example, the 520 Shanghai authority acted to raise the flood protection level of coastal defence from 1-in-100 to 1-in-1000 years protection level during the early 2000s (Yin et al., 2015; Zhou et al., 2016). In Guangzhou, the municipality government similarly reacted after frequent floods in the late 1990s and adopted flood risk measures (Wong and Zhao, 2001). The authorities then promoted the green infrastructure (e.g. via “Green-blue network” in NanSha District) to protect ecological and increased the hydrological risk understanding and recognised cultural value by 525 conservation of heritage out of flood impacts (Timmeren, 2014; Han et al., 2015).

525 In China, Shanghai and Guangzhou governments have moved steps forward that in aligned alignment with the National Climate Change strategy. For example, Guangzhou has followed the National 12th Five Year Plan included a National Adaptation Strategy (NAS) for climate change (UNDP China, 2012), and established a scientific warning system that based on accurate flood risk information (Lyu et al., 2016). Shanghai was identified as one of the most vulnerable Chinese cities 530 under climate change (Hallegatte et al., 2013; Francesch-Huidobro et al., 2017; Yuan et al., 2017). The authority further established the flood monitoring and forecast systems were established and the Meteorological Office worked with the IPCC on climate (e.g. sea level rise) projections to further improve public emergency warning, planning, and public preparedness (Li, 2015). Singapore is transforming from a “City in a Garden” to a “City of Gardens and Water”. Singapore The government 535 Government is also taking a role to further implementing the “Active Beautiful Clean” (ABC) Waters Program for delivering sustainable and climate-resilient measures on urban stormwater management and adopted the “source-pathway-receptor” (SPR) model to address flood risk and climate change (Chan et al., 2018; Liao 2019).

540 In fact, Climate change is raising sea levels sea levels making storm surges more hazardous (Nicholls, 2011), and is increasing the frequency, intensity, and magnitude of storms (typhoons), intense rainfall events, and sea surges (Webster, 2008; Webster et al., 2005). Natural resource extraction is also increasing flood hazard through the land subsidence it causes; for example, in the coastal area of Bangkok groundwater extraction has resulted in subsidence of two metres since 1970 (Syvitski et al., 2009). The cities that are selected in this review rely upon hard engineered hard-engineered defences and their previous ways to deal with flooding, but these structures offer a relatively low degree of protection. For example, the major urban drainage systems in Singapore have been improved from 1-in-50 years years up to 1-in-100 years years, whilst Guangzhou and Shenzhen only have a 1-in-20-year return period protection against typhoon and sea surge surges (Chan et al., 2012; Chan et al., 2018). For 545 example Further, fatalities occurred in Hong Kong in 2010 when pluvial flooding overwhelmed the 1-in-50-year protection level protection defences, whilst Shenzhen only has a 1-in-20-year return period protection against typhoon typhoons and sea surge surges (Chan et al., 2012).

Confront with Climate Change, the existing ~~Such~~ levels of protection are not enough. There is urgency improving flood protection standards which are modest and likely many investment in flood protection standards have been financially but weaken need to address social and environmental perspectives altogether finding future flood hazard need in the name of flood risk but hardly reduced which ~~that~~ is been been done among the Asian cities move more future towards SFRM We have been using other by learning from the global lessons and experiences ~~(from 4 countries)~~ that and that destined ways forward on flood management extensively in other Asian cities

550

Table 4: Development of flood management practices in selected E. and S.E. Asian cities

City	Flood management practice in Asian cities relative to dominant flood paradigm in the West		
	Before <u>the</u> 1990s Flood protection (control and <u>defended</u> <u>defence</u>)	2000s Flood risk management (FRM)	Post-2000s Sustainable flood risk management (SFRM)
Jakarta, Indonesia	Solely engineering response with Dutch colonisation influence (Jha et al., 2012).	FRM practice develops after <u>the</u> 2002 and 2007 floods. Non-structural measures were implemented in the Urgent Flood Mitigation Project (WHO, 2007; World Bank, 2009).	Improving resilience e.g. established the Coastal Defense Strategy (JCDS) in 2014 (Hidayatno et al., 2017).
Bangkok, Thailand	Practice focused on engineering solutions (Takeuchi, 1993; Bourbouin, 1998).	Improved flood engineering technology (e.g. dykes, drainage system, etc.) and identified evacuation areas at the Metropolitan Administration (Chen, 2007; Phamornpol, 2011).	Established the community resilience plans, recognised flood risk after 2011 big floods (Berkowitz, 2013; Supachai, 2016).
Ho Chi Minh City, Vietnam	Irrigation canals and agricultural engineering works dominated to protect crops (Huu, 2011; Katzschnier et al, 2016).	Doi Moi social market economy reforms and dominated engineered measures (Krystian and Nguyen, 2005; Labb��, 2010). In the late 1990s, initiated flood relocation scheme in flood zones (Danh and Mushtaq, 2011).	Integrated flood management <u>was</u> established (Eckert and Huynh, 2016).
Guangzhou, China	Engineered measures to protect settlements (Zou, 2012; Meng and Dubrowski, 2016).	Combat flood risk in various practices (Wong and Zhao, 2001); Promote ecological and cultural value (Timmeren, 2014; Han et al., 2015).	Guangzhou improved <u>the</u> flood warning system and adopted <u>a</u> Climate Change resilience plan (Lyu et al., 2016).
Shanghai, China	Flood management focused on engineering works (Dou, 1991; Ke, 2014).	The municipal government extended flood risk analysis and raised <u>the</u> level of protection to 1 in 1000-year flood (Yin et al., 2015; Zhou et al., 2016).	Shanghai Meteorological Office worked with the IPCC on climate (e.g. sea-level rise) projections and improved resilience measures (Li, 2015).
Singapore	Singapore government invested <u>on-in</u> engineering works to alleviate floods in 1972 (Lim, 1997; Lim and Lu, 2016; Chan et al., 2018).	Pioneered in SE Asia to establish the LID practices after <u>the</u> 1990s (Lim and Lu, 2016).	ABC Waters Program <u>was</u> launched that based on BGI and LID in 2006 (Liao, 2019). Addressing climate change with <u>the</u> SPR model (Chan et al., 2018 and Liao 2019).

However, aA key impetus of the shift in practice from the flood protection and defence paradigms, to SFRM, has been a recognition that the costs of traditional hard engineered flood defences are increasingly unaffordable, and that a wider package of measures is needed to address flood risk. As learntlearned in the aftermath of the Hurricane Katrina disaster in New Orleans,

560 FRM also requires better development of non-engineered measures (e.g. conduct a Multi-Criteria Decision Analysis (MCDA) on considering alternative strategies), ranging from strategic land use planning with substantive public participation (Neville and Coats, 2009), specific attention to the most vulnerable communities (including insurance to aid recovery) (Chamlee-Wright and Storr, 2009; Burby, 2006), and well-prepared emergency and evacuation plans for when floods strike (Niedoroda et al. 2010). All of these should be considered through a Multi-Criteria Decision Analysis of alternative strategies). Experience with Hurricane Harvey in 2017 suggests that even if these lessons have been learnt learned, Flood-flood risk may remain high due 565 to a legacy effect of past land use and land-use planning and investment decisions.

Hard engineered flood protection measures will always be important in the defence of Asian cities, but whilst these defences can be more coherently planned (Francesch-Huidobro et al., 2017), evidence indicates that the level of protection needed is unaffordable (Jongman et al., 2014). Despite the apparent limitations of relying solely on structural defences, few efforts have yet been made to adopt a wider set of measures that incorporate non-structural protection measures, pre-emptive strategic and 570 land use planning, risk awareness and communication, emergency planning, and post-event recovery and learning.

Current approaches also tend to focus on potential economic losses, neglecting the role and value of the natural environment and social considerations, such as impacts and recovery potential of different social groups, and participatory planning. Indeed, most Asian cities (even those with high flood risk) remain focussed focused on hard engineering solutions (refer to Table 4) and lack a sufficient range of climate change adaptation guidance and practice (Nguyen, et al., 2021), which may prove 575 problematic as sea-level rises, and extreme storms, surges, and typhoons become more frequent. Given the lack of unaffordability of the level of engineered defences necessary to mitigate their rising flood risk, Asian coastal megacities may find it advantageous to recognise the the wider international experience, and develop coping strategies that reflect a greater acceptance of options to of 'Living with flood risk' rather than assume that all such risk can be engineered away. Such coping strategies combine traditional engineering, soft engineering (e.g. SuDs), land-use planning, working with rather than against 580 nature, and social strategies that recognise vulnerable communities, and engage stakeholders in the co-production of responses to flood-flood risk. The international experience clearly shows that the SFRM approach is more complex than control or defend, hence significant operational and procedural challenges can be expected, with good governance needed to engage stakeholders effectively whilst avoiding undue institutional complexity.

4 Conclusion

585 In Asian coastal megacities, flood risk is high and rising, and defending against flooding effectively using traditional approaches is becoming financially unsustainable. Coping with flood risk, as illustrated by 'Room for river' River' type concepts, and through 'soft measures', as discussed above, is in some countries increasingly considered a necessary and more sustainable alternative to hard-engineered defences alone.

The case studies in the four countries showed demonstrate some good important lessons to for achieve achieving long term 590 SFRM direction to deliver flood management practices consistent with social socio-economic and environmental concerns. We

understand accept that different countries and cities have their own interpretation on of SFRM- but recommend policy makers that policymakers to adopt “mixed options” towards thinking about for long term and-sustainability that with social, economic, and environmental considerations.

However, this is a philosophy that has had relatively little influence on practice in the coastal megacities of Asia. There is, of course, no prescriptive template for developing coping strategies, and each country and city will need and wish to develop measures appropriate to their specific contexts - physical, social and o-economic, environmental, and cultural. We are fully understood that needs to be qualified concerning It is clear that Specific local knowledge (i.e. circumstances, contexts and constraints) in Asian coastal cities/megacities will need to be taken into account considered.

For very dense coastal megacities ‘making space for water’ opportunities may be rather more limited than they are elsewhere in the world, such that coping strategies will develop with different emphases. Once the limitations of hard-engineered defences are recognised and understood, sustainable development principals-principles and tools can be used to shape coping strategies and help deliver more flood resilient cities.

References

Aerts, J.C.J.H., Lin, N., Botzen, W., Emanuel, K., de Moel, H.: Low-Probability Flood Risk Modeling for New York City, 605 Risk Analysis, 33, 772-788, <https://doi.org/10.1111/risa.12008>, 2013.

Arnell, N.W.: Flood hazard management in the United States and the National Flood Insurance Program, Geoforum, 15, 525-542, [https://doi.org/10.1016/0016-7185\(84\)90023-X](https://doi.org/10.1016/0016-7185(84)90023-X), 1984.

Ashley R., Gersonius B. and Horton B. Managing flooding: from a problem to an opportunity. Royal Society Philosophical Transactions A. 378, 2169, <http://doi.org/10.1098/rsta.2019.0214>, 2020.

Böhm, H.R., Haupter, B., Heiland, P., Dapp, K.: Implementation of flood risk management measures into spatial plans and policies, River Research and Applications, 20, 255-267, <https://doi.org/10.1002/rra.776>, 2004.

Bagstad, K.J., Stapleton, K., D'Agostino, J.R.: Taxes, subsidies, and insurance as drivers of United States coastal development, Ecological Economics, 63, 285-298, <https://doi.org/10.1016/j.ecolecon.2006.09.019>, 2007.

615 Ball, T., Werritty, A., Geddes, A.: Insurance and sustainability in flood-risk management: the UK in a transitional state, Area, 45(3), 266-272, <https://doi.org/10.1111/area.12038>, 2013.

Beck, S.: Between Tribalism and Trust: The IPCC Under the "Public Microscope", Nature and Culture, 7, 151-173, <https://doi.org/10.3167/nc.2012.070203>, 2012.

Berke, P.R.: Why is Houston so vulnerable to devastating floods? BBC News. Available at: <https://www.bbc.com/news/world-us-canada-41107049>. Accessed at: August 5th 2019, 2017.

620 Bouriboun S.: Food and Agriculture Organization. Flood management and mitigation in the Mekong River Basin. Available at: (<http://www.fao.org/docrep/004/ac146e/AC146E01.htm>) Accessed at: August 20th 2017, 1998.

Brody, S., Kang, J., Bernhardt, S.: Identifying factors influencing flood mitigation at the local level in Texas and Florida: the role of organizational capacity, *Natural Hazards*, 52, 167-184, 10.1007/s11069-009-9364-5, 2008.

625 Brown, J.D., Damery, S.L.: Managing flood risk in the UK: towards an integration of social and technical perspectives, *Transactions of the Institute of British Geographers*, 27, 412-426, <https://doi.org/10.1111/1475-5661.00063>, 2002.

Brundtland, G.H.: Our common future—Call for action. *Environmental Conservation*, 14(4), 291-294, <https://doi.org/10.1017/S0376892900016805>, 1987.

Burby, R.J.: Flood insurance and floodplain management: the US experience, *Global Environmental Change Part B: Environmental Hazards*, 3, 111-122, <https://doi.org/10.3763/ehaz.2001.0310>, 2001.

630 Burby, R. J.: Hurricane Katrina and the paradoxes of government disaster policy: Bringing about wise governmental decisions for hazardous areas, *The annals of the American academy of political and social science*, 604, 171-191, <https://doi.org/10.1177%2F0002716205284676>, 2006.

Bureau of Meteorology, "What is a Tropical Cyclone?", Bureau of Meteorology, Melbourne, Australia. Available at: <http://www.bom.gov.au/other/accessibility.shtml?ref=ftr> Accessed on December 12th 2021.

635 Burgess, K., Jay, H., Nicholls, R.J., Green, C., Penning-Rowsell, E.C.: Assessment of future coastal erosion risk, Thomas Telford, 2007.

Butler, C., Pidgeon, N.: From 'flood defence' to 'flood risk management': exploring governance, responsibility, and blame, *Environment and Planning C: Government and Policy*, 29, 533-547, <https://doi.org/10.1068%2Fc09181j>, 2011.

640 Chamlee-Wright, E., Storr, V.H.: "There's no place like New Orleans": a sense of place and community recovery in the Ninth Ward after Hurricane Katrina, *Journal of Urban Affairs*, 31, 615-634, <https://doi.org/10.1111/j.1467-9906.2009.00479.x>, 2009.

Chan, F., Adekola, O., Ng, C., Mitchell, G., McDonald, A.: Coastal Flood-Risk Management Practice in Tai O, a Town in Hong Kong, *Environmental Practice* 15, 1-19, <https://doi.org/10.1017/S1466046613000215>, 2013a.

645 Chan, F., Mitchell, G., Cheng, X., Adekola, O., McDonald, A.: Developing a Sustainable Flood Risk Appraisal (SFRA) Framework for the Pearl River Delta, Environment and Urbanization Asia, 4, 301-323, <https://doi.org/10.1177%2F0975425313510770>, 2013b.

Chan, F., Mitchell, G., McDonald, A.T.: Flood risk appraisal and management in mega-cities: a case study of practice in the Pearl River Delta, China, *Water Practice & Technology*, 7, 1-9, <https://doi.org/10.2166/wpt.2012.060>, 2012.

650 Chan, F., Wright, N., Cheng, X., Griffiths, J.: After Sandy: Rethinking Flood Risk Management in Asian Coastal Megacities, *Natural Hazards Review*, 15, 101-103, 2014.

Chan F., Joon C.C., Ziegler A., Dabrowski M. and Varis O.: Towards resilient flood risk management for Asian coastal cities: lessons learned from Hong Kong and Singapore, *Journal of Cleaner Production*, 187, 576-589, <https://doi.org/10.1016/j.jclepro.2018.03.217>, 2018.

655 Chan, F., Yang, L.E., Scheffran, J., Mitchell, G., Adekola, O., Griffiths, J., Chen, Y., Li, G., Lu, X., Qi, Y., Li, L., Zheng, H., McDonald, A.: Urban flood risks and emerging challenges in a Chinese delta: The case of the Pearl River Delta, *Environmental Science & Policy*, 122, 101-115, <https://doi.org/10.1016/j.envsci.2021.04.009>, 2021.

Chan, F., Gu, X., Qi, Y., Thadani, D., Chen, Y. D., Lu, X., Li, L., Griffiths, J., Zhu, F., Li, J. & Chen, W. Y. Lessons learnt from Typhoons Fitow and In-Fa: implications for improving urban flood resilience in Asian Coastal Cities. *Natural Hazards*, 2021.

660

Changnon, S.A.: The Historical Struggle with Floods on the Mississippi River Basin -- Impacts of Recent Floods and Lessons for Future Flood Management and Policy, *Water International*, 23, 263 – 271, <https://doi.org/10.1080/02508069808686781>, 1998.

665 Coupe, S.J., Faraj, A.S., Nnadi, E.O., Charlesworth, S.M.: Integrated Sustainable Urban Drainage Systems, Water Efficiency in Buildings: Theory and Practice, 147-163, 2013.

Crichton, D.: Towards a Comparison of Public and Private Insurance Responses to Flooding Risks, *International Journal of Water Resources Development*, 24, 583-592, <https://doi.org/10.1080/07900620801923161>, 2008.

Criss, R.E., Shock, E.L.: Flood enhancement through flood control, pp. 875-878, [https://doi.org/10.1130/0091-7613\(2001\)029%3C0875:FETFC%3E2.0.CO;2](https://doi.org/10.1130/0091-7613(2001)029%3C0875:FETFC%3E2.0.CO;2), 2001.

670 Dadson, S.J., Hall, J.W., Murgatroyd, A., Acreman, M., Bates, P., Beven, K., Heathwaite, L., Holden, J., Holman, I.P., Lane, S.N. and O'Connell, E. March.: A restatement of the natural science evidence concerning catchment-based 'natural' flood natural flood management in the UK, *Physical and Engineering Sciences*, 473(2199), 2016.

Danh, V. T. and S. Mushtaq.: Living with floods: an evaluation of the resettlement program of the Mekong Delta of Vietnam, In Environmental change and agricultural sustainability in the Mekong Delta (pp. 181-204), 2011.

675 DCLG.: Development and Flood Risk: A practice guide companion to PPS25 'Living Draft', Crown Copyright London, 2007. DCLG.: National Planning Policy Framework, Crown Copyright London, 2012.

De Bruijn, K.M., Green, C., Johnson, C., McFadden, I., Begum, S., Stive, M.J.F.: Flood risk management in Europe. Innovation in policy and practice. Springer The Netherlands, 2007.

680 Defra.: Making Space for Water: Taking Forward a New Government Strategy for Flood & Coastal Erosion Risk Management Encouraging and Incentivising Increased Resilience to Flooding, 2007.

Dou Z.: A Round-up of Shanghai City flood management construction. Yangtze River. Vol.22 No. 8 in Chinese, 1991.

Eckert, R. & Huynh. L. H. C.: Climate Responsive Neighborhoods Neighbourhoods for HCMC: Compact City vs. Urban Landscape. Sustainable Ho Chi Minh City: Climate Policies for Emerging Mega Cities. Springer International Publishing, 685 2016.

Environment Agency.: Live Flood Warning Map Environment Agency, London, England, 2014b.

Environment Agency.: Risk of Flooding from Surface Water Environment Agency, London, England, 2014c.

690 Environmental Protection Agency.: Flood Resilience – A Basic Guide for Water and Wastewater Utilities. Office of Water, United States of America, 2014.

Evans, E., Hall, J., Penning-Rowsell, E., Sayers, P., Thorne, C., Watkinson, A.: Water Management 159, 53, 2006.

Evans, E.P., Ashley, R., Hall, J.W., Penning-Rowsell, E.P., Saul, A., Sayers, P.B., Thorne, C.R., Watkinson, A.: Foresight Future Flooding, Scientific Summary: Volume 1: Future Risks and their Drivers, 2004.

Fan, Juan, and Guangwei Huang.: Evaluation of Flood Risk Management in Japan through a Recent Case, Sustainability 12, 695 no. 13: 5357, <https://doi.org/10.3390/su12135357>, 2020.

Fleming, G.: How can we learn to live with rivers? The findings of the Institution of Civil Engineers Presidential Commission on flood-risk management. Philosophical transactions, Series A, Mathematical, physical, and engineering sciences, 360, 1527-1530, <https://doi.org/10.1098/rsta.2002.1014>, 2002.

Flood Risk Management (FRM) and Urban Resilience Workshop.: The Global Facility for Disaster Reduction and Recovery 700 (GFDRR) Workshop Proceedings, 2-3 May 2012, Jakarta, Indonesia, 2012.

Francesch-Huidobro, M., Dabrowski, M., Tai, Y., Chan, F., & Stead, D.: Governance challenges of flood-prone delta cities: integrating flood risk management and climate change in spatial planning, Progress in Planning 114, 1-27, <https://doi.org/10.1016/j.progress.2015.11.001>, 2017.

Fuchs, R., Conran, M., Louis, E.: Climate Change and Asia's Coastal Urban Cities-: Can they-They Meet the Challenge?, 705 Environment and Urbanization Asia 2, 13-28, <https://doi.org/10.1177%2F097542531000200103>, 2011.

Fujita, M., Hamaguchi, N.: Japan and economic integration in East Asia: post-disaster scenario, Ann Reg Sci 48, 485-500, 10.1007/s00168-011-0484-y, 2012.

Galloway, G.E., Balabanis, P., Bronstert, A., Casale, R., Samuels, P.: In Ribamod. River Basin Modeling, Management and Flood Mitigation. Concerted Action, 1999.

Gerritsen, H.: What happened in 1953? The Big Flood in the Netherlands in retrospect, Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences 363, 1271-1291, <https://doi.org/10.1098/rsta.2005.1568>, 2005.

Graf, W.L.: Geomorphology and American dams: The scientific, social, and economic context, Geomorphology, 71, 3-26, <https://doi.org/10.1016/j.geomorph.2004.05.005>, 2005.

Green, C.: Competent authorities for the flood risk management plan – reflections on flood and spatial planning in England, 715 Journal of Flood Risk Management, 10(2), 195-204, DOI10.1111/jfr3.12097, 2014.

Green, C.H., Tunstall, S.M., Fordham, M.H.: The Risks from Flooding: Which Risks and Whose Perception?, 15(3), 227-236 <https://doi.org/10.1111/j.1467-7717.1991.tb00456.x>, 1991.

Hall, J.W., Evans, E.P., Penning-Rowsell, E.C., Sayers, P.B., Thorne, C.R., Saul, A.J.: Quantified scenarios analysis of drivers and impacts of changing flood risk in England and Wales: 2030–2100, Environmental Hazards, 5, 51-65, 2003.

720 Hallegatte, S., Green, C., Nicholls, R. J., & Corfeemorlot, J.: Future flood losses in major coastal cities, Nature Climate Change, 3(9), 802-806, 2013.

Hamin, E.M., Abunnasr, Y., Ryan, R.L.: Planning for climate change-: a reader in green infrastructure and sustainable design for resilient cities. Routledge, New York, NY, 2019.

Han J., Pan H., Zhang G., Sun H.: Innovative Practice of Green Infrastructure Planning- Example as Guangzhou Nansha New
725 Distract Mingzhu Bay Core Distract, Construction Technology, (16), 47-50. In Chinese, 2015.

Hanson, S., Nicholls, R., Ranger, N., Hallegatte, S., Corfee-Morlot, J., Herweijer, C., Chateau, J.: A global ranking of port
cities with high exposure to climate extremes, Climatic Change, 104, 89-111, 2011.

Hey, R.D., Heritage, G.L., Patteson, M.: Impact of flood alleviation schemes on aquatic macrophytes, pp. 103-119, 1994.

Hooijer, A., Klijn, F., Pedroli, G.B.M., Van Os, A.G.: Towards sustainable flood risk management in the Rhine and Meuse
730 river basins: synopsis of the findings of IRMA-SPONGE. River Research and Applications 20, 343-357, 2004.

Huang, G.: A Comparative Study on Flood Management in China and Japan. Water, 6, 2821-2829.
<https://doi.org/10.3390/w6092821>, 2014.

Hudson, P.F., Middelkoop, H., Stouthamer, E.: Flood management along the Lower Mississippi and Rhine Rivers (The
Netherlands) and the continuum of geomorphic adjustment, Geomorphology 101, 209-236,
735 <https://doi.org/10.1016/j.geomorph.2008.07.001>, 2008.

Hulme, M., Jenkins, G.J., Lu, X., Turnpenny, J.R., Mitchell, T.D., Jones, R.G., Lowe, J., Murphy, J.M., Hassell, D., Boorman,
P., McDonald, R., Hill, S.: Climate Change Scenarios for the United Kingdom: The UKCIP02 Scientific Report, 2002.

Hutter, G.: Strategic Planning for Long-Term Flood Risk Management: Some Suggestions for Learning How to Make Strategy
at Regional and Local Level, International Planning Studies 12, 273 – 289, <https://doi.org/10.1080/13563470701640168>, 2007.

Huu, P. C.: Planning and implementation of the dyke systems in the mekong-Mekong delta, Vietnam, Pedobiologia, 54(4),
740 217-224, 2011.

Ikeda, S., Sato, T., Fukuzono, T.: Towards an integrated management framework for emerging disaster risks in Japan. Natural
Hazards 44, 267-280, 2008.

Japan International Cooperation Agency (JICA).: The project for capacity development of Jakarta Comprehensive Flood
745 Management in Indonesia technical cooperation report comprehensive flood management plan, 2013.

Janssen, J.A.E.B.: On peaks and politics; governance analysis of flood risk management cooperation between Germany and
the Netherlands, International Journal of River Basin Management, 6, 349 – 355,
<https://doi.org/10.1080/15715124.2008.9635362>, 2008.

Jha, A. K., Bloch, R., & Lamond, J.: Cities and Flooding: A Guide to Integrated Urban Flood Risk Management for the 21st
750 Century. The World Bank, Washington DC, 2012.

Ji, T., Wei, H.H., Sim, T., Yang, L.E., Scheffran, J.: Disaggregated validation of disaster-resilience indicators using household
survey data: A case study of Hong Kong, Sustainable Cities and Society, 67, 102726,
<https://doi.org/10.1016/j.scs.2021.102726>, 2021.

Johnson, C., Penning-Rowsell, E., Parker, D.: Natural and imposed injustices: the challenges in implementing ‘fair’ flood risk
755 management policy in England, Geographical Journal, 173, 374-390, <https://doi.org/10.1111/j.1475-4959.2007.00256.x>, 2007.

Johnson, C.L., Priest, S.J.: Flood Risk Management in England: A Changing Landscape of Risk Responsibility? International
Journal of Water Resources Development, 24, 513-525, 2008.

Jongman, B., Koks, E.E., Husby, T.G., Ward, P.J.: Increasing flood exposure in the Netherlands: implications for risk financing, Natural Hazards and Earth System Sciences, 14(5), 1245-1255, <https://doi.org/10.5194/nhess-14-1245-2014>, 2014.

760 Katzschnner, A., Waibel, M., Schwede, D., Katzschnner, L., Schmidt, M., & Storch, H.: Sustainable Ho Chi Minh City: Climate Policies for Emerging Mega Cities. Springer International Publishing, Switzerland, 2016.

Ke, Q.: Flood risk analysis for metropolitan areas – a case study for shanghai. Civil Engineering & Geosciences, PhD thesis, Delft University of [Technology](#), Delft, the Netherlands, 2014.

Keokhumcheng, Y., Tingsanchali, T., Clemente, R.S.: Flood risk assessment in the region surrounding the Bangkok 765 Suvarnabhumi Airport, Water International, 37, 201-217, <https://doi.org/10.1080/02508060.2012.687868>, 2012.

Klijn, F., Samuels, P., Van Os, A.: Towards flood risk management in the EU: State of affairs with examples from various European countries, International Journal of River Basin Management, 6, 307-321, <https://doi.org/10.1080/15715124.2008.9635358>, 2008.

770 Klijn, F., Van Buuren, M., Van Rooij, S.A.M.: Flood-risk management strategies for an uncertain future: Living with rhine river floods in the Netherlands? AMBIO: A Journal of the Human Environment, 33(3), 141-147, <https://doi.org/10.1579/0044-7447-33.3.141>, 2004.

Klima, K., Lin, N., Emanuel, K., Morgan, M.G., Grossmann, I.: Hurricane Modification and Adaptation in Miami-Dade County, Florida, Environmental Science & Technology, 46, 636-642, <https://doi.org/10.1021/es202640p>, 2011.

Krystian W. Pilarczyk, & Nguyen Si Nuoi.: Experience and practices on flood control in Vietnam, Water International, 30(1), 775 114-122, <https://doi.org/10.1080/02508060508691843>, 2005.

Kundzewicz, Z.W., Budhakooncharoen, S., Bronstert, A., Hoff, H., Lettenmaier, D., Menzel, L., Schulze, R.: Coping with variability and change: Floods and droughts, Natural Resources Forum, 26, 263-274, <https://doi.org/10.1111/1477-8947.00029>, 2002.

780 Kundzewicz, Z. W.: Flood protection – sustainability issues, Hydrological Sciences Journal, 44(4), 559-571, <https://doi.org/10.1080/0262669909492252>, 1999.

Kundzewicz, Z.W., Takeuchi, K.: Flood protection and management: quo vadimus? Hydrological Sciences Journal, 44, 417-432, <https://doi.org/10.1080/0262669909492237>, 1999.

785 Lawson E, Farmani R, Woodley E, Butler D. [A Resilient and Sustainable Water Sector: Barriers to the Operationalisation of Resilience](#). Sustainability. 2020; 12(5):1797. <https://doi.org/10.3390/su12051797>

Li, Y.: Protection of shanghai from flooding. Master thesis. Delft University of Technology, Delft, the Netherlands, 2015.

Link, L.E.: The anatomy of a disaster, an overview of Hurricane Katrina and New Orleans, Ocean Engineering 37, 4-12, <https://doi.org/10.1016/j.oceaneng.2009.09.002>, 2010.

Liao, K. H.: The socio-ecological practice of building blue-green infrastructure in high-density cities: what does the ABC Waters Program in Singapore tell us? Socio-Ecological Practice Research, 1(1), 67-81, 2019.

790 Lim, M.C., 1997. Drainage planning and control in the urban environment: The Singapore experience, Environmental Monitoring and Assessment, 44: 183-197.

Lim, H. S., & Lu, X. X.: Sustainable urban stormwater management in the tropics: An evaluation of Singapore's ABC Waters Program. *Journal of Hydrology*, 538, 842-862, <https://doi.org/10.1016/j.jhydrol.2016.04.063>, 2016.

795 Lo, A.Y., Chan, F.K.S.: Preparing for flooding in England and Wales: the role of risk perception and the social context in driving individual action. *First Online* (17th April 2017), 1-21. DOI: 10.1007/s11069-017-2870-y, 2017.

Lu Y.: Impacts of Climate Change on Shanghai Flood Prevention. Shanghai Water Engineering Design & Research Institute Available at: <https://www.atse.org.au/Documents/International%20Collaboration/Workshops/Aust%20China%20Science%20and%20Tech/Climate%20Change/Yongjin.pdf>. Accessed at: 23rd August 2017.

800 Longenecker, G.: HAZUS-MH Coastal Flood Module: FEMA Region IV Standard Operating Procedure For Coastal Flood Hazard & Loss Analysis, 2008.

Lumbroso, D., Stone, K., Vinet, F.: An assessment of flood emergency plans in England and Wales, France and the Netherlands, *Natural Hazards*, 58, 341-363, 2011.

805 Lyu, H. M., Wang, G. F., Shen, J., Lu, L. H., & Wang, G. Q.: Analysis and GIS mapping of flooding hazards on 10 May 2016, Guangzhou, China. *Water*, 8(10), 447, <https://doi.org/10.3390/w8100447>, 2016.

Maantay, J., Maroko, A.: Mapping urban risk: Flood hazards, race, & environmental justice in New York, *Applied Geography* 29, 111-124, <https://doi.org/10.1016/j.apgeog.2008.08.002>, 2009.

Meehan R.: Thailand Floods 2011: Causes and Prospects from an Insurance Perspective. *Stanford University Footnotes* 17, United States, 2012.

810 Meehl, G.A., Covey, C., Taylor, K.E., Delworth, T., Stouffer, R.J., Latif, M., McAvaney, B., Mitchell, J.F.B.: The WCRP CMIP3 multimodel dataset: A new era in climate change research. *Journal Name: Bulletin of the American Meteorological Society; Journal Volume: 88; Journal Issue: 9; Other Information: DOI: 10.1175/BAMS-88-9-1383, Medium: X; Size: page(s) 1383-1394, 2007.*

Meng, M., & Dubrwoiski, M.: The governance of flood risk planning in Guangzhou, China: using the past to study the present. 815 International Planning History Society Proceedings, Delft University of Technology, the Netherlands, 2016.

Michel-Kerjan, E., Kunreuther, H.: Redesigning Flood Insurance. *Science* 333, 408-409, <https://doi.org/10.1126/science.1202616>, 2011.

Mitchell, G.: Mapping hazard from urban non-point pollution: a screening model to support sustainable urban drainage planning. *Journal of Environmental Management* 74, 1-9, <https://doi.org/10.1016/j.jenvman.2004.08.002>, 2005.

820 MILT.: About Comprehensive Flood Risk Management Measures. Available online: https://www.mlit.go.jp/river/shinngikai_blog/past_shinngikai/gaiyou/seisaku/sougouchisui/pdf/2_1haikei_keii.pdf (accessed on 1 July 2021).

MLIT.: Kasen Kankyo no Seibi, Hozen no Torikumi [An approach to the maintenance and keep up of river environments], in: Ministry of Land, I., Transport and Tourism (Ed.), Tokyo, 2008.

825 MLIT.: 100 mm/h Safety Plan. Available online: <https://www.mlit.go.jp/common/001011616.pdf> (accessed on 1 August 2021), 2013.

MILT.: The 2018 amendment of the Act on Special Measures concerning Urban Reconstruction. Available online: <http://www.mlit.go.jp/toshi/common/001283640.pdf> (accessed on 1 July 2021), 2018.

Morse, S.: Post-sustainable development, Sustainable Development, 16, 341-352, <https://doi.org/10.1002/sd.354>, 2008.

830 National Association of Insurance Commissioners and the Center for Insurance Policy and Research.: Flood Risk and Insurance. Available at: (https://www.naic.org/documents/cipr_study_1704_flood_risk.pdf). Accessed at: August 5th 2019, 2017.

National Oceanic and Atmospheric Administration.: 2018's Billion Dollar Disasters in Context. Available at: (<https://www.climate.gov/news-features/blogs/beyond-data/2018s-billion-dollar-disasters-context>). Accessed at: August 5th 835 2019, 2019.

National Weather Service.: Weather-Related Fatality and Injury Statistics. Available at: (<https://www.weather.gov/hazstats>). Accessed at: August 5th 2019, 2018.

Nguyen, M.T., Sebesvari, Z., Souvignet, M., Bachofer, F., Braun, A., Garschagen, M., Schinkel, U., Yang, L.E., Nguyen, L.H., Hochschild, V., Assmann, A., Hagenlocher, M.: Understanding and assessing flood risk in Vietnam: Current status, persisting 840 gaps, and future directions, Journal of Flood Risk Management, 14(2), e12689, <https://doi.org/10.1111/jfr3.12689>, 2021.

Nicholls, R.J.: Planning for the impacts of sea level rise, Oceanography, 24, 144 – 157, 2011.

Nedoroda, A.W., Resio, D.T., Toro, G.R., Divoky, D., Das, H.S., Reed, C.W.: Analysis of the coastal Mississippi storm surge hazard, Ocean Engineering 37, 82-90, <https://doi.org/10.1016/j.oceaneng.2009.08.019>, 2010.

OECD. OECD Studies in Risk Management Japan-Floods.: Available online: <https://www.oecd.org/japan/37378001.pdf> 845 (accessed on 1 July 2021), 2006.

Olivier, H., Wytze, S.: Flood standards or risk analyses for polder management in the Netherlands, 55(S1), S113-S119, <https://doi.org/10.1002/ird.249>, 2006.

Parker, D., Fordham, M.: An evaluation of flood forecasting, warning and response systems in the European Union. Water Resources Management 10, 279-302, 1996.

850 Pearce, D., Hamilton, K., Atkinson, G.: Measuring sustainable development: progress on indicators. Cambridge Journals Online, pp. 85-101, 1996.

Penning-Rowsell, E., Johnson, C., Tunstall, S.: 'Signals' from pre-crisis discourse: Lessons from UK flooding for global environmental policy change? Global Environmental Change, 16, 323-339, <https://doi.org/10.1016/j.gloenvcha.2006.01.006>, 2006.

855 Penning-Rowsell, E.C., Chatterton, J.B.: The Benefits of Flood Alleviation: A Manual of Assessment Techniques (The Blue Manual), 1977.

Penning-Rowsell, E.C., Green, C.: New Insights into the Appraisal of Flood-Alleviation Benefits: (1) Flood Damage and Flood Loss Information, Water and Environment Journal, 14(5), 347-353, <https://doi.org/10.1111/j.1747-6593.2000.tb00272.x>, 2000.

860 Phamornpol K.: Flood Mitigation and Management in Bangkok Metropolitan Area. Department of Drainage and Sewerage Bangkok Metropolitan Administration. Available at: http://www.unescap.org/sites/default/files/S3b4_Thailand.pdf Accessed ~~at-on~~ 23rd August 2017, 2011.

Pitt, M.: Learning lessons from the 2007 floods., Final Report, The Cabinet Office, London, UK, 2008.

Plate, E.J.: Flood risk and flood management, Journal of Hydrology, 267, 2-11, [https://doi.org/10.1016/S0022-1694\(02\)00135-X](https://doi.org/10.1016/S0022-1694(02)00135-X), 2002.

Poaponsakorn, N., Meethom, P., & Pantakua, K.: The Impact of the 2011 Floods, and Flood Management on Thai Households. Resilience and Recovery in Asian Disasters. Springer Japan, 2015.

Porter, J., Demeritt, D.: Flood-risk management, mapping, and planning: the institutional politics of decision support in England, Environment and Planning A, 44, 2359-2378, <https://doi.org/10.1068%2Fa444660>, 2012.

870 Rosenzweig, C., Solecki, W.: Hurricane Sandy and adaptation pathways in New York: Lessons from a first-responder city, Global Environmental Change, 28, 395-408, <https://doi.org/10.1016/j.gloenvcha.2014.05.003>, 2014.

Samuels, P.: A European perspective on current challenges in the analysis of inland flood risks, In Flood risk management: hazards, vulnerability and mitigation measures (pp. 21-34), 2006.

875 Schanze, J.: Flood risk management-a basic framework In Flood risk management: hazards, vulnerability and mitigation measures, pp. 1-20, 2006.

Schanze, J., Zeman, E., Marsalek, J.: Flood Risk Management. Hazards, Vulnerability, Mitigation Measures, Springer Science & Business Media, 2005.

880 Scott, M., White, I., Kuhlicke, C., Steinährer, A., Sultana, P., Thompson, P., Minnery, J., O'Neill, E., Cooper, J., Adamson, M., Russell, E.: Living with flood risk/The more we know, the more we know we don't know: Reflections on a decade of planning, flood risk management and false precision/Searching for resilience or building social capacities for flood risks?/Participatory floodplain management: Lessons from Bangladesh/Planning and retrofitting for floods: Insights from Australia/Neighbourhood design considerations in flood risk management/Flood risk management – Challenges to the effective implementation of a paradigm shift. Planning Theory & Practice 14, 103-140, 2013.

Sneddon, C., Fox, C.: Rethinking transboundary waters: A critical hydropolitics of the Mekong basin, Political Geography, 25, 181-202, <https://doi.org/10.1016/j.polgeo.2005.11.002>, 2006.

Storch, H., Downes, N.K.: A scenario-based approach to assess Ho Chi Minh City's urban development strategies against the impact of climate change, Cities, 28, 517-526, <https://doi.org/10.1016/j.cities.2011.07.002>, 2011.

Supachai T.: Bangkok Climate Resilience. Resilient Cities Asia Pacific 2016. Melaka, Thailand, 2016.

890 Syvitski, J.P.M., Kettner, A.J., Overeem, I., Hutton, E.W.H., Hannon, M.T., Brakenridge, G.R., Day, J., Vorosmarty, C., Saito, Y., Giosan, L., Nicholls, R.J.: Sinking deltas due to human activities, Nature Geosci, 2, 681-686, 2009.

Takeuchi K.: Analyses of the flow regime of the Chao Phraya River. *Hydrology of Warm Humid Regions*. IAHS Publ. 216, 199, 1993.

Takahasi, Y.: History of Water Management in Japan from the End of World War II, *International Journal of Water Resources Development*, 25, 547-553, <https://doi.org/10.1080/07900620903274091>, 2009.

895 Tanaka, N.: Implementation of community flood risk communication in Kumamoto, Japan, *Journal of Advanced Transportation*, 45, 117-128, 2011.

Ten Brinke, W.B.M., Bannink, B.A.: Dutch Dikes and Risk Hikes. A Thematic Policy Evaluation of Risks of Flooding in The Netherlands, 2004.

Terry, J.P., Winspear, N., Cuong, T.Q.: The 'terrific Tongking typhoon' of October 1881 implications for the Red River Delta 900 (northern Vietnam) in modern times. *Weather* 67, 72e75. <https://doi.org/10.1002/wea.882>, 2012.

Texier, P.: Floods in Jakarta: when the extreme reveals daily structural constraints and mismanagement, *Disaster Prevention and Management*, 17, 358-358-372, 2008.

Thorne, C.: Geographies of UK flooding in 2013/4. *The Geographical Journal* 180, 297-309, <https://doi.org/10.1111/geoj.12122>, 2014.

905 Timmeren V.A.& Bacchin T.K.and Aires C.: Green Blue Infrastructures: Overview of Smart Spatial Strategies Worldwide. 13th International conference on urban drainage, Sarawak, Malaysia, 7-12 September 2014, 2014.

Tol, R.S.J., Van Der Grijp, N., Olsthoorn, A.A., Van Der Werff, P.E.: Adapting to Climate: A Case Study on Riverine Flood Risks in the Netherlands. *Risk Analysis* 23, 575-583. <https://doi.org/10.1111/1539-6924.00338>, 2003.

Ueno, T.: On some problems in river administration and flood control measures fitting in the twenty-first century. *Annu. Disas. Prev. Res.*: Inst. Kyoto Univ, 45, 1–16, 2002.

910 UNCE.: Earth Summit, Agenda 21, The United Nations Programme of Action from Rio, 1992.

United Nations Development Programme (UNDP) China.: Climate Change and Development in China. Available at: (<http://www.undp.org/content/dam/china/docs/Publications/UNDP-CH-EE-Publications-Climate-Change-a> nd-Development-in-China.pdf). Accessed at: 23rd August 2017, 2012.

915 Van der Brugge, R., Rotmans, J., Loorbach, D.: The transition in Dutch water management, *Regional Environmental Change*, 5, 164, 2005.

Van Stokkom, H.T.C., Smits, A.J.M., Leuven, R.S.E.W.: Flood Defense in The Netherlands -- A New Era, a New Approach, *Water international*, 30(1), 76-87, <https://doi.org/10.1080/02508060508691839>, 2005.

Van Stokkom, H.T.C., Witter, J.V.: Implementing integrated flood risk and land-use management strategies in developed 920 deltaic regions, exemplified by The Netherlands, *International Journal of River Basin Management*, 6, 331 – 338, <https://doi.org/10.1080/15715124.2008.9635360>, 2008.

Vance, J.H.: Hurricane Sandy: Flood defence for financial hubs. *Nature* 491, 527-527, 2012.

VanKoningsveld, M., Mulder, J.P.M., Stive, M.J.F., VanDerValk, L., VanDerWeck, A.W.: Living with Sea-Level Rise and Climate Change: A Case Study of the Netherlands, *Journal of Coastal Research*, 367-379, <https://doi.org/10.2112/07A-0010.1>, 2008.

Vis, M., Klijn, F., De Bruijn, K.M., Van Buuren, M.: Resilience strategies for flood risk management in the Netherlands. *International Journal of River Basin Management* 1, 33-40, <https://doi.org/10.1080/15715124.2003.9635190>, 2003.

Wannowitz, M. and Garschagen, M.: Mapping the adaptation solution space – lessons from Jakarta for other coastal cities. *Nat. Hazards Earth Syst. Sci. Discuss. [preprint]*, <https://doi.org/10.5194/nhess-2020-370>, 2021.

925 Water Resource Management Strategic Committee.: Master Plan on Water Resource Management. National Economic and Social Development Board. Accessed at: (http://www.boi.go.th/upload/water_flood_th_master_0212_eng_98335.pdf). Accessed at: 23rd August 2017, 2012.

Webster, P.J.: Myanmar's deadly daffodil. *Nature Geosci* 1, 488-490, 2008.

Webster, P.J., Holland, G.J., Curry, J.A., Chang, H.-R.: Changes in Tropical Cyclone Number, Duration, and Intensity in a 930 Warming Environment, *Science*, 309, 1844-1846, <https://doi.org/10.1126/science.1116448>, 2005.

Wesselink, A.J., Bijker, W.E., de Vriend, H.J., Krol, M.S.: Dutch Dealings with the Delta, *Nature and Culture*, 2, 188-209, [https://doi.org/10.3167/nc.2007.020206](https://doi.org/10.3167/nc.2007.02020206), 2007.

935 Wong, K. K., & Zhao, X.: Living with floods: victims' perceptions in beijiangBeijing, guangdongGuangdong, chinaChina. Area, 33(2), 190-201, 2001.

940 World Bank.: Project Information Document and Report NO. AB4043. Available at: (<http://documents.worldbank.org/curated/en/911741468040156450/pdf/PID0JEDI1concept0stage.pdf>). Accessed at: August 19th, 2009.

945 World Health Organization (WHO).: Emergency Situation Report#6.19 February. Available at: (http://www.who.int/hac/crises/idn/sitreps/indonesia_floods_jakarta_province_19feb2007.pdf?ua=1). Accessed at: August 19th, 2007.

Wind, H.G., Nierop, T.M., de Blois, C.J., de Kok, J.L.: Analysis of flood damages from the 1993 and 1995 Meuse Floods. *Water Resour. Res.* 35, 3459-3465, <https://doi.org/10.1029/1999WR900192>, 1999.

950 Wright, J.M.: The Nation's Response to Flood Disasters: A Historical Account. Madison, WI: Association of State floodplain Managers. Available at: (https://www.floods.org/PDF/hist_fpm.pdf). Accessed at: August 5th 2019, 2000.

Xiao, Y., Wan, J., & Hewings, G.J.D.: Flooding and the Midwest economy: assessing the Midwest floods of 1993 and 2008, *GeoJournal*, 78, 245-258, 2011.

955 Yamamoto, M., Fujimi, T., Tanaka, N.: Implementation of community flood risk communication in Kumamoto, Japan, *Journal of Advanced Transportation*, 45, 117-128, 2011.

Yang, L., Lü, Y., Zheng, H.: Review on the research of urban land carrying capacity, *Progress in Geography* 29 (5), 593-600, in Chinese, 2010.

Yang, L., Scheffran, J., Qin, L., You, Q.: Climate-related flood risks and urban responses in the Pearl River Delta, China, *Regional Environmental Change*, 15 (2), 379-391, 2015.

Yang, L.E., Scheffran, J., Süsser, D., Dawson, R., Chen, Y.D.: Assessment of Flood Losses with Household Responses: Agent-Based Simulation in an Urban Catchment Area, *Environmental Modeling & Assessment*, 23, 369-388, 2018.

960 Yang, L.E., Bork, H.R., Fang, X., Mischke, S.: *Socio-Environmental Dynamics along the Historical Silk Road*. Springer, Cham, Switzerland. P525, 2019.

Yang, L.E.: Managing water-related vulnerability and resilience of urban communities in the Pearl River Delta. In: Brzoska, M., Scheffran, J. (Eds.), *Climate Change, Security Risks, and Violent Conflicts: Essays from Integrated Climate Research in Hamburg*. Hamburg University Press, pp. 121-141, 2020.

965 Yang, L.E., Chen, J., Geng, J., Fang, Y., Yang, W.: Social resilience and its scale effects along the historical Tea-Horse Road. *Environmental Research Letters* 16 (4), 045001, 2021.

Yang, M., Sang, Y.-F., Sivakumar, B., Ka Shun Chan, F., Pan, X.: Challenges in urban stormwater management in Chinese cities: A hydrologic perspective, *Journal of Hydrology*, 591, 125314, <https://doi.org/10.1016/j.jhydrol.2020.125314>, 2020.

Yin, J., Ye, M., Yin, Z., & Xu, S.: A review of advances in urban flood risk analysis over China, *Stochastic Environmental Research & Risk Assessment*, 29(3), 1063-1070, 2015.

970 Yuan, Y., Xu, Y. S., & Arulrajah, A.: Sustainable measures for mitigation of flooding hazards: a case study in Shanghai, China, *Water*, 9(5), 310, <https://doi.org/10.3390/w9050310>, 2017.

Zhai, G., Sato, T., Fukuzono, T., Ikeda, S., Yoshida, K.: Willingness to pay for flood risk reduction and its determinants in Japan, *Journal of the American Water Resources Association*, 42, 927-940, <https://doi.org/10.1111/j.1752-1688.2006.tb04505.x>, 2006.

975 Zhou, Z., Liu, S., Zhong, G., & Cai, Y.: Flood disaster and flood control measurements in shanghai. *Natural Hazards Review*, 18(1), 2016.

Zou D.: "The understanding of urban planning strategies in the Republic of China of Guangzhou" in Chinese 122-125, 2012.