Automated snow avalanche release area delineation in data sparse,

2 remote, and forested regions

3 John Sykes¹, Pascal Haegeli¹, Yves Bühler^{2,3}

⁴ ¹Geography Department, Simon Fraser University, Burnaby, British Columbia, Canada

5 ²WSL Institute for Snow and Avalanche Research SLF, Davos, Switzerland

6 3Climate Change, Extremes and Natural Hazards in Alpine Regions Research Center CERC, 7260 Davos Dorf, Switzerland

7

8 *Correspondence to*: John Sykes (John_Sykes@sfu.edu)

9 Abstract. Potential avalanche release area (PRA) modelling is critical for generating automated avalanche terrain maps which 10 provide low-cost large scale spatial representations of snow avalanche hazard for both infrastructure planning and recreational 11 applications. Current methods are not applicable in mountainous terrain where high-resolution (≤ 5 m) elevation models are 12 unavailable and do not include an efficient method to account for avalanche release in forested terrain. This research focuses 13 on expanding an existing PRA model to better incorporate forested terrain using satellite imagery and presents a novel approach 14 for validating the model using local expertise, thereby broadening its application to numerous mountain ranges worldwide. 15 The study area of this research is a remote portion of the Columbia Mountains in southeastern British Columbia, Canada which 16 has no pre-existing high-resolution spatial data sets. Our research documents an open source workflow to generate high-17 resolution DEM and forest land cover data sets using optical satellite data processing. We validate the PRA model by collecting 18 a polygon dataset of observed potential release areas from local guides, using a method which accounts for the uncertainty of 19 human recollection and variability of avalanche release. The validation dataset allows us to perform a quantitative analysis of 20 the PRA model accuracy and optimize the PRA model input parameters to the snowpack and terrain characteristics of our 21 study area. Compared to the original PRA model our implementation of forested terrain and local optimization improved the 22 percentage of validation polygons accurately modelled by 11.7 percentage points and reduced the number of validation 23 polygons that were underestimated by 14.8 percentage points. Our methods demonstrate substantial improvement in the 24 performance of the PRA model in forested terrain and provide means to generate the requisite input datasets and validation 25 data to apply and evaluate the PRA model in vastly more mountainous regions worldwide than was previously possible.

26 **1 Introduction**

27 Snow avalanches are a significant natural hazard for traffic and settlement infrastructure as well as for individuals who travel 28 in snow covered mountainous regions. Roads, railroads, utilities, and permanent structures that are located in areas with 29 potential avalanche hazard can be destroyed by large avalanche impacts or blocked for extended periods during winter storm 30 events causing financial losses and potential for injury or death from individuals being buried in the debris. In economically 31 developed countries, the majority of avalanche fatalities occur during recreational activities (i.e., backcountry skiing, 32 snowmobile riding, mountaineering) where individuals voluntarily expose themselves to avalanche hazard (Boyd et al., 2009). 33 and accidental avalanches are mostly triggered by the party that is caught (Schweizer and Lütschg, 2001; Techel et al., 2016). 34 In North America and Europe, an average of approximately 140 people are killed in avalanches each year (Jamieson et al., 35 2010: Techel et al., 2016: Colorado Avalanche Information Center, 2020).

36 To mitigate avalanche hazard, locations with potential for avalanche release need to be identified so elements at risk can 37 attempt to minimize their exposure. This can be achieved by avoiding avalanche prone areas, minimizing exposure time, or 38 implementing avalanche control methods (McClung and Schaerer, 2006). Avalanche hazard mapping is a time honored 39 practice for determining the spatial distribution of snow avalanche hazards (Margreth and Funk, 1999; Rudolf-Miklau et al., 40 2015). Traditional manual hazard mapping combines multiple methods such as terrain inspection, numerical simulations, 41 avalanche event databases and expert experience to evaluate avalanche hazard exposure and spatial extent making it both labor 42 and cost intensive. This highly detailed approach is the gold standard for determining avalanche zoning for permanent 43 infrastructure, but the costs make it unsuitable for mapping large areas of mountainous terrain (Rudolf-Miklau et al., 2015, 44 Bühler et al., 2018, 2022).

45 To overcome this challenge, automated GIS and remote sensing based methods have been developed to expedite the mapping 46 process and produce avalanche terrain indication maps based on digital elevation model (DEM) and land cover data (Maggioni 47 and Gruber, 2003; Gruber and Haefner, 1995). The foundation of automated avalanche terrain mapping is potential avalanche 48 release area (PRA) modelling, which estimates the location of potential hazards based on the local terrain characteristics 49 (Bühler et al., 2013, 2018; Veitinger et al., 2016). PRA models can be applied to define the spatial extent of release areas in 50 dynamic avalanche simulations, which estimate the runout distance, velocity, and flow height of avalanche debris (Christen et 51 al., 2010), or as a standalone spatial layer to assist with hazard identification. Their ability to operate at the mountain range 52 scale with limited human input dramatically reduces cost and time to develop spatial data sets which can assist infrastructure 53 planners and recreationists in making more informed decisions about their avalanche hazard exposure (Bühler et al., 2018). 54 The development of large-scale avalanche hazard indication maps in Switzerland has led to them being applied as a tool to 55 help backcountry recreationists visualize terrain hazards and incorporate them into their trip planning process (Harvey et al., 56 2018).

57 The current state of the art methods for PRA modelling have been developed and validated in regions with widely available 58 high-resolution DEM and forest cover data as well as long term records of avalanche observations (Bühler et al., 2018; 59 Veitinger et al., 2016). However, the majority of mountainous regions in the world do not have freely available high-resolution 60 DEM or forest cover data yet, and long term spatially accurate records of avalanche release are very rare. This seriously limits 61 the application and local validation of PRA models-around the world.

An additional limitation of existing high-resolution PRA models is that they do not account for the interaction between forest characteristics and avalanche release. For example, both the Bühler et al. (2018) and Veitinger et al. (2016) PRA models allow for forested areas to be excluded from PRA calculations based on a forest mask layer, but they do not explicitly capture forest avalanche interaction. This reduces the applicability of these PRA models in mountain ranges where a significant portion of the avalanche terrain is forest covered, such as in western North America.

67 To address these challenges and make PRA models applicable more broadly, the objective of this research is to develop a costeffective workflow for generating the required input datasets for the Bühler et al. (2018) PRA model using satellite data and 68 69 open-source remote sensing methods. In addition, we present a relatively simple method for adapting the current PRA model 70 to work in forested terrain. In the absence of long-term avalanche observations, we develop a novel approach for utilizing the 71 expertise and terrain knowledge of local mountain guides to validate the PRA model output and optimize the input parameter 72 for the unique terrain and snowpack characteristics of our study area. These three developments—the use of satellite data, the 73 adaptation of the model to work in forested terrain, and the validation with local terrain expertise-together open new 74 opportunities for applying state of the art avalanche terrain modelling in regions with limited existing datasets and resources.

75 **2 Background**

76 2.1 Potential Avalanche Release Area Modelling

77 Early versions of GIS based avalanche terrain models (e.g., Gruber and Haefner, 1995; Maggioni and Gruber, 2003) struggled 78 to outperform simple slope based avalanche release area estimates (Voellmy, 1955) due to the inability of low resolution DEMs 79 (20-30 m) to detect small scale terrain features. Current PRA modelling methods evolved over the course of a decade and 80 benefit from developments in high-resolution DEM production and remote sensing (e.g., Bühler et al., 2013, 2018, 2022; 81 Veitinger et al., 2016; Kumar et al., 2019). To define avalanche release areas the algorithms use different combinations of 82 DEM derivatives (i.e., slope angle, terrain ruggedness, curvature, and aspect), which are calculated using focal functions of 83 raster pixels. Bühler et al (2013) found that 5 m resolution is the optimal tradeoff between processing efficiency and small-84 scale feature identification for PRA modelling. With DEM resolution of 5 m, a common nine cell focal neighborhood (3x3) is 85 225 m², which is well below the median slab size for human triggered avalanches of 4,000 m² (Schweizer and Lütschg, 2001). 86 Hence, high resolution input data is essential to capture sub-release area scale terrain characteristics which are critical for 87 accurate potential release area modelling.

88 The development of these algorithms depends on a robust validation dataset of observed avalanche events to determine the 89 optimal input parameter settings for the target study area. By comparing the extent of the PRA model output to the location of 90 avalanche observations the overall accuracy of the PRA model can be evaluated and comparisons can be made between 91 different combinations of input parameters. Such datasets can be created through recording of manual observations or 92 generated by applying satellite mapping (Lato et al., 2012; Bühler et al., 2019; Hafner et al., 2021). The most comprehensive 93 known avalanche release area validation dataset currently available is curated by the WSL Institute for Snow and Avalanche 94 Research SLF in Davos, Switzerland with experienced staff manually mapping avalanche outlines throughout the winter in the 95 surrounding mountain areas. This avalanche observation catalog began in 1970, and as of 2016 it included 5785 mapped 96 avalanches (Bühler et al., 2018). This dataset is now expanded including data from satellite avalanche mapping (Bühler et al., 97 2019) as well as airplane (Bühler et al., 2009; Korzeniowska et al., 2017) and drone surveys (Bühler et al., 2017).

98 Using a subset of this validation data, Bühler et al. (2018) compared their PRA algorithm performance against another PRA 99 model (Veitinger et al., 2016) and a simple slope based release area estimation method from Voellmy (1955). The validation 100 study showed that the Bühler et al. (2018) and Veitinger et al. (2016) PRA models had lower probability of detection compared 101 to the slope based model, by 3.5% and 2% respectively, but also had lower probability of false detection, by 13.3% and 8.4% 102 respectively. This means that the slope only model detected a greater percentage of observed release areas compared to the 103 PRA models but also overpredicted release areas at a higher rate than the PRA models. Due to the relatively smaller decrease 104 in probability of detection (3.5% and 2%) compared to the decrease in probability of false detection (13.3% and 8.4%) the 105 more sophisticated PRA models are considered more skillful than the slope based model. The relatively small improvements 106 over the slope based release area estimate illustrates the fact PRA modelling is a field of marginal gains, but when applied over 107 large areas marginal improvements can have a large impact on the output extent of PRA models. The results also show slightly 108 better performance for the Bühler et al. (2018) PRA model over the Veitinger et al. (2016) PRA model, with lower probability 109 of false detection and higher measures of Pierce skill score and Heidke skill score.

An additional advantage of the Bühler et al. (2018) PRA model is the ability to convert the raster based PRA model output to polygon features using object based image analysis. Converting the PRA model output to polygon features enables the PRA model to be paired with dynamic avalanche simulation software (Christen et al., 2010; Bühler et al., 2018) to estimate runout distance, impact pressures, flow depth and velocity of the avalanche flow. This powerful combination of release area and runout modelling represent the state of the art of current avalanche terrain indication modelling practices and are a valuable resource for large scale avalanche hazard indication mapping. Therefore, this research seeks to improve and expand upon the existing Bühler et al. (2018) PRA model.

The Bühler et al. (2018) PRA model has been applied in multiple regions worldwide, including Chile, Alaska, Afghanistan, and India. However, the input parameters have not been independently tested and optimized using local validation data. Therefore, it is unknown whether the input parameters optimized for Davos, Switzerland are appropriate for mountain regions with different topographic and snowpack characteristics. Our research aims to address this knowledge gap by applying an

- 121 updated version of the Bühler et al. (2018) PRA model to the Columbia Mountains of southeast British Columbia, Canada and
- 122 seeks to optimize the input parameters for the study area based on locally available validation data.

123 2.2 Avalanches in Forested Terrain

124 In addition to DEM derived terrain variables some PRA algorithms use forest coverage to define PRA based on the assumption 125 that avalanche release is less common in areas with tall and dense vegetation. The snowpack in forested areas is generally 126 more stable due to the anchoring effect of trees, forest canopy snow interception, the disruption of the continuity of weak 127 layers due to snow drop from canopy, and altered snow surface radiation and temperature conditions. However, it is still 128 possible for avalanches to release in forested areas, especially in areas with steep slope angles, low tree density, or in openings 129 within forested areas (Bebi et al., 2009). Small and medium avalanches generally do not have enough impact force to damage 130 trees or tree stands, and forests tend to reduce their runout potential by detraining snow from the flowing avalanche (Feistl et 131 al., 2014). Larger avalanches can break or uproot trees and cause massive destruction to the forest ecosystem (Feistl et al., 132 2015; Bebi et al., 2009). The location of avalanche release areas in relation to the forest plays a large role in whether trees will 133 impede avalanche flow or be destroyed and possibly entrained (Teich et al., 2012).

The ability to account for forest characteristics in avalanche terrain modelling is largely based on locally available data sets. Laser scanning or LiDAR data provide high-resolution digital surface model (DSM) and digital terrain model (DTM) datasets to define the forest character, including canopy height, location and size of forest gaps, and basal area (Brožová et al., 2020; Dash et al., 2016). Vegetation height models derived from DSM and DTM data can be used to identify forests with protective function and input as forest masks in PRA models (Bebi et al., 2021; Bühler et al., 2018, 2022; Waser et al., 2015). Similar to their application for DEM production, the high accuracy of these data sets comes at a high cost.

Alternative lower cost methods for estimating forest characteristics include traditional field based sample plots and radar or optical remote sensing instruments (Hyyppä et al., 2000; Waser et al., 2015). The most accessible of these alternative methods is satellite based optical imagery, which can be used to create a forest land cover classification, to determine the extent of the forested area (Bühler et al., 2013), and can be combined with field plot observations of specific forest characteristics to create a predictive model based on the spectral and textural characteristics of the imagery (Dash et al., 2016).

Prior research has attempted to incorporate forest characteristics with PRA modelling (Sharp et al., 2018), but low resolution DEM and forest data combined with a limited validation data set make it challenging to evaluate the overall performance of the model. However, the principle of adjusting the potential for avalanche release based on forest character aligns with analytical and theoretical understanding of avalanche release in forested terrain (Bebi et al., 2009; McClung, 2001). This research aims to expand existing methods for capturing forest avalanche interaction in PRA models using satellite remote sensing methods that are cost-effective and efficient for processing large scale avalanche terrain models.

151 **3 Methods**

152 Applying the potential avalanche release area (PRA) model to the study area required three main analysis steps (Figure 1). 153 First, developing a pipeline for producing high-resolution DEM and forest classification data from satellite imagery. Second, 154 adapting the existing PRA model to better capture forested terrain and processing many versions of the PRA model using a 155 predefined range of input parameters. Third, developing new methods to validate the PRA model using polygons collected 156 from local experts in order to optimize the input parameters for our study area. Steps two and three required many iterations 157 (Figure 1, Step 3c) to test different baseline input parameters and evaluate performance using our grid search validation 158 procedure. The datasets and code required for replication of our DEM processing, forest classification, and PRA validation are 159 available in our Open Science Framework (OSF) repository (Sykes et al., 2021).



Figure 1. Workflow diagram illustrating the necessary input datasets and processing steps to apply and validate the PRA model in our remote, data sparse, and forested study area. The dashed lines in step 3c indicate the option to either refine the baseline input parameters of the PRA model and re-start from step 2a or select the final PRA model and move to step 3d.

165 **3.1 Study area**

166 The study area for this research is the tenure area of CMH Galena, a mechanized skiing operation that operates in the Selkirk 167 Mountains of British Columbia, Canada, approximately 100 km southeast of Revelstoke (Figure 2). The tenure covers 168 1162 km², ranges from 450–3,050 m in elevation and is composed of roughly 60% forested terrain. The Selkirk Mountains 169 have a transitional snow climate with a maritime influence where persistent avalanche problem types are common. The most 170 common persistent weak layers associated with these avalanche problems are surface hoar and faceted crystals associated with 171 a crust (Hägeli and McClung, 2003; Haegeli and McClung, 2007; Shandro and Haegeli, 2018). The best existing DEM and 172 land cover datasets for the study area are the Canadian Digital Elevation Model (CDEM) with a resolution of 18m and the 173 2015 National Land Cover Dataset (NLCD) with a resolution of 30 m. The resolution of both these datasets is too coarse for 174 high-resolution PRA modelling.

175



- 176
- Figure 2. Study area map showing the CMH Galena tenure, lodge location, ski run polygons, and the subset of runs used to validate
 the PRA model. Forest data created using Planet Labs imagery (Planet Team, 2017), inset map made with Natural Earth.

179

180 **3.2 Data preparation**

181 **3.2.1 DEM generation**

182 Based on our desire to develop a cost-effective and reproducible approach for applying PRA models across large areas, we 183 chose to purchase raw satellite imagery and use open source photogrammetry software to produce our own DEM. At the time 184 we purchased the imagery our estimate was that producing our own DEM would be roughly 2-10x less expensive than 185 alternative methods to acquire a 5 m DEM based on price quotes from multiple commercial suppliers. However, the cost 186 savings of producing a DEM using raw imagery come at a tradeoff of requiring significant technical knowhow to process the 187 stereo imagery. One downside of this approach is that the vegetation cover inhibits the ability to create a bare ground DEM 188 (known as a digital terrain model; DTM) and we end up with a digital surface model (DSM) that represents the reflective 189 surface at the top of the vegetation. While a DSM is not the ideal representation of terrain in forested areas (Brožová et al., 190 2020), the high cost of LiDAR, the only remote sensing method that can produce a DTM in vegetation covered terrain, currently 191 prevents its widespread use.

192 Producing a 5 m DEM requires satellite imagery with a spatial resolution of at least 1.5 m. After comparing the products from 193 various providers (Pleiades 1, Worldview 1-4, GeoEye 1, SPOT 6/7, and KOMPSAT 2-3) we purchased SPOT 6/7 imagery 194 based on our requirements of DEM resolution, study area size, and cost. The listed price for tasking new imagery collection 195 for 1.5 m resolution SPOT 6/7 tri-stereo imagery at the time of acquisition was USD \$12.65 per km² for a minimum study area 196 of 500 km², which does not account for any academic or other discounts available through imagery suppliers. The SPOT 6 tri-197 stereo satellite images were captured on August 19th, 2019 with 1.5% cloud cover and no visible atmospheric distortions 198 (wildfire smoke, haze) in the images. Tri-stereo imagery captures forward, nadir, and backward looking images in a single 199 pass and provides three stereo image perspectives which increases DEM accuracy in steep terrain and minimizes sensor 200 shading. For a more detailed description of our DEM processing interested readers should reference the supplementary material 201 'DSM production in mountainous, forested terrain using SPOT 6 tri-stereo imagery with Ames Stereo Pipeline'.

To improve and assess the accuracy of our DEM we collected a set of 66 ground control points (GCP) distributed across our study area using a Trimble Geo7x handheld differential global navigation satellite system (DGNSS) unit connected to an H– star base station network, from August 24–27th 2019. We collected GCP in locations with high contrast such as edges of snowfields, water body inlets, bridges, and land cover transitions (e.g., boundary of talus slope and vegetation) to make the locations accurately identifiable in the satellite imagery. The timing of our image collection (August 19th, 2019) and GCP data collection (August 24–27th, 2019) meant that there were minimal changes in the natural features we used as reference points (i.e., snowfields, water bodies).

To process the imagery, we used a combination of open source software tools from Geospatial Data Abstraction Software Library (GDAL), QGIS, and the Ames Stereo Pipeline (ASP) version 2.6.2 (Beyer et al., 2018; GDAL, 2021; QGIS, 2021).

211 Several steps of preprocessing were necessary to optimize our images prior to stereophotogrammetry, including bundle

212 adjustment and orthorectification (Shean et al., 2016). The ASP stereo tool was developed for imagery containing bare rock 213 and glacial landscapes. Differences in image texture in forested terrain are challenging for the default settings of ASP to 214 produce accurate pixel matches. To address this issue, we extensively tested different stereo correlation algorithms and stereo 215 processing settings to optimize performance for forested mountainous terrain. Our best results were achieved using the smooth 216 semi-global matching (MGM) stereo correlation algorithm (Facciolo et al., 2015), which resulted in fewer DEM holes in 217 forested terrain and terrain with suboptimal lighting conditions. Optimizing the settings of the ASP stereo tool produced 218 accurate pixel matches in forested terrain and was only limited by artifacts in the original imagery (cloud, cloud shadow, poor 219 lighting conditions).

Our stereo processing workflow generated 6 separate DSMs from the SPOT 6 tri-stereo imagery by taking all possible combinations of left and right stereo images. The goal of this method was to reduce DSM holes in steep or poorly lit terrain by taking advantage of the multiple view angles provided by the tri-stereo imagery. Before combining the individual DSMs to produce the final DSM mosaic, we removed pixels with a triangulation error greater than the resolution of the input images (1.5 m) to ensure robust elevation estimates (Figure 3a). Overall, we see low normalized median absolute deviation (NMAD) values across the DSM mosaic (Figure 3b), with a median NMAD of 0.32 m.

226



227

Figure 3. SPOT 6 DSM error estimates. Triangulation error for each set of stereo pairs (a) with pixels where error is greater than image resolution (1.5 m) removed from DSM. Normalized median absolute deviation (NMAD) for mosaic of 6 stereo pairs (b) with inset map showing slope scale detail. Internal checkpoints (green points) with height difference in meters between DSM surface and DGNSS measurement (negative values indicate the DSM surface height is lower than ICP height).

- To improve the alignment of the final DSM mosaic to our GCP, we used the ASP point cloud alignment tool to co–register the output DSM to the GCP (Shean et al., 2016). To evaluate the accuracy of our DSM we used 15 internal checkpoints which were not used as part of our GCP dataset (Höhle and Höhle, 2009).
- Localized cloud cover and poor lighting on steep north facing terrain caused several holes in our SPOT6 DSM mosaic, which account for approximately 1% of the total DEM area (11.7 km²). We filled these holes by down sampling the existing Canadian DEM to 5m, aligning the CDEM to our SPOT6 DSM mosaic using the point cloud alignment tool in ASP, and then blending the two DEM datasets together. To avoid smoothing the entire SPOT6 DSM we progressively blended the datasets across a 60 m buffer from holes in the SPOT 6 DSM.
- The methods described here were only tested on a single set of SPOT 6 tri–stereo images, but the performance in forested terrain was vastly improved compared to the default ASP settings. For more detailed information on the ASP workflow or the computer resources used to calculate the DSM please see the supplementary material or contact the authors.

244 **3.2.2 Forest classification**

- The existing PRA model of Bühler et al. (2018) uses a binary forest mask based on photogrammetric vegetation height model classification to mask release areas in forested terrain. We tested several approaches to generate a binary forest mask for our study area. Since our SPOT 6 imagery was limited by poor lighting conditions on steep north facing terrain due to early morning sun angle, we substituted Planet Labs' RapidEye imagery, collected on July 14th, 2018 (Planet Team, 2017). An advantage of the RapidEye imagery is that it includes a red edge band which provides additional spectral resolution to differentiate between forests and other types of vegetation (Dash et al., 2016).
- 251 The overall accuracy of the classifier is critical for providing a distinction between forested land cover and other types of 252 vegetation, such as shrubs and herbaceous plants. For avalanche release area modelling this distinction is important because 253 shrubs and herbaceous plants are buried or pressed down beneath the winter snowpack and therefore have minimal effect on 254 the potential for avalanche release. Trees with rigid trunks that resist being laid over by the winter snowpack and canopy 255 heights greater than the snowpack depth (approximately 2-3 m) have an anchoring effect on the snowpack which is essential 256 to capture accurately in order to account for their effect on avalanche release. By iteratively fine tuning the training dataset we 257 were able to control how the classier identified forested terrain and opted to select a model that primarily captured densely 258 forested areas and omitted areas with isolated smaller trees surrounded by shrubs and herbaceous plants.
- To perform the classification, we used a random forest algorithm on the blue, green, red, red edge, and near infrared image bands utilizing the python libraries Numpy, GDAL, Rasterio, and SciKit Learn (GDAL, 2021; Gillies et al., 2013; Harris et al., 2020; Pedregosa et al., 2011). To improve the classification accuracy, we included the normalized difference red edge index (NDRI), normalized difference vegetation index (NDVI), and normalized difference water index (NDWI) as additional bands for the random forest classifier. Training data were created by manually drawing polygons around individual land cover types (forest, water, bare ground, snow and ice, shrub, moss and lichen) based on RapidEye, SPOT6, and Google Earth imagery

- from our study area. Our training dataset is composed of 253 individual polygons (12.0 km²), with 73 polygons of forested
- terrain (3.6 km²). For further details on the analysis methods used for the forest classification interested readers are referred to
 our OSF directory where the data and code are available for review (Sykes et al., 2021).

268 **3.3 Integration of forest information into PRA model**

Our development of additional PRA model functions to improve performance in forested terrain was guided by two principles;
1. Minimize additional complexity when running the PRA model compared to the original version. 2. Utilize remote sensing
datasets that are available in data sparse locations and do not require extensive field validation.

To integrate forest information into the PRA model, we created two additional input parameters: an ordinal *forest density* (Open -0, Sparse -1, Moderate -2, Dense -3, Very Dense -4) (Figure 4) and a numeric *forest slope scalar* (0.0–2.0) (Figure 5). The *forest density* parameter controls what classes of forest are included in the PRA model, while the *forest slope scalar* adjusts the *slope angle minimum* threshold based on the *forest density* class for each pixel. Including these parameters takes advantage of the existing forest mask functions of the PRA model and only adds two input parameters when running the PRA model, both of which are optional and can be omitted to run the PRA model in the prior configuration from Bühler et al. (2018).

279 3.3.1 Forest density

280 To estimate forest density, we used a focal function to calculate the total number of forested pixels within a five-cell 281 neighborhood (625 m²). The function simply summed up the total number of forested pixels and did not account for the location 282 of the forested pixels within the five-cell neighborhood. This step resulted in a forest sum raster with values ranging from 0 to 283 25, with 0 meaning no forested cells and 25 meaning all cells within the five-cell neighborhood are forested (Figure 4, step 284 3). We included this step to capture the fuzzy transition between forested and non-forested snowpack characteristics. In areas 285 adjacent to forested terrain the snowpack can be altered by forest cover (i.e., wind dynamics, radiation balance, canopy snowfall 286 interception) despite not being directly covered by the forest canopy (Bebi et al., 2009). This method also helps to identify 287 glades or meadows within the forest canopy by creating a fuzzy buffer around small non-forested islands within densely 288 forested terrain. The size of the neighborhood function (625 m^2) is representative of small human triggered avalanches that 289 have the potential to bury or injure a person, especially if they are carried into a forested area (Schweizer and Lütschg, 2001).



291

292 Figure 4. Forest density layer processing workflow.

293

We then reclassified each forest sum cell into an ordinal variable with the *forest density* categories open (0 cells), sparse (1– 10 cells), moderate (11–20 cells), dense (21–24 cells), and very dense (25 cells) (Figure 4, step 4). We chose this uneven classification scheme to bias the application of the *forest slope scalar* parameter towards increasing the *slope angle minimum* more strongly in densely or very densely forested areas (i.e., cells with 21 to 25 neighboring forested cells). Since areas with more surrounding forested pixels likely represent more mature forests, this approach captures the fact that more mature forests have a greater potential impact on avalanche release. The resulting *forest density* layer provides a foundation to control how forested cells are included in the PRA model.

301 **3.3.2** Forest slope scalar

302 As an additional control on how the PRA model is applied in forested terrain, we introduced a *forest slope scalar* parameter 303 to increase the *slope angle minimum* based on the *forest density* value. Applying this parameter assumes that steeper slopes 304 are necessary for avalanche release in forested terrain, which is supported by prior research (Campbell and Gould, 2013; 305 Schneebeli and Bebi, 2004). The rate of slope angle increase is controlled by the *forest slope scalar* parameter (0.0-2.0), 306 which is applied as an exponent to the *forest density* value (0-4) and added to the *slope angle minimum* value (e.g., 30°). For 307 example, a slope angle minimum of 30° and a forest slope scalar value of 1 would result in the following slope angle 308 minimums for forested terrain: open (0) 30° , sparse (1) 31° , moderate (2) 32° , dense (3) 33° , very dense (4) 34° . Whereas a 309 slope angle minimum of 30° and a forest slope scalar value of 2 would result in the following slope angle minimums: open 310 (0) 30° , sparse (1) 31° , moderate (2) 34° , dense (3) 39° , very dense (4) 46° (Figure 5). Altering the *slope angle minimum* 311 input parameter changes the starting position of the *forest slope scalar* function but does not impact the rate of increase for 312 each forest density value.



314 Figure 5. *Forest slope scalar* functions applied to a 30° minimum slope angle threshold.

313

316 **3.4 Parameter tuning and validation**

To develop a meaningful validation dataset in the absence of long term records of avalanche events, we collaborated with two CMH Galena guides, who each have decades of experience in the study area, to develop a novel method that takes advantage of their local expertise to optimize the PRA model for our study area. For technical details on our statistical calculations and processing workflow, our validation processing script and data necessary to reproduce our results are available in our OSF repository (Sykes et al., 2021).

322 **3.4.1 Validation data collection**

CMH Galena primarily operates on approximately 300 defined ski runs within their tenure. The runs range in size from 0.2– 19.0 km² and their locations have been mapped with polygons that outline the typical skiing terrain (Figure 2). The frequency of how often these runs are used varies significantly depending on terrain characteristics, weather conditions for flying, and snowpack conditions. To validate the PRA model, the two collaborating guides selected five runs (highlighted in Figure 2) based on their familiarity with the terrain, their representativeness of the terrain characteristics relative to the entire study area, and the balance of forested and alpine avalanche terrain contained in the runs. 329 The process of collecting validation polygons from the CMH guides was carried out on a custom designed website. The website 330 platform enabled us to develop and present meaningful reference layers (e.g., satellite imagery, topo maps, terrain data, GPS 331 tracks, heat maps) and provide the guides with multiple perspectives of the study area to assist with drawing the validation 332 polygons. Both guides drew release area polygons for the five validation runs individually before creating a final consensus 333 set of polygons in collaboration. Through the process of developing the validation data collection workflow we found that 334 mapping the precise location of start zones based on personal recollection without being in the terrain at the time is extremely 335 difficult. Therefore Therefore, we developed an alternative method that would explicitly accommodate this uncertainty. Instead 336 of forcing the participating guides to explicitly outline all avalanche release areas, we asked them to draw validation polygons 337 around terrain features with similar characteristics (i.e. slope angle, forest density, ruggedness) and specify for each polygon 338 what proportion represent potential release areas (0%, 25%, 50%, 75%, 100%) (Figure 6). Polygons of obvious probable 339 release areas or non-release areas where guides had high confidence about their spatial extent were labeled with 100% and 340 0% respectively. Areas with scattered probable release areas, such as open forests with glades, where the identification of each 341 probable release area would be cumbersome and unreliable, were marked as larger polygons and labelled with the estimated 342 spatial proportion of the probable release areas (25%, 50% or 75%). Outliers, such as infrequent release areas with very low 343 slope angles that require specific snowpack structures and weak layer types (e.g., surface hoar), were not included in the 344 validation dataset in order to avoid biasing the validation dataset toward rare events that are not representative of typical 345 conditions in the study area.-

346 Our fuzzy approach to mapping probable release areas has several advantages. Foremost, accommodating uncertainty in the 347 spatial extent of release areas is a requirement when relying on human memory to generate the validation data as specifying 348 probable release areas with higher precision from memory is simply unrealistic. This method also accounts for the variability 349 in release area extent that results from the dynamic nature of snowpack and weather conditions. The workflow also minimizes 350 the effects of local errors in the reference layers that we provided the guides with to record their validation polygons. Specific 351 examples of uncertainty caused by reference layers are variations in satellite imagery lighting due to sun angle and artifacts of 352 the DSM generation process, such as over steepened slope angle values caused by transitions from forested to non-forested 353 terrain.



Figure 6. Validation polygons from one run at CMH Galena. Polygons are color coded based on the release area proportion of each
 polygon. Forest data created using Planet Labs RapidEye imagery (Planet Team, 2017).

355

Our final validation dataset consists of 167 polygons across five runs with a total area of 8.42 km^2 , with sample sizes of 100% = 91, 75% = 23, 50% = 23, 25% = 18, 0% = 7, run polygons = 5. In locations where the polygons overlapped, we retained the highest proportion value of the overlapping polygons. The overlapping region was also clipped from the total area of the lower probability polygon. Locations within the run polygons that were not explicitly mapped by the guides were assumed not to be release areas. However, our validation approach differentiates between these implied and the explicit 0% validation polygons because we have more confidence in the latter.

365 **3.4.2 PRA model grid search**

366 In contrast to the raster based validation approach of Bühler et al. (2018), our validation dataset requires analysis on the scale 367 of individual polygons. Since we do not know the explicit locations of the release areas in polygons with release area 368 proportions of 25%, 50%, or 75%, we cannot directly compare the PRA model output to the validation polygons on a pixel-369 by-pixel basis. Instead, we have to compare the total area within each polygon that is considered a PRA by the model to the 370 proportion provided by the local guides. To calculate the PRA error we subtracted the proportion of the polygon that the PRA 371 model determines as a release area (0-100%) from the release area proportion determined by the guides (0%, 25%, 50%, 75%, 372 100%) for each validation polygon. For example, if the PRA model output predicted that a polygon contained 60% PRA and 373 the guides designated that polygon as containing 50% release area, then the PRA error would be -10%. This PRA error value

- 374 is the basis of our grid search process and can range from -100% to 100% depending on whether the PRA model overpredicted
- or underpredicted the guides estimated release area proportion.
- To properly reflect the validation data collection process in our analysis we also need to consider the hierarchical structure of assessment polygons collected from the local guides. The highest value validation data are the 100% and 0% polygons because they provide explicit spatial extents for PRA locations. These polygons are from locations the participating guides are most familiar with and have the highest level of confidence in. We therefore placed more emphasis on PRA model performance in these areas when selecting the optimal inputs. The validation polygons with the greatest uncertainty are the run polygons. They were not explicitly drawn by the guides and the absence of PRA within these polygons was implicit and not explicitly specified. Hence, the accuracy of these polygons was weighted least in selecting the optimal PRA input parameters.



Figure 7. PRA model input parameters. *Slope angle, curvature*, and *ruggedness* derived from the DEM (a-c) and *forest density* derived
 from the forest mask (d). Forest data created using Planet Labs RapidEye imagery (Planet Team, 2017).

386

To select optimal input parameters for the PRA model we performed a grid search as described by Bühler et al. (2018) using the following values: *slope angle minimum* (default 30°, range 20°–40°), *slope angle maximum* (default 60°, range 45°–65°), *ruggedness window* (default 9, range 3–15), *ruggedness maximum* (default 6.0, range 0.5–10.0), *curvature maximum* (default 6.0, range 0.5–10.0), *forest density* (default NA, range 0–4), *forest slope scalar* (default NA, range 0.0–2.0) (Table 1). It is computationally not feasible to test all possible combinations of input parameters, therefore we used a set of default parameters from Bühler et al. (2018) as a baseline and iterated over each parameter to analyze the impact on the accuracy of the model. Based on validation using the guide polygons we systematically updated the default parameters to optimize the PRA model accuracy for our study area (Figure 1, Step 3c). The input parameters *slope angle minimum, slope angle maximum, ruggedness window, ruggedness maximum,* and *curvature maximum* are derived from the DEM (Figure 7 a–c). The *forest density* input

396 parameter is derived from the forest mask (Figure 7 d).

Table 1. Grid search input parameter values. Optimized input parameters indicate that the grid search led us to change the default
 input parameter to a value that improved the PRA model accuracy for our study area.

Input Parameter	Range	Interval	Default	Optimized
Slope Angle Minimum	20°-40°	1°	30°	Yes
Slope Angle Maximum	45°-65°	1°	60°	No
Ruggedness Window	3-15	2	9	No
Ruggedness Maximum	0.5-10.0	0.5	6.0	No
Curvature Maximum	0.5-10.0	0.5	6.0	No
Forest Density	0-4	1	NA	Yes
Forest slope scalar	0.0-2.0	0.25	NA	Yes

399

400 Selecting the optimal set of input parameters did not rely on any single statistic. Each PRA model iteration was compared 401 using the mean absolute error (MAE), mean bias error (MBE), proportion of accurate polygons, and proportion of 402 underestimated and overestimated errors. MAE values can range from 0 to 100, with lower values indicating a more accurate 403 model. MBE values can range from -100 to 100, with 0 indicating a balance between positive and negative errors. Polygons 404 were considered accurately predicted if the PRA error was within $\pm 12.5\%$, meaning that the area of the PRA model output 405 and guide estimate were within a 25% range of each other which is equivalent to 1 step in the guides rating scale (0%, 25%). 406 50%, 75%, 100%). Underestimated and overestimated polygons are defined as having a PRA error greater than $\pm 12.5\%$, and 407 polygons with a PRA error greater than $\pm 25\%$ were considered severely overestimated or underestimated.

The accuracy statistics for each grid search iteration were calculated on the basis of the total number of polygons (n = 167). We elected not to weight the statistics based on polygon size because the highest value validation polygons (0% and 100%) are generally the smallest. Selecting the optimal input parameters for our PRA model required evaluating performance across all these statistics and taking the structure of our validation dataset into account.

When selecting the optimal set of input parameters we erred on the side of a model that overestimates the extent of potential avalanche release areas, which is indicated by a negative MBE. We consider this an appropriate approach because the guides' polygons reflect only the avalanche conditions that they have experienced and recall. Despite their multiple decades of experience, the guides have not witnessed all potential combinations of snowpack conditions, which could cause avalanche 416 release in uncommon areas. In contrast, the PRA model is a terrain based tool which aims to identify locations in the study

417 area which have the potential for avalanche release independent of snowpack conditions.

418 4 Results and discussion

Since the context of the input data, parameter settings, and output from the original model are vital for evaluating the performance of our updated version of the PRA model, we combine the results and discussion into a single section. After presenting and commenting on the results, we conclude this section with an evaluation of some likely sources of error for our updated PRA model and share our thoughts on the limitations of a purely satellite remote sensing based method for capturing forest character in the PRA model.

424 **4.1 Data preparation pipeline**

The data preparation pipeline produced a 5 m resolution satellite DSM and forested land cover data set as input for the PRA model. Using 15 internal check points (ICP), the DSM accuracy can be described with a median vertical error of -0.43 m and normalized median absolute deviation (NMAD) of 4.72 m (Table 2). These accuracy metrics indicate good performance of the stereo DSM method, especially considering the rugged mountainous terrain across our study area and close proximity of steep slopes to some of the ICP. Compared to the best available existing DEM for our study area (18 m resolution CDEM), the SPOT 6 DSM provides vastly improved small scale terrain feature identification (Figure 8).

431



Figure 8. Comparison of existing 18 m resolution CDEM to 5 m resolution SPOT6 satellite stereo DSM, derived from our data
 preparation pipeline. Canadian DEM data from Natural Resources Canada.

435 Table 2. Accuracy statistics for SPOT6 satellite stereo DSM based on 15 ICP. The error type Δ h indicates the change in height 436

Metric	Error Type	Value (m)	
Median	Δh	-0.43	
NMAD	Δh	4.72	
68.3% quantile	Δ h	3.96	
95% quantile	∆ h	9.25	

between the ICP and the DSM surface.

437

438 The forested land cover classification that emerged from our random forest analysis yielded an overall accuracy of 98.88% 439 based on 253 training polygons (12.0 km²). The area under the receiver operating characteristic curve (AUC) is 99.89%. The 440 classification feature importance showed heavy reliance on the red edge (59.8%), NDWI (15.2%), and green (14.9%) bands. 441 This indicates that the red edge band was by far the most important imagery band to delineate forested pixels.

442 Creating the forested land cover classification using the same satellite imagery as the stereo DSM processing would be the 443 most efficient workflow for producing the necessary input data sets for PRA modelling, because it uses the least possible input 444 data and thereby minimizes data acquisitions costs and effort. However, in our study, we elected to utilize Rapid Eye imagery 445 as an alternative due to better overall lighting conditions and improvements in accuracy, primarily due to the red-edge spectral 446 band. The overall accuracy of our classifier and the feature importance of the red edge band highlight the strength of RapidEve 447 imagery for forest classification modelling.

448 Our processing pipeline provides a cost-effective approach for creating high-resolution DEM and forested land cover 449 classification data in remote and data sparse regions. Compared to alternative methods, such as LiDAR and commercial 450 satellite stereo DEM products, purchasing raw satellite stereo imagery to produce a high-resolution DEM provides significant 451 cost savings, control over the DEM generation settings, and produces a DEM product with sufficient accuracy (Kramm and 452 Hoffmeister, 2019; Shean et al., 2016). The primary limitations are the inability to resolve bare ground terrain features, 453 susceptibility to DEM holes due to cloud cover and lighting conditions, and degree of technical knowhow and computer 454 processing resources required to convert the raw imagery to a DEM product. Despite these limitations, the processing pipeline 455 enhances accessibility for high-resolution PRA modelling in remote regions.

456 An alternative approach, which has the advantage of decreasing the technical skills required to produce a stereo DEM while 457 still having significant cost saving benefits over LiDAR, is to purchase an off the shelf stereo DEM from a commercial satellite 458 imagery provider. Costs vary greatly depending on resolution, location, and whether archival imagery is available for a given 459 study area. In our case existing DEMs or stereo imagery were not available in our study area, so the added costs of new image 460 acquisition and processing made producing our own DEM more advantageous. Those interested in applying these methods to 461 their own area should carefully evaluate costs of acquiring a 5 m DEM to assess the feasibility of high resolution PRA 462 modelling.

463 **4.2 Model parameter selection based on grid search**

464 Based on the grid search we determined the optimal model input values for our study area are: *slope angle minimum* 27°, *slope* 465 angle maximum 60° , curvature maximum 6.0, ruggedness window 9, ruggedness maximum 6.0, forest density 4, and forest 466 slope scalar 1.25. The grid search method that we implemented is based on a set of default input parameters and does not 467 calculate all possible combinations of input parameters in order to reduce the amount of computer resources necessary. 468 Therefore, the results of the grid search are dependent on the selected default parameters. We tested a wide range of potential 469 default parameters for our grid search and used the values from Bühler et al. 2018 as a starting point. We selected the optimal 470 values by visualizing the distribution of the *PRA error* and plotting the MAE and MBE values for each grid search iteration 471 (Figure 9).

472 Due to the high quality and long-term avalanche observation records used for validation in Bühler et al. 2018, we retained their 473 default parameter values if the grid search did not demonstrate notable improvement in overall accuracy based on the local 474 validation dataset. This was the case for slope angle maximum, ruggedness window, ruggedness maximum, and curvature 475 maximum. The results of our grid search for these parameters are similar to those shown in Figure 3 of Bühler et al. 2018, with 476 relatively low variation in accuracy across the range of grid search values (Figure 9, panels b to e). The consistency of these 477 input parameters for both Davos and Galena are likely due to using the same DEM resolution of 5m and points to the 478 universality of the physical characteristics necessary for avalanche release. In addition, this consistency is a testament to the 479 accuracy of our satellite DSM in comparison to the high-resolution DEM data used in the Davos research.



Figure 9. Results of PRA model grid search. In each of the panels, the left Y-axis shows the percentage of polygons in different PRA error classes with colored bars (accurate – yellow, underestimated – red, overestimated – blue). Black squares and triangles show the values of MAE and MBE for each grid search iteration with a grey dashed horizontal line to show the 0 threshold which correspond to the right Y-axis. The vertical back lines indicate the optimized parameter settings.

485 4.2.1 Slope angle minimum

486 Slope angle minimum has the largest impact on the performance of the PRA model. Selecting the optimal input parameter 487 required balancing the performance of the PRA model against the different types of validation polygons and considering our 488 target of a frequent avalanche scenario. When considering the entire validation polygon data set, there is a sharp increase in 489 the percentage of underestimated validation polygons as the *slope angle minimum* threshold increases from 25°, which 490 indicates that the PRA model progressively excludes observed release areas (Figure 9, panel a). The MAE minimum of 491 approximately 18 occurs between 26° and 28° , indicating that these values produce the most accurate versions of the PRA 492 model. The MBE is negative for *slope angle minimum* values below 30° with a steep decrease between 26° and 30° . This 493 shows that decreasing the *slope angle minimum* below 30° creates PRA models that are progressively more biased towards 494 overestimating release areas.

To further analyze the performance of the PRA model we separated the validation polygons based on the validation polygon type. 0% and 100% polygons have the highest accuracy with values of *slope angle minimum* less than 25° (Figure 109, panel a). This trend strongly contrasts the other polygon types (Figure 109, panels b and c), which have higher percentages of accurate polygons for *slope angle minimum* values > 26°. For 0% and 100% polygons the percentage of accurate polygons declines steeply above 26° accompanied by an increase in severely underestimated polygons. The MAE and MBE statistics follow a similar trend, with relatively uniform values until 27° followed by steeply increasing error rates and positive bias for the remaining grid search inputs.



503

Figure 10. Frequent avalanche scenario PRA model grid search results for *slope angle minimum* with validation polygons split based on the type of polygon.

507 The 25%, 50%, and 75% polygons (Figure 10, panel b) have a bimodal distribution for percent of accurate polygons, with 508 slight peaks at 27° and 33°, accompanied by a steep increase in underestimated polygons from 27° upward. The MAE values 509 are at their minimum between 27° and 33° with relatively uniform values within that range. Both above and below that range 510 we see increasing MAE values, indicating a less accurate model for this group of polygons. Below 30° the MBE values indicate 511 a negative bias and have a steeply negative trajectory. This shows a strong bias toward overestimating PRA area for 25%, 50%, and 75% polygons at lower values of *slope angle minimum*. 513 The run polygons (Figure 10, panel c) have the highest accuracy with *slope angle minimum* greater than 31°. However, the

- 514 percentage of severely overestimated polygons decreases drastically at 27°. Below 28°, the MAE and MBE have steeply 515 increasing error rates and negative biases, respectively. Above 28° the curves flatten out and trend towards 0 for both MAE 516 and MBE.
- 517 Our choice of a 27° *slope angle minimum* strikes a balance between PRA model performance for each polygon type with a 518 priority towards optimizing performance on the 0% and 100% polygons, which are the most spatially explicit and have the

519 highest degree of certainty. Setting the *slope angle minimum* lower than 27° would result in too strong of a bias towards 520 minimizing underestimated errors which is not appropriate given our target of a frequent avalanche scenario. This is illustrated 521 by a decrease in overestimated and severely overestimated polygons at a *slope angle minimum* value of 27° for the 25%, 50%, 522 75% polygon dataset as well as the run polygons (Figure 10, panels b and c).

523 4.2.2 Forest density and forest slope scalar

Determining the optimal value for *forest density* was the most straightforward of the three parameters we optimized because the percentage of accurate polygons, lowest MAE, and lowest proportion of underestimated polygons all occur at a density value of *very dense (4)* (Figure 9, panel f). Setting *forest density to very dense (4)* means that the PRA model is not restricted by any forest mask and the *forest slope scalar* is applied across the full range of *forest density* values.

528 Out of the three parameters we optimized, *forest slope scalar* has the least variation in percentage of accurate polygons, MAE, 529 and MBE across the range of values tested in the grid search (Figure 9, panel g). This indicates that the PRA model 530 performance is less sensitive to changes in *forest slope scalar* compared to *slope angle minimum* and *forest density*. However, 531 setting this parameter to 1.25 helps to create a more balanced model by decreasing the number of overestimated polygons, 532 which is illustrated in the upward trend of the MBE value.

Similar to *slope angle minimum*, we see a decrease in the percentage of severely overestimated polygons for the 25%, 50%, and 75% and run polygon datasets for higher values of *forest slope scalar* (Figure 11, panels b and c). This is a trade off with a slight decrease in the percentage of accurate polygons and increase of percentage of underestimated polygons for the 0% and 100% polygons (Figure 11, panel a). This is reflected in the 0% and 100% polygon MBE value of -0.81 at 1.25, which is relatively high compared to the other polygon types. Given our target of a frequent avalanche scenario this trade off is justified to create a balanced PRA model and account for the influence of forested terrain on avalanche release.



540

541 Figure 11. Frequent avalanche scenario PRA model grid search results for *forest slope scalar* with validation polygons split based on 542 the type of polygon.

544 **4.3 PRA model output and comparison**

The final PRA model captures 57.5% (96 of 167) of the consensus validation polygon data set accurately, which we define as the PRA model predicted area is within \pm 12.5% of the area specified by the guides for each validation polygon (Table 3). The remainder of the validation polygons were either underestimated 10.2% (17 of 167) or overestimated 32.3% (54 of 167), compared to the guides' consensus estimates of release area proportion. The MAE value is 18.2, which is a measure of the average error across all polygons. The MBE value is -10.9, which indicates that the PRA model errors are negatively biased towards overestimating release areas. This interpretation of the MBE value aligns with the skewed distribution of underestimated and overestimated polygons.

- 552
- 553
- 554

555 Table 3. PRA model comparison

PRA Model	MAE	MBE	Accurate %	Under %	Over %
Present model	18.2	-10.9	57.5	10.2	32.3
Bühler 2018 – Forest Mask	33.1	22.3	31.0	58.3	10.7
Bühler 2018 – No Forest Mask	21.4	-3.7	45.8	25.0	29.1

556

557

To evaluate whether our parameter optimization demonstrates meaningful improvement, we compared the accuracy statistics of the model using the optimized parameters (Present model) to the Bühler et al. (2018) defaults both with and without a forest mask (Table 3). The 'Bühler 2018 – forest mask' PRA model does not identify release areas in any terrain identified as forested based on the land cover classification, whereas the 'no forest mask' version allows the PRA model to calculate release areas in all terrain. Since the 'forest mask' version naturally performs substantially worse in most accuracy statistics due to the large proportion of forested terrain in our study area, we will focus the comparison on the 'Bühler 2018 – no forest mask' model version.

565 Overall, we see improvements in the MAE, percent of accurate polygons, and percent of underestimated polygons using the 566 locally optimized input parameters. The MAE for the present model is 18.2 compared to 21.4 for the 'Bühler 2018 – no forest 567 mask' version, demonstrating a slight improvement in overall model error (Table 3). The present model improves the percent 568 of accurate polygons by 11.7 percentage points over the 'Bühler 2018 – no forest mask' PRA model, which is a substantial 569 improvement given the marginal gains observed in prior PRA model comparisons (Bühler et al. 2018). Similarly, the reduction 570 of 14.8 percentage points for underestimated polygons between the present model and the 'Bühler 2018 – no forest mask' 571 demonstrates the improved performance of the grid search optimization. These improvements can be attributed to optimizing 572 the *slope angle minimum* and *forest slope scalar* input parameters using the local validation data.

The trade off of the optimized input parameters for the present model is a bias towards overestimation, which is indicated by the MBE of -10.9 compared to -3.7 for the 'Bühler 2018 – no forest mask'. This is also shown by the slight increase of 3.2 percentage points in overestimated polygons from the 'Bühler 2018 – no forest mask' to the present model. Producing a more negatively biased PRA model is in line with our mindset of creating a PRA model that errs on the side of overestimating observed release areas. In our opinion, the benefits of improved percentage of accurate polygons and underestimated polygons outweighs the downside of a slight increase in overestimated polygons.

The present model has a substantially lower *slope angle minimum* of 27° compared to the default value of 30° from Bühler et al. (2018), which results in a notable increase in the overall area of the PRA output due to expansion into lower angle terrain (Figure 12). The fact that the validation data led us to a substantial decrease in *slope angle minimum* is likely due to differences in the terrain and snowpack characteristics in our study area compared to the region of Davos in Switzerland where the model 583 was initially validated. The avalanche character in our study area is prone to persistent avalanche problem types with the most 584 common weak layers being either surface hoar or faceted crystals associated with a crust (Hägeli and McClung, 2003; Haegeli 585 and McClung, 2007; Shandro and Haegeli, 2018). As a weak layer, surface hoar can release at lower slope angles and has 586 increased potential to propagate across terrain features compared to other weak layer types (McClung and Schaerer, 2006). 587 Despite our aim of excluding outlier release areas with extremely low slope angles that are only capable of producing 588 avalanches under very specific snowpack conditions from the validation dataset in order to target a more frequent avalanche 589 scenario, the widespread influence of surface hoar as a weak layer in our study area still contributes to an overall lower 590 minimum slope angle threshold. The fact that our validation data set and grid search approach produced a PRA model that also 591 aligns with our theoretical understanding of the snowpack properties in our study area is an encouraging result. However, in 592 terrain within the study area that is not prone to surface hoar development, such as alpine terrain with a high degree of wind 593 and sun exposure, our PRA model is likely to overestimate PRA extent.

594



595

Figure 12. Comparison of present PRA model to 'Bühler 2018 – forest mask'. Present model PRA area is dark purple with light
 purple for forested areas. 'Bühler 2018 – forest mask' is shown in orange for comparison. Inset map shows detailed PRA comparison
 on a local scale, extent shown by black dotted line. Forest data created using Planet Labs RapidEye imagery (Planet Team, 2017).

600 4.4 Potential sources of PRA model errors

601 Based on discussions with our collaborating guides and exploring spatial patterns of discrepancies between our validation data 602 set and PRA model output, we have highlighted two likely sources of error in our PRA model. First is the limitation of using 603 a relatively simple remote sensing based approach to account for forested release areas in the PRA model, which does not 604 explicitly capture forest characteristics that are known to have a strong bearing on the interaction of avalanches and forest, 605 such as crown cover, stem density, and gap size (Bebi et al., 2009; Teich et al., 2012). Second is the inherent uncertainty of 606 relying on human experience to generate validation data, which can be subject to individual biases and faulty recollection. 607 Overall, we believe that the forest characterization is responsible for a larger portion of the PRA model error and is the most 608 fruitful direction for future research to try and address. This section provides examples of these sources of error and discusses 609 how we have attempted to minimize their impact on the PRA model accuracy.

610 **4.4.1 Forest characteristics**

To shed light on potential sources of PRA model errors we applied two different approaches that consider different spatial scales. First, we visualized the spatial patterns in the PRA errors for each validation run and consulted the local guides to provide their insight. Second, we extracted the terrain characteristics of the entire set of validation polygons and compared the distributions of the terrain characteristics based on the PRA error value. Both approaches yielded similar insight, which highlight the challenge of capturing forested avalanche release areas accurately using an approach based purely on satellite imagery.

617 Visualizing the patterns of PRA model error by validation run reveals concentrated clusters of higher PRA error on specific 618 runs or subregions within runs (Figure 13). The 'Lunatic Fringe' run has by far the highest proportion of overestimated 619 polygons out of the five validation runs, with 22 out of the 42 validation polygons being overestimated (Figure 13, panel a). 620 Based on information provided by the local guides, this run is characterized by a steep continuous face with several well-621 defined large avalanche paths dissecting mostly forested terrain. The forest is very dense and impassable for a guided group at 622 the upper elevations of this run. In contrast, the 'Red Baron' run, which is located directly across the valley from 'Lunatic 623 Fringe', contains lower slope angle terrain with a large proportion of mature forest (Figure 13, panel b). The forest has greater 624 canopy height with widely spaced gaps between the individual trees. The forest canopy between each tree extends horizontally 625 enough that the land cover classification is unable to detect many of the gaps on the forest floor. This run contains 7 out of 8 626 of the severely underestimated validation polygons, with the other polygon located in a forested area with similar 627 characteristics on the 'Bandito' run.





Figure 13. PRA model accuracy for each validation run, with the downslope direction at the bottom of each panel. The validation
 polygons are labelled with their release are proportion and color coded based on the *PRA error* for each individual polygon. For
 overlapping validation polygons we retain the highest release area proportion value and clip that area from the surrounding lower
 proportion polygon.

While the *forest slope scalar* input parameter is designed to account for the interaction of forest and avalanche release, it is challenging to apply it on these two drastically different types of forested terrain. For 'Lunatic Fringe', increasing the *forest slope scalar* input parameter would improve accuracy by increasing the *slope angle minimum threshold* based on the local *forest density*. However, increasing the *forest slope scalar* would be detrimental for 'Red Baron' because of the potential for avalanche release in forest gaps within densely forested areas. These two contrasting examples of how the PRA model handles avalanche forest interaction highlight the challenge in creating a balanced PRA model which compromises performance in each type of forested terrain.

The guides' descriptions of the local forest character causing PRA errors for 'Lunatic Fringe' and 'Red Baron' are supported by our analysis of terrain characteristics based on the validation polygon dataset. To investigate whether there are common patterns in the terrain characteristics of validation polygons based on their PRA error value we extracted the aspect, curvature, elevation, forest cover, forest density, ruggedness, and slope angle distributions for the validation polygon dataset. While the majority of these terrain characteristics had similar distributions for all classes of PRA error, forest cover percentage and forest density had distinct differences. For 'severely underestimated' polygons the distributions and median values are biased towards higher percentages of forest cover and forest density compared to other PRA error classes (Figure 14).

650





Figure 14. Analysis of PRA error based on forest density and percentage of forested area for the validation polygon data set. The plots show the distribution of forest density and forest cover percentage for validation polygons based on their PRA error.

32

This further illustrates the guides' interpretation that the severely underestimated polygons on 'Red Baron' have high forest density and the limitation of our *forest slope scalar* approach for accounting for forested terrain with highly variable characteristics. It is important to note that the sample size of 'severely underestimated' polygons is small with only eight polygons. For context, the distribution 'severely overestimated' (n = 37) polygons also include high percentages of forest cover and forest density, which can be partially attributed to the dense and tightly spaced forested terrain on 'Lunatic Fringe'.

660 The PRA errors on 'Lunatic Fringe' and 'Red Baron' demonstrate the limitations of our approach in capturing the real world 661 forest characteristics. Further improving the performance of the PRA model in forested terrain would require more detailed 662 data sets such as LiDAR or a field based forest inventory which could capture additional forest characteristics such as stem spacing (Waser et al., 2015; Hyyppä et al., 2000; Dash et al., 2016), which are beyond the scope of this research. A notable 663 664 publicly available source of LiDAR vegetation height measurements which could be used to interpolate forest height or overall 665 biomass and potentially improve the performance of PRA models in forested terrain is the NASA ICESat-2, which collects 666 LiDAR point measurements across the globe. The benefit of our method is to create cost-effective and high-resolution 667 avalanche terrain maps based exclusively on remotely sensed data which can be applied in any location, regardless of 668 remoteness or accessibility. For this purpose, our approach allows forested terrain to be captured in the PRA model on a basic 669 level and broadens the range of avalanche terrain that the model can be applied to.

670 4.4.2 Uncertainty in validation data

One of the key differences in relying on local expertise for model validation is the necessity to incorporate uncertainty. There are two distinct types of uncertainty that are relevant for validating the PRA model: 1) Uncertainty in the accuracy of the observations, recollection, and experience of our collaborating guides, and 2) uncertainty in the reference datasets we provided them with to transfer their knowledge into spatial datasets and precision of polygon drawing.

In the case of guide observations, the primary sources of uncertainty in determining the location of avalanche release areas are the variability of avalanche conditions, how often the terrain is observed throughout the season, the guides recollection of avalanche events, and the potential for altered snowpack structure due to frequent guiding. These limitations are inherent to relying on human recollection as a source of validation data. However, our approach for capturing validation polygons from local experts accommodates these limitations by allowing for fuzzy boundaries in drawing polygons, collecting validation data from multiple guides independently, and intentionally minimizing the specificity that we ask the guides to label the release area proportions (0%, 25%, 50%, 75%, 100%).

The process for collecting validation data from our collaborating guides evolved through frequent back and forth discussions. When applying the validation polygons to select optimal input parameters for our study area we accounted for the nature of the data collection by placing more emphasis on the performance of 0% and 100% polygons, which have the highest level of certainty for the guides and are the most spatially explicit. We also preferred input parameters that resulted in a PRA model

33

- that is biased toward overestimating release areas in order to account for the potential that the guides have not witnessed all possible combinations of snowpack and weather conditions in our study area, despite their extensive experience.
- 688 An example of how the guides' experience can influence our validation data set can be seen in the right half of the 'Rendezvous' 689 ski run, where there are many severely overestimated validation polygons (Figure 13, panel c). According to our DEM, the 690 slope angles in this area are predominantly in the low to mid thirties, which are within the range observed for human triggered 691 avalanches (Schweizer and Lütschg, 2001). However, the guiding operation frequently uses this piece of terrain and 692 intentionally manages the snowpack using skier traffic to minimize the potential for weak layers to form and persist on the 693 surface (e.g., surface hoar). Frequent guiding use and intentional maintenance of weak layers can create a modified snowpack 694 structure (Haegeli and Atkins, 2016) and has the potential to impact the guides' perception of release area potential. In areas 695 where the guide's experience is largely based on modified snowpack structures there is a high potential for the PRA model to 696 overestimate avalanche release compared to the validation data set.
- 697 While our workflow for collecting validation data from local guides was customized for our use case, these methods could be 698 adapted to other professional communities such as avalanche forecasters or ski patrol. We recommended considering the 699 following key principles for developing meaningful PRA validation datasets:
- Identify a manageable size area to create the validation dataset that is representative of the terrain and snowpack
 conditions in the larger study area you want to apply the PRA model.
- Solicit feedback from collaborators to identify sources of uncertainty in their ability to translate their local experience
 into polygons that can be compared to the PRA model output.
- Incorporate that uncertainty into the validation process by allowing them to use fuzzy boundaries to identify potential
 release areas.
- Take the structure of the validation data into account when performing statistical comparisons to the PRA modeloutput.
- This process can be time consuming and iterative, but it is critical to ensure shared understanding of the validation data between researchers and collaborators. In the absence of long-term observations of avalanche events in most mountainous regions the development of methods to extract local knowledge from human experts is critical to the application and validation of PRA models.

712 4.5 Limitations

The primary limitations of this research are direct consequences of our aim to minimize the cost of input data production and create a flexible workflow to apply and validate the PRA model in remote and data sparse regions. Using a DSM as input for a PRA model has not been thoroughly tested, and the inability to detect bare ground features within forest canopy likely causes localized errors in the PRA model. Recently, a comparison of high-resolution DSM and DTM models for avalanche runout

717 modelling demonstrated some of the limitations of a DSM for dynamic avalanche simulation (Brožová et al., 2020). We were

- unable to test the accuracy of the SPOT6 DSM compared to a DTM due to the lack of alternative high-resolution data in ourstudy area.
- Relying exclusively on optical satellite imagery to account for forest avalanche interaction provides limited detail on meaningful forest characteristics. Explicit modelling of stem density, gap size, or crown cover could improve the PRA model's ability to capture forest avalanche interaction (Dash et al., 2016; Wallner et al., 2015). However, our focus is on minimizing field data collection to create a workflow that is applicable in remote areas.
- Finally, the experience of local experts is not an ideal source to generate validation data compared to long term observation records. Observations from individual experts are prone to biases in their experience and potential for faulty recollection. We attempted to minimize these effects on our dataset by collaborating closely with the guides to develop a system for recording their observations that allows for uncertainty and is based on independent observations of multiple guides.

728 **5 Conclusions**

729 This research aimed to increase the range of application for existing high-resolution PRA modelling by developing a cost-730 effective workflow for generating the required input datasets, expanding current PRA modelling methods to include avalanche 731 forest interaction, and by creating a novel approach for validating the model based on the local expertise of avalanche 732 practitioners for data sparse regions. The research produced an updated version of the Bühler et al. (2018) PRA model which 733 enables high-resolution avalanche terrain modelling in a vastly greater proportion of mountainous terrain than previously 734 possible. This is thanks to the widespread availability of the necessary satellite remote sensing input data and local expertise 735 required to validate and optimize the PRA model input parameters. The updated model also allows for inclusion of forested 736 terrain with varying densities, contributing to a substantial improvement in the performance of the PRA model in our study 737 area.

738 The data preparation pipeline developed for this research is based on open source software and intended to be reproducible in 739 areas without existing high-resolution DEM and forest cover data sets, which achieves our goal of making high-resolution 740 PRA modelling more accessible in remote and data sparse areas. Producing a satellite stereo DSM based on raw imagery 741 provides control over the DSM characteristics and minimizes the cost associated with acquiring this essential data set. Further 742 testing of the DSM pipeline developed for this research is required, especially in forested terrain, and could provide a 743 meaningful direction for future research. Despite the dramatic cost reduction of our workflow, high resolution satellite stereo 744 imagery areas still relatively costly so readers interested in applying PRA models in their own area should carefully evaluate 745 costs of acquiring the necessary input data.

746 Using locally optimized input parameters, our updated PRA model has a higher overall accuracy and less underestimated 747 release areas compared to the default parameters developed for Davos, Switzerland in Bühler et al. (2018). Our validation 748 approach utilizes local expertise to collect avalanche release area polygons via a custom-built online mapping tool and applies spatial and statistical analysis to quantify the accuracy of the PRA model. We leveraged this unique validation data set to develop a new polygon based grid search approach to optimize the PRA model input parameters. Creating a validation method that allows for optimization of the PRA model in areas without a long standing avalanche observation dataset is essential to evaluate the PRA model performance in new locations. This method also provides the opportunity for comparison of optimal input parameters in different snow and avalanche climates. Future research applying the PRA model in maritime and continental snow climates would provide additional insight into how the input parameters can be optimized for a broader range of snowpack and avalanche conditions, which are not captured in the existing Davos or Galena study areas.

To include forested terrain in the PRA model we focused on creating a simple addition to the existing PRA model which does not require any additional input data and remains an optional extension of the existing PRA model framework. We also focused on maintaining the ability to create the input data sets via optical satellite remote sensing methods to minimize the overhead cost and effort to produce forest characteristic data. Our approach allows the PRA model to capture the interactions between forests and avalanche release by controlling the *forest density* where the PRA model is applied and altering the *slope angle minimum* threshold based on the local forest density. These two changes are simple yet effective methods to account for forest cover in PRA modelling.

Additional research focused on satellite imagery based modelling of forest characteristics (Dash et al., 2016; Hyyppä et al., 2000), such as stem density and gap size, could further improve the performance of PRA models in forested terrain. While the availability of high-resolution LiDAR, laser scanning, or field measured forest characteristics are essential for meaningfully validating the derivation of these forest characteristics datasets (Waser et al., 2015), this type of development and analysis was beyond the scope of this research. The forest regions in our study area are dominated by coniferous tree species, which limits our ability to generalize the effectiveness of the PRA model in coniferous or mixed forest ecosystems. Hence, we encourage other researchers to explore our approach in other forest types.

Despite the limitations and shortcomings of our approach, the present research improves the accessibility of high-resolution PRA modelling by combining an existing state of the art PRA model with open source software tools and lower cost input data and presenting a flexible validation method to assess accuracy of the model output based on local terrain expertise. These developments have the potential to enable a more widespread application of high-resolution avalanche terrain indication modelling worldwide.

775 Code and data availability.

The data, code, and output for our analysis and the data and code for the figures and tables included in this paper are available at osf.io/yq5s3 (Sykes et al., 2021).

778 Author contributions

- JS created the data preprocessing workflow and input data sets with guidance from YB and PH. YB provided the original PRA
- 780 model. JS developed the *forest density* and *forest slope scalar* modification to the PRA model. PH and JS collaborated with
- 781 CMH Galena guides to collect validation data and implement online mapping tools to record the data. JS developed the
- validation and grid search methods with guidance from PH. JS prepared the manuscript with contributions from all co–authors.

783 **Competing interests**

YB and PH are members of the editorial board of Natural Hazards and Earth Science Sciences. The authors do not declare any
 other competing interests.

786 Acknowledgements

787 The study area of this research is located on the ancestral and unceded territories of the Secwéperc, Ktunaxa, Sinixt, and 788 Okanagan first nations. We wish to acknowledge our collaborators on this research from WSL Institute for Snow and 789 Avalanche Research (SLF) and Canadian Mountain Holidays Galena Lodge. In particular, we would like to thank Roger Atkins 790 and Mike Welch for their contribution to this work with their numerous conversations to develop our validation data collection 791 methods and their time and effort in translating their experience into a validation data set. This research was enabled in part 792 bv the support and computer resources provided by WestGrid (www.westgrid.ca) and Compute Canada 793 (www.computecanada.ca). The NSERC Industrial Research Chair in Avalanche Risk Management at Simon Fraser University 794 is financially supported by Canadian Pacific Railway, HeliCat Canada, Mike Wiegele Helicopter Skiing and the Canadian 795 Avalanche Association. The research program receives additional support from Avalanche Canada and the Avalanche Canada 796 Foundation. The NSERC Industrial Research Chair in Avalanche Risk Management receives financial support from HeliCat 797 Canada, the trade association of mechanized skiing operations in Canada.

798 **Financial support**

This research was funded by the Government of Canada Natural Sciences and Engineering Research Council via the NSERC
 Industrial Research Chair in Avalanche Risk Management at Simon Fraser University (grant no. IRC/515532-2016).

801 **References**

- Bebi, P., Bast, A., Helzel, K., Schmucki, G., Brozova, N., and Bühler, Y.: Avalanche Protection Forest: From Process
 Knowledge to Interactive Maps, in: Protective forests as Ecosystem-based solution for Disaster Risk Reduction,
 10.5772/intechopen.99514, 2021.
- Bebi, P., Kulakowski, D., and Rixen, C.: Snow avalanche disturbances in forest ecosystems State of research and implications
 for management, Forest Ecol. Manag., 257, 1883–1892, https://doi.org/10.1016/J.FORECO.2009.01.050, 2009.
- 807 Beyer, R. A., Alexandrov, O., and McMichael, S.: The Ames Stereo Pipeline: NASA's Open Source Software for Deriving
- and Processing Terrain Data, Earth Sp. Sci., 5, 537–548, https://doi.org/10.1029/2018EA000409, 2018.
- Boyd, J., Haegeli, P., Abu-Laban, R. B., Shuster, M., and Butt, J. C.: Patterns of death among avalanche fatalities: a 21-year
 review., Can, Med, Assoc, J., 180, 507–12, https://doi.org/10.1503/cmai.081327, 2009.
- Brožová, N., Fischer, J. T., Bühler, Y., Bartelt, P., and Bebi, P.: Determining forest parameters for avalanche simulation using
 remote sensing data, Cold Reg. Sci. Technol., 172, 102976, https://doi.org/10.1016/i.coldregions.2019.102976, 2020.
- 813 Bühler, Y., Bebi, P., Christen, M., Margreth, S., Stoffel, L., Stoffel, A., Marty, C., Schmucki, G., Caviezel, A., Kühne, R.,
- 814 Wohlwend, S., and Bartelt, P.: Automated avalanche hazard indication mapping on a statewide scale, Nat. Hazards Earth Syst.
- 815 Sci., 22, 1825-1843, 10.5194/nhess-22-1825-2022, 2022.
- 816 Bühler, Y., Hüni, A., Christen, M., Meister, R., and Kellenberger, T.: Automated detection and mapping of avalanche deposits 817 using airborne optical remote sensing data, Cold Reg. Sci. Technol., 57, 99-106. 818 https://doi.org/10.1016/j.coldregions.2009.02.007, 2009.
- Bühler, Y., Kumar, S., Veitinger, J., Christen, M., and Stoffel, A.: Automated identification of potential snow avalanche release
 areas based on digital elevation models, Nat. Hazard. Earth Sys., 13, 1321–1335, https://doi.org/10.5194/nhess-13-1321-2013,
 2013.
- 822 Bühler, Y., Adams, M. S., Stoffel, A., and Boesch, R.: Photogrammetric reconstruction of homogenous snow surfaces in alpine
- terrain applying near-infrared UAS imagery, Int. J. Remote Sens., 38, 3135–3158,
 https://doi.org/10.1080/01431161.2016.1275060, 2017.
- 825 Bühler, Y., von Rickenbach, D., Stoffel, A., Margreth, S., Stoffel, L., and Christen, M.: Automated snow avalanche release 826 area delineation - validation of existing algorithms and proposition of a new object-based approach for large-scale hazard 827 indication and proposition of a new object-based approach for large-scale hazard
- 827 indication mapping, Nat. Hazard. Earth Sys., 18, 3235–3251, https://doi.org/10.5194/nhess-18-3235-2018, 2018.
- 828 Bühler, Y., Hafner, E. D., Zweifel, B., Zesiger, M., and Heisig, H.: Where are the avalanches? Rapid SPOT6 satellite data
- acquisition to map an extreme avalanche period over the Swiss Alps, Cryosphere, 13, 3225–3238, https://doi.org/10.5194/tc13-3225-2019, 2019.
- 831 Campbell, C. and Gould, B.: A proposed practical model for zoning with the Avalanche Terrain Exposure Scale, in:
- 832 <u>Proceedings International Snow Science Workshop, 2013.</u>

- 833 Christen, M., Kowalski, J., and Bartelt, P.: RAMMS: Numerical simulation of dense snow avalanches in three-dimensional
- terrain, Cold Reg. Sci. Technol., 63, 1–14, https://doi.org/10.1016/j.coldregions.2010.04.005, 2010.
- Colorado Avalanche Information Center (CAIC), [online] Available from: https://avalanche.state.co.us/accidents/statisticsand-reporting/, last access: 27 April 2020.
- 837 Dash, J. P., Watt, M. S., Bhandari, S., and Watt, P.: Characterising forest structure using combinations of airborne laser
- 838 scanning data, RapidEye satellite imagery and environmental variables, Forestry, 89, 159-169,
- 839 https://doi.org/10.1093/forestry/cpv048, 2016.
- 840 Facciolo, G., De Franchis, C., and Meinhardt, E.: MGM: A Significantly More Global Matching for Stereovision, 2015.
- Feistl, T., Bebi, P., Teich, M., Bühler, Y., Christen, M., Thuro, K., and Bartelt, P.: Observations and modeling of the braking
 effect of forests on small and medium avalanches, 60, 124–138, https://doi.org/10.3189/2014JoG13J055, 2014.
- 843 Feistl, T., Bebi, P., Christen, M., Margreth, S., Diefenbach, L., and Bartelt, P.: Forest damage and snow avalanche flow regime,
- 844 Nat. Hazard. Earth Sys., 15, 1275–1288, https://doi.org/10.5194/nhess-15-1275-2015, 2015.
- 845 GDAL Contributors,: GDAL/OGR Geospatial Data Abstraction software Library., 2021.
- 646 Gillies, S. and Others: Rasterio: geospatial raster I/O for Python programmers, https://github.com/mapbox/rasterio, 2013.
- Gruber, U. and Haefner, H.: Avalanche hazard mapping with satellite data and a digital elevation model, Appl. Geogr., 15,
- 848 99–113, https://doi.org/10.1016/0143-6228(94)00004-A, 1995.
- 849 Haegeli, P. and Atkins, R.: Managing the Physical Risk From Avalanches in a Helicopter Skiing Operation--Merging and
- Contrasting Gps Tracking Data with the Operational Guiding Perspective, in: Proceedings International Snow Science
 Workshop, 104–111, 2016.
- 852 Haegeli, P. and McClung, D. M.: Expanding the snow-climate classification with avalanche-relevant information: initial 853 J. Glaciol.. 53. description of avalanche winter regimes for southwestern Canada. 266 - 276.854 https://doi.org/10.3189/172756507782202801, 2007.
- Hafner, E. D., Techel, F., Leinss, S., and Bühler, Y.: Mapping avalanches with satellites evaluation of performance and
 completeness, Cryosphere, 15, 983–1004, https://doi.org/10.5194/tc-15-983-2021, 2021.
- Hägeli, P. and McClung, D. M.: Avalanche characteristics of a transitional snow climate—Columbia Mountains, British
 Columbia, Canada, Cold Reg. Sci. Technol., 37, 255–276, https://doi.org/10.1016/S0165-232X(03)00069-7, 2003.
- Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S.,
- 860 Smith, N. J., Kern, R., Picus, M., Hoyer, S., van Kerkwijk, M. H., Brett, M., Haldane, A., del Río, J. F., Wiebe, M., Peterson,
- 861 P., Gérard-Marchant, P., Sheppard, K., Reddy, T., Weckesser, W., Abbasi, H., Gohlke, C., and Oliphant, T. E.: Array
- 862 programming with NumPy, Nature, 585, 357–362, https://doi.org/10.1038/s41586-020-2649-2, 2020.
- 863 Harvey, S., Schmudlach, G., Buhler, Y., Durr, L., Stoffel, A., and Christen, M.: Avalanche Terrain Maps for Backcountry
- 864 Skiing in Switzerland, in: Proceedings International Snow Science Workshop, 300, 2018.

- 865 Höhle, J. and Höhle, M.: Accuracy assessment of digital elevation models by means of robust statistical methods, ISPRS J.
- 866 Photogramm., 64, 398–406, https://doi.org/10.1016/j.isprsjprs.2009.02.003, 2009.
- Hyyppä, J., Hyyppä, H., Inkinen, M., Engdahl, M., Linko, S., and Zhu, Y. H.: Accuracy comparison of various remote sensing
 data sources in the retrieval of forest stand attributes, Forest Ecol. Manag., 128, 109–120, https://doi.org/10.1016/S03781127(99)00278-9, 2000.
- Jamieson, Bruce., Haegeli, P., and Gauthier, D.: Avalanche accidents in Canada, Canadian Avalanche Association, 2010.
- Korzeniowska, K., Bühler, Y., Marty, M., and Korup, O.: Regional snow-avalanche detection using object-based image
 analysis of near-infrared aerial imagery, Nat. Hazard. Earth Sys., 17, 1823–1836, https://doi.org/10.5194/nhess-17-1823-2017,
 2017.
- 874 Kramm, T. and Hoffmeister, D.: EVALUATION OF DIGITAL ELEVATION MODELS FOR GEOMORPHOMETRIC
- 875 ANALYSES ON DIFFERENT SCALES FOR NORTHERN CHILE, Int. Arch. Photogramm. Remote Sens. Spat. Inf. Sci.,

876 XLII-2/W13, 1229–1235, https://doi.org/10.5194/isprs-archives-XLII-2-W13-1229-2019, 2019.

- Kumar, S., Srivastava, P. K., Snehmani, and Bhatiya, S.: Geospatial probabilistic modelling for release area mapping of snow
 avalanches, Cold Reg. Sci. Technol., 165, 102813, https://doi.org/10.1016/J.COLDREGIONS.2019.102813, 2019.
- 879 Lato, M. J., Frauenfelder, R., and Bühler, Y.: Automated detection of snow avalanche deposits: segmentation and classification
- of optical remote sensing imagery, Nat. Hazard. Earth Sys., 12, 2893–2906, https://doi.org/10.5194/nhess-12-2893-2012,
 2012.
- 882 Maggioni, M. and Gruber, U.: The influence of topographic parameters on avalanche release dimension and frequency, Cold
- 883 Reg. Sci. Technol., 37, 407–419, https://doi.org/10.1016/S0165-232X(03)00080-6, 2003.
- 884 Margreth, S. and Funk, M.: Hazard mapping for ice and combined snow/ice avalanches two case studies from the Swiss
- and Italian Alps, Cold Reg. Sci. Technol., 30, 159–173, https://doi.org/10.1016/S0165-232X(99)00027-0, 1999.
- 886 McClung, D. and Schaerer, P.: The avalanche handbook, Mountaineers Books, 342 pp., 2006.
- 887 McClung, D. M.: Characteristics of terrain, snow supply and forest cover for avalanche initiation caused by logging, Ann.
- 888 Glaciol., 32, 223–229, https://doi.org/10.3189/172756401781819391, 2001.
- 889 Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R.,
- 890 Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., and Édouard, D.: Scikit-learn: Machine
- 891 Learning in Python, J. Mach. Learn. Res., 2825–2830 pp., 2011.
- 892 Planet Team.: Planet Application Program Interface: In Space for Life on Earth, https://api.planet.com, 2017.
- 893 QGIS Development Team.: QGIS Geographic Information System, http://qgis.org, 2021.
- 894 Rudolf-Miklau, F., Skolaut, C., and Sauermoser, S.: Avalanche Hazard Assessment and Planning of Protection Measures, in:
- 895 The Technical Avalanche Protection Handbook, 91–126, https://doi.org/10.1002/9783433603840.ch04, 2015.
- 896 Schweizer, J. and Lütschg, M.: Characteristics of human-triggered avalanches, Cold Reg. Sci. Technol., 33, 147–162, 2001.
- 897 Schneebeli, M. and Bebi, P.: Snow and Avalanche Control, Encycl. For. Sci., 397–402, 2004.

- 898 Shandro, B. and Haegeli, P.: Characterizing the nature and variability of avalanche hazard in western Canada, Nat. Hazard.
- 899 Earth Sys., 18, 1141–1158, https://doi.org/10.5194/nhess-18-1141-2018, 2018.
- Sharp, E., Haegeli, P., and Welch, M.: Patterns in the exposure of ski guides to avalanche terrain, in: Proceedings International
 Snow Science Workshop, 2018.
- 902 Shean, D. E., Alexandrov, O., Moratto, Z. M., Smith, B. E., Joughin, I. R., Porter, C., and Morin, P.: An automated, open-
- source pipeline for mass production of digital elevation models (DEMs) from very-high-resolution commercial stereo satellite
- 904 imagery, ISPRS J. Photogramm., 116, 101–117, https://doi.org/10.1016/j.isprsjprs.2016.03.012, 2016.
- Sykes, J., Haegeli, P., and Bühler, Y.: Automated snow avalanche release areas delineation in data sparse, remote, and forested
 regions -- Code and Data, https://doi.org/10.17605/OSF.IO/YO5S3. 2021.
- 907 Techel, F., Jarry, F., Kronthaler, G., Mitterer, S., Nairz, P., Pavšek, M., Valt, M., and Darms, G.: Avalanche fatalities in the
- European Alps: long-term trends and statistics, Geogr. Helv., 71, 147–159, https://doi.org/10.5194/gh-71-147-2016, 2016.
- 909 Teich, M., Bartelt, P., Grêt-Regamey, A., and Bebi, P.: Snow Avalanches in Forested Terrain: Influence of Forest Parameters,
- 910 Topography, and Avalanche Characteristics on Runout Distance, Arct. Antarct. Alp. Res., 44, 509-519,
- 911 https://doi.org/10.1657/1938-4246-44.4.509, 2012.
- 912 Veitinger, J., Purves, R. S., and Sovilla, B.: Potential slab avalanche release area identification from estimated winter terrain:
- a multi-scale, fuzzy logic approach, Nat. Hazard. Earth Sys., 16, 2211–2225, https://doi.org/10.5194/nhess-16-2211-2016,
 2016.
- 915 Voellmy, A.: Über die Zerstörungskraft von Lawinen, Schweizerische Bauzeitung, 73, 159–165, 1955.
- 916 Wallner, A., Elatawneh, A., Schneider, T., and Knoke, T.: Estimation of forest structural information using RapidEye satellite
- 917 data, Forestry, 88, 96–107, https://doi.org/10.1093/forestry/cpu032, 2015.
- 918 Waser, L., Fischer, C., Wang, Z., Ginzler, C., Waser, L. T., Fischer, C., Wang, Z., and Ginzler, C.: Wall-to-Wall Forest
- 919 Mapping Based on Digital Surface Models from Image-Based Point Clouds and a NFI Forest Definition, Forests, 6, 4510-
- 920 4528, https://doi.org/10.3390/f6124386, 2015.