

RC1: '[Comment on nhess-2022-210](#)', Dai Yamazaki, 21 Sep 2022

<General Comments>

The proposed research compared the different surface object removal method on Arctic DEM, and analyzed how DEM error correction impacts flood inundation simulation. Considering increasing availability of high-resolution DEM, I think the suggestions from this research (which correction method is better, which parameters are feasible, how correction impact flood inundation simulation) is very useful. It is good to see that the DEM error correction using SMRF method is robust using wide range of parameters.

One major suggestion I'd like to provide to enhance the manuscript is to include more discussion on the transferability of the proposed method (SMRF algorithm with optimum parameter range) to other regions. Readers must be interested in whether the optimum SMRF parameters detected by this study can be safely used to other regions or not. Please include some discussions about the parameter transferability (detailed suggestions are in the Specific Comments.)

Other than the above concern, the manuscript is I think very well organized. And it can be accepted after minor revision.

Thank you so much for your thorough comments, Dr Yamazaki. They are very useful in improving our manuscript. Our responses to each comment are made below.

<Specific Comments>

Line 41: "exponentially increased computational costs".

"Exponentially" is not precise. The calculation cost of 2D flow simulation follows approximately $(1/dx)^3$ where dx is the spatial resolution. If grid size becomes half, the computational cost is almost 8 ($=2^3$) times, it's not exponential.

Thanks for pointing this out. We revised the writing to be more precise.

'because of the rapidly increased computational cost of running fine grid models (roughly the ratio of grid change to the power of three)'.

Line 78: ASTER GDEM

Why not including AW3D DEM in reference here, which is more precise and now being widely used as high-accuracy stereo-view DEM?

This is a good point. We replaced the ASTER with the AW3D in the revision.

L84: SETSM

Please explain what "SETSM" stands for? When it appears first time.

Thanks for pointing this out. We changed it in the revision.

'ArcticDEM covers areas above 60°N and was produced using the Surface Extraction with TIN-based Search-space Minimization (SETSM) method from in-track and cross-track high-

resolution (~0.5 m) imagery acquired by the WorldView and GeoEye satellites.’

P257: Table 1

I suggest to put a line to distinguish PMF and SMRF, as the boundary is not clear.

Good suggestion. We now revised the table as below.

Table 1. Key parameter settings of the morphological filters tested in the three samples.

Filter	Sample	Key Parameters			
		Window size (m)		Slope threshold	
		range	interval	range	interval
PMF	S1	10-66	4	0.1-0.3	0.2
	S2	10-66	4	0.1-0.3	-
SMRF	S1	10-50	2	0.01-0.1	0.005
	S2	10-50	2	0.01-0.1	0.005
	S3	10-180	10	0.03-0.15	0.01

* The unit of the slope threshold values shown here is radian for PMF, percent of slope/100 for SMRF.

P270: Replaced with the LIDAR DTM values.

Please describe the situation of the Arctic DEM original value here. Are they “missing data”, or there are large error?

Thanks for this comment. This was done purely because that the errors in these areas are not of concern of this paper as they are covered by water, whereas we focus on modelling the flooding over the land surface in this paper.

P278: ensuring that the difference between the simulations was distinguishable.

The logic here is unclear. If large-magnitude flood is used as a test case, I assume flood extent is more confined by large-scale topography. Focusing on smaller-magnitude flood might be better to discuss the impact of topography improvement on flood risk estimation.

Thanks for raising this point. Regarding to flood performance evaluation, the flood inundation extent and water depth are the two aspects to our concern.

From the perspective of flood extent, we agree that larger-magnitude floods are more confined by large-scale topography compared to small ones. We also agree that the inundation extent of smaller-magnitude flood will be more sensitive to the topography error. But the flood extent can become overly sensitive to the topography error when the inundation depth is extremely shallow.

From the perspective of the water depth error, larger magnitude of scenarios can better assess the impact of topography error on the simulated water depth as the inundation will cover a higher ratio of the overall areas.

We meant to emphasize that this rarely occurred frequency of 500 years extreme rainfall was used as we preferred a short duration scenario. The sentence is now revised as '*A designed rainfall scenario with duration of 3 h and return period of 500 years was used in the simulation. To minimize the simulation time a short duration scenario is preferred, which led to our choice of the 3 h duration. The relatively low occurring frequency (500 years return period) was then chosen to avoid flood inundation being overly sensitive to the topography which would happen when the inundation is extremely shallow.*'

We also want to point out that the return period of 500 years is for the designed rainfall. It indicates the amount of water comes in the simulated domain but does not necessarily indicate the same return period of flooding.

P286: small isolated wet areas

Please explain the mechanism of how these are caused?

Thanks for the comment. The small isolated wet areas are common in pluvial flooding because its flow pathways are often not so confined as fluvial flooding. These small, isolated areas also appear in the simulation results of the LIDAR data. We excluded these areas with the same method for the LIDAR and ArcticDEM simulations.

P347: Figure 4

I don't think the cross marks for man error (right column) are meaningful. The optimum points exist as a "line" in white-color area, rather than as a point in case of the mean error. Putting one cross mark could be miss-leading.

Thanks for this comment. Yes, there might be multiple points where the absolute value of the mean error is the smallest among the 234 realizations. To avoid miss-leading, we now change the mark for the mean error as the location where the lowest RMSE is achieved (shown below). The figure caption is changed correspondingly.




Figure 4. Surface plots of the slope threshold and the window size parameters of the SMRF filter against the RMSE, the RMSE reduction percentage and Mean error of the filtered DEM-ArcticDEM-SMRF for sample S3. The location of the smallest values of the RMSE (which is the same as the location of the greatest values of the RMSE reduction) are marked as \times , with the values displayed. The values of the Mean error at the above location are displayed and marked as $+$. Parameter details can be found in Table 1.

L361: More than 40% of the parameter combinations can 362 reduce the RMSE by greater than a half.

This is important, but there must be something more to discuss for ensuring the robustness of the method. [1] The optimum combinations are almost same for three different land covers, suggesting the robustness of the parameter for various-time land-surface characteristics. [2] The skill-score does not significantly drop when parameter combination is slightly changed from the optimum location, suggesting the robustness of

estimated parameters. There must suggest the transferability of the method to another region?

Thanks for offering this comment. We made changes to the results section and extend the robustness in the discussion section in the revision of the manuscript.

‘These optimum parameters only vary within a rather small range for different land covers, suggesting that the parameter choice is robust for various land-surface characteristics. Moreover, the error removal effectiveness does not significantly drop when parameters slightly deviate from the optimum location, suggesting the robustness of parameters. More than 40% of the 234 parameter combinations can reduce the RMSE by greater than a half. The robustness of the filter across different land covers and a range of parameters is favoured as this loosens the prior knowledge request of the study site and simplifies the parameter setting for application across large domains.’

This robustness is inherent in the SMRF algorithm and thus is transferable. The robustness of parameter to the error reduction was also demonstrated by the [Pingel \(2013\)](#) which proposed the SMRF filter. The key of ensuring the robustness is deciding the range of the parameters. We explained it below.

In theory, to remove all objects in the target areas the window size should correspond to the size of the largest object in the target area. This is a hypothesized entirely flat area. In a real topography over large areas, there is always hilly areas or terrain variations. Therefore, applying such a window size will identify some hilly areas as objects incorrectly and flatten them, which will result in negative errors in the filtered DEM. Therefore, a smaller window size has to be chosen instead. This smaller window size will inevitably miss out some of the object with large sizes. Similarly, the choice of the slope threshold has to consider preserving the hilly areas (using large slope threshold) and removing the objects (using small slope threshold).

The surface plot of the RMSE and Mean error of the filtered ArcticDEMs (Figure 4) evidence that the combination of large window size and small slope threshold enforces the strictest rule of removing objects while the combination of large window size and large slope threshold enforces the loosest rule. Therefore, we are confident that the robustness and the pattern of the filtered DEM error and the parameter choice is transferable to other sites (although the parameter numbers might be different in other sites, and we will explain finding the optimum parameters in the response for comment L589).

L379: The error distribution of...


Please connect this sentence to the following paragraph. One sentence paragraph is not recommended.

Thanks for this comment. We changed this in the revision.

L382: Figure 5

The blue color overlaid on satellite map is very difficult to see. Please adjust colors.

Thanks for this comment. We have changed Figure 5 as below.



L405: Figure 6:

Can you add one more “cross symbol” which represent the result of the best optimum parameter combination (which are common in all land covers). Readers must be interested in how “best-corrected DEM performs” simultaneously for all skill scores for all land covers.

Thanks for this comment. We add the mark for the lowest RMSE as triangle now. We now also mark the location where the ArcticDEM-SMRF were filtered with the window size of 10 m, which corresponds to the comment to L450.




Figure 6. Surface plot of the CSI score, Hit Rate, FAR, the water depth RMSE and Mean error (ME) simulated using the ArcticDEM-SMRF realizations (ArcticDEM filtered using the 234 SMRF parameter combinations) at sample S3 plotted against the RMSE and the Mean error of each realization member. The location of the highest CSI and Hit Rate, the smallest FAR, RMSE and the smallest absolute value of mean water depth error are marked as red crosses, with the values displayed. The location of the lowest RMSE of the ArcticDEM-SMRF

are marked as triangle, with values displayed (values are not shown if both the location and value are the same as the best flood inundation metric value). In addition, the RMSE, Mean error of the original ArcticDEM are located and marked as blue crosses in each panel with the five metrics value of the original ArcticDEM simulation displayed. Locations of ArcticDEM-SMRF filtered with window size = 10 m are marked with cyan color.

L446: ArcticDEM-SMRF with larger error.

What do you mean by “error” is not clear here. Do you mean “larger elevation error”?

Thanks for this comment. The error here meant to say that the filtered ArcticDEM with greater error (RMSE) than the optimum ArcticDEM-SMRF. The optimum ArcticDEM-SMRF is defined as the ArcticDEM-SMRF with the smallest RMSE among the 234 ArcticDEM-SMRF realizations. We now make this clearer as *‘However, there are two other cases where equally good flooding performance can be simulated using ArcticDEM-SMRF with larger error than the optimum ArcticDEM-SMRF.’*

L450: shown at the spike areas in Fig6


I cannot find where is “the spike” in Figure 6. Please provide better explanation.

Thanks for this comment. We revise the Figure 6 by adding marks to the area (see the revised Figure 6 in the response to L405). This area means that under-filtered ArcticDEM with good scores of assessed metrics.

L458: Figure 7

Please check the color map of the bottom figure. It seems there are many “green” colors which is not in the color bar.

Thanks for this comment. The previous figure display was log normalized which was not correctly reflected in the colour bar. We now revise Figure 7 as below. It should be noted that this display change does not alter our analysis of water depth error in the manuscript.



L517: similarly good flood simulation

I agree that the flood extents are almost similar, but how about flood depth? Can we say “similar”?

This is a good point. The water depth errors of the over-filtered ArcticDEM-SMRF and the under-filtered ArcticDEM-SMRF also compare well with the simulations based on the ArcticDEM-SMRF with the lowest RMSE error as shown in the Figure 6 row 4 and row 5.

We further checked the error of the water surface elevation (WSE) of these simulations and found that the over-filtered ArcticDEM-SMRF WSE error remain as similar low as the simulation of the ArcticDEM-SMRF with the lowest RMSE error, but not the under-filtered ArcticDEM-SMRF. We now add this finding of the water surface elevation error in the discussion section 5.2.

L543: ICESAT2

It should be “ICESat-2”.

Thanks for this comment. The word will be changed to ICESat-2.

L589: which resulted in an optimal window size of 30 m and slope threshold of 0.07 in the city of Helsinki.

Please make some discussions on the possibility of transferring this parameter to other regions, or possibility of estimating best parameter for other regions (without Lidar DEM coverage). Readers must be interested in this. If the parameter has relationship to land object characteristic (such as typical building size), there might be a chance to find good parameters for other regions.

As we analyzed above (response to comment L361), the residual errors mainly depend on the ratio of areas with residual errors and error values of these areas. The areas of residual errors mostly are contributed by objects that the used parameter cannot remove and by hills that were flattened incorrectly with the used parameters. Thus, balanced window size and slope threshold between the minimum and maximum as the SMRF parameters are needed to achieve the bare-earth DEM with the lowest error.

In this paper, we found a range of 0.04-0.1 of the slope thresholds has overall good performance of filtering the ArcticDEM, with 0.07 (or 7%) generating the bare-earth ArcticDEM with the lowest error. The value 0.07 is close to the mean slope in our study site (0.077 or 7.7%). Note the slope is calculated as percentage.

The 30 m window size are gauged visually corresponding to the average size of the objects because of lacking building footprint data. We tried to compute the object sizes from the difference between the original ArcticDEM and the LIDAR DTM. But we found the footprint heavily depend on the elevation difference threshold and the smallest patch size threshold. This makes the size measurements derived from that being not very reliable. So, we did not include the size analysis from this approach in the manuscript.

Therefore, we suggest testing the mean value of the slope and average size of objects first and adjusting these values up and down will likely find the optimum parameter quickly. Discussion of the parameter choice is now extended in the revision of Section 5.2.

The theory of SMRF algorithm and the optimum window size between different land covers clearly show that there is a positive relationship between the optimum window size and the size of the objects. But because of lacking the footprint data of the objects we could not further quantify this relationship. The slope of study site will also play a role in this relationship. Thus, it might not be easy to define a universal relationship with this study site. We argue that further quantification might not be so critical. Because that both urban and forest sizes are not very difficult to gauge given general knowledge, and that the error is robust to a reasonable range of the parameters.