

# What drives landslide risk: Disaggregating risk analyses, an example from the Franz Josef and Fox Glacier Valleys, New Zealand

Saskia de Vilder<sup>1</sup>, Chris Massey<sup>1</sup>, Biljana Lukovic<sup>1</sup>, Tony Taig<sup>2</sup>, Regine Morgenstern<sup>1</sup>

<sup>1</sup>GNS Science, Lower Hutt, 6012, New Zealand

5 <sup>2</sup>TTAC Ltd, Cheshire, CW9 6EU, United Kingdom

*Correspondence to:* Saskia de Vilder (s.devilder@gns.cri.nz)

**Abstract.** We present a quantitative risk analysis (QRA) case-study from the Franz Josef and Fox Glacier Valleys, on the West Coast of the South Island, New Zealand. The Glacier Valleys are important tourist destinations that are subject to landslide hazards. Both valleys contain actively retreating glaciers, experience high rainfall, and are proximal to the Alpine Fault, which is a major source of seismic hazard on the West Coast. We considered the life safety risk from rockfalls, soil/rock avalanches and flows that are either seismically triggered or occur aseismically. To determine the range in risk values, and dominant contributing variables on the risk, we modelled nine different risk scenarios where we incrementally changed the variables used in the risk model to account for the underlying uncertainty. The scenarios represent our central estimate of the risk, e.g., neither optimistic nor conservative, through to our upper estimate of the risk. We include in these estimates the impact of time-variable factors, such as a recently reactivated landslide has had on locally increasing risk and the time-elapsd since the last major earthquake on the nearby Alpine Fault. We disaggregated our risk results to determine the dominant drivers in landslide risk, which highlighted importance of considering dynamic time variable risk scenarios and the changing contributions to risk from aseismic versus seismic landslides. A detailed understanding of the drivers of landslide risk in each valley is important to determine the most efficient and appropriate risk management decisions.

20

## 1 Introduction

High mountain areas are subject to a variety of natural hazards, including slope instability. Globally, these mountainous areas are currently experiencing declining low elevation snow cover, retreating glaciers and degrading permafrost as a result of climate change (cf. Hock et al., 2020). Such changes in environmental, meteorological and geomorphological conditions may influence the rate, size and characteristics of landslide hazards (Gariano and Guzzetti, 2016). Additionally, such high relief mountain areas are subject to seismic hazards, including seismically triggered landslides. Given that the exposure of people and infrastructure to landslide hazards is also increasing from population growth, tourism, and socio-economic development (Hock et al., 2020), the risk from landslides may change and increase with time.

Quantitative risk analysis (QRA) is an important tool for assessing, managing and communicating the risks from landslide hazards (Corominas et al., 2014; 2015), and there is an increasing need to undertake QRA from legislative authorities and from

30

within the engineering and engineering geological communities (Corominas et al., 2014; Van Westen and Soeters, 2006; Ho et al., 2000). QRA are undertaken for a land use planning (e.g., Bell and Glade, 2004; Vega and Hidalgo, 2016), infrastructure (e.g., Voumard et al., 2013; Macciotta et al., 2015a), and for visitor destinations (e.g., Corominas et al., 2019; Stock et al., 2014). However, the ability to estimate quantified levels of risk is often challenging as the input datasets used in risk analyses are inherently uncertain. Such uncertainty is mainly due to the lack of completeness, quality, or range within the input datasets required to undertake a QRA (Van Westen and Soeters, 2006). A landslide inventory, which details where landslides have occurred in the past, provides information critical to understand what triggers landslides, what makes a particular slope more susceptible to landsliding, and how frequently landslides are likely to occur (Guzzetti et al., 2012). Yet, for many landslide prone areas this spatial and temporal record of landsliding is limited or does not exist. This is particularly the case for certain trigger events, such as earthquakes, where the return period of the trigger event may be greater than the length of the historical record (van Westen et al., 2008). Consequently, assessments of landslide susceptibility and frequency rely heavily on practitioner experience and judgement (Lee, 2009), and may not always reveal the full levels of uncertainty attached to the risk estimates (Corominas et al., 2014; Macciotta et al., 2015b). Most approaches use past landslide behaviour to predict what may occur in the future based on the maxim “the past is key to the future” (Varnes, 1978). However, the present or future conditions that make a slope susceptible to, or trigger landsliding may be different to those of the past. Changes in the location and the frequency of landslide activity may substantially alter the estimated risk, adding to the uncertainty associated with the risk value.

Fell et al., (2005) suggest using sensitivity factor analysis as a tool to understand the influence of potential uncertainties on the estimated risk levels, and communicate the influence of this input variability to users of the risk analysis and assessment. A current limitation of risk analysis is the need to be able to ‘disaggregate’ the risk results in order to determine the importance of the different input factors included in the QRA, such as the annual frequency of a given landslide type and volume occurring under a given set of triggers, how far landslide debris travels down a slope, where people are present on the slope and their biophysical vulnerability if present and hit by landslide debris. Such limitation means that the contribution to the risk and sensitivity of the results relating to the input variables used are rarely quantified, thus making it difficult for risk managers to understand and implement targeted risk reduction measures and risk communication options. We address this here, by presenting the QRA results, and their uncertainties, from a local to regional scale (1: 10,000 – 1: 50,000) analyses of landslide hazards and the risk they pose to the lives of people visiting and working in the Franz Josef and Fox Glacier Valleys, located on the West Coast of New Zealand. In the Southern Alps of New Zealand, landslides are a common feature that play a significant role in driving erosion (e.g., Hovius et al., 1997; Korup et al., 2004) and present an increasing natural hazard and risk to people and property (Allen et al., 2011; Cox et al., 2015; McSaveney, 2002).

## 2 Study Site

The Glacier Valleys, which are important tourist destinations, are located on the West Coast of the South Island, New Zealand (Figure 1). Both valleys contain multiple trails (walking and/or cycling tracks), which take between 30 minutes and up to 8 hours to walk/cycle, that allow visitors to access and experience a glacial environment. The glaciers themselves can now only be accessed via helicopters, with visitors undertaking paid tours on the glacier. Given the commercial sensitivities the risk from landslide hazards to visitors on commercial tours on the glacier has not been quantified in our risk analysis. . Prior to the Covid 19 pandemic and associated closure of New Zealand's border to international tourists, c.700,000 people per year walked the tracks in the Franz Josef Glacier Valley and c.400,000 people per year walked the tracks in Fox Glacier Valley. A maximum number of 6,000 people per day and 3,500 people per day walked the tracks in Franz Josef and Fox Glacier Valley respectively. Within this environment, visitors are exposed to a variety of landslide hazards. Numerous near-misses have been documented, and two fatalities occurred in January 1980 when a debris avalanche occurred along a track in the Fox Glacier Valley. Currently, the northern road and access track within Fox Glacier Valley is closed due to repeated damage from debris flow events. Evidence of landsliding is present within each valley, with the types of landslide broadly classified into rock falls, slides and topples, debris and rock avalanches and debris flows (as classified by Hungr et al., 2014: see Figure 2). In addition to these broad landslide types, deep-seated gravitational slope deformations (DSGSD's) can be observed in both study areas. These large DSGSD's typically provide sources of material for smaller rockfall/debris avalanches or debris flows (Cody et al., 2020). Earthquakes are potential triggering mechanisms for landslides, as both study areas are located less than 10 km southeast of the Alpine Fault (Figure 1), which is a major source of earthquakes in New Zealand (Stirling et al., 2012). Additionally, both valleys experience high rainfall, with 5 m/year recorded in Franz Josef village increasing to >10 m/year towards the main divide of the Southern Alps (Langridge et al., 2016). The glaciers in each valley are currently retreating (Purdie et al., 2015,2021), exposing more disturbed and consequently weaker rock masses, which appear to be the source of many recently documented landslides. Many of these 'aseismic' landslides appear to be triggered by intense rainfall; however, several have no documented trigger. Therefore, the slopes in the study areas have and will continue to be subjected to transient changes in stress, typically caused by precipitation-induced variations in pore-water pressure, erosion, freeze-thaw cycles, and diurnal and seasonal temperature variations (Gunzburger et al., 2005; Viles, 2013; Eppes and Keanini, 2017). Transient stress changes within a slope can lead to deformation, fracturing, and joint dilation, thus reducing rock mass strength leading to failure (e.g., Eberhardt et al., 2004; Eppes and Keanini, 2017).

The study areas (shown in Figure 1) are dominated by ice-free slopes comprised of schist (Cox and Barrell, 2007). The structural geology of the bedrock schist is complex, given the proximity of both sites to the Alpine Fault (Figure 1). Large persistent faults cut through the area trending north-east to south-west and east to west. The quality of the rock mass is highly variable over the study areas and tends to change with proximity and location relative to these persistent faults. Moraine and colluvium deposits are present within the main and tributary valleys, with the valley floors formed of predominantly alluvium,

and re-worked moraine and colluvium. The glaciers have carved the valleys, resulting in steep bedrock valley sides truncated by deeply incised streams. Debris fans are present at the mouth of these incised streams, which feed into the Fox and Waiho (Franz Josef) rivers. Flow rates within these rivers are highly seasonal and their courses, within their respective wider valleys, change frequently.

100

In Fox Glacier Valley, there are more extensive and thicker debris deposits (both moraine and colluvium) and larger debris fan deposits (e.g., Yellow Creek Fan; Gomez and Purdie, 2018), indicating that debris flows and avalanches may be more prevalent. With glacier retreat, these debris deposits are free to begin creeping, and debris is available for remobilisation via debris flows (Cody et al., 2020). In contrast, Franz Josef contains less debris and is more dominated by bedrock slopes, which may have been the result of limited debris accumulation through time or the ability of erosional processes to keep pace and remove material from the valley.

105

### 3 Methodology

#### 3.1 Risk calculation route

110 To estimate the risk, we follow the quantified risk analyses method described in the Australian Geomechanics Society (2007), and the Joint Technical Committee on Natural Slopes and Landslides (JTC1, as outlined in Fell et al., 2008). We calculated the probability of death (life risk) of an individual,  $P_{(LOL)}$ , from:

$$P_{(LOL)} = P_{(L)} \times P_{(T:L)} \times P_{(S:T)} \times V_{(D:T)} \quad (1)$$

115 where:

- $P_{(L)}$  is the probability (annual frequency) of the landslide occurring
- $P_{(T:L)}$  is the probability of the landslide (e.g., the debris from a landslide of a given type) reaching the element at risk (e.g., visitor on a track)
- $P_{(S:T)}$  is the spatio-temporal probability of the person at risk being present and in the path of landslides (the proportion of a year that the person is exposed to landslides)
- $V_{(D:T)}$  is the vulnerability of the person if present and in the path of landslide debris (i.e. the probability that the person will be killed if impacted by the landslide). In our analyses, we include in the vulnerability estimates, the potential for a person to be aware of the hazard and take evasive action.

120

125 Within the Fox and Franz Josef Glacier Valleys, we sum risk from several landslide hazards where people are exposed to 1) Several types of landslides, 2) Landslides of the same type but different volume, 3) Landslides triggered by more than one phenomenon, and 4) Several slopes on which landslides can occur. To take such cases into account, we re-wrote Equation 1 as:

$$P_{(LOL)} = \sum_{i=1}^n (P_{i(L)} \times P_{i(T:L)} \times P_{i(S:T)} \times V_{i(D:T)}) \quad (2)$$

130 where  $n$  is the number of landslide hazards of a given type and volume. This assumes that the hazards are independent of each other. However, in the valleys, it is possible that one or more of the hazards may result from the same causative event, e.g., an earthquake. Therefore, we estimate the probabilities using the theory of uni-modal bounds where the upper bound conditional probability ( $P_{UB}$ ) is calculated from:

$$P_{UB} = 1 - (1 - P_1) \times (1 - P_2) \dots (1 - P_n) \quad (3)$$

135

where:  $P_1$  to  $P_n$  are the estimate of several individual hazard conditional probabilities. We then multiplied the  $P_{UB}$  by the annual probability of the common causative event, e.g., the given level of shaking representing a given earthquake. More detail on the equation route is provided in the Appendices.

### 3.2 Risk metrics

140 We estimated the risk to life, using four risk metrics. Firstly, we estimated the local personal risk (LPR), which represents the annual probability of death for a hypothetical person present at a particular location for 100% of the time (24-hours a day and 365 days of the year). LPR, a metric used in flooding and seismic hazard studies (Crowley, 2017; Jonkman et al., 2003, van Elk et al., 2017), can be used to visualise the spatial distribution of risk within the study areas in order to help plan/realign tracks and roads. Secondly, we estimated the individual risk per trip, which is expressed in terms of the fatality risk (probability of death) of an individual resulting from one return trip along one of the main access tracks or roads within the study areas. We use this to represent the risk to visitors. We then estimated the annual individual fatality risk (AIFR), which is expressed in terms of the fatality risk experienced by the most exposed individual over one full year of, e.g., working in the valleys and undertaking frequent track checks for two to three hours a day (cf. Massey et al., 2022a). We use AIFR to estimate the risk to the most exposed worker in each valley who is present every day for substantial periods of the year. We estimated societal risk by determining fN pairs, which represents the frequency ( $f$ ) of an accident killing ( $N$ ) or more people in a single event, plotted on a fN curve (Strouth and Mcdougall, 2021). In this paper, we focus on and report the results for LPR and individual risk per trip. AIFR and the fN curve results are reported in Massey et al. (2018c).

150

### 3.3 Methodology framework

Our risk analysis firstly considers the possible range of triggering events in terms of a set (bands) of earthquake triggers and aseismic triggers (e.g., rain, time). In our compilation of the landslide inventories for each valley, we were unable to determine a relationship between rainfall or snowmelt with landslide occurrence. The recorded near misses in Franz Josef Glacier Valley and two fatalities (January 1980) in Fox Glacier Valley from a debris avalanche occurred in the absence of any discernible trigger. Therefore, we subsume potential rainfall triggering, snowmelt triggering and climatic factors into an aseismic annualised rate of landsliding. However, due to the proximity of the Alpine Fault and the seismic history of the region, we explicitly considered the possibility of seismically triggered landslides.

For each representative earthquake event, we determined the annual frequency of the event and the number of landslides of a given volume class produced in that event. For aseismic landslides, we determined the annual frequency of landslides of a given volume occurring in each valley using historical data on aseismic landslides in the valleys and the wider Southern Alps (Massey et al., 2022a). For both seismic and aseismic landslides we considered the full range of volume classes that could occur in each valley, which are: 1)  $\leq 10 \text{ m}^3$ , 2)  $10 \text{ m}^3$  to  $100 \text{ m}^3$ , 3)  $100 \text{ m}^3$  to  $1,000 \text{ m}^3$ , 4)  $1,000 \text{ m}^3$  to  $10,000 \text{ m}^3$ , 5)  $10,000 \text{ m}^3$  to  $50,000 \text{ m}^3$ , 6)  $50,000 \text{ m}^3$  to  $100,000 \text{ m}^3$ , 7)  $100,000 \text{ m}^3$  to  $500,000 \text{ m}^3$ , 8)  $500,000 \text{ m}^3$  to  $1,000,000 \text{ m}^3$ , 9)  $1,000,000 \text{ m}^3$  to  $5,000,000 \text{ m}^3$ , and 10)  $>5,000,000 \text{ m}^3$ . We estimated the number of landslides that could occur for each volume class using the Moon et al. (2005) method, by calculating the area under the landslide volume frequency curve (see Figure 2) using log-log histogram bins.

Secondly, we considered the locations from which landslides are most likely to source in each glacier valley. We explicitly determined landslide source locations, in order to estimate how far the debris could travel downslope from a particular source. We used slope angles, volume to area scaling relationships and geomorphic mapping to delineate these source areas. We compiled information on pre-disposing factors of slope instability in each valley to understand spatial controls on landslide occurrence, with these datasets forming an important input into landslide susceptibility modelling for each valley (Reichenbach et al., 2018). We used logistic regression susceptibility models for both seismic (Massey et al., 2021) and aseismic landslides to weight which source areas may preferentially generate landslides.

We conducted 3D numerical runout simulations to determine  $P_{(T,L)}$ : the probability of the debris from a landslide reaching or passing a portion of slope as it travels downhill from the source area. We conducted these numerical simulations for rockfall, debris avalanches and debris flows from our explicitly determined source areas. We used RAMMS rockfall software (2015) for rockfall simulations, and RAMMS debris flow software (2011) for debris flow and debris avalanche simulations.

We compiled information on the length of time visitors and workers spend along the tracks in each valley to estimate the spatio-temporal probability of the person at risk being present at a location ( $P_{(T,S)}$ ) and consequently in the path of debris. We used empirical estimates of vulnerability ( $V$ ), which is the probability of a person being killed if present and in the path of one

or more boulders, considering both: a) the likelihood of being killed if struck; and b) the possibility of being able to take evasive action and avoid being struck.

190 For each of these steps and elements of the risk equation, we determined central estimates (which we define as neither optimistic nor conservative and is based on taking the mean estimate) and upper estimates (based on the 84<sup>th</sup> percentile) of the different variables used in the QRA. We used these different estimates in our sensitivity analysis, where we incrementally changed the variable estimates from central to upper, until all variables were upper estimates. This results in 9 different risk models, from which we can calculate the incremental change in risk based on varying the input assumptions and document the impact of aleatory uncertainty.

195

### **3.4 The probability(annual frequency) of the landslide occurring: $P(L)$**

#### **3.4.1 Seismic Landslides**

We determined the frequency and volume of landslides likely to be generated at different magnitudes of ground shaking intensity from the mapped landslide distributions of historical New Zealand and international earthquakes, as detailed in de Vilder et al. (2020). We used the landslides generated during the 2016  $M_w$  7.8 Kaikoura, 1968  $M_w$  7.1 Inangahua and 1929  $M_w$  7.8 Murchison earthquakes, as proxies (Massey et al., 2018b; Hancox et al., 2014, 2015). We selected these three landslide inventories as they represent the most complete New Zealand inventories for seismic landslides that occurred in fractured hard rock (such as greywacke) similar to that of schist and occurred in mountainous and hilly terrain.

205 We assessed the number of landslides that could be generated for four different representative earthquake events, as represented by peak ground acceleration (PGA) bands: Band 1 (0.2 – 0.35 g); Band 2 (0.35 – 0.65 g); Band 3 (0.65 – 1.2 g) and Band 4 ( $\geq$  1.2 g). It is unlikely that several landslides will be generated by ground shaking  $< 0.2$  g (Dowrick et al., 2008). We calculated the annual frequency of the representative PGA per band from the New Zealand National Seismic Hazard Model (NSHM) (Stirling et al., 2012), by subtracting the annual frequencies that represent the PGA boundaries (start and end) of each band.

210 The active fault component of the NSHM defines the Alpine Fault local to Franz Josef and Fox Glacier Valley as the AlpineF2K fault source. Within the NSHM the AlpineF2K source generates a  $M_w$   $8.1 \pm 0.2$  earthquake with a single-event (strike-slip + dip-slip) displacement of c. 9.2 m with a mean recurrence interval of 341 years (Stirling et al., 2012). This is time independent variable and does not consider time elapsed since the last earthquake on the Alpine fault in 1717 (Howarth et al., 2021). Landgride et al., (2016) disaggregated the NSHM to see what other fault sources may contribute to the shaking hazard at Franz Josef. For a probability of roughly 10% in 250 years (or 2,500 years) the disaggregation indicates that the main contributor of seismic hazard is the  $M_w$  8.1 AlpineF2K source (i.e., the Alpine Fault). Additionally, the second largest seismic hazard over 2,500 years comes from moderate magnitude ( $M_w$  5-6) earthquakes that can occur  $< 10$  km from the townships.

Although the Alpine Fault is the main seismic source in the area, the section of fault that could rupture might be located some distance away from the sites. For this reason, and to consider the contribution from the  $M_w$  5-6 earthquakes, we, therefore estimate the landslide severity for the four different bands of PGA as determined from the NSHM. Recent research (Howarth et al., 2021) shows that the probability of an earthquake occurring on the central section of the Alpine Fault is 75% per cent in the next 50 years, and that there is an 82% chance that the earthquake will be greater than  $M_8$ . To account for this, our upper estimate of the PGA annual frequencies, we increase the annual frequency of the most intense ground shaking (Band 4) to 0.015 to reflect time elapsed since the last Alpine Fault earthquake.

225

To assess the magnitude-frequency of seismic landslides in each band, as outlined in de Vilder et al. (2020), we firstly determined the appropriate landslide source volume to area scaling relationship (from Massey et al., 2020). Secondly, we estimated the landslide frequency (number) and source area scaling relationship. Thirdly, we investigated the relationship between landslide occurrence and PGA, slope angle and material type using the Kaikoura, Inangahua and Murchison landslide inventories. Finally, we combined estimates of the annual frequency of the representative event PGA for each earthquake band in the NSHM. Using this relationship, we estimated the probability of a landslide of a given volume class occurring within each study area for each PGA band considered, along with the annual frequency of the representative PGA in the band occurring (see Figure 3 a). We fitted power laws to the data, with these representing our central estimate of the number of landslides of given volume class occurring for each PGA band considered. To derive an upper estimate, we added the standard error of the gradient of our best-fit power-law to the power-law relationship to calculate the number of landslides that could be generated.

230  
235

### 3.4.2 Aseismic Landslides

We collated information on the occurrence of aseismic landslides from various data sources, which we used to assess the historical type, mechanisms, and rates of aseismic landslides for both valleys. These data sources include 1) a rockfall register compiled from observations made by staff of the Department of Conservation (DOC), Franz Josef Glacier Guides Ltd, and Fox Glacier Guides Ltd, 2) a landslide inventory derived from historical aerial imagery analysis of both valleys, and 3) a large landslide inventory of historical landslides observed in the wider Southern Alps (see the appendices for more information on the compilation of the landslide inventories).

240

We determined valley-specific magnitude-frequency relationships of landslides, given the amount of catchment-specific information about landslides. We fitted power law trends to the data to generate a central estimate and an upper estimate (using the standard error of the power law) of the number of landslides that could occur in each valley per  $\text{km}^2$  and their annual frequency (see Figure 3 b). These landslide rates were then scaled to each valley by multiplying them with the total area of the slopes greater than  $30^\circ$  within each valley. We used a slope angle of  $30^\circ$  as a cut-off as within our landslide inventory no landslides occurred on slopes with angles  $<30^\circ$ .

245  
250



### 3.5 The probability of the landslide reaching the track or road

#### 3.5.1 Landslide Susceptibility

In the absence of historical information on landslides triggered by an Alpine Fault earthquake, we used the 2016 Mw 7.8 Kaikoura Earthquake-induced landslide inventory to understand the spatial controls on susceptibility to failure. From this dataset, Massey et al. (2018a, 2021) used a logistic regression model to correlate the three aforementioned mapped earthquake induced landslide inventories with various topographic, geological and seismological parameters to understand which parameters best explained the occurrence of coseismic landslides. We applied the Massey et al. (2018a) logistic regression model to both valleys, using PGA input from the NSHM. The PGA input varied from 0.8 g to 1.1 g across both valleys, which along with the other components of Massey 2018a logistic regression model such as distance to fault, slope angle, geology, and local slope relief, was used to determine the probability of a landslide occurring from a particular source location.

We developed valley-specific logistic regression models to determine aseismic landslide susceptibility, given the amount of landslide-specific information and slight differences in the landslide hazards within each valley (see Figure 4 for an example from Fox Glacier Valley). These models are based on the correlation of mapped landslides, and various topographic, geological and land use characteristics (cf Massey et al., 2018a and the appendices). Rockfalls recorded in the rockfall register were not included within the analysis as the data do not have accurate geographic locations. More information on the aseismic susceptibility models is provided in the appendices.

#### 3.5.2 Landslide Runout

Landslide sources  $\leq 1,000 \text{ m}^3$  were assumed to be rockfalls rather than debris flows and debris avalanches. Potential rockfall source areas were defined using all slopes  $\geq 45^\circ$ , assuming any slope  $\geq 45^\circ$  can potentially generate rockfalls (Figure 5) (Budetta, 2010; Massey et al., 2014a). For landslide volumes  $\leq 100,000 \text{ m}^3$  the landslide sources were assumed to be pixels of a given area based on the area to volume scaling exponents (Figure 5). For landslide volumes  $> 100,000 \text{ m}^3$ , the shapes of the sources were defined using the geomorphic features (Figure 45).

For the rockfall simulations, we used RAMMS rockfall software (2015), which simulates the rigid body motion of falling rocks and predicts rock trajectories in general three-dimensional terrain (see the appendices for more information). For the debris avalanches and debris flow simulations, we used RAMMS debris flow software (2011), changing the Voellmy friction parameters (see the appendices for more information) to determine if a particular source area failed as a debris avalanche or debris flow. From these simulations, we derived the runout extent and maximum debris height. The simulated maximum height of debris passing through a given grid cell is converted into the number of boulders (our central estimate), with our field measurements indicating that the median boulder size is  $1 \text{ m}^3$  (Figure 6). For example, if the maximum debris height passing through a 3 m by 3 m grid cell is 1 m, then the total volume of debris passing through that grid cell is  $9 \text{ m}^3$ , which when

converted into N boulders, would be on average 9 boulders. Based on sensitivity analysis of the Voellmy friction parameters (see the appendices for more information), we calculated a standard deviation-based factor of difference in debris height. We applied this factor of difference to the simulation results to increase debris height, providing an upper estimate.

We calculated the probability of one boulder in the debris hitting an object when passing through a particular portion of the slope, perpendicular to the debris path, using the equation:

$$P_{1(T:L)} = \frac{D+d}{L} \quad (4)$$

where  $D$  is the diameter of the boulder,  $d$  is the diameter of a person (our central estimate assumes a person is a “cylinder” with a 1 m diameter, while our upper assumes an estimate of 2 m diameter), and  $L$  is the unit length of slope perpendicular to the runout path, which for this study is 3 m grid cell. Our equation includes a “buffer-zone” around the person ( $D + d$ ) within which the boulder travels along a path either side of  $d$  and cannot miss.

### 3.6 Exposure

We calculated the probability that a person will be occupying a given grid cell along one of the tracks/roads ( $P_{(S:T)}$ ) if they spend a number of hours ( $N_{HRS}$ ) per trip per year walking/driving that route using the equation:

$$P_{(T:S)} = \frac{(N_{HRS})}{(N_C)} \quad (5)$$

Where  $N_C$  is the number of cells visited along the route. We compiled information provided by DOC on the estimated time taken to travel by vehicle along given roads to/from the car parks, and the time taken for walking a round trip from the car park to the glacier viewing points to determine the time exposed for an average walker (central estimate) or a slow walker (upper estimate). In Fox Glacier Valley, our average walker spent 1.5 hours walking to and from the glacier viewpoint and 0.2 hours driving to and from the car park (see Figure 1 c), while the slower walker spent 2 hours walking to and from the glacier viewpoint and 0.3 hours driving to and from the car park. In Franz Josef Glacier Valley, our average walker spent 2-hour walking to and from the glacier viewpoint, and 0.3 hours driving to and from the car park (see Figure 1 d) while the slower walker spent 2.5 hours walking to and from the glacier viewpoint and 0.4 hours driving to and from the car park. Therefore, we assumed that the time spent on each one metre section of track was equal to the duration (time) of travel divided by the total length of the track. However, exposure can be adjusted to account for longer time spent by a visitor at a viewing area, picnic spots etc. For the calculation of LPR, we assumed  $P_{(T:S)}$  of 1, where a person is present 100% of the time.

### 3.7 Vulnerability

Physical vulnerability ( $V$ ) depends on the landslide intensity, the characteristics of the elements at risk, and the impact of the landslide (Du et al., 2013). To derive our central estimate of vulnerability, we link vulnerability values to representative  
315 landslide volumes, which act as a proxy for landslide intensity (see the appendices for more information). Anecdotal evidence from the glacier valleys suggests that evasive action reduces vulnerability. This was the case on 13 October 2011 and 16 June 2014, when boulders and fly rock from debris avalanches passed over several people on the ice. During these near misses, the guides heard the debris moving down the slope and had time to instruct their clients to take evasive action. In Table 1 our vulnerability values scale with landslide volume, were for landslide volumes  $\leq 100,000 \text{ m}^3$  an individual may be able to take  
320 evasive action. However, the ability to take evasive action decreases with landslide volume. For landslide volumes  $> 100,000 \text{ m}^3$  an individual is likely to be buried by debris and killed. To derive an upper estimate of vulnerability, we assume a vulnerability of 1 for all rockfall and landslide volumes.

### 3.8 Risk scenarios modelled

325 For each valley, we estimated the individual risk per trip for a visitor using nine different risk model scenarios (Table 2) which ranged from our central estimate of the risk to our upper estimate of the risk. Our central estimate (Scenario 1: Table 2) risk model uses the central estimate input variables and a time independent ground shaking annual frequency. For each risk model scenario we incrementally change the variable from central to upper estimates, starting with the number of landslides that could occur in an earthquake event (Scenario 2), then the number of aseismic landslides that occur annually (Scenario 3),  
330 before increasing our estimate of debris height (Scenario 4), the diameter of a person (Scenario 5), our vulnerability estimate (Scenario 6), the time elapsed since the last Alpine Fault earthquake (Scenario 7), and lastly increase the length of time a visitor is exposed to the risk (Scenario 8). We also included a risk model scenario (Scenario 9: Table 2), where we used central estimate input variables but account for the increased probability of Alpine Fault earthquake occurring, to understand the impact of these assumptions on the risk results.

335

## 4 Results

### 4.1 Individual risk per trip

The individual risk per trip in Franz Josef Glacier Valley ranged from  $7.8 \times 10^{-7}$  (central estimate: Scenario 1) to  $8.3 \times 10^{-6}$  (upper estimate: Scenario 8). The risk along the road in Franz Josef ranges from  $7.88 \times 10^{-9}$  to  $1.03 \times 10^{-7}$ , while the risk along  
340 the track in Franz Josef ranges from  $7.72 \times 10^{-7}$  to  $1.08 \times 10^{-5}$ . For Scenario 9 (central estimate with higher earthquake annual frequency), the risk along the road in Franz Josef was  $6.84 \times 10^{-8}$  and the risk along the track was  $2.73 \times 10^{-6}$ , with a total risk

per trip of  $2.8 \times 10^{-6}$ . The individual risk per trip in Fox Glacier Valley ranged from  $4.9 \times 10^{-6}$  (central estimate: Scenario 1) to  $1.7 \times 10^{-5}$  (upper estimate: Scenario 8). The risk along the road in Fox ranges from  $2.57 \times 10^{-7}$  to  $6.34 \times 10^{-7}$ , while the risk along the track in Fox ranges from  $4.63 \times 10^{-6}$  to  $1.62 \times 10^{-5}$ . For Scenario 9 (central estimate with higher earthquake annual frequency), the risk along the road in Fox was  $4.22 \times 10^{-7}$  and the risk along the track was  $7.16 \times 10^{-6}$ , with a total risk per trip of  $7.59 \times 10^{-6}$ . The risk along roads is less than that along tracks; this is a function of both overall lower LPR risk, and less time spent on the roads. It is important to note that the risk numbers reported here do not consider any risk management and mitigation so should not be treated as indicative of current residual risk levels following actions taken in light of this analysis.

## 350 4.2 Risk disaggregation

Using Scenario 1, we disaggregate our risk results to understand the contributions to risk from the different risk model components. Figure 7 and Figure 8 display an LPR map of Franz Josef and Fox respectively, illustrating the spatial variation in risk within the valley and along the access tracks to the viewpoint of the glaciers. Aseismic landslides account for 66% and 83% of total LPR along the access tracks in Franz Josef and Fox, respectively, in contrast to 34% and 17% for seismic landslides (Figure 7 b & 8 b). In Fox, increases in aseismic landslide risk are observed when the track is close to the base of larger, steeper slopes or crosses a large debris fan (Figure 8 a). Although the risk to an individual is higher for aseismic landslides, the risk of a large landslide causing multiple fatalities or multiple landslides occurring at the same time leading to multiple fatalities, is dominated by earthquake events with  $PGA's > 0.6 \text{ g}$  (Band 3 & Band 4) (cf. Massey et al., 2022a). For aseismic landslides, we disaggregated the risk further to determine which landslide volume classes contributed most to the risk. In Franz Josef, moderate sized landslide volume classes of  $10,000 \text{ m}^3$ ,  $50,000 \text{ m}^3$ , and  $100,000 \text{ m}^3$  account for 31%, 30%, and 14% of the aseismic landslide risk along the track, while landslide volume classes of  $500,000 \text{ m}^3$  and  $1 \text{ M m}^3$  account for a further 7%, and 11% of LPR, respectively (Figure 7 c). Landslide volume classes of  $5 \text{ M m}^3$  or greater account for less than 3% of LPR. The risk from rockfalls (4% of LPR along track), increases when the track is closer to the base of the steep valley sides as displayed in the spikes in risk associated with volume classes of  $10 \text{ m}^3$  (Figure 7 c). Increases in the risk associated with  $10,000 \text{ m}^3$  landslide volume is associated with increases in both aseismic and seismic risk along the track (Figure 7). In Fox Glacier Valley, landslide volume classes of  $10,000 \text{ m}^3$ ,  $50,000 \text{ m}^3$ , and  $100,000 \text{ m}^3$  account for 24%, 21%, and 12% of LPR, respectively (Figure 8 c). Larger volume classes of  $500,000 \text{ m}^3$ ,  $1 \text{ M m}^3$ ,  $5 \text{ M m}^3$  and  $> 5 \text{ M m}^3$  contribute 12%, 15%, 10% and 6% to LPR, respectively. For seismic landslides in Franz Josef, Band 2 contributes the most to the risk, accounting for 43% of LPR, while Band 1 accounts for 21%, Band 3 for 32% and Band 4 for 4% of LPR (Figure 7 d). A similar pattern exists for seismic landslides in Fox, where Band 2 contributes the most risk, accounting for 48% of LPR, while Band 1 accounts for 29%, Band 3 accounts for 21% and Band 4 accounts for 2% of LPR (Figure 8 d).

However, in Scenario 9 (Table 2), we modelled the increased annual frequency of a large Alpine Fault event that was assumed to result in the greatest ground shaking (Band 4), while using central estimate for all other input variables to the risk model. In

375 this scenario, the seismic landslide risk in Franz Josef (Figure 9 a) is higher, accounting for 81% of LPR along the track, than  
that of aseismic landslide risk in contrast to the patterns in Scenario 1 (Figure 7 b). In Fox, the contribution of seismic landslide  
risk is higher in Scenario 9, accounting for 46% of LPR along the track (Figure 9 b), than in Scenario 1 (Figure 8 b), and in  
locations along the track, surpasses that of aseismic landslides. However, aseismic landslides contribute more to the overall  
LPR (54%), particularly in locations where the track crosses debris fans (Figure 9 b).

380

For the eight different risk scenarios (Table 3), we calculate the overall cumulative increase in risk as a percentage, along with  
the amount of cumulative increase in risk between each scenario. We also calculate the increase in risk between each scenario  
as a percentage, to understand the contribution of each variable to overall risk in order to negate the effect of the order in which  
each variable is altered in the risk models and the compounding effect of changes to variables on the cumulative risk results.

385 Our sensitivity analysis of the risk model inputs for Franz Josef (Table 3) shows that, within the ranges of inputs considered,  
the largest increase in the risk is associated with increasing the number of aseismic landslides that occur annually with a  
cumulative increase in risk of 365%. Second to this, is the increased earthquake annual frequency, with a cumulative increase  
in risk of 330%. Thirdly, increased exposure time results in a cumulative risk increase of 328% while a constant vulnerability  
of 1 result in a cumulative increase in risk of 219%. Changes in input variables (debris height and diameter of a person) that  
390 affect the  $P_{(T,L)}$  term resulted in negligible changes to risk, with  $< 10\%$  change in cumulative risk. Overall, changes in the input  
variables from central estimate to upper estimate resulted in a 1298% cumulative increase (just over an order of magnitude) in  
the risk results. For Fox, increases in exposure time and vulnerability resulted in the largest increase in risk ( increase in  
cumulative risk of 80% and 60%, respectively: Table 3), while changes in the annual frequency of earthquake events as well  
as the number of aseismic landslides resulted in cumulative increases of risk of 56% and 30%, respectively (Table 3). Changes  
395 in the number of seismic landslides resulted in a cumulative increase in risk of 10%. Similarly, to Franz Josef, changes in  
debris height and the diameter of a person had negligible impact (Table 3). The range in risk values for Fox from central  
estimate to upper estimate was smaller than for Franz Josef, with a cumulative percentage of increase of 244%.

### 4.3 Changing risk through time

400 Recently within the Fox Glacier Valley, there has been increased debris flow events from the Mill's Creek catchment. The  
debris flows are sourced from the toe of the Alpine Gardens landslide, which is an approximately  $\sim 50$  million  $m^3$  actively  
moving landslide complex in the Fox Glacier Valley (Figure 10). These debris flows travel down Mill's Creek and deposit on  
the debris fan at its confluence with the Fox River. The debris flow activity has resulted in the expansion of the Mill's Creek  
debris fan, which in turn, has forced the migration of the Fox river to the true-right side of the valley.

405

This is changing the rate of debris flow activity, and concentration in a specific area influences landslides susceptibility and  
magnitude-frequency. The change to the landslide hazard has an impact on the estimated risk levels. The increase in activity

from a particular area is a common phenomenon, based on the long-term observations of national park staff and glacier guides (Marius Bron- personal communication), with this type of behaviour described colloquially as “switching on – and off”, whereby a particular gully or slope will display enhanced rates of landslide activity for a period of time (sometimes in the order of years) before the levels of activity reduce. We incorporated the elevated debris flow activity into the risk analysis, by deriving a specific magnitude-frequency relationship for debris flows from the Alpine Gardens and Mill’s Creek catchment and applying this revised magnitude-frequency relationship to source areas within this catchment (see the appendices for information).

415

The increased landsliding from the Alpine Gardens area was propagated through the risk equation. Figure 11 displays the LPR map that includes the current elevated rates of debris flow activity in the Fox Glacier Valley. In the Alpine Gardens – Mill’s Creek catchment, the increase in LPR ranges from 5% to 1442%, with a mean increase in LPR of  $285.5\% \pm 245\%$ .

## 420 **5 Discussion**

### **5.1 Drivers of risk**

We disaggregate our QRA to determine the dominant contributors to risk in each Glacier Valley. For both valleys, in our central estimate scenario, aseismic landslides dominate the risk profile. Of these aseismic landslides, the major contributors to the risk are the moderate sized landslides ( $10,000 \text{ m}^3$  to  $100,000 \text{ m}^3$ ), which happen more frequently than the large or very large landslides ( $> 100,000 \text{ m}^3$ ) but travel further and impact a larger area than the more frequently occurring small landslides ( $<10,000 \text{ m}^3$ ). Only when the tracks veer closer to the base of the slope does the risk from small landslides and rockfalls increase. We suggest that a similar pattern would be observed for seismic landslide volumes, given that the same volumes will impact the same area and that increases in the risk associated with  $10,000 \text{ m}^3$  landslide volume class in Franz Josef is associated with increases in both seismic and aseismic LPR.

430

Even when the annual frequency of a large ground shaking event is increased to account for the probability of  $> \text{Mw } 8$  Alpine Fault event occurring in the next 50 years (Howarth et al., 2021), aseismic landslides account for more than half of the risk in Fox Glacier Valley. In Franz Josef Glacier Valley, increases in the number of aseismic landslides result in a large increase in risk of 365%, suggesting that within the aleatory uncertainty (e.g., within the standard deviation) of the landslide magnitude-frequency relationships, aseismic landslides are a dominant contributor to the risk. Similar conclusions were reached by Robinson et al. (2016) in their analysis of co-seismic landsliding from an Alpine Fault event, which suggests that for the central section of the Southern Alps aseismic erosional processes are more important than seismically driven landslide erosion on annual time-scales.

440 However, accounting for the increased probability of an Alpine Fault earthquake occurring in the next 50 years and increasing  
the number of landslides that could occur during an earthquake event each lead to increases in our risk estimates, both the  
individual risk per trip, discussed in detail here, and societal risk, as determined by  $fN$  pairs, which represents the frequency  
( $f$ ) of an accident killing ( $N$ ) or more people in a single event. In Franz Josef, increasing earthquake annual frequency and the  
445 frequency results in a larger cumulative increase in risk of 330% compared to 46% for the increased number of seismic  
landslides – the difference may be the result of the order of the scenarios and compounding effect of variables. For example,  
the cumulative increase in risk associate with including a time dependent earthquake scenario in Scenario 7 is 330 % and 56  
% for Franz Josef and Fox respectively, while for Scenario 9 (time dependent only scenario) it is 260% and 54%. We suggest  
that the differences between the example scenarios are due to changes in the number of seismic landslides generated, spatial  
450 probability of impact and vulnerability. However, the relative differences between the scenarios do not change. In Fox,  
increasing the annual frequency of earthquakes and the increasing number of aseismic landslides both result in risk increases  
of 56% and 30%, respectively. Increasing the number of seismic landslides results in risk increases of 10%, lower risk increases  
than that observed in Franz Josef. In Fox Glacier Valley, the presence of large debris fans indicates debris flow activity (Gomez  
and Purdie, 2018; e.g. Cody et al., 2020), however, debris flow records in both valleys are limited and therefore the aseismic  
455 debris flow risk may be underestimated. Our example from Mill’s Creek debris fan highlights that local increases in debris  
flow activity can significantly affect the risk, with local increases in risk of up to 1442%. For both seismic and aseismic  
landslides, the impact of the number of landslides generated, which is the  $P_{(L)}$  term in the risk equation, emphasises the  
importance of the landslide inventory as an input into the risk calculation process. Therefore, more time and resources  
dedicated to the creation of a landslide inventory may reduce the uncertainty associated with the risk values (van Westen et  
460 al., 2008).

For seismic landslides, the landslide inventories of the 2016  $M_w$  7.8 Kaikoura, 1968  $M_w$  7.1 Inangahua and 1929  $M_w$  7.8  
Murchison earthquakes (Massey et al., 2018b; Hancox et al., 2014, 2015), were used as proxies for Franz Josef and Fox Glacier  
Valleys given the lack of seismic landslide inventories for the West Coast. All three inventories were dominated by shallow  
debris avalanches, with such failure types potentially being the dominant type of seismic landslide type (Keefer, 2002). The  
465 schist rock mass of both glacier valleys is fractured with persistent faulting (Cox and Barrell, 2007) and therefore we assume  
that shallow debris avalanches are the dominant failure type. While all three inventories occurring in similar mountainous  
terrain to Franz Josef and Fox Glacier Valleys, climatic differences exist, with the impact of these climatic differences on the  
number and size of seismic landslides triggered unknown.

470 The biggest increase in risk values in Fox is associated with increases in the vulnerability and spatio-temporal probability of a  
visitor being in the path of a landslide (66% and 80% increases in risk respectively), with these factors resulting in increases  
in risk in Franz Josef (219% and 328%, respectively). This emphasises the importance of risk management decisions to reduce

475 exposure and lower vulnerability. Changes to the diameter of a person and debris height had a very limited impact on the  
estimated risk values, which affect the  $P_{(T,L)}$  term in the risk equation. Changes in the spatial extent of debris from the numerical  
simulations were not included within the sensitivity analysis, but could be included using empirical or other probability based  
(e.g. Flow-R: Horton et al., 2013) runout analysis and calculations of runout probability of exceedance (McDougall, 2017; e.g.  
Brideau et al., 2020). In this case-study, we assume such variations are not particularly meaningful given the number of source  
480 areas the rockfall and landslide runouts were simulated from (Figure 2), the confined nature of the valleys, and the proximity  
of the access tracks and road to the base of the steep slopes from which the debris is sourced.

## 5.2 Time variable risk

Our sensitivity analysis highlights the importance of accounting for time-variable risk with the inclusion of the increased  
frequency of an Alpine Fault earthquake resulting in cumulative increases in risk of 330% and 56% for Franz Josef and Fox  
Glacier Valleys, respectively. Alongside this, increases in aseismic landsliding results in cumulative increases of risk of 365%  
485 and 30% for Franz Josef and Fox Glacier Valley, respectively. Use of the upper estimate of the number of aseismic landslides  
that could occur may represent a future climate change scenario, reflecting the increased rates of landsliding (Gariano and  
Guzzetti, 2016) as glaciers retreat, slopes debuttreass and the environmental condition changes. Our sensitivity analysis suggests  
that climatically driven increases in landsliding will have a larger impact on landslide risk in Franz Josef than in Fox Glacier  
Valley. We hypothesise that the differences in sensitivity analysis between the valleys may reflect the geomorphology of each  
490 valley. In Franz Josef, increases in the number of larger landslides may significantly increase the probability of such landslides  
reaching the element at risk.

However, the size and frequency of landslides may change in response to climate change (Huggel et al., 2012; Korup et al.,  
2012), with Liu et al. (2021) observing a shift in the frequency-area distribution with larger landslides occurring in their dataset  
495 of landslides in the high mountains of Asia. In our sensitivity analysis we do not test changes in gradient of the -magnitude –  
frequency distributions to reflect increases in the frequency of larger landslides occurring relative to the frequency of smaller  
landslides. Such shifts in the magnitude – frequency distribution will impact the risk results and associated uncertainty. The  
larger debris and alluvial fans in Fox may indicate higher rates of aseismic landsliding than those observed in Franz Josef, and  
consequently may also explain that due to the already high rates of landsliding, increases in landslide rates (both seismic and  
500 aseismic) may have limited impact on risk, while the changes in vulnerability and exposure have a relatively bigger impact on  
the overall risk value.

Changes in landslide susceptibility should also be accounted for, as highlighted by Reichenbach et al. (2018), where the spatial  
pre-disposition to landsliding may change in response to environmental changes though the exact changes to landslide  
505 susceptibility are unknown. Given that landslide susceptibility is usually the starting point for risk analyses, time-variable  
landslide and therefore susceptibility means that the risk to people and infrastructure from landslides is also time-variable,



especially after a major earthquake (e.g. Massey et al., 2014b; Lin et al., 2006; Marc et al., 2015). Following the Canterbury earthquake sequence in New Zealand, a time-varying seismic hazard model was used as input to quantify the risk to life from rockfall in the Port Hills of Christchurch (cf. Massey et al., 2014b). Consequently, the rockfall risk was shown to be time-  
510 variable with a rapid 50% decrease in seismic rockfall risk in the 5 years post earthquake event and a 14% decrease in risk 5 to 10 years post event. Massey et al. (2022b) shows that aseismic rockfall risk is also elevated post-earthquake event with a similar 50% decrease in rockfall rates 1 to 5 years post earthquake event. Our example of increased debris flow activity on the Mill's Creek debris fan allows for spatial changes in landslide susceptibility frequency and magnitude to be easily incorporated into the risk model. Our analysis shows that the impact on LPR on the Mill's creek debris fan is significant. The ability to  
515 dynamically update the risk model to account for increased landslide activity in a specific area or catchment, allows changes in environmental conditions and progressive failure, for example, increased number and size of landslides (Purdie et al., 2015; Fischer et al., 2012; Liu et al., 2021; e.g. Allen and Huggel, 2013) in a recently deglaciated area, to be assessed. The only required input is an estimate of approximate landslide size and frequency for a particular spatial area. Sensitivity analysis could be undertaken to understand if variations in the magnitude-frequency relationship had a significant impact on the resulting risk  
520 estimates. It is also important to note that our risk analysis does not include cascading hazards, such as landslide dam formation and associated dam break floods as well as catastrophic glacier multi-phase mass movements, which may be important in an Alpine Fault earthquake scenario (Robinson and Davies, 2013). Such cascading hazards could be incorporated into future risk analysis potentially using an event tree approach (e.g. Macciotta et al., 2016). Alongside changes in hazard behaviour, risk analysis should also account for dynamic changes in exposure and vulnerability. Voumard et al.,(2013) developed a dynamic  
525 traffic simulator to simulate changing traffic speeds, with their results showcasing increased risk due to slow -moving traffic and traffic light placement compared with static speed, and therefore exposure. Stock et al., (2014) quantitative rockfall risk analysis of people within in Yosemite Valley highlights that closure of buildings within their rockfall hazard line and reduced exposure resulted in decreased cumulative risk in the valley. Since 2019 and 2020 the main visitor tracks in the Fox and Franz Josef Glacier valleys respectively have been closed or partially closed due to geomorphic processes. Until access is restored  
530 in both valleys, the exact location of the tracks in each valley and the number of people walking the tracks is unknown. In Fox Glacier Valley, the expansion of the Mill's Creek fan from debris flow activity has damaged access on the true -right side of the valley, while in Franz Josef Glacier Valley, the course of the Waiho River has restricted access on the true-left side of the valley. As such visitor exposure and therefore risk to landslide hazard is reduced. Alongside this, the Covid-19 pandemic and associated closure of New Zealand's border to international tourists has resulted in a reduction in visitor numbers to both  
535 glacier valleys. This reduction in visitor numbers will impact our societal risk metric, by reducing exposure of 1 or more people to an event that might result in fatalities.

### **5.3 Risk communication and management**

Our analysis quantitatively estimates the risk to life to visitors from landslides, with this information used by risk managers and decision makers to evaluate risk tolerability, determine appropriate risk mitigation measures and communicate the risk to

540 visitors and workers in each valley. Due to the uncertainty associated with risk analysis (Lee and Jones, 2014), we report our risk estimates as bands and not as single points (see Figure 12). The risk bands represent our central estimate through to upper estimate of the risk; we do not present a lower estimate of the risk as lower estimates are not currently used in decision-making regarding risk acceptability, in order to ensure that the highly uncertain risk levels are not underestimated. However, we note and agree with Strouth and McDougall (2021) that risk assessment conservatism should be avoided, with central estimates  
545 used for risk evaluation and uncertainties in the risk analysis presented transparently. The risk bands can be presented against risk comparator data to inform risk evaluation and risk tolerability processes in conjunction with an evaluation of how visitors and decision makers perceive risk (cf. Taig et al., 2012; Taig, 2022b, a). In Figure 10, the individual risk per trip for visitors to both Franz Josef and Fox Glacier Valleys (though it is important to note that the risk numbers do not include any mitigation measures and are therefore not residual risk), are plotted against other activities that a visitor may undertake. These activities  
550 include popular tourist activities in New Zealand, modes of transport to and from the Glacier Valleys, and risk per trip in other national park settings globally. More information on these datasets can be found in Taig (2022 a, b). Not only can this be used to inform the risk evaluation process but can also help with risk communication to visitors. The range in risk values can be presented as a graphic to illustrate the risk, and to avoid confusion with small numbers or scientific notation along with helping visitors, whose main language may not be English, understand the uncertainty in risk results (Taig, 2022).

555

The disaggregation of the QRA allows a greater understanding of both the contributors to landslide risk, and their associated uncertainty. Such an approach presents a useful tool to inform and communicate to risk managers where appropriate management and mitigation strategies may be most effective. Reductions in vulnerability and exposure can be important risk mitigation measures (e.g., Schneiderbauer et al., 2017), as highlighted by our risk sensitivity scenario analysis. The LPR maps  
560 can be used to inform track placement and re-alignment, reducing the time spent and exposure of an individual in high hazard zones beneath steep slopes. The LPR maps may also be used for informing and identifying suitable, “less risky” stopping points in the valley, when tracks are partially closed due to rainfall, high stream flows or other events. Where it is not possible to relocate the tracks, other mitigation measures such as track closures during heavy rainfall may reduce the risk from rainfall-induced landslides within the aseismic landslides class. As aseismic landslides dominate the risk profiles, reduction in exposure  
565 to rainfall-induced landslides may result in a significant reduction in visitor risk per trip. In Figure 12, we include a theoretical reduction in aseismic landslide risk of 75%, assuming that 75% of aseismic landslides are triggered under heavy rainfall conditions. In this example, if the track is closed under heavy rainfall conditions substantial reductions in the visitor risk per trip occurs (cf. Massey et al., 2022a). However, due to the limitations of our landslide inventory, we are unable to link landslide occurrence to rainfall events in each valley, and therefore cannot provide a quantitative basis for the risk reduction associated  
570 with track closures. To provide a robust basis for using track closures as a risk reduction method, rockfall and landslide events should be documented and recorded within each valley, along with meteorological observations. This should also include any information of the occurrence of debris flows, particularly within Fox, as this landslide type is difficult to determine within our landslide inventory analysis and are therefore underrepresented in our magnitude-frequency analysis even though debris

575 fans are higher risk environments (see Figure 6). Such information could be crowd-sourced, with visitors in Yosemite Valley  
able to report rockfall occurrences to Park Staff (<https://www.nps.gov/yose/learn/nature/rockfall.htm>). For both valleys, the  
glacier guides continue to record rockfall and landslide activity. A rockfall/landslide register can also be used to inform  
dynamic risk analysis, by recording areas of locally high activity. Our methodology presents a base risk model that can be  
easily updated and amended to incorporate future information such as revised track locations, visitor numbers and changes in  
landslide activity.

580

## 6 Conclusion

We have presented a quantitative risk analysis (QRA) case study from the Franz Josef and Fox Glacier Valleys, on the West  
Coast of the South Island, New Zealand. We deconstructed the QRA to reveal the relative contributions of aseismic versus  
seismic landsliding, and landslide volume classes to risk. Our results reveal that for both valleys in our central estimate scenario  
585 aseismic landslides contribute more to the overall risk than that of seismic landslides. However, our sensitivity analysis of nine  
risk scenarios, to explore the uncertainties in our inputs to the model, suggests that the contribution of seismic or aseismic  
landslide risk is dependent on time-variable input assumptions. The increasing probability of a large Alpine Fault earthquake  
occurring results in increased seismic landslide risk, both individual and societal. Increases in the number of aseismic  
landslides, within the standard deviation of the valley specific magnitude-frequency relationships, also increase the landslide  
590 risk, particularly in Franz Josef. This increase in aseismic landsliding may reflect climatically induced changes in landslide  
rates in these actively deglaciating valleys and suggests that the risk of landsliding will change under different climate change  
scenarios. Additionally, the spatial location and susceptibility of landsliding may also change in response to environmental  
changes. We presented an example to show-case how local changes in the rates of landsliding can be explored and incorporated  
in the analysis. We present our risk results as bands, not points, that display the uncertainty of our risk results. We suggest that  
595 QRA is not only a valuable tool for evaluating the risk to an individual but can be used to better understand what drives  
landslide risk and as such what risk management decisions will be most effective and appropriate in significantly reducing  
risk. In order to do this, QRA must be able to be deconstructed as well as be dynamic to account for changing hazards and  
exposure with time.

## 600 Appendix

### Appendix A: Aseismic landslide inventories

The data sources for the aseismic landslide include 1) a rockfall register compiled from observations made by staff of the  
Department of Conservation (DOC), Franz Josef Glacier Guides Ltd, and Fox Glacier Guides Ltd, 2) a landslide inventory

derived from historical aerial imagery analysis of both valleys, and 3) a large landslide inventory of historical landslides  
605 observed in the wider southern alps. The record of observed rockfall activity in the rockfall register contains data collected  
since 2008 for Franz Josef and 2009 for Fox. The rockfall registers record the date, approximate size, and source location, if  
identifiable, of rockfalls. Alongside this, local knowledge of long-term guides Craig Buckland, Jon Tyler (Franz Josef Glacier  
Guides Ltd) and Marius Bron (Fox Glacier Guides Ltd) informed the relative changing rates and sources of landslide activity  
within each valley. We identified and mapped landslides from a series of historical aerial photographs for each valley (1948,  
610 1965, 1981, 1985, 1987, 2011, 2017 in Franz Josef Glacier Valley, and 1953, 1981, 2017 for Fox Glacier Valley), and these  
landslides were subsequently verified in the field. Additionally, we identified large (>500,000 m<sup>3</sup>) relict landslides in each  
valley, with an unknown temporal occurrence. To assess the potential for large landslides to occur, we used a landslide dataset  
recorded in the wider Southern Alps region, where there is evidence of large landslides occurring under aseismic conditions,  
such as the 2007 11 million m<sup>3</sup> Young River landslide (Massey et al., 2013). We also used data from the following studies  
615 which detail the occurrence of debris avalanches since 1978: McSaveney (2002), Hancox et al. (2010), Cox and Allen (2009)  
, Allen et al. (2011), Allen and Huggel (2013), Massey et al. (2013), and Cox et al. (2015). We assumed that landslides  
<500,000 m<sup>3</sup> are unlikely to have been noticed or mapped unless they impacted people or property in the wider Southern Alps.  
We also assume that landslides in both valleys where the glacier guides and DOC operate would be well documented as people  
are present almost on a daily basis.

## 620 **Appendix B: Aseismic landslide susceptibility models**

We used best sub-set regressions to explore which group of variables could statistically best explain landslide occurrence.  
From these variable groupings, we undertook backward step-wise regression modelling to determine which group of variables  
was the most statistically significant. Using the variables of slope angle, local slope relief (LSR), material type and vegetation,  
we estimated the aseismic landslide probability using the following logistic regression equation (with output coefficients in  
625 Table B 1) for Fox study area:

$$\text{Non EQ LS prob} = 1/(1 + e^{-(\text{Intercept} + \text{Slope Angle} + \text{LSR} + \text{Material type} + \text{veg})}) \quad (\text{B1})$$

For the Franz Josef study area, we found vegetation to be a statistically insignificant variable when used to explain landslide  
occurrence, and as such was not included in the model. For the aseismic landslide probability in the Franz Josef study area, we  
used the following logistic regression equation (with output coefficients in Table B 2):

$$630 \text{ Non EQ LS prob} = 1/(1 + e^{-(\text{Intercept} + \text{Slope Angle} + \text{LSR} + \text{Material type})}) \quad (\text{B2})$$

## Appendix C: Landslide runout analysis

### C.1 Rockfall

We modelled landslides with volumes  $\leq 1,000 \text{ m}^3$  as rockfalls using RAMMS rockfall software (2015) for all material types. The software simulates the rigid body motion of falling rocks and predicts rock trajectories in general three-dimensional terrain. Rock trajectories are governed by the interaction between the rock, its associated shape, and the nature of the ground (e.g., a soft substrate such as sand will dampen the rock energy in contrast to a hard substrate such as rock). Generalised rock shapes are simulated, and rock block orientation and rotational speed are included in the rock/ground interaction. We determined the simulation parameters for forecasting by back-analysing recorded rockfalls within the study areas, where the source area, boulder shape and rockfall trails were recorded or could be accurately inferred. The RAMMS rockfall forecast parameters adopted from back analysis are shown in Table C 1, along with descriptions of the parameters and the data sources used to derive them. The results from the simulations comprise: kinetic energy; runout distance; jump heights and the number of simulated trajectories passing through a given grid cell.

### 645 C.2 Debris avalanche and flows

To identify the areas impacted by landslides, and the associated height of debris and number of boulders, we conducted a suite of runout simulations for the different volume bins. We modelled landslides with source volumes  $> 1,000 \text{ m}^3$  as debris avalanches (if sourced from rock) or as debris flows (if sourced from colluvium or moraine) using RAMMS debris flow software (2011). RAMMS is based on Voellmy friction law, where the frictional resistance consists of a dry-Coulomb type friction (coefficient  $\mu$  or  $\text{Mu}$ ), which scales with normal stress, and a viscous turbulent friction (coefficient  $\xi$ ), which scales with landslide volume. These coefficients are calibrated from the back -analysis of case-studies. For this assessment, we used the back -analysis of 67 debris avalanches (ranging in volume from  $300 \text{ m}^3$  to  $100 \text{ Mm}^3$ ) published in the literature (Schneider et al., 2011; Allen et al., 2009). For debris flows, we used 22 back analysis case-studies ranging in volume from  $1,000 \text{ m}^3$  to  $200,000 \text{ m}^3$  (Loup et al., 2012; Cesca and Agostino, 2008; Deubelbeiss et al., 2011; Hussin, 2011; Scheuner et al., 2011). We fitted a power-law to the data (Figure C1 and Figure C2) to calculate the coefficients for the numerical simulations. For debris flows, the  $\xi$  parameters did not vary with source volume and so we adopted a central estimate of 350 in the numerical simulations.

In areas where the source area could potentially fail as either a debris avalanche or debris flow (for example, potential failure from the top of the larger creeping Yellow Creek landslide in Fox study area), we simulated both and calculated the maximum debris flow height from the two outputs.

### C 3: Sensitivity analysis of debris avalanche and debris flow output

We assessed the sensitivity of the simulated maximum debris heights to varying RAMMS input parameters. Different input Mu and Xi parameters within RAMMS result in a change in both the extent of the debris runout (and therefore area inundated by debris) and the height of the debris and therefore the number of boulders passing through a given location on the ground (grid cell). For the debris avalanche simulations, we calculated the standard error of the modelled fit of the data (Figure C. 3) We both added and subtracted the standard error from the power-law relationship to obtain the mean  $\pm 1$  standard error (SE) values of both Mu ( $\mu$ ) and Xi parameters (Figure C3). For the debris flow simulations, we used the same procedure as outlined for debris avalanches to calculate the Mu parameter. As no relationship existed for the Xi debris flow parameters (Figure C 2), we used the standard deviation ( $\sigma$ ) of the mean parameters to calculate both mean  $+1\sigma$  and mean  $-1\sigma$  ( Figure C4). We choose one representative source area for both debris flow and debris avalanche deposits, to simulate both mean  $+1$  SE (or standard deviation) and mean  $-1$  SE (or standard deviation) runouts. For each source area, the following volume classes were simulated; 10,000 m<sup>3</sup>, 50,000m<sup>3</sup>, 100,000 m<sup>3</sup> and 1 million m<sup>3</sup>. We varied the simulated volume size to assess if the range in maximum flow height increased or decreased for larger volumes. From the simulation results, we calculated the difference in debris heights (per grid cell) between the standard parameter simulation results and the results from each respective mean  $\pm 1$  SE simulation. We calculated the mean and standard deviation of the difference (in debris height per grid cell) for each simulation result (i.e., we calculated the difference of the difference). We summed the values to calculate the mean  $+1\sigma$  (upper-bound) value of the difference between the simulations.

The results from our sensitivity assessment indicate that the absolute difference in debris heights increases with volume size, whereby larger landslides can display several metres of difference in flow height for any given grid cell. Proportionally, the differences in maximum flow height for debris avalanches were on average  $60\% \pm 22\%$  higher than those modelled using the preferred forecast parameters. For debris flows, the difference in maximum flow heights are on average  $60\% \pm 28\%$  higher than those simulations adopting the preferred forecast parameters. We applied this 60% factor of difference to all simulation results to derive upper estimates of debris heights.

### Appendix D Calculation of LPR

For seismic landslides, the probability of death ( $P_D$ ) is calculated for each earthquake Band 1 to 4, for each individual source area of a given volume class, and the debris that the given source area generates. The calculations were done for each grid cell within the study areas. Firstly, we calculated the probability of death for each landslide source and its related debris ( $P_{D(\text{Source})}$ ), where:

$$P_{D(EQ\ Band\ x; Vol\ Class\ y; Source\ z)} = P_{A\ or\ B\ (dependent\ on\ LS\ Vol\ Class)} \times P_{2(S:H)} \times V \quad (D1)$$

695  $P_{A/B}$  is the probability the given source within each landslide volume class, will generate the given volume of debris.  $P_2$  is the probability of being in the path of  $N$  boulders within the debris generated by a given source if it occurs.  $V$  is the vulnerability, defined as the probability of a person being killed if present and in the path of one or more boulders. We then calculated the  $P_{D(Source)}$  for each source area of a given landslide volume class ( $y$ ), and its related debris, and combined for each landslide volume class to estimate the probability of death from all landslides of the same volume class that might contribute to the given grid cell ( $P_{D(Vol\ Class)}$ ), where:

$$700 \quad P_{D(EQ\ Band\ x; Vol\ Class\ y)} = 1 - (1 - P_{D(Vol\ Class\ y1; LS\ Source\ z1)}) \times (1 - P_{D(Vol\ Class\ y1; LS\ Source\ z2)}) \times (1 - P_{D(Vol\ Class\ y1; LS\ Source\ zN...)}) \quad (D2)$$

We then calculated the probability of death from ALL landslides of a given volume class generated by each earthquake band.  $P_{D(EQ\ Band\ x; Vol\ Class\ y)}$  for a given earthquake band ( $x$ ) and volume class ( $y$ ), was multiplied by the number of landslides of a given volume class ( $N_{LS}$ ) generated by the representative earthquake PGA of the given band. If the number of landslides ( $N_{LS}$ ) triggered in the band was  $\geq 1$ , then instead of multiplying  $P_{D(EQ\ Band\ x; Vol\ Class\ y)}$  by the number of landslides ( $N_{LS}$ ), the following formula was used:

$$P_{D(EQ\ Band\ x; ALL\ Vol\ Class\ y)} = 1 - (1 - P_{D(EQ\ Band\ x; Vol\ Class\ y)})^{N_{LS}} \quad (D3)$$

710 We combined the contribution to each grid cell from each landslide volume class per band to calculate the probability of death from all landslides triggered by the representative PGA in the given band ( $P_{D(EQ\ Band\ x)}$ ), where:

$$P_{D(EQ\ Band\ x)} = 1 - (1 - P_{D: ALL\ Vol\ Class\ 1k}) \times (1 - P_{D: All\ Vol\ Class\ 10k}) \times (1 - P_{D: All\ Vol\ Class\ N...}) \quad (D4)$$

We calculated the local personal risk from all landslides that occur within the given band by multiplying  $P_{D(EQ\ Band\ x)}$  by the annual frequency of the presentative earthquake PGA in that band.

715 For aseismic landslides, we calculated the probability of death ( $P_{D(Vol\ Class\ y)}$ ) in the same way as earthquakes except ignored the need to calculate for each earthquake band. We then calculated the LPR for each volume class, by multiplying  $P_{D(Vol\ Class\ y)}$  by the annual frequency of the given volume class ( $y$ ) of landslide occurring.

### 7.5 Mill's creek catchment magnitude – frequency relationship

720 We used several datasets to derive the magnitude-frequency relationship for the Mill's Creek Catchment, including: 1) A change detection model from differencing of a March 2017 digital surface model (DSM) and June 2018 digital elevation model

(DEM); 2) National park staff observations of the frequency of debris flow events and a rough estimate of their associated volume; and 3) NIWA weather observation data from Franz Josef township, which represents the closest meteorological observation point. Our change detection model revealed that between March 2017 and June 2018, approximately 6.5 million m<sup>3</sup> was eroded and 3 million m<sup>3</sup> deposited within the Alpine Gardens and Mill's Creek catchment. During this same time  
725 period, the valley was closed 34 times due to heavy rain and flooding. For the larger storm events, including ex-tropical Cyclone Fehi in February 2018, national park staff observed debris flow activity that resulted in damage to the road. The staff estimated that for the Cyclone Fehi event, approximately 2 million m<sup>3</sup> had been deposited on the Mill's Creek debris fan (Tony Hart – personal communication). Using this information, including both the rough national park staff volume estimates and frequency of heavy rain events likely to trigger debris flows, we divided the approximately 6.5 million m<sup>3</sup> into different debris  
730 flow events based on magnitude – frequency principles. We normalised the data over the 1.38 year time record and the spatial area of the Alpine Gardens and Mills Creek catchment to derive a magnitude frequency power – law relationship, with elevated rates of landslide activity compared to the magnitude – frequency relationship for the Fox Glacier Valley overall.

### **Author contribution**

SdV wrote the manuscript, collated data inputs, conducted hazard and risk analysis. CIM contributed to the manuscript and  
735 conducted hazard and risk analysis. BL contributed to the manuscript and conducted susceptibility and risk analysis modelling. TT contributed to the manuscript plus provided input into the risk analysis, evaluation, and management. RM contributed to the manuscript, collated data inputs and undertook runout modelling. SdV, CIM and RM undertook fieldwork towards the project.

### **Competing interests**

740 The authors declare that they have no conflict of interest.

### **Acknowledgements**

Funding and support for this project was provided by the Department of Conservation (DOC), New Zealand and the Strategic Science Investment Fund (SSIF), NZ. We would like to thank Wayne Costello, Owen Kilgour, Tony Hart and Don Bogie (DOC) for their help and support of the project. Thanks to Marius Bron (Fox Glacier Guides), Craig Buckland, and Jon Tyler  
745 (Franz Josef Glacier Guides) for their local hazard information and knowledge. Thanks also to Garth Archibald, Katie Jones, and Salman Ashraf (GNS Science) for help and support with fieldwork and remote sensing data.



## References

- AGS: Practice Note Guidelines for Landslide Risk Management, in: Australian Geomechanics, vol. 42, Australian Geomechanics Society, 2007.
- 750 Allen, S. and Huggel, C.: Extremely warm temperatures as a potential cause of recent high mountain rockfall, *Glob. Planet. Change*, 107, 59–69, <https://doi.org/10.1016/j.gloplacha.2013.04.007>, 2013.
- Allen, S. K., Schneider, D., and Owens, I. F.: First approaches towards modelling glacial hazards in the Mount Cook region of New Zealand 's Southern Alps, *Nat. Hazards Earth Syst. Sci.*, 9, 481–499, 2009.
- 755 Allen, S. K., Cox, I. S. C., and Owens, I. I. F.: Rock avalanches and other landslides in the central Southern Alps of New Zealand : a regional study considering possible climate change impacts, 33–48, <https://doi.org/10.1007/s10346-010-0222-z>, 2011.
- Bell, R. and Glade, T.: Quantitative risk analysis for landslides – Examples from Bildudalur, NW - Iceland, *Nat. Hazards Earth Syst. Sci.*, 4, 117–131, 2004.
- 760 Brideau, M. ., Massey, C. I., de Vilder, S. J., Mitchell, A., Mcdougall, S., and Aaron, J.: Empirical relationships to estimate the probability of runout exceedence for various landslide types, in: *World Landslide Forum 2020*, 1–6, 2020.
- Budetta, P.: Rockfall-induced impact force causing a debris flow on a volcanoclastic soil slope : a case study in southern Italy, 1995–2006, <https://doi.org/10.5194/nhess-10-1995-2010>, 2010.
- Cesca, M. and Agostino, V. D.: Comparison between FLO-2D and RAMMS in debris-flow modelling : a case study in the Dolomites, in: *WIT Transactions on Engineering Sciences*, 197–206, <https://doi.org/10.2495/DEB080201>, 2008.
- 765 Cody, E., Anderson, B. M., Mccoll, S. T., Fuller, I. C., and Purdie, H. L.: Geomorphology Paraglacial adjustment of sediment slopes during and immediately after glacial debuttressing, 371, 107411, <https://doi.org/10.1016/j.geomorph.2020.107411>, 2020.
- Corominas, J., van Westen, C., Frattini, P., Cascini, L., Malet, J. P., Fotopoulou, S., Catani, F., Van Den Eeckhaut, M., Mavrouli, O., Agliardi, F., Pitilakis, K., Winter, M. G., Pastor, M., Ferlisi, S., Tofani, V., Hervás, J., and Smith, J. T.: Recommendations for the quantitative analysis of landslide risk, *Bull. Eng. Geol. Environ.*, 73, 209–263, <https://doi.org/10.1007/s10064-013-0538-8>, 2014.
- 770 Corominas, J., Matas, G., and Ruiz-carulla, R.: Quantitative analysis of risk from fragmental rockfalls, 16, 5–21, <https://doi.org/10.1007/s10346-018-1087-9>, 2019.
- 775 Cox, S. and Allen, S. K.: Vampire rock avalanches of January 2008 and 2003 , Southern Alps , New Zealand, 6, 161–166, <https://doi.org/10.1007/s10346-009-0149-4>, 2009.
- Cox, S., Mcsaveney, M. J., Spencer, J., Allen, S. K., Ashraf, S., Hancox, G. T., Sirguyev, P., Salichon, J., and Ferris, B. G.: Rock avalanche on 14 July 2014 from Hillary Ridge , Aoraki / Mount Cook , New Zealand, <https://doi.org/10.1007/s10346-015-0556-7>, 2015.
- 780 Cox, S. C. and Barrell, D. J. A.: Geology of the Aoraki area: Institute of Geological and Nuclear Sciences 1:250 000 geological

- map, Lower Hutt, New Zealand, 1 sheet + 71 pages pp., 2007.
- Crowley, H.: Framework for Developing Fragility and Consequence Models for Local Personal Risk, *Earthq. Spectra*, 33, 1325–1345, <https://doi.org/10.1193/083116EQS140M>, 2017.
- Deubelbeiss, Y., Graf, C., and Christen, M.: Numerical modelling of debris flows with RAMMS - Alpine case studies, in: 785 *World Landslide Forum Abstracts*, 308, 2011.
- Dowrick, D. J., Hancox, G. T., Perrin, N. D., and Dellow, G. D.: The modified mercalli intensity scale - revisions arising from New Zealand experience, *Bull. New Zeal. Soc. Earthq. Eng.*, 41, 193–205, 2008.
- Du, J., Yin, K., Nadim, F., and Lacasse, S.: Quantitative vulnerability estimation for individual landslides, 18th Int. Conf. Soil Mech. Geotech. Eng. Paris 2013, 2181–2184, 2013.
- 790 Eberhardt, E., Stead, D., and Coggan, J. S.: Numerical analysis of initiation and progressive failure in natural rock slopes — the 1991 Randa rockslide, 41, 69–87, [https://doi.org/10.1016/S1365-1609\(03\)00076-5](https://doi.org/10.1016/S1365-1609(03)00076-5), 2004.
- Eppes, M.-C. and Keanini, R.: Mechanical Weathering and Rock Erosion by Climate-Dependent Subcritical Cracking, *Rev. Geophys.*, 55, 1–39, <https://doi.org/10.1002/2017RG000557>, 2017.
- Fell, R., Ho, K. K. ., Lacasse, S., and Leroi, E.: A framework for landslide risk assessment and management, in: *Landslide*, 3–795 25, 2005.
- Fell, R., Corominas, J., Bonnard, C., Cascini, L., Leroi, E., and Savage, W. Z.: Commentary: Guidelines for landslide susceptibility, hazard and risk zoning for land-use planning, *Eng. Geol.*, 102, 99–111, <https://doi.org/10.1016/j.enggeo.2008.03.014>, 2008.
- Fischer, L., Purves, R. S., Huggel, C., Noetzi, J., and Haeberli, W.: On the influence of topographic, geological and cryospheric 800 factors on rock avalanches and rockfalls in high-mountain areas, *Nat. Hazards Earth Syst. Sci.*, 12, 241–254, <https://doi.org/10.5194/nhess-12-241-2012>, 2012.
- Gariano, S. L. and Guzzetti, F.: Landslides in a changing climate, *Earth-Science Rev.*, 162, 227–252, <https://doi.org/10.1016/j.earscirev.2016.08.011>, 2016.
- Gomez, C. and Purdie, H.: Point cloud technology and 2D computational flow dynamic modeling for rapid hazards and disaster 805 risk appraisal on Yellow Creek fan , Southern Alps of New Zealand, 1–10, 2018.
- Gunzburger, Y., Merrien-Soukatchoff, V., and Guglielmi, Y.: Influence of daily surface temperature fluctuations on rock slope stability: a case study of the Rochers de Valabres slope (France), *Int. J. Rock Mech. Min. Sci.*, 42, 331–349, 2005.
- Guzzetti, F., Cesare, A., Cardinali, M., Fiorucci, F., Santangelo, M., and Chang, K.: Landslide inventory maps : New tools for an old problem, *Earth Sci. Rev.*, 112, 42–66, <https://doi.org/10.1016/j.earscirev.2012.02.001>, 2012.
- 810 Hancox, G. T., Mcsaveney, M. J., Manville, V. R., Davies, T. R., Hancox, G. T., Mcsaveney, M. J., Manville, V. R., Tim, R., Mcsaveney, M. J., and Manville, V. R.: The October 1999 Mt Adams rock avalanche and subsequent landslide dam - break flood and effects in Poerua river , Westland , New Zealand, 8306, <https://doi.org/10.1080/00288306.2005.9515141>, 2010.
- Hancox, G. T., Ries, W., Lukovic, B., and Parker, R. N.: Landslides and ground damage caused by the Mw 7,1 Inangahua earthquake of 24 May 1968 in northwest South Island, New Zealand, *GNS Sci. Rep.*, 2014/06, 89, 2014.

- 815 Hancox, G. T., Ries, W., Parker, R. N., and Rosser, B.: Landslides caused by the MS 7.8 Murchison earthquake of 17 June 1929 in northwest South Island, New Zealand, *GNS Sci. Rep.*, 2015/42, 105, 2015.
- Ho, K., Leroi, E., and Roberds, B.: Keynote lecture: quantitative risk assessment - application, myths and future direction, in: *Proceedings of the International Conference on Geotechnical and Geological Engineering, GEOENG 2000*, 236–312, 2000.
- Hock, R., Rasul, G., Adler, C., Caceres, B., Gruber, S., Hirabayashi, Y., Jackson, M., Kaab, A., Kang, S., Kutuzov, S., Milner, A., Molau, U., Morin, S., Orlove, B., and Steltzer, H.: High Mountain Areas, in: *IPCC Special Report on the Ocean and Cryosphere in a Changing Climate*, 131–202, 2020.
- 820 Horton, P., Jaboyedoff, M., Rudaz, B., and Zimmermann, M.: Flow-R , a model for susceptibility mapping of debris flows and other Atmospheric, *Nat. Hazards Earth Syst. Sci.*, 13, 869–885, <https://doi.org/10.5194/nhess-13-869-2013>, 2013.
- Hovius, N., Stark, C. P., and Allen, P. A.: Sediment flux from a mountain belt derived by landslide mapping, *Geology*, 25, 231–234, [https://doi.org/10.1130/0091-7613\(1997\)025<0231:SFFAMB>2.3.CO;2](https://doi.org/10.1130/0091-7613(1997)025<0231:SFFAMB>2.3.CO;2), 1997.
- 825 Howarth, J. D., Barth, N. C., Fitzsimons, S. J., Richards-dinger, K., Clark, K. J., Biasi, G. P., Cochran, U. A., Langridge, R. M., Berryman, K. R., and Sutherland, R.: Spatiotemporal clustering of great earthquakes on a transform fault controlled by geometry, *Nat. Geosci.*, 14, 314–320, <https://doi.org/10.1038/s41561-021-00721-4>, 2021.
- Huggel, C., Clague, J. J., and Korup, O.: Is climate change responsible for changing landslide activity in high mountains ?, *Earth Surf. Process. Landforms*, 37, 77–91, <https://doi.org/10.1002/esp.2223>, 2012.
- 830 Hungr, O., Leroueil, S., and Picarelli, L.: The Varnes classification of landslide types, an update, 11, 167–194, <https://doi.org/10.1007/s10346-013-0436-y>, 2014.
- Hussin, H. Y.: Probabilistic Run-out Modeling of a Debris Flow in Barcelonnette , France Probabilistic Run-out Modeling of a Debris Flow in Barcelonnette , France, 94 pp., 2011.
- 835 Jonkman, S. N., Gelder, P. H. A. J. M. Van, and Vrijling, J. K.: An overview of quantitative risk measures for loss of life and economic damage, *J. Hazard. Mater.*, A99, 1–30, [https://doi.org/10.1016/S0304-3894\(02\)00283-2](https://doi.org/10.1016/S0304-3894(02)00283-2), 2003.
- Keefer, D. K.: Investigating landslides caused by earthquakes - a historical review, *Surv. Geophys.*, 23, 473–510, 2002.
- Korup, O., McSaveney, M. J., and Davies, T. R. .: Sediment generation and delivery from large historic landslides in the Southern Alps, New Zealand, 61, 189–207, <https://doi.org/10.1016/j.geomorph.2004.01.001>, 2004.
- 840 Korup, O., Hayakawa, Y., and Science, N.: State of Science Without power ? Landslide inventories in the face of climate change, 99, 92–99, <https://doi.org/10.1002/esp.2248>, 2012.
- Langridge, R., Howarth, J., Buxton, R., and Ries, W.: A Natural Hazard Assessment for the Township of Franz Josef, Westland District, 61 pp., 2016.
- Lee, E. M.: Landslide risk assessment : the challenge of estimating the probability of landsliding, *Q. J. Eng. Geol. Hydrogeol.*, 42, 445–458, <https://doi.org/10.1144/1470-9236/08-007>, 2009.
- 845 Lee, E. M. and Jones, D. K. C.: *Landslide Risk Assessment*, 2nd ed., ICE Publishing, London, 509 pp., 2014.
- Lin, C., Liu, S., Lee, S., and Liu, C.: Impacts of the Chi-Chi earthquake on subsequent rainfall-induced landslides in central Taiwan, *Eng. Geol.*, 86, 87–101, <https://doi.org/10.1016/j.enggeo.2006.02.010>, 2006.

- Liu, J., Wu, Y., and Gao, X.: Increase in occurrence of large glacier - related landslides in the high mountains of Asia, *Sci. Rep.*, 1–12, <https://doi.org/10.1038/s41598-021-81212-9>, 2021.
- Loup, B., Egli, T., Stucki, M., Bartlet, P., McArdeell, B., and Baumann, R.: Impact pressures of hillslope debris flows, in: 12th Congress INTERPRAEVENT, 225–236, 2012.
- Macciotta, R., Martin, I. C. D., Morgenstern, I. N. R., and Cruden, I. D. M.: Development and application of a quantitative risk assessment to a very slow moving rock slope and potential sudden acceleration, 765–785, <https://doi.org/10.1007/s10346-015-0609-y>, 2015a.
- Macciotta, R., Martin, C. D., Morgenstern, N. R., and Cruden, D. M.: Quantitative risk assessment of slope hazards along a section of railway in the Canadian Cordillera — a methodology considering the uncertainty in the results, <https://doi.org/10.1007/s10346-014-0551-4>, 2015b.
- Macciotta, R., Martin, I. C. D., Morgenstern, I. N. R., and Cruden, I. D. M.: Development and application of a quantitative risk assessment to a very slow moving rock slope and potential sudden acceleration, 765–785, <https://doi.org/10.1007/s10346-015-0609-y>, 2016.
- Marc, O., Hovius, N., Meunier, P., Uchida, T., and Hayashi, S.: Transient changes of landslide rates after earthquakes, 43, 883–886, <https://doi.org/10.1130/G36961.1>, 2015.
- Massey, C., Mcsaveney, M., and Davies, T.: Evolution of an Overflow Channel Across the Young River Landslide Dam , New Zealand, in: *Landslide Science and Practice*, 43–49, <https://doi.org/10.1007/978-3-642-31319-6>, 2013.
- Massey, C., Townsend, D., Rathje, E., Allstadt, K. E., Lukovic, B., Kaneko, Y., Bradley, B., Jibson, R. W., Petley, D. N., Horspool, N., Hamling, I., Carey, J., Cox, S., Davidson, J., Godt, J. W., Holden, C., Jones, K., Kaiser, A., Little, M., Lyndsell, B., Mccoll, S., Rengers, F. K., Rhoades, D., Rosser, B., Strong, D., Singeisen, C., and Villeneuve, M.: Landslides Triggered by the 14 November 2016 M w 7 . 8 Kaik ō ura Earthquake , New Zealand, 108, 1630–1648, <https://doi.org/10.1785/0120170305>, 2018a.
- Massey, C., Townsend, D., Rathje, E., Allstadt, K. E., Lukovic, B., Kaneko, Y., Bradley, B., Jibson, R. W., Petley, D. N., Horspool, N., Hamling, I., Carey, J., Cox, S., Davidson, J., Godt, J. W., Holden, C., Jones, K., Kaiser, A., Little, M., Lyndsell, B., Mccoll, S., Rengers, F. K., Rhoades, D., Rosser, B., Strong, D., Singeisen, C., and Villeneuve, M.: Landslides Triggered by the 14 November 2016 Mw 7.8 Kaikoura Earthquake , New Zealand, *Bull. Seismol. Soc. Am.*, 108, 1630–1648, <https://doi.org/10.1785/0120170305>, 2018b.
- Massey, C. I., Mcsaveney, M. J., Taig, T., Richards, L., Litchfield, N. J., Rhoades, D. A., Mcverry, G. H., Eeri, M., Lukovic, B., Heron, D. W., and Ries, W.: Determining Rockfall Risk in Christchurch Using Rockfalls Triggered by the 2010 – 2011 Canterbury Earthquake Sequence, 30, 155–181, <https://doi.org/10.1193/021413EQS026M>, 2014a.
- Massey, C. I., Townsend, D. B., Jones, K., Lukovic, B., Rhoades, D., Morgenstern, R., Rosser, B., Ries, W., Howarth, J., Hamling, I., Petley, D., Clark, M., Wartman, J., Litchfield, N., Olsen, M., Wartmann, J., Litchfield, N., and Olsen, M.: Volume characteristics of landslides triggered by the Mw 7.8 2016 Kaikoura Earthquake, New Zealand, derived from digital surface difference modelling, *J. Geophys. Res.*, 125, 2020.

- Massey, C. I., Lukovic, B., Huso, R., Buxton, R., and Potter, S, H.: Earthquake-induced landslide forecast tool for New Zealand: version 2. GNS Science Report 2018/08, 77 pp., 2021.
- 885 Massey, C. I., de Vilder, S., Taig, T., Lukovic, B., Archibald, G., and Morgenstern, R.: Landslide hazard and risk assessment for the Fox and Franz Josef Glacier Valleys, GNS Sci. Science. Rep., 2022/29, 101, 2022a.
- Massey, C.I., Olsen, M.J., Wartman, J., Senogles, A., Lukovic, B., Leshchinsky, B.A., Archibald, G., Litchfield, N., Van Dissen, R., de Vilder, S., and Holden, C.: Rockfall Activity Rates before, during and after the 2010/2011 Canterbury Earthquake Sequence, *J. Geophys. Res.*, 127, 2022.
- 890 McDougall, S.: 2014 Canadian Geotechnical Colloquium : Landslide runout analysis — current practice and challenges, 54, 605–620, 2017.
- McSaveney, M. J.: Recent rockfalls and rock avalanches in Mount Cook National Park, New Zealand, *Geol. Soc. Am. Rev. Eng. Geol.*, XV, 35–70, 2002.
- Moon, A., Wilson, R., and Flentje, P.: Developing and using landslide size frequency models, *Fac. Eng.*, 384, 895 <https://doi.org/10.1603/0046-225X-31.3.573>, 2005.
- Purdie, H., Gomez, C., and Espiner, S.: Glacier recession and the changing rockfall hazard: Implications for glacier tourism, *N. Z. Geog.*, 71, 189–202, 2015.
- RAMMS: RAMMS - rapid mass movements simulation, A numerical model for debris flows in research and practice, User Manual v1.7.0, Debris Flow, Manuscript update November 2017. WSL Institute for Snow and Avalanche Research SLF, 2011.
- 900 RAMMS: A numerical model for rockfall in research and practice. User Manual v1.6 Rockfall, 2015.
- Reichenbach, P., Rossi, M., Malamud, B. D., Mihir, M., and Guzzetti, F.: A review of statistically-based landslide susceptibility models, *Earth-Science Rev.*, 180, 60–91, <https://doi.org/10.1016/j.earscirev.2018.03.001>, 2018.
- Robinson, T. R. and Davies, T. R. H.: Review Article : Potential geomorphic consequences of a future great (  $M_w = 8.0+$  ) Alpine Fault earthquake , South Island , New Zealand, *Nat. Hazards Earth Syst. Sci.*, 13, 2279–2299, 905 <https://doi.org/10.5194/nhess-13-2279-2013>, 2013.
- Robinson, T. R., Davies, T. R. H., Wilson, T. ., and Orchiston, C.: Coseismic landsliding estimates for an Alpine Fault earthquake and the consequences for erosion of the Southern Alps, New Zealand, 263, 71–86, 2016.
- Scheuner, T., Schwab, S., and Mcardell, B. W.: Application of a two-dimensional numerical model in risk and hazard assessment in Switzerland, *Ital. J. Eng. Geol. Environ.*, 03, 993–1001, <https://doi.org/10.4408/IJEGE.2011-03.B-108>, 2011.
- 910 Schneider, D., Huggel, C., Haerberli, W., and Kaitna, R.: Unraveling driving factors for large rock-ice avalanche mobility, *Earth Surf. Process. Landforms*, 36, 1948–1966, <https://doi.org/10.1002/esp.2218>, 2011.
- Stirling, M., McVerry, G., Gerstenberger, M., Litchfield, N., Van Dissen, R., Berryman, K., Barnes, P., Wallace, L., Villamor, P., Langridge, R., Lamarche, G., Nodder, S., Reyners, M., Bradley, B., Rhoades, D., Smith, W., Nicol, A., Pettinga, J., Clark, K., and Jacobs, K.: National seismic hazard model for New Zealand: 2010 update, *Bull. Seismol. Soc. Am.*, 102, 1514–1542, 915 <https://doi.org/10.1785/0120110170>, 2012.
- Stock, G. M., Luco, N., Collins, B. D., Harp, E. L., Reichenbach, P., and Frankel, K. L.: Quantitative Rock-Fall Hazard and

- Risk Assessment for Yosemite Valley, Yosemite National Park, California, in: U.S. Geological Survey Scientific Investigations Report 2014-5129, 52, 2014.
- 920 Strouth, A. and Mcdougall, S.: Societal risk evaluation for landslides: historical synthesis and proposed tools, 18, 1071–1085, <https://doi.org/10.1007/s10346-020-01547-8>, 2021.
- Taig, T.: Guidelines for DOC on dealing with natural hazard risk, Cheshire (GB), 91 pp., 2022a.
- Taig, T.: Risk comparisons for DOC visitors and staff, Cheshire (GB), 131 pp., 2022b.
- 925 Taig, T., Massey, C. I., and Webb, T.: Canterbury Earthquakes 2010/11 Port Hills Slope Stability: Principles and Criteria for the Assessment of Risk from Slope Instability in the Port Hills, Christchurch, in: GNS Science Consultancy Report 2011/399, 47, 2012.
- Varnes, D. J.: Slope movement types and processes, in: Special Report 176: Landslides - Analysis and Control, edited by: Schuster, R. L. and Krizek, R. J., Transportation and Road Research Board, National Academy of Science, Washington D.C., 11–33, 1978.
- 930 Vega, J. A. and Hidalgo, C. A.: Geomorphology Quantitative risk assessment of landslides triggered by earthquakes and rainfall based on direct costs of urban buildings, 273, 217–235, <https://doi.org/10.1016/j.geomorph.2016.07.032>, 2016.
- de Vilder, S. J., Massey, C. I., Taig, T., Lukovic, B., Archibald, G., and Morgenstern, R.: Quantitative risk analysis of earthquake induced landslides, in: Understanding and reducing landslide disaster risk. [WLF 2020]. Volume 4, Testing, modelling, and risk assessment., 465–470, 2020.
- 935 Viles, H.: Linking weathering and rock slope instability: non-linear perspectives, *Earth Surf. Process. Landforms*, 38, 62–70, <https://doi.org/10.1002/esp.3294>, 2013.
- Voumard, J., Caspar, O., Derron, M., and Jaboyedoff, M.: Dynamic risk simulation to assess natural hazards risk along roads, 2763–2777, <https://doi.org/10.5194/nhess-13-2763-2013>, 2013.
- van Westen, C. J., Castellanos, E., and Kuriakose, S. L.: Spatial data for landslide susceptibility, hazard, and vulnerability assessment: An overview, *Eng. Geol.*, 102, 112–131, <https://doi.org/10.1016/j.enggeo.2008.03.010>, 2008.
- 940 Van Westen, C. J. and Soeters, R.: Landslide hazard and risk zonation — why is it still so difficult ?, *Bull. Eng. Geol. Environ.*, 65, 167–184, <https://doi.org/10.1007/s10064-005-0023-0>, 2006.

**Table 1: Physical vulnerability values used in study**

Representative Landslide Volume (m <sup>3</sup> )	Vulnerability	
	Central Estimate	Upper Estimate
1,000	0.1	1
10,000	0.5	1
50,000	0.5	1
100,000	0.9	1
≥500,000	1	1

945

**Table 2: Risk model scenarios and associated input variables**

Risk Scenario	Number of landslides generated during an earthquake	Annual number of aseismic landslides	Debris Height	Diameter of a person	Vulnerability	EQ Scenario	Spatio-temporal probability
1	Central	Central	Central	1	Central estimate	Time Independent	Average walker
2	Upper	Central	Central	1	Central estimate	Time Independent	Average walker
3	Upper	Upper	Central	1	Central estimate	Time Independent	Average walker
4	Upper	Upper	Upper	1	Central estimate	Time Independent	Average walker
5	Upper	Upper	Upper	2	Central estimate	Time Independent	Average walker
6	Upper	Upper	Upper	2	Upper estimate	Time Independent	Average walker
7	Upper	Upper	Upper	2	Upper estimate	Time Dependent	Average walker
8	Upper	Upper	Upper	2	Upper estimate	Time Dependent	Slow Walker
9	Central	Central	Central	1	Central	Time Dependent	Average Walker

**Table 3: Risk Model Sensitivity Analysis displaying the factor in increased risk between each scenario and the cumulative increase in risk from central to upper estimate (Scenario 8).**

Risk Model Scenario	Changing risk variable	Franz Josef Glacier Valley		Fox Glacier Valley	
		Cumulative Increase %	Risk Percentage	Cumulative Increase %	Risk Percentage
1	Central Estimate Scenario	NA	NA	NA	NA
2	Increased number of landslides generated during an earthquake	46	46	10	10
3	Increased number of aseismic landslides	411	365	40	30
4	Increased debris height	420	9	42	2
5	Increased diameter of a person	421	1	42	0
6	Increased vulnerability	640	219	108	66
7	Increased earthquake annual frequency	970	330	164	56
8	Increased exposure time	1298	328	244	80

950 **Table B 1 : Summary table of co-efficient estimates for the variables used in the Fox study area logistic regression equation.**

Parameter Type		Estimate (coefficients)	Standard error	Statistical significance (p)
Intercept		-7.07532	0.235784	0.000000
Slope Angle		0.03376	0.000177	0.000000
Local Slope Relief		0.02067	0.000188	0.000000
Material Type	Rock	1.33131	0.235734	0.000000
	Alluvium	-5.16420	0.471425	0.000000
	Colluvium	0*	NA	NA
Vegetation	Vegetated	-1.08698	0.003315	0.000000
	No Vegetation	0**	NA	NA

\*Colluvium is set as the reference material, which means that Alluvium is less likely to fail with a negative estimate and rock more likely to fail with a positive estimate.

\*\*Slopes that are not vegetated is set as the reference vegetation variable, which means that areas that are vegetated are less likely to fail with a negative estimate.

955 **Table B 2: Summary table of co-efficient estimates for the variables used in the Franz Josef study area logistic regression equation.**

Parameter Type		Estimate (coefficients)	Standard error	Statistical significance (p)
Intercept		-5.70152	0.061317	0.000000
Slope Angle		0.01196	0.000176	0.000000
Local Slope Relief		0.00506	0.000159	0.000000
Material type	Colluvium	1.33545	0.061123	0.000000
	Rock	2.39511	0.060985	0.000000
	Alluvium	0*	NA	NA

\*\*Alluvium is set as the reference material, which means that colluvium and rock are more likely to fail with a positive estimate.

960

965



**Table C 1: RAMMS Rockfall model parameters used for forecasting rockfalls.**

Simulation Variable	Description	RAMMS parameter	Data source
Substrate material	Alluvium, swamp	Terrain parameter: Soft	Materials taken from the engineering geomorphology materials layer
	Colluvium, talus and moraine, and mixed colluvium, moraine, and talus	Terrain parameter: Medium	
	Rock, rock at/near surface	Terrain parameter: Hard	
Vegetation	Scrub	Forest parameter: Open forest	Mapped from aerial photographs and field verified
	Trees	Forest parameter: Medium forest	
Rock shape	The shape of the boulders used in the simulations	Rock parameter: “Real long”, dimensions (1.5 by 1.0 by 1.0 m). Rock volume = 1 m <sup>3</sup> (assumes rounded edges). Mass = 2,730 kg	Field mapping and measurements of rockfalls
Topography	The digital elevation model used in the simulations	Terrain = 3 m by 3 m grid cell resolution	Digital Elevation Models (DEM) (bare earth) derived from the LiDAR surveys of both study areas
Release	Number of random orientations of the rock blocks at source	Three random orientations were selected	N/A
	Source area locations	Rock positions: from 3 m by 3 m grid cells, with slope angles $\geq 45^\circ$	From the LIDAR DEMs
	Initial velocities of the rock blocks	Initial velocities of: X = 1.5 m/s, Y = 1.5 m/s and Z = 1.0 m/s, were assumed	N/A

970

975

980

985 **Figure 1:** Location of the Franz Josef and Fox Glacier Valleys on the West Coast of the South Island (a & b), which contains data sourced from the LINZ Data service and licensed for reuse under the CC BY 4.0 licence. c) Photograph of Franz Josef Glacier Valley. d) Fox Glacier Valley, including the access roads, cycleway, and tracks within it. e) Franz Josef Glacier valley, including the access roads, cycleway, and tracks within it.

**Figure 2:** Schematic and example photographs of landslide types considered in the QRA, including a) rockfall, b) debris and rock avalanches, and c) debris flows.

990 **Figure 3:** a) The number of landslides of given landslide volume that could be generated for different levels of ground-shaking as represented by Bands 1 through to 4. The power law for Band 2 is  $y = 2.28x 10^6x (\text{vol}^{-1.60})$ , for Band 3 is  $y = 2.33x 10^6x (\text{vol}^{-1.45})$ , for Band 4 is  $y = 1.47x 10^7x (\text{vol}^{-1.41})$ . b) Magnitude Frequency relationships for aseismic landslides for Fox Glacier Valley and Franz Josef Glacier Valley. The two power laws on each graph represent the central estimate (using the power-law relationships). The power law for Franz Josef Glacier Valley is  $y = 9.08x (\text{vol}^{-0.66})$ , and for Fox Glacier Valley it is  $y = 5.21x (\text{vol}^{-0.51})$ .

995 **Figure 4:** Generation of both a seismic and seismic logistic regression model for Fox Glacier Valley. The aseismic logistic regression model is determined from the correlation between a) The landslide inventory, and the static variables of b) slope angle, c) local slope relief (LSR- defined as maximum height difference within a fixed 80 m radius of the grid cell), d) geology, and e) vegetation (as classified from imagery and the Land Cover Database). The logistic regression model calculates f) aseismic landslide susceptibility. The seismic logistic regression model is determined from the correlation between g) peak ground acceleration (PGA), and the static variables of b) slope angle, c) local slope relief (LSR), d) geology, and h) distance to active faults (Massey et al., 2018a). The logistic regression model calculates i) seismic landslide susceptibility.

1000 **Figure 5:** a) Simulated source areas in Fox Glacier Valley for all volume classes. b) Numerical rockfall simulations, using RAMMS, from pixel source areas. c) Numerical debris avalanche and debris flow simulations, using RAMMS, from pixel source areas for volume classes 10,000 m<sup>3</sup> to 100,000 m<sup>3</sup>. d) Numerical debris avalanche simulations, using RAMMS, for geomorphically defined source areas for volume classes  $\geq 500,000$  m<sup>3</sup>.

1005 **Figure 6:** a) Boxplot of the measured boulder volumes (n = 36) in the field, indicating a median boulder volume of 1 m<sup>3</sup>. b) Histogram of the measured boulder volumes in the field.

**Figure 7:** Risk results from Scenario 1 (Central Estimate) risk model for Franz Josef Glacier Valley. a) LPR map displaying areas of higher and lower risk, along with the location of tracks (black dotted lines) in the valley. The risk results presented in b) to d) are extracted along the lower track in a). b) LPR values for aseismic landslides compared with seismic landslides, c) LPR values for different volume classes of aseismic landslides. d) LPR values for the different bands of ground shaking (from lowest Band 1 through to highest Band 4).

1010 **Figure 8:** Risk results from Scenario 1 (Central Estimate) risk model for Fox Glacier Valley. a) LPR map displaying areas of higher and lower risk, along with the location of the access track (black dotted line) in the valley. The risk results presented in b) to d) are extracted along the track in a). b) LPR values for aseismic landslides compared with seismic landslides, c) LPR values for different volume classes of aseismic landslides. d) LPR values for the different bands of ground shaking (from lowest Band 1 through to highest Band 4).

**Figure 9:** Risk results for Scenario 9 (central estimate & time dependent earthquake frequency) along the access track in a) Franz Josef Glacier Valley and b) Fox Glacier Valley, displaying the contributions of aseismic landslide risk and seismic landslide risk.

1020 **Figure 10:** a) & b) Photographs of the evolution of the Mill's Creek debris fan and Alpine Gardens landslide. c) The linkage between the Alpine Gardens landslide and Mill's Creek debris channel and fan.

**Figure 11:** Calculation of local personal risk for Fox Glacier Valley, including recent elevated levels of activity in the Alpine Gardens – Mill's Creek debris complex.

1025 **Figure 12:** Quantitative estimates of individual risk per trip for Fox Glacier and Franz Josef Glacier visitors compared against popular tourist activities, modes of transportation used to access the glaciers, and individual risk per trip to national parks overseas (sourced from Taig, 2022). The band range for each activity represents both the statistical uncertainty and uncertainty in the denominators of units of activity undertaken (cf. Taig, 2022).

**Figure C 1:** Debris avalanches: Range of parameters used to back-analyse the runout of debris avalanches published in the literature (n = 67), using the RAMMS software.

1030 **Figure C 2: Debris flow: Range of parameters used to back-analyse the runout of debris flows published in the literature (n = 22), using the RAMMS software**

**Figure C 3: Range of parameters used to back analyse the runout of debris avalanches published in the literature. Purple fitted line represents the mean  $-1\sigma$ , the red line represents the modelled fit of the data, and the green line represents the mean  $+1\sigma$ .**

1035 **Figure C 4: Range of parameters used to back analyse the runout of debris flows published in the literatures. The purple fitted line represents the mean  $-1\sigma$ , the red line represents the rounded parameters used within the simulation, and the green line represents the mean  $+1\sigma$ .**