

Strategies for Comparison of Modern Probabilistic Seismic Hazard Models and Insights from the Germany and France Border Region

Graeme Weatherill¹, Fabrice Cotton^{1,4}, Guillaume Daniel², Irmela Zentner³, Pablo Iturrieta^{1,4}, Christian Bosse¹

5 ¹GFZ German Research Centre for Geosciences, Potsdam, 14473, Germany

²Électricité de France, Aix-en-Provence, 13290, France

³Électricité de France, EDF R & D Lab Paris-Saclay, 91120, France

⁴University of Potsdam, Potsdam-Golm, 14476, Germany

Correspondence to: graeme.weatherill@gfz-potsdam.de

10 **Abstract.** The latest generation of national and regional probabilistic seismic hazard assessments (PSHA) in Europe presents stakeholders with multiple representations of the hazard in many regions. This raises the question of why and by how much seismic hazard estimates between two or more models differ, not where models overlap geographically but also where new models update existing ones. As modern PSHA incorporates increasingly complex analysis of epistemic uncertainty, the resulting hazard is represented not as a single value or spectrum but rather as probability distribution. Focusing on recent
15 PSHA models for France and Germany, alongside the 2020 European Seismic Hazard Model, we explore the differences in model components and highlight the challenges and strategy for harmonising the different models into a common PSHA calculation software. We then quantify the differences in the source model and seismic hazard probability distributions using metrics based on information theory, illustrating their application to Upper Rhine Graben region. Our analyses reveal the spatial variation and complexity of model differences when viewed as probability distributions and highlight the need for more
20 detailed transparency and replicability of the models when used as a basis for decision making and engineering design.

Short Summary. New generations of seismic hazard models are developed with sophisticated approaches to quantify uncertainties in our knowledge of the earthquake process. To understand why and how recent state-of-the-art seismic hazard models for France, Germany and Europe differ despite similar underlying assumptions, we present a systematic approach to
25 investigate model-to-model differences and to quantify and visualise them while accounting for their respective uncertainties.

1 Introduction

Effective mitigation of seismic risk, be it at a local, national, or regional scale, requires a quantitative assessment not only of the strength or impacts of the perils to which an area may be subject, but also their probability of occurrence over a given time frame. For earthquakes, probabilistic seismic hazard assessment (PSHA) is now established as the primary means through
30 which our understanding of the physical phenomena is translated into a framework that can yield critical information of

relevance for engineering design, urban planning and development, and financial instruments to mitigate the economic impacts of these events on society. Given the volume of information for risk mitigation that PSHA can produce, national and regional scale PSHA models are now available for every country across the globe (Pagani et al, 2020), with many countries now having developed several successive generations of seismic hazard models and, in some regions, multiple models offering different perspectives on seismic hazard for the same area of interest (Gerstenberger et al., 2020).

The issue of multiple perspectives on seismic hazard in a region can be an important one to address from the point of view of model developers, but it also has significant implications for the users of the seismic hazard outputs. In the case that a new seismic hazard model for a region is produced that is intended to update or supersede an existing model, while there may be a recognition that new data for that region and/or developments in PSHA practice justifies revising or updating a seismic hazard model periodically, this revision will inevitably have implications for stakeholders, particularly when hazard is found to increase or decrease substantially at a location as a result of the new information. In Europe, many different countries are confronted with this situation as new generations of national seismic hazard models emerge. There is, however, also a compounding issue, which is the need for Pan-European assessments of seismic hazard. Two major models within the last decade have resulted from large-scale multi-institution projects that have put a strong focus on incorporating state-of-the-art developments in PSHA, namely the 2013 European Seismic Hazard Model (ESHM13) (Wössner et al., 2015) and the 2020 European Seismic Hazard model (ESHM20) (Danciu et al., 2021).

Since the completion of the ESHM13 many new seismic hazard models have been developed at national scale, among which are Switzerland (Wiemer et al. 2016)), Spain (IGN, 2017), Turkey (Akkar et al., 2018), Germany (Grünthal et al., 2018), France (Drouet et al., 2020), Italy (Meletti et al., 2021), United Kingdom (Mosca et al., 2022), and many more. Furthermore, in other countries such as Portugal and Greece, although no new national seismic hazard model has been developed, ESHM13 was instrumental in prompting efforts to collect and improve geophysical datasets as an initial step toward new seismic hazard models in these countries in the future. In many cases, it has been possible to leverage upon these efforts within the model development process of ESHM20. Several factors have motivated these national scale developments, but chief among these is the establishment of Eurocode 8 (EC8; CEN, 2004) as the predominant standard covering earthquake resistant design. EC8 devolves some specific components of its seismic design requirements to each of the participating member states via their respective National Annexes. Among these components are the seismic hazard map on which the design levels of seismic input are based. In many cases, national building design authorities have opted to undertake revisions to their national seismic hazard maps, in part aiming to bring these into line with (or even exceeding of) standards for state-of-practice PSHA modelling in Europe set by the ESHM13, but also because new or more detailed data may be available at local scale to allow a refined estimate of hazard that may not be scalable to larger multi-national regions. These national models should form the authoritative reference seismic hazard model for application to engineering design in their respective countries. In some cases,

however, these models have integrated components or ideas developed within the ESHM13. We also expect this trend to
65 continue with expected updates to Eurocode 8 and following the publication of the ESHM20.

The dual existence of both a regional scale model (or models) and a national model that cover the same territory raises the
question of comparison between models. How and why do models differ and how can we quantify differences? It has become
standard practice for modern seismic hazard assessment to contain detailed assessments of epistemic uncertainty in both the
70 seismogenic source model (SSM) and ground motion model (GMM) components. These are incorporated into the analysis in
the form of logic trees, which generate many seismic hazard curves by enumerating (or sampling) combinations of alternative
models or model parameterisations and their associated weights. Logic trees have been adopted as the standard tool for
epistemic uncertainty assessment in site specific PSHA for several decades, yet at national and/or regional scale the latest
generation of European seismic hazard models is only the second generation to consider epistemic uncertainties as standard
75 practice. The increase in sophistication and complexity of the logic trees between the first and second generations is
considerable. A clear example of this can be found in the national seismic hazard models of Switzerland, which in the previous
generation model contained 72 logic tree branches, with no more than two or three different models capturing epistemic
uncertainties on the seismogenic source, the magnitude frequency distribution and the GMM (Giardini et al., 2004), while the
2015 update boasts more than 1 million logic tree branches describing epistemic uncertainties on a much greater range of
80 source and ground motion parameters (Wiemer et al., 2015). A similar development can be seen in Italy where the 2004
national seismic hazard map (MPS04, Stucchi et al., 2011) was based on a logic tree of only 16 branches, while the MPS19
(Meletti et al., 2021) contains between 33 and 7 986 branches depending on whether earthquake hazard at a location is affected
by subduction and/or volcanic earthquakes in addition to the shallow crustal seismicity. With a comprehensive treatment of
epistemic uncertainty now standard in models, the breadth and definition of outputs from PSHA means that we cannot quantify
85 differences purely in terms of an increase or decrease in a map of peak ground acceleration (PGA) with a 10 % Probability of
Exceedance (PoE) in 50 years, but rather we need to consider the differences in terms of distributions of hazard from the
epistemic uncertainty analysis and do so across the range of outputs.

This paper aims to illustrate the full depth of what we mean by “comparison of PSHA models” by focusing on three recent
90 models that overlap with one another in terms of the territory covered: 1) the 2016 national seismic hazard model for Germany
prepared by Grünthal et al. (2018), 2) the PSHA model for metropolitan France by Drouet et al. (2020), and 3) the 2020
European Seismic Hazard Model (ESHM20). These models and the overlapping area in question are of particular interest to
us for several reasons. Firstly, the area of overlap for the three models corresponds to the Upper and Lower Rhine region, one
of the most populated and economically productive regions of Europe with high economic and human exposure (Crowley et
95 al., 2021), meaning that differences in the characterisation of seismic hazard and its uncertainty may result in significant
differences in terms of economic risk or risk to life. In both France and Germany, successive and/or alternative seismic hazard
models have prompted discussions among the scientific and engineering communities in both countries as to the causes of

differences between models, their interpretation, and their implications for risk and/or engineering design. In this case, however, each model adopts a complex logic tree to describe the epistemic uncertainty in seismic hazard, and as such they illustrate the challenges faced in understanding and interpreting differences between models developed according to the current state-of-practice standards in PSHA.

We begin with a general overview of the three models in section 2, highlighting both the common elements in the models and the critical differences. As each model uses a different PSHA calculation engine we have endeavoured to translate both the French and German hazard models from their original proprietary software into the open-source OpenQuake-engine, which allows us to explore the models in detail, affording us more control over the calculation and understanding the detailed modelling differences that the PSHA software can introduce. Section 3 will therefore describe the motivations of translating the models across to another software and some of the lessons learned from this process. With the models implemented into a common PSHA software we outline various quantitative techniques to explore the differences between them firstly in terms of the spatial variation in distribution of activity rates (Section 4), and then by looking at the differences in the hazard outputs for the three models in the France-Germany border region (Section 5). An overview of the extent of the France-Germany border region and the geographical features of relevance mentioned in this article can be seen in Figure 1. We will conclude with recommendations on how to approach model to model comparison based on insights gained from our experience. An additional set of notes has been compiled that expand upon certain topics mentioned in the current paper, which can be found in the electronic supplementary material.

We hope these recommendations may form a useful reference point for end users of these models when considering how and why PSHA models for a given region can differ and how to use this information to form a basis for decision making when it comes to adopting models or migrating from one to another for use in application.

2 Overview of the Recent PSHA Models for Europe, France and Germany

The first seismic hazard model considered here is the 2016 national seismic hazard model of Germany (DE2016 hereafter), which was prepared by Grünthal et al. (2018) on behalf of the Deutsches Institut für Bautechnik (DIBt) with the aim of providing an up-to-date seismic zonation for the current design code and national annex to Eurocode 8 (E DIN EN 1998-1/NA:2018-10, 2018). Among the developments included in DE2016 is a new earthquake catalogue for Germany) and the surrounding regions that updates the previous European-Mediterranean Earthquake Catalogue (Grünthal & Wahlström, 2012), seismogenic source and ground motion models logic trees, and a novel rigorous approach to characterise uncertainty in the magnitude frequency distribution. The PSHA model covers the entire national territory of Germany (plus a small band outside the national borders) with hazard curves calculated at every 0.1° longitude and latitude, resulting in seismic hazard curves at 6,226 locations across the country for PGA and spectral accelerations for periods in the range of 0.02 s and 3.0 s. Hazard curves are calculated on a reference site condition of V_{S30} 800 m/s.




Figure 1. Extent of the France-Germany border region with the main locations of interest for this study marked. Active faults shown for the Lower Rhine Graben and Upper Rhine Graben are taken from the ESHM20 seismic fault model and European Database of Seismogenic Faults (Basili et al., 2024)

135

The second seismic hazard model we are considering is that of Drouet et al. (2020), which covers all metropolitan France (FR2020 hereafter) and was developed to capitalise on the outcomes of preceding research into seismic hazard emerging from the SIGMA project (Pecker et al. 2017). New developments included an updated magnitude homogeneous earthquake catalogue (FCAT-17, Manchuel et al., 2018), recently developed ground motion models (GMM) for France (Ameri, 2014; Ameri et al., 2017; Drouet & Cotton, 2015), and refinements to the characterisation of seismic sources and magnitude frequency relations (MFRs) that built on innovative approaches adopted in the Eastern United States (EPRI, 2012). The hazard model is produced assuming a site condition of V_{S30} 800 m/s (Eurocode 8 Class A), with hazard curves calculated at 6,836 sites for PGA and spectral acceleration with periods in the range 0.01 s to 3 s.

145 The 2020 European Seismic Hazard Model (ESHM20) is the latest generation seismic hazard model for Europe, covering 36 countries from Iceland in the northwest to Turkey in the southeast. As a comprehensive and state-of-the-art multi-national scale model that builds on new data and scientific developments since ESHM13, ESHM20 provides a comprehensive set of seismic hazard curves, hazard maps and uniform hazard spectra calculated at more than 100,000 locations including all

Continental Europe, UK and Ireland, Iceland and various islands in the Mediterranean and Atlantic. ESHM20 is not only the
 150 basis for the seismic input parameter maps of S_α and S_β (the short and long period coefficients anchoring the elastic design
 spectrum) that will form an informative annex to the forthcoming Eurocode 8, it also provides the seismic hazard input into
 the 2020 European Seismic Risk Model for Europe (Crowley et al. 2021). For Eurocode 8, seismic hazard is calculated with
 respect to the reference soil condition of V_{S30} 800 m/s (assuming depth to the V_S 800 m/s layer of less than 5 m), which is
 consistent with both FR2020 and DE2016.

155

Our comparison of the models begins at the level of the model components. At the first level this comprises the *seismogenic
 source model(s)* and the *ground motion model(s)*, but we will subsequently deconstruct the former into elements relating to the
 delineation of the sources, the calculation and representation of earthquake recurrence in the logic tree. The respective logic
 trees of our three hazard models (DE2016, FR2020 and ESHM20) all implement *branch sets* to capture epistemic uncertainty
 160 on each of these components. An overview of the components of the three models and how they approach the characterisation
 of each aspect, and its epistemic uncertainty can be seen in Table 1. The complete logic trees are shown for DE2016, FR2020
 and ESHM20 in Figures 2, 3, and 4 respectively.

Table 1: Comparison of Seismic Hazard Model Components for each of the three models (DE2016, FR2020, ESHM20)

Model Component	DE2016	FR2020	ESHM20
Seismogenic Source Model	<ul style="list-style-type: none"> • Five area source zonations (two LASZ, three SASZ) • Two smoothed seismicity (zoneless) models based on smoothing using Woo (1996) approach – adaptive kernel and fixed-width kernel • Active faults included for the Lower Rhine Graben in Model C 	<ul style="list-style-type: none"> • Three small-scale area source zonations (SASZ) • One smoothed seismicity (zoneless) model with an adaptive kernel M_{MAX} and b-value based on one large-scale area source zonation (LASZ) • No active faults 	<ul style="list-style-type: none"> • One SASZ • One combined active fault and smoothed seismicity model with an adaptive kernel • Smoothed seismicity kernel optimised using log-likelihood scoring
Magnitude Frequency Relation Calibration	<ul style="list-style-type: none"> • a and b fit via MLE – depending on number of events in zone (see explanation in Section 2.2) • M_{MAX} distribution using EPRI (2012) methodology • Two MFRs: one fit to all magnitude data, the other to only larger magnitude data 	<ul style="list-style-type: none"> • a, b and $COV(a, b)$ via penalised Maximum Likelihood Estimation (MLE) (EPRI, 2012) • LASZ values used as prior distributions • M_{MAX} distribution using EPRI (2012) methodology 	<ul style="list-style-type: none"> • a and b fit using penalised MLE with LASZ used for prior distribution • M_{MAX} based on three values (originally shaped on posterior distribution from EPRI methodology): M_{MAX}^{obs}, $M_{MAX}^{obs} + 0.3$ and $M_{MAX}^{obs} + 0.6$

Magnitude Frequency Relation Logic Tree	<ul style="list-style-type: none"> Posterior distribution of M_{MAX} discretised into 5 branches (Miller & Rice, 1983) Activity rates determined from $COV(a, b)$ for each M_{MAX} branch, discretised into 4 branches according to Stromeyer & Grünthal (2015) Appendix B 40 branches in total 	<ul style="list-style-type: none"> a and b sampled from multivariate Gaussian – each a separate branch Stratified sampling (see Electronic Supplement) M_{MAX} sampled from posterior distribution – with stratified sampling independent of a and b 100 branches (1 per sample) 	<ul style="list-style-type: none"> For each M_{MAX}, $COV(a, b)$ is randomly sampled and the 16th, 50th and 84th percentile activity rates used for each magnitude Two MFRs: 1) truncated Gutenberg-Richter, 2) tapered Pareto For active fault sources, include uncertainty on b-value, slip rate and M_{MAX}
Ground Motion Model	<ul style="list-style-type: none"> 5 GMMs: Akkar et al. (2014a) [Ak14]; Bindi et al. (2014) [Bi14]; Derras et al. (2014) [De14]; Cauzzi et al. (2015) [C15]; Bindi et al. (2017) [Bi17] Weights split evenly between European models (Ak14, Bi14, De14), and “global” models (Bi17, C15) 4 branches with additional stress drop scaling 	<ul style="list-style-type: none"> Four GMMs with equal weights: Ameri (2014); Abrahamson et al. (2014); Cauzzi et al. (2015); Drouet & Cotton (2015) Represents “local” (France)[Am14, DC15] and “global” [ASK14, C15] 0.5 weight on “local”, 0.5 on “global” 	<ul style="list-style-type: none"> Regionalized scaled backbone GMM (Kotha et al., 2020; Weatherill et al. 2020) 5 branches for stress parameter scaling, and 3 for residual attenuation scaling Branch weights based on uncertainty distributions (Miller & Rice, 1983) Calibrated to local data, where available
Branches	4040	1600	315 (Western Germany) / 5985 (Eastern Germany)

165






Figure 2. Complete logic tree of seismogenic source models (left) and ground motion models (right) for DE2016 (Grünthal et al. 2018)



170

Figure 3. Complete logic tree for France (Drouet et al., 2020) containing both the seismogenic source model and ground motion model



175

Figure 4. Complete logic tree of seismogenic source models (left) and ground motion models (right) for ESHM20 (Danciu et al. 2021)

2.1 Representation of the Seismic Source

As our focus is on Germany/France, we are working in areas of primarily low-to-moderate seismicity and low tectonic deformation. Although active faults have been mapped in certain areas, most notably the Lower Rhine Graben (Vanneste et al., 2013), not all the assessment have aimed to represent these explicitly in the seismic source models, or they have only chosen to do so in some branches. The definition of “active fault” in the current context is one that is capable of generating earthquakes with $M \geq 5.5$ and with a non-zero minimum bound on the slip rate (e.g. Danciu et al., 2021). As such the

180

distribution of active faults is limited only to the fastest slipping and most well constrained structures in and around the Rhine Graben, each set of seismogenic source models comprise principally *area source zones* and/or gridded seismicity *zoneless* sources. These types of sources are known as *distributed seismicity* sources, and earthquake recurrence is modelled mostly by
185 a double-truncated Gutenberg-Richter model whose parameters a , b , $COV(a,b)$ and maximum magnitude (M_{MAX}) are constrained by fit to observed seismicity in each zone. The area zonations of the three models can be found in Electronic Supplement A: Note 1.

190 DE2016 adopts five alternative area source zonations (Models A, B, C, D and E) alongside two zoneless smoothed seismicity models. For the area sources, Grünthal et al. (2018) explicitly formulate their logic tree as a combination of large-scale area source zones (LASZ) and small-scale area source zones (SASZ). Models A and B are LASZ, which assume that the regional-scale tectonics are the main factors delineating the seismic sources and that seismicity may be uniform across large areas when viewed at longer timescales than those captured by the observed seismicity. Models C to E are SASZ, which consider local
195 scale seismicity and geological features as the primary guide to the seismogenic sources and therefore delineate smaller scale zones. The smoothed seismicity branches differ in approach from those found in both FR2020 and ESHM20, which use a smoothing kernel with an adaptive bandwidth but for which the bandwidth is calibrated on the local density of seismicity (e.g. Helmstetter & Werner, 2012). Instead, DE2016 uses an adaptive kernel with magnitude-dependent bandwidth based on the method of Woo (1996). The two branches are equally weighted and consider the two cases in which the bandwidth is capped
200 at 25 km ($H(m) \leq 25$ km) and one in which it is unconstrained ($H(m) \leq \infty$). One feature of note among the SASZ models is that Model C adds explicit active fault sources in the Lower Rhine Graben (LRG). These adopt the fault geometry proposed by Vanneste et al. (2013) but use observed seismicity with $M \geq 5.3$ across two catchments (area sources) to constrain long-term seismic activity rates for the faults. The seismic activity rates for $M \geq 5.3$ within the two catchments are distributed among the faults within the catchments according to their respective fault length, while for $M < 5.3$ the catchments are treated as area
205 source. This combined area and fault source model receives the highest weighting of the five source models.

FR2020 adopts three area source zonations, which assimilate those implemented in previous studies by different organisations: Geoter (now Fugro) (GTR), Électricité de France (EDF) and Institut de Radioprotection et de Sûreté Nucléaire (IRSN). In addition, a single zoneless source model branch is included, which is developed using smoothed seismicity with an adaptive
210 kernel bandwidth applied to the observed seismicity in France from 1960 to 2017. The smoothed seismicity produces seismic sources in the form of 10 km \times 10 km cells, with activity rate (a-value) varying cell-by-cell but b-value and M_{MAX} calculated based on the location of the cell with respect to a set of superzones, i.e. large scale area zones delineating tectonically based domains (“Grands Domaines”).

215 The seismogenic source model of ESHM20 follows a different approach to either that of FR2020 or DE2016. In terms of the
number of different source models considered, the source model branch set is simpler. It contains one branch of exclusively
area source zones and another branch for a combined smoothed seismicity and active fault model. As described in Danciu et
al. (2021) the area source model aims to unify existing area source zonations from different national PSHA models across
Europe, modifying the source geometries at the boundaries of models to ensure a seamless transition from region one to
220 another. In the France/Germany region, the unified area source model adopts DE2016's Model C as its basis in Germany and
the IRSN source model branch of FR2020 for France, alongside existing models from Belgium, Switzerland (Wiemer et al.,
2016), and the United Kingdom (Mosca et al., 2022). The active fault and smoothed seismicity model includes explicit
characterisation of faults in both the Upper and Lower Rhine Graben regions, as well as numerous faults in France adapted
from the dataset of Jomard et al. (2017). Information regarding the dataset of active faults can be found in Basili et al. (2023).
225 Smoothed seismicity is characterised using an isotropic power law kernel with adaptive bandwidth, whose parameters are
optimised using log-likelihood scoring (Nandan et al. 2022). To combine the smoothed seismicity with the active faults, a
buffer zone is defined for each fault, within which magnitudes lower than a fault-size dependent threshold are kept as smoothed
seismicity, while magnitudes larger than the threshold as associated to the fault surface. For regions away from the fault, b -
value and M_{MAX} are based on those fit to sources in a large-scale zonation, reflecting regional scale tectonics (named TECTO).
230 More information on the relevance of this will be seen in section 2.2.

In this first component we can see that the three PSHA models display both similarities and differences in their approach to
characterising epistemic uncertainty in the seismogenic source model. FR2020 and DE2016 aim to represent uncertainty in
the sources predominantly through multiple uniform area zonations, while ESHM20 divides its weights more evenly between
235 two different source typology definitions. Though only DE2016 adopts explicitly the LASZ/SASZ characterisation, this same
philosophy is present in FR2020's "Grands Domaines" model and ESHM20's TECTO model. In the FR2020 model the
distinction between large- and small-scale zone models within the three zonations considered (GTR, EDF and IRSN) is not as
clear and intentional as it had been for DE2016. Where the contrast exists, it manifests mostly in the difference between the
IRSN and EDF models (46 and 49 zones respectively) and the zonation provided by GTR (92 zones). Each of these three
240 models could be described as delineating zones accounting both for geology and seismology, albeit in proportions that are
difficult to define. Only DE2016 models the LASZ explicitly in its A and B source zonations; however, all three models will
come to adopt similar approaches toward earthquake recurrence by using their LASZ as a basis for fitting their earthquake
recurrence models, which may then inform (either by direct calibration or as a prior distribution) the MFRs for the small-scale
area sources with few events. In that sense, the philosophies toward area zonation are similar, but their implementation differs.

245 Adaptive kernel smoothed seismicity source models are present in all respective logic trees, though each PSHA model has
taken a different approach to characterisation and implementation. Both FR2020 and ESHM20 have used approaches similar
to that of, for example, Helmstetter & Werner (2012), optimising the parameters controlling the adaptive kernel's bandwidth

using log-likelihood analysis applied to a pseudo-prospective seismicity forecast. The models arrive at significantly different
 250 outcomes in terms of the spatial distribution of activity rate, however. DE2016 adopts a different approach by using magnitude-
 dependent adaptive kernels, which increase the bandwidth for larger magnitudes meaning that the rate in many low seismicity
 regions is dominated by activity from the most extreme events. This contrasts with the adaptive bandwidth methods used in
 FR2020 and ESHM20 for which the bandwidth is based on the density of seismicity. For FR2020 and DE2016 the total weight
 assigned to the smoothed seismicity branches is the same (0.25), while for ESHM20 the smoothed seismicity/active faults
 255 branch receives half the total weight.

2.2 Magnitude Frequency Relation (MFR)

For the majority of the seismic sources found within the three source model logic trees (DE2016, FR2020, ESHM20) a
 truncated form of the Gutenberg-Richter model (Gutenberg & Richter, 1944) is adopted as the magnitude frequency relation.
 The only exceptions to this are the DE2016 smoothed seismicity models (which may be considered non-parametric recurrence
 260 models) and those branches of the ESHM20 for which a tapered Pareto model is used. In all three regional seismic hazard
 models, epistemic uncertainty on the recurrence model is included, both in terms of its a - and b -value as well as M_{MAX} .

The first issue to address in comparing the derivation and representation of the magnitude frequency distribution is that of
 declustering, as all three models choose to remove foreshocks and aftershocks from their respective catalogue prior to fitting
 265 the MFR. This means that the distributions of activity rates shown subsequently refer to the rates of the mainshocks and not of
 the total seismicity. Both FR2020 and DE2016 claim to apply the declustering process described in Burkhard & Grünthal
 (2009), which is based upon earlier studies by Grünthal (1985). It is unclear whether the same code for implementation was
 adopted by both studies, so it is difficult to assess the extent to which the same seismic clusters are identified. ESHM20
 explored the impact that the choice of declustering algorithm has on the resulting activity rate models, noting a contrast in the
 270 proportions of the catalogue removed by different algorithms when applied to more seismically active or stable regions (Danciu
 et al., 2021). Despite the different outputs of declustering, however, ESHM20 too opts to adopt the same algorithm as FR2020
 and DE2016 to remove non-Poissonian events from the catalogue prior to calculation of activity rate in the final model. At
 present, the use of declustering remains in common practice across many seismic hazard models, both in Europe and
 worldwide. Whether this will remain the case for future models remains an open question, particularly when emerging practice
 275 has shifted toward calculating activity rates using the complete catalogue in recent state-of-the-art PSHA models in the United
 States (Field et al., 2024) and New Zealand (Rollins et al., 2024).

The general form of the truncated Gutenberg-Richter model to determine the rate $\nu(M)$ of earthquakes with magnitude greater
 than or equal to M is:

$$280 \quad \nu(M) = \nu_0 \int_M^{M_{MAX}} \frac{\beta e^{-\beta m}}{e^{-\beta M_{MIN}} - e^{-\beta M_{MAX}}} dm \quad (1)$$


where $\beta = b \ln(10)$ and ν_0 is the rate of earthquakes greater than or equal to minimum magnitude M_{MIN} , which can be retrieved from the a -value by $\nu_0 = \frac{e^\alpha}{\beta} (e^{-\beta M_{MIN}} - e^{-\beta M_{MAX}})$ where $\alpha = a \ln(10)$. As both France and Germany are regions that would be characterized as low-to-moderate seismicity, the number of events per individual source zone is often too small to determine a and b . All three models address this issue in a similar way by invoking the concept of large scale *superzones* that span a sufficiently large region from which to define estimates of the recurrence parameters using a maximum likelihood estimator accounting for the temporal variation in catalogue completeness (Weichert, 1980). The a and b values from these superzones then act as prior distributions for estimates of each source zone in the respective seismogenic source models within a penalized maximum likelihood estimation (MLE) approach (FR2020), or alternatively maximising a likelihood function assuming a common b value across multiple zones but with seismicity rate varying for each zone (described in Appendix B of Stromeyer & Grünthal, 2015). For specific details of how the two approaches perform the MLE and how they account for uncertainties in the catalogue and its completeness, the reader is referred to the original publications. The relevant point here is that either approach will define for each source zone an expected \hat{a} - and \hat{b} -value (or similarly $\hat{\alpha}$ and $\hat{\beta}$) and corresponding covariance matrix $\mathbf{COV}(\alpha, \beta)$ from which we retrieve the uncertainties σ_α and σ_β and their correlation $\rho_{\sigma_\alpha, \sigma_\beta}$. Where individual source zones contain very few events, or span an insufficiently wide magnitude range, the distributions of the recurrence parameters may be informed by, or be fit according to, the superzone to which the source zone is assigned.

The superzone concept is critical for each of the models, not only in defining estimates of a and b value, but also for characterization of M_{MAX} . Here both the FR2020 and DE2016 adopt the EPRI methodology to characterize the distribution M_{MAX} (Johnston et al, 1994; EPRI, 2012). This invokes a Bayesian approach in which a global prior Gaussian distribution of M_{MAX} is defined based on the observed maximum magnitudes in analogous tectonically stable regions across the Earth, which is then updated for each superzone such that $f(M_{MAX}) = 0$ for $M_{MAX} < M_{MAX}^{obs}$ in any given region and the posterior distribution combines the shape of the prior and corresponding likelihood function $\mathcal{L}(M|\beta, N_{EQ})$. \mathcal{L} is dependent both on the b value of the zone as well as the number of earthquakes observed during the corresponding period. The resulting posterior distribution is either sampled (in the case of FR2020) or approximated by a discrete set of weighted values using Miller & Rice (1983) (in the case of DE2016). ESHM20 updates an earlier work of Meletti et al. (2013) to define the M_{MAX} distribution, which yields the three branches M_{MAX}^{obs} , $M_{MAX}^{obs} + 0.3$, $M_{MAX}^{obs} + 0.6$ assigned weights of 0.5, 0.4 and 0.1 respectively. Though not explicitly applying the EPRI methodology, the weights assigned to each of the three branches reflect an interpretation of a posterior distribution for $f(M_{MAX})$ that is broadly consistent with those of the EPRI approach.

As the superzones are acting as larger-scale constraints on the parameters of the MFR (a , b and M_{MAX}) for regions of tectonic similarity, it is inevitable that their definition is based almost exclusively on tectonic and geological criteria rather than local scale seismicity. This is applied consistently across all three models: the “Grands Domaines” for FR2020, LASZ Model A for DE2016, and the TECTO model for ESHM20. The three superzonations are compared in Figure 5. In the regions where these

models overlap there is a considerable degree of divergence in the tectonic zonations, with different models providing strongly
315 contrasting interpretations of the extent of the larger scale tectonic structures that influence the spatial distribution of seismicity.
ESHM20 and DE2016 are perhaps more consistent with one another in defining three zones of similar extent that delineate the
Paris Basin, the Upper Rhine Graben and the South German Block. In the lower Rhine Graben and continuing through Belgium
and the Netherlands and into the North Sea, however, all three models diverge. Though far from the only factor that will
eventually contribute toward the differences between the three models in terms of seismic hazard, this divergence in the
320 tectonic interpretations in the superzone models will inevitably propagate into the recurrence models, particularly in regions
of low seismicity where the superzones act to fix parameters of, or provide strong priors for, the resulting MFRs.

Though we have so far focused our attention on the definition of the superzones and their influence in constraining the MFRs
themselves, equally important in terms of the impact on PSHA is how the resulting distribution of \hat{a} , \hat{b} and $COV(a, b)$ (or
325 $COV(\alpha, \beta)$) are evaluated within the logic tree. Here, there is yet again significant divergence between the models, with each
model constructing the logic tree for MFR epistemic uncertainty using an entirely different approach.



330 **Figure 5: Large-scale area source zonations (LASZ) assumed for DE2016 (top left), FR2020 (top right) and the two LASZ zonations for ESHM20 based on regional tectonics (bottom left) and maximum magnitude (bottom right). Colours for DE2016 indicate the groupings of LASZ (from Model A) sharing a common b-value.**

DE2016 follows the methodology set out by Stromeyer & Grünthal (2015), who describe the uncertainty in cumulative activity rate ν at each magnitude m , from the covariance matrix such that:

$$\sigma^2(m) = \begin{pmatrix} 1 \\ -m \end{pmatrix}^T \mathbf{COV}(a, b) \begin{pmatrix} 1 \\ -m \end{pmatrix} = \sigma_a^2 - 2m\sigma_a\sigma_b + m^2\sigma_b^2 \quad (2)$$

335 The cumulative rate of events greater than or equal to magnitude $\nu_c(m)$ then becomes:

$$\nu_{c,i}(m) = \int_M^{M_{MAX}} 10^{\bar{a}-\bar{b}m+\sigma(m)z_i} dm \quad (3)$$

where z_i is the number of standard deviations of a standard normal distribution. The incremental activity rate in any given bin of width dm then simply becomes $10^{\bar{a}-\bar{b}m+\sigma(m)z_i}$. The uncertainty on each magnitude is now represented by a marginal distribution of $\mathcal{N}(0, \sigma(m))$. This epistemic uncertainty can thus be mapped into a discrete set of $i = 1, 2, \dots, k$ branches such that z_i and its corresponding weight, w_i , are discrete approximations to the standard normal distribution according to the Gaussian Quadrature approach of Miller & Rice (1983). As equation 1 is dependent on M_{MAX} , the posterior distribution $f(M_{MAX})$ returned by the EPRI approach for each zone is first approximated into five discrete branches using the same Gaussian Quadrature method. Each of the five M_{MAX} values are then input into (3), which is then discretised into four branches to approximate $\mathcal{N}(0, \sigma(m))$. The epistemic uncertainty in MFR for each area source is therefore represented by 20 logic tree
345 branches (shown in Figure 2).

ESHM20 starts from a similar point as DE2016, as it defines \hat{a} , \hat{b} and $\mathbf{COV}(a, b)$ according to Stromeyer & Grünthal (2015) but then approximates the distribution differently. Monte Carlo sampling is used to generate 1 million realisations of a and b from the multivariate normal distribution, and from these samples the pairs corresponding to the 16th, 50th and 84th percentile values are taken to define the lower, middle and upper branches respectively, with weights of 0.2, 0.6 and 0.2 respectively. M_{MAX} is defined independently of a and b using the three branches described previously. Though the ESHM20 evaluates the multivariate distribution of a , b and $\mathbf{C}(a, b)$ in a slightly less formally correct manner compared to that of DE2016, one would still expect the distribution of resulting hazard curves to be similar. ESHM20 diverges further from both the DE2016 and FR2020 approaches, however, by introducing as an alternative set of MFR branches a tapered Gutenberg-Richter recurrence
355 model (Kagan, 2002):

$$\nu(M_0) = \left(\frac{M_t}{M_0}\right)^\beta \exp\left(\frac{M_t - M_0}{M_{cm}}\right) \quad \text{for } M_t \leq M_0 < \infty \quad (4)$$

where M_0 is the seismic moment of an event with magnitude m , M_t the threshold moment, $\beta = b \ln(10)$ and M_{cm} the corner moment. Unlike the truncated Gutenberg-Richter model, the tapered Gutenberg-Richter distribution is theoretically unbounded at large moments; however, the exponential decay in the functional form above M_{cm} effectively tapers the rate of events to
360 triviality for magnitudes larger than the corresponding M_{cm} , so truncation can be safely applied within 0.2 – 0.3 magnitude units above M_{cm} with only minimal impact on the hazard calculation. For the set of branches corresponding to this distribution the rate and b-value are fixed according to the \hat{a} and \hat{b} values defined previously, while the three M_{MAX} branches are applied as epistemic uncertainty on M_{cm} . In total, for area sources the source model logic tree contains 12 branches to represent the

uncertainty in the MFR: for the truncated Gutenberg-Richter model three branches of a and b and another three of M_{MAX} , and
365 for the tapered Gutenberg-Richter model only three branches for M_{cm} .


For both DE2016 and ESHM20 it is also necessary to define activity rates for both the smoothed seismicity sources and the active fault sources. Because of its implicitly non-parametric approach to defining activity rates, no MFR uncertainty is considered for the zoneless smoothed seismicity model of DE2016. Similarly, for ESHM20 the smoothed seismicity model is
370 optimized through an iterative forecast testing approach, which yields a single preferred smoothed seismicity model without epistemic uncertainty on the MFR. Both models do define epistemic uncertainty on the activity rates for the fault-based models. In the case of DE2016 the maximum magnitudes on the composite fault sources are characterized according to their fault dimension using a normal distribution of $\mathcal{N}(M_{MAX}, 0.3)$ (Vanneste et al. 2013). These distributions are mapped into 5 branches using the Miller and Rice (1983) methodology. On-fault recurrence is modelled using a truncated Gutenberg-Richter relation,
375 but as the authors could not constrain the proportion of aseismic slip they opted to assign the seismicity for $M_W \geq 5.3$ to the fault sources and the rest to their respective catchment zone (Model C, zones C15 and C22), with the proportion of seismicity rate for each fault assigned according to the relative length of the fault. This results in a total of 20 MFR branches on the fault sources, comprising five M_{MAX} branches and the four branches of recurrence uncertainty from the catchment zones. In ESHM20 the recurrence models for the active fault sources also use a truncated Gutenberg-Richter model, albeit moment
380 balanced from the geological coseismic slip rate. As the slip rates are themselves uncertain, three branches for alternative coseismic slip rates are considered along with three branches for M_{MAX} .

FR2020 takes a different approach to characterizing epistemic uncertainty than either ESHM20 or DE2016. For each area source and for each larger-scale superzone the seismicity is represented by a truncated Gutenberg-Richter model represented
385 by \hat{a} , \hat{b} and $C(a, b)$, in addition to the posterior density function $f(M_{MAX})$ that is defined for each superzone. Rather than discretise the distributions of $v(m)$ (as DE2016) or of a , b and M_{MAX} into a small set of branches according to Miller and Rice, (1983), Drouet et al. (2020) instead use Monte Carlo sampling, drawing 100 samples from each distribution with each sample then represented as an equally weighted MFR branch (weight = 1 / 100) in the logic tree. Samples are drawn independently
from $f(M_{MAX})$ and from the multivariate normal distribution representing the a and b values $MVN\left(\begin{smallmatrix} \hat{a} \\ \hat{b} \end{smallmatrix}, C(a, b)\right)$. This results
390 in a total of 400 source model branches from four source models (GTR, EDF, IRSN and Zoneless), each with 100 MFR samples. Implementation of the model revealed that the original authors had adopted a stratified sampling strategy for a and b , which is illustrated in more detail in the Electronic Supplement Appendix A: Note 2.

2.3 Upper Rhine Graben Source Example: Similar Approaches, Different Outcomes

395

To illustrate how the different approaches to characterization and implementation of the MFRs in a logic tree can yield quite different distributions of activity rate for a given source, even where many inputs to the source model are similar, we consider the case of the Upper Rhine Graben (URG). Among the different source zonations within the different logic trees there are some differences to the exact shape of the source(s) in the Upper Rhine, though most models describe a source that follows the main outline of the graben starting just north of the Basel earthquake sequence in the south and terminating close to Karlsruhe in the northwest. We select the zone DEAS107 from the ESHM20 unified area source model branch, the FRS zone from the FR2020 GTR source zonation and the D051 zone from the DE2016 model to look at in detail as they depict similar geometries with respect to the spatial seismicity distribution. These sources are shown with seismicity from their respective earthquake catalogues in the top row of Figure 6. Here we observe a first point of divergence, as the catalogues show remarkably different patterns of seismicity for the same zone. This is somewhat surprising as the ESHM20 adopts the same F-CAT earthquake catalogue as FR2020 within the French territory and the same DE2016 catalogue within the German territory for the post-1900 seismicity. Differences emerge in the pre-1900 earthquake catalogues as ESHM20 adopts the European Pre-Instrumental Earthquake Catalogue (EPICA) (Rovida et al., 2022), which is compiled independently to the other catalogues.



410 **Figure 6: Example comparison of fit and representation of earthquake recurrence for the Upper Rhine Graben (URG) for the DE2016 (left column), FR2020 (middle column) and ESHM20 (right column). Example geometry of the selected URG seismic source in different models and the respective earthquake catalogues with symbols scaled according to magnitude (top row), distribution**
 415 **magnitude with time for the respective zones and the corresponding temporal completeness magnitude assumed by the model (middle row), and distribution of magnitude frequency relations for the zone colour scaled according to weight. All catalogues share the same symbol size scaling with magnitude (top row) and all magnitude frequency distributions share the same colour scale (bottom row).**

The next point of divergence can be seen in the estimate of completeness magnitude and its variation in time, which can be seen in the middle row of Figure 6 and given in Table 2. FR2020 and DE2016 estimate completeness using the method of

420 Hakimhashemi & Grünthal (2012), albeit adopting different spatial zones to apply the method, while ESHM20 estimates completeness using an inversion method based on forecast testing (Nandan et al. 2022). Drouet et al. (2020) provide the uncertainty range for the completeness estimates, and although the preferred values are different for many magnitude bins, the earliest years of completeness for magnitudes in the range $4.0 \leq M_w \leq 6.5$ for the DE2016 and ESHM20 models are consistent with the uncertainty range shown in Table 2 for FR2020. Taking the best estimates, however, and contrasting these against the catalogues (shown in the middle row of Figure 6), it is obvious that both the catalogues and completeness estimates are dissimilar.

The bottom row of Figure 6 shows the distributions of activity rate with magnitude for all the MFR branches assumed by the respective logic trees. Although each model is using some form of maximum likelihood estimate (Johnson et al., 1994; 430 Stromeyer & Grünthal, 2015) to determine the Gutenberg-Richter parameters for the zone, the results are significantly different. ESHM20 has an expected a and b value of 1.9565 and 0.7334 respectively, which are mapped into three branches of a, b pairs: (1.886, 0.685), (1.9565, 0.7443), (2.0278, 0.803). By contrast FR2020 yields a and b values of 2.3711 ± 0.182 and 0.8696 ± 0.0918 respectively, with $\rho_{ab} = 0.8991$, and while DE2016 is dependent on M_{MAX} the a and b values range from 3.89 to 2.86 and from 1.08 to 0.95 respectively. Not only do the MFR parameters themselves vary then significantly, but Figure 435 6 illustrates how the different mappings into logic tree branches yield significantly different activity rate distributions. ESHM20 places more weight on the middle branches, and in this case the MFR logic tree mixes both the truncated Gutenberg-Richter and the tapered Pareto distributions. FR2020 clearly shows the largest spread of MFRs, which arises in part from the independence of a and b from M_{MAX} and in part because of the large number of evenly weighted sample values. DE2016 is something of a middle point, with a narrower range of values and notably higher weights on a specific sub-set of branches.

440

Table 2: Variation in completeness window for each magnitude bin assumed for the selected URG source zone

Magnitude Bin	DE2016	FR2020	ESHM20
2.5 – 3.0	1973/74	1970 [1965 – 1975]	-
3.0 – 3.5	1870	1950 [1940 – 1960]	-
3.5 – 4.0	1870	1850 [1800 – 1875]	1857
4.0 – 4.5	1870	1850 [1800 – 1875]	1822
4.5 – 5.0	1800	1700 [1650 – 1800]	1822
5.0 – 5.5	1650	1600 [1500 – 1700]	1479
5.5 – 6.0	1450	1500 [1400 – 1600]	1479
6.0 – 6.5	1250	1500 [1400 – 1600]	1479
≥ 6.5	1250	1500 [1400 – 1600]	1479

The comparison here is not an exhaustive description of all the reasons for what we will eventually see as the differences in seismic hazard between the three models, but it is illustrative of how they can diverge significantly in the critical information for PSHA (namely activity rate per magnitude bin) despite adopting theoretically similar approaches. Particularly insightful is the contrast in the way in which the distribution of a and b is mapped into the epistemic uncertainty, which would potentially 445

suggest that even if the three models produced a similar fit in their recurrence models, they could still diverge significantly in the resulting activity rate distributions inside the PSHA calculation. We will discuss in the conclusions chapter the implications here for future harmonization of the seismic hazard, but a key point to take from this brief analysis is that each step of the process from the basic earthquake data through to the distribution of activities rates requires both transparency and scrutiny. Though the models considered here are arguably better documented than many, there are still many steps in the processes that are not completely described, or if they are described it may be difficult to perceive how this can influence the hazard. These factors will contribute to the differences in hazard model components and hazard model outputs shown in sections 4 and 5.

2.4 Ground Motion Models

For the ground motion model (GMM) logic tree it is not necessarily the technical process itself, and the decisions made therein, that differs significantly between the three PSHA models, but rather the general philosophy of how to characterize epistemic uncertainty. Specifically, between the three models we see an example of a multi-model (or “weights-on-models”) GMM logic tree (FR2020), a hybrid multi-model logic tree with backbone scaling factors (DE2016), and a fully regionalized scaled backbone logic tree (ESHM20). All three models explicitly invoke the same objective of “capturing epistemic uncertainty in terms of the centre, body and range of the technically-defensible interpretations of available data” (U. S. Nuclear Regulatory Commission, 2012). To contrast distributions of GMMs from different PSHA models we have created a set of trellis plots, in which the GMM selections from two different models are plotted side-by-side for the same set of predictor variables. The range of GMM median or standard deviation values for the contrasting model is described by a shaded region beneath the GMMs for the model in question.

The GMM logic tree for DE2016 is initially based on a multi-model approach, with five models identified as suitable for application to Germany (Akkar et al., 2014a; Bindi et al., 2014; Derras et al., 2014; Cauzzi et al., 2015; Bindi et al., 2017), but adds to each of these models a set of scaling factors to the median ground motions (0.7, 1.0, 1.25 and 1.5) to account for epistemic uncertainty in regional stress drop. Of the five models selected, Akkar et al. (2014a), Bindi et al. (2014) and Derras et al. (2014) are fit to data from the pan-European RESORCE dataset, Cauzzi et al. (2015) fit using predominantly data from Japan (supplemented by some records from other regions of the globe), and Bindi et al. (2017). The latter is fit using records from the NGA West 2 dataset but using a simpler functional form than the NGA West 2 GMMs. This makes Bindi et al. (2017) better suited for the level of parameterization commonly found in moderate to low seismicity regions where seismogenic sources are predominantly based on distributed seismicity rather than directly on active faults. The DE2016 GMM logic tree combines both a standard multi-model approach with elements of a scaled backbone approach to capture some of the uncertainty in the underlying seismological properties of the target region; hence, we refer to it as a hybrid multi-model and backbone GMM logic tree.

Grünthal et al. (2018) outline several key factors that influence their decision-making process: i) varying strengths of the
480 different databases of ground motion (e.g., tectonic similarity for Europe [RESORCE], a wealth of short distance records
[NGA West 2], detailed site parameterization [Japan – Cauzzi et al., 2014]), ii) variation in functional form and how this
influences ground motion prediction for small-to-moderate magnitude events, and iii) the observation of several earthquakes
with higher than average stress drop in stable regions of France, Germany and the UK. The multi-model approach and the
choice of models selected largely address the first two of these issues. Three different datasets (RESORCE, NGA West 2 and
485 Japan) are represented, which also implicitly incorporate GMM source-region to source-region variability (i.e., Europe,
Western US, Japan). The highest weight [0.5] assigned to the three GMMs derived from RESORCE and then split evenly
between the three models therein, while the Cauzzi et al. (2015) and Bindi et al. (2017) models receive equal weights of 0.25.
Functional form variation and parameterization is accounted for by mixing classical random effects models (each with slight
differences in functional form) with purely data-driven neural network models (Derras et al. 2014).

490

The GMM logic tree adopted for FR2020 is the simplest of the three, using four ground motion models each assigned an equal
weight of 0.25 (Ameri, 2014¹; Abrahamson et al., 2014; Cauzzi et al., 2015 [with variable reference V_{S30}]; Drouet and Cotton,
2015 [using rupture distance and with 10 MPa stress drop for large magnitude events]). Two of these models (Ameri, 2014;
Drouet and Cotton, 2015) are based exclusively on French seismological data, while Abrahamson et al. (2014) is fit to records
495 from the NGA West 2 dataset (global in scope but with most records originating from California), and Cauzzi et al. (2015) is
fit predominantly to Japanese strong motion data. None of the selected GMMs is based on the pan-European RESORCE ground
motion dataset (Akkar et al., 2014b), although Drouet et al. (2020) indicate that several of the GMMs that were derived using
pan-European ground motion data were considered in the selection process. The analysis to support their model selection is
based on the exploration of the model space of the GMMs using Sammon’s maps (Scherbaum et al., 2010), which reveal that
500 the four models are relatively well separated within the model space described by all pre-selected GMMs and by a set of
reference models derived from the mean of the considered GMMs scaled up and down (representing stress drop variation) and
with faster or slower attenuation. In this sense, the multi-model logic tree accounts for epistemic uncertainty in both the model
functional form as well as the geophysical properties of the target region, the latter being represented by the different GMM
source regions implicit within the selected models: France (Ameri, 2014; Drouet and Cotton, 2015), Western United states
505 (Abrahamson et al. 2014) and Japan (Cauzzi et al. 2015).

In practice, the DE2016 and FR2020 approaches yield similar outcomes, with the same three source regions represented:
“local/Europe”, “Japan” and Western United States, and with the “local” region receiving a weight of 0.5 and the other two a
weight of 0.25 each. The two sets of GMMs for the DE2016 and FR2020 models are compared in terms of their range of


¹ The original paper of Drouet et al. (2020) indicated that Ameri et al. (2017) is adopted here; however, discussions with the
authors revealed it was in fact the earlier Ameri (2014) model used.

510 median ground motions (Figure 7) and their aleatory uncertainty σ_T (Figure 8). For these comparisons, and those in the subsequent Figures 9 to 12, the three scenario magnitudes (M_W 4.0, 5.5 and 6.5) are chosen because they represent the minimum magnitude considered by the models (M_W 4.0), the typical controlling magnitude of the hazard for return periods of engineering interest (M_W 5.5) and a feasible but low probability extreme scenario (M_W 6.5) that is close to the M_{MAX} in stable zones but lower than the M_{MAX} of the active fault sources found in the Rhine Graben and Alpine front.

515

The uncertainty in stress drop is the motivation behind adding the additional scaling factors, which capture both the possibility that stress drop may be lower in Germany than in the respective source regions of the models (0.75) as well as the possibility that it is higher (1.25 and 1.5). Weights of 0.36 are assigned to each of the 1.0 and 1.25 scaling factors, while the outer branches (for lower than average or much higher than average stress drop) are assigned smaller weights of 0.14 each. This pushes the

520 balance of the weight toward higher stress drop in Germany.



525 **Figure 7: Trellis plots comparing the median ground motions of the GMM selections of the FR2020 and DE2016 logic trees. (left) Attenuation with distance for S_a (0.15 s) for M_W 4.0, 5.25 and 6.0, and (right) scaling with period at a site R_{JB} 30 km from the source for M_W 4.0, 5.25 and 6.0. The range of values from the compared models is shown by the grey shaded region in each plot, while the dashed black lines show the sum of the median ground motions from each model (μ_i) weighted by their logic tree weights (w_i): $\sum_i(\mu_i \cdot w_i)$.**

Compared to the strategies adopted for FR2020 and DE2016, the ESHM20 model has taken a different approach to defining a GMM logic tree that captures the centre, body and range of the technically defensible interpretations of available data, and it does so by abandoning entirely the multi-model concept in favour of a regionalized scaled backbone logic tree. The full explanation of the logic tree, including both its motivation and calibration, is given in Weatherill et al. (2020). This change in

530

approach is motivated in large part by the development of the Engineering Strong Motion (ESM) database and flatfile (Lanzano et al., 2019), which increases by nearly an order of magnitude the number of ground motion records available in Europe, particularly those of small-to-moderate magnitude earthquakes including many more from France and Switzerland than in RESORCE. The backbone GMM is fit to this dataset (Kotha et al., 2020), but with such a large volume of data additional random effects are included to capture region-to-region variability in the stress parameter scaling of the model ($\delta L2L1$) and in the attenuation (δc_3 – where c_3 is the coefficient of the anelastic attenuation term of the model). These two random effects are both normally distributed variables with means of 0 and standard deviations of τ_{L2L1} and τ_{c_3} respectively, and individually they quantify the total regional variability in stress parameter and residual attenuation within Europe. For regions with little or no ground motion data, the distributions of $\mathcal{N}(0, \tau_{L2L1})$ and $\mathcal{N}(0, \tau_{c_3})$ are mapped into sets of discrete branches using the method of Miller and Rice (1983), making the model a scaled backbone model. Where data are available the distributions can be adjusted to reflect the local stress parameter or attenuation properties implied by the data, thus the model is also regionalisable.




Figure 8: As Figure 7, comparing the aleatory uncertainty distributions of the FR2020 and DE2016 GMM logic trees. The dashed black lines refer to the sum of the aleatory variabilities of each GMM (σ_i) weighted by their logic tree weight (w_i): $\sum_i(\sigma_i \cdot w_i)$

Even in the larger ESM flatfile there are few events from Germany, and those that are present are almost all located in the Upper Rhine Graben and Alpine Foreland. In France the majority of earthquake and records come from the Alpine and Pyrenees regions. Observations were available for the regions where δc_3 could be calibrated, so regions of similar δc_3 were grouped together to differentiate between regions of slower, average, or faster attenuation. These differences are reflected in the model, where the attenuation parameters of the backbone GMM for sites in these regions are adjusted to incorporate these

555 differences. Altogether, the regionalized scaled backbone logic tree maps the unadjusted (un-regionalised) $\delta L2L_1$ term into 5 branches and the regionalized δc_3 term into three branches, resulting in 15 GMM branches altogether. The median accelerations predicted by ESHM20 GMMs are compared against those of FR2020 and DE2016 in Figure 9 and 10 respectively, and the aleatory uncertainties in Figures 11 and 12.




Figure 9. As Figure 7, comparing the median ground motions of the ESHM20 and FR2020 GMM logic trees

560






Figure 10: As Figure 7, comparing the median ground motions ESHM20 and DE2016 GMM logic trees

565 Among the most important trends to be seen in the plots in Figures 7 to 12 are the general tendencies toward higher median
ground motions at short distances and small magnitudes for the GMM logic trees of the DE2016 and ESHM20 model compared
to that of FR2020. For larger magnitudes the trends reverse, and it is the ESHM20 GMM logic tree that provides a lower
central tendency in the ground motions. At intermediate magnitudes and distances, where we are best constrained by data,
ESHM20's GMM logic tree tends toward lower short period motions at most magnitudes and distances, while longer period
570 motions are comparable. We note, however, the very high and very low stress parameter branches of the ESHM20 GMM logic
tree that envelope the range of values in the plots have very little weight associated to them, and it is the three more central
branches that have the greatest influence on the mean hazard.



575 **Figure 11.** As Figure 8, comparing the aleatory uncertainty distributions of the FR2020 and ESHM2020 GMM logic trees

For the DE2016 and FR2020 comparisons, the DE2016 GMMs tend to skew higher. This reflects the influence of the stress drop scaling, where more weight is put on toward the scaling factors greater than or equal to 1.0. Without these adjustments
 580 the GMM selections would likely have returned a similar centre and range of ground motions, except at near source distances ($R_{JB} < 10$ km) where the Derras et al. (2014) GMM with the point-source to finite rupture distance correction seems to extrapolate toward much higher motion than the other models.



585 **Figure 12: As Figure 8, comparing the aleatory uncertainty distributions of the ESHM20 and DE2016 GMM logic trees**

For the aleatory variability the ESHM20 is based on a scaled backbone model with no branches for epistemic uncertainty in this term; thus the range of σ_T collapses to a simple line in Figures 11 and 12. What is evident, however, is the heteroskedastic variability that is present in the ESHM20 model and in the Abrahamson et al. (2014) model. The results in lower σ_T at high magnitudes, which in turn lowers the aleatory uncertainty in the ESHM20 model compared to the other GMM logic trees. We also observed that the ESHM20 model shows a lower aleatory variability in general compared to the spread found in other GMM logic trees. Two factors play a role here, the first is that the Kotha et al. (2020) model was derived using robust linear mixed effects regression that down-weights outlier values, and the second is that the ESHM20 GMM implementation adopts different site-to-site variability (ϕ_{S2S}) for the cases when the site condition (V_{S30}) is measured and when it is inferred from a proxy (Danciu et al., 2021; Crowley et al. 2021). For the measured V_{S30} case, which is the one being considered in the ESHM20 application, ϕ_{S2S} is reduced compared to most other GMMs shown here because it is fit to the site-to-site variability of the subset of stations with measured V_{S30} , while most other models have calibrated this variability based on records from stations that mix measured and inferred V_{S30} .

3. Harmonising Model Implementations into a Common Software Format

600 We have so far looked at some of the fundamental differences in the seismic hazard inputs between the three national seismic hazard models, and though there are different approaches and philosophies underpinning each there are also many key

similarities, most notably in the types of sources being adopted (i.e., uniform area zones, smoothed seismicity and, in the case of ESHM20 and DE2016, active fault surfaces). An important difference, however, is not just in the construction of the inputs but how they are processed in the PSHA calculation. Here the PSHA calculation software plays an important role. Each of the three models was implemented in a different PSHA software: FR2020 used a proprietary software developed by Fugro that is based on a customized version of the FRISK88 (McGuire, 1976); DE2016 also used a proprietary software that is their own customization of FRISK88 for the area and fault sources, which was combined with their own software code to implement smoothed seismicity PSHA; ESHM20 was developed using OpenQuake (Pagani et al., 2014).

Our first major objective in this work was to harmonise all three models into a common format around the OpenQuake-engine seismic hazard and risk software. This harmonization serves multiple purposes. The first is to migrate the models from the proprietary software in which they were originally implemented and to support them using an open-source software so that they can be reproduced by other parties. The second purpose is the main objective of this paper, which is to define a common representation of hazard inputs and outputs that will allow for the quantitative comparisons shown in sections 4 and 5. Finally, OpenQuake includes both a seismic hazard and a seismic risk calculator, which in combination with the exposure and vulnerability models provided as part of ESRM20 allows us to explore implications of the different models in terms of seismic risk. This latter objective will, however, be the subject of a future work and is beyond the scope of the current paper.

3.1 PSHA Software Comparisons: Rationale and Applications

Although PSHA models have developed in sophistication over the decades, the fundamental framework for PSHA is largely unchanged since its establishment by Cornell (1968) and McGuire (1976). Arguably the most notable evolutions in practice emerge with the “grand inversion” methodology for modelling fault systems (e.g., Field et al., 2015; 2024), and more widespread usage of Monte Carlo techniques (e.g., Ebel & Kafka, 1999; Musson, 2000; Weatherill & Burton, 2010; Assatourians & Atkinson, 2014). These later adaptations do not alter this core probabilistic framework but rather they evaluate it in a manner that may be flexible or better suited to incorporate new modelling developments or provide input into a broader range of applications. Yet despite the robustness of the conceptual probabilistic seismic hazard integral, different PSHA software can be remarkably divergent in the way the input source and ground motion models are processed and translated into the PSHA framework.

Differences between PSHA software can be broadly grouped into three categories:

Irreconcilable discrepancies owing to fundamental differences in software operation. These can include characterization of the seismic source and/or magnitude frequency relation and their discretisations within the hazard integral, treatment of rupture finiteness in distributed seismicity sources and its scaling with earthquake magnitude, calculation of fault rupture to site distances, and evaluation and/or approximation of the statistical density functions to retrieve probabilities of exceedance of

635 ground motion. Such differences can be identified but not necessarily replicated from one software to another without significant changes to the code.

Implementation discrepancies, which mainly refer to bugs or errors in the source codes themselves, potential instability due to rounding errors, or different interpretations of ambiguously described features or parameters in implemented models such as
640 GMMs. These can be identified and resolved by following quality assurance procedures, and greatly assisted by model authors providing open-source implementations of their models.

Free modelling parameters and configuration choices that allow users to control the operation of the software but that are seldom fully documented (particularly in scientific papers). These may resemble more the irreconcilable discrepancies if one
645 software implements a part of the hazard calculation in a flexible manner that affords the user control of the operation, while another software may hard-code this same process and afford the user no control.

The way that different software packages characterise common elements of a PSHA calculation, and the corresponding impacts on the resulting hazard curves, have been evaluated as part of the PEER Probabilistic Seismic Hazard Code Verifications
650 (PEER Tests hereafter) (Thomas et al., 2010; Hale et al., 2018). These are elemental PSHA calculations usually comprising a single source, ground motion model and a limited number of target sites with fixed properties, which are designed specifically to assess how the different software approach a particular modelling issue. The results are compared against either “exact” solutions calculated by hand, where possible, or against the range of curves determined from the participating PSHA codes when the problem cannot be evaluated by hand.

655
The PEER Tests have been particularly insightful in identifying how and why PSHA codes diverge, which is especially important given that many codes participated to them (both proprietary and open source) that are widely used in commercial application. As they are elemental in nature, however, they cannot necessarily predict the extent to which different codes will yield different outputs for seismic hazard at a given location, where many modelling differences come into play. The
660 importance of this type of application and the benefits of multi-software implementations of a seismic hazard model as part of a quality assurance (QA) process for the design of critical facilities have been emphasized by Bommer et al. (2015) and Tromans et al. (2019), among others, and is becoming more widely used in practice. The QA application is only one context, however, and arguably a favourable one in which multiple parties are involved and resources are often made available to document and debate the implementations, and to resolve discrepancies as and when they emerge.

665
A more relevant for the case at hand is migration of an existing or established hazard model from one software to another. Here the challenges are different, as the existing model forms the reference, and the new software may need to replicate the behaviour of the previous one in order to ensure consistency in the outputs. In some cases, if the new software user is different

670 from, or does not have support of, the original software developer and the source code of the software is closed, then there can often be critical elements of the PSHA calculation process that are hidden to the user. In this instance complete agreement between the existing and migrated models may not be possible due primarily to the irreconcilable differences between software highlighted above. Instead, a target level of “acceptable agreement” between previous and new implementation needs to be defined (e.g., Abbot et al., 2020; Allen et al., 2020).

675 In the migration processes described in this section we set a target level of agreement in terms of the OpenQuake calculated seismic hazard curves at given target sites agreeing with those produced from the original PSHA software code to within ± 10 % *annual probability of exceedance (APOE)* for the corresponding range of ground motion *intensity measure levels (IMLs)* for APOEs greater than 10^{-4} (corresponding to a return period of approximately 10,000 years). Though in many cases agreement can be achieved for lower APOEs, the irreconcilable differences due to issues of discretization, rounding, numerical
680 instability etc. may begin to influence the extreme tails of the distributions that assume greater importance at these longer return periods. An APOE of 10^{-4} is sufficient to span the range of return periods considered for conventional design building codes, which reflect the applications for which these specific hazard models are intended. As both the FR2020 and DE2016 models have logic trees we undertake comparisons in two steps, the first comparing specific branches of the logic tree to ensure broad agreement over source and ground motion model combination, the second comparing the curves in terms of the respect
685 means and quantiles. We note that from the seismic hazard curves similar agreement targets could be set in terms of the IMLs for a fixed range of APOEs, which may be slightly more intuitive. Both options were explored, and no cases were found in which the agreement in curves for the IMLs failed to reach the set ± 10 % target when the agreement in terms of APoEs did. As all three software considered return seismic hazard curves in terms of PoE for a user-input set of IMLs, and statistics of means and quantiles were calculated based on PoE, we opted to use APoE as the variable for the comparisons to avoid
690 introducing potential discrepancies from different interpolation approaches. Summaries of the migration issues for both FR2020 and DE2016 can be count in Electronic Appendix A Notes 3, 4 and 5, with further details of the issues encountered in the migration of FR2020 to OpenQuake can be found in Weatherill et al. (2022). Illustrative comparison plots of the two software implementations both for national seismic hazard maps and seismic hazard curves at selected locations can be seen in Electronic Appendix B.

695

3.2 Defining Means and Quantiles

In OpenQuake the mean is calculated as the weighted *arithmetic* mean of the probabilities of exceedance (PoE) for each given intensity measure level (IML). Similarly, quantiles are determined based on the probabilities of exceedance for each intensity measure level by sorting the PoEs from lowest to highest at each IML and interpolating the corresponding cumulative density
700 function to the desired quantile values (typically 0.05, 0.16, 0.5 [median], 0.84 and 0.95). As OpenQuake adopts the earthquake rupture forecast (ERF) formulation for the PSHA calculation (Field et al., 2003), all hazard statistics are extracted from the probabilities of exceedance rather than the rates of exceedance. This formulation of the mean and quantiles represents one of

several different ways of retrieving this term. Other PSHA software may apply the statistics to the IMLs for a given PoE and/or work with the geometric rather than arithmetic means and each approach yields different results. From communication with the model developers, we verified that FR2020 defines the mean hazard as the arithmetic mean of the probabilities of exceedance, while for DE2016 the means are based on the arithmetic mean of the annual rates of exceedance. For consistency with OpenQuake, in the comparisons of means and quantiles show we have retrieved these values from the complete suite of hazard curves and processed them identically, rather than taking the mean or quantiles from the software itself.

710 3.3 Source-to-Source Correlation in MFR Epistemic Uncertainties

We have seen in section 2 how the three different models attempt to translate the uncertainty on a , b and $COV(a, b)$ into the logic tree, and how this yields quite different distributions of activity rates. An issue that is not discussed is the issue of source-to-source correlation in the MFRs. To summarise, consider an idealized model with just four area sources, each with their own truncated Gutenberg-Richter MFR, and a corresponding logic tree with three branches for uncertainty on a and b (e.g., $-\Delta \cdot (a, b)$, $(\overline{a, b})$, $+\Delta \cdot (a, b)$) and three for uncertainty on M_{MAX} (e.g., M_{MAX}^{LOW} , $\overline{M_{MAX}}$ + M_{MAX}^{HIGH}). If the MFRs are fit independently for each zone then the resulting logic tree would need to permute every combination of the MFR parameters for each source, which would in this simple case results in $9^4 = 6561$ logic tree end branches, i.e., $(N_{BRANCHES})^{N_{SRCS}}$. Applying this same logic to the area source zonations for DE2016, for example, we have between 31 and 107 sources per model and 20 MFR branches, which would result in between 20^{31} to 20^{107} logic tree branches for each source model. This is clearly intractable for any PSHA calculation software and OpenQuake cannot even construct such a logic tree from which to sample. A common alternative is to assume perfect correlation between the sources, which in the idealized case would be to apply the same branches (e.g. $-(a, b)|M_{MAX}^{low}$, $(\overline{a, b})|M_{MAX}^{LOW}$, $+(a, b)|M_{MAX}^{LOW}$, $-(a, b)|\overline{M_{MAX}}$, ..., $+(a, b)|M_{MAX}^{HIGH}$) to all of the sources at the same time. This results in a more manageable logic tree of just 9 branches in the simple idealized case and 20 MFR branches per source model in the DE2016 case.

725

Both DE2016 and ESHM20 adopt discrete MFRs for each of the sources meaning that in order to execute the calculation perfect correlation between sources had to be assumed in both cases. By sampling the MFRs for each source separately in the 100 branches, however, FR2020 is preserving independence in the source model MFRs. This issue of correlation can impact on the outcomes of the hazard as the assumption of perfect source-to-source correlation in MFRs could conceivably assign disproportionately large weights to the extreme cases that all sources may have higher or lower activity rates. This inflates the uncertainty meaning that the resulting hazard distributions may be larger than intended and potentially skewing the mean toward higher values compared to the case in which MFR epistemic uncertainties are characterized independently for each source. Work is currently ongoing to explore this issue in further detail and its impacts on seismic risk assessment for a country.

735 3.4 Calculation Scale

A final issue of PSHA implementation relates to the scale of calculation, by which we refer to the volume of data and, by extension, the CPU time and RAM needed to execute the PSHA for logic trees of this size. Each of the three software address this differently, and as two of the software are proprietary we have not been able to benchmark the calculations. For OpenQuake, however, this type of logic tree with many source- and MFR-branches is not efficiently handled *at the time of*
740 *writing*. The main reason for this is that for each source model and MFR branch a new earthquake rupture forecast is constructed. This requires re-calculation of distances and ground motions for each logic tree branch MFR branch, increasing both the CPU and RAM requirements. Calculations here were run on a 192 CPU server with 760 Gb RAM, and this was insufficient to execute the calculations in a single run. Instead, the models for FR2020 and DE2016 were split into subsets of branches and the resulting hazard curves were later recombined and post-processed to retrieve the mean and quantiles. It is
745 hoped that future efforts will be undertaken to improve the efficiency of the calculations for this type of epistemic uncertainty, which is commonly applied in regions of low to moderate seismicity.

4. Quantitative Comparisons of the Seismogenic Source Models by Visualising Activity Rate Model Space

In section 2 we showed the overall structure of the different models, contrasting some of the assumptions behind them and looking in detail at the France-Germany border region to understand the differences in catalogues, definitions of source models,
750 and the fitting and characterization of the recurrence models. Though this process brings to light some of the main factors that will go toward explaining the differences in seismic hazard results shown in the next section, it is also important to be able to quantify and interpret differences in the two primary components of the PSHA model: the seismic source model and the ground motion model. Comparisons at this point can be particularly useful as they can allow us to understand the cumulative impact of the diverging steps that have led to the construction of the respective source and ground motion models before these are
755 then integrated into the PSHA calculation. A crucial motivation for the migration of the PSHA models into a common software, as described in detail in section 3, is to have the three models represented in a common format that allows us to isolate the model-to-model differences from the software differences. In this section all the analysis is working with the OpenQuake implementations of the models rather than the original implementations (in the case of FR2020 and DE2016).

4.1 Interpreting the Seismogenic Source Model Space using Descriptive Statistics

Section 2 explained how all three models share some similarities in the source types that they are using, but their differences
760 too. As each model is adopting a logic tree with epistemic uncertainty on both the source types and recurrences, how can one quantitatively compare not just the sources but their respective distributions? The starting point is to render each source into a common representation that allows for quantitative comparisons of the models and their respective distributions. Each source branch of each model is translated into a three dimensional array $\lambda(\phi, \theta, M)$ of latitude, longitude and magnitude, with each
765 cell containing the incremental rate of activity for each the corresponding longitude, latitude and magnitude bin λ_{ijm} , where $i = 1, 2, \dots, N_\phi$ corresponds to the longitude bin, $j = 1, 2, \dots, N_\theta$ to the latitude bin, and $m = 1, 2, \dots, N_m$ to the magnitude bin.

For area sources, the rate of the uniform area source is partitioned into each grid cell according to the proportion of total area overlapping with each cell. In the case of gridded seismicity, the rate assigned to each target grid cell corresponds to that of the original source cell's centroid falls (which can result in latitudinally-dependent striations of "empty" cells depending on the different map projections used). Finally, for the fault sources the seismicity rate per cell is partitioned according to the proportion of the fault's surface projection that intersects the cell. All seismogenic sources here are shallow crustal sources, so although hypocentral depth is relevant to the seismic hazard, for the current purposes rates are not distributed across different depth layers.

Each source model logic tree branch k of N_k total branches is rendered into the 3D rate grid $\lambda_k(\boldsymbol{\phi}, \boldsymbol{\theta}, \mathbf{M})$ and each grid is associated with its respective logic tree branch weight. This relatively simple translation of the respective source models into a common grid representation facilitates quantitative comparisons by virtue of simple descriptive statistics. For example, Figure 13 shows the spatial variation in mean cumulative rate of seismicity above M 4.5 for each of the three models, which is weighted by the logic tree branch weight for each source branch:

$$\overline{\lambda(\boldsymbol{\phi}, \boldsymbol{\theta} | M \geq 4.5)} = \sum_{k=1}^{N_k} w_k \cdot \sum_{m=1}^{N_M} \lambda_k(\boldsymbol{\phi}, \boldsymbol{\theta}, M_m) \cdot H[M_m \geq 4.5] \quad (5)$$

where $H[\cdot]$ is the Heaviside step function. Similarly, weighted percentiles can be extracted for each spatial bin, which we show in Figure 13 as the 16th and 84th percentiles. The minimum magnitude $m_{min} = M$ 4.5 is used in these comparisons as this is the common minimum magnitude in the PSHA calculations for all three models. Other values of m_{min} could be compared depending on the relevant context; however, $m_{min} = 4.5$ is sufficient to illustrate the application here. From these descriptive statistics we can extract a measure of the centre and body of the activity rate distributions, the latter being illustrated in terms of the weighted interquartile range in Figure 14. Note that the striations in the maps for the FR2020 model emerge from the gridded seismicity branches being regularly Cartesian spaced every 10 km, while the reference grid is in a geodetic system (longitude and latitude).

It is not our intention to provide a complete interpretation of all the features visible in these maps, though for the comparisons of hazard in the France-Germany border region noteworthy differences include the relative activity of Albstadt Shear Zone (SE Germany) and the Upper and Lower Rhine Graben. The Albstadt Shear Zone is a particularly complex feature where the smoothed seismicity driven branches of the DE2016 and ESHM20 produce very localized zone of high activity while several area zonations (particularly those based on regional tectonics) do not isolate this region from the larger-regional seismicity. So higher quantiles tend to reflect the smoothed seismicity branches in which the ASZ is highly visible and lower quantiles reflect the larger scale zonations where the ASZ is not present.




Figure 13: Grids of activity rate for $M \geq 4.5$ for FR2020 (top row), DE2016 (middle row) and ESHM20 (bottom row) in terms of mean rate (left column), 16th percentile (middle column) and 84th percentile (right column)

800




Figure 14: Interquartile ranges of activity rates from each source model logic tree: FR2020 (left), DE2016 (middle) and ESHM20 (right)

Relative differences between the models can be quantified from this same characterization via the use of difference maps, both for the mean activity rates (Figure 15, top) or for relative differences in the model range shown by the ratio of the interquartile ranges (Figure 15, bottom). The difference maps present a somewhat incoherent picture, which is not unexpected given the complexities and variations in the constituent source models. We note that in the presentation of the relative comparisons in Figure 15 (and in subsequent figures) we do not identify any specific model as a reference and instead show all combinations.




Figure 15: Relative increase (in %) between the mean activity rate grids for each model comparison (top row) and the increase in interquartile range (%) (bottom row): FR2020 / DE2016 (left), ESHM20 / DE2016 (middle) and ESHM20 / DR2020 (right)

4.2 A Non-Parametric Statistical Approach

Comparisons of the mean and quantiles of the rate distributions such as those shown in Figures 13 and 15 are certainly important as they highlight regions where the underlying source models have a general tendency toward increased or reduced activity. However, these metrics alone don't necessarily provide insight into the complete similarity or dissimilarity of the full distributions of activity rates diverse, or how this divergence varies geographically. To visualize that sort of information we can instead adopt metrics from information theory to help quantify dissimilarity between distributions: weighted Kolmogorov-Smirnov Statistic (D_{KS}) (e.g. Monohan, 2001) and Wasserstein Distance (D_{WS}) (Vaserstein, 1969). If $\lambda_k(\phi, \theta, m_{min})$ is the


rate grid for source branch k , with weight w_k then we can define for each complete source model logic tree a probability distribution $f_{MODEL}(\lambda_k|\phi, \theta, m_{min})$ at each location, where $\lambda_k|\phi, \theta, m_{min}$ is the total activity rate in the spatial domain (ϕ, θ) greater than or equal to a specified minimum magnitude m_{min} . In the simplest case the spatial domain refers to each grid cell; however, this same process applies to any spatial subdomain of the region enclosed by the original rate grid and could be applied to larger regions or somehow coarsened with respect to the grid. If $f_{MODEL_A}(\lambda_k|\phi, \theta, m_{min})$ and $g_{MODEL_B}(\lambda_k|\phi, \theta, m_{min})$ are the respective empirical probability density functions for the two full seismic source models A and B implied by their logic trees, then:

$$D_{KS} = \sup_{\lambda_k} |F_{MODEL_A}(\lambda_k|\phi, \theta, m_{min}) - G_{MODEL_B}(\lambda_k|\phi, \theta, m_{min})| \quad (6)$$

and

$$D_{WS} = \int_{-\infty}^{\infty} |F_{MODEL_A}(\lambda_k|\phi, \theta, m_{min}) - G_{MODEL_B}(\lambda_k|\phi, \theta, m_{min})| d\lambda_k \quad (7)$$

where F_{MODEL_A} and G_{MODEL_B} are the respective empirical cumulative density functions of models A and B . The conceptual definitions of these terms are illustrated in Figure 16, where we can see D_{KS} as maximum absolute distance between the empirical CDFs and D_{WS} as total area enclosed between the CDFs. D_{KS} is constrained to the domain $[0, 1]$, with 0 indicating perfect agreement in the CDFs and 1 indicating no overlap in the respective ranges of λ_k , while D_{WS} is constrained only by a lower bound of 0 (total agreement). By working on the cumulative density functions, both terms account for the distribution of weights in each of the logic trees.




840 **Figure 16. Definition of the Kolmogorov-Smirnov (KS) statistic (left) and Wasserstein Distance (right) with respect to empirical CDFs $F(x)$ and $G(x)$**

With D_{KS} and D_{WS} we have metrics that allow us to assess spatial variation in the similarity between the effective rate distributions predicted by two different models, which is shown for the combinations of FR2020/DE2016, ESHM20/DE2016

and ESHM20/FR2020 in Figure 17. The most immediate contrast between the maps using the two different metrics is the
845 apparent “noisiness” of the D_{KS} metric compared to that of D_{WS} . The Kolmogorov-Smirnov statistic can appear to change
significantly over short distances, often highlighting boundaries of source zones, while Wasserstein Distances show a smoother
transition, particularly in regions of higher seismicity. The sharp spatial contrasts and variability appear to be particularly
exacerbated for comparisons involving ESHM20. This behaviour may be anticipated by the conceptual definitions of the
metrics shown in Figure 16, in which the largest absolute distance between empirical CDFs can change significantly even with
850 relatively small changes in the shape of the CDF. In the empirical CDFs for F_{MODEL_A} and G_{MODEL_B} , notable changes in shape
may appear from one source zone to another due to changes in the MFRs for each of the zones, while in the case of ESHM20
the comparatively few MFR branches results in empirical CDFs that are more step-like, which results from having gaps in the
PDF that can arise due to coarse discretisation of the continuous distributions and/or transitions from one type of source or
recurrence model to another. In this respect, D_{WS} appears to be a better suited metric for interpretation as it is less sensitive to
855 small changes in the empirical CDFs than D_{KS} . Focusing on this metric, in the France-Germany border regions we can see
more coherent trends, such as greater divergence in the lower Rhine Graben than along the upper Rhine for all models, with
the ESHM20 providing a notably divergent distribution here. Similarly, the Albstadt Shear Zone emerges as a point of
divergence between FR2020 and the other two models.

860 The rendering of each model into regular rate grids allows us to make comparisons of the source models in a common
framework and to interpret differences using simple descriptive statistics as well as through more non-parametric measures
that are based on information theory. We contrast here the source models from the three different PSHA models (FR2020,
DE2016 and ESHM20), though similar comparisons could be undertaken for successive generations of models, albeit one does
not need to go back more than one or two generations of regional scale model before concepts such as the logic tree are no
865 longer found. From the comparisons of the source models shown here, a recommendation would be to compare models firstly
via difference maps of mean rates, and potentially a small number of selected quantiles, then to apply D_{WS} to be able to interpret
quantitatively how and where the distributions diverge.



870 **Figure 17: Seismicity rate distribution differences between the models given in terms of KS Distance, D_{KS} (top row), and Wasserstein Distance, D_{WS} (bottom row): FR2020 to DE2016 (left), ESHM20 to DE2016 (middle), and ESHM20 to FR2020 (right)**


5. Quantitative Comparisons of the Seismic Hazard Model Results

With the components of the seismic hazard models compared in the previous section the obvious endpoint to this analysis is to undertake a comparison of the distribution of the seismic hazard results. To make such comparisons we limit the area of investigation to the France-Germany border region, stretching from the border with Switzerland in the south to the Luxembourg border in the north. The focus is now limited to this region as it is only here that we have sufficient overlap between all three models to capture contributions from sources up to the stated integration distance of 200 km. Though the Lower Rhine Graben to the north is also of critical importance for understanding seismic hazard in Germany, this region is located at the very eastern extreme of the source models for France, thus the FR2020 sources do not provide complete coverage. Seismic hazard calculations have been run using the OpenQuake-engine implementations of each model for a target region enclosed by 5°E – 9.5°E and 47°N to 50.5°N, with target locations spaced every 0.05° ($\approx 3.5 - 3.7$ km spacing EW and ≈ 5.5 km spacing NW). Mean hazard and its respective quantiles are calculated using the arithmetic mean of the probabilities of exceedances, rather than the levels of ground motion. Hazard curves are determined for all models PGA and spectral accelerations at periods

875

880

between 0.05 s and 3.0 s. Seismic hazard maps and corresponding difference maps for the 10 % probability of exceedance in
 885 50 years are shown for three intensity measures (PGA, Sa (0.2 s) and Sa (1.0 s)) in Figure 18.




890 **Figure 18: (left) Probabilistic seismic hazard maps covering the France/Germany border region for PGA (top row), Sa (0.2 s) (middle row) and Sa (1.0 s) (bottom row) for 10 % PoE in 50 years. (right) Corresponding difference maps for the hazard comparing FR2020 / DE2016 (right column), ESHM20 / DE2016 (middle column) and ESHM20 / FR2020 (right column)**

As we had seen for the distributions of activity rate, comparisons of the resulting hazard maps for means and quantiles only reflect part of a larger picture. Instead, we can also frame the concept of similarity in hazard at a given probability of exceedance in terms of similarity or dissimilarity in the full distribution of hazard values emerging from the logic tree. Once again, we can
 895 invoke the two distances (D_{KL} and D_{WS}) as measures of dissimilarity for a given ground motion level, A, with a P % probability in T years. In addition, we consider a third metric developed by Sum Mak (*personal communication*), which we refer to as Overlap Index (*OI*). The *OI* is illustrated conceptually in Figure 19 for the distribution of ground motions from the FR2020 and DE2016. The distribution of hazard (here as PGA with a 10 % probability of exceedance in 50 years) is rendered into a

900 histogram, with the weights of each value corresponding to its branch weight from the logic tree. OI between the distributions of seismic hazard from two different PSHA models at a given probability of exceedances is calculated from:

$$OI = \int_x \min(f(x), g(x)) dx \quad (8)$$

where $f(x)$ and $g(x)$ correspond to the observed probabilities densities of ground motion values for the two models respectively. As with D_{KS} , OI is bounded in the region $[0, 1]$ but here 0 indicates no region of overlap between the models and 1 a perfect agreement.




905 **Figure 19: Illustration of the Overlap Index (OI) between the distribution of hazard at a site using the FR2020 and DE2016 models**


The spatial distribution of dissimilarity between the full hazard models (in terms of the 10 % probability of exceedance in 50 years) can be mapped using the three metrics (D_{KL} , D_{WS} and OI) shown in Figures 20 and 21 respectively. The different maps reveal several interesting features about the differences in the models in this region. Along the main channel of the Rhine as it forms the border between France and Germany from Basel to near Karlsruhe, both the D_{KS} and D_{WS} measured indicate less dissimilarity between the ESHM20 and DE2016 models, while for these same two models the OI finds less overlap along much of the entire Rhine Graben. Differences between the FR2020 and other models are clearly period-dependent in this same region, with the Upper Rhine Graben seemingly in good agreement with other models for PGA and Sa (1.0 s). Yet for Sa (0.2 s) this same region is clearly illuminated as an area of significant disagreement. Dissimilarity seems to be lower in the northwest of the target region close to the France-Luxembourg border, while it is in most cases at its greatest in northern Switzerland. The Albstadt shear zone in the south east is once again clearly highlighted, with the divergence between the FR2020 and other models clearly visible.

920 The hazard maps and the corresponding dissimilarity maps show how the distributions of seismic hazard for a given IMT and return period change with space, but these should also be complemented with more in-depth comparisons of the hazard curves and uniform hazard spectra at specific locations. In Figure 22 we show two such comparisons for the cities of Saarbrücken

(7.0°E, 49.23°N), in an area of lower hazard, and Strasbourg (7.76°E, 48.58°N), which sits in the region of higher hazard along the Upper Rhine Graben. Here the full seismic hazard curves including the mean, 16th and 84th percentile are shown for Sa (0.15 s) (a period close to the peak of the UHS), alongside corresponding UHS for a 10 % and 2 % probability of being exceeded in 50 years. Saarbrücken sits in a region that we infer from Figures 20 and 21 shares a similar seismic hazard distribution in the FR2020 and ESHM20 models but is notably lower in DE2016, while Strasbourg lies about halfway along the Upper Rhine Graben, a region where all three models seem to agree with one another. If we recall the comparison of the URG source zone in Section 2 (Figure 6) and the differences between the recurrence models for the three PSHA models found therein, the degree of agreement between the three models for Strasbourg is somewhat surprising. For both return periods the mean curves and UHS predicted by each model is falling within the 16th to 84th percentile of each of the others. Though this is illustrative of the considerable range of ground motion values described by the 16th to 84th percentile, it does suggest a degree of consistency between them that may not be understood if one were to consider solely the changes in mean hazard.



935 **Figure 20: Spatial variation in the dissimilarity between distributions of seismic hazard values for a 10 % PoE in 50 years for PGA (top row), Sa (0.2 s) (middle row) and Sa (1.0 s) (bottom row) using KS Distance (left column set) and Wasserstein Distance (right column set)**



940 **Figure 21: As Figure 20 considering the overlap index (OI)**

6. Discussion and Conclusion

The key aim of this study has been to set out a broader perspective on what we mean by *comparison* in the sense of PSHA models, and to illustrate different quantitative techniques to undertake this. Through the examples compared here (FR2020, DE2016 and ESHM20), we are considering seismic hazard models that are sufficiently complex for “simple” difference maps to be an insufficient metric of comparison. The degree of complexity observed in the models is indicative of the current state of practice, however, particularly for PSHA in low-to-moderate seismicity regions. Model comparison, therefore needs to account for this degree of complexity. In the current analysis we are considering three models developed by three separate

950 teams of modellers, each of which was working for different objectives, with different tools and with a different geographical scope. Under such circumstances it is inevitable that the perspectives on seismic hazard that emerge for a common region (in this case the France/Germany border region) will display a degree of divergence, even if there are many similar elements in each of the models. These can reflect different views as to which uncertainties should be captured by the logic tree and, depending on the tools available, how these uncertainties are evaluated. An important point often overlooked in model comparison is the extent to which the calculation software can influence the actual decisions made by the modeller. The execution of the epistemic uncertainty on the magnitude frequency relation in the three models is a clear example of the

955 complex relationship between tools and modelling decisions, and how these can lead to quite different outcomes.




Figure 22. Comparison of the distributions of seismic hazard for Saarbrücken (top row) and Strasbourg (bottom row) for hazard curves at Sa (0.15 s) (left) column) and UHS for 10 % PoE in 50 years (middle column) and 2 % PoE in 50 years (right column)

960

To understand why and how PSHA models for a region diverge, one needs to break down the key factors in the model development and implementation process, and analyse each systematically: input data, modelling approach and philosophy, modelling tools, seismic hazard model components (e.g., seismogenic source model and ground motion model) and, finally,

the seismic hazard model outcomes. The first two factors are compared more in a qualitative sense than a quantitative one.

965 This is reflected in the presentation of the three models in section 2 of this paper, which juxtaposes the approaches the three different models have taken to represent the seismogenic sources, to model the recurrence of earthquakes from each source and to capture the expected ground motions from each earthquake. Each of the three models is working from input data that share many common characteristics such as the earthquake catalogue, which for ESHM20 comprises data from both the FCAT-17 catalogue and the input seismic catalogue used by DE2016. Likewise, all three models had available geological data for

970 active faults in both the Upper and Lower Rhine Graben, and these have been either discarded, partly integrated or fully integrated depending on the model. In terms of the modelling approach and philosophy, however, it is interesting to note the many places in which the models have largely adopted a similar philosophy, yet the respective implementations yield substantially different outcomes. A key example of this is the use of large-scale area zones (LASZs) based on tectonics and smaller scale area zones based on local seismicity or geological features, both of which are balanced against a smoothed

975 seismicity model. The LASZs then form the prior zones, or direct measurements, for the MFRs of the small area source zones within the maximum likelihood estimation, the outcomes of which are distributions of a and b values and their covariances. Each model differs, however, in the specific zonations and in how the MFRs are, first, fit to the data and then how they are mapped into branches of a logic tree.

980 One of the main opportunities that emerged from this work was to have all three models implemented in a common format for use with the OpenQuake-engine seismic hazard and risk calculation software. This served several purposes, one of which being to understand to what extent the three models differ by virtue of the calculation engine used to run them. The migration process of a PSHA model from one software tool to another is seldom a trivial issue. Discrepancies emerge in computational implementation of the PSHA calculations from one software to the next, which we separate into the following categories: i)

985 irreconcilable differences in operation, ii) bugs/errors and/or differences of interpretation, and iii) configurable parameters. Migration of an implemented or existing model from one software to another is therefore a time-consuming process that focuses on the finest details of the PSHA calculation rather than the general strategy for source and ground motion modelling.

Model migration differs from dual implementation, a practice becoming more widely adopted for quality assurance for critical

990 facilities that executes models in multiple software side by side, identifying discrepancies that are then discussed and potentially resolved (e.g., Bommer et al., 2015; Aldama-Bustos et al., 2019). Migration assumes a reference seismic hazard output from the original software, which the target software aims to reproduce regardless of whether the calculation processes of the original software are deemed optimal. As perfect agreement in the calculations is rarely, if ever, achievable, we can only define agreement between the implementations of a model in its original software and that in the target software in terms of a

995 degree of mismatch over a APoE range of relevance for application. We adopted $\pm 10\%$ for $\text{APoE} \geq 10^{-4}$ (return period $\approx 10,000$ years) for this purpose, which applies firstly at a branch-by-branch level and then in terms of the mean and quantiles. For DE2016 the target agreement was achieved for the mean and upper quantiles of seismic hazard for the vast majority of

sites considered and across multiple spectral periods. In some cases, the OpenQuake implementation estimated lower quantiles that exceeded those of the original software beyond the specified target range. For FR2020 the target agreement could be achieved for all area source branches individually; however, for the smoothed seismicity branches the OpenQuake hazard curves appeared to be on average 20 – 30 % higher over the APoE range of interest. This resulted in OpenQuake’s estimation of the mean and quantiles to exceed those of the original software by between 10 – 20 % depending on the location and period, which does not meet the target agreement. At the time of writing, no specific cause for this disagreement has been identified, and we hope that this may still be resolved in subsequent iterations of the model.

1005

The process of model migration for FR2020 and DE2016 was greatly facilitated in this case by the authors of the original models, who supplied us with digital files of both the software inputs and the resulting seismic hazard curve outputs. Despite this, each migration took several iterations, with more information regarding the calculation details needed as each discrepancy is identified and, where possible, resolved. In both cases the specific details of the calculations were not found in the accompanying documentation to the model and required clarification from the authors. In several cases the points of clarification were not just related to small details of implementation but instead to major differences in how the models were being executed within the calculation, sometimes even contradicting the supporting literature for the model. Though we are sincerely grateful for the input of the model authors to aid this migration, this highlights a larger problem of model reproducibility and a lack of standardisation in PSHA model documentation. One recommendation for improving practice here would be to require that where PSHA models are intended for use in large scale applications (e.g., a seismic design code) the digital input and output files for the calculation are made available. In addition, a standard documentation template may be developed that requires the modellers to specify explicitly how the software they are using implements each component of the PSHA model, which parts of the process are configurable and what values are adopted. Such information could greatly reduce the effort in model migration and ensure greater transparency in the entire PSHA model implementation.

1020

With the FR2020 and DE2016 models migrated to OpenQuake with a satisfactory level of agreement, we had a consistent framework within which we can make quantitative comparisons of the hazard models, both in terms of the fundamental components of the model inputs (i.e., the source and ground motion model) and the resulting hazard outputs. The latter describe the extent to which models differ while the former provide insights as to why they do. The key issue we have sought to address in the comparisons is the growing complexity of the logic trees that means we must now describe both the hazard model inputs and outputs in terms of probability distributions and model space. This is the fundamental difference between the current generation of PSHA models in Europe and many of their precedents. The logic trees of each of the three models considered here incorporate not only alternative source models but multiple branches for epistemic uncertainty in the magnitude frequency relation. This results in a much larger number of alternative predictions of activity rate and magnitude recurrence (400 for FR2020 and 200 for DE2016), which begin to better resemble probability distributions (albeit of no specific functional form) rather than individual alternative models. We have illustrated here how we can compare models in this context quantitatively,

1030

first by looking at metrics describing the centre and variance of the distributions, then by invoking more information theoretic metrics that quantify proximity of different probability distributions in model space, such as Kolmogorov-Smirnov Distance (D_{KS}) and Wasserstein Distance (D_{WS}). Combining these different metrics and exploring their spatial trends can help provide insight as to where the models are most divergent, which can help identify future efforts could be placed to improve consistency across models in future generations of seismic hazard models for Europe.

This last point takes us toward a critical question that we believe emerges from the work and affect how we may use the models in practice. *What can we do to effectively harmonise multiple seismic hazard models that cover a region?* This question is not necessarily a scientific one but rather a procedural one. Multiple groups developing separate models for a region and making individual modelling decisions will inevitably result in different estimates of seismic hazard. This is widely recognised and procedures such as those adopted by SSHAC (Ake et al., 2018) are intended specifically to formalise the management of information and scientific review in order to define the set of technically defensible interpretations and ensure that their centre, body and range are adequately represented. Seismic hazard modelling in Europe (illustrated here for the FR2020, DE2016 and ESHM20) does not currently take place within such a framework, as each model has been commissioned for different purposes and by different organisations with no designation of a body to oversee coordination. ESHM20 aimed to integrate components of both the FR2020 and DE2016 models, yet practical limitations, the desire to incorporate new data and developments in PSHA, and the need to create a harmonised model at a larger scale, prevented it from faithfully incorporating all elements of the existing models into its framework. Divergence is therefore ensured from the very beginning of this process. Efforts such as the European Facility for Earthquake Hazard and Risk (EFEHR) are seeking to provide a community structure to hazard and risk modelling around which data and tools are made openly available, and its working groups aim to focus on broadening the discussion of key issues and challenges for modelling. EFEHR cannot necessarily act in the role of technical integrator to the various organisations with remits to model hazard and risk in their respective countries, but it can and does provide harmonised datasets and tools for use as well open-source implementations of hazard and risk, all combined with extensive documentation. These can facilitate harmonisation from the bottom up, eventually moving differences in modelling decisions, alternative interpretations and parameter uncertainties into a broad distribution of technically defensible interpretations across a region. We hope that if the EFEHR community is successful and can continue to expand, divergence between the models may eventually be minimised to better reflect the actual epistemic uncertainty in a region.

1060 **Supplementary Material**

Additional information relating to the France (Drouet et al., 2020) and Germany (Grünthal et al., 2018) PSHA models and their implementation into OpenQuake is available with the online version. These include images and information about the model translation (Appendix A) and comparisons of the seismic hazard results for the respective countries and selected cities (Appendix B).

1065

Author Contribution

Author contributions are defined according to the [CRediT Taxonomy](#). **Conceptualization:** GW, FC, GD, IZ. **Methodology and Investigation:** GW, PI, CB. **Writing (original draft):** GW. **Data Curation and Software:** GW, CB, PI, **Writing – Review and Editing:** GW, FC, GD, IZ, PI, CB. **Funding Acquisition:** FC, GD, IZ

Declaration of Competing Interests

The authors declare no conflicts of interest.

Acknowledgements

The work presented here has benefitted from discussion with, and data provided by, Emmanuel Viallet, Stephane Drouet, David Baumont and Gabriele Ameri (FR2020), Gottfried Grünthal and Dietrich Stromeier (DE2020), and Laurentiu Danciu (ESHM20) and members of the European Facility for Earthquake Hazard and Risk (EFEHR). We thank Sum Mak (formerly of GFZ) for his proposal and explanation of the Overlap Index. The manuscript has benefitted from reviews from Peter Powers, Ilaria Mosca and two anonymous reviewers, whose comments have helped improve its clarity and quality. Seismic hazard calculations have been undertaken using the OpenQuake-engine, for which we thank the GEM Foundation for their ongoing development and support. Other quantitative analysis used tools from the Python Scientific Stack (including Numpy, Scipy, Pandas, Matplotlib, H5Py and Geopandas), and some maps have been prepared using QGIS. This work has been supported by the SIGMA2 research program and partially funded by Électricité de France.

References

- Abbott, E., Horspool, N., Gerstenberger, M., Huso, R., Van Houtte, C., McVerry, G., and Canessa, S.: Challenges and opportunities in New Zealand seismic hazard and risk modeling using OpenQuake, *Earthquake Spectra*, 36, 210–225, <https://doi.org/10.1177/8755293020966338>, 2020.
- Abrahamson, N. A., Silva, W. J., and Kamai, R.: Summary of the ASK14 Ground Motion Relation for Active Crustal Regions, *Earthquake Spectra*, 30, 1025–1055, <https://doi.org/10.1193/070913EQS198M>, 2014.
- Ake, J., Munson, C., Stamatakos, J., Juckett, M., Coppersmith, K., Bommer, J.: Updated Implementation Guidelines for SSHAC Hazard Studies. Report No. NUREG-2213. U. S. Nuclear Regulatory Commission, Washington D. C., 145pp., 2018.

- Akkar, S., Sandikkaya, M. A., and Bommer, J. J.: Empirical ground-motion models for point- and extended-source crustal earthquake scenarios in Europe and the Middle East, *Bull Earthquake Eng*, 12, 359–387, <https://doi.org/10.1007/s10518-013-9461-4>, 2014a.
- 1095 Akkar, S., Sandikkaya, M. A., Senyurt, M., Azari Sisi, A., Ay, B. Ö., Traversa, P., Douglas, J., Cotton, F., Luzi, L., Hernandez, B., Godey, S.: Reference database for seismic ground-motion in Europe (RESORCE), *Bull Earthquake Eng*, 12, 311 – 339, 2014b.
- Akkar, S., Azak, T., Çan, T., Çeken, U., Demircioğlu Tümsa, M. B., Duman, T. Y., Erdik, M., Ergintav, S., Kadirioğlu, F. T., Kalafat, D., Kale, Ö., Kartal, R. F., Kekovalı, K., Kılıç, T., Özalp, S., Altuncu Poyraz, S., Şeşetyan, K., Tekin, S., Yakut, A.,
- 1100 Yılmaz, M. T., Yücemem, M. S., and Zülfikar, Ö.: Evolution of seismic hazard maps in Turkey, *Bull Earthquake Eng*, 16, 3197–3228, <https://doi.org/10.1007/s10518-018-0349-1>, 2018.
- Aldama-Bustos, G., Tromans, I. J., Strasser, F., Garrard, G., Green, G., Rivers, L., Douglas, J., Musson, R. M. W., Hunt, S., Lessi-Cheimariou, A., Daví, M., and Robertson, C.: A streamlined approach for the seismic hazard assessment of a new nuclear power plant in the UK, *Bull Earthquake Eng*, 17, 37–54, <https://doi.org/10.1007/s10518-018-0442-5>, 2019.
- 1105 Allen, T. I., Halchuk, S., Adams, J., and Weatherill, G. A.: Forensic PSHA: Benchmarking Canada’s Fifth Generation seismic hazard model using the OpenQuake-engine, *Earthquake Spectra*, 36(1_suppl), 91 – 111, <https://doi.org/10.1177/8755293019900779>, 2020
- Ameri, G.: Empirical Ground Motion Model Adapted to the French Context, Seismic Ground Motion Assessment (SIGMA) Deliverable No. SIGMA-2014-D2-131, 2014.
- 1110 Ameri, G., Drouet, S., Traversa, P., Bindi, D., and Cotton, F.: Toward an empirical ground motion prediction equation for France: accounting for regional differences in the source stress parameter, *Bull Earthquake Eng*, 15, 4681–4717, <https://doi.org/10.1007/s10518-017-0171-1>, 2017.
- Assatourians, K., Atkinson, G. M.: EqHaz: An Open-Source Probabilistic Seismic Hazard Code Based on the Monte Carlo Simulation Approach, *Seismological Research Letters*, 84(3), 516 – 524, 2014
- 1115 Basili, R., Danciu, L., Beauval, C., Sesetyan, K., Vilanova, S. P., Adamia, S., Arroucau, P., Atanackov, J., Baize, S., Canora, C., Caputo, R., Carafa, M. M. C., Cushing, E. M., Custódio, S., Demircioglu Tumsa, M. B., Duarte, J. C., Ganas, A., García-Mayordomo, J., Gómez de la Peña, L., Gràcia, E., Jamšek Rupnik, P., Jomard, H., Kastelic, V., Maesano, F. E., Martín-Banda, R., Martínez-Loriente, S., Neres, M., Perea, H., Šket Motnikar, B., Tiberti, M. M., Tsereteli, N., Tsironi, V., Vallone, R., Vanneste, K., Zupančič, P., and Giardini, D.: The European Fault-Source Model 2020 (EFSM20): geologic input data for the
- 1120 European Seismic Hazard Model 2020, *Nat. Hazards Earth Syst. Sci. Discuss.* [preprint], <https://doi.org/10.5194/nhess-2023-118>, in press, 2024.
- Bindi, D., Massa, M., Luzi, L., Ameri, G., Pacor, F., Puglia, R., and Augliera, P.: Pan-European ground-motion prediction equations for the average horizontal component of PGA, PGV, and 5 %-damped PSA at spectral periods up to 3.0 s using the RESORCE dataset, *Bull Earthquake Eng*, 12, 391–430, <https://doi.org/10.1007/s10518-013-9525-5>, 2014.

- 1125 Bindi, D., Cotton, F., Kotha, S. R., Bosse, C., Stromeyer, D., and Grünthal, G.: Application-driven ground motion prediction equation for seismic hazard assessments in non-cratonic moderate-seismicity areas, *J Seismol*, 21, 1201–1218, <https://doi.org/10.1007/s10950-017-9661-5>, 2017.
- Bommer, J. J. and Akkar, S.: Consistent Source-to-Site Distance Metrics in Ground-Motion Prediction Equations and Seismic Source Models for PSHA, *Earthquake Spectra*, 28, 1–15, <https://doi.org/10.1193/1.3672994>, 2012.
- 1130 Bommer, J. J. and Montaldo Falero, V.: Virtual Fault Ruptures in Area-Source Zones for PSHA: Are They Always Needed?, *Seismological Research Letters*, 91, 2310–2319, <https://doi.org/10.1785/0220190345>, 2020.
- Bommer, J. J., Coppersmith, K. J., Coppersmith, R. T., Hanson, K. L., Mangongolo, A., Neveling, J., Rathje, E. M., Rodriguez-Marek, A., Scherbaum, F., Shelembe, R., Stafford, P. J., and Strasser, F. O.: A SSHAC Level 3 Probabilistic Seismic Hazard Analysis for a New-Build Nuclear Site in South Africa, *Earthquake Spectra*, 31, 661–698, <https://doi.org/10.1193/060913EQS145M>, 2015.
- 1135 Burkhard, M. and Grünthal, G.: Seismic source zone characterization for the seismic hazard assessment project PEGASOS by the Expert Group 2 (EG 1b), *Swiss Journal of Geosciences*, 102(1), 149 – 188, 2009
- Cauzzi, C., Faccioli, E., Vanini, M., and Bianchini, A.: Updated predictive equations for broadband (0.01–10 s) horizontal response spectra and peak ground motions, based on a global dataset of digital acceleration records, *Bull Earthquake Eng*, 13, 1587–1612, <https://doi.org/10.1007/s10518-014-9685-y>, 2015.
- 1140 CEN: Eurocode 8: Design of structures for earthquake resistance – Part 1: General rules, seismic actions and rules for buildings. European Committee for Standardization (Comité Européen de Normalisation). 2004
- Crowley, H., Dabbeek, J., Despotaki, V., Rodrigues, D., Martins, L., Silva, V., Romão, X., Pereira, N., Weatherill, G., and Danciu, L.: European Seismic Risk Model (ESRM20), EFER Technical Report 002 V1.0.1, 2021
- 1145 Cornell, C. A.: Engineering seismic risk analysis, *Bulletin of the Seismological Society of America*, 58, 1583 – 1606, 1968
- Derras, B., Bard, P. Y., and Cotton, F.: Towards fully data driven ground-motion prediction models for Europe, *Bull Earthquake Eng*, 12, 495–516, <https://doi.org/10.1007/s10518-013-9481-0>, 2014.
- Danciu, L., Nandan, S., Reyes, C., Basili, R., Weatherill, G., Beauval, C., Rovida, A., Vilanova, S., Sesetyan, K., Bard, P-Y., Cotton, F., Wiemer, S., Giardini, D.: The 2020 update of the European Seismic Hazard Model: Model Overview.
- 1150 EFER Technical Report 001, v1.0.0, <https://doi.org/10.12686/a15>, 2021
- Drouet, S. and Cotton, F.: Regional Stochastic GMPEs in Low-Seismicity Areas: Scaling and Aleatory Variability Analysis—Application to the French Alps, *Bulletin of the Seismological Society of America*, 105, 1883–1902, <https://doi.org/10.1785/0120140240>, 2015.
- Drouet, S., Ameri, G., Le Dortz, K., Secanell, R., and Senfaute, G.: A probabilistic seismic hazard map for the metropolitan France, *Bull Earthquake Eng*, 18, 1865–1898, <https://doi.org/10.1007/s10518-020-00790-7>, 2020.
- 1155 Ebel, J. E. and Kafka, A. L.: A Monte Carlo Approach to Seismic Hazard Analysis, *Bulletin of the Seismological Society of America*, 89, 854–866, 1999.

- E DIN EN 1998-1/NA:2018-10: Nationaler Anhang – national festgelegte Parameter – Teil 1/NA: Eurocode 8: Auslegung von Bauwerken gegen Erdbeben – Grundlagen, Erdbebenwirkungen und Regeln für Hochbau. Berlin: Beuth-Verlag. Ausgabe Okt. 2018, 2018
- 1160 EPRI: Central and Eastern United States Seismic Source Characterization for Nuclear Facilities, U.S. DOE and U.S. NRC Technical Report, Palo Alto, CA, 2012. <https://www.nrc.gov/reading-rm/doc-collections/nuregs/staff/sr2115/v1/index.html>
- Field, E. H., Jordan, T. H., and Cornell, C. A.: OpenSHA: A Developing Community-modeling Environment for Seismic Hazard Analysis, *Seismological Research Letters*, 74, 406–419, 2003.
- 1165 Field, E. H., Biasi, G. P., Bird, P., Dawson, T. E., Felzer, K. R., Jackson, D. D., Johnson, K. M., Jordan, T. H., Madden, C., Michael, A. J., Milner, K. R., Page, M. T., Parsons, T., Powers, P. M., Shaw, B. E., Thatcher, W. R., Weldon, R. J., and Zeng, Y.: Long-term time-dependent probabilities for the third uniform California earthquake rupture forecast (UCERF3), *Bulletin of the Seismological Society of America* 105(2a), 511–543, <https://doi.org/10.1785/0120140093>, 2015.
- Field, E. H., Milner, K. R., Hatem, A. E., Powers, P. M., Pollitz, F. F., Llenos, A. L., Zeng, Y., Johnson, K. M., Shaw, B. E., 1170 McPhillips, D., Thompson Jobe, J., Shumway, A. M., Michael, A. J., Shen, Z.-K., Evans, E. L., Hearn, E. H., Mueller, C. S., Frankel, A. D., Petersen, M. D., DuRoss, C., Briggs, R. W., Page, M. T., Rubinstein, J. L., Herrick, J. A.: The USGS 2023 Conterminous U.S. Time-Independent Earthquake Rupture Forecast, *Bulletin of the Seismological Society of America*, 114 (1), 523–571, <https://doi.org/10.1785/0120230120>, 2024
- Gerstenberger, M. C., Marzocchi, W., Allen, T., Pagani, M., Adams, J., Danciu, L., et al.: Probabilistic seismic hazard analysis 1175 at regional and national scales: State of the art and future challenges, *Reviews of Geophysics*, 58, e2019RG000653. <https://doi.org/10.1029/2019RG000653>, 2020
- GEOTER: Probabilistic seismic hazard maps for the French metropolitan territory, Fugro, 2017.
- Giardini, D., Wiemer, S., Fäh, D., Deichmann, N.: Seismic Hazard Assessment of Switzerland, 2004, Technical Report, Swiss Seismological Service, 1 – 95, 2004
- 1180 Grünthal, G.: The updated earthquake catalogue for the German Democratic Republic and adjacent areas – statistical data characteristics and conclusions for hazard assessment, 3rd International Symposium on the Analysis of Seismicity and Seismic Risk, Liblice/Czechoslovakia, 17 – 22 June 1985 (Proceedings Vol. 1, 19 – 25), 1985
- Grünthal, G., Wahlström, R.: The European-Mediterranean Earthquake Catalogue (EMEC) for the last millennium, *Journal of Seismology*, 16, 535 – 570, <https://doi.org/10.1007/s10950-012-9302-y>, 2012
- 1185 Grünthal, G., Stromeyer, D., Bosse, C., Cotton, F., and Bindi, D.: The probabilistic seismic hazard assessment of Germany—version 2016, considering the range of epistemic uncertainties and aleatory variability, *Bull Earthquake Eng*, 16, 4339–4395, <https://doi.org/10.1007/s10518-018-0315-y>, 2018.
- Gutenberg, B. and Richter, C. F.: Frequency of Earthquakes in California, *Bulletin of the Seismological Society of America*, 34, 185 – 188, 1944
- 1190 Hakimhashemi, A. H. and Grünthal, G.: A Statistical Method for Estimating Catalog Completeness Applicable to Long-Term Nonstationary Seismicity Data, *Bulletin of the Seismological Society of America*, 102, 2530–2546, 2012.

- Hale, C., Abrahamson, N., and Bozorgnia, Y.: Probabilistic Seismic Hazard Analysis Code Verification, Pacific Earthquake Engineering Research Center, 2018.
- Helmstetter, A. and Werner, M. J.: Adaptive Spatiotemporal Smoothing of Seismicity for Long-Term Earthquake Forecasts in California, *Bulletin of the Seismological Society of America*, 102, 2518–2529, <https://doi.org/10.1785/0120120062>, 2012.
- 1195 Johnston, A. C., Coppersmith, K. J., Kanter, L. R., and Cornell, C. A.: The Earthquakes of Stable Continental Regions, Electric Power Research Institute, 1994.
- Instituto Geográfico Nacional (IGN): Actualización de mapas de peligrosidad sísmica de España, Centro Nacional de Información Geográfica, Technical Report, 1 – 272, DOI: 10.7419/162.05.2017, 2017
- 1200 Jomard, H., Cushing E. M., Palumbo, L., Baize, S., David, C., and Chartier, T.: Transposing an active fault database into a seismic hazard model for nuclear facilities – Part 1: Building a database of potentially active faults (B DFA) for metropolitan France, *Natural Hazards and Earth System Sciences*, 17, 1573 – 1584, <https://doi.org/10.5194/nhess-17-1573-2017>, 2017
- Kagan, Y. Y.: Seismic moment distribution revisited: 1. Statistical results, *Geophysical Journal International*, 148, 521–542, 2002.
- 1205 Kotha, S. R., Weatherill, G., Bindi, D., and Cotton, F.: A regionally-adaptable ground-motion model for shallow crustal earthquakes in Europe, *Bull Earthquake Eng*, 18, 4091–4125, <https://doi.org/10.1007/s10518-020-00869-1>, 2020.
- Lanzano, G., Sgobba, S., Luzi, L., Puglia, R., Pacor, F., Felicetta, C., D’Amico, M., Cotton, F., and Bindi, D.: The pan-European Engineering Strong Motion (ESM) flatfile: compilation criteria and data statistics, *Bull Earthquake Eng*, 17, 561–582, <https://doi.org/10.1007/s10518-018-0480-z>, 2019.
- 1210 Manchuel, K., Traversa, P., Baumont, D., Cara, M., Nayman, E., and Durouchoux, C.: The French seismic CATalogue (FCAT-17), *Bull Earthquake Eng*, 16, 2227–2251, <https://doi.org/10.1007/s10518-017-0236-1>, 2018.
- McGuire, R.: FORTRAN computer program for seismic risk analysis, USGS Open-File Report 76-67, 1976
- Meletti, C., D’Amico, V., and Martinelli, F.: Homogenous determination of maximum magnitude. Seismic Hazard Harmonisation in Europe (SHARE) Deliverable 3.3, 1 – 23, 2013
- 1215 Meletti, C., Marzocchi, W., D’Amico, V., Lanzano, G., Luzi, L., Martinelli, F., Pace, B., Rovida, A., Taroni, M., Visini, F., and Group, M. W.: The new Italian seismic hazard model (MPS19), *Annals of Geophysics*, 64, 6, <https://doi.org/10.4401/ag-8579>, 2021.
- Miller, A. C. and Rice, T. R.: Discrete Approximations of Probability Distributions, *Management Science*, 29, 352–362, 1983.
- Monahan, J. F.: Numerical Methods of Statistics. Cambridge Series in Statistical and Probabilistic Mathematics. Cambridge University Press. ISBN 0-52179168-5, 2001
- 1220 Monelli, D., Pagani, M., Weatherill, G., Danciu, L., and Garcia, J.: Modeling Distributed Seismicity for Probabilistic Seismic-Hazard Analysis: Implementation and Insights with the OpenQuake Engine, *Bulletin of the Seismological Society of America*, 104, 1636–1649, <https://doi.org/10.1785/0120130309>, 2014.
- Mosca, I., Sargeant, S., Baptie, B., Musson, R. M. W., and Pharaoh, T. C.: The 2020 national seismic hazard model for the United Kingdom, *Bull Earthquake Eng*, 20, 633–675, <https://doi.org/10.1007/s10518-021-01281-z>, 2022.
- 1225

- Musson, R. M. W.: The use of Monte Carlo simulations for seismic hazard assessment in the UK, *Annali di Geofisica*, 43, 1–9, 2000.
- Nandan, S., Danciu, L., Wiemer, S., and Giardini, D.: Background smoothed seismicity model underlying ESHM20, In *Proceedings of the 3rd European Conference on Earthquake Engineering and Seismology*, Bucharest, Romania, 2022
- 1230 Pagani, M., Monelli, D., Weatherill, G., Danciu, L., Crowley, H., Silva, V., Henshaw, P., Butler, L., Nastasi, M., Panzeri, L., Simionato, M., and Viganò, D.: OpenQuake Engine: An Open Hazard (and Risk) Software for the Global Earthquake Model, *Seismological Research Letters*, 85, 692–702, <https://doi.org/10.1785/0220130087>, 2014a.
- Pagani, M., Garcia-Pelaez, J., Gee, R., Johnson, K., Poggi, V., Silva, V., Simionato, M., Styron, R., Viganò, D., Danciu, L., Monelli, D., and Weatherill, G.: The 2018 version of the Global Earthquake Model: Hazard component, *Earthquake Spectra*, 1235 36, 226–251, <https://doi.org/10.1177/8755293020931866>, 2020.
- Pecker, A., Faccioli, E., Gurpinar, A., Martin, C., and Renault, P.: *An Overview of the SIGMA Research Project*, Springer, 2017.
- Rollins, C., Gerstenberger, M. C., Rhoades, D. A., Rastin, S. J., Christophersen, A., Thingbaijam, K. K. S., Van Dissen, R. J., Graham, K., DiCaprio, C., Fraser, J.; The Magnitude–Frequency Distributions of Earthquakes in Aotearoa New Zealand and on Adjoining Subduction Zones, Using a New Integrated Earthquake Catalog, *Bulletin of the Seismological Society of America*, 114 (1), 150–181, <https://doi.org/10.1785/0120230177>, 2024.
- 1240 Rovida, A., Antonucci, A., and Locati, M.: The European Pre-instrumental Earthquake Catalogue EPICA, the 1000 - 1899 catalogue for the European Seismic Hazard Model 2020, *Earth System Science Data*, submitted, 2022.
- Scherbaum, F., Schmedes, J., and Cotton, F.: On the Conversion of Source-to-Site Distance Measures for Extended Earthquake Source Models, *Bulletin of the Seismological Society of America*, 94, 1053–1069, <https://doi.org/10.1785/0120030055>, 2004.
- 1245 Scherbaum, F., Kuehn, N. M., Ohrnberger, M., and Koehler, A.: Exploring the Proximity of Ground-Motion Models Using High-Dimensional Visualization Techniques, *Earthquake Spectra*, 26, 1117–1138, <https://doi.org/10.1193/1.3478697>, 2010.
- Stromeier, D. and Grünthal, G.: Capturing the Uncertainty of Seismic Activity Rates in Probabilistic Seismic-Hazard Assessments, *Bulletin of the Seismological Society of America*, 105, 580–589, <https://doi.org/10.1785/0120140185>, 2015.
- 1250 Thomas, P., Wong, I., and Abrahamson, N.: *Verification of Probabilistic Seismic Hazard Analysis Computer Programs*, Pacific Earthquake Engineering Research Center, 2010.
- Stucchi, M., Meletti, C., Montaldo, V., Crowley, H., Calvi, G. M., Boschi, E.: Seismic Hazard Assessment (2003 – 2009) for the Italian Building Code. *Bulletin of the Seismological Society of America*, 101(4), 1885 – 1911, <https://doi.org/10.1785/0120100130>, 2011
- 1255 Tromans, I. J., Aldama-Bustos, G., Douglas, J., Lessi-Cheimariou, A., Hunt, S., Daví, M., Musson, R. M. W., Garrard, G., Strasser, F. O., and Robertson, C.: Probabilistic seismic hazard assessment for a new-build nuclear power plant site in the UK, *Bull Earthquake Eng*, 17, 1–36, <https://doi.org/10.1007/s10518-018-0441-6>, 2019.
- U. S. Nuclear Regulatory Commission: *Practical Implementation Guidelines for SSHAC Level 3 and 4 Hazard Studies*. NUREG-2117, U. S. Nuclear Regulatory Commission Report, Washington, D. C. 2012

- 1260 Vanneste, K., Camelbeeck, T., and Verbeeck, K.: A Model of Composite Seismic Sources for the Lower Rhine Graben, Northwest Europe, *Bulletin of the Seismological Society of America*, 103, 984–1007, <https://doi.org/10.1785/0120120037>, 2013.
- Vaserstein, L. N.: Markov processes over denumerable products of spaces, describing large systems of automats. *Problemy Peredaci Informacii*. 5(3), 64 – 72, 1969
- 1265 Weatherill, G. and Burton, P. W.: An alternative approach to probabilistic seismic hazard analysis in the Aegean region using Monte Carlo simulation, *Tectonophysics*, 492, 253–278, <https://doi.org/10.1016/j.tecto.2010.06.022>, 2010.
- Weatherill, G., Kotha, S. R., and Cotton, F.: A regionally-adaptable “scaled backbone” ground motion logic tree for shallow seismicity in Europe: application to the 2020 European seismic hazard model, *Bull Earthquake Eng*, 18, 5087–5117, <https://doi.org/10.1007/s10518-020-00899-9>, 2020.
- 1270 Weatherill, G., Cotton, F., Daniel, G., and Zentner, I.: Implementation of the Drouet et al. (2020) PSHA for France in OpenQuake: Comparisons and Modelling Issues, EDF, <https://www.sigma-2.net/pages/deliverables/deliverables.html>, 2022.
- Weichert, D. H.: Estimation of the Earthquake Recurrence Parameters for Unequal Observation Periods for Different Magnitude, *Bulletin of the Seismological Society of America*, 70, 1337–1346, 1980.
- Wiemer, S., Danciu, L., Edwards, B., Marti, M., Fäh, D., Hiemer, S., Wössner, J., Cauzzi, C., Kästli, P., and Kremer, K.:
- 1275 *Seismic Hazard Model (2015) for Switzerlan (SUIhaz2015)*, Swiss Seismological Service, ETH Zurich, 2016.
- Woessner, J., Laurentiu, D., Giardini, D., Crowley, H., Cotton, F., Grünthal, G., Valensise, G., Arvidsson, R., Basili, R., Demircioglu, M. B., Hiemer, S., Meletti, C., Musson, R. W., Rovida, A. N., Sesetyan, K., Stucchi, M., and The SHARE Consortium,: The 2013 European Seismic Hazard Model: key components and results, *Bull Earthquake Eng*, 13, 3553–3596, <https://doi.org/10.1007/s10518-015-9795-1>, 2015.
- 1280 Woo, G.: Kernel Estimation Methods for Seismic Hazard Area Source Modelling, *Bulletin of the Seismological Society of America*, 86, 353–362, 1996.